SPECIFICATION NOTES

- (1) 4" FPT inlet/outlet with 4" plain end fittings
- (2) Unit weight: 69 lbs. For wet weight, add 335 lbs.
- (3) Maximum operating temperature: 150° F continuous
- (4) Liquid Capacity: 40 gal
 - Grease Capacity (50 GPM): 268.1 lbs (36.7 gal)
 - Solids Capacity: 1.9 gal
- (5) This unit does not require flow control for 50 GPM applications
- (6) For gravity drainage applications only
- (7) Do not use for pressure applications
- (8) Cover placement allows full access to tank for proper maintenance
- (9) Vent not required unless per local code
- (10) Engineered inlet and outlet diffusers with inspection ports are removable to inspect / clean piping
- (11) Integral air relief / anti-siphon / sampling access
- (12) Designed for indoor, on-floor, below-grade or low-profile under sink installations

CERTIFIED PERFORMANCE


Great Basin® hydromechanical grease interceptors are third party performance-tested and listed by IAPMO to ASME A112.14.3 and CSA B481.1 grease interceptor standards and greatly exceed requirements for grease separation and storage. They are compliant to the Uniform Plumbing Code and the International Plumbing Code.


ENGINEER SPECIFICATION GUIDE

Schier Great Basin® grease interceptor model GB3 shall be lifetime guaranteed and made in USA of seamless, molded polyethylene with minimum 5/16" uniform wall thickness. Inlet diffuser cap shall be PVC. Interceptor shall be furnished for above or below-grade installation. This unit is certified for hydromechanical performance to ASME A112.14.3 (Type D) and CSA B481.1, with field cut riser system and three outlet options. Interceptor flow rate shall be 50 GPM. Interceptor grease capacity shall be 268.1 lbs (36.7 gal) @ 50 GPM. Cover shall provide water/gas-tight seal and have a minimum of 450 lbs load capacity.

Static Water Line

SECTION A-A





INVERT

INLET END VIEW