

Industrial Splice Housing (ISH)

Accepts up to (12) category 2S splice trays

CORNING

Corning Cable Systems Industrial Splice Housing (ISH) is ideal for manufacturing and industrial applications.

The housing is finished with a baked on silver-gray powder-coat finish and may be used indoors or outdoors. Wall-mountable for transition splicing between cable at building entrance or pigtail splicing, the ISH provides storage and protection of fiber splices in individually accessible trays. The units have a padlockable outer door.

The ISH is designed to accommodate conduit fittings with the provided plugs and reduction washer, and it accepts standard LANscape® Solutions splice trays. The industrial splice housing is also compatible with Corning Cable Systems Industrial Connector Housings ICH-02P-IND, ICH-06P-IND and ICH-12P-IND.

Features and Benefits

NEMA 250-1997 3S and IP64, 65, 66, 67 and 69k tested
Reliability in harsh environments

Accepts standard LANscape® Solutions splice trays
Ease of installation

Keyhole mounting holes
Fast installation

Padlockable with user-supplied padlock
Secure access

Standards

Design and Test Criteria NEMA 250-1997 3S and IP64, 65, 66, 67 and 69k tested



Part Number: ISH-12SPT



Part Number: ISH-12SPT

Industrial Splice Housing (ISH)

Accepts up to (12) category 2S splice trays

CORNING

Specifications

General Specifications	
Application	Enterprise Networks
Mounting Type	Wall-Mountable
Product Type	Wall-Mountable Hardware

Design - Hardware	
Housing Type	ISH
Splice Tray Options	Up to (12) category 2S splice trays

Mechanical Characteristics	
Dimensions (HxWxD)	40.1 cm x 50.8 cm x 15.2 cm (16 in x 20 in x 6 in)

Ordering Information	
Order Number	ISH-12SPT
Product Description	Industrial Splice Housing (ISH), accepts up to (12) Type 2S splice trays

Shipping Information	
Units per Delivery	1/1
Shipping Weight	9.1 kg (20 lb)
Package Contents	Housing with installation guide; unit ID label; UCC strain-relief kit; UCC strain-relief bracket; central strength member strain-relief kit; 2 #6-32 SS self-locking nuts; (18) 1/8 x 4-in tie wraps; 3-in gasket washer; 2 reduction washer, 2-in to 1-in

Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks.

Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.