

Keystone-Tip Screwdrivers – Heavy-Duty Square-Shanks

Additional Features:

- Heavy-duty square shank for wrench-assisted turning.
- Bolster reinforces shank for hard use.
- Designed for the most demanding uses.



| Cat. No. | Shank Tip Width | Shank Length | Overall Length | Weight (lbs.) |
|----------|-----------------|--------------|--------------------|---------------|
| 600-4 | 1/4" (6 mm) | 4" (102 mm) | 8-11/32" (212 mm) | .25 |
| 600-6 | 5/16" (8 mm) | 6" (152 mm) | 10-15/16" (278 mm) | .40 |
| 600-8 | 3/8" (10 mm) | 8" (203 mm) | 13-7/16" (341 mm) | .65 |
| 600-12 | 1/2" (13 mm) | 12" (305 mm) | 17-7/16" (443 mm) | .80 |

Keystone-Tip Screwdrivers – Heavy-Duty Round-Shanks

Additional Features:

- Built to handle the tough jobs with ease.
- Hex bolster reinforces shank for hard use and allows wrench assisted turning.



| Cat. No. | Shank Tip Width | Shank Length | Overall Length | Weight (lbs.) |
|----------|-----------------|----------------|--------------------|---------------|
| 600-1* | 1/4" (6 mm) | 1-1/2" (38 mm) | 3-7/16" (87 mm) | .10 |
| 602-3 | 7/32" (6 mm) | 3" (76 mm) | 6-3/4" (171 mm) | .15 |
| 602-4 | 1/4" (6 mm) | 4" (102 mm) | 8-11/32" (212 mm) | .25 |
| 602-6 | 5/16" (8 mm) | 6" (152 mm) | 10-15/16" (278 mm) | .35 |
| 602-8 | 3/8" (10 mm) | 8" (203 mm) | 13-7/16" (341 mm) | .55 |
| 602-10 | 3/8" (10 mm) | 10" (254 mm) | 15-7/16" (392 mm) | .60 |
| 602-12 | 3/8" (10 mm) | 12" (305 mm) | 17-7/16" (443 mm) | .65 |

* Bolster not available on 600-1.
Refer to the insulated section for insulated screwdrivers.

Cabinet-Tip Screwdrivers – Round-Shanks

Additional Feature:

- Narrow cabinet-tip permits blade access where space is limited.



| Cat. No. | Shank Tip Width | Shank Length | Overall Length | Weight (lbs.) |
|----------|-----------------|--------------|------------------|---------------|
| 601-3 | 3/16" (5 mm) | 3" (76 mm) | 6-3/4" (171 mm) | .10 |
| 601-4 | 3/16" (5 mm) | 4" (102 mm) | 7-3/4" (197 mm) | .15 |
| 601-6 | 3/16" (5 mm) | 6" (152 mm) | 9-3/4" (248 mm) | .15 |
| 601-8 | 3/16" (5 mm) | 8" (203 mm) | 11-3/4" (298 mm) | .20 |
| 601-10 | 3/16" (5 mm) | 10" (254 mm) | 13-3/4" (349 mm) | .20 |

| Cat. No. | Shank Tip Width | Shank Length | Overall Length | Weight (lbs.) |
|--------------------------|-----------------|--------------|--------------------|---------------|
| Heavy-Duty Shanks | | | | |
| 605-4 | 1/4" (6 mm) | 4" (102 mm) | 8-11/32" (212 mm) | .25 |
| 605-6 | 1/4" (6 mm) | 6" (152 mm) | 10-11/32" (263 mm) | .30 |
| 605-8 | 1/4" (6 mm) | 8" (203 mm) | 12-11/32" (314 mm) | .30 |
| 605-10 | 1/4" (6 mm) | 10" (254 mm) | 14-11/32" (365 mm) | .35 |

Refer to the insulated section for insulated screwdrivers.

Profilated Phillips-Tip Screwdrivers – Round-Shanks

Additional Features:

- Tips are precision-machined to provide a more consistent geometric symmetry than conventional Phillips-tip screwdrivers.
- Provides accurate fit and torque without slippage.



| Cat. No. | Point Size | Shank Length | Overall Length | Weight (lbs.) |
|----------|------------|----------------|-------------------|---------------|
| 603-1 | No. 2 | 1-1/2" (38 mm) | 3-7/16" (87 mm) | .10 |
| 603-3 | No. 1 | 3" (76 mm) | 6-3/4" (171 mm) | .15 |
| 603-4 | No. 2 | 4" (102 mm) | 8-5/16" (211 mm) | .25 |
| 603-6 | No. 3 | 6" (152 mm) | 11" (279 mm) | .35 |
| 603-7 | No. 2 | 7" (178 mm) | 11-5/16" (287 mm) | .30 |
| 603-10 | No. 2 | 10" (254 mm) | 14-5/16" (364 mm) | .35 |

Refer to the insulated section for insulated screwdrivers.

All dimensions are in inches and (millimeters).

WARNING: Always wear approved eye protection.

WARNING: NOT insulated. Will NOT protect against electrical shock.

WARNING: Do NOT use to pry or chisel.

