2415 INTEGRATED SHORT ORDER WASH SYSTEM, 24"

Incorporate Heinzen's state-of-the-art Integrated Wash System into your line today! Quickly washes, cools and de-waters product.

FEATURES

- Innovative Channelized[™] Stainless Steel Construction
- 110 gal. capacity tank with adjustable nozzles completely submerges and gently conveys product
- Sand trap with drain valve
- 160 gal. capacity recirculation tank with parabolic screen filtration
- Pump, controls, and recirculation tank mounted to a common frame for minimal footprint
- SS water manifold with sanitary clamps and fittings
- System ships pre-wired and plumbed
- Options:
- Different chiller options available
- Integrated de-watering belt with spray bar features drop-down product guides, belt -lifter and pivoting tail section for easy sanitation and maintenance
- Dewatering shaker allows for ease of product conveyance and simplicity in sanitation

SPECIFICATIONS

- Capacity: 1,000-3,000pph
- 5hp wash-down duty SST pump motor for wash tank / 7.5hp for agitation nozzles
- 200 gpm SST pump for tank, 140 gpm for spray nozzles
- Available in 40A/480V, 60HZ, 3ph
- Footprint: 65"W x 172"L x 56" feed height



PRODUCT APPLICATIONS

- Fresh-Cut Leafy Greens
- Tender leaf Products



YOUR PARTNER IN FOOD SAFE INNOVATION