

2460 FOOD PUMP SYSTEMS

The latest in pumping technology allowing for creative and efficient transfer of product!

OPERATING LEVELS

	6"	8"	10"
MIN FLOW	300 GPM	525 GPM	525 GPM
MAX FLOW	2000 GPM	1600 GPM	4250 GPM
DISCHARGE SIZE	6"	8"	10"
SUCTION SIZE	6"	8"	10"
SOLIDS HANDLING	4"x6"	5"x9"	7.5"x12"
MAX SPEED	1400 RPM	950 RPM	810 RPM
SHUT-OFF HEAD	120'	86'	104'
BEP HEAD	64'	47'	50'
BEP FLOW	1650 GPM	1400 GPM	3200 GPM
BEP PERCENT	75%	65%	70%



PARTS & MATERIALS

WEAR RING	304 SS
IMPELLER	304 SS
VOLUTE	304 SS
SHAFT	STRESSPROOF STEEL
SHAFT SLEEVE	316 SS
SEAL HOUSING	304 SS
SEAL	MECHANICAL SEAL (TYPE 2)
BEARING FRAME	CAST IRON, ASTM A48
PUMP BODY	304 SS

APPLICATIONS

- Wash & Delivery of Products to Different Plant Locations and Elevations
- An Alternative Solution where Space is at a Minimum for Normal Flume Systems

*Now Available in Raw Stainless Steel Finish—
Epoxy Coating Optional!*

HEINZEN™

YOUR PARTNER IN FOOD SAFE INNOVATION