SetPixel function

9 out of 16 rated this helpful

The **SetPixel** function sets the pixel at the specified coordinates to the specified color.

Syntax

```
C++

COLORREF SetPixel(
    _In_ HDC hdc,
    _In_ int X,
    _In_ int Y,
    _In_ COLORREF crColor
);
```

Parameters

hdc [in]

A handle to the device context.

X [in]

The x-coordinate, in logical units, of the point to be set.

Y [in]

The y-coordinate, in logical units, of the point to be set.

crColor [in]

The color to be used to paint the point. To create a **COLORREF** color value, use the **RGB** macro.

Return value

If the function succeeds, the return value is the RGB value that the function sets the pixel to. This value may differ from the color specified by *crColor*; that occurs when an exact match for the specified color cannot be found.

If the function fails, the return value is -1.

This can be the following value.

Return code	Description
ERROR_INVALID_PARAMETER	One or more of the input parameters is invalid.

Remarks

The function fails if the pixel coordinates lie outside of the current clipping region.

Not all devices support the ${\bf SetPixel}$ function. For more information, see ${\bf GetDeviceCaps}$.

Requirements

Minimum supported client	Windows 2000 Professional [desktop apps only]
Minimum supported server	Windows 2000 Server [desktop apps only]
Header	Wingdi.h (include Windows.h)
Library	Gdi32.lib
DLL	Gdi32.dll

See also

Bitmaps Overview
Bitmap Functions
GetDeviceCaps
GetPixel
SetPixelV
COLORREF
RGB

Build date: 6/12/2013

Community Additions

GetPixel versus SetPixel

Note that it is possible to set a pixel using SetPixel and then get back a slightly different colour when you use GetPixel on the same pixel. Whether or not this happens depends on the device context and its capabilities and colour depth properties.



© 2014 Microsoft. All rights reserved.