



US008837144B1

(12) **United States Patent**
Allen

(10) **Patent No.:** **US 8,837,144 B1**

(45) **Date of Patent:** **Sep. 16, 2014**

(54) **LOCKING ASSEMBLY FOR ELECTRONIC
TABLET AND OTHER DEVICES**

(71) Applicant: **Peter Allen**, Oyster Bay, NY (US)

(72) Inventor: **Peter Allen**, Oyster Bay, NY (US)

(73) Assignee: **Think Products, Inc.**, Hauppauge, NY
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/270,085**

(22) Filed: **May 5, 2014**

Related U.S. Application Data

(63) Continuation of application No. 13/526,514, filed on
Jun. 18, 2012, now Pat. No. 8,717,758, which is a

(Continued)

(51) **Int. Cl.**

H05K 5/00 (2006.01)

H05K 7/00 (2006.01)

E05B 69/00 (2006.01)

E05B 73/00 (2006.01)

H01L 23/34 (2006.01)

A47B 81/00 (2006.01)

A47B 97/00 (2006.01)

G06F 1/16 (2006.01)

(52) **U.S. Cl.**

CPC **E05B 73/00** (2013.01); **G06F 1/1656**
(2013.01); **E05B 73/0082** (2013.01)

USPC **361/679.57**; 361/679.58; 312/223.2;
211/8; 211/9; 70/15; 70/50

(58) **Field of Classification Search**

USPC 361/679.57, 679.58, 679.01, 679.02;
312/223.1, 223.2, 223.3; 211/8, 9;
257/727; 70/15, 50

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,181,319 A 5/1965 Hudon

3,275,160 A 9/1966 Zurker

(Continued)

FOREIGN PATENT DOCUMENTS

CA 454901 3/1949

CA 791364 8/1968

(Continued)


Primary Examiner — Anthony Haughton

(74) *Attorney, Agent, or Firm* — Alfred M. Walker; John F.
Vodopia

(57) **ABSTRACT**

A method for securing a portable electronic device having a housing to a substantially immovable object utilizing a locking assembly having a security rod or spike formed with an anchoring end separated axially by a protruding end, a locking device with an internal locking mechanism and a cable permanently attached to the locking device at one end, includes several steps. The steps include securely fixing the anchoring end of the security rod or spike to the portable electronic device upon or through the housing, attaching an other end of the cable to the substantially immovable object and inserting the protruding end of the security rod into an opening in the locking device to actuate the internal locking mechanism and lock the locking device to the captive security rod. Locking the security rod to the locking device concurrently locks the portable electronic device to which it is anchored to the substantially immovable object.

20 Claims, 41 Drawing Sheets



ACCO Brands
Exhibit 1003

ACCO Brands v. Think Products
IPR2015-01167



US008837144B1

(12) **United States Patent**
Allen

(10) **Patent No.:** **US 8,837,144 B1**
(45) **Date of Patent:** **Sep. 16, 2014**

(54) **LOCKING ASSEMBLY FOR ELECTRONIC
TABLET AND OTHER DEVICES**

(71) Applicant: **Peter Allen**, Oyster Bay, NY (US)

(72) Inventor: **Peter Allen**, Oyster Bay, NY (US)

(73) Assignee: **Think Products, Inc.**, Hauppauge, NY
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/270,085**

(22) Filed: **May 5, 2014**

Related U.S. Application Data

(63) Continuation of application No. 13/526,514, filed on
Jun. 18, 2012, now Pat. No. 8,717,758, which is a

(Continued)

(51) **Int. Cl.**

H05K 5/00 (2006.01)

H05K 7/00 (2006.01)

E05B 69/00 (2006.01)

E05B 73/00 (2006.01)

H01L 23/34 (2006.01)

A47B 81/00 (2006.01)

A47B 97/00 (2006.01)

G06F 1/16 (2006.01)

(52) **U.S. Cl.**

CPC **E05B 73/00** (2013.01); **G06F 1/1656**
(2013.01); **E05B 73/0082** (2013.01)

USPC **361/679.57**; 361/679.58; 312/223.2;
211/8; 211/9; 70/15; 70/50

(58) **Field of Classification Search**

USPC 361/679.57, 679.58, 679.01, 679.02;
312/223.1, 223.2, 223.3; 211/8, 9;
257/727; 70/15, 50

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,181,319 A 5/1965 Hudon

3,275,160 A 9/1966 Zurker

(Continued)

FOREIGN PATENT DOCUMENTS

CA 454901 3/1949

CA 791364 8/1968

(Continued)


Primary Examiner — Anthony Haughton

(74) *Attorney, Agent, or Firm* — Alfred M. Walker; John F.
Vodopia

(57) **ABSTRACT**

A method for securing a portable electronic device having a housing to a substantially immovable object utilizing a locking assembly having a security rod or spike formed with an anchoring end separated axially by a protruding end, a locking device with an internal locking mechanism and a cable permanently attached to the locking device at one end, includes several steps. The steps include securely fixing the anchoring end of the security rod or spike to the portable electronic device upon or through the housing, attaching an other end of the cable to the substantially immovable object and inserting the protruding end of the security rod into an opening in the locking device to actuate the internal locking mechanism and lock the locking device to the captive security rod. Locking the security rod to the locking device concurrently locks the portable electronic device to which it is anchored to the substantially immovable object.

20 Claims, 41 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/031,174, filed on Feb. 18, 2011, now Pat. No. 8,223,488, which is a continuation-in-part of application No. 12/657,670, filed on Jan. 25, 2010, now Pat. No. 8,139,356, which is a continuation-in-part of application No. 12/154,561, filed on May 23, 2008, now Pat. No. 7,724,520, which is a continuation-in-part of application No. 11/454,433, filed on Jun. 15, 2006, now Pat. No. 7,443,665, which is a continuation-in-part of application No. 11/359,871, filed on Feb. 22, 2006, now Pat. No. 7,324,333, which is a continuation-in-part of application No. 11/038,591, filed on Jan. 19, 2005, now Pat. No. 7,315,443.

- (60) Provisional application No. 60/626,839, filed on Nov. 10, 2004, provisional application No. 60/655,270, filed on Feb. 22, 2005, provisional application No. 60/569,561, filed on May 10, 2004, provisional application No. 60/725,333, filed on Oct. 11, 2005, provisional application No. 60/691,476, filed on Jun. 17, 2005, provisional application No. 60/678,911, filed on May 6, 2005, provisional application No. 60/757,737, filed on Jan. 10, 2006, provisional application No. 60/783,188, filed on Mar. 16, 2006.

References Cited

U.S. PATENT DOCUMENTS

3,410,122 A 11/1968 Moses
 3,410,580 A 11/1968 Longenecker
 3,535,898 A 10/1970 Allport
 3,707,860 A 1/1973 Singer
 RE28,187 E 10/1974 Longenecker
 3,945,227 A 3/1976 Reiland
 3,965,705 A 6/1976 Nadler
 4,009,599 A 3/1977 Patriquin
 4,066,231 A 1/1978 Bahner
 4,418,553 A 12/1983 Applegate
 4,426,863 A 1/1984 Gillette
 4,696,449 A 9/1987 Woo
 4,733,840 A 3/1988 D'Amore
 4,738,428 A 4/1988 Themistos
 4,821,538 A 4/1989 Gray
 4,856,304 A 8/1989 Derman
 4,870,842 A 10/1989 Plumer
 5,052,198 A 10/1991 Watts
 5,052,199 A 10/1991 Derman
 5,076,079 A 12/1991 Monoson
 5,082,232 A 1/1992 Wilson
 5,085,395 A 2/1992 Frater
 5,135,197 A 8/1992 Kelley
 5,154,456 A 10/1992 Moore
 5,169,114 A 12/1992 O'Neil
 5,265,449 A 11/1993 Rashleigh
 5,345,219 A 9/1994 Rogers
 5,351,507 A 10/1994 Derman
 5,351,508 A 10/1994 Kelley
 5,361,610 A * 11/1994 Sanders 70/14
 5,381,685 A 1/1995 Carl
 5,406,809 A 4/1995 Igelmund
 5,446,618 A 8/1995 Tetsuya
 5,469,726 A 11/1995 Rushing
 5,493,878 A 2/1996 Murray
 5,502,989 A 4/1996 Murray
 5,526,226 A 6/1996 Katoh
 5,531,082 A 7/1996 Wolk
 5,542,723 A 8/1996 Scharf
 5,560,481 A 10/1996 Doodson
 5,568,359 A 10/1996 Cavello
 5,582,044 A 12/1996 Bolich

5,595,074 A 1/1997 Munro
 5,608,605 A * 3/1997 Siow et al. 361/679.43
 5,645,261 A 7/1997 Glynn
 5,675,998 A * 10/1997 Monteiro 70/18
 5,709,110 A * 1/1998 Greenfield et al. 70/58
 5,760,690 A 6/1998 French
 5,762,306 A 6/1998 Day
 5,787,738 A * 8/1998 Brandt et al. 70/58
 5,787,739 A 8/1998 Derman
 5,794,463 A 8/1998 McDaid
 5,816,076 A 10/1998 Biedermann
 5,836,183 A 11/1998 Derman
 D405,348 S 2/1999 Orr
 5,926,092 A 7/1999 Kim
 5,927,108 A 7/1999 Pierce
 D415,950 S 11/1999 Anderson
 6,000,252 A 12/1999 Murray
 6,006,557 A 12/1999 Carl
 D425,402 S 5/2000 Welborn
 6,138,483 A 10/2000 Galant
 6,155,088 A 12/2000 Murray
 D436,310 S 1/2001 Arnold
 6,178,089 B1 1/2001 Alfonso
 6,182,481 B1 * 2/2001 Nagy 70/58
 6,185,964 B1 2/2001 Addiego
 6,212,921 B1 4/2001 Knighton
 6,216,499 B1 4/2001 Ronberg
 6,237,375 B1 5/2001 Wymer
 6,257,542 B1 7/2001 Westfield
 6,275,378 B1 8/2001 Lee
 6,308,928 B1 10/2001 Galant
 6,317,936 B1 11/2001 McDaid
 6,331,934 B1 12/2001 Helot
 6,427,499 B1 8/2002 Derman
 6,443,417 B2 9/2002 Galant
 6,477,871 B1 11/2002 Derman
 6,497,125 B1 12/2002 Necchi
 6,560,710 B1 5/2003 Leyden
 6,578,394 B2 * 6/2003 Yin 70/58
 6,581,420 B1 6/2003 Ling
 6,590,767 B2 7/2003 Liao
 6,612,455 B2 9/2003 Byrne
 D485,060 S 1/2004 DeCotis
 6,684,548 B1 2/2004 Petrus
 6,689,954 B2 2/2004 Vaughan
 6,697,252 B2 2/2004 Maeda
 6,705,133 B1 3/2004 Avganim
 6,708,966 B1 3/2004 Troudt
 6,711,921 B1 3/2004 Yang
 6,735,990 B1 5/2004 Murray
 D491,009 S 6/2004 Burdett
 6,755,056 B2 6/2004 Igelmund
 6,763,690 B2 7/2004 Galant
 6,788,216 B2 * 9/2004 Chen 340/693.5
 6,796,536 B1 9/2004 Sevier
 6,810,698 B2 11/2004 Weinraub
 6,820,362 B1 11/2004 Petrus
 D499,546 S 12/2004 Smithers
 6,865,914 B2 3/2005 Irgens
 D503,532 S 4/2005 Andre
 6,913,238 B2 7/2005 Bakker
 6,920,770 B2 7/2005 Lurie
 6,926,141 B2 8/2005 Montler
 7,007,912 B1 3/2006 Giuliani
 D519,731 S 5/2006 Andre
 D521,232 S 5/2006 Andre
 7,107,054 B2 9/2006 Florkey et al.
 D533,994 S 12/2006 Hussaini
 7,255,228 B2 8/2007 Kim
 D553,352 S 10/2007 Allen
 D559,076 S 1/2008 Allen
 7,315,443 B2 1/2008 Allen
 D565,839 S 4/2008 Allen
 7,409,842 B2 8/2008 Kuo
 7,443,665 B2 10/2008 Allen
 7,499,269 B2 3/2009 Allen
 7,499,270 B2 3/2009 Allen
 7,647,796 B2 1/2010 Francke
 7,963,132 B2 6/2011 Andres

(56)

References Cited

U.S. PATENT DOCUMENTS

8,107,236	B2 *	1/2012	Lin	361/679.57
8,111,511	B2 *	2/2012	Ruch et al.	361/679.57
2001/0049949	A1	12/2001	Iglemund	
2003/0085125	A1	5/2003	Yatabe	
2004/0007651	A1	1/2004	Williams	
2005/0150263	A1	7/2005	Murray	
2005/0161557	A1	7/2005	Heintz	
2005/0178173	A1	8/2005	Kuo	
2005/0247584	A1	11/2005	Lu	
2006/0032877	A1	2/2006	Obolo	
2006/0117814	A1 *	6/2006	Francke	70/18
2006/0176661	A1	8/2006	Allen	
2007/0205125	A1	9/2007	Ikebe	
2007/0235493	A1	10/2007	Fortson	
2008/0110217	A1 *	5/2008	Andrews et al.	70/58
2010/0320884	A1 *	12/2010	Shiroishi et al.	312/223.1

FOREIGN PATENT DOCUMENTS

CA	987121	4/1976
DE	329934	12/1920
DE	335741	4/1921
DE	361068	4/1923
DE	456219	2/1928
DE	577757	6/1933
DE	3202700	4/1983
DE	3407723	9/1985
DE	3824393	7/1989
FR	455740	8/1913
FR	877220	12/1942
FR	1026519	4/1953
FR	1085107	1/1955

FR	2308006	11/1976
FR	2636686	3/1990
FR	2741375	5/1997
GB	4470901	5/1936
GB	1256295	12/1971
GB	1376011	12/1974
GB	2109109	5/1983
GB	2234856	2/1991
HU	P0000398	6/2000
HU	224329	6/2003
IT	451949	3/1949
JP	49-91096	11/1947
JP	37-7592	6/1959
JP	52-36813	3/1977
JP	57-25092	2/1982
JP	57-179618	11/1982
JP	08-7462	1/1996
JP	087462	1/1996
JP	2000-305845	11/2000
JP	2002149264	A 5/2002
JP	2004318426	A 11/2004
JP	2000-140948	5/2005
NO	14095	5/1905
WO	WO86/00396	A1 1/1986
WO	WO93/15295	A1 8/1993
WO	WO95/10680	A1 5/1995
WO	WO96/07002	A1 3/1996
WO	WO9615347	A1 5/1996
WO	WO2008/051919	A2 5/2008
WO	WO2008/051930	A2 5/2008
WO	2008067173	A2 6/2008
WO	WO2008/147818	A1 12/2008
WO	WO2009/026225	A1 2/2009
WO	WO2010/080402	A1 7/2010
WO	2011000108	A1 3/2011

* cited by examiner




FIG. 1




FIG. 2




FIG. 2A






FIG. 2B






FIG. 2D





FIG. 3A






FIG. 4




FIG. 6




FIG. 5





FIG. 7






FIG. 9




FIG. 11




FIG. 12





FIG. 10






FIG. 13A

FIG. 13B




FIG. 14





FIG. 15








FIG. 17













FIG. 20








FIG. 29

FIG. 28




FIG. 28A











FIG. 28B












FIG. 38




FIG. 39




FIG. 36








FIG. 37






FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52






FIG. 53






FIG. 56




FIG. 55A




FIG. 55B




FIG. 57




FIG. 58B








FIG. 58A














FIG. 63



1

LOCKING ASSEMBLY FOR ELECTRONIC TABLET AND OTHER DEVICES

RELATED APPLICATIONS

This application is a continuation of application of U.S. application Ser. No. 13/526,514 filed Jun. 18, 2012, which '514 application is a continuation application of U.S. application Ser. No. 13/031,174, filed Feb. 18, 2011, which '174 continuation application is a continuation-in-part ("CIP") of U.S. application Ser. No. 12/657,670, filed Jan. 25, 2010, which '670 application is a continuation-in-part (CIP) application of U.S. application Ser. No. 12/154,561, filed May 23, 2008 ('561 application), which '561 application is a CIP application of U.S. application Ser. No. 11/454,433, filed Jun. 16, 2006 ('433 application), which '433 application is a CIP application of U.S. application Ser. No. 11/359,871, filed Feb. 22, 2006 ('871 application), which '871 application is a CIP application that claims priority from a) U.S. Provisional Appln. No. 60/655,270, filed Feb. 22, 2005, b) Provisional Appln. No. 60/678,911, filed May 6, 2005 and c) U.S. application Ser. No. 11/038,591, filed Jan. 19, 2005 ('591 application), which '591 application claims priority from i) U.S. Appln. No. 60/569,561, filed May 10, 2004 and ii) Provisional Appln. No. 60/626,839, filed Nov. 10, 2004. The '433 application further claims priority from A) Provisional Appln. No. 60/691,476, filed Jun. 17, 2005, B) Provisional Appln. No. 60/725,333, filed Oct. 11, 2005, C) Provisional Appln. No. 60/757,737, filed Jan. 10, 2006, and D) Provisional Appln. No. 60/783,188, filed Mar. 16, 2006.

FIELD OF THE INVENTION

The present invention relates to a locking assembly for tablet computers (i.e. iPad®), smart phones, electronic books known as "ereaders", and other hand-held personal digital devices, as well as to plunger security locks, and to laptop computers, notebook computers and other hand-held electronic devices such as cell phones, personal digital assistants, personal music and/or video players (i.e. iPod®), etc., without limitation, which are configured for operational use with a locking assembly associated with such a plunger security lock.

BACKGROUND OF THE INVENTION

Notebook computers, tablet computers or other personal electronic devices are increasingly used by students at educational institutions. They are also used by workers at job sites. Notebook computers are often referred to as laptop computers, meaning a portable, foldable computer which can be used while positioned upon the user's lap. In some instances, "laptop computer" refers to the term used in the trade for an older version of a larger portable computer. However, with increasing streamlining and downsizing of portable computers, compact, smaller versions are referred to as "notebook computers", but to the terms are generally interchangeable.

Personal electronic devices, such as tablet computers (i.e. iPad®), cell phones, smart phones, personal digital assistants, personal music and/or video players (i.e. iPod®), etc. without limitation, can be used just about anywhere. Other personal digital assistants, including electronic books, known as "ereaders", such as the Nook®, can download virtual images of books.

In order to safeguard the personal electronic device, such as a tablet computer, a notebook computer, smart phone, ereader

2

or personal music and/or video player, it must be shut down, closed and transported by the user.

However, it is often advantageous for the user of a tablet computer, notebook computer or other personal electronic device to take a break and leave the device/computer open and operable at a work station, library study carrel, etc., with other papers and books left at their current open position. This leaves the personal electronic device, such as a tablet computer or notebook computer, vulnerable to theft.

Moreover, in the commercial retail environment, it is advantageous to display consumer electronic devices, such as tablet computers, notebook computers, cell phones or personal digital assistants in a secure but visually accessible display.

For that matter, various security devices are known for securing personal electronic devices configured for use with the known security devices.

For example, U.S. Pat. No. 6,755,056 (the '056 patent), discloses a security device (e.g., male lock fitting **100**) for securing portable equipment having a security slot in the chassis of the equipment, and adaptor for adapting electronic portable equipment without a slot for use with the security device. The security device (**100, 100'**) is tethered to a piece of heavy furniture or otherwise immovable structure, typically with a braided cable or like means, and includes an attachment with a slot mating head and an axial movable head locking member. This is inserted into the slot in the housing of the electronic equipment (or in the adaptor affixed to the housing where there is no slot) after the slot mating head to prevent rotation and removal of the head from the slot.

For example, the FIG. 7 security device (**100'**) is inserted into a lock fitting receptacle **106** where pin **104** passes through the head locking aperture **25** into mounting end **22** and into slot opening **12**. When fully inserted, the housing lockably engages the fitting by way of conventional locking mechanisms, such as fixed or retractable teeth **108, 108'** on the male lock fitting and teeth engaging notches **110** within the receptacle, so the pin is secured in the head locking position.

One of the shortcomings of the '056 patent, however, is that the security provided is only as strong as either the housing material and therefore slot integrity, or the adhesive adhering the adaptor to the housing. A thin, sheet-metal housing is pliable and a plastic housing is frangible, allowing for easy removal of the attachment with slot mating head and axial moveable head locking member, once in place.

U.S. Pat. No. 6,513,350 (the '350 patent), discloses a physical security system comprising a combination lock for connecting specially designed security slots in portable electronic devices, such as a notebook computer. Like the '056 patent, the security device of '350 patent operates with a portable computer with a wall **10** having an inner surface **20**, which wall is configured with a slot **15**. A lock interface **25** is engageable with wall **10** through slot **15**. A locking mechanism **30** comprising a tethering cable and lock **40** allows that, upon inserting lock interface **25** in slot **15** and engaging the interface with inner surface **20**, the lock interface is then attached to a stationary object with lock **40** and cable **40**.

FIG. 6 shows an alternative locking system **600**, including a housing **605** and slot engagement member **610** with locking member **615** and retaining member **620**. Engagement member **610** is coupled to the housing **605** so that it moves between an extended and retracted position. Two pins **625** extend from the housing **605** and are located on opposing sides of a shaft of engagement member **610**. The housing **605** includes a combination lock mechanism **630** for interacting with the

3

engagement member 610 and retaining in the retracted position until the correct combination code is dialed in to the lock mechanism.

Also like the '056 patent, however, the security provided by the '350 patent is only as strong as the housing material and therefore slot integrity. Moreover, and as is readily apparent in FIG. 6, there does not appear to be a means for effecting retraction and extension of pins 625 to/from housing 605, or means for comfortably grasping the lock mechanism to articulate slot engagement member in the slot 660 in wall 650 (FIG. 6).

OBJECTS AND SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a locking assembly security apparatus for a non-foldable tablet computer, ereader or smart phone preferably associated with a plunger-type security lock or other locking device, and an electronic device configured to be secured in cooperation with the locking assembly and plunger-type security lock, which overcome the shortcomings of the prior art.

In one embodiment, the invention comprises a locking bar associated with a plunger-type or other security lock comprising a cradle including at least one diagonally extending chassis bar with respective pockets at opposite ends, wherein one of the pockets is hingeably releasable to insert one corner of the tablet computer, smart phone, ereader, or other hand held personal digital assistant device therein while the other end is a non-hingable pocket into which the opposite corner of the tablet computer, smart phone, ereader or other hand held personal digital assistant is inserted therein. The hingeable pocket includes a hingable housing which pivots to allow insertion of one corner of the device to be inserted therein, after the opposite corner has already been inserted in the slot of the fixed, non-hingable pocket at the opposite side of the at least one chassis bar. The chassis bar is preferably adjustable in length, to allow for different sized devices to be locked therewith. Although there is preferably one diagonal chassis bar with opposite corner pockets to receive one of respective diagonally opposed corners of the device, it is contemplated that more than one chassis bar can be utilized, and/or comprise a frame with at least a pair of pockets each pocket supporting a respective corner of the device therein. One end of the chassis bar is configured as an axially extending flange with an aperture hole, which flange is insertable within a corresponding slot in lock having a movable pin or hook of a combination lock and locking mechanism in a housing.

For example, in a preferred embodiment, the security apparatus of this invention is designed to engage diagonal corners of an electronic tablet (such as an iPad®). The locking assembly apparatus engages with a tablet computer or similar device, which is securely locked to it via a combination pin lock, such as, for example, a plunger lock. A respective distal corner pocket engages one corner of the tablet computer, while a respective proximal lockable corner pocket engages the diagonally opposite corner of the tablet computer. The security apparatus includes a chassis bar, such as a flat metal chassis bar connecting the fixed distal pocket to the diagonally opposite proximal hingable pocket.

The base of the proximal pocket extends from the attachment portion to the diagonally extending chassis bar to the flanges at the proximal end on the other side of the integral hinge pin housing of the proximal pocket, which flips up to permit a corner of the tablet computer or other device to be inserted or disengaged. The hingable tail section of the flange fits between the forked flange protrusions of the base of

4

the proximal hingable pocket; when it is co-planar with the base and the slot of the pin lock can be fit over the end and locked by its pin engaging the hole within the hingable tail section of the hingable pocket, to complete the locking procedure.

Although a pre-determined sized security apparatus can be provided for the size most popular tablets or similar devices on the market, an adjustable single unit can also be provided as an alternate embodiment. In one embodiment, the adjustability feature is formed by permitting the metal chassis bar to slide through a slot in a modified distal pocket. An array of holes in the chassis provides the adjustability by virtue of a friction fit removable locking pin. The pin cannot be taken out once the tablet computer is engaged, but it is simply lifted up for adjustment to permit the pocket to slide on the bar.

Another adjustable embodiment uses a two-part telescoping metal chassis bar. This embodiment is more compact for smaller tablets or like items since there is no distal metal bar extending beyond the distal engagement pocket.

While any kind of plunger type pin lock having a slot and movable pin or hook can be utilized, in another embodiment a connector is provided connecting permanently connecting the locking housing to a tether, a plunger operational in cooperation with locking mechanism and a sliding key operate to lock the tether to a one end of a locking strip, which end extend part way through the electronic device. The other end of the locking strip comprises wedge stop, to prevent the locking strip from passing all the way through the housing, for example, a hinge gap between upper and lower housings.

The plunger-type security lock preferably operates by grasping the housing, dialing in a correct combination and pushing the plunger through the hole associated with one of the pockets. In another embodiment the plunger is pushed to extend the sliding key from a housing in order to engage a portion of the locking member. Once engaged, and upon release of the pushing force, the sliding key retracts the engaged portion of the locking member at least partially into the housing, and maintains it until the combination locking mechanism is unlocked.

In another embodiment, the invention comprises an electronic device configured for allowing a locking member to pass partially through, but not completely through some part of the electronic device chassis or housing, a locking member and a plunger-type security lock configured for lockingly engaging some part of the locking member once passed through the chassis or housing part.

Other objects which become apparent from the following description of the present invention.

When locked in place, the notebook computer or other personal electronic device is secure from being taken away from the surface to which it is locked. Furthermore, taking advantage of software and/or software/biometric security systems, the computer or other personal electronic device will also be unusable by unauthorized individuals when its owner is away from the area for a break, telephone call, or other short-term pursuits. With a few keystrokes, the owner of the computer or other personal electronic device can resume activity in exactly the same place as when activity had been suspended. This is especially useful for leaving an active computer or other personal electronic device on a study desk or library carrel.

In an alternative embodiment, the invention includes a method for securing a portable electronic device having a housing to a substantially immovable object utilizing a locking assembly having a security rod or spike formed with an anchoring end separated axially by a protruding end, a locking device with an internal locking mechanism and a cable

5

permanently attached to the locking device at one end, includes several steps. The steps include securely fixing the anchoring end of the security rod or spike to the portable electronic device upon or through the housing, attaching an other end of the cable to the substantially immovable object and inserting the protruding end of the security rod into an opening in the locking device to actuate the internal locking mechanism and lock the locking device to the captive security rod. Locking the security rod to the locking device concurrently locks the portable electronic device to which it is anchored to the substantially immovable object.

In yet another alternative embodiment, the invention includes a locking assembly for securing a portable electronic device having at least one housing to a substantially immovable object. The locking assembly includes a captive security rod having a locking end and an anchoring end, wherein the anchoring end is passed through the at least one housing to anchor the captive security rod thereto and a locking device with a locking mechanism, wherein the locking device is configured to receive the locking end of the captive security rod to activate the locking mechanism and thereby lock the security rod and portable electronic device to the locking device.

The locking assembly also includes means for securing the locking device and, therefore, the captive security rod and portable electronic device to which the captive security rod is anchored, to a substantially non-movable object, e.g., a cable or lanyard, preferably permanently attached to the locking device. The locking end of the captive security rod comprises a knob that extends from the at least one housing after the anchoring end anchors the captive security rod thereto. Preferably, the small knob that is captured and held by the locking mechanism at locking actuation.

The captive security rod, upon anchoring to the at least one housing of the portable electronic device, is stored in a recess and grasped to deploy in an extended position. The locking end of the captive security rod operates to collapse into the at least one housing during non-use. The portable electronic device may be any of the group consisting of a laptop computer, a notebook computer, and tablet computer, a cell phone, a camera, a Smartphone, a music storage and a playback device, without limitation. For that matter, the portable electronic device preferably comprises a first housing, a second housing and a hinge, wherein said hinge separates and allows said first housing to be closed upon said second housing and wherein said captive security rod is deployed to extend and protrude from any surface of said first housing or said second housing.

In addition, and in one form, the second housing is a keyboard part and said captive security rod is inserted through and anchored, and operates to extend in a deployed position out of a surface of said second housing. The substantially immovable object may comprise a base plate and the locking device may comprise a pin lock, a plunger-type security lock, or other known lock, without limitations.

In yet another embodiment, the invention provides a locking assembly for securing a portable electronic device having a housing to a substantially immovable object. The locking assembly comprises a security rod or spike, a cable and a locking device.

The security rod or spike has a protruding end, an anchoring end opposite the protruding end and a transverse hole positioned between the protruding end and the anchoring end, wherein the anchoring end is configured for passing through an opening in the housing to anchor the security rod to the portable electronic device while leaving the transverse hole exposed. The cable has a first end and a second end, wherein

6

the second end is configured for secure fastening to the substantially immovable object. The locking device is configured with an opening for receiving the first end of the cable after it is passed through the transverse hole of the security rod or spike.

An actuating mechanism in the locking device captures the first end of the cable to lock security rod and spike and, therefore, the portable electronic device to the which the security rod is anchored, to the substantially immovable object. The first end of the cable is formed as a ferrule configured with a locking groove, and wherein the actuating mechanism captures the ferrule groove upon insertion of the first end of the cable into the lock device to actuate the locking mechanism.

After anchoring to the housing, the portion of the security rod or spike including the transverse hole and protruding end is always exposed.

The portable electronic device comprises a first housing, a second housing and a hinge, wherein said hinge separates and allows said first housing to be closed upon said second housing after the security rod is anchored to either the first or the second housing. The second housing is a keyboard part and said captive security rod is fixedly inserted through a surface of said second housing.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention can best be understood in connection with the accompanying drawings. It is noted that the invention is not limited to the precise embodiments shown in drawings, in which:

FIG. 1 is a perspective view of a locking base and locking collar of one of the embodiments for a notebook computer lock of this invention;

FIG. 2 is a side view of the embodiment of FIG. 1, taken along in the direction of arrow "2" of FIG. 1, showing a typical notebook computer locked with a locking base and locking collar to a work surface with a padlock;

FIG. 2A is a partial fragmentary view of the locking base as in FIG. 2, taken along in the direction of arrow "2A" of FIG. 2;

FIG. 2B is a partial perspective view of the typical notebook computer locked in place between the locking base and locking collar of FIG. 2;

FIG. 2C is a partial front elevational view of the locking base and locking collar as in FIG. 2;

FIG. 2D is a side elevational view of the notebook computer shown used by a person at a work station;

FIG. 3 is a perspective view of an alternate embodiment showing a typical notebook computer in the locking base with an elongated back side;

FIG. 3A is an exploded perspective view of a further embodiment, showing handheld electronic accessories displayed upon respective shelves, added to the front side of the locking base of FIG. 3;

FIG. 3B is a close-up of one type of key lock used with the notebook computer lock of the present invention;

FIG. 4 is a side view of alternate embodiment for a notebook computer lock of FIG. 3, showing dual locking flanges;

FIG. 5 is a perspective view of a transparent locking panel of the alternate embodiment shown in FIG. 4;

FIG. 6 is a side edge view of the transparent locking panel showing a locking flange, taken along in the direction of arrow "6" of FIG. 5;

FIG. 7 is a top plan view of the transparent locking panel showing a padlock hole in the locking flange, taken along in the direction of arrow "7" of FIG. 6;

7

FIG. 8 is an exploded perspective view showing the addition of an optional battery pack housing cage feature to the locking apparatus of the embodiment shown in FIG. 1, although it can be used with any of the embodiments herein;

FIG. 9 is a side view of the locking apparatus of FIG. 8 used on a notebook computer showing the housing cage feature;

FIG. 10 is a perspective view of a further alternate swing arm embodiment using a swinging arm, such as a telescoping bar, to secure a typical notebook computer;

FIG. 11 is a top plan view of a clad steel cable used as a locking element for the further alternate swinging arm embodiment;

FIG. 12 is a top plan view of a chain inside a flexible tube as an alternate locking element in the embodiment of FIG. 10;

FIG. 13 is a perspective view of an alternate embodiment of a notebook computer lock using a separate "over the table" locking base and a computer lock using a captive swinging locking bar, which fits across lower portion of the display;

FIG. 13A is a front elevation of a clamp detail of the locking base shown in FIG. 13, taken along the ellipse 13A of FIG. 13;

FIG. 13B is a clamp bracket side elevational view thereof, showing use of a key lock;

FIG. 14 is a side edge view of the locking base of FIG. 13, shown attached to a work surface;

FIG. 15 is a top plan view of the computer lock of FIG. 13, secured within a locking base, also showing the position of the notebook computer with dashed lines;

FIG. 16 is a perspective view of one embodiment for a width adjustable notebook computer lock;

FIG. 17 is a perspective view of a further embodiment for a discrete width adjustable notebook computer lock;

FIG. 18 is a perspective view of an integrated locking base/computer lock embodiment;

FIG. 19 is a top plan view of another integrated locking base/computer lock with two pivot links;

FIG. 20 is a perspective view of a preferred embodiment for a low profile notebook computer, shown attached by fasteners, such as screws, down to the work surface;

FIG. 21 is a perspective view of the locking base of FIG. 20 used as a portable device secured to the work surface via a cable and clamp;

FIG. 22 is a detail side view of the clamp screw subassembly used in FIG. 21, shown in the ellipse "22" of FIG. 21;

FIG. 23 is an exploded perspective view of the components of an alternate embodiment with a socket wrench type clamp screw subassembly;

FIG. 24 is a bottom view of the end cap of the embodiment of FIG. 23, showing the recess which forms the socket wrench element;

FIG. 25 is a top view of the clamp screw assembly as in FIG. 23, shown with the captive screw;

FIG. 26 is a side view cross-section of the clamp screw assembly as in FIG. 23, taken along line "26-26" of FIG. 25, shown with the screw head seated in the socket wrench recess and preventing insertion of the cable;

FIG. 27 is a side view in cross-section of the clamp screw assembly as in FIG. 23, shown with the cable preventing seating of the screw head in the socket wrench recess.

FIG. 28 is a perspective view showing the possible locations of through-holes for use of an alternate protrusion spike embodiment security feature used with a cable;

FIG. 28A is a perspective detail showing the closed front section of a notebook computer wherein a security feature is two through holes which align upon closing display lid permitting a padlock with an elongated hasp to lock the display to the keyboard base.

8

FIG. 28B is a perspective view of a notebook computer with a security hole in the top right corner of the display section.

FIG. 28C is a perspective view of the computer of FIG. 28B with a pin lock and locking ferrule aligned prior to insertion through security hole.

FIG. 28D is a perspective view of the computer of FIG. 28C after pin lock is used to secure ferrule thereby using a cable to secure computer to a table top.

FIG. 29 is a perspective view of the spike with a cable attached ferrule, pin lock, and secure cable clamp used to secure a notebook computer;

FIG. 30 is a schematic perspective view of a notebook computer with captive security rods for cable attachment;

FIG. 31 is a schematic perspective view of a notebook computer with a hole downward through the base for use with a long protrusion spike and a transverse locking pin;

FIG. 32 is a diagrammatic side elevational view of one embodiment for a flexible strip lock for a computer;

FIG. 33 is a front elevational view thereof, taken in the view direction of arrow "33" shown in FIG. 32;

FIG. 34 is a top plan view of the shim strip of the flexible lock;

FIG. 35 is a side elevational view taken in the view direction of arrow "35" of FIG. 34;

FIG. 36 is a perspective view of a lower protective shoe of the flexible lock;

FIG. 37 is a diagrammatic perspective view illustrating a flexible locking means;

FIG. 38 is a diagrammatic exploded view of a key locking means with a spring;

FIG. 39 is a partial view of a key locking means;

FIG. 40 is a perspective view of a notebook computer showing the hinge gap and the path of weaving the distal end of a locking strip through the hinge gap, as well a slot in the housing of the notebook computer permitting access to a rigid protruding locking strip therein;

FIG. 41 is a perspective view of a "flip top" cellular phone showing the hinge gap;

FIG. 42 is a perspective view of a PDA showing the hinge gap;

FIG. 43 is a perspective view of a personal DVD player showing the hinge gap;

FIG. 44 is a side elevation of an alternative embodiment of a strip captivating locking clamp of this invention, shown using an ordinary padlock;

FIG. 45 is a top view of the base portion of FIG. 44;

FIG. 46 is a side elevation of the handle portion of the alternate embodiment clamp of FIG. 44;

FIG. 47 is a bottom view (in the direction of arrow "47" in FIG. 46) of the handle of FIG. 46;

FIG. 48 is a top plan view of a further alternate embodiment for a locking strip of this invention;

FIG. 49 is a perspective view of the locking strip of FIG. 48 secured to a stud attached to the work surface by the use of a padlock;

FIG. 50 is a perspective of an alternate method of securing the locking strip of FIG. 48 by the use of a secure cable and a cable lock;

FIG. 51 is a perspective view of yet another method of securing the locking strip of FIG. 48 by virtue of a free cable with attached stop member;

FIG. 52 is a perspective view of one embodiment of a plunger-type security lock of the invention;

FIG. 53 is a plan view of another embodiment of a plunger-type security lock of the invention;

9

FIG. 54A is a plan view of the plunger-type security lock of FIG. 53, seen along A-A therein;

FIG. 54B is a cut away view of the plan view of the plunger-type security lock as shown in FIG. 54A;

FIGS. 55A and 55B are alternative perspective views of a cylindrical sliding key receptacle;

FIG. 56 is a perspective view of a cylindrical plunger;

FIG. 57 is a perspective view of a sliding key;

FIGS. 58A and 58B are bezels;

FIG. 59 is a perspective view of the security apparatus of this invention engaged with a computer tablet;

FIG. 60 is a perspective detail of the apparatus of FIG. 69 showing a close-up of the proximal locking mechanism with a pin lock;

FIG. 61 is a perspective view of the security apparatus with the computer tablet removed for clarity;

FIG. 62 is a perspective view of the proximal locking mechanism in the closed or engaged position;

FIG. 63 is a perspective view of the proximal locking mechanism in the open position as it would be when engaging or disengaging the security apparatus to or from a tablet;

FIG. 64 is a perspective detail of an embodiment of this invention with adjustment for accommodating different sized tablets or similar devices by using a movable distal engagement pocket; and

FIG. 65 is another adjustable embodiment using a telescoping chassis bar.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 shows locking base 1 for a notebook computer lock, which is secured to a working surface by fastener holes, such as screw through holes 4 in base mounting pads 3. A back surface 10 is tilted at angle "X" to provide a good viewing angle of the computer screen. Side panel members 6 with bent tabs 7 provide a space for sliding locking collar 2. Locking flange 8 with a locking hole, such as padlock hole 9, is used to secure locking collar 2 with flange 14 via hole 15, which is in positional registration with hole 9 when mated. Width "W" is wider than the widest notebook computer or other personal electronic device to be accommodated by this locking base system. Locking bar 12, attached to the distal ends of sides 13, actually secures the notebook computer or other personal electronic device. This is the preferred embodiment. The display screen portion rests within space 16 between sides 13. In use, the keyboard portion of a notebook computer or other personal electronic device would deny access to the fasteners, such as retaining screws, in holes 4.

Side panel members 6 may have one or more ports 6a to accommodate computer cables therethrough.

FIGS. 2, 2A, 2B and 2C show how locking collar 2 is placed over notebook computer screen 19 and then upon flange 14, and is locked to lower flange 8 via a lock, such as padlock 20. Keyboard 18 fits between sides 6. Space 5 is created by a raised back panel 10 so as to permit access to a variety of connectors at the back of computer keyboard portion 18. FIG. 2 also shows an optional compartment 42 for a power source accessory 43, such as an auxiliary battery charger or battery eliminator, wherein compartment 42 extends between power flange 8 and further lower flange 8A.

FIG. 2D shows the notebook computer being used by a person at a work station;

In an alternate embodiment shown in FIG. 3, upright portion 25 supports the entire height of screen 19 above raised back panel 10 mounted upon base pads 3. This can also be shown in FIG. 4. FIG. 3B shows another example of a lock 20a, which can be used in lieu of padlock 20.

10

FIG. 3A shows a further alternate embodiment where shelves 36 and 36a are depicted supporting electronic handheld devices such as folding cell phone 37a, upright cell phone 37b, marine VHF radio 37c, personal digital assistant 37d, calculator 37e and video game pad controller 37f.

A transparent panel, such as LEXAN® polycarbonate panel 30, shown in FIG. 5, is used as a locking frame, by sliding it over screen 19 within the four tabs shown in FIG. 3 at the distal corners of upright 25.

Panel 30, shown in FIGS. 4-7, has a top portion 32 and a locking flange 33 with padlock hole 35. In use, this hole is in positional registration with that of upper locking flange 27 shown in FIG. 4. A padlock 20 or other small lock 20a can be used to secure the two members together. Front face 31 of transparent panel 30 protects the surface of computer screen 19. This can be used to advantage in a retail demo environment. Alternately, the locking collar of FIG. 1 can be used with base of FIG. 3 by locking into lower locking tab 26; this would offer a better unencumbered view of screen 19.

FIG. 8 shows the addition of an optional battery pack housing cage 42 feature to the locking apparatus of the embodiment shown in FIG. 1, although it can be used with any of the embodiments herein;

The optional power source component 42 of FIGS. 2 and 8 can be added to any of the embodiments of this invention, including those shown in FIGS. 3-51. It is preferably a cage made of heavy duty wire screen or perforated metal that is attached (as by welding or rivets) to a rear panel, such as panel 41 in FIG. 8. This provides a secure compartment 42 for a power source accessory 43, such as an auxiliary battery, charger, or battery eliminator.

Compartment 42 is also shown in the side view of FIG. 9.

In a further alternate embodiment, shown in FIG. 10, a locking base using a telescoping rod 54 is shown. In this embodiment, there is no member such as locking collar 2 or transparent panel 30 that can be readily removed from the locking base when a computer or other personal electronic device is not secured to the base. This should reduce the incidence of vandalism or theft of the removable item which would render the base unusable. In FIG. 10, one end of bar 54 is attached to the left side panel member 51 of base 50 via a pivotable fastener, such as ball joint 53. After the notebook computer or other personal electronic device is inserted between sides 51 and 52, bar 54 is swung over the lower (hinge) portion of the notebook computer's screen, such as a liquid crystal display (LCD) screen and is elongated so as to insert lock plug 55 through locking hole 56 in right side 52. A lock (not shown), such as padlock 20, is then inserted through the hole in plug 55 thus locking computer to base.

Alternate locking members include locking members such as vinyl clad steel cable 60 shown in FIG. 11, and the flexible tubing clad chain 65 shown in FIG. 12. These two devices do not require a ball joint attachment to left flange 51. Cable 60 can be simply inserted through a hole in flange 51 and then retaining washer 61 can be permanently attached as by spot welding. Lock plug 55, used as for telescoping rod, is attached to the distal end of cable 60. Chain 65 can be attached to flange 51 in a similar fashion by attaching washer 66 to its proximal end after threading through a hole. The distal end of chain 65 has an elongated link 67 with stop washer attached. The padlock is engaged through this link after it emerges through hole 56 in side 52.

FIG. 13 shows an alternate embodiment using a separate locking base 81 used with a notebook computer or other personal electronic device lock 80 which slides in from the left so that one or more base pads 87 are retained by one or more brackets 82 on base 81. FIGS. 13 and 14 also show a

11

clamp **86** which secures the lock in place by clamping the lock over a working surface, such as a table top **85**.

A better view of this is the side edge view of FIG. **14**. Clamp **86** slips over the edge of work surface **85**. Locking bar **84** is captive in left bracket of computer or other personal electronic device lock **80**, but it can swing out to permit access of computer or other personal electronic device display. The distal end **88** is grooved to accommodate a key lock to secure the computer or other personal electronic device as well as lock **80** to base **81**. The long neck portion of base **81** from clamp **86** to brackets **82** positions the computer or other personal electronic device at a convenient distance from the front edge of table working surface **85**. The detail of clamp **86** in FIG. **13A** shows how screw **92** with optional security head **91** is screwed into the bottom surface of table working surface **85** via pointed end **93**.

FIG. **13B** shows how tang **97** prevents screw **91** from being loosened when lock **95** is locked via key **96**. Lock **95** can be easily removed from hole **94** in lock bracket **90**. When tang **97** is turned to position **98**, screw head **91** is not obstructed so that it can be removed or tightened.

FIG. **15** is a top plan view showing details of notebook computer or other personal electronic device lock **80** locked to base **81** with a computer or other personal electronic device display shown in dashed lines in position **117** and keyboard shown in dashed lines in position **118**. Power supply box **100** can pivot open in the direction of arrow **101** on shaft **102** with a retaining cap; it is locked via tang **112**. Notebook computer or other personal electronic device lock **80** is slid into a captive position within brackets **82** retaining the edges of base plates **87** in the direction of arrow **104**. The left end of swinging locking bar **84** (which can swing out in the direction of arrow **103**) is retained via retaining cap **105** within slotted hole **115** and an oversize hole on front of the left bracket. Key lock **110** grasps rod end **88** of swinging locking bar **84**, which maintains the security of the assemblage via bracket tang **114**, which is part of locking base **81**. Key **111** can be used to remove the lock body from the end of swinging locking bar **84**.

While FIG. **13-15** shows a separate over the table locking base **81** used with a notebook computer or other personal electronic device lock **80** which slides in from the left so that base pads **87** are retained by brackets **82** on base **81** of notebook computer or other personal electronic device lock **80**, it is contemplated that a further alternate embodiment includes attaching notebook computer or other personal electronic device lock **80** directly to a work surface **85**, such as a study desk, by providing fastener receptacles within base pads **87**, wherein fasteners, such as screws or bolts fasten base **81** directly to an upper side of the work surface **85**, without the use of over the table base **81**.

FIG. **16** shows another embodiment of a notebook computer or other personal electronic device lock **130** with a telescoping width adjusting feature to accommodate computer or other personal electronic devices of varying widths more securely. Base pads **136** are compatible with the use of locking base **81** of the previous embodiment to retain this continuous adjustment feature. Locking bar portions **137** and **138** are adjustable in size.

For example, as in FIG. **17**, incrementally spaced detents or pins and holes may be used to facilitate width adjustment.

Alternatively, as in FIG. **16**, locking bar **137** may be hollow and threaded with a coarse thread; it is captive within left bracket **134** and slotted back hole **133**. Right section of locking bar **138** is screwed into portion **137** and can be quickly length adjusted by twisting it clockwise or counter-clockwise. Horizontal section **131** fits into section **132** in a tele-

12

scoping fashion. After the notebook or laptop computer or other personal electronic device display is placed between the spread-apart brackets, the brackets are pushed against its sides and swinging locking bar portions **137** and **138** are adjusted accordingly to fit into holes in right bracket **135** for locking.

FIG. **17** shows a different width adjustable computer or other personal electronic device lock **170** with a discrete locking mechanism including pivoted flange **178** with peg **176** at its distal end. Flange **178** is pivoted on pivot **182**, such as a rivet, attached to outer telescoping member **132** of notebook computer or other personal electronic device lock **170**. When swung in the direction of arrow **179**, flange **178** will force peg **176** through hole **175** in telescoping section **132** and further into one of the holes **180** in inner telescoping member **171** when in positional registration. Flange **178** is locked in position when hole **185** is in positional registration with hole **184** and locking bar **173** end **139** is passed through both. The swinging locking bar includes hollow side section **172** and inner, preferably solid, side section **173**, which is telescopic within outer hollow side section **172**.

FIG. **18** shows another embodiment **150** of this invention wherein the locking base has been integrated with the notebook computer or other personal electronic device lock. Clamp **153** locks onto work surface **85** as described in a previous embodiment with a separate locking base **81** (see FIGS. **13-14**). Upright brackets **151** and **152** with bar **83** between capture the notebook computer or other personal electronic device display which is then locked via swinging locking bar **84** and a key lock (not shown).

A related embodiment in FIG. **19** shows integrated base/computer or other personal electronic device lock **160** which has one or more pivot points **164** and **166** (on base part **167**). Link **165** now pivots in relation to clamp section **163** such that the notebook computer or other personal electronic device lock **160** can be more conveniently positioned on work surface **85**.

In FIG. **19**, for example, clamp **163** is placed on the edge to the side of computer or other personal electronic device lock base **167** instead of directly in front of it as would be necessary in the embodiment of FIG. **18**.

The preferred low profile locking base embodiment of this invention for consumer use is detailed in FIGS. **20-27**.

FIG. **20** shows a low profile locking base **200** with narrow base **202** and low rise back **201**. It is screwed to work surface **285** via fasteners, such as screws **203**. Locking bar **284** with optional rubber or elastomer grommets **205** and machined end **288** is used to lock the display of a notebook or laptop computer or other personal electronic device (not shown) to locking base **200**. End **288** is passed through hole **204** and locked with pin lock **110**. Key **111** is used to unlock and remove the computer or other personal electronic device.

The preferred simpler method of use of a locking base is not to screw it down as shown in FIG. **20** but instead to create a portable locking kit by adding a clamp **211** and cable **210** as shown in FIG. **21**.

Due to the low profile design with a narrow base, all components of the portable kit conveniently fit into a tubular carrying case (not shown).

FIG. **21** also shows Clamp **211** having a fastener, such as a screw subassembly, including screw **212** and short container, such as a cylinder **216**, with transverse cable attachment hole **213**. At the first end of cable **210** is a ferrule **215** with a transverse hole. This fits through hole **213**. The cable is threaded through hole **213** after clamp **211** is secured using

13

the appropriate tool to tighten screw **212**. The distal end of cable **210** has ferrule **214** with enlarged end which does not fit through hole **213**.

FIG. **22** shows the arrangement more clearly. It is noted that cylinder **216** has distal hole **220** which accommodates the screw head and also has a screw clearance hole **221** on its top surface. After cable **210** is threaded through hole **213**, a tool cannot reach screw head **222** to loosen clamp **211** since access is denied through distal hole **220**. After cable **210** is installed through cylinder **216**, the end **288** of locking bar **284** is passed through the transverse hole in ferrule **215** prior to locking bar **284** to base **200**.

In an alternate embodiment of the clamp screw subassembly no tool is required to tighten or loosen clamp **211**.

For example, an exploded view of subassembly **230** is shown in FIG. **23** with end cap **231** pushed down over clamp screw **233** and press fit into the end of knob **235**. Optional pins **238** can be driven radially to insure positive attachment. Cap **231** has screw clearance hole **232** at its center. Screw **233** becomes captive as a subassembly with tall head **234** within knob **235** once cap **231** is attached. Offset transverse hole **237** in knob **235** goes through both walls and is sized for cable attachment.

FIG. **24** shows the underside of cap **231** revealing hexagonal recess **240** sized to engage bolt head **234**.

FIG. **25** is a top view of subassembly **230**. In the side cross-section of FIG. **26**, bolt head **234** is seated in recess **240** of cap **231**. This is prior to the insertion of cable **210** through holes **237**. Clamp **211** can be tightened in this depicted configuration by turning knob **235** since recess **240** acts as a socket wrench to bolt **233**. It is noted also that the size of head **234** interferes with the placement of hole **237** thereby preventing insertion of cable **210** while head **234** is seated in recess **240**.

If knob **235** is pushed up as shown in FIG. **27**, cable **210** can now be easily inserted through holes **237** adjacent to screw **233** and spacing head **234** away from recess **240**. In this configuration with cable **210** installed through knob **235**, if turned, knob **235** will spin freely regardless of the up or down forces exerted. Clamp **211** can only be removed after cable **210** is removed and head **234** is re-seated in recess **240**. In lieu of a non-standard screw **233** with tall head **234**, a standard hex screw can be used with a nut screwed up against the head and adhesively bonded as a unit. A washer between the nut and the screw head would only enhance the operation creating a more positive barrier with cable **210**.

In an alternate protruding member locking embodiment of this invention, spikes, security rods or strips are used to secure a personal electronic device, such as a notebook computer, cell phone, personal digital assistant (PDA) or electronic music and/or video player (i.e. iPod®).

For example, in FIG. **28**, a notebook computer or other personal electronic device with base **275** and display **276** is shown. One of the three through-holes is required for this embodiment. Hole **278** is at the hinge line, while hole **279** is through the display housing; hole **277** is diagonally through one of the front or rear corners of the base.

In the alternate locking embodiment shown in FIG. **28A**, a notebook computer **500** has a through hole **503** in the display portion which aligns in positional register with through hole **504** in the base or keyboard portion **502** when in the closed position. A protruding lock, such as, for example, padlock **505** with elongated hasp **506**, is used to prevent display portion **501** from being opened in a usable position. In addition, if a secure cable with a loop on its distal end is in the vicinity, this loop can also be engaged by hasp **506** thereby securing computer **500** to fixed location. Other protruding locks, such

14

as spikes, security rods or strips, can also be used to lock display portion **501** with keyboard portion **502** when in the closed position.

FIGS. **28B-D** illustrate yet another locking embodiment for notebook computer **515** with display **516** which has a security hole **517** in the upper right corner of display portion **516**. Hole **517** is a through hole. FIGS. **28C** and **28D** illustrate how the apparatus of FIG. **29** (without spike **285**) is used to secure computer **515**. Ferrule **286** is passed through hole **517** and locked by pin lock **110**. In this manner cable **210** attaches computer **515** to secure table top clamp **211** or to another securing member, such as a table leg of the work surface upon which notebook computer **500** is placed.

It is further noted that ferrule **286** can also be used to lock notebook computer **500** in place in the closed position as in FIG. **28A**, or the hasp **506** of FIG. **28A** can also be used to lock the display portion **516** of notebook computer **500** instead of ferrule **286** and pin lock **110** shown in FIG. **28C**.

FIG. **29** shows locking rod or spike **285** which is inserted in any of the three hole locations discussed. Ferrule **286** with a groove near its distal end is then inserted through the transverse hole of spike **285** and locked with pin lock **110**. Ferrule **286** is securely attached to cable **210** which had been passed through knob **235** after clamp **211** had been tightened at the edge of a table or desk top. In this manner, the illustrated notebook computer or other personal electronic device is secured via a secure cable.

In a variation of this embodiment, the separate spike **285** is replaced by a captive security rod **291** as shown in FIG. **30**. Note that rod **291** may be attached either to one end of the hinge or alternatively to the top surface of the base of computer or other personal electronic device **290** at any convenient location where space permits. Rods **291** are stored in a recessed position with only a small knob protruding so that they may be easily grasped to unlock into the extended position to expose a transverse hole. Ferrule **286** and lock **110** are then used in the same manner as with the separate spike **285**.

In another spike variation shown in FIG. **31**, long spike **296** is used to secure computer or other personal electronic device **294** which has a hole **295** through its base. Hole **295** is placed over pre-existing hole **298** through table top **293**; then spike **296** is inserted such that transverse hole **297** is accessible beneath table top **293**. Then transverse pin **299** with a groove adjacent its distal end is inserted through hole **297** and locked with pin lock **110**. Thus this variation locks a notebook computer or other personal electronic device using a spike without the aid of a cable.

In another embodiment shown in FIG. **32** with a flexible locking strip **301**, a detail of notebook computer **304** with display **305** and keyboard portion **306** is shown adjacent to clamp **302**. Flexible locking strip **301** is shown prior to insertion through the hinge gap between display **305** and keyboard **306** (not shown) and further between bottom jaw **314** and top movable jaw **312** of clamp **302**.

In lieu of being inserted within a hinge gap, flexible locking strip **301** may be inserted within a thin, longitudinally extending slot, similar to holes **277**, **278**, **279** for rod **285** of FIG. **29**.

FIGS. **33**, **36** and **37** show other features of clamp **302** with movable top **311** and stationary base **313**. Locking strip **301** is clearly shown in top view and side view in FIGS. **34** and **35** respectively. Wedge stop **325** is shown at one the proximal end with narrow rectangular strip **326** at the distal end. Wedge stop **325** is preferably plastic which is bonded to strip **326** as by overmolding. It is noted that base portion **313** of clamp **302** is typically screwed to work surface **303** via screws **322**, however, alternatively security cable **320** with secured distal end (not shown) can be used.

15

Gripping means, such as serrations 337 in FIG. 36, form lower static jaw 314 of FIGS. 32 and 33; they engage strip 301. Hole 336 is used for optional cable 320. Holes 322a accommodate fasteners 322, such as screws. Rectangular holes 335 accept tabs 339 of upper movable jaw 311 to form a hinge. The vertical wall 313a of base 313 can be alternatively joined to movable section 311 via ordinary hinges.

As in FIGS. 38 and 39, spring 319 tends to keep jaws 312 and 314 slightly apart unless lock 317 is locked via key 318. In that case if key 318 is rotated while moving member 311 is pressed down, lock tang 331 will engage lock recess 316 at the distal end of spring 319; recess 316 is attached to base 313. This action will lock locking strip 301 between jaws 312 and 314. Note that lock 317 is attached to hinged part 311 via a fastener, such as lock nut 330.

FIGS. 40-43 show notebook computer 304, cellular phone 346, PDA 347 and personal DVD player 348 each with hinge gap 345. In addition, the entry path of locking strip 301 is shown by arrows in FIG. 40.

FIG. 40 also shows a further alternate embodiment whereby the housing of notebook computer 304 contains a slot 326 for insertion of a flexible or rigid locking strip 328 therethrough.

FIGS. 44-47 relate to an alternate embodiment of clamp 355 which incorporates a leaf spring 358 to impart locking force to locking strip 301 when shackle 366 of padlock 365 is passed through lock loops 362 and handle loop 376 (as in FIG. 46). In this embodiment, shallow recess 359 with transverse serrations aggressively grasps strip end 326 under bending force of spring 358, which itself can have optional transverse serrations on its contact surface.

When handle 357 is free to swing up, strip end 326 can be easily passed between brackets 371 which are spaced apart a distance "W" (as in FIG. 45) to accommodate the width of strip end 326. Base 356 is secured to work surface 303 via fasteners, such as screws 369, which are passed through countersink holes 367 (as in FIG. 45). Leaf spring 358 is swaged or brazed at region 363 within slot 373 of handle 357. Hole 375 in loop 376 accommodates shackle 366. It is noted that spring 358 has to be bent somewhat for handle 357 to be in registration with the holes in padlock brackets 362. This bending also permits clamp 355 to accommodate strip ends 326 of varying thicknesses. Also, with respect to the geometry of spring 358 in FIG. 44, if a pulling force is placed on locking strip 301, frictional forces will tend to rotate the free end of spring 358 in a counter-clockwise direction thereby increasing clamping force on strip end 326; this further counteracts the pull-out force. Since spring 358 is wider than handle 357 (as in FIG. 47), centering washers 377 are used on either side of it to increase the combined width to X which is just slightly smaller than W. Rivet 360 in brackets 361 acts as an axle for handle 357; hole 372 is a clearance fit for rivet 360.

FIG. 48 illustrates alternate embodiment locking strip 390 with locking wedge 391, strip 393 and end hole 392. Locking strip 390 may be rigid or flexible.

Dashed lines 305 of FIG. 48 show the position of a computer display if this is being secured. Added hole 392 permits at least three non-clamp locking methods to be used. These are illustrated in FIGS. 49-51; for clarity, no item is shown being locked in these FIGS. 49-51.

It is understood that instead of being inserted through a hinge gap, locking strip 390 may be first passed through a thin, longitudinally extending slot in the housing of the personal electronic device, such as a notebook computer, instead of a round hole provided for a rod 285 or 296, as is shown in FIGS. 29-31. In this case, the thinness of the slot 327 for strip 328 minimizes any intrusion into the interior of the walls of

16

the personal electronic device, such as a notebook computer 305 and the like, with its intricate wiring located in a tight space within the walls of the notebook computer 305, or other personal electronic device.

The strip 390 may be a rigid rectangle or other geometric shape. Additionally strip 390 may be flexible. If flexible, strip 390 may pass through a slot in the housing of the personal electronic device, or if the device is hinged, through a hinge gap between the display of the device and the main body of the device being secured.

In FIG. 49, stud 395 is attached to and protrudes from work surface 303. Hole 392 is simply passed over the distal end of stud 395 and then the shackle of padlock 397 is passed through the transverse hole in stud 395 to lock strip 390.

In FIG. 50, secure cable 400 with collar 402 and a rigid stud at its distal end is used to secure strip 390. After the rigid stud is passed through hole 392, cable lock 401 is snapped over the end of the stud thereby securing strip 390.

In FIG. 51, free cable 405 with lock member 406 permanently attached is passed through hole 392. Since member 406 is a bulge larger than the diameter of hole 392, locking strip 390 will be secured when the distal end of cable 405 is looped or otherwise secured to work surface 303 or to some point adjacent to it.

The plunger type security lock will now be described with reference to FIGS. 52, 53, 54A, 54B, 55A, 55B, 56, 57, 58A and 58B.

FIG. 52 depicts a perspective view of a plunger-type security lock 500 of the invention. While security lock 500 is designed for use with electronic devices such as notebook computers and like devices, e.g., those with a base connected by a hinge to an upper section typically comprising a display device, the invention is not limited thereto. The invention is not limited to what is to be locked or secured, but only that the object to be locked or secured have a hinge or through hole through which a flexible locking strip may pass to its stopping means (e.g., wedge), which is then hooked or captured by the end of the sliding key of the security lock, as will now be described in detail.

Plunger-type security lock 500 includes a cylindrical sliding key receptacle 502, shown in the perspective views of FIGS. 55A and 55B. The cylindrical sliding key receptacle comprises a slotted, first cylindrical portion 504 and a second cylindrical portion 506. The slotted, first cylindrical portion 504 includes a first end formed with a slot 508 extending longitudinally through to its other end, and opening into the second cylindrical portion. The second cylindrical portion is formed as an open cylindrical cavity 510 that is contiguous with the first cylindrical portion's open slot 508.

A locking member 512 (for example, a ferrule) is arranged on an outer cylindrical surface of the second cylindrical portion 504 of the sliding key receptacle 502 that is configured for attachment to a cable 513. The cable is then attached to a stationary object such as a post, pillar, heavy desk, or other fixture that is substantially immobile.

A cylindrical plunger 516, having a pushing end 518 and a cylindrical plunger end 520, is configured for insertion into the second cylindrical portion of the sliding key receptacle 502. A sliding key 522, comprising a flat, longitudinal member constructed with a rectangular cross-section that includes a hooking end 524 and a plunger-contact end 526, which sliding key is configured with a key definition (see rectangular cut out teeth) and for slidable spring-loaded operation within (slot 508) the slotted, first cylindrical portion 504 in cooperation with the cylindrical plunger 516 and spring 528 in order to extend and hook a flexible locking strip and retract with and lock the locking strip 514 in locking state.

17

A locking mechanism **530** defines the locking state in cooperation with the key definition. Locking mechanism **30** comprises a plurality of number dials **532** (four in the embodiment shown) arranged about an outer surface of the slotted, first cylindrical portion **508** to prevent the extending of the sliding key **522** when arranged in the locking state and to allow extending of the sliding key when in an unlock state. The locking state and unlock state are correlated to a numerical setting of the number dials in cooperation with the key definition. Spring washers (not shown in the drawing) are included to maintain the number dials, as well as a finger grip flange **534** (not shown in the FIG. **51** embodiment).

The locking member **512** or ferrule preferably comprises a cable for tethering the security lock to an anchoring means, such as a desk or stanchion, without limitation. The locking strip **514** for which the hooking end **526** of the sliding key **522** is configured to hook when extending from the sliding key receptacle **502** is configured with a blocking end **515**, and to slide through an electronic device (**304**; FIG. **40**), i.e., via a through opening, up to the blocking end. For example, a through opening may comprise a hinge gap between two parts. The blocking end may be formed as a wedge. In this way, the electronic device is secured to the plunger-type security lock (**500**) when in a locking state.

A bezel **540** is arranged about an outside diameter of the open end of the slotted, first cylindrical portion **504** of the sliding key receptacle **502**, through which a portion of the longitudinal member of the sliding key **522** extends and retracts. Spring **528** is positioned to cooperate with the sliding key **522**, the sliding key receptacle **502** and the plunger **516** to provide the spring loaded sliding key movement in cooperation with locking mechanism **530**.

In another embodiment, the invention comprises an electronic device with security locking system. The electronic device **305** is required to have a through slot, such as a hinge gap (FIG. **40**). A flexible locking strip **514** includes an insertion end **517** and a stopping end **515**, configured for insertion partially through the through slot or hinge gap up to the stopping end **515**. A plunger-type security lock (**500**) comprising a cylindrical sliding key receptacle **502** with a slotted, first cylindrical portion **504** and a second cylindrical portion **506**, a locking member **512** arranged on an outer cylindrical surface of the second cylindrical portion **506** of the sliding key receptacle **502** is configured for attachment to a tether means (i.e., cable, chain, etc.) **513**, a cylindrical plunger **516**, a sliding key **522** including a hooking end **526** and a plunger-contact end **524** that is configured with a key definition (cut out teeth) and for slidable spring-loaded operation within the slotted, first cylindrical portion **504** in cooperation with the cylindrical plunger **516** to extend and hook the flexible locking strip **514** and to retract with and lock the locking strip **514** in locking state and a locking mechanism **530** that defines the locking state in cooperation with the key definition.

In another embodiment, the invention includes a locking assembly for a notebook computer or other personal electronic device having a visual display portion attached to a keyboard base portion by a hinge. The assembly includes a notebook computer or other personal electronic device with visual display portion separated from a keyboard base portion by a hinge. A flexible locking strip including an insertion end and a stopping end, configured for insertion partially through the hinge up to the stopping end.

A plunger-type security lock **500** comprising a slotted, cylindrical sliding key receptacle **502**, a locking member **512** or ferrule is arranged on an outer cylindrical surface of sliding key receptacle **502** and is preferably attached to a tether means (e.g., cable or chain) **513**. A cylindrical plunger **516** is

18

included, as well as a sliding key **522** formed to include a hooking end **526** and a plunger-contact end **524**. The sliding key is configured with a key definition to capture the numbers dialed in via the locking mechanism. A spring **528** is included to provide for spring loaded sliding key cooperation with the plunger and locking mechanism **530** within the slotted, cylindrical sliding key receptacle to extend and hook the flexible locking strip **514** and to retract with and lock the locking strip **514** in locking state.

In the preferred embodiment shown in FIGS. **59-65**, the security apparatus of this invention is designed to engage diagonal corners of an electronic tablet (such as an iPad®).

FIG. **59** shows apparatus **600** engaged with tablet **601** and securely locked to it via combination pin lock **607**, such as, for example, plunger lock **500** of FIGS. **52-58**. Distal corner pocket **606** engages one corner while proximal lockable corner pocket **608** assembly engages the diagonally opposite corner of tablet **601**.

FIG. **60** is a close-up detail view showing the engagement of pin lock **607**. Cable **609**, which is attached to lock **607** is used secure tablet **601** by engaging one corner thereof within proximal lockable corner pocket **608**.

Security apparatus **600** is more clearly shown in FIG. **61** which now reveals flat metal chassis bar **604** connecting distal pocket **606** to proximal pocket assembly **608**. Note stud **611** attached to lock **607**; it is permanently secured to cable **609**.

FIGS. **62** and **63** show proximal locking pocket assembly **608** in the closed and open positions respectively. Note that base **610** extends from the attachment portion to chassis bar **604** to the flanges at the proximal end on the other side of the integral hinge pin housing **618**. Pocket **612** flips up (see FIG. **63**) to permit a corner of tablet **601** to be inserted or disengaged. The hingable tail section **614** fits between flange protrusions of base **610**; when it is co-planar with base **610** (see FIG. **62**), the slot of pin lock **607** can be fit over the end and locked by its pin engaging hole **616**. This completes the locking procedure.

Although purpose-sized security apparatus **600** of this invention can be provided for the most popular tablets or similar devices on the market, an adjustable single unit can also be configured. In one embodiment, the adjustability feature is formed by permitting metal chassis bar **624** in FIG. **64** to slide through a slot in a modified distal pocket **628**. An array of holes **626** in chassis **624** provides the adjustability by virtue of a friction fit removable locking pin **630** with a large flat head. The pin cannot be taken out once tablet **601** is engaged, but it is simply lifted up for adjustment to permit pocket **628** to slide on bar **624**.

Another adjustable embodiment **640** shown in FIG. **65** uses a two-part telescoping metal chassis bar consisting of hollow proximal portion **646** and solid distal portion **642** which fits inside. An array of holes **644** provides adjustability by virtue of friction fit pin **648** with a large flat head. Again, this pin is locked once tablet **601** is installed. This embodiment is more compact for smaller tablets or like items since there is no distal metal bar extending beyond the distal engagement pocket as in embodiment of FIG. **64**.

Please note that features of the above described locking assembly for securing a portable electronic device having at least one housing to a substantially immovable object, the locking assembly for securing a portable electronic device having a housing to a substantially immovable object and the method for securing a portable electronic device having a housing to a substantially immovable object utilizing a locking assembly are supported by the written description and drawing figures as filed. For example, the captive security rod and locking device find support in rod **291** and pin lock **100** of

19

FIGS. 29 and 30, and the security rod or spike and cable with first end formed with a ferrule having a locking groove of FIG. 21 finds support in spike 285 and cable 210 of FIG. 29, and text describing same.

In the foregoing description, certain terms and visual depictions are used to illustrate the preferred embodiment. However, no unnecessary limitations are to be construed by the terms used or illustrations depicted, beyond what is shown in the prior art, since the terms and illustrations are exemplary only, and are not meant to limit the scope of the present invention.

It is further known that other modifications may be made to the present invention, without departing the scope of the invention.

What is claimed is:

1. A locking assembly for securing a portable electronic device having at least one housing to a substantially immovable object, the locking assembly comprising:

a captive security rod having a locking end and an anchoring end, wherein the anchoring end is installed in the at least one housing to anchor the captive security rod thereto;

said captive security rod being captive partially in said at least one housing after installation and partially out of said at least one housing during and before locking use after installation; and,

a locking device with a locking mechanism, wherein the locking device is configured with an opening to receive the locking end of the captive security rod to activate the locking mechanism, where the activation causes the locking mechanism to securely grasp the locking end and thereby lock the installed security rod and portable electronic device to the locking device.

2. The locking assembly as set forth in claim 1, further comprising means for securing the locking device and, therefore, the captive security rod and portable electronic device to which the captive security rod is anchored, to a substantially non-movable object.

3. The locking assembly as set forth in claim 2, wherein the means for securing is a cable or lanyard.

4. The locking assembly as set forth in claim 3, wherein the cable or lanyard is permanently attached to the locking device.

5. The locking assembly as set forth in claim 1, wherein the locking end of the captive security rod comprises a knob that extends from the at least one housing after the anchoring end anchors the captive security rod thereto.

6. The locking assembly as set forth in claim 5, wherein said knob is captured and held by the locking mechanism at locking actuation.

7. The locking assembly as set forth in claim 1, wherein said portable electronic device comprises any of the group consisting of a laptop computer, a notebook computer, and tablet computer, a cell phone, a camera, a Smartphone, a music storage and a playback device.

8. The locking assembly as set forth in claim 1, wherein said portable electronic device comprises a first housing, a second housing and a hinge, wherein said hinge separates and allows said first housing to be closed upon said second housing and wherein said captive security rod is deployed to extend and protrude from any surface of said first housing or said second housing.

9. The locking assembly as set forth in claim 8, wherein said second housing is a keyboard part and said captive security rod is inserted through and anchored, and operates to extend in a deployed position out of a surface of said second housing.

20

10. The locking assembly as set forth in claim 1, wherein the substantially immovable object is a base plate.

11. The locking assembly as set forth in claim 2, wherein the cable or lanyard has a loop opposite its end permanently attached to the locking device through which the locking device is passed after the cable is wrapped around the substantially immovable object whereinafter the locking device is lockingly attached to the captive security rod and, therefore, the portable electronic device to which the captive security rod is anchored.

12. The locking assembly as set forth in claim 1, wherein the locking device is a pin lock.

13. The locking assembly as set forth in claim 1, wherein the locking device is a plunger-type security lock.

14. A locking assembly for securing a portable electronic device having at least one housing to a substantially immovable object, the locking assembly comprising:

a captive security rod or spike having a locking end and an anchoring end, said anchoring end of said captive security rod or spike configured for installing to the at least one housing by anchoring to the portable electronic device through the at least one housing;

a locking device having a lock opening to a locking mechanism, said locking device configured to lock to said captive security rod or spike upon insertion of the locking end of said installed security rod or spike into said lock opening to actuate said locking mechanism, therein locking said locking device to said captive security rod or spike; and,

a cable attached to said locking device and configured for fastening to the substantially immovable object prior to locking said locking device to said installed captive security rod or spike,

wherein said locking end of said installed captive security rod or spike comprises a small knob axially located on a distal end of said captive security rod or spike, wherein said installed captive security rod or spike is positioned in a recess in the at least one housing during non-use, and said small knob protrudes from the at least one housing during non-use.

15. The locking assembly as set forth in claim 14, wherein said locking end of said captive security rod or spike comprises a knob that extends from the at least one housing after the anchoring end anchors said captive security rod or spike thereto.

16. The locking assembly as set forth in claim 15, wherein the small knob that is captured and held by the locking mechanism at locking actuation.

17. The locking assembly as set forth in claim 14, wherein said portable electronic device comprises any of the group consisting of a laptop computer, a notebook computer, and tablet computer, a cell phone, a camera, a Smartphone, a music storage and a playback device.

18. The locking assembly as set forth in claim 14, wherein said portable electronic device comprises a first housing, a second housing and a hinge, wherein said hinge separates and allows said first housing to be closed upon said second housing and wherein said captive security rod is deployed to extend and protrude from any surface of said first housing or said second housing.

19. The locking assembly as set forth in claim 18, wherein said second housing is a keyboard part and said captive security rod is inserted through and anchored, and operates to extend in a deployed position out of a surface of said second housing.

20. A method for securing a portable electronic device having a housing to a substantially immovable object utiliz-

21

ing a locking assembly, the locking assembly comprising a security rod or spike formed with an anchoring end separated axially by a protruding end, a locking device with an internal locking mechanism and a cable permanently attached to the locking device at one end, the method comprising acts of: 5
securely installing the anchoring end of the security rod or spike to the portable electronic device in the housing;
attaching an other end of the cable to the substantially immovable object; and
inserting the locking end of the security rod or spike into an 10
opening in the locking device to actuate the internal locking mechanism and lock the locking device to the captive security rod or spike and, therefore, the portable electronic device to which it is anchored, to the substantially immovable object. 15

* * * * *

22