

Macintosh PowerBook 540: Technical Specifications

Last Modified: October 13, 2008

Article : SP162



Macintosh PowerBook 540

Logic Board		Ports		Power	
Processor:	68LC040, 66	USB:		Max Watts: 40	
PMMU:	integrated	ADB: 1		Amps: 1.015	
FPU:	none	Video: mini-15		BTU per Hr: 136.8	
Data Path:	32, 33	Floppy: none		Voltage: 100-240	
L1 Cache:	8K	SCSI: HDI-30		Freq Range: 50-60 Hz	
L2 Cache:	none	Geoports:		Battery Type: PB500, NiMH	
2nd Processor:	none	Ethernet: AAUI-15		Soft Power: yes	
Slots:	modem	FireWire:			
		Mic Type: Line in			
		AirPort Ready:			
		Other Ports: Printer Speaker ,			
Memory		Video Memory			
Logic Board:	4 MB	Resolution	Video Memory built-in LCD screen (built in)	Video Memory 512K VRAM (ext. only) (built in)	
RAM Slots:	1, PB5xx	512 x 384	n/a-bit	8-bit	
Min - Max RAM:	4 MB - 36 MB	640 x 400	n/a-bit	n/a-bit	
Min RAM Speed:	70	640 x 480	8-bit	8-bit	
RAM Sizes:	4, 8, 12, 20, 32 MB	800 x 600	n/a-bit	8-bit	
Install in Groups of:	1	832 x 624	n/a-bit	8-bit	
		1024 x 768	n/a-bit	n/a-bit	
		1152 x 870	n/a-bit	n/a-bit	
		1280 x 1024	n/a-bit	n/a-bit	
		Notes: At 8-bit setting, the 540◆s LCD screen will display up to 64 grays.			
Physical		Software		Storage	
Introduced:	5/16/1994	Addressing Modes:	32-bit	Floppy Size: 1.44MB	
Discontinued:	10/17/1994	Orig SSW:	7.1.1	Floppy Inject: manual	
Form Factor:	PowerBook 520	Orig Enabler:	PowerBook 500 Series Enabler	Min. Int HD Size: 240MB	
Gestalt ID:	72	ROM ID:	n/a	Int HD Interface: SCSI	
Weight (lbs):	7.1	ROM Ver:	n/a	Orig CD Speed n/a	
Dimensions (in):	2.3 H x 11.5 W x 9.7 D	ROM Size:	2MB	Int CD Support:	
		AppleTalk Ver:	57.0.4		
		Mac OS Supported:	7.1.1 7.5 7.5.1 7.5.3 7.5.5 7.6 7.6.1 8.0 8.1		