

# **High-Value Grain Deserves A High-Quality Ride**

**Durability, Performance And Convenience From The High** \*\* Line\*





Some producers think all gravity wagons are just alike; high-capacity Unverferth gravity wagons, however, are much, much more. We design and build them with the Innovative design and Quality manufacturing characteristics of performance, durability and convenience you expect with all Unverferth products.

\* Innovative design • Quality manufacturing



# **High-Value Grain Deserves A High-Quality Ride**

**Durability, Performance And Convenience From The High** \*\* Line\*





Your grain may not know the difference, but you will. Your Unverferth Grain Wagon will still be making trips to town when the others aren't good for much except temporary storage. Only Unverferth Grain Wagons are designed and built with the Innovative design and Quality manufacturing characteristics of performance, durability and convenience.

\* Innovative design • Quality manufacturing

- Front, side and rear windows and a front-mounted ladder for load viewing are standard equipment; a rear-mounted ladder is optional
- Flashing amber and red taillights plus front and rear industry-standard, seven-pin electrical receptacles for convenient linking of tandem units are standard equipment for enhanced transport safety
- Wiring is wrapped with a mesh coating and routed through protective conduit for increased life
- Locating the shock-absorbing brake actuator at the rear of the tongue provides for improved braking control and a spring-lift-assist makes hitching easy
- Left-side unloading is standard; right-side unloading is optional
- Front and rear built-in attachments for optional safety chains increase transport safety





For complete details about the entire line of Unverferth gravity wagons, see your Unverferth dealer today or call 1-800-322-6301.

#### **UNVERFERTH GRAIN WAGONS\***

MODEL	630*	530	430
Capacity**	625 bushels	550 bushels	450 bushels
Length	16'9"	15'7"	14'3"
Width	9'	9'	8'
Height	10'4"	10'	9'8"
Front/Rear Slope	37°	40°	40°
Back Slope	32°	32°	32°
Door Width	60"	60"	60"
Chute Height	1'7"	1'7"	1'7"
Unloading Time	90 sec.	80 sec.	70 sec.
Spindle Size	3.25"	3"	2.75"
Hub Size	10-bolt/11.25" BC	8-bolt/8" BC	8-bolt/8" BC
Wheel Size	13 x 22.5	13 x 22.5	13 x 22.5
Wheel Base	11'5"	10'5"	10'5"
Track Width	7'5"	7'1"	7'1"
Approximate Weight	6,760 lbs.	5,640 lbs.	5,340 lbs.

\* Please check local weight and towing restrictions when pulling in tandem.

Specifications calculated with standard tires; all measurements are approximate and can vary, depending on tire size and brand.

\*\* Capacities measured with #2 corn at 15% moisture (56 lb. per bushel test weight)

Additional facilities in California, Georgia, Idaho, Iowa, Kansas, Michigan, Oregon and Canada

®,TM Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, Ohio © 1996 Unverferth Manufacturing Co., Inc.

UC69108M15

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.



## Unverterth Manufacturing Company, Inc.

P.O. Box 357 • Kalida, Ohio 45853 (419) 532-3121 • FAX (419) 532-2468 e-mail: umwheels@bright.net

\*Innovative design — Quality manufacturing



Printed in U. S. A.

1-800-322-6301

## **Durability:**

- The one-piece unitized sidewall construction increases strength and capacity without the need for add-on sideboards. The sleek design also has fewer joints and seams that can rust
- All exposed seams are silicone-sealed for corrosion resistance
- Heavy-duty spindles and hubs provide years of dependable service
- A high-solid painting process includes a primer basecoat and choice of red or green high-gloss topcoat for a car-like finish with increased durability





#### **Performance:**

- Steep-sloped sides and graphite-coated interiors result in fast and complete unloading; up to 630 bushels in only 90 seconds
- A low center of gravity and balanced weight distribution result in true, stable towing when hitched singly or in tandem
- The unloading door's rack-and-pinion mechanism with gear reduction permits easy opening, even when fully loaded with high-moisture corn
- Unverferth's exclusive torsion-bar suspension and four-corner mounting with spring hold-down keeps the load level in the toughest terrain and minimizes bounce for smooth, quiet towing even when empty
- Rear-wheel hydraulic surge brakes on the 430 and 530 models and four-wheel brakes on the 630 are standard equipment and help ease the heaviest loads to a smooth and complete stop



Front, side and rear windows and a front-mounted ladder for load viewing are standard equipment

### **Convenience:**

- A rear electric receptacle and hitch for convenient linking of tandem units are standard equipment
- The side-unloading chute is equipped with a center-dump deflector for unloading flexibility