



U.S. UTILITY PATENT APPLICATION

DIN	O.I.P.E.	PATENT DATE NOV 1 4 2000
SCANNED.	16.00 a.A. W	190A T & WIR

SECTOR	CLASS	SUBCLASS	ART UNIT	EXAMINER
	340	606	2736	POPS
			. FILED WI	TH: DISK (CRF) FICHE

PREPARED AND APPROVED FOR ISSUE

ISSUING CLASSIFICATION .											
ORIGINA	L		CROSS REFERENCE(S)								
CLASS	SUBCLASS	CLASS	St	JBCLASS (O	NE SUBCL	ASS PER BL	оск)				
340	506	340	539	825.06	825.36	825.49					
INTERNATIONAL	CLASSIFICATION	700	17		-						
608B 29	/ 00	1									
		·									
					·						
					Continued	on Issue Slip	Inside File	Jacket			

TERMINAL		DRAWINGS		CLAIMS ALLOWED			
└─ DISCLAIMER	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.		
	8	8.	[43			
a) The term of this patent				NOTICE OF ALL	OWANCE MAILED		
subsequent to (date) has been disclaimed.	(Assistant f	Examiner)	(Date)	7-5	CD		
b) The term of this patent shall not extend beyond the expiration date							
of U.S Patent. No		DARYL POPE PRIMARY EXAMINER			ISSUE FEE		
			, lamba	Amount Due	Date Paid		
	(Permary E	xanfiner)	6/28/00 (Date)	\$ 605-00	22 0		
	10 1	~ X	~ ~ ~	ISSUE BAT	CH NUMBER		
c) The terminalmonths of this patent have been disclaimed.	(Legal Instruments Examiner) (Date)			090	7		
WARNING:							
The information disclosed herein may be res Possession outside the U.S. Patent & Trader					5, Sections 122, 181 and 368.		

Form PTO-436A (Rev. 6/98)

ISSUE FEE IN FILE

(LABEL AREA)

Formal Drawings(__shts) 594___

PATENT	A DDY TO	A PTT	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~	3.7.0	
DATEME	יזו וטטו א	ATTICAN.	CLDIAL	NI/ N	
FAILUNI.	AFFLIN	A I II /II	JEKIMI.	171	

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE FEE RECORD SHEET

06/03/1999 PSTANBAC 00000020 09317235

01 FC:201

380.00 OP

PTO-1556 (5/87) *Ú.S. GPO: 1998-433-214/80404

SERIAL NUMBER	FILING DATE	CLASS	GROUP ART SANT	ี สรายสั พธิบ อะ	POKET NO.
09/317,235	05/24/99	340	2736	225.03	orte orte
DAVID SANDELMAN, C	HATHAM, NJ; DANI	IEL SHPRECHER, I	HIGHLAND LAKES	3, NJ.	
and the second second					
**CONTINUING DOMES					
VERIFIED PROVISI	ONAL APPLICATION	NO. 60/115,305	01/09/99	•	
1).//-					
371 (NAT'L STAGE) DATA*****	****			
VERIFIED					
None II.					. **
U					
					1.
· · · · · · · · · · · · · · · · · · ·					*
FOREIGN APPLICAT VERIFIED	TOMS******				
DI /	4				
1.1.	•				•
			•		
			•	3	
IF REQUIRED, FOREI	GN FILING LICENS	SE GRANTED 06/1	5/99 ** SMALI	ENTITY **	
eign Priority claimed USC 119 (a-d) conditions me	//		OR SHEETS	TOTAL	NDEPENDE
rified and Acknowledged	Dyl. Dyl. Dyles Blue Diviser and	er Allowance COUNTR NJ	Y DRAWING 8	CLAIMS 50	CLATIVE 2
Exam	iner's initials ini	tials		1	<u> </u>
BARRY E NEGRIN LEVINSOHN LERNER	BERGER AND LANGS	MAE			ا از آن این این این این این این این این این ای
SUITE 2400			•		1
757 THIRD AVENUE NEW YORK NY 10017	r de la companya de La companya de la co		•	ĺ	
				//	»
ELECTRONIC MESSAG EQUIPMENT AND MET		EM UTILIZABLE II	N THE MONITOR	ING OF	
REMOTE			•		
FILING FEE RECEIVED			☐ All Fee		
FEES: A	uthority has been gi	iven in Paper lit DEPOSIT ACCOU	1.16 F	ခုခ်နှာ (Filing)	
\$650 NO.		e following:		ees (Processing ees (Issue)	g E va of time
			Other		and the second of the second o
			☐ Credit		_ , \

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. 1216.034

Total Pages in this Submission

TO THE ASSISTANT COMMISSIONER FOR PATENTS **Box Patent Application**

PTO Washington, D.C. 20231 Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent applicatio ${f 0}$

invent	ion er	ntitled	l:							
1							ABLE IN THI	E MONITORING		
OF	EQU	IPME	INT ANI	METHOD O	F SA	ME				
Ì										
		. I. I								
and in		<u>·</u>							<u>"</u>	
Dav	via sa	nuem	nan, et al						1,71,2	
								•		Jan P
If a C	ONT	NUA	TION A	PPLICATION,	ched	ck appropriate bo	ox and supply	the requisite information:	,	
	Conti	nuat	ion 🗆	Divisional		Continuation-	in-part (CIP)	of prior application No.:		
Partie.	h is a						. , ,			
1:1	Conti		ion 🗆	Divisional		Continuation-	in-nart (CIP)	of prior application No.:		
grep.				DIVISIONAL	استا	Oommaanon-	m-part (On)	or prior application No		<u> </u>
 184 3	h is a						(017)	e a a a a a a a a a a a a a a a a a a a		, *
	Conti	nuat	ion 🗀	Divisional	Ш	Continuation-	in-part (CIP)	of prior application No.:		
LT.						4				
Enclo	osed a	are:		•						
						Application	n Elements			
	\boxtimes	Filin	a fee as	calculated and	d trai	nsmitted as desc	ribed below			
			0							
1. 402.	X	Spe	cification	having		28	pages and in	ncluding the following:		
302									+	,
	a.	\boxtimes	Descrip	tive Title of the	e Inv	ention				,
	b.		Cross F	References to	Rela	ted Applications	(if applicable)			
	C.		Statem	ent Regarding	Fed	erally-sponsored	Research/De	velopment (if applicable)		
		_		·-		•		······································		
	d.	Ц	Referen	nce to Microtic	he A	ppendix (if applic	cable)			
	e.	\boxtimes	Backgr	ound of the Inv	/enti	on				
	f.	\boxtimes	Brief Su	ummary of the	Inve	ention		•		
	g.	\boxtimes	Brief De	escription of th	e Dr	awings (if drawir	ngs filed)			
	h.	\boxtimes	Detaile	d Description						
	i.	\boxtimes		s) as Classified	l Bel	ow .				
	j.		·	ct of the Disclo						
	J.		MUSURC	or the Disclo	oul e	i			*	

Page 1 of 3

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. 1216.034

Total Pages in this Submission

		Application Elements (Continued)								
3.	\boxtimes	Drawing(s) (when necessary as prescribed by 35 USC 113)								
	a.	□ Formal b. □ Informal Number of Sheets 8								
4.	\boxtimes	Oath or Declaration								
	a.	Newly executed (original or copy) □ Unexecuted								
	b.	Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional application only)								
	C.	With Power of Attorney □ Without Power of Attorney ■ Without Power of Attorney □ Without Power Of Att								
	d.	DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. 1.63(d)(2) and 1.33(b).								
15. 11 11		Incorporation By Reference (usable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.								
116. 117.		Computer Program in Microfiche								
₩ ₇ .		Genetic Sequence Submission (if applicable, all must be included)								
	a.	□ Paper Copy								
	b.	☐ Computer Readable Copy								
i.	C.	Statement Verifying Identical Paper and Computer Readable Copy								
¥Ū		Accompanying Application Parts								
8.	×	Assignment Papers (cover sheet & documents)								
9.		37 CFR 3.73(b) Statement (when there is an assignee)								
10.		English Translation Document (if applicable)								
11.		Information Disclosure Statement/PTO-1449								
12.		Preliminary Amendment								
13.	X	Acknowledgment postcard								
14.	×	Certificate of Mailing First Class X Express Mail (Specify Label No.): EL 161217675 US								

Page 2 of 3

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. 1216.034

Total Pages in this Submission

	Accompanying Application Parts (Continued)											
15.		Certified Copy of Priority Document(s) (if foreign priority is claimed)										
16.	\boxtimes											
17.		Additional Enclosures (please identify below):										
		,										
				Fee Calcula	tion and Tr	ansmittal		e gweet				
				CLAIMS A	S FILED							
	For		#Filed	#Allowed	#Extra	Rate		Fee				
Total	Claim	ıs	50	- 20 =	30	x \$9.00		\$270.00				
Indep.	Clai	ms ————	2	- 3 =	0	x \$41.00		\$0.00				
_ E . E _ ~	le De	pendent Cl	aims (check	if applicable)]			\$0.00				
LT LT						BĄ	SIC FEE	\$380.00				
322	ER FI	EE (specify	purpose)		Assign	ment		\$40.00				
						TOTAL FILI	NG FEE	\$690.00				
⊠ T	as described below. A duplicate copy of this sheet is enclosed. ☐ Charge the amount of as filing fee. ☐ Credit any overpayment. ☐ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17. ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).											
cc:					L 75 N T	Signarry E. Negrin, Reg. No. 3 EVISOHN, LERNER, BE 77 Third Avenue, Suite 24 ew York, NY 10017 el. No. 212-486-7272 ax No. 212-486-0323	37,407 RGER & L	ANGSAM				

Page 3 of 3

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Total Pages in this S

1216.034

Docket No.

TO THE ASSISTANT COMMISSIONER FOR PATENTS **Box Patent Application** Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an

nvention en	titled		
1		MESSAGE DELIVERY SYSTEM UTILIZABLE IN THE MONITORING	
OF EQUI	PME	NT AND METHOD OF SAME	
<u> </u>	· · · · · ·		
and invente			<u> </u>
David Sar	ndelm	an, et al	
If a CONTI	NUA'	TION APPLICATION, check appropriate box and supply the requisite information:	•
☐ Conti	nuati	on Divisional Continuation-in-part (CIP) of prior application No.:	
Which is a:			
☐ Conti	nuati	on Divisional Continuation-in-part (CIP) of prior application No.:	_
Which is a:			
☐ Conti		on Divisional Continuation-in-part (CIP) of prior application No.:	
- Conta	iiuati	on a bivisional a continuation-in-part (on) or prior application its	
Enclosed a	re:		•
		Application Elements	
1. 🗵	Filin	g fee as calculated and transmitted as described below	
2. 🗵	Spe	cification having 28 pages and including the following:	
	_		. •
a.	×	Descriptive Title of the Invention	
b.		Cross References to Related Applications (if applicable)	
c.		Statement Regarding Federally-sponsored Research/Development (if applicable)	
d.		Reference to Microfiche Appendix (if applicable)	
e.	\boxtimes	Background of the Invention	
f.	×	Brief Summary of the Invention	AF
	×	Brief Description of the Drawings (if drawings filed)	
g.			
	\boxtimes	Detailed Description	
i.	\boxtimes	Claim(s) as Classified Below	
j.	\boxtimes	Abstract of the Disclosure	•

Page 1 of 3

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. 1216.034

Total Pages in this Submission

3.	\boxtimes	Drawing(s) (when necessary as prescribed by 35 USC 113)
	a.	□ Formal
4.	\boxtimes	Oath or Declaration
	a.	□ Newly executed (original or copy) □ Unexecuted
	b.	Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional application only)
	C.	
	d.	DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5.		Incorporation By Reference (usable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6.		Computer Program in Microfiche
7.		Genetic Sequence Submission (if applicable, all must be included)
	a.	□ Paper Copy
	b.	□ Computer Readable Copy
	C.	Statement Verifying Identical Paper and Computer Readable Copy
		Accompanying Application Parts
8.	\boxtimes	Assignment Papers (cover sheet & documents)
9.		37 CFR 3.73(b) Statement (when there is an assignee)
10.		English Translation Document (if applicable)
11.		Information Disclosure Statement/PTO-1449 Copies of IDS Citations
12.		Preliminary Amendment
13.	\boxtimes	Acknowledgment postcard
14.	\boxtimes	Certificate of Mailing
		☐ First Class ☒ Express Mail (Specify Label No.): EL 161217675 US

Page 2 of 3

Application Elements (Continued)

Petitioner Alarm.com Exhibit 1202 1202.0008

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. 1216.034

Total Pages in this Submission

	Accompanying Application Parts (Continued)												
15.	15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)												
16.	16. Small Entity Statement(s) - Specify Number of Statements Submitted: 2												
17.	17. Additional Enclosures (please identify below):												
		,				. *	2.8						
	Fee Calculation and Transmittal												
				CLAIMS A	S FILED								
	For		#Filed	#Allowed	#Extra	Rate	Fee						
Total (Clain	าร	50	- 20 =	30	× \$9.00	\$270.00						
Indep.	Clai	ms	2	- 3 =	0	× \$41.00	\$0.00						
Multip	le De	ependeņt Cl	aims (check if	applicable) []		\$0.00						
				4		BASIC FEE	\$380.00						
ОТНЕ	ER F	EE (specify	purpose)		Assignn	nent	\$40.00						
		,				TOTAL FILING FEE	\$690.00						
⊠ T													
Dated:	Signature Barry E. Negrin, Reg. No. 37,407 LEVISOHN, LERNER, BERGER & LANGSAM 757 Third Avenue, Suite 2400 New York, NY 10017 Tel. No. 212-486-7272												

Page 3 of 3

5

ELECTRONIC MESSAGE DELIVERY SYSTEM UTILIZABLE This Apply claims the benefit of 18. Provisional No. 60/115, 305 Filed Som. 9, 1999.

BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to monitoring systems, and more specifically to networks for remotely monitoring the condition of devices such as those employed in heating, ventilating, and cooling (HVAC) systems.

Description of the Related Art

It is desirable to be able to monitor remotely equipment that may require periodic preventive maintenance and/or that may require rapid response time should a catastrophic failure occur. For example, the components of a building's HVAC system must be monitored or checked frequently. Preventive maintenance must be performed on a constant basis, particularly with larger systems. Fault or failure conditions may vary in degrees of severity, however the contractor responsible for maintaining the HVAC equipment should be made aware of each failure in due course. Since a contractor, in all likelihood, is responsible for the care and maintenance of the installations of multiple clients, and since fault conditions may occur at any time of day or night, it is not practical for a contractor to remain on-site all the time. Remote detection at a central location (for example, the contractor's office) of fault conditions is desirable and often crucial.

5

Some remote monitoring devices have been developed. U.S. Patent No. 5,629,687 to Sutton et al. describes a universal interface for remotely-monitored security or alarm systems. In Sutton et al., a local control unit at a monitored site can, under an event condition, initiate a telephone call to a central control unit to alert a human operator of an event such as an intrusion, fire, or other emergency at the site. The local control unit, via the telephone link, sends a serial number indicative of the specific site and emergency to the monitoring center computer. The monitoring center computer receives the serial number and alerts a human operator as to the emergency. The human operator can then act accordingly, e.g., establish one- or two-way communication with the local site.

U.S. Patent No. 5,748,104 to Argyroudis et al. describes a wireless remote telemetry system which provides real-time reading and remote control of devices such as electricity meters. A home base unit communicates with remote metering units via cellular telephone lines. The home base unit also communicates with a central controller operated by the electric utility. When the utility determines that there is too much load on the power grid, for example, the central controller can send messages to an appliance to turn off. A customer could also remotely activate or deactivate an appliance via a cellular phone through the home base unit.

U.S. Patent No. 5,061,916 to French et al. describes a system for remotely reporting, in graphical format, alarms or other conditions in a building's automation system. Sensors in a building are hooked up via a telephone line to control module which is, in turn, hooked up to a central controller. When a sensor detects a fault condition, graphical information is compiled at the central controller and transmitted to one or more remote facsimile machines.

All of the above systems and the prior art are limited in scope because they do not allow for sufficient flexibility in routing fault messages to a variety of different potential recipients of such messages via a variety of different media, depending on the urgency or nature of the fault. Also, the above systems and the prior art do not enable customers and contractors to enter or modify such information easily. As an example, a customer that has an HVAC system with a monitoring network may want to send certain non-emergency condition notifications (e.g., filter needs cleaning) to certain individuals (e.g., contractor/maintenance personnel) via a certain medium (e.g., e-mail) and emergency condition notifications (e.g., low or high refrigerant pressure) to other individuals (building owner, contractor, etc.) via other means (e.g., via beeper or other personal communication device). Such a list of who to contact via what means depending on which fault has occurred may be referred to as a "message profile". The conventional device/contractor interface requires a dedicated land line at both the HVAC device and the contractor; that is, the HVAC system requires its own phone line, and the contractor must have a dedicated modern line as well. Moreover, the conventional system does not allow for easy customer modifications to the message profile.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the invention to provide a system for remotely monitoring electrical and/or mechanical equipment.

5

It is another object of the invention to provide a system for remotely monitoring electrical and/or mechanical equipment that can deliver messages to different individuals for different fault conditions.

It is another object of the invention to provide a system for remotely monitoring electrical and/or mechanical equipment that can deliver fault notification messages to different individuals for different fault conditions via different electronic media.

It is another object of the invention to provide a system for remotely monitoring electrical and/or mechanical equipment in which a customer may interactively modify its message profile.

It is another object of the invention to provide a system for remotely monitoring electrical and/or mechanical equipment in which a customer may interactively modify its message profile via the Internet.

The above and other objects are satisfied by the invention which is a remote equipment monitoring system and method for monitoring remote equipment. In the inventive method, the steps include determining a state of at least one parameter of at least one piece of remote equipment, communicating messages regarding the state to a central location as incoming messages, and forwarding exception messages based on the incoming messages to at least one user-defined end device.

The inventive system includes a sensor in communication with a piece of remote equipment, and an interface unit, connected to the sensor, having a message generating mechanism. A central computer server is in communication with the interface unit and is adapted to receive messages generated by the interface unit. When the sensor detects an

exception condition in the piece of remote equipment (i.e., an operating condition that is either out of the ordinary or beyond nominal parameters), the interface unit generates an incoming exception message and forwards the message to the server. The server forwards at least one outgoing exception message to at least one predetermined user-defined end device based on the incoming exception message.

The system can contact a customer or contractor via a number of different media (fax, e-mail, pager, etc.) in case of an equipment failure. The contractor can determine which people to contact and which medium to use for which equipment failure. For example, if the condition is not very serious (e.g., filter needs cleaning), the contractor can set up the system to send a message via e-mail; if, however, it is serious (e.g., low/high refrigerant pressure), then the system can page the contractor and/or send a text message over his personal communication service (PCS). Also, the system includes the capability to send multiple messages to multiple recipients via differing media simultaneously for a given exception condition. Preferably, the system includes a centralized electronic message delivery device or server that routes the various incoming exception messages to the desired individuals via the desired electronic media in accordance with the predetermined message profile. More preferably, the contractor or consumer can access the centralized message server via the Internet and modify the message profile through software on the device.

20

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic of a preferred embodiment of a system according to the invention.

5

Fig. 2'is a schematic of a preferred embodiment of a link between the monitored equipment and the system according to the invention.

Figs. 3a-d'are schematics of links between an end-user's machine and the system according to the invention.

Fig. 4'is a schematic of a preferred embodiment of the electronic message delivery server according to the invention.

Fig. f is a flow chart depicting the operation of the system according to the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Equipment that needs to be monitored frequently, such as HVAC equipment, preferably operates within certain acceptable parameters. Some of these parameters are more crucial to the operation and/or life span of the equipment than are other parameters. For example, a low battery condition might be a lot less serious than a low coolant level condition. Whenever a piece of equipment operates outside its preferred parameters, an "exception" condition is created or said to exist. An exception condition can also be indicative of a regularly scheduled event occurring too often, too infrequently, or not at all. An exception condition could also be indicative of a measured value being beyond the design specification for the equipment.

When a monitored piece of equipment detects an exception condition, it activates its interface to the cellular phone network. The interface effectively acts as a cell phone in a roaming condition. The interface "attempts" to make a telephone call; because it is not recognized as being a resident of the local cell, the local cell (via the cellular network or mobile

5

switching center) contacts the "home cell" of the interface to insure that the interface is in good standing to complete the "call." There really is no home cell; in actuality, what is taking the place of the home cell of a cellular telephone is a message routing service such as those provided by Aeris or Bell South Cellemetry. When the local cell is contacting the message routing service, it transmits the following information: the serial number of the interface; the multi-digit "phone number" assigned to the interface; and the multi-digit phone number that the interface is "attempting to call." The message routing service tells the local cell that the interface is okay and should not be blacklisted, that the call need not go through, and that the interface should be removed from the "okay to roam" list immediately.

The interface is not really trying to call anyone; the multi-digit phone number it was trying to call represents a multi-digit code of information that is being sent to the message routing service and may represent fault information (e.g., 212-555-1212 means "filter needs cleaning"). The phone number assigned to the interface (which is also sent along with the phone number it is "trying to contact") may not only indicates which unit is doing the transmitting but may also convey fault information, since many of the devices being monitored do not have a large number of different fault conditions. This type of technology, in which information is transmitted in the handshaking portion of a cellular transmitter communicating to a local cell, appears in U.S. Patent Nos. 5,594,740 to LaDue and 5,546,444 to Roach, Jr. et al., and is commonly referred to as using control channel data. In LaDue (the Aeris version), the exception or status information is embedded in the digits of the "phone number"the interface is allegedly calling (the "dialed digits"); in Roach, Jr. (the Bell South Cellemetry version), the exception or

5

status information is embedded in the electronic serial number (ESN) of the interface, a number which identifies the physical hardware of the device. The information which identifies which interface has sent a message may be embedded in the mobile identification number (MIN) assigned to the interface unit. In the Aeris system, the ESN may also contain interface identification information.

The present invention expands on this technology and includes the message delivery technique mentioned above. The Aeris or Bell South Cellemetry router transmits the exception data to the inventive message delivery system which forwards the information to the contractor who is responsible for maintaining the faulty equipment. The contractor is provided with an account on the message delivery system that he can access via the Internet. The contractor sets up the specific parameters of which exception conditions are reported to which individuals. The contractor also sets up by which media (fax, e-mail, PCS) these individuals are to be notified. Multiple individuals may be alerted as to a exception condition. All of this data constitutes the contractor's message profile. For example, both the contractor and the owner of the premises might be signaled if there is a low/high refrigerant condition, however perhaps only one of them would be notified if a filter required cleaning. The user may also set, as part of the message profile, that different messages be delivered to different individuals at different times of the day, week, month, season, or year. For example, a high priority exception message may be directed to one repair/maintenance entity during regular business hours but be directed to a different repair/maintenance entity at night. Similarly, the same person could be contacted by different

5

means (e.g., fax or PCS) at different times. The content of the messages may also vary as a function of time.

In addition to notifying contractors when a problem arises, the interface may be programmed to check in once a day with an "all systems okay" message. This "okay" message also gets routed to the message delivery system. However, instead of being handled by an exception message subroutine in the message delivery system -the portion of the system which handles the above-mentioned fault messages-, the "okay" message is checked by a missing message subroutine. The missing message subroutine checks the entire list of HVAC interfaces that are supposed to signal "okay" from the message delivery system database. The missing message subroutine compares the entire list to the list of HVAC interfaces that actually checked in as "okay". If an interface failed to check in "okay", the message delivery system sends out the appropriate messages to the proper individuals via the selected media, all in accordance with the user's message profile lodged in the user's account with the message delivery system. The periodic "okay" or status message is not merely limited to providing a status "heartbeat" for the equipment but may also be employed to transmit information about the monitored piece of equipment. As will be explained below, the status message only requires a portion of its digits to convey equipment identification information, thus allowing other information to be transmitted as well. For example, the status message may include statistical information about the equipment such as how many cycles it has performed since the last message, the run time of the motor, etc. The status message may also serve as a reminder for routine maintenance, or it may report very minor or low-priority conditions that are not time sensitive.

5

The format of the message sent from the failing device to the local cell to the router to the message delivery system is a multi-digit code. The first digit can be for message format (e.g., status message, exception message, etc.). The sub-address is a digit or two reserved to identify to which unit that a transceiver interface is assigned is experiencing an exception condition; i.e., one transceiver interface may be assigned to a building having nine HVAC units, all connected to the transceiver via a bus line. The final digits would indicate the specific exception condition. The multi-digit message received by the message delivery system is normalized, converted into a regular text message, and forwarded to the user/contractor.

Description will now be given of the preferred embodiments with reference to Figs. 1-5. Figure 1 shows an overall view of the inventive system 50. An existing piece of equipment may be monitored, for example; an air-conditioner 2, boiler 3, motor starter 4, heater 5, or any other piece of equipment they may be desired to be monitored. The existing piece of equipment is fitted with an interface unit 10. Periodically, the interface unit 10 sends to the message delivery server 1 a status signal to let the message delivery server 1 know that the equipment being monitored and the interface unit 10 are functioning correctly. When a predetermined exception condition occurs in the piece of equipment being monitored, the interface unit 10 sends an incoming exception message to the message delivery server 1. The message delivery server 1 then routes the message as an outgoing exception message to the appropriate user interface; e-mail 6, fax 7, pager 8, voice 9, etc., according to the message profile as configured by the user of the system 21 via the Internet 122.

5

Messages from some of the interface units 10 may be delivered by means of wireless transmission over the cellular telephone network (see US Patent Nos. 5,594,740 and 5,546,444). Figure 2 is a detailed view of link 11 shown in Figure 1. A message is transmitted from the cellular interface unit 10a via a radio frequency link 13 to a nearby cellular transceiver site 14, the message is then routed to the cellular network or mobile switching center (MSC, e.g., a cellular carrier such as Bell Atlantic) 16 where the message is then delivered via data circuits 17 and via router 51 (e.g., Bell South Cellemetry or Aeris) to the message delivery server 1. As will be clear from the discussion of Fig. 4, reference numerals 11a and 11b refer to different types of links. Specifically, link 11a is for receiving incoming exception and status messages from interfaces 10 which are in regions wired for sending data via the dialed digits control channel; link 11b forwards messages along the ESN channel to the message server 1.

Based on the configuration of the user's message profile, the outgoing exception message (or messages) is then delivered to the specified end device or devices. Figures 3a-d show a more detailed view of the various outbound links 12a-d that connect the server 1 to the various electronic media. In Fig. 3a, server 1 sends the message over a telephone line 18a to the Internet 122 and deposits the message in the user's e-mail box 6. In Fig. 3b, server 1 sends the message over a telephone line 18b through the public telephone switched network (PTSN) 19 to the user's fax machine 7. In Fig. 3c, server 1 sends the message over a telephone line 18c to the user's pager service 53 and thence to the user's pager or PCS 8. In Fig. 3d, server 1 sends the message over a telephone line 18d through the PTSN 19 to the user's voice mail box 9. The same message may also be sent to a number of other devices as configured by the user 121 over the

5

Internet 122. The same message that is being sent to a fax machine 7 as described above may also simultaneously be sent to an e-mail 6 recipient via the Internet. Preferably, different messages can be sent to different individuals simultaneously for the same fault condition; for example, the owner of the premises may receive a less-detailed message than the contractor.

A user's message profile can also be configured to store messages on server 1 for delivery at a later time or after certain conditions are met. For example, a contractor may not want his beeper activated every time server 1 receives an incoming exception message. The user profile can be configured to deliver messages on groups or only after several messages have accumulated for the same user/contractor. Optionally, an outgoing exception message may be generated only after several of the same type of incoming message are received; a portion of the memory of server 1 may be devoted to the storing and/or accumulating of messages.

Alternatively, a single outgoing exception message may be generated in response to several incoming messages.

Figure 4 shows the details of the message delivery server 1. In the preferred embodiment, server 1 includes four hardware devices 200, 300, 400, and 500. Device 200 is responsible for receiving incoming messages, processing them in accordance with the user's preferences, and routing them for output. Messages may be temporarily stored or accumulated on device 200 before being transmitted to the user if the user's message profile is set up accordingly. Device 300 enables the user 121 to access server 1 and create or edit his message profile residing in relational data base 21 of device 200. Device 400 includes the various drivers 33 which are responsible for transmitting the various messages to the various media (fax, e-mail,

5

etc.). Device 500 includes billing computer 38 for keeping track of the charges and fees associated with the user's use of the service.

At the core of server 1 is a relational data base 21. Incoming messages are received by a specific service designed to handle both the transport method and message formatting. Every interface unit 10 is provided, like a cellular telephone, with an electronic serial number (ESN, to identify the specific interface unit sending the message) and a mobile identification number (MIN, similar to a cellular telephone's phone number). In some instances, the exception or status information is embedded in the dialed digits the interface transmits. The dialed digits control channel module 25 specifically receives messages that are encoded in the control channel's dialed digits (see US Patent 5,594,740). The ESN control channel module 24 receives messages that are encode in the electronic serial number of the message (US Patent 5,546,444). It is preferable to have both a dialed digits module 25 and an ESN module 24, because some geographic regions employ dialed digit data coding, while other regions employ ESN data coding. Information may be transmitted via the MIN of the interface 10 and also received by message delivery server 1. Services are also available to receive messages for analog modems connected to the public telephone switched network 23, and the cellular digital packet data network 22. As additional methods of transmitting data become available, they can be added to the services layer.

All incoming messages are normalized at the normalization module 26 so that all incoming messages can then be processed without regard to their incoming medium. All incoming messages are passed to the normal message subroutine 27, exception messages are

5

passed on for processing and routing via the user's configuration through the data base 21, and periodic status messages are queued. The missing message subroutine 28 compares received status messages with a list of expected messages. Status messages that are not received have an error message generated by the missing message subroutine 28 which are then delivered as configured by the user in his message profile as recorded in the relational database 21.

Messages to be delivered are placed in a message queue 32; as message traffic permits the appropriate drivers 33 request messages from the message queue 32 and route the messages over the appropriate transport. Numeric pages, faxes, voice and DTMF 34 are sent over the PTSN 12b-d, e-mail 35 is sent over the Internet 122. When a driver 33 has successfully delivered, a record is made in the data base 21 by the delivery confirmation subroutine 31 showing time and date of successful deliveries. Undeliverable messages are routed back to the database for generation of undeliverable message errors.

Users 121 connect to an Internet information server 30 via the Internet 122. The Internet information server presents to the user the information pertaining to that user's interfaces. Requests to alter the user's data are passed through active server pages 29 to protect both the integrity and security of the data base 21. All messages and transactions that pass through the system are logged in section 36, the transaction and message logs are then interfaced by section 37 to a billing system 38.

An example of the system's operation is as follows. When a user-contractor 121 first signs up with the system 50, he receives an account on the electronic message delivery server 1. Via the Internet, the contractor 121 is prompted through software to enter the pager numbers,



5

cellular telephone numbers, facsimile machine numbers, and Internet addresses of any individuals who are to be contacted in the event of an exception condition in building equipment 2-5 for which the contractor is responsible. The user-contractor 121 may also set the software to notify him of the periodic successful routine status check messages conveyed from equipment 2-5.

Fig. 5 depicts a flow chart of the basic steps that occur when a message is received by server 1. At step S1, the message is received. At step S2, normalization module 26 removes the required elements from the incoming message and arranges them in a normalized format and stores them as a record in a table. Server 1 can now examine a specific element in a message of any received media type. At step S3, it is determined what type of error message has been received. If it is an exception message that requires immediate action, it is passed onto a process to begin configuration of a readable message at step S4 for delivery at step S5. If not, server 1 determines if the received message is a "unit checking in" or a "system ok" status message at step S6. If the user has his message profile so configured, a storing/accumulating step (not shown) may occur between steps S4 and S5. Undefined messages are handled at step S7. If it is configured as a periodic message received to indicate normal operation of a unit, the message is stored at step S8 for use at a later time. Periodically, the list of units that have reported in at step S8 and the list of active units expected to report in (part of database 21) are compared at step S9. Units on the active list that do not appear on the checked-in units list are processed, and units that failed to report in have messages created at step S10. These messages are then posted for further processing and message delivery at step S5.

In the example given, suppose boiler 3 breaks down in a non-catastrophic manner. The fault condition is detected by a sensor (not shown) and encoded to interface 10. Interface 10 transmits a radio message via link 13 to a local cell site 14, which contacts data circuits 17 via cellular network 16. Circuits 17 forward the message to message server 1. If the message is transmitted by the cellular telephone network 16, the ESN arrives via link 11b to ESN channel 24; alternatively, the dialed digits information arrives via link 11a to dialed digits channel 25. The message is normalized in normalization module 26 and passed along to the normalized message process module 27. Module 27 selects the user's message profile from relational database 21 and in accordance therewith, determines what message gets sent to whom and by which medium.

The invention is not limited to the above description but rather is defined by the claims appearing hereinbelow. Modifications to the above description that include that which is known in the art are well within the scope of the contemplated invention. For example, the invention is designed to be adaptable to all forms of electronic communication, be they cellular telephone, land line telephone, electronic mail, facsimile, text page, voice mail, etc. All forms of electronic media are contemplated as being within the scope of the invention. Also, multiple formats of incoming and outgoing messages are contemplated as included within the scope of the claims and the invention. The user can adjust the format and content of the messages he receives by setting up his message profile accordingly.



What is claimed is:

A method of monitoring remote equipment comprising the steps of:

- a) determining a state of at least one parameter of at least one piece of remote equipment;
- b) communicating messages regarding the state to a central location as incoming messages;\and
- c) forwarding outgoing exception messages based on the incoming messages to at least one user-defined communication device.
- A method according to Claim 1, wherein said step b) further comprises the step of communicating the incoming messages to the central location via one of a plurality of different communication media.
- A method according to Claim 2, further comprising the step of d) normalizing the 3. incoming messages into a uniform format to dreate normalized messages, wherein the outgoing exception messages are generated based on the normalized messages.
- 4. A method according to Claim 1, wherein the at least one parameter is at least one of an exception condition and a normal status condition.



- A method according to Claim 1, further comprising the step of e) determining whether an incoming message is an incoming exception message or a normal status message.
- 6. A method according to Claim 5 wherein, if an incoming message is determined to be an incoming exception message in step e), the method further comprises the step of f) routing the incoming exception message as the outgoing exception message to the at least one user-defined communication device.
- 7. A method according to Claim 6, further comprising the step of g) creating a user-defined message profile, wherein said forwarding step c) forwards the outgoing exception message in accordance with the user-defined message profile.
- A method according to Claim 7, wherein step g) further comprises the step of h) enabling a user to create or edit the user-defined message profile remotely from the central location.
- A method according to Claim 8, wherein said step h) is performed by the user via the Internet.
- 10. A method according to Claim 8, wherein step g) further comprises the steps of:
- 1) selecting at least one type of user-defined communication device to which outgoing exception messages are to be forwarded;

- 2) selecting specific user-defined communication devices of the types selected in step 1); and
 - 3) determining the content of the outgoing exception messages forwarded in step c).
- 11. A method according to Claim 5, wherein if the incoming message is determined in step e) to be a normal status message, the method further comprises the step of i) storing the normal status message in a normal status memory.
- A method according to Claim 11, further comprising the steps of: 12.
 - j) providing a main list of all pieces of remote equipment being monitored;
- k) comparing the normal status memory with the main list to determine which pieces of remote equipment did not communicate a normal status message within a predetermined period of time; and
- 1) generating an outgoing exception message for each piece of equipment identified in step k).
- A method according to Claim 12, further comprising the step of g) creating a user-defined 13. message profile, wherein said forwarding step c) forwards the outgoing exception message in accordance with the user-defined message profile.

- 14. A method according to Claim 13, wherein step g) further comprises the step of h) enabling a user to create or edit the user-defined message profile remotely from the central location.
- 15. A method according to Claim 14, wherein the central location includes a computer database and said step h) is performed by the user via the Internet.
 - 16. A method according to Claim 14, wherein step g) further comprises the steps of:
 - 1) selecting at least one type of user-defined communication device to which outgoing exception messages are to be forwarded.
 - 2) selecting specific user-defined communication devices of the types selected in step 1); and
 - 3) determining the content of the error messages forwarded in step c).
 - A method according to Claim 1, wherein the communication devices include at least one of a facsimile machine, an e-mail account, a cellular telephone, a beeper, a pager, a PCS device, and a telephone.
 - 18. A method according to Claim 2, wherein the communication media of step b) includes at least one of a cellular telephone network, radio transmissions, telephone lines, and the Internet.

- 19. A method according to Claim 13, wherein step c) further comprises forwarding multiple outgoing exception messages to multiple user-defined communication devices in response to a single incoming message in accordance with the user-defined message profile.
- 20. A method according to Claim 13, wherein step c) further comprises forwarding a single outgoing exception message to a user-defined communication device in response to multiple incoming messages in accordance with the user-defined message profile.
- 21. A method according to Claim 13, further comprising the step of m) storing a plurality of user-defined message profiles at the central location.
- 22. A method according to Claim 7, wherein step c) further comprises forwarding multiple outgoing exception messages to multiple user-defined communication devices in response to a single incoming message in accordance with the user-defined message profile.
- 23. A method according to Claim 7, wherein step c) further comprises forwarding a single outgoing exception message to a user-defined communication device in response to multiple incoming messages in accordance with the user-defined message profile.
- 24. A method according to Claim 7, further comprising the step of m) storing a plurality of user-defined message profiles at the central location.

- 25. A method according to Claim 1, wherein the remote equipment includes heating, ventilating, and cooling equipment.
- 26. Amethod according to Claim 1, wherein said step b) further comprises the step of communicating an identification code of the piece of remote equipment in the incoming messages.
 - 27. A method according to Claim 26, wherein said step c) further comprises the step of forwarding the identification code to the at least one user-defined communication device.
 - 28. A method according to Claim 7, wherein step g) further comprises the step of enabling selection of different user-defined communication devices to receive outgoing exception messages at different time periods.

- A method according to Claim 13, wherein step 3 further comprises the step of enabling selection of different user-defined communication devices to receive outgoing exception messages at different time periods.
- 30. A method according to Claim 11, further comprising the step of forwarding operational information embedded within a normal status message.

a se

31.

10世

A system for monitoring remote equipment, comprising:

a sensor in communication with a piece of remote equipment;

an interface unit, connected to said sensor, said interface unit having a message generating mechanism; and

a central computer server in communication with said interface unit, said server adapted to receive messages generated by said interface unit,

wherein when said sensor detects an exception condition in the piece of remote equipment, said interface unit generates an incoming exception message and forwards said message to said server,

and wherein said server forwards at least one outgoing exception message to at least one predetermined user-defined communication device based on said incoming exception message.

32. A system according to Claim 31, wherein said message generating mechanism forwards said incoming exception messages via at least one of a plurality of communication media, said media comprising at least one of a cellular telephone network, radio transmissions, telephone lines, and the Internet.

A system according to Claim 32, said server comprising a normalization module, wherein said server receives said incoming exception messages from said interface unit and said normalization module normalizes said incoming exception messages into a uniform format to

create normalized messages, wherein said outgoing exception messages are generated based on said normalized messages.

A system according to Claim 31, wherein said sensor monitors at least one parameter of said piece of remote equipment, wherein the at least one parameter is at least one of an exception condition and a normal status condition.

system according to Claim 31, said system monitoring a plurality of pieces of 35. equipment, each piece having an identification code, said server further comprising:

a first memory on which equipment identification codes of all monitored equipment are stored;

a second memory in which communication device identification codes of all of said userdefined communication devices are stored, said communication device identification codes being configured in user-defined message profiles.

- 36. A system according to Claim 35, said server further comprising a user interface remotely accessible by users and in communication with said second memory, wherein users can create or edit said user-defined message profiles remotely from said server.
- A system according to Claim 36, wherein said user interface enables a user to select at 37. least one type of user-defined communication device to which outgoing exception messages are

to be forwarded, select specific user-defined communication devices of the types selected, and determine the content of said outgoing exception messages forwarded by said server to said user-defined communication devices.

- 38. A system according to Claim 31, wherein said user-defined communication devices include communication devices including at least one of a facsimile machine, an e-mail account, a cellular telephone, a beeper, a pager, a PCS device, and a telephone.
- 39. A system according to Claim 35, wherein said interface unit periodically generates a normal status message if its respective piece of equipment is functioning properly, said normal status message including an equipment identification code.
- 40. A system according to Claim 39, said server further comprises:
 a third memory for storing said normal status messages;

means for comparing the normal status memory with the main list and for identifying which of said pieces of remote equipment did not communicate a normal status message within a predetermined period of time; and

means for generating and forwarding an outgoing exception message for each piece of equipment identified by said comparing and identifying means, said outgoing exception message being forwarded to at least one of said user-defined communication devices in accordance with at least one of said user-defined message profiles.

sub.

A system according to Claim 39, said server further comprising a normalization module, wherein said server receives said incoming exception messages from said interface unit and said normalization module normalizes said incoming exception messages into a uniform format to create normalized messages, wherein said outgoing exception messages are generated based on said normalized messages.

- A system according to Claim 35, said interface unit comprising a plurality of interface units, wherein each of said plurality of interface units is connected to a single piece of said pieces of equipment.
- 43. A system according to Claim 35, said interface unit comprising a plurality of interface units, wherein each of said plurality of interface units is connected to a number of said pieces of equipment.
- 44. A system according to Claim 35, wherein said user-defined message profiles are each configurable to cause said server to forward a plurality of said outgoing exception messages in response to receipt of a single incoming exception message.

- A system according to Claim 35, wherein said user-defined message profiles are each configurable to cause said server to forward a single of said outgoing exception messages in response to receipt of multiple incoming exception messages.
- A system according to Claim 40, wherein said outgoing exception message generating 46. and forwarding means is adaptable to forward a plurality of said outgoing exception messages for each piece of equipment identified by said comparing and identifying means.

A system according to Claim 31, wherein said incoming exception message comprises exception information and identification information concerning said piece of remote equipment.

- system according to Claim 47, wherein said outgoing exception message comprises exception information and identification information concerning said piece of remote equipment.
- A system according to Claim 39, wherein said normal status message further comprises operational information of said piece of remote equipment.
- A system according to Claim 40, further comprising a fourth memory upon which 50. outgoing exception messages are stored.

5

ABSTRACT

A system and method for monitoring remote equipment are provided. A sensor is in communication with a piece of remote equipment, and an interface unit, having a message generating mechanism, is connected to the sensor. A central computer server is in communication with the interface unit and is adapted to receive messages generated by the interface unit. When the sensor detects an exception condition in the piece of remote equipment, the interface unit generates an incoming exception message and forwards the message to the server. The server forwards at least one outgoing exception message to at least one predetermined user-defined communication device based on the incoming exception message. Multiple outgoing exception messages may be forwarded to multiple communication devices in accordance with a user-defined message profile, or a single outgoing exception message may be forwarded in response to receipt of multiple incoming exception messages. The message profile is remotely configurable by the user.

%

Docket No.	
1216.034	

Declaration and Power of Attorney For Patent Application

English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

ELECTRONIC MESSAGE DELIVERY SYSTEM UTILIZABLE IN THE MONITORING OF EQUIPMENT AND METHOD OF SAME

the specification of which

(check one)			
☐⊠ is attached here	to.		. •
		as United States Application	No. or PCT International
Application Num and was amend	ber		
and was amend	ed on		
T		(if applicable)	
	have reviewed and under , as amended by any ame	rstand the contents of the aboundary referred to above.	ve identified specification,
<u> </u>	•	ited States Patent and Tradem as defined in Title 37, Code	
Section 365(b) of a any PCT Internation listed below and ha inventor's certificate		er Title 35, United States Coo for patent or inventor's certific inated at least one country oth	eate, or Section 365(a) of
on which priority is	e or PCT International app	y checking the box, any foreig lication having a filing date bef	n application for patent or
Prior Foreign Applic	e or PCT International app claimed.	y checking the box, any foreig	n application for patent or
, ,	e or PCT International app claimed.	y checking the box, any foreig	n application for patent or ore that of the application
, ,	e or PCT International app claimed.	y checking the box, any foreig	n application for patent or fore that of the application Priority Not Claimed and application
Prior Foreign Applic	e or PCT International app claimed. cation(s) (Country)	y checking the box, any foreig lication having a filing date bef (Day/Month/Year Fil	n application for patent or fore that of the application Priority Not Claimed and a column
Prior Foreign Applic	e or PCT International app claimed. cation(s)	y checking the box, any foreig lication having a filing date bef	n application for patent or fore that of the application Priority Not Claimed and a color of the application Priority Not Claimed and a color of the application

Form PTO-SB-01 (9-95) (Modified)

P02/REV02

50/115,305	Jan. 9, 1999	
(Application Serial No.)	(Filing Date)	
(Application Serial No.)	(Filing Date)	
(Application Serial No.)	(Filing Date)	
ffice all information known to mection 1.56 which became availal	ne to be material to patentable between the filing date of	lity as defined in Title 37, C. F. F
ffice all information known to m	ne to be material to patentable between the filing date of	lity as defined in Title 37, C. F. F. he prior application and the nation (Status)
ffice all information known to mection 1.56 which became availal PCT International filing date of the	ne to be material to patentabi ble between the filing date of his application:	ity as defined in Title 37, C. F. F. he prior application and the nation (Status) (patented, pending, abandoned) (Status)
ffice all information known to mection 1.56 which became availal PCT International filing date of the (Application Serial No.)	ne to be material to patentabilities between the filing date of his application: (Filing Date)	(patented, pending, abandoned)
ffice all information known to mection 1.56 which became availal PCT International filing date of the (Application Serial No.) (Application Serial No.) (Application Serial No.) hereby declare that all statements made on information a ere made with the knowledge the	ne to be material to patentabilities between the filing date of mis application: (Filing Date) (Filing Date) (Filing Date) ents made herein of my own discount of the part of the part willful false statements and part Section 1001 of Title 18 of the part willful false statements and part Section 1001 of Title 18 of the part willful false statements and part Section 1001 of Title 18 of the part of	(Status) (patented, pending, abandoned) n knowledge are true and that are; and further that these statements the like so made are punishable in the United States Code and that such

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Peter L. Berger Andrew S. Langsam Morris E. Cohen Barry E. Negrin

Reg. No. 24,570 Reg. No. 28,556 Reg. No. 39,947 Reg. No. 37,407

Send Correspondence to: Barry E. Negrin

LEVISOHN, LERNER, BERGER & LANGSAM

757 Third Avenue, Suite 2400

New York, NY 10017

)
Date, 5/20/99
p p p p p p p p p p p p p p p p p p p

Full name of second inventor, if any	
Daniel Shprecher	5/20/99
Second inventor's signature	Date
Residence Highland Lakes, NJ	
Citizenship USA	
Post Office Address	
5 Brentwood Road, Highland Lakes, NJ 07422	

Form PTO-SB-01 (6-95) (Modified)

		•	LAIMING SMALL TIT LL BUSINESS CONCERN	Docket No. 1216.034
Serial N	0.	Filing Date	Patent No.	Issue Date
Applicant/ Davi Patentee:	id Sandelmar	and Daniel Shprecher		
Invention: ELI			EM UTILIZABLE IN THE MON	IITORING
	vner of the s	mall business concern identifie mall business concern empowe	ed below: ered to act on behalf of the conc	ern identified below:
		at Timer Corporation 20 New Dutch Lane, Fairfield,	NJ 07004	
of Title 35, Unit not exceed 500 average over the basis during earliectly or indirectly or indirectl	18, and repro- ed States Concepts of the previous ach of the pectly, one control both	oduced in 37 CFR 1.9(d), for pode, in that the number of emor purposes of this statement, fiscal year of the concern of tay periods of the fiscal year, incern controls or has the powith.	concern qualifies as a small bus urposes of paying reduced fees ployees of the concern, includin (1) the number of employees of the persons employed on a full- and (2) concerns are affiliates fer to control the other, or a third en conveyed to and remain with	under Section 41(a) and (b) g those of its affiliates, does the business concern is the time, part-time or temporary of each other when either, d party or parties controls or
dentified above	with regard	to the above identified invention	on described in:	THE CHILL BUSINESS CONCOM
all'i		on filed herewith with title as lis	ted above.	
	• •	identified above.		,
	·	atified above.	ss concern are not exclusive,	each individual concern or
organization ha	aving rights than the inverse would not q	to the invention is listed on the entor, who could not qualify a	e next page and no rights to the san independent inventor undocern under 37 CFR 1.9(d) or a	e invention are held by any er 37 CFR 1.9(c) or by any
				•
		•		
Copyright 1994 Le	nalsoft	P05/REV01	Datast and Trademark Of	fice-U.S. DEPARTMENT OF COMMERCE

•		-		ave assigned, grante /ey, or license any righ	•	censed or am under an is listed below:
			organization ex or organization			
FULL NAME ADDRESS						
FULL NAME		Individual		Small Business Concern		Nonprofit Organization
FULL NAME		Individual		Small Business Concern		Nonprofit Organization
ADDRESS		Individual		Small Business Concern		Nonprofit Organization
FULL NAME ADDRESS		Individual		Small Business Concern		Nonprofit Organization
Liacknowledge Entitlement to maintenance Thereby decentiformation a willful false suffice 18 of the	erring to their ge the duty o small ent fee due afte lare that all and belief ar tatements a e United Sta	to file, in the lity status per the date of statements believed to the Code, at the	mall entities. (3 is application or rior to paying, on which status made hereing be true; and so made are pund that such wi	7 CFR 1.27) or patent, notification of or at the time of patens as a small entity is not of my own knowledge further that these statenishable by fine or in	of any change in aying, the earliest longer appropriate are true and the ements were mad apprisonment, or both any jeopardize the	ation having rights to the status resulting in loss of of the issue fee or any e. (37 CFR 1.28(b)) at all statements made on e with the knowledge that oth, under Section 1001 of evalidity of the application,
NAME OF PERTITLE O	RSON SIGN		David Sandel	man President		
ADDRESS OF	PERSONS	SIGNING:	20 New Dutch	ı Lane, Fairfield, NJ 07	7004	
SIGNATURE:	·	0) Land		DATE: 5/2	

	ERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS (37 CFR 1.9(f) AND 1.27 (b)) - INDEPENDENT INVENTOR						Docket No. 1216.034		
Serial	No.	Filing	g Date	Pater	nt No.	Issue Date			
Applicant/ Datentee:	avid Sandelma	n and Daniel Si	aprecher						
Invention: E	LECTRONIC	MESSAGE DI	ELIVERY SY	STEM UTILIZABL	E IN THE MON	ITORI	NG		
OF EQUIPME	NT AND MET	THOD OF SAM	Œ						
purposes of	paying reduce	ed fees under	section 41(a		35, United State		in 37 CFR 1.9(c) for e, to the Patent and		
🖾 the	specification t	o be filed here	with.				•		
	•	entified above.							
□ the	patent identifi	ed above.							
convey or lice under 37 CF bosiness con Each person obligation und	ense, any righ R 1.9(c) if tha cern under 37, concern or other contract or	ts in the invert person had CFR 1.9(d) or organization to law to assign,	ntion to any primade the in a nonprofit of which I has grant, conve	person who could no vention, or to any conganization under 3 we assigned, grantery, or license any rig	ot be classified concern which variety of CFR 1.9(e).	as an i vould n	law to assign, grant, independent inventor of qualify as a small sed or am under an sted below:		
2 77	•	concern or orga n, concern or o							
 1	E: Separate ve	erified statemer	nts are requi	red from each name atus as small entities	•		rganization having		
FULL NAME ADDRESS	Heat Timer C	orporation Lane, Fairfield	N 1 0 7 0 0 4						
ADDITEOG		ndividual		Small Business Concern		□ No	onprofit Organization		
FULL NAME									
ADDRESS									
		Individual		Small Business Concern		☐ No	onprofit Organization		
FULL NAME					.`				
ADDRESS		La de Charal		0		<u> </u>	St. O and a final		
FULL NAME		Individual	•	Small Business Concern		U No	onprofit Organization		
ADDRESS		Individual		Small Business Concern			onprofit Organization		
		•					1, 0		


P03/REV01

Copyright 1994 Legalsoft

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF INVENTOR David Sandelman		/ 1
SIGNATURE OF INVENTOR Can famile	DATE:	5/20/99
		, ,
NAME OF INVENTOR Daniel Shprechen		1 1 m
SIGNATURE OF INVENTOR For MINISTER SIGNATURE OF INVENTOR	DATE:	5/20/99
		•
NAME OF INVENTOR		•
SENATURE OF INVENTOR	DATE:	
		•
NAME OF INVENTOR	nd water to the discourse with the con-	
SIGNATURE OF INVENTOR	DATE:	
in the second of		
NAME OF INVENTOR		
SIGNATURE OF INVENTOR	DATE:	
NAME OF INVENTOR	***************************************	
SIGNATURE OF INVENTOR	DATE:	
NAME OF INVENTOR		
SIGNATURE OF INVENTOR	DATE:	
NAME OF INVENTOR		
SIGNATURE OF INVENTOR	DATE:	6.7.2
	· · · · · · · · · · · · · · · · · · ·	
NAME OF INVENTOR		
SIGNATURE OF INVENTOR	DATE:	
NAME OF INVENTOR		
SIGNATURE OF INVENTOR	DATE:	






Figure 2




Figure 3a




Figure 3b




Figure 3c





Figure 3d







Figure 5



. O9317835 . O52495




Figure 2




Figure 3a




Figure 3b




Figure 3c





Figure 3d






Figure 5



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

OCT 2 8 1999

In re application of: Sandelman et al.

Serial No. 09/317,235

Filed: May 24, 1999

Art Unit 2736

Attorney Docket: 1216.034

For: Electronic Message Delivery System Utilizable in the Monitoring of Equipment and

Method of Same

PATENT

INFORMATION DISCLOSURE STATEMENT

Assistant Commissioner of Patents Washington, DC 20231

Sir:

Pursuant to 37 CFR §1.97(b) Applicant submits the Information Disclosure Statement (IDS) filed herewith for the above-identified application. Since the IDS is being filed before the mailing of a first Office Action, no fee is due. A PTO-1449 and a copy of the 13 references cited thereon are also being submitted herewith. If any fees are required or if any overpayment needs to be credited, please charge/credit same to Deposit Account 02-2105.

Dated: October 26, 1999

Levisohn, Lerner, Berger & Langsam 757 Third Avenue, Suite 2400 New York, New York 10017 (212) 486-7272

Respectfully submitted,

Barry E. Negrin Reg. No.: 37,407

Attorney for Applicant

			Docket Number (Optional) Application Number 1216.034 09/317,235						
	INFO	RMATION DISCLOSURE (Use several sheets if necessary)			Applicant(s) Sandelman, et al.				
		(0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.			Filing Date 05/24/99		Group Art Unit	736	
				U.S. PAT	TENT DOCUMENTS				
*EXAMINER INITIAL	REF	DOCUMENT NUMBER	DATE		NAME	CLASS	SUBCLASS	FILING	
M.		5,855,008	12/29/1998	Goldha	ber et al.	705	14		
		5,794,210 PE	08/11/1998	Goldha	aber et al.	705	14		
		5,748, 04 2 2 8 1999	05/05/1998	Argyro	oudis et al.	340	870.11		
		5,734,645 5,729,596	03/31/1998	Raith e	et al.	370	329.		
		5,729,596 CAT & TRADE	03/17/1998	Reeder	et al.	379	102.09		
		5,642,356	06/24/1997	Wenk		310	337	4	
		5,629,687	05/13/1997	Sutton	et al.	340	825.37	. *** ::	
	5,594,740		01/14/1997	LaDue		455	410		
		5,546,444	08/13/1996	Roach	, Jr. et al.	455	412		
		5,528,675	06/18/1996	Chen		379	106.01		
		5,526,401	06/11/1996		Roach, Jr. et al.		426		
				FOREIG	GN PATENT DOCUMENTS				
	REF	DOCUMENT NUMBER	DATE		COUNTRY	CLASS	SUBCLASS	Trans YES	lation NO
							100 a		
							CENT		
								NE E	
							2700	, 	Í
			·	OTHER	R DOCUMENTS (Including	Author, Title,	Date, Pertinent Pa	ges, Etc.)	
		·							

					(*)				
EXAMINI	ER /	and Parks			DATE CONSIDERED	6/28	100		
		tial if citation considered, whether nclude copy of this form with next				Draw line thro	ough citation if not	in conform	ance and

P09A/REV04

Form PTO-A820 (also form PTO-1449)

Petitioner Alarm.com Exhibit 1202 1202.0062

Patent and Trademark Office * U.S. DEPARTMENT OF COMMERCE

OF 2

SHEET 1

			ATTY DOCKET NO. 1216.		SERIAL NO. 09/3	317,235
I	NFORMATION DISCLOSUF (Use several sheets if nec	RE CITATION	Sandelman, et al.			
	(0	CT 2 8 1999 2	FILING 05/24		GROUP 2	2736
	3	357	S. PATENT DOCUMENTS			
*EXAMINER	DOCUMENT NUMBER	DATE	NAME	CLASS	SUBCLASS	FILING DATE
D. R	5,517,690	05/14/1996	Linquist et al.	455	426	IF APPROPRIATE
00	5,061,916	10/29/1991	French et al.	340	522	
	,				1	
						Jak II
						+
· .		FOR	EIGN PATENT DOCUMENTS			
	DOCUMENT NUMBER	DATE	COUNTRY	CLASS	SUBCLASS	TRANSLATION YES NO
					C	
					E S	
					700	
	OTHER DOCU	MENTS (Includ	ing Author, Title, Date, Pert	inent Pages, Etc	.)	
			: 			1
			entre en la companya de la companya			
EXAMINER	Day Port		DATE CONSIDERE	ED 6/2	8/00	
	R: Initial if reference considered, wh			9; Draw line through	citation if not in o	conformance and not

Form PTO-A820 (also form PTO-1449)

P09C/REV03

Patent and Trademark Office * U.S. DEPARTMENT OF COMMERCE

PAGE 2

OF 2

		, , , , , , , , , , , , , , , , , , ,		.1 1-
CERTIFICATE OF MADE Applicant(s): Sandelman	MAILING // FIRST CLAS	SS MAIL (37 CFR 1.8)		Docket No.
Serial No. 09/317,235	Filing Date May 24, 1999	Examiner		Group Art Unit 2736
Invention: Electronic M	essage Delivery System Utilizable	e in the Monitoring of Equipm	ent and M	lethod of Same
OCT 2 8 1999		(Identify type of correspondence)		
is being deposited wit	h the United States Postal Ser	vice as first class mail in an	envelope	addressed to? The
Assistant Commission	er for Patents, Washington, D.C	Lourdes Roy (Typed or Printed Name of Person (Signature of Person Mailin	driguez Mailing Co.	rrespondence)
	Note: Each paper must ha	ave its own certificate of mailing.	,	RECEIVED 1501 CENTER 2700

P07A/REV03



UNITED STATES DE, ARTMENT OF COMMERCE **Patent and Trademark Office**

Address: COMMISSIONER OF PATENTS AND TRADEMARKS

DATE MAILED:

Washington, D.C. 20231

FIRST NAMED INVENTOR ATTORNEY DOCKET NO. APPLICATION NO. FILING DATE 05/24/99 SANDELMAN 09/317,235 ${\mathbb D}$ 1216.034 **EXAMINER** Г LM02/0120 BARRY E NEGRIN POPE PAPER NUMBER ART UNIT LEVINSOHN LERNER BERGER AND LANGSAM 3 SUITE 2400 757 THIRD AVENUE NEW YORK NY 10017 2736

Please find below and/or attached an Office communication concerning this application or proceeding.

Commissioner of Patents and Trademarks

01/20/00

PTO-90C (Rev. 2/95)

U.S. G.P.O. 1999 460-693

1- File Copy

	Application No.	Applicant(s)		
Office Action Summary	09/317,235		SANDELMAI	N ET AL
	Examiner DARYL C. POPE		Group Art Unit 2736	
Responsive to communication(s) filed on				
This action is FINAL.				
Since this application is in condition for allowance ex in accordance with the practice under Ex parte Quality			tion as to the m	erits is closed
A shortened statutory period for response to this action longer, from the mailing date of this communication. Fa application to become abandoned. (35 U.S.C. § 133). 37 CFR 1.136(a).	ailure to respond within the	e period for	response will ca	use the
Disposition of Claim			. 1	
X Claim(s) 1-50		····	is/are pen	ding in the applicat
Of the above, claim(s)			is/are withdraw	n from consideration
Claim(s)			is/ar	e allowed.
				e rejected.
☐ Claim(s)			is/ar	e objected to.
☐ Claims		are subject t	o restriction or e	election requirement.
Application Papers				•
🛚 See the attached Notice of Draftsperson's Patent	Drawing Review, PTO-94	8.		
☐ The drawing(s) filed on	is/are objected to by the B	Examiner.		
☐ The proposed drawing correction, filed on	is 🗌 a	approved	_disapproved.	
☐ The specification is objected to by the Examiner.				
☐ The oath or declaration is objected to by the Exar	miner.			
Priority under 35 U.S.C. § 119				
☐ Acknowledgement is made of a claim for foreign	priority under 35 U.S.C. §	119(a)-(d).		
☐ All ☐Some* None of the CERTIFIED c	opies of the priority docum	nents have	been	
received.				
received in Application No. (Series Code/S				
received in this national stage application in the stage applic		•		
Acknowledgement is made of a claim for domest				
•	,	3		
Attachment(s) X Notice of References Cited, PTO-892				
☐ Information Disclosure Statement(s) PTO 1449	Paper No(e)			

U. S. Patent and Trademark Office PTO-326 (Rev. 9-95)

☐ Interview Summary, PTO-413

X Notice of Draftsperson's Patent Drawing Review, PTO-948

☐ Notice of Informal Patent Application, PTO-152

Office Action Summary

--- SEE OFFICE ACTION ON THE FOLLOWING PAGES ---

Part of Paper No. 3

Application/Control Number: 09/317235 Page 2

Art Unit: 2736

DETAILED ACTION

ART REJECTION:

Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 2. Claims 1-50 are rejected under 35 U.S.C. 103(a) as being unpatentable over Wilson et al(5,400,246).
 - -- In considering claim 1, the claimed subject matter that is met by Wilson et al(Wilson) includes:
- 1) the claimed sensor, and interface unit are met by the various sensors and detectors and as well the PC interface unit(12, figure 2, column 9, lines 27 et seq).
 - Wilson does not show:
 - 1) the claimed server.

Since the system of Wilson is monitored and controlled via computer interface, it would have been obvious to one of ordinary skill in the art at the time the invention was made to incorporate a server into the system of Wilson, since a server would have been necessary to effectively monitor and operate the computerized system.

-- Claims 31-50 recite subject matter that was met as discussed in claim 31 above.

Application/Control Number: 09/317235 Page 3

Art Unit: 2736

-- Claims 1-30 recite methods that are met with regards to the discussion of the apparatus of claim 31 above.

Conclusion

3. Any response to this action should be mailed to:

Commissioner of Patents and Trademarks

Washington, D.C. 20231

. or faxed to:

(703) 308-9051(for formal communications intended for entry)

Or:

(703) 305-3988(for informal or draft communications, please label "PROPOSED" or "DRAFT")

Hand-delivered responses should be brought to Crystal Park II, 2121 Crystal Drive, Arlington. VA., Sixth Floor (Receptionist).

4. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Daryl C. Pope whose telephone number is (703) 305-4838. The examiner can normally be reached on M-Th from 8:30 to 6:00. The examiner can also be reached on alternate Fridays from 8:30 to 5:00 since the examiner works on a flex-time schedule in which every other Friday is the examiner's day off.

Art Unit: 2736

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Jeff Hofsass, can be reached on (703) 305-4717. The fax phone number for the organization where this application or proceeding is assigned is (703) 305-3988.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is (703) 305-8576.

Daryl C. Pope

Jan. 11, 2000

NOTICE OF DRAFTSPERSON'S WAIVEN DRIWAND TRATAGET OF TRANSCERS

The drawing(s) filed (insert date) 6 240 are:	Carroban Adminimation - 3/CFR LBB
A. approved by the Draftsperson under 37 CFR 1.84 or 1.152. B. objected to by the Draftsperson under 37 CFR 1.84 or 1.152 for the resubmission of new, corrected drawings when necessary. Corrected drawing meaning in the control of	
me and telephone number of a person to call if the Office	
1. DRAWINGS: 37 CFR 1.84(a): Acceptable categories of drawings. Another of the property of the	Words do not appear on a horizontal, left to right fashion when page is either upright or turned so that the top becomes the right side, except for graphs. Fig(s)
Photographs not properly mounted (must use brystol board or photographic double-weight paper). Fig(s)	reproduction. Fig(s) 10. CHARACTER OF LINES, NUMBERS, & LETTERS.
Poor quality (half-tone). Fig(s) 3. TYPE OF PAPER. 37 CFR 1.84(e) Property Paper, not flexible, strong, white, and durable; night regardent before Fig(s) Fig(s) Fragues, alterations, overwritings, interfficients, and continuous all	37 CFR 1.84(i) Lities numbers & letters not uniformly thick and well defined, clean, durable, and black (poor line quality). Fig(s)
Mylar, velum paper is not acceptable (too thin) or hote grant to note Fig(s) 4. SIZE OF PAPER. 37 CFR 1.84(f): Acceptable sizes: 21.0 cm by 29.7 cm (DIN size A4)	
21.6 cm by 27.9 cm (8.1/2 x 11 inches) All drawing sheets nor the same size is 15000 from the same size is 15000	Fig(s)
Drawings sheets not an acceptable size. Fig(s) 5. MARGINS. 37 CFR 1.84(g): Acceptable margins: Top 2.5 cm Left 2.5cm Right 1.5 cm Bottom 1.0 cm	Figure legends are poor. Fig(s) Numbers and reference characters not oriented in the Same direction as the view. 37 CFR 1.84(p)(1) Fig(s)
SIZE: A4 Size Top 2.5 cm Left 2.5 cm Right 1.5 cm Bottom 1.0 cm (1940 1941 1940 1940 1940 1940 1940 1940	
6. VIEWS. 37 CFR 1.84(h) REMINDER: Specification may require revision to correspond to drawing changes. Partial views. 37 CFR 1.84(h)(2) Brackets needed to show figure as one entity. Fig(s)	Lead line's cross each other. Fig(s) Lead lines missing. Fig(s) 14. NUMBERING OF SHEETS OF DRAWINGS. 37 CFR 1.84(t) Sheets not numbered consecutively, and in Arabic numerals beginning with number 1. Sheet(s) 15. NUMBERING OF VIEWS. 37 CFR 1.84(u)
Views not labeled separately or properly. Fig(s) Enlarged view not labeled separetely or properly.	Views not numbered consecutively, and in Arabic numerals, beginning with number 1. Fig(s) 16. CORRECTIONS. 37 CFR 1.84(w) Corrections not made from prior PTO-948
Fig(s) 7. SECTIONAL VIEWS. 37 CFR 1.84 (h)(3) Hatching not indicated for sectional portions of an object. Fig(s) Sectional designation should be noted with Arabic or Roman numbers. Fig(s)	dated 17. DESIGN DRAWINGS. 37 CFR 1.152 Surface shading shown not appropriate. Fig(s) Solid black shading not used for color contrast. Fig(s)
COMMENTS	
REVIEWER DATE 71	7199 TELEPHONE NO.
ATTACHMENT TO PAPER NO	

Nation of Defendance Oited		09/317,235 SANDE			LMAN ET AL		
,	Notice of References Cited		Examiner DARYL 0	· · · · · · · · · · · · · · · · · · ·		rt Unit 736 Page 1 of 1	
	April (U.	S. PATENT DOCUMENTS	······································			
	DOCUMENT NO.	DATE		AME		CLASS	SUBCLASS
А	5,400,246	3/1995	WILSO	ON ET AL		340	825.06 X
В							
С							
D							
E		-				,	
F			:				
G	,					t ;	·
н				•			-
1							ميهادر الم
J							
к							
L							
М							
		FOR	EIGN PATENT DOCUME	NTS			
	DOCUMENT NO.	DATE	COUNTRY	NAI	ΛE	CLASS	SUBCLASS
N	,						
0			4				
P							
Q							
R				, , , , , , , , , , , , , , , , , , , ,			
s							
Т							
		. NO	N-PATENT DOCUMENT	s			
		DOCUMENT (Including A	uthor, Title, Source, and Pert	inent Pages)			DATE
υ						٠.	
V							
w							
x							
			•				
Patent ar	nd Trademark Office ? (Rev. 9-95)		ice of References Cit		· Part o		

Petitioner Alarm.com Exhibit 1202 1202.0071

	Application No. 09/317,235	Applicant(s)	SANDELMAN		
Interview Summary	Examiner DARYL C. POPE		Group Art Unit 2736		
All participants (applicant, applicant's representative, PTO p	personnel):				
(1) DARYL C. POPE	(3) <u>DAVID SANI</u>	DELMAN			
(2) BARRY NEGRIN	(4)				
Date of Interview May 11, 2000					
Type: ☐Telephonic Maersonal (copy is given to	applicant ap⊠ican	's represen	tative).		
Exhibit shown or demonstration conducted: Yes	📆. If yes, brief descrip	ion:			
Agreement _was reached. Was not reached. Claim(s) discussed: 1, 31, 51, and 52					
Identification of prior art discussed: WILSON ET AL(5,400,246)					
THE MESSAGE PROFILES BEING USER DEFINABLE AN REPRESENTATIVE THAT THESE LIMITATIONS APPEAR					
(A fuller description, if necessary, and a copy of the amend the claims allowable must be attached. Also, where no cop is available, a summary thereof must be attached.)					
1. 🖄 It is not necessary for applicant to provide a separa	ate record of the substa	nce of the ir	nterview.		
Unless the paragraph above has been checked to indicate OFFICE ACTION IS NOT WAIVED AND MUST INCLUDE T 713.04). If a response to the last Office action has already INTERVIEW DATE TO FILE A STATEMENT OF THE SUBS	THE SUBSTANCE OF T been filed, APPLICANT	HE INTERV IS GIVEN	IEW. (See MPE	P Section	
 Since the Examiner's interview summary above (in each of the objections, rejections and requirement claims are now allowable, this completed form is conflict of office action. Applicant is not relieved from providing also checked. 	s that may be present in considered to fulfill the re	the last Of esponse rec	fice action, and s juirements of the	since the last	
Examiner Note: You must sign and stamp this form unless it is an attack	hment to a signed Office acti	on.		ARY EXAMINER RT UNIT 2736	
. s. Patent and Trademark Office PTO-413 (Rev. 10-95) Inter	view Summary		F	Paper No4	

Petitioner Alarm.com Exhibit 1202 1202.0072

LEVISOHN, LERNER, BERGER LANGSAM

757 THIRD AVENUE SUITE 2400 NEW YORK, NEW YORK 10017

212-486-7272

FACSIMILE: 212-486-0323

Bnegrin@LLBL.com

FACSIMILE TRANSMISSION

TO:	U.S. Patent and Trademark Office	FAX NO.:	703-305-3988	
ATTN:	Examiner Darryl Pope	Ser. No.:	09/317,235	
FROM:	Barry E. Negrin LEVISOHN, LERNER, BERGER & LA	ANGSAM	URGENT	
DATE:	05/04/00	Inventor:	Sandelman et al.	
	INCLUDING THIS COVER SHEET: 17 RMATION BY MAIL TO FOLLOW - 🗆 Y	ES- N NO		1
comprision application	FICATE OF FAX TRANSMISSION: I he age Proposed Amendment for Interview Purpoon, are being submitted and facsimile transmitted 305-3988 on May 4, 2000. By: Barry E. Negrin, 1	oses Only, for the ab	ove-referenced patent	
PLEASE	NOTE OUR FACSIMILE NUMBER (21)	2) 486-0323, Wi	HICH AUTOMATICALLY	
RECEIV	ES GROUP 1, 2 AND 3 TRANSMISSIO	NS. IF YOU HAY	VE NOT RECEIVED ALL C)
THE PA	GES, PLEASE CALL THE TELECOMMU	NICATOR AT (2	12) 486-7272	
IMMED	IATELY.			
TELECO	OMMUNICATOR: BEN			

CONFIDENTIALITY NOTE

The documents accompanying this facsimile transmission contain information from the law firm of LEVISOHN, LERNER, BERGER & LANGSAM which is confidential or privileged. The information is intended to be for the use of the individual or entity named on this transmission sheet. If you are not the intended recipient, be aware that any disclosure, copying, distribution, or use of the contents of this faxed information is prohibited. If you have received this facsimile in error, please notify us by telephone immediately so that we can arrange for the retrieval of the original documents at no cost to you.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

Sandelman, David et al.

Serial No.:

09/317,235

Filing Date:

May 24, 1999

For:

Electronic Message Delivery System Utilizable in the Monitoring of Remote Equipment and Method of Same (as amended herein)

Examiner:

Pope, D.

Art Unit:

2736

Attorney Docket No.:

1216.034

Patent

DRAFT

ATTENTION: EXAMINER DARRYL POPE

VIA FACSIMILE: 703-305-3988 Assistant Commissioner for Patents Washington, DC 20231

PROPOSED AMENDMENT FOR INTERVIEW PURPOSES ONLY

In the Title: Before "EQUIPMENT" insert -REMOTE-.

In the Claims:

- 1. (Amended) A method of monitoring remote equipment comprising the steps of:
- a) determining a state of at least one parameter of at least one piece of the remote equipment;
- b) communicating [messages regarding] a message indicative of the state from the piece of remote equipment to a computer server [central location] as an incoming message[s]; [and]
- c) enabling a user to remotely configure or modify a user-defined message profile containing outgoing message routing instructions, the user-defined message profile being storable on the computer server;

15

d) determining whether an incoming message is an incoming exception message indicative of improper operation of the piece of remote equipment;

[c)]e) if it is determined in step d) that an incoming message is an incoming exception message, forwarding at least one outgoing exception message[s] based on the incoming message[s] to at least one user-defined communication device specifiable in the user-defined message profile.

wherein the user can remotely configure or modify the user-defined message profile by remotely accessing the computer server.

- 2. (Amended) A method according to Claim 1, wherein said step b) further comprises the step of communicating [the] a plurality of incoming messages to the computer server [central location] via one of a plurality of different communication media.
- 3. (Amended) A method according to Claim 2, further comprising the step of [d)] normalizing the incoming messages into a uniform format to create normalized messages, wherein the outgoing exception messages are generated based on the normalized messages.
- 5. (Amended) A method according to Claim 1, wherein step (e) further comprises [comprising] the step of [e)] determining whether an incoming message is [an incoming exception message or] a normal status message indicative of proper operation of the piece of remote equipment.

Kindly cancel Claims 6-8 without prejudice or disclaimer.

9. (Amended) A method according to Claim [8] 1, wherein [said step h)] the remote configuring or modifying of the message profile enabled in step c) is performed by the user via the Internet.

5

- 10. (Amended) A method according to Claim [8] 1, wherein [step g)] the remote configuring or modifying of the message profile enabled in step c) further comprises the steps of:
- 1) selecting at least one type of user-defined communication device to which outgoing exception messages are to be forwarded;
- 2) selecting specific user-defined communication devices of the types selected in step 1); and
 - 3) determining the content of the outgoing exception messages forwarded in step [c)] d),
- 11. (Amended) A method according to Claim 5, wherein if the incoming message is determined in step [e] <u>d</u>) to be a normal status message from the remote equipment indicating proper operation of the equipment, the method further comprises the step of i) storing the normal status message in a normal status memory.
- 12. (Amended) A method according to Claim 11, further comprising the steps of:
- j) providing a main list <u>having information identifying</u> [of] all pieces of <u>the</u> remote equipment being monitored;
- k) comparing the <u>contents of the</u> normal status memory with the main list to determine [which pieces of remote equipment did not communicate] <u>whether</u> a normal status message <u>was</u> not communicated within a predetermined period of time for any pieces of the remote equipment <u>being monitored</u>; and
- l) generating an outgoing exception message in accordance with the message profile for each piece of equipment identified in step k) as not having sent a normal status message.

Kindly cancel Claims 13 and 14 without prejudice or disclaimer.

15. (Amended) A method according to Claim [14] 1, wherein the computer server [central location] includes a [computer] database in which a plurality of message profiles may be stored, and [said step h)] wherein the remote configuring or modifying of the message profile enabled in step c) is performed by the user via the Internet.

Kindly cancel Claim 16 without prejudice or disclaimer.

- 17. (Amended) A method according to Claim 1, wherein the <u>at least one remote</u> communication devices <u>specifiable by the message profile</u> include at least one of a facsimile machine, an e-mail <u>receiving device [account]</u>, a cellular telephone, a beeper, a pager, a PCS device, and a telephone.
- 18. (Amended) A method according to Claim 2, wherein the <u>plurality of communication</u> media of step b) includes at least one of a cellular telephone network, radio transmissions, telephone lines, and the Internet.
- 19. (Amended) A method according to Claim [13] 1, wherein step [c)] e) further comprises forwarding multiple outgoing exception messages to multiple user-defined communication devices in response to a single incoming message in accordance with the user-defined message profile.
- 20. (Amended) A method according to Claim [13] 1, wherein step [c)] e) further comprises forwarding a single outgoing exception message to a user-defined communication device in response to multiple incoming messages in accordance with the user-defined message profile.

21. (Amended) A method according to Claim [13] 1, further comprising the step of [m)] storing a plurality of user-defined message profiles on [at] the computer server [central location].

Kindly cancel Claims 22-24 without prejudice or disclaimer.

- 26. (Amended) A method according to Claim 1, wherein said step b) further comprises the step of communicating in the incoming message an identification code of the piece of remote equipment to which the incoming message pertains [in the incoming messages].
- 27. (Amended) A method according to Claim 26, wherein said step [c)] e) further comprises the step of forwarding the identification code in the outgoing exception message to the at least one user-defined communication device in accordance with the user-defined message profile.
- 28. (Amended) A method according to Claim [7] 1, wherein step [g)] c) further comprises the step of enabling selection of different user-defined communication devices to receive outgoing exception messages at different time periods in accordance with the message profile, the message profile being definable to have the exception messages forwarded to different specified remote communication devices at different times.
- 30. (Amended) A method according to Claim [11] 5, [further comprising the step of forwarding] wherein each normal status message includes operational information concerning the piece of remote equipment to which the [embedded within a] normal status message pertains.
- 31. (Amended) A system for monitoring remote equipment, comprising:

 a sensor in <u>local</u> communication with a piece of remote equipment, said sensor detecting

 a state of at least one parameter of the piece of remote equipment;

10

15

an interface unit, <u>locally</u> connected to said sensor, said interface unit having a message generating mechanism; and

a [central] computer server in <u>remote</u> communication with said interface unit, said server adapted to receive messages generated by said interface unit, <u>said computer server having a user interface</u>, a user being capable of remotely accessing said computer server via said user interface to remotely configure a user-defined message profile containing outgoing message routing instructions,

wherein when said sensor detects an exception condition in the piece of remote equipment, said interface unit generates an incoming exception message <u>indicative of the exception condition</u> and forwards said message to said server,

and wherein said server forwards at least one outgoing exception message to at least one predetermined user-defined remote communication device based on said incoming exception message as specified in said user-defined message profile.

- 32. (Amended) A system according to Claim 31, wherein said message generating mechanism of the interface unit forwards said incoming exception messages to said computer server via at least one of a plurality of communication media, said media comprising at least one of a cellular telephone network, radio transmissions, telephone lines, and the Internet.
- 35. (Amended) A system according to Claim 31, said system monitoring a plurality of pieces of equipment, each piece having an identification code, said server further comprising:
- a first memory on which equipment identification codes of all monitored equipment are stored;

a second memory in which communication device identification codes of all of said userdefined communication <u>remote</u> devices are stored, said communication device identification codes being configured in <u>a plurality of said</u> user-defined message profiles.

- 36. (Amended) A system according to Claim 35, wherein said [server further comprising a] user interface [remotely accessible by users and] is in communication with said second memory[, wherein] so that users can create or edit said user-defined message profiles remotely from said server.
- 37. (Amended) A system according to Claim 36, wherein said user interface enables a user to configure a user-defined message profile to select at least one type of [user-defined] communication device to which outgoing exception messages are to be forwarded, select specific user-defined communication devices of the types selected, and determine the content of said outgoing exception messages forwarded by said server to said user-defined communication devices.
- 38. (Amended) A system according to Claim 31, wherein said <u>remote</u> [user-defined] communication devices include [communication devices including] at least one of a facsimile machine, an e-mail <u>receiving device</u> [account], a cellular telephone, a beeper, a pager, a PCS device, and a <u>land line</u> telephone.
- 39. (Amended) A system according to Claim 35, wherein said interface unit periodically generates a normal status message if said sensor to which said interface unit is connected detects a normal status condition indicative of proper operation of [its] said respective piece of equipment to which said sensor is connected [is functioning properly], said normal status message including an equipment identification code of said respective piece of equipment.
- 40. (Amended) A system according to Claim 39, said server further [comprises] comprising:
 - a third memory for storing said normal status messages;

10

[means for comparing the normal status memory with the main list and for identifying] a comparator processor in communication with said first and third memories adapted to identify which of said pieces of monitored remote equipment having an identification code stored in said first memory did not communicate a normal status message stored in said third memory within a predetermined period of time; and

[means for generating and forwarding] a server message generator in communication with said comparator processor adapted to generate an outgoing exception message for each piece of equipment identified by said [comparing and identifying means] comparator processor, said outgoing exception message being forwarded by said server to at least one of said user-defined communication devices specified by [in accordance with] at least one of said user-defined message profiles.

- 42. (Amended) A system according to Claim 35, said interface unit comprising a plurality of <u>remote</u> interface units, wherein each of said plurality of <u>remote</u> interface units is <u>locally</u> respectively connected to a single piece of said <u>remote</u> pieces of equipment.
- 43. (Amended) A system according to Claim 35, said interface unit comprising a plurality of remote interface units, wherein each of said plurality of interface units is locally connected to a plurality of sensors which are in turn respectively connected to a number of said remote pieces of equipment.
- 44. (Amended) A system according to Claim 35, wherein said user-defined message profiles are each <u>remotely</u> configurable <u>by a user</u> to cause said server to forward a plurality of said outgoing exception messages in response to receipt of a single incoming exception message <u>in accordance with the user-defined message profile</u>.

- 45. (Amended) A system according to Claim 35, wherein said user-defined message profiles are each <u>remotely</u> configurable <u>by a user</u> to cause said server to forward a single of said outgoing exception messages in response to receipt of multiple incoming exception messages <u>in accordance with the user-defined message profile</u>.
- 46. (Amended) A system according to Claim 40, wherein said [outgoing exception message generating and forwarding means] computer server is adaptable to forward a plurality of said outgoing exception messages for each piece of equipment identified by said [comparing and identifying means] comparator processor in accordance with the user-defined message profile.
- 48. (Amended) A system according to Claim 47, wherein said outgoing exception message comprises exception information and identification information concerning said piece of remote equipment to which said normal status message pertains.
- 49. (Amended) A system according to Claim 39, wherein said normal status message further comprises operational information of said piece of remote equipment to which said normal status message pertains.
- 50. (Amended) A system according to Claim 40, <u>said computer server</u> further comprising a fourth memory upon which outgoing exception messages are stored.

Kindly add the following new claims.

- -51. A method for monitoring remote equipment comprising the steps of:
- a) determining a state of at least one parameter of at least one piece of the remote equipment;
- b) communicating a message indicative of the state to a computer server as an incoming message, the incoming message having a respective incoming format;

15

20

5

- c) normalizing the incoming message to form a corresponding normalized message having a predetermined uniform format;
- d) storing the normalized message in a normalized message database on the computer server;
- e) determining from the incoming message whether at least one exception message related to the incoming message is to be sent to at least one remote communication device specified by a plurality of message profiles stored at the computer server;
- f) if it is determined in step e) that at least one exception message related to the incoming message is to be sent, deriving the at least one exception message from the stored normalized message corresponding to the related incoming message and the message profiles, the at least one exception message derived thereby having a respective format suitable for reception by the at least one remote communication device to which the at least one exception message is to be sent; and
- g) sending the at least one exception message derived in step f) to the at least one remote communication device specified by the message profiles,

wherein the message profiles may be created or modified at least in part by a user by remote access of the computer server.

52. A system for monitoring remote equipment, comprising:

a sensor in communication with a piece of the remote equipment for detecting the state of at least one parameter thereof;

an interface unit, coupled to said sensor, said interface unit having a message generating mechanism for generating messages indicative of the state of the at least one parameter of the piece of the remote equipment; and

a computer server in communication with said interface unit, said server comprising:
a message interface for receiving messages generated by said interface unit;

a message normalizer for normalizing each one of the messages received from the interface unit to form corresponding normalized messages having a predetermined uniform format;

a normalized message database for storing normalized messages, including normalized messages from the message normalizer;

15

a message profile database for storing a plurality of message profiles;

a message processor for determining from each one of the messages received from the interface unit whether at least one exception message related to the received message is to be sent to at least one remote communication device specified by the message profiles;

20

an exception message generator for deriving the at least one exception message determined to be sent by the message processor to the at least one remote communication device, the at least one exception message being derived from a normalized message corresponding to the related message received from the interface unit and the message profiles, the at least one exception message derived thereby having at least one respective format suitable for reception by the at least one remote communication device to which the at least one exception message is to be sent;

25

a message interface for sending the at least one exception message derived by the exception message generator to the at least one remote communication device specified by the message profiles; and

a user interface for enabling a user at a remote location to create or modify at least a portion of the message profiles in the message profile database,

wherein when said sensor detects an exception condition in the piece of remote

30

wherein when said sensor detects an exception condition in the piece of remote equipment, said interface unit generates an incoming message indicative of the exception condition and forwards said message to said server.—

REMARKS

These proposed amendments are being submitted <u>for interview purposes only</u>. The gist of the claim amendments can be found in Claims 1 and 31; the remaining claims have, by and large, been amended for proper antecedency/dependency reasons. New claims 51 and 52 are of slightly different scope from Claims 1 and 31. No new matter has been added.

The invention is an electronic message delivery system for monitoring <u>remote</u> equipment, receiving signals from the remote equipment based on the status of the equipment, and sending outgoing messages to the appropriate parties and their various communication devices based on the messages received. The invention includes sensors locally connected to the remote equipment, interface units locally connected to the sensors, and a computer server that can receive messages from the remote interface units based on the readings of the sensors. The interface units are <u>not</u> hardwired into the central server, they communicate via <u>remote</u> means, such as via the cellular telephone network or the Internet.

One of the critical aspects of the invention is that the server includes a <u>user interface</u> which allows each user to <u>remotely</u> configure the server by configuring (creating, modifying, deleting, etc.) a message profile. The message profile is essentially a set of instructions that tells the server any or all of the following: a) to whom to route outgoing messages; b) which messages get routed to which person; c) to what communication devices the messages are routed (fax, pager, e-mail, etc.); d) if there should be a time delay before routing the messages; e) if several incoming messages should be received before sending out an outgoing message; f) if one incoming message should trigger the sending of several outgoing messages; and the like. The user can, from his home, his office, his Palm Pilot, or any other location that is <u>remote</u> from the computer server, connect with the server via the interface and reconfigure his message profile. In the preferred embodiment, the user interface is an Internet link which enables the user to access from a remote computer and create or edit his message profile. Passwords are provided so that a user's profile can only be edited by the proper person (i.e., the user).

An example of how the system is implemented is in the heating, ventilating, and cooling (HVAC) arts. Contractors and maintenance workers have to be able to monitor the equipment they are responsible for; however going around to all the boilers and air conditioners in their care just to check up on them is very time consuming. With the present system, sensors are locally attached—on site— to the air conditioner, for example, which can detect when specific problems occur. In the preferred embodiment, an interface unit is connected—also on site— to the sensors. When the sensors detect an abnormal condition—such as a lack of fan blower speed even though the air conditioner should be working—they send a signal to the interface unit. The interface unit can remotely access, via a national wireless network, for example, the computer server utilizing, for example, the handshaking portion of the cellular network. Thus, the interface unit and the computer server can be thousands of miles away and still communicate effectively.

The server receives the incoming message from the remote interface unit that the air conditioner's fan is not operating. On the computer is stored a user-defined message profile, which is like a laundry list of message routing instructions such as "if X goes wrong, tell Mr. Y via his pager/fax machine/e-mail, etc." For example, if the fan is not blowing in an air conditioner, there could be a blockage which is physically preventing the fan blades from turning, or there could be an electrical short preventing current from flowing to the fan motor, or several other possible problems. A contractor could have his message profile set up to notify one of his crew by sending the crewman a message. Connected to the server are a number of message output mechanisms that can send a message over a variety of different media as specified by the message profile. The crewman could get a beep or a message on his pager or could receive an e-mail for a lower priority problem. The contractor/supervisor could also receive a message so that he can check up on his crew.

Some messages require more attention than others. For example, if the trouble with the air conditioner were so serious as to threaten the whole building, the crewman, the contractor, and the owner of the building could be sent messages via their pagers. The contractor would be able to make the determination as to which problems require which messages and who should

hear about it. The interface units also send out periodic "heartbeat" signals which let the server know that everything is okay. The server is designed to route messages from multiple pieces of equipment to multiple people in accordance with multiple message profiles. That is, a number of different contractors can use the system independently of each other.

The Examiner cited Wilson et al. (USP. No. 5,400,246) as rendering obvious the claimed invention. Applicant disagrees for several reasons. First, there is absolutely no teaching, suggestion, or even a hint in Wilson of enabling a user to remotely configure a message profile on the computer server. The system of Fig. 12, for example, can send voice messages or faxes out to a recipient (see col. 34, lines 6-15), but it cannot receive instructions remotely from the intended message recipients. More specifically, Wilson does not permit a remote user to configure a message profile to specify where the outgoing messages are to be sent. There is absolutely no remote user interface in Wilson as recited and set forth in the claims of the present application. Wilson does discuss enabling the user to configure the system for a particular application (see Abstract, cols. 9-11 generally and col. 10, line 67 and on, in particular), but not remotely. In this description, the user must be sitting down at the central PC 12 in order to effect any changes on the system whatsoever. Thus, in Wilson, the "user" is the person who is setting up the system. Thus, while the "user" can go to the central computer and configure the system, he cannot do it from home, the office, or in the field. Remote communication between user and system is thus unidirectional, from the system to the user.

In Applicant's invention, by contrast, the user, as recited in the claims, is the person subscribing to the service, the person intended to receive the messages. He can log into the server via remote means, such as the Internet, to configure his message profile to tell the computer server where to send what error messages to whom and under what circumstances. Remote communication between the subscriber/user and the system is thus bidirectional: from the system to the user when the system is sending an error message, and from the user to the system when the user is creating/editing the message profile (among other things). Also, in Wilson, only a computer programmer can alter or modify any instructions on the computer; by

contrast, in Applicant's invention, the end user, not the programmer setting the system up, can adjust the message profile without any knowledge of computer programming.

Wilson also fails to teach or suggest the monitoring of <u>remote</u> equipment. All of the equipment being monitored in Wilson is <u>hardwired</u> into the system and is monitored <u>locally</u>. All of the various systems in Wilson require the I/O bridge device 14 into which all of the monitored equipment is directly wired. For example, Fig. 2 of Wilson shows an alarm system with smoke detectors 66 and 67 and burglar alarm loops 62 and 64. All of the devices are connected <u>via</u> <u>wires</u> to I/O bridge device 14 (see col. 9, lines 40-55). The equipment being monitored is not remote equipment, as required by the present claims, but rather <u>local</u> equipment.

Even the system shown in Fig. 12 of Wilson is only good for monitoring <u>local</u> equipment despite the presence of radio transceivers. As described in columns 33 and 34 of Wilson, Fig. 12 represents an alarm system for a car dealership lot. Instead of using wires to connect the anti-theft devices to the base transceiver 700, each car is provided with an RF transmitter which can broadcast back to the main base. However, what is described is a <u>local RF network only</u>. It is designed to cover the parking lot of an automobile dealer (see col. 34, lines 46-61), or a range of maybe a few thousand feet. Applicant's invention can monitor equipment that is truly remote, and it can be used over the entire world, because of: a) the ability of the remote interface units to contact the central server remotely; b) the ability of the central server to contact the message recipient remotely via any format of communication device, and c) the ability of the user/subscriber to contact the server and configure his message profile remotely.

Finally, Wilson fails to teach that multiple subscribers can utilize the system simultaneously. The inventive system can store multiple message profiles of multiple subscribers and route the messages from each person's equipment to that person in accordance with his message profile. By contrast, Wilson is silent as to accommodating multiple users.

U.S. Appl'n No. 09/317,235 Proposed Amendment FOR INTERVIEW PURPOSES ONLY

Applicant and the undersigned are willing to meet with the Examiner for an interview if this draft amendment is not entirely acceptable. Otherwise, an early Notice of Allowance is respectfully requested.

Date: May 4, 2000

Levisohn, Lerner, Berger & Langsam 757 Third Avenue, Suite 2400 New York, New York 10017 (212) 486-7272

F:\ARCHIVE\Barry\WPDOCS\PROSEC\1216-34propamdt.wpd

Respectfully submitted,

Barry B. Negrin

Reg. No.: 37,407

Attorney for Applicant

COMBINED AMENDMENT & PETITION FOR EXTENSION OF TIME UNDER 37 CFR 1.136(a) (Small Entity) Docket No. 1216,0347							
In Re Application	n Of. Sandelman, Dav	id et al.			M. ASS		
Serial No,	Group Art Unit						
09/317,255		g Date 4, 1999	Daryl Pope		2736		
Invention: Electronic Message Delivery System Utilizable in the Monitoring of Remote Equipment and Method of							
Same RECEIV							
TO THE ASSISTANT COMMISSIONER FOR PATENTS: This is a combined amendment and petition under the provisions of 37 CFR 1.136(a) to extend the period for filing a response to the Office Action of Date							
The requested e	xtension is as follows (,	desired):				
⊠ One m	onth 🗆 Two m	onths 🗆 T	hree months 🔲 Fou	ır months	☐ Five months		
from:	4/20/00 Date		until:	5/20/00 Date	,		
A verified statement of small entity status as a small entity under 37 CFR 1.27: is enclosed. has already been filed in this application. The fee for the amendment and extension of time has been calculated as shown below:							
		CLAIMS A	AS AMENDED				
	CLAIMS REMAINING AFTER AMENDMENT	HIGHEST #	NUMBER EXTRA	RATE	ADDITIONAL FEE		
TOTAL CLAIMS	43 -	50 =		x \$9.0			
INDEP, CLAIMS	4 -	2 =	: 2	x \$39.	00 \$78.00		
			FEE FOR	AMENDME	NT \$78.00		
	ЛE \$55.00						
	лЕ \$133.00						

P28SMALL/REV03

COMBINED AMENDMENT & PETITION FOR EXTENSION OF TIME UNDER 37 CFR 1.136(a) (Small Entity)

Docket No. 1216.034

The	fee for the amendment a	and extension of tir	me is to be paid as foll	ows:	
\boxtimes	A check in the amount of	of \$133.00	for the amendment	and extension of time is	enclosed.
	Please charge Deposit A duplicate copy of this			mount of	
×	communication or cred A duplicate copy of this Any additional filing	it any overpaymen s sheet is enclosed ng fees required un	nt to Deposit Account I		ated with this
	If an additional extension which may be required	•	· •	s a petition therefor and A duplicate copy of thi	charge any additional fees s sheet is enclosed.
		4			
				• .	
Barry	Signatu E. Negrin, Esq. (Reg. No.	=	Dated:	May 17, 2000	•
Leviso 757 Tl New Y Feleph Facsin	ohn, Lerner, Berger & La hird Avenue - Suite 2400 York, New York 10017 none (212) 486-7272 nile (212) 486-0323			on 5/17/00 Express mail under 37 C. Assistant Commissioner 20231 Express mail Signature of Person	ent and fee is being deposited with the U.S. Postal Service as F.R. 1.8 and is addressed to the for Patents, Washington, D.C. label#FL470650785US Mailing/Correspondence s Rodriguez
CC:					Person Mailing Correspondence
					P28SMALL/REV03

	AMENDM INT & ME UNDER 37 CF					Docket No. 1216.034	
In Re Application	Of: Sandelman, Dav	id et al.		JP			
Serial No. Filing Date Examiner Group Art							
09/317,235	[™] 2736 →						
09/317,235 May 24, 1999 Daryl Pope 2736 Invention: Electronic Message Delivery System Utilizable in the Monitoring of Remote Equipment and Method of							
OTPE Sam						EIVED 23 2000	
TO THE ASSISTANT COMMISSIONER FOR PATENTS:							
This is a combined amendment and petition under the provisions of 37 CFR 1.136(a) to extend the period for filing a response to the Office Action of $\frac{1/20/00}{Date}$ in the above-identified application.							
I ne requested ex	tension is as follows (donth	·	desired): nree months □	Falls man	.	7 =:	
	4	onuis 🗀 ji		Four mon		Five months	
from: 4/20/00 until: 5/20/00 Date Date							
A verified statement of small entity status as a small entity under 37 CFR 1.27: is enclosed. has already been filed in this application. The fee for the amendment and extension of time has been calculated as shown below:							
		CLAIMS A	S AMENDED				
	CLAIMS REMAINING	HIGHEST#	NUMBER EXT	DΛ	· · · · · · · · · · · · · · · · · · ·	ADDITIONAL	
	AFTER AMENDMENT	PREV. PAID FOR		F	RATE	FEE	
TOTAL CLAIMS	43 -	50 =		x	\$9.00	\$0.00	
INDEP. CLAIMS	4 -	2 _ =	2	x	\$39.00	\$78.00	
FEE FOR AMENDMENT \$78.00							
FEE FOR EXTENSION OF TIME \$55.00							
TOTAL FEE FOR AMENDMENT AND EXTENSION OF TIME \$133.00							
		·				,	

COMBINED AMENDMENT & PETITION FOR EXTENSION OF TIME UNDER 37 CFR 1.136(a) (Small Entity)	Docket No. 1216.034		
MAY 1 7 2000 H			
The fee for the amendment and extension of time is to be paid as follows:	75		
□ A check in the amount of \$133.00 for the amendment and extension of the amendment	f time is enclosed.		
☐ Please charge Deposit Account No. in the amount of A duplicate copy of this sheet is enclosed.	23. 23.		
 ☑ The Commissioner is hereby authorized to charge payment of the following fees communication or credit any overpayment to Deposit Account No. 02-2105 A duplicate copy of this sheet is enclosed. ☑ Any additional filing fees required under 37 C.F.R. 1.16. ☑ Any patent application processing fees under 37 CFR 1.17. 	associated with this a		
 If an additional extension of time is required, please consider this a petition there which may be required to Deposit Account No. A duplicate cop	for and charge any additional fees by of this sheet is enclosed.		
2000 WKOROMA 00000015 09317235 215 55.00 QP 7 8.00 GP 4	•		
	,		
757 Third Avenue - Suite 2400 New York, New York 10017 Telephone (212) 486-7272 Facsimile (212) 486-0323	s document and fee is being deposited with the U.S. Postal Service as der 37 C.F.R. 1.8 and is addressed to the lesioner for Patents, Washington, D.C. s mail label#FL470650785US Of Person Mailing Correspondence		

月 FC: 岩·FC:

cc: ·

P28SMALL/REV03

Lourdes Rodriguez

Typed or Printed Name of Person Malling Correspondence



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re: application of: Sandelman, David et al.

Serial No.:

09/317,235

Filing Date:

May 24, 1999

For:

Electronic Message Delivery System Utilizable

in the Monitoring of Remote Equipment and

Method of Same (as amended herein)

Examiner:

Daryl Pope

Art Unit:

2736

Attorney Docket No.: 1216.034

Patent Application

RECEIVED
NAY 23 2000
RECEIVED

Assistant Commissioner For Patents Washington, DC 20231

TRANSMITTAL LETTER

Sir:

Enclosed herewith is an Amendment. Check for \$133.00. In the event of any deficiency in the fee due in connection with this transmittal, the Commissioner is authorized and directed to debit our deposit account No. 02-2105 for the amount of such deficiency.

Dated: May 17, 2000

Levisohn, Lerner, Berger & Langsam

757 Third Avenue, Suite 2400 New York, NY 10018 Respectfully submitted,

Barry E Negrin (Reg. No. 37,407)

Attorney for Applicant

Certificate of Mailing

I certify that this document and fee are being deposited with the U.S. Postal Service by Express Mail, addressed to Assistant Commissioner for Patents, Washington, DC 20231.

Lourdes Rodriguez

Mailing Date: May 17, 2000

Express Mail Label: EL470650785US

a



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

re application of: Sandelman, David et al.

Serial No.: 09/31/1,23:

Filing Date: May 24, 1999

For: Electronic Message Delivery

System Utilizable in the Monitoring of Remote Equipment and Method of

Same (as amended herein)

Examiner: Daryl Pope

Art Unit: 2736

Attorney Docket No.: 1216.034

Patent

5-33-00

RECEIVED
MAY 23 2000
TC 2700 MAIL ROOM

Assistant Commissioner for Patents Washington, DC 20231

AMENDMENT

Sir:

This Amendment is believed fully responsive to the Examiner's Office Action of January 20, 2000. Favorable reconsideration is respectfully requested. No new matter has been added. Applicant hereby petitions under 37 CFR § 1.136 for a **one month** extension of time extending the response period to **May 20, 2000**. Since Applicants and Applicants' assignee are both small entities, a check for the one-month extension fee of \$55 is enclosed.

Kindly amend the application as follows.

In the Title: Before "EQUIPMENT" insert -REMOTE-.

In the Claims:

(Amended) A method of monitoring remote equipment comprising the steps of:

00000015 03317835

50 JP 2

- a) determining a state of at least one parameter of at least one piece of <u>the</u> remote equipment;
- b) communicating [messages regarding] <u>a message indicative of</u> the state <u>from the piece</u> <u>of remote equipment</u> to a <u>computer server</u> [central location] as <u>an</u> incoming message[s]; [and]
- c) enabling a user to remotely configure or modify a user-defined message profile containing outgoing message routing instructions, the user-defined message profile being storable on the computer server;
- d) determining whether an incoming message is an incoming exception message indicative of improper operation of the piece of remote equipment;
- [c)]e) if it is determined in step d) that an incoming message is an incoming exception message, forwarding at least one outgoing exception message[s] based on the incoming message[s] to at least one user-defined communication device specifiable in the user-defined message profile.

wherein the user can remotely configure or modify the user-defined message profile by remotely accessing the computer server.

- 2. (Amended) A method according to Claim 1, wherein said step b) further comprises the step of communicating [the] a plurality of incoming messages to the computer server [central location] via one of a plurality of different communication media.
- 3. (Amended) A method according to Claim 2, further comprising the step of [d)] normalizing the incoming messages into a uniform format to create normalized messages, wherein the outgoing exception messages are generated based on the normalized messages.
- 5. (Amended) A method according to Claim 1, wherein step (e) further comprises [comprising] the step of [e)] determining whether an incoming message is [an incoming

as Out.

5

15



as Conld.

exception message or] a normal status message <u>indicative of proper operation of the piece of</u> remote equipment.

Kindly cancel Claims 6-8 without prejudice or disclaimer.

(Amended) A method according to Claim [8] 1, wherein [said step h)] the remote configuring or modifying of the message profile enabled in step c) is performed by the user via the Internet.

(Amended) A method according to Claim [8] 1, wherein [step g)] the remote configuring or modifying of the message profile enabled in step c) further comprises the steps of:

- 1) selecting at least one type of user-defined communication device to which outgoing exception messages are to be forwarded;
- 2) selecting specific user-defined communication devices of the types selected in step 1); and
 - 3) determining the content of the outgoing exception messages forwarded in step [c)] d).

(Amended) A method according to Claim 5, wherein if the incoming message is determined in step [e] <u>d</u>) to be a normal status message from the remote equipment indicating proper operation of the equipment, the method further comprises the step of () storing the normal status message in a normal status memory.

(Amended) A method according to Claim 2, further comprising the steps of:

(Amended) A method according to Claim 2, further comprising the steps of:

(Amended) A method according to Claim 2, further comprising the steps of:

(Amended) A method according to Claim 2, further comprising the steps of:

(Amended) A method according to Claim 2, further comprising the steps of:

(Amended) A method according to Claim 2, further comprising the steps of:

(Amended) A method according to Claim 2, further comprising the steps of:

3

N

B

5

B

A3 (1)

k) comparing the <u>contents of the</u> normal status memory with the main list to determine [which pieces of remote equipment did not communicate] <u>whether</u> a normal status message <u>was</u> not communicated within a predetermined period of time <u>for any pieces of the remote equipment</u> <u>being monitored</u>; and

l) generating an outgoing exception message <u>in accordance with the message profile</u> for each piece of equipment identified in step k) as not having sent a normal status message.

Kindly concel Claims 13 and 14 without prejudice or disclaimer.

af

(Amended) A method according to Claim [14] 1, wherein the computer server [central location] includes a [computer] database in which a plurality of message profiles may be stored, and [said step h)] wherein the remote configuring or modifying of the message profile enabled in step c) is performed by the user via the Internet.

Kindly cancel Claim 16 without prejudice or disclaimer.

(Amended) A method according to Claim 1, wherein the <u>at least one remote</u> communication devices <u>specifiable by the message profile</u> include at least one of a facsimile machine, an e-mail <u>receiving device</u> [account], a cellular telephone, a beeper, a pager, a PCS device, and a telephone.

45 10st.

18. (Amended) A method according to Claim 2, wherein the <u>plurality of communication</u> media of step b) includes at least one of a cellular telephone network, radio transmissions, telephone lines, and the Internet.



U.S. Appl'n No. 09/317,235 Amendment

A method according to Claim [13] 1, wherein step [c)] e) further (Amended) comprises forwarding multiple outgoing exception messages to multiple user-defined communication devices in response to a single incoming message in accordance with the userdefined message profile.

(Amended) A method according to Claim [13] 1, wherein step [c)] e) further comprises forwarding a single outgoing exception message to a user-defined communication device in response to multiple incoming messages in accordance with the user-defined message profile.

A method according to Claim [13] 1, further comprising the step of [m)] (Amended) storing a plurality of user-defined message profiles on [at] the computer server [central location].

Kindly cancel Claims 22-24 without prejudice or disclaimer.

17 26. (Amended) A method according to Claim 1, wherein said step b) further comprises the step of communicating in the incoming message an identification code of the piece of remote equipment to which the incoming message pertains [in the incoming messages].

18 21. A method according to Claim 26, wherein said step [c)] e) further (Amended) comprises the step of forwarding the identification code in the outgoing exception message to the at least one user-defined communication device in accordance with the user-defined message profile.

19 28. (Amended) A method according to Claim [7] 1, wherein step [g)] c) further comprises the step of enabling selection of different user-defined communication devices to receive outgoing exception messages at different time periods in accordance with the message profile,







the message profile being definable to have the exception messages forwarded to different specified remote communication devices at different times.

(Amended) A method according to Claim [11] 5, [further comprising the step of forwarding] wherein each normal status message includes operational information concerning the piece of remote equipment to which the [embedded within a] normal status message pertains.

21.

5

15

(Amended) A system for monitoring remote equipment, comprising:

a sensor in <u>local</u> communication with a piece of remote equipment, <u>said sensor detecting</u> a state of at least one parameter of the piece of remote equipment;

an interface unit, <u>locally</u> connected to said sensor, said interface unit having a message generating mechanism; and

a [central] computer server in <u>remote</u> communication with said interface unit, said server adapted to receive messages generated by said interface unit, <u>said computer server having a user interface</u>, a user being capable of remotely accessing said computer server via said user interface to remotely configure a user-defined message profile containing outgoing message routing instructions,

wherein when said sensor detects an exception condition in the piece of remote equipment, said interface unit generates an incoming exception message <u>indicative of the exception condition</u> and forwards said message to said server,

and wherein said server forwards at least one outgoing exception message to at least one predetermined user-defined remote communication device based on said incoming exception message as specified in said user-defined message profile.

(Amended) A system according to Claim 21, wherein said message generating mechanism of the interface unit forwards said incoming exception messages to said computer

8

90/

a



<u>server</u> via at least one of a plurality of communication media, said media comprising at least one of a cellular telephone network, radio transmissions, telephone lines, and the Internet.

(Amended) A system according to Claim 37, said system monitoring a plurality of pieces of equipment, each piece having an identification code, said server further comprising: a first memory on which equipment identification codes of all monitored equipment are stored;

a second memory in which communication device identification codes of all of said userdefined communication <u>remote</u> devices are stored, said communication device identification codes being configured in <u>a plurality of said</u> user-defined message profiles.

(Amended) A system according to Claim 35, wherein said [server further comprising a] user interface [remotely accessible by users and] is in communication with said second memory[, wherein] so that users can create or edit said user-defined message profiles remotely from said server.

(Amended) A system according to Claim 36, wherein said user interface enables a user to configure a user-defined message profile to select at least one type of [user-defined] communication device to which outgoing exception messages are to be forwarded, select specific user-defined communication devices of the types selected, and determine the content of said outgoing exception messages forwarded by said server to said user-defined communication devices.

26. (Amended) A system according to Claim 21, wherein said <u>remote</u> [user-defined] communication devices include [communication devices including] at least one of a facsimile machine, an e-mail <u>receiving device</u> [account], a cellular telephone, a beeper, a pager, a PCS device, and a <u>land line</u> telephone.

7

(Amended) A system according to Claim 35, wherein said interface unit periodically generates a normal status message if said sensor to which said interface unit is connected detects a normal status condition indicative of proper operation of [its] said respective piece of equipment to which said sensor is connected [is functioning properly], said normal status message including an equipment identification code of said respective piece of equipment.

(Amended) A system according to Claim 39; said server further [comprises] comprising:

a third memory for storing said normal status messages;

[means for comparing the normal status memory with the main list and for identifying] <u>a</u> comparator processor in communication with said first and third memories adapted to identify which of said pieces of <u>monitored</u> remote equipment <u>having an identification code stored in said</u> first memory did not communicate a normal status message <u>stored in said third memory</u> within a predetermined period of time; and

[means for generating and forwarding] a server message generator in communication with said comparator processor adapted to generate an outgoing exception message for each piece of equipment identified by said [comparing and identifying means] comparator processor, said outgoing exception message being forwarded by said server to at least one of said user-defined communication devices specified by [in accordance with] at least one of said user-defined message profiles.

(Amended) A system according to Claim 35, said interface unit comprising a plurality of remote interface units, wherein each of said plurality of remote interface units is locally respectively connected to a single piece of said remote pieces of equipment.

43. (Amended) A system according to Claim 35, said interface unit comprising a plurality of remote interface units, wherein each of said plurality of interface units is locally connected to

8

3)

az Zmal

10

ag Nort. a <u>plurality of sensors which are in turn respectively connected to a number of said remote</u> pieces of equipment.

(Amended) A system according to Claim 35, wherein said user-defined message profiles are each remotely configurable by a user to cause said server to forward a plurality of said outgoing exception messages in response to receipt of a single incoming exception message in accordance with the user-defined message profile.

(9 Md.

(Amended) A system according to Claim 35, wherein said user-defined message profiles are each remotely configurable by a user to cause said server to forward a single of said outgoing exception messages in response to receipt of multiple incoming exception messages in accordance with the user-defined message profile.

(Amended) A system according to Claim 40, wherein said [outgoing exception message generating and forwarding means] computer server is adaptable to forward a plurality of said outgoing exception messages for each piece of equipment identified by said [comparing and identifying means] comparator processor in accordance with the user-defined message profile.

(Amended) A system according to Claim 47, wherein said outgoing exception message comprises exception information and identification information concerning said piece of remote equipment to which said normal status message pertains.

(Amended) A system according to Claim 39, wherein said normal status message further comprises operational information of said piece of remote equipment to which said normal status message pertains.

^

10

(Amended) A system according to Claim 40, said computer server further comprising a fourth memory upon which outgoing exception messages are stored.

Kindly and the following new claims.

A method for monitoring remote equipment comprising the steps of:

- a) determining a state of at least one parameter of at least one piece of the remote equipment;
- b) communicating a message indicative of the state to a computer server as an incoming message, the incoming message having a respective incoming format;
- c) normalizing the incoming message to form a corresponding normalized message having a predetermined uniform format;
- d) storing the normalized message in a normalized message database on the computer server;
- e) determining from the incoming message whéther at least one exception message related to the incoming message is to be sent to at least one remote communication device specified by a plurality of message profiles stored at the computer server;
- f) if it is determined in step e) that at least one exception message related to the incoming message is to be sent, deriving the at least one exception message from the stored normalized message corresponding to the related incoming message and the message profiles, the at least one exception message derived thereby having a respective format suitable for reception by the at least one remote communication device to which the at least one exception message is to be sent; and
- g) sending the at least one exception message derived in step f) to the at least one remote communication device specified by the message profiles,

wherein the message profiles may be created or modified at least in part by a user by remote access of the computer server.

10

15

5

10

A system for monitoring remote equipment, comprising:

a sensor in communication with a piece of the remote equipment for detecting the state of at least one parameter thereof;

an interface unit, coupled to said sensor, said interface unit having a message generating mechanism for generating messages indicative of the state of the at least one parameter of the piece of the remote equipment; and

a computer server in communication with said interface unit, said server comprising:

a message interface for receiving messages generated by said interface unit;

a message normalizer for normalizing each one of the messages received from the interface unit to form corresponding normalized messages having a predetermined uniform format;

a normalized message database for storing normalized messages, including normalized messages from the message normalizer;

a message profile database for storing a plurality of message profiles;

a message processor for determining from each one of the messages received from the interface unit whether at least one exception message related to the received message is to be sent to at least one remote communication device specified by the message profiles;

an exception message generator for deriving the at least one exception message determined to be sent by the message processor to the at least one remote communication device, the at least one exception message being derived from a normalized message corresponding to the related message received from the interface unit and the message profiles, the at least one exception message derived thereby having at least one respective format suitable for reception by the at least one remote communication device to which the at least one exception message is to be sent;

a message interface for sending the at least one exception message derived by the exception message generator to the at least one remote communication device specified by the message profiles; and

11

34

a/15

20

a user interface for enabling a user at a remote location to create or modify at least a portion of the message profiles in the message profile database,

wherein when said sensor detects an exception condition in the piece of remote equipment, said interface unit generates an incoming message indicative of the exception condition and forwards said message to said server.-

REMARKS

Claims 1-50 were examined. Claims 1-50 were rejected under 35 U.S.C. § 103(a) as being unpatentable over U.S. Patent No. 5,400,246 to Wilson et al. On May 4, 2000, the undersigned submitted some proposed claim amendments in further of an interview. On May 11, 2000, the undersigned and the Examiner, Daryl Pope, had an in-person interview where the proposed claims were discussed. The above claim amendments are the same claims discussed on . May 11. The gist of the claim amendments can be found in Claims 1 and 31; the remaining claims have, by and large, been amended for proper antecedency/dependency reasons. New claims 51 and 52 are of slightly different scope from Claims 1 and 31. No new matter has been added. The Examiner indicated that it appeared that the independent claims, Claims 1 and 31 as well as newly added Claims 51 and 52 recited patentable subject matter. Applicants wholeheartedly thank the Examiner for taking the time and effort to review the proposed claim amendments and meet with them in the interview, and they appreciate the indication that the claims are likely patentable over the cited art.

The invention is an electronic message delivery system for monitoring remote equipment, receiving signals from the remote equipment based on the status of the equipment, and sending outgoing messages to the appropriate parties and their various communication devices based on the messages received. The invention includes sensors locally connected to the remote equipment, interface units locally connected to the sensors, and a computer server that can receive messages from the remote interface units based on the readings of the sensors. The

interface units are not hardwired into the computer server, they communicate via remote means, such as via the cellular telephone network or the Internet.

One of the critical aspects of the invention is that the server includes a user interface which allows each user to remotely configure the server by configuring (creating, modifying, deleting, etc.) a message profile. The message profile is essentially a set of instructions that tells the server any or all of the following: a) to whom to route outgoing messages; b) which messages get routed to which person; c) to what communication devices the messages are routed (fax, pager, e-mail, etc.); d) if there should be a time delay before routing the messages; e) if several incoming messages should be received before sending out an outgoing message; f) if one incoming message should trigger the sending of several outgoing messages; and the like. Essentially, the message profile tells the server the who, what, when, where, and how to send outgoing messages. The user can, from his home, his office, his Palm Pilot, or any other location that is remote from the computer server, connect with the server via the user interface and reconfigure his message profile. In the preferred embodiment, the user interface is an Internet link which enables the user to access from a remote computer and create or edit his message profile. Passwords are provided so that a user's profile can only be edited by the proper person (i.e., the user).

An example of how the system is implemented is in the heating, ventilating, and cooling (HVAC) arts. Contractors and maintenance workers have to be able to monitor the equipment they are responsible for; however going around to all the boilers and air conditioners in their care just to check up on them is very time consuming. With the present system, sensors are locally attached –on site– to the air conditioner, for example, which can detect when specific problems occur. In the preferred embodiment, an interface unit is connected -also on site- to the sensors. When the sensors detect an abnormal condition –such as a lack of fan blower speed even though the air conditioner should be working-they send a signal to the interface unit. The interface unit can remotely access, via a national wireless network, for example, the computer server utilizing,

for example, the handshaking portion of the cellular network. Thus, the interface unit and the computer server can be thousands of miles away and still communicate effectively.

The server receives the incoming message from the remote interface unit that the air conditioner's fan is not operating. On the computer is stored a user-defined message profile, which is like a laundry list of message routing instructions such as "if X goes wrong, tell Mr. Y via his pager/fax machine/e-mail, etc." For example, if the fan is not blowing in an air conditioner, there could be a blockage which is physically preventing the fan blades from turning, or there could be an electrical short preventing current from flowing to the fan motor, or several other possible problems. A contractor could have his message profile set up to notify one of his crew by sending the crewman a message. Connected to the server are a number of message output mechanisms that can send a message over a variety of different media as specified by the message profile. The crewman could get a beep or a message on his pager or could receive an e-mail for a lower priority problem. The contractor/supervisor could also receive a message so that he can check up on his crew.

Some messages require more attention than others. For example, if the trouble with the air conditioner were so serious as to threaten the whole building, the crewman, the contractor, and the owner of the building could be sent messages via their pagers. The contractor would be able to make the determination as to which problems require which messages and who should hear about it. The interface units also send out periodic "heartbeat" signals which let the server know that everything is okay. The server is designed to route messages from multiple pieces of equipment to multiple people in accordance with multiple message profiles. That is, a number of different contractors can use the system independently of each other.

Wilson et al. does not render obvious the claimed invention for several reasons. First, there is no teaching, suggestion, or even a hint in Wilson of enabling a user to remotely configure (edit, modify, create, etc.) a message profile on the computer server. The system of Fig. 12, for example, can send voice messages or faxes out to a recipient (see col. 34, lines 6-15), but it cannot receive instructions remotely from the intended message recipients. More specifically,

Wilson does not permit a remote user to configure a message profile to specify where the outgoing messages are to be sent. There is absolutely no remote user interface in Wilson as recited and set forth in the claims of the present application. Wilson does discuss enabling the user to configure the system for a particular application (see Abstract, cols. 9-11 generally and col. 10, line 67 and on, in particular), but not remotely. In this description, the user must be sitting down at the central PC 12 in order to effect any changes on the system whatsoever. Thus, in Wilson, the "user" is the person who is setting up the system. Thus, while the "user" can go to the central computer and configure the system, he cannot do it from home, the office, or in the field. Remote communication between user and system is thus unidirectional, from the system to the user.

In Applicant's invention, by contrast, the user, as recited in the claims, is the person subscribing to the service, the person intended to receive the messages. He can log into the server via remote means, such as the Internet, to configure his message profile to tell the computer server where to send what error messages to whom and under what circumstances. Remote communication between the subscriber/user and the system is thus bidirectional: from the system to the user when the system is sending an error message, and from the user to the system when the user is creating/editing the message profile (among other things). Also, in Wilson, only a computer programmer can alter or modify any instructions on the computer; by contrast, in Applicant's invention, the end user, not the programmer setting the system up, can adjust the message profile without any knowledge of computer programming.

Wilson also fails to teach or suggest the monitoring of remote equipment. All of the equipment being monitored in Wilson is <u>hardwired</u> into the system and is monitored <u>locally</u>. All of the various systems in Wilson require the I/O bridge device 14 into which all of the monitored equipment is directly wired. For example, Fig. 2 of Wilson shows an alarm system with smoke detectors 66 and 67 and burglar alarm loops 62 and 64. All of the devices are connected via wires to I/O bridge device 14 (see col. 9, lines 40-55). The equipment being monitored is not remote equipment, as required by the present claims, but rather <u>local</u> equipment.

Even the system shown in Fig. 12 of Wilson is only good for monitoring <u>local</u> equipment despite the presence of radio transceivers. As described in columns 33 and 34 of Wilson, Fig. 12 represents an alarm system for a car dealership lot. Instead of using wires to connect the antitheft devices to the base transceiver 700, each car is provided with an RF transmitter which can broadcast back to the main base. However, what is described is a local RF network only. It is designed to cover the parking lot of an automobile dealer (see col. 34, lines 46-61), or a range of maybe a few thousand feet. Applicant's invention can monitor equipment that is truly remote, and it can be used over the entire world, because of: a) the ability of the remote interface units to contact the central server remotely; b) the ability of the central server to contact the message recipient remotely via any format of communication device, and c) the ability of the user/subscriber to contact the server and configure his message profile remotely.

Finally, Wilson fails to teach that multiple subscribers can utilize the system simultaneously. The inventive system can store multiple message profiles of multiple subscribers and route the messages from each person's equipment to that person in accordance with his message profile. By contrast, Wilson is silent as to accommodating multiple users.

In view of the foregoing, Applicants respectfully submit that Claims 1-5, 9-12, 15, 17-21, and 26-52 recite patentable subject matter and that the application is in condition for allowance. The Examiner is invited to telephone the undersigned to discuss any further changes that might be deemed necessary. Prompt and favorable action toward the issuance of a patent is earnestly solicited and believed to be fully warranted.

U.S. Appl'n No. 09/317,235 Amendment

Applicant hereby petitions for any extension of time which may be required to maintain the pendency of this case, and any additional required fee, except for the Issue Fee, for such extension is to be charged to Deposit Account No. 02-2105.

Date: May 17, 2000

Levisohn, Lerner, Berger & Langsam 757 Third Avenue, Suite 2400 New York, New York 10017 (212) 486-7272

F:\ARCHIVE\Barry\WPDOCS\PROSEC\1216-34.115.wpd

Respectfully submitted,

Barry F. Negrin Reg. No.: 37,407

Attorney for Applicant

Notice of Allowability

Application No. 09/317,235 Applicant(s)

SANDELMAN ET AL Group Art Unit

Examiner

DARYL C. POPE

2736



All claims being allowable, PROSECUTION ON THE MERITS IS (OR REMAINS) CLOSED in this appli herewith (or previously mailed), a Notice of Allowance and Issue Fee Due or other appropriate communin due course.	
[X] This communication is responsive to <u>amendment filed 5/17/00</u>	
X The allowed claim(s) is/are 1-5, 9-12, 15, 17-21, and 25-52	
The drawings filed on are acceptable.	
☐ Acknowledgement is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d).	*
☐ All ☐Some* ☐None of the CERTIFIED copies of the priority documents have been	
☐ received.	N. Marine
received in Application No. (Series Code/Serial Number)	
received in this national stage application from the International Bureau (PCT Rule 17.2(a)).	, w *
*Certified copies not received:	
Acknowledgement is made of a claim for domestic priority under 35 U.S.C. § 119(e).	
A SHORTENED STATUTORY PERIOD FOR RESPONSE to comply with the requirements noted below THREE MONTHSROM THE "DATE MAILED" of this Office action. Failure to timely comply will result in ABANDONMENT of this application. Extensions of time may be obtained under the provisions of 37 Cl	
☐ Note the attached EXAMINER'S AMENDMENT or NOTICE OF INFORMAL APPLICATION, PTO-15 the oath or declaration is deficient. A SUBSTITUTE OATH OR DECLARATION IS REQUIRED.	2, which discloses that
Applicant MUST submit NEW FORMAL DRAWINGS	
because the originally filed drawings were declared by applicant to be informal.	
including changes required by the Notice of Draftsperson's Patent Drawing Review, PTO-948, at Paper No3.	tached hereto or to
including changes required by the proposed drawing correction filed onapproved by the examiner.	, which has been
including changes required by the attached Examiner's Amendment/Comment.	
Identifying indicia such as the application number (see 37 CFR 1.84(c)) should be written on the drawings. The drawings should be filed as a separate paper with a transmittal lettter add Draftsperson.	
☐ Note the attached Examiner's comment regarding REQUIREMENT FOR THE DEPOSIT OF BIOLOG	GICAL MATERIAL.
Any response to this letter should include, in the upper right hand corner, the APPLICATION NUMBER CODE/SERIAL NUMBER). If applicant has received a Notice of Allowance and Issue Fee Due, the ISS and DATE of the NOTICE OF ALLOWANCE should also be included.	
Attachment(s)	
□ Notice of References Cited, PTO-892	
☐ Notice of Draftsperson's Patent Drawing Review, PTO-948	DARYL POPE PRIMARY EXAMINER
☐ Notice of Informal Patent Application, PTO-152	AMINER .
☐ Interview Summary, PTO-413 ★ Examiner's Amendment/Comment	' ,) /// ₋
Examiner's Amendment Comment Examiner's Comment Regarding Requirement for Deposit of Biological Material	1 10 mg / 19/1
Examiner's Statement of Reasons for Allowance	PRIMARY EXAMINER ART UNIT 2736

J. S. Patent and Trademark Office PTO-37 (Rev. 9-95)

Notice of Allowability

Part of Paper No. ____

Application/Control Number: 09/317235

Art Unit:



EXAMINER'S AMENDMENT

- 1. An examiner's amendment to the record appears below. Should the changes and/or additions be unacceptable to applicant, an amendment may be filed as provided by 37 CFR 1.312. To ensure consideration of such an amendment, it MUST be submitted no later than the payment of the issue fee.
- 2. The application has been amended as follows:

IN THE CLAIMS:

- 1) Claim 11 line 3, "i)" has been changed to -- f) --;
- 2) Claim 12 line 2, "j)" has been changed to -- g) --;
- 3) Claim 29 line 1, "claim 13" has been changed to -- claim 12 --;
- 4) Claim 29 line 1, "g)" has been changed to -- e) --.
- 3. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Daryl C. Pope whose telephone number is (703) 305-4838.

Daryl C. Pope

July 1, 2000



UNITED STATES DEPARTMENT OF COMMERCE Patent and Trademark Office

NOTICE OF ALLOWANCE AND ISSUE FEE DUE

LM01/0705

BARRY E NEGRIN LEVINSOHN LERNER BERGER AND LANGSAM SUITE 2400 757 THIRD AVENUE NEW YORK NY 10017

APPLICATION NO.	FILING DATE	TOTAL CLAIMS		EXAMINER AND GROUP ART UNIT	\$ 2 . de	DATE MAILED
09/317,235	05/24/99	043	POPE,	D	2736	07/05/00
First Named SANDELMAN Applicant	the state of the s	35 U	SC 154	(b) term ext. =	0 Days	; ₄

TITLE OF ELECTRONIC MESSAGE DELIVERY SYSTEM UTILIZABLE IN THE MONITORING OF REM OTE EQUIPMENT AND METHOD OF SAME

ATTY	r'S DOCKET NO.	CLASS-SUBCLASS	ватснио.	A	PPLN. TYPE	SMALL ENTITY	FEE DUE	. DATE DUE
3	1216.034	340-50	6. 000	090	UTILITY	YES	\$605.00	10/05/00

THE APPLICATION IDENTIFIED ABOVE HAS BEEN EXAMINED AND IS ALLOWED FOR ISSUANCE AS A PATENT. PROSECUTION ON THE MERITS IS CLOSED.

THE ISSUE FEE MUST BE PAID WITHIN <u>THREE MONTHS</u> FROM THE MAILING DATE OF THIS NOTICE OR THIS APPLICATION SHALL BE REGARDED AS ABANDONED. <u>THIS STATUTORY PERIOD CANNOT BE EXTENDED.</u>

HOW TO RESPOND TO THIS NOTICE:

- I. Review the SMALL ENTITY status shown above. If the SMALL ENTITY is shown as YES, verify your current SMALL ENTITY status:
 - A. If the status is changed, pay twice the amount of the FEE DUE shown above and notify the Patent and Trademark Office of the change in status, or
 - B. If the status is the same, pay the FEE DUE shown above.

If the SMALL ENTITY is shown as NO:

- A. Pay FEE DUE shown above, or
- B. File verified statement of Small Entity Status before, or with, payment of 1/2 the FEE DUE shown above.
- II. Part B-Issue Fee Transmittal should be completed and returned to the Patent and Trademark Office (PTO) with your ISSUE FEE. Even if the ISSUE FEE has already been paid by charge to deposit account, Part B Issue Fee Transmittal should be completed and returned. If you are charging the ISSUE FEE to your deposit account, section "4b" of Part B-Issue Fee Transmittal should be completed and an extra copy of the form should be submitted.
- III. All communications regarding this application must give application number and batch number.

 Please direct all communications prior to issuance to Box ISSUE FEE unless advised to the contrary.

IMPORTANT REMINDER: Utility patents issuing on applications filed on or after Dec. 12, 1980 may require payment of maintenance fees. It is patentee's responsibility to ensure timely payment of maintenance fees when due.

- PATENT AND TRADEMARK OFFICE COPY TO SHAPE A SHAPE A SEA OF A SEA

PTOL-85 (REV. 10-96) Approved for use through 06/30/99. (0651-0033)

*U.S. GPO: 1999-454-457/24601



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re: application of: Sandelman, David et al.

Serial No.:

09/317,235

Filing Date:

May 24, 1999

For:

Electronic Message Delivery System Utilizable

in the Monitoring of Remote Equipment and

Method of Same

Examiner:

Daryl Pope

Art Unit:

2736

Attorney Docket No.: 1216.034

Assistant Commissioner For Patents Washington, DC 20231

TRANSMITTAL LETTER

Sir:

Enclosed herewith is an Issue Fee Transmittal form and eight sheets of formal drawings. In the event of any deficiency in the fee due in connection with this transmittal, the Commissioner is authorized and directed to debit our deposit account No. 02-2105 for the amount of such deficiency.

Dated: August 3, 2000

Levisohn, Lerner, Berger & Langsam 757 Third Avenue, Suite 2400

New York, NY 10017

Respectfully submitted,

Barry E. Negrin (Reg. No. 37,407)

Attorney for Applicant

Certificate of Mailing

I certify that this document and fee are being deposited with the U.S. Postal Service by Express Mail, addressed to Assistant Commissioner for Patents, Washington, DC 20231.

Lourdes Rodriguez

Mailing Date: August 3, 2000 Express Mail Label: EL470650635US

Petitioner Alarm.com Exhibit 1202

Patent Application



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

Sandelman

For

Electronic Message Delivery System Utilizable in the

Monitoring of Remote

Equipment and Method of Same

Serial No.:

09/317,235

Filing Date:

05/24/99

Art Unit:

2736

Examiner:

Pope, D.

Attorney Docket No.:

1216.034

Allowed:

July 5, 2000

PATENT

SUBMISSION OF FORMAL DRAWINGS

BOX ISSUE FEE

Commissioner of Patents Washington, DC 20231

Sir:

Applicant herewith submits **eight** sheets of formal drawings for the above-identified application. No new matter has been entered. The formal drawings are believed to address fully the deficiencies indicated on the PTO-948 form Applicant received as part of Paper No. 3.

Dated: August 3, 2000


Levisohn, Lerner, Berger & Langsam 757 Third Avenue, Suite 2400 New York, New York 10017

(212) 486-7272

Respectfully submitted,

Barry E. Negrin Reg. No.: 37,407


Attorney for Applicant





M








Figure 2




Figure 3a




Figure 3b




Figure 3c





Figure 3d






Figure 5

OS - OLL COPART B-ISSUE FEE TRANSMITTAL

Complete and mail this form, together with applicable fees, to:

Assistant Commissioner for Patents Washington, D.C. 20231





(Depositor's name)

MAILING INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE. Blocks 1 through 4 should be completed where appropriate. All further correspondence including the Issue Fee Receipt, the Patent, advance orders and notification of maintenance fees will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications.

CURRENT CORRESPONDENCE ADDRESS (Note: Legibly mark-up with any corrections or use Block 1)

LM01/0705

BARRY E NEGRIN LEVINSOHN LERNER BERGER AND LANGSAM SUITE 2400 757 THIRD AVENUE

Note: The certificate of mailing below can only be used for domestic mailings of the Issue Fee Transmittai. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing.

Certificate of Mailing

I hereby certify that this Issue Fee Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Box Issue Fee address above on the date indicated below.

Lourdes Rodriguez

NEW YORK NY	10017			Hardes Tax	trejus-	(Signature)
				8/3/00		(Date)
APPLICATION NO.	FILING DATE	TOTAL CLAIMS		EXAMINER AND GROUP AR	DATE MAILED	
09/317,235	05/24/99	043 POPI	E, D		2736	07/05/00
First Named Applicant SANDELMAN.		35 USC 1		term ext. =	0 Days	· u
TITLE OF NVENTION ELECTRONIC ME OTE EQUIPMENT			ILIZA	BLE IN THE MON	VITORING	OF REM

ATTY'S DOCKET NO.	CLASS-SUBCLASS	BATCH NO.	APPLN. TYPE		SMALL ENTITY	FEE DUE	DATE D	JE
1. Change of correspondence address or indication of "Fee Address" (37 CFR 1.363). Use of PTO form(s) and Customer Number are recommended, but not required. Change of correspondence address (or Change of Correspondence Address form PTO/SB/122) attached. Change of correspondence address (or Change of Correspondence Address form PTO/SB/122) attached. The Fee Address* indication form PTO/SB/47) attached. Change of Correspondence address form pto/SB/47) attached. Change of a single film (having as a member a registered attomey of a single film (having as a member a registered attomey of a single film (having as a member a registered attomey of a single film (having as a member a registered attomey of a single film (having as a member a registered attomey of a single film (having as a member a registered attomey or agent; of upo a registered attomey or agent; of upo a re								/00
Use of PTO form(s) and Customer N Change of correspondence addre	Number are recommended, but	t not required. ence Address for	(1) the name attorneys or the name of member a rand the riam attorneys or	agen agen f a s registe es of agent	up to 3 registered patents OR, alternatively, (2 single firm (having as a period attorney or agent up to 2 registered patents. If no name is listed, no)	Lerner, Langsam	Berger
PLEASE NOTE: Unless an assigne Inclusion of assignee data is only a the PTO or is being submitted undefiling an assignment. (A) NAME OF ASSIGNEE He. (B) RESIDENCE: (CITY & STATE OF Please check the appropriate assignment includes the state of the sta	ne is identified below, no assign ppropiate when an assignmen ar separate cover. Completion at - Timer Corp. OR COUNTRY) Fairfie	nee data will appe t has been previou of this form is NO eld, New J	ar on the patent. usly submitted to T a substitue for ersey	[of Patents and Tradem. Issue Fee Advance Order - # o The following fees or d DEPOSIT ACCOUNT I (ENCLOSE AN EXTRA Issue Fee	arks): If Copies effclency in these fee NUMBER02-2.1	es should be charg I 05 DRM)	
The COMMISSIONER OF PATENTS A	AND TRADEMARKS IS reque	sted to apply the is	ssue Fee to the ap			ii Copies	3172	/()() Berge: missioner
NOTE; The Issue Fee will not be accept or agent; or the assignee or other party		ne applicant; a reg	S/G3/CO istered attorney				022105 0	
depending on the needs of the indiv to complete this form should be se Office, Washington, D.C. 20231. D ADDRESS. SEND FEES AND TH	ridual case. Any comments int to the Chief Information of NOT SEND FEES OR COIS FORM TO: Box Issue Feet tof 1995, no persons are reconstructed.	on the amount of Officer, Patent a OMPLETED FOR se, Assistant Cor	f time required and Trademark RMS TO THIS nmissioner for		do	cketec	2000 HMICHRE1 00000122 242 605.00 CH 561 30.00 CH	
	and the second s	RANSMIT THI	S FORM WITH	FEE		7[11]00	08/08/2 01 FC:2 02 FC:5	

PTOL-85B (REV.10-96) Approved for use through 06/30/99. OMB 0651-0033

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE



United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Vinginia 22313-1450 www.usplo.gov

APPLICATION NUMBER PATENT NUMBER GROUP ART UNIT FILE WRAPPER LOCATION 09/317,235 6147601 2736 9200 K 10021 1012 113

Change of Address/Power of Attorney

The following fields have been set to Customer Number 4617 on

- Correspondence Address
- Maintenance Fee Address

The address of record for Customer Number 4617 is: LEVISOHN, BERGER & LANGSAM, LLP 805 THIRD AVENUE, 19TH FLOOR NEW YORK, NY 10022

The Practitioners of record for Customer Number 4617 are:

PTO INSTRUCTIONS:

Please take the following action when the correspondence address has been changed to a customer number:

- 1) Add 'ADDRESS CHANGE TO CUSTOMER NUMBER' on the next available content line of the File Jacket.
- 2) Put a line through the old address on the File Jacket and enter the Customer Number as the new address.
- 3) File this Notice in the File Jacket.


Please take the following action when the correspondence address has NOT been changed:

1) File this Notice in the File Jacket

			•	*					A	pplication	or D	ocket Num	nber
	PATENT	APPL		N FEE D			ON RECT A	RD	9	1/317	23 <u>.</u>	<u> </u>	
		CLA		S FILED -	PAF	•	mn 2)		ALL PE	ENTITY	OR	OTHER SMALL	
FC)R		NUMBE	R FILED		NUMBER	EXTR	RA	TE	FEE]	RATE	FEE
ВА	SIC FEE									380.00	OR		760.00
тс	TAL CLAIMS			50 minus	20=	* 30		X\$	9=	270	OR	X\$18=	
INE	EPENDENT CL	AIMS		2 minus	3 =	*		ХЗ	9=		OR	X78=	
ML	ILTIPLE DEPEN	IDENT	CLAIM PI	RESENT				+13	0=		OR	+260=	
* If	the difference	in colu	ımn 1 is	less than ze	ero, e	nter "0" in c	column 2	TO	AL	650	OR	TOTAL	
	С		S AS A umn 1)	MENDE	-	ART II olumn 2)	(೬ ಸೆumn 3)	ŞM	ALL	ENTITY	OR	OTHER SMALL	
ENTA		REM	AIMS IAINING FTER NDMENT		PR	HIGHEST NUMBER EVIOUSLY PAID FOR	PRESENT EXTRA	RA	TE	ADDI- TIONAL FEE		RATE	ADDI- TIONAL FEE
AMENDMENT	Total	*	42	Minus	**	50	= 💢	X\$	9=		OR	X\$18=	
AME	Independent	* L	 	Minus	***		= /	Х3:	9=	37.00	OR	X78=	7
 	FIRST PRESE	NIAIIC	ON OF MI	JUIPLE DE	PEND	₽	+13	0=		OR	+260=		
					ند			TO ADDIT	OTAL FEE	Pd.	OR	TOTAL ADDIT. FEE	
			um n 1)			olum n 2)	(Column 3)			7	_		
MENT B		REM	AIMS IAINING TER NDMENT		PA	HIGHEST NUMBER EVIOUSLY PAID FOR	PRESENT EXTRA	RA ⁻	ΓE	ADDI- TIONAL FEE		RATE	ADDI- TIONAL FEE
	Total	*		Minus	**		=	X\$	9=		OR	X\$18=	
AMEND	Independent FIRST PRESE	*	ON OF M	Minus	***	ENT OLAMA	<u> </u>	X39)=		OR	X78=	
-	TINOT FALSE	MATIC	DIN OF MIL	DETIFIE DE	FEIND	ENT CLAIM		+13	0=		OR	+260=	
						1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	:	ADDIT.	FEE		OR	TOTAL ADDIT. FEE	·
	7		umn 1)			olumn 2)	(Column 3)						
AMENDMENT C		REM AF	AIMS AINING TER NDMENT		PR	HIGHEST NUMBER EVIOUSLY PAID FOR	PRESENT EXTRA	RA	E	ADDI- TIONAL FEE		RATE	ADDI- TIONAL FEE
NDA	Total	•		Minus	**		= ;	X\$:	9=		OR	X\$18=	
AME	Independent	*	N. 05 ***	Minus	***	P P P P P P P P P P] =	X39)=		OR	X78=	
	FIRST PRESE	MIAIIC	ON OF MI	JUIPLE DE	PEND	ENI CLAIM							
• 1	f the entry in colu	mn 1 is l	ess than th	e entry in colu	ımn 2,	write "0" in co	lumn 3.	+13)=)TAL		OR	+260= TOTAL	
***	If the "Highest Nu If the "Highest Nu	mber Pr	eviously Pa	aid For" IN TH	IS SPA	CE is less tha	n 3, enter *3.*	ADDIT.	FEE			ADDIT. FEE	
	The "Highest Nun	nber Pre	viously Pai	d For" (Total o	r Inder	pendent) is the	highest number	found in t	ne api	propriate box	k in col	umn 1.	

FORM PTO-875 (Rev. 6/08*

Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE



SEARCHED

·			_
Class	Sub.	Date	Exmr.
340	506	1/11/00	DR
200 Welster	511 539 825.36 825.36 825.49	429/00	D.P.
		·	

INTERFERENCE SEARCHED Class Sub. Date Exmr. 506 6/28/00 538 825.06 825.36 825.49 700

	Date	Exmr.
		I
,		
	·	•
		in.

1202.0129

9

POSITION	INITIALS	ID No.	DATE
FEE DETERMINATION	\$5		63
O.I.P.E. CLASSIFIER		2	6/9/99
FORMALITY REVIEW		10608	10-110-99

INDEX OF CLAIMS

~	Rejected	N	Non-elected
=	Allowed	1	Interference
	(Through numeral) Canceled	Α	Appeal
÷	Restricted	0	Objected

							÷	••••	·••••	• • • •	••••
Cla	im					Dat	e			··	
		<u>`</u>	1.3	X							
-a	C Original	Í	1 %								
Final	Ę	1	170								,
7	3	1	×	+							
늣	2	K	-	 		_					_
<u>2</u> 3	2	Н	#	ـــ							
2	3	Ц	11	<u> </u>							
4	4	Ц	11	<u> </u>							
5	5	Ш	W		Ŀ						
	6										
	X		1.	T							
	8	Ĭ									······································
ℓ_a	9	M	-	 	 		-			`	
(2) 7 8	10	H	ᡮ	┼	 					-	
6	11	╫	+	-	├		_		-		_
å		╀	+	-	}						
ഺ	12 18	+	14	+		-		 			ļ
<u>_</u>		니	1_	 	<u> </u>						
<u></u>	14	Ц	1_	ļ							
<u> </u>	15	Ц	1=			<u> </u>	<u> </u>				
L	76										
Ш	17		=								
12	18		П								
13	19	П									
17	20	1	††	-	 	\vdash			_	_	_
19	1	H	₩	╄	 	ļ					<u> </u>
45,	21	1	14/	<u>'</u>	ļ						
L	285	II.	↓_			L					<u> </u>
<u></u>	23	1									
	24	Ц				<u> </u>					
16	25	$ \cdot $	=								
117	26	П	П	T							
18	27	Π	$\dagger \dagger$	1	1						
119	28	$\dag \uparrow$	$\forall t$	1	\vdash	<u> </u>	Ė		····		
龙	29	╫	ΗŦ	+-	├─	-	 			-	┝
器	20	Η,	₩	+	├	├			-	_	<u> </u>
NA 13	30	γ,	$\mathbb{A}^{\mathbb{A}}$	4_	 -	-	_	<u> </u>	ļ	_	
36	رك	Y	上	┼	<u> </u>		ļ	<u> </u>	<u> </u>		
23	32	Ц	4	<u> </u>	<u> </u>	<u> </u>	L		<u> </u>	L_	ļ
24 25	33	Ц	$\perp \downarrow$		<u></u>	<u> </u>					
25	34	Ц	$\perp \perp$				L				
260	35										
27	36	П	П						<u> </u>	<u> </u>	Γ
X	37	T	1	1		T	<u> </u>	l	\Box		
29	38		T	1	 	 	T	\vdash			
30	39	-	+-	#-	 	 	 	 	_		-
끍	100	+	╁	₩	├					\vdash	├
31	1	Н	+	-	 	<u> </u>	 			<u> </u>	<u> </u>
3a	41	Ш	Щ.	Щ_	_		<u> </u>				
33	42	\bigsqcup	$\perp \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \!$	_	L		L_	<u> </u>		L	
34	43	П	П								
2T	44	П	17	1	T			·			
26	45		11	\vdash	\vdash	\vdash	\vdash	 	\vdash	 	-
35	46	Н	++	+-	 	-	-	 	 	 	
밁	47	┝┤	++	+-	+-		_	 	\vdash		-
38 39	47	H	+	┼	├-	<u> </u>	├	 	├	 	
121	48	\sqcup	+	-	ـ	-		-	<u> </u>	 	<u> </u>
40	49	Ц	Ц.	1_			ļ		ļ		
141	50	1		1	1	١.	1	l		I	ı


		····									
Cla	im	L				Dat	е		á		
	Original		18							l	
al	ği		18)								
Fir	ğ	,	3								
4)(51)	(1			'					
42	52	<u> </u>	=								
-	53	-	F	_		_				-	
Final	54									-	
<u> </u>	55		_		_				-	\dashv	_
<u> </u>											
	5 6	<u> </u>									
	57										
	58										
	59										
	60										
	61	 		H							
-	62	\vdash		 							
_	63		-	-	H					-	_
	64	 	-	<u> </u>	_					_	
				<u> </u>							
	65	_									
	66										
	67										
	68										
	69										
	70			<u> </u>		-					
	71	 	-		_						
		-									
	72										_
_	73	ļ									_
<u> </u>	74										_
	75	<u>.</u>									
	76										
	77										
	78	Π									
	79										
	80		<u> </u>							_	
-	81		 			\vdash	 			┝	-
-	82	-	┢			-				\vdash	-
-	83	├	⊢	<u> </u>	-	 			_	-	H
<u> </u>	84		-		 	<u> </u>				-	<u> </u>
		_	-				<u> </u>			_	
	85	ļ	<u> </u>	<u>. </u>	<u> </u>	<u> </u>	_				<u> </u>
	86	<u> </u>				_					L
	87			<u></u>							
<u> </u>	88										
	89										
	90			Γ							
	91	1	 	\vdash		I^-	<u> </u>	-		_	
-	92	 	 	 	-	 	\vdash	\vdash	_	-	-
	-	-	\vdash	-	-	-	-	-	-	-	-
<u></u>	93	-	-	<u> </u>			 _ :	<u> </u>	<u> </u>		_
L	94	_	<u></u>	<u> </u>	_	<u> </u>	<u> </u>		<u> </u>		<u>_</u>
<u></u>	95	Ľ				<u> </u>	_	_	<u> </u>	<u> </u>	L
	96				_	L			<u></u>		L
L	97										
	98										

Claim		Date											
Final	Original												
	101											1	
	102												
	103												
	104												
	105												
	106												
	107												
	108												
	109												
	110												
	111												
	112										ļ		
	113												
	114 115				-	-							
	116					-							
	117				-	-							
	118					-							
	119												
	120			_	-	_							
	121				_	_					_		
	122					-							
	123								-				
	124				-	_			-				
	125				-	-					-		
	126				-					-			
	127				 	-			 		_		
	128			-			-	-				1	
-	129				-	 			_		 	l	
	130	L			_	†				-	ļ	1	
	131								 			1	
	132			\Box					Г			1	
	133										1	1	
	134					Γ		Γ			T	1	
	135]	
	136												
	137												
	138			_					L	\perp		_	
	139			_	<u> </u>	_	_						
	140			_	1	L	1_			1			
	141						L					_	
	142						L		\prod			_	
	143		ļ										
	144				L								
	145				\Box	\prod		\perp	I	I	I	_	
	146			_	_								
	147		_	_	L							_	
	148		_		1	\perp	1	1	1	_	_		
	149		_	1	\perp	\downarrow	_	\perp	_	_	_		
	150			<u></u>			\perp						

If more than 150 claims or 10 actions staple additional sheet here

PATENT APPLICATION 09317235





CONTENTS

,	Date received (Incl. C. of M.)		(Incl. C. of M.)
^	or Date Mailed		or Date Mailed
1. Application papers.		42	
1 LDS	10-26-99	43	
n Key (3nthe)	1-20-00	44	
Anterview Summary	5-11-00	45	
5 Ext. of Time (1)	5-17-00	46	
6 Unott. a	5-17-00	47	
nex and B	7-500	48	
ofmal Drawings(Sshts)set	8-3-00	49	
9		50	
10		51	
ll		52.	* *.
12	<u>.</u>	53	*
13		54	
14		55	
15		56	
16		57	
17	· · · · · · · · · · · · · · · · · · ·	58	
18		59	
19		60	
20		61	
21		62	
22		63	
23		64	
24		65	
25		66	
26		67	
27		68	
28		69	
29		70	
30		71	
31		72	
32		73	
33		74 75	
34		76.	
35		77.	
36		78	
37		79.	
38		80.	
39		81	
40		92	
41		Petitioner Alai	rm.com Exhibit 1202