

US005799010A

United States Patent [19]**Lomp et al.**[11] **Patent Number:** **5,799,010**[45] **Date of Patent:** **Aug. 25, 1998****[54] CODE DIVISION MULTIPLE ACCESS (CDMA) COMMUNICATION SYSTEM**

[75] **Inventors:** **Gary Lomp**, Centerpot; **John Kowalski**, Hempstead; **Fatih Ozluturk**, Port Washington; **Avi Silverberg**, Commack; **Robert Regis**, Huntington; **Michael Luddy**, Sea Cliff, all of N.Y.; **Alexander Marra**, Hoboken, N.J.; **Alexander Jacques**, Mineola, N.Y.

[73] **Assignee:** **Interdigital Technology Corporation**, Wilmington, Del.

[21] **Appl. No.:** **669,775**

[22] **Filed:** **Jun. 27, 1996**

Related U.S. Application Data

[60] **Provisional application No.** 60/000,775 **Jun. 30, 1995.**

[51] **Int. Cl.⁶** **H04J 13/02; H04B 7/216**

[52] **U.S. Cl.** **370/335; 370/342; 375/208**

[58] **Field of Search** 370/203, 208, 370/209, 320, 328, 329, 335, 342, 441, 479; 375/200, 206, 208, 354, 362, 365, 367; 455/31.1, 33.1, 38.1, 53.1, 54.1, 67.1, 226.1, 422, 507, 517

[56] References Cited**U.S. PATENT DOCUMENTS**

4,901,307 2/1990 Gilhousen et al. 370/320
5,022,049 6/1991 Abrahamson et al. 375/200

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

0464839A2 1/1992 European Pat. Off. .
0526106A2 2/1993 European Pat. Off. .
0654913A2 5/1995 European Pat. Off. .
0656716A1 6/1995 European Pat. Off. .
0668662A1 8/1995 European Pat. Off. .
3743731A1 7/1989 Germany .

(List continued on next page.)

OTHER PUBLICATIONS

"Code Division Multiple Access (CDMA)", Franz Josef Hagmanns, Volker Hespelt, 8273 ANT Nachrichtentechnische Berichte (1993) Aug., No. 10, Backnang, DE, pp. 64-71.

(List continued on next page.)

Primary Examiner—Alpus H. Hsu


Assistant Examiner—Kwang B. Yao

Attorney, Agent, or Firm—Ratner & Prestia

[57] ABSTRACT

A multiple access, spread-spectrum communication system processes a plurality of information signals received by a Radio Carrier Station (RCS) over telecommunication lines for simultaneous transmission over a radio frequency (RF) channel as a code-division-multiplexed (CDM) signal to a group of Subscriber Units (SUs). The RCS receives a call request signal that corresponds to a telecommunication line information signal, and a user identification signal that identifies a user to receive the call. The RCS includes a plurality of Code Division Multiple Access (CDMA) modems, one of which provides a global pilot code signal. The modems provide message code signals synchronized to the global pilot signal. Each modem combines an information signal with a message code signal to provide a CDM processed signal. The RCS includes a system channel controller is coupled to receive a remote call. An RF transmitter is connected to all of the modems to combine the CDM processed signals with the global pilot code signal to generate a CDM signal. The RF transmitter also modulates a carrier signal with the CDM signal and transmits the modulated carrier signal through an RF communication channel to the SUs. Each SU includes a CDMA modem which is also synchronized to the global pilot signal. The CDMA modem despreads the CDM signal and provides a despread information signal to the user. The system includes a closed loop power control system for maintaining a minimum system transmit power level for the RCS and the SUs, and system capacity management for maintaining a maximum number of active SUs for improved system performance.

9 Claims, 35 Drawing Sheets



U.S. PATENT DOCUMENTS

5,084,900	1/1992	Taylor	370/320	5,392,287	2/1995	Tiedemann, Jr. et al.	370/311
5,093,840	3/1992	Schilling	375/200	5,396,516	3/1995	Padovani et al.	375/225
5,103,459	4/1992	Gilhausen et al.	370/209	5,404,376	4/1995	Dent	375/200
5,109,390	4/1992	Gilhausen et al.	370/335	5,414,728	5/1995	Zehavi	375/200
5,166,951	11/1992	Schilling	375/200	5,414,729	5/1995	Fenton	375/209
5,193,094	3/1993	Viterbi	371/43.7	5,416,797	5/1995	Gilhausen et al.	370/209
5,204,876	4/1993	Bruckert et al.	375/200	5,420,896	5/1995	Schilling	370/479
5,228,054	7/1993	Rueth et al.	370/479	5,430,760	7/1995	Dent	375/200
5,228,056	7/1993	Schilling	375/200	5,440,597	8/1995	Chung et al.	375/200
5,237,586	8/1993	Bottomley	370/206	5,442,662	8/1995	Fukasawa et al.	370/342
5,241,690	8/1993	Larsson et al.	455/522	5,488,629	1/1996	Takahashi et al.	375/206
5,245,629	9/1993	Hall	375/200	5,519,736	5/1996	Ishida	375/367
5,253,268	10/1993	Omura et al.	375/200	5,528,624	6/1996	Kaku et al.	375/206
5,257,283	10/1993	Gilhausen et al.	375/200	5,559,790	9/1996	Yano et al.	370/342
5,260,967	11/1993	Schilling	370/342				
5,265,119	11/1993	Gilhausen et al.	370/335				
5,267,262	11/1993	Wheatley, III	375/200				
5,283,536	2/1994	Wheatley, III et al.	330/279				
5,295,152	3/1994	Gudmundson et al.	370/342				
5,299,226	3/1994	Schilling	375/200				
5,299,228	3/1994	Hall	370/335				
5,309,474	5/1994	Gilhausen et al.	370/209				
5,327,455	7/1994	DeGaudenzi et al.	370/207				
5,327,467	7/1994	DeGaudenzi et al.	375/356				
5,329,547	7/1994	Ling	375/342				
5,341,396	8/1994	Higgins et al.	375/206				
5,345,598	9/1994	Dent	455/522				
5,347,536	9/1994	Meehan	375/210				
5,349,606	9/1994	Lovell et al.	375/206				
5,373,502	12/1994	Turban	370/441				
5,377,183	12/1994	Dent	370/335				

FOREIGN PATENT DOCUMENTS

3743732A1	7/1989	Germany
WO93/07702	4/1993	WIPO
WO95/03652	2/1995	WIPO
WO97/02665	1/1997	WIPO

OTHER PUBLICATIONS

"CDMA and ATM—zwei Technologien, ein Ziel", 2323
 Telcom Report (Siemens) 18(1995) Maerz/Apr., No. 2,
 Munchen, DE, pp. 60–63.
 Search Report, Apr. 10, 1997.
 Search Report, Apr. 15, 1997.
 Search Report, Apr. 17, 1997.
 Search Report, Apr. 29, 1997.
 Search Report, Mar. 5, 1997.
 International Search Report, Jan. 14, 1997.

FIG. 1




FIG. 2a




FIG. 2b






FIG. 2c








FIG. 3a




FIG. 3b





FIG. 3c







FIG. 5b







FIG. 6






FIG. 8a




FIG. 8b




FIG. 8c




FIG. 8d







FIG. 9










FIG. 13





FIG. 14






FIG. 16




FIG. 17




FIG. 18




FIG. 19





FIG. 20






FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30

1

CODE DIVISION MULTIPLE ACCESS (CDMA) COMMUNICATION SYSTEM

This application claims the benefit of U.S. Provisional Application 60/000,775 filed Jun. 30, 1995.

BACKGROUND OF THE INVENTION

The present invention generally pertains to Code Division Multiple Access (CDMA) communications, also known as spread-spectrum communications. More particularly, the present invention pertains to a system and method for providing a high capacity, CDMA communications system which provides for one or more simultaneous user bearer channels over a given radio frequency, allowing dynamic allocation of bearer channel rate while rejecting multipath interference.

DESCRIPTION OF THE RELEVANT ART

Providing quality telecommunication services to user groups which are classified as remote, such as rural telephone systems and telephone systems in underdeveloped countries, has proved to be a challenge in recent years. These needs have been partially satisfied by wireless radio services, such as fixed or mobile frequency division multiplex (FDM), frequency division multiple access (FDMA), time division multiplex (TDM), time division multiple access (TDMA) systems, combination frequency and time division systems (FD/TDMA), and other land mobile radio systems. Usually, these remote services are faced with more potential users than can be supported simultaneously by their frequency or spectral bandwidth capacity.

Recognizing these limitations, recent advances in wireless communications have used spread spectrum modulation techniques to provide simultaneous communication by multiple users. Spread spectrum modulation refers to modulating a information signal with a spreading code signal; the spreading code signal being generated by a code generator where the period T_c of the spreading code is substantially less than the period of the information data bit or symbol signal. The code may modulate the carrier frequency upon which the information has been sent, called frequency-hopped spreading, or may directly modulate the signal by multiplying the spreading code with the information data signal, called direct-sequence spreading (DS). Spread-spectrum modulation produces a signal with bandwidth substantially greater than that required to transmit the information signal. Synchronous reception and despreading of the signal at the receiver recovers the original information. A synchronous demodulator in the receiver uses a reference signal to synchronize the despreading circuits to the input spread-spectrum modulated signal to recover the carrier and information signals. The reference signal can be a spreading code which is not modulated by an information signal. Such use of a synchronous spread-spectrum modulation and demodulation for wireless communication is described in U.S. Pat. No. 5,228,056 entitled SYNCHRONOUS SPREAD-SPECTRUM COMMUNICATIONS SYSTEM AND METHOD by Donald L. Schilling, which techniques are incorporated herein by reference.

Spread-spectrum modulation in wireless networks offers many advantages because multiple users may use the same frequency band with minimal interference to each user's receiver. Spread-spectrum modulation also reduces effects from other sources of interference. In addition, synchronous spread-spectrum modulation and demodulation techniques may be expanded by providing multiple message channels

2

for a single user, each spread with a different spreading code, while still transmitting only a single reference signal to the user. Such use of multiple message channels modulated by a family of spreading codes synchronized to a pilot spreading code for wireless communication is described in U.S. Pat. No. 5,166,951 entitled HIGH CAPACITY SPREAD-SPECTRUM CHANNEL by Donald L. Schilling, which is incorporated herein by reference.

One area in which spread-spectrum techniques are used is in the field of mobile cellular communications to provide personal communication services (PCS). Such systems desirably support large numbers of users, control Doppler shift and fade, and provide high speed digital data signals with low bit error rates. These systems employ a family of orthogonal or quasi-orthogonal spreading codes, with a pilot spreading code sequence synchronized to the family of codes. Each user is assigned one of the spreading codes as a spreading function. Related problems of such a system are: supporting a large number of users with the orthogonal codes, handling reduced power available to remote units, and handling multipath fading effects. Solutions to such problems include using phased-array antennas to generate multiple steerable beams, using very long orthogonal or quasi-orthogonal code sequences. These sequences may be reused by cyclic shifting of the code synchronized to a central reference, and diversity combining of multipath signals. Such problems associated with spread spectrum communications, and methods to increase capacity of a multiple access, spread-spectrum system are described in U.S. Pat. No. 4,901,307 entitled SPREAD SPECTRUM MULTIPLE ACCESS COMMUNICATION SYSTEM USING SATELLITE OR TERRESTRIAL REPEATERS by Gilhousen et al. which is incorporated herein by reference.

The problems associated with the prior art systems focus around reliable reception and synchronization of the receiver despreading circuits to the received signal. The presence of multipath fading introduces a particular problem with spread spectrum receivers in that a receiver must somehow track the multipath components to maintain code-phase lock of the receiver's despreading means with the input signal. Prior art receivers generally track only one or two of the multipath signals, but this method is not satisfactory because the combined group of low power multipath signal components may actually contain far more power than the one or two strongest multipath components. The prior art receivers track and combine the strongest components to maintain a predetermined Bit Error Rate (BER) of the receiver. Such a receiver is described, for example, in U.S. Pat. No. 5,109,390 entitled DIVERSITY RECEIVER IN A CDMA CELLULAR TELEPHONE SYSTEM by Gilhousen et al. A receiver that combines all multipath components, however, is able to maintain the desired BER with a signal power that is lower than that of prior art systems because more signal power is available to the receiver. Consequently, there is a need for a spread spectrum communication system employing a receiver that tracks substantially all of the multipath signal components, so that substantially all multipath signals may be combined in the receiver, and hence the required transmit power of the signal for a given BER may be reduced.

Another problem associated with multiple access, spread-spectrum communication systems is the need to reduce the total transmitted power of users in the system, since users may have limited available power. An associated problem requiring power control in spread-spectrum systems is related to the inherent characteristic of spread-spectrum systems that one user's spread-spectrum signal is received

by another user's receiver as noise with a certain power level. Consequently, users transmitting with high levels of signal power may interfere with other users' reception. Also, if a user moves relative to another user's geographic location, signal fading and distortion require that the users adjust their transmit power level to maintain a particular signal quality. At the same time, the system should keep the power that the base station receives from all users relatively constant. Finally, because it is possible for the spread-spectrum system to have more remote users than can be supported simultaneously, the power control system should also employ a capacity management method which rejects additional users when the maximum system power level is reached.

Prior spread-spectrum systems have employed a base station that measures a received signal and sends an adaptive power control (APC) signal to the remote users. Remote users include a transmitter with an automatic gain control (AGC) circuit which responds to the APC signal. In such systems the base station monitors the overall system power or the power received from each user, and sets the APC signal accordingly. Such a spread-spectrum power control system and method is described in U.S. Pat. No. 5,299,226 entitled ADAPTIVE POWER CONTROL FOR A SPREAD SPECTRUM COMMUNICATION SYSTEM AND METHOD, and U.S. Pat. No. 5,093,840 entitled ADAPTIVE POWER CONTROL FOR A SPREAD SPECTRUM TRANSMITTER, both by Donald L. Schilling and incorporated herein by reference. This open loop system performance may be improved by including a measurement of the signal power received by the remote user from the base station, and transmitting an APC signal back to the base station to effectuate a closed loop power control method. Such closed loop power control is described, for example, in U.S. Pat. No. 5,107,225 entitled HIGH DYNAMIC RANGE CLOSED LOOP AUTOMATIC GAIN CONTROL CIRCUIT to Charles E. Wheatley, III et al. and incorporated herein by reference.

These power control systems, however, exhibit several disadvantages. First, the base station must perform complex power control algorithms, increasing the amount of processing in the base station. Second, the system actually experiences several types of power variation: variation in the noise power caused by the variation in the number of users and variations in the received signal power of a particular bearer channel. These variations occur with different frequency, so simple power control algorithms can be optimized to compensate for only one of the two types of variation. Finally, these power algorithms tend to drive the overall system power to a relatively high level. Consequently, there is a need for a spread-spectrum power control method that rapidly responds to changes in bearer channel power levels, while simultaneously making adjustments to all users' transmit power in response to changes in the number of users. Also, there is a need for an improved spread-spectrum communication system employing a closed loop power control system which minimizes the system's overall power requirements while maintaining a sufficient BER at the individual remote receivers. In addition, such a system should control the initial transmit power level of a remote user and manage total system capacity.

Spread-spectrum communication systems desirably should support large numbers of users, each of which has at least one communication channel. In addition, such a system should provide multiple generic information channels to broadcast information to all users and to enable users to gain access to the system. Using prior art spread-spectrum sys-

tems this could only be accomplished by generating large numbers of spreading code sequences.

Further, spread-spectrum systems should use sequences that are orthogonal or nearly orthogonal to reduce the probability that a receiver locks to the wrong spreading code sequence or phase. The use of such orthogonal codes and the benefits arising therefrom are outlined in U.S. Pat. No. 5,103,459 entitled SYSTEM AND METHOD FOR GENERATING SIGNAL WAVEFORMS IN A CDMA CELLULAR TELEPHONE SYSTEM, by Gilhousen et al. and U.S. Pat. No. 5,193,094 entitled METHOD AND APPARATUS FOR GENERATING SUPER-ORTHOGONAL CONVOLUTIONAL CODES AND THE DECODING THEREOF, by Andrew J. Viterbi, both of which are incorporated herein by reference. However, generating such large families of code sequences with such properties is difficult. Also, generating large code families requires generating sequences which have a long period before repetition. Consequently, the time a receiver takes to achieve synchronization with such a long sequence is increased. Prior art spreading code generators often combine shorter sequences to make longer sequences, but such sequences may no longer be sufficiently orthogonal. Therefore, there is a need for an improved method for reliably generating large families of code sequences that exhibit nearly orthogonal characteristics and have a long period before repetition, but also include the benefit of a short code sequence that reduces the time to acquire and lock the receiver to the correct code phase. In addition, the code generation method should allow generation of codes with any period, since the spreading code period is often determined by parameters used such as data rate or frame size.

Another desirable characteristic of spreading code sequences is that the transition of the user data value occur at a transition of the code sequence values. Since data typically has a period which is divisible by 2^N , such a characteristic usually requires the code sequence to be an even length of 2^N . However, code generators, as is well known in the art, generally use linear feedback shift registers which generate codes of length $2^N - 1$. Some generators include a method to augment the generated code sequence by inserting an additional code value, as described, for example, in U.S. Pat. No. 5,228,054 entitled POWER-OFTWO LENGTH PSEUDONOISE SEQUENCE GENERATOR WITH FAST OFFSET ADJUSTMENT by Timothy Rueth et al and incorporated herein by reference. Consequently, the spread-spectrum communication system should also generate spreading code sequences of even length.

Finally, the spread-spectrum communication system should be able to handle many different types of data, such as FAX, voiceband data, and ISDN, in addition to traditional voice traffic. To increase the number of users supported, many systems employ encoding techniques such as ADPCM to achieve "compression" of the digital telephone signal. FAX, ISDN and other data, however, require the channel to be a clear channel. Consequently, there is a need for a spread spectrum communication system that supports compression techniques that also dynamically modify the spread spectrum bearer channel between an encoded channel and a clear channel in response to the type of information contained in the user's signal.

SUMMARY OF THE INVENTION

The present invention is embodied in a multiple access, spread-spectrum communication system which processes a

5

plurality of information signals received simultaneously over telecommunication lines for simultaneous transmission over a radio frequency (RF) channel as a code-division-multiplexed (CDM) signal. The system includes a radio carrier station (RCS) which receives a call request signal that corresponds to a telecommunication line information signal, and a user identification signal that identifies a user to which the call request and information signal are addressed. The receiving apparatus is coupled to a plurality of code division multiple access (CDMA) modems, one of which provides a global pilot code signal and a plurality of message code signals, and each of the CDMA modems combines one of the plurality of information signals with its respective message code signal to provide a spread-spectrum processed signal. The plurality of message code signals of the plurality of CDMA modems are synchronized to the global pilot code signal. The system also includes assignment apparatus that is responsive to a channel assignment signal for coupling the respective information signals received on the telecommunication lines to indicated ones of the plurality of modems; The assignment apparatus is coupled to a time-slot exchange means. The system further includes a system channel controller coupled to a remote call-processor and to the time-slot exchange means. The system channel controller is responsive to the user identification signal, to provide the channel assignment signal. In the system, an RF transmitter is connected to all of the modems to combine the plurality of spread-spectrum processed message signals with the global pilot code signal to generate a CDM signal. The RF transmitter also modulates a carrier signal with the CDM signal and transmits the modulated carrier signal through an RF communication channel.

The transmitted CDM signal is received from the RF communication channel by a subscriber unit (SU) which processes and reconstructs the transmitted information signal assigned to the subscriber. The SU includes a receiving means for receiving and demodulating the CDM signal from the carrier. In addition, the SU comprises a subscriber unit controller and a CDMA modem which includes a processing means for acquiring the global pilot code and despreading the spread-spectrum processed signal to reconstruct the transmitted information signal.

The RCS and the SUs each contain CDMA modems for transmission and reception of telecommunication signals including information signals and connection control signals. The CDMA modem comprises a modem transmitter having: a code generator for providing an associated pilot code signal and for generating a plurality of message code signals; a spreading means for combining each of the information signals, with a respective one of the message code signals to generate spread-spectrum processed message signals; and a global pilot code generator which provides a global pilot code signal to which the message code signals are synchronized.

The CDMA modem also comprises a modem receiver having associated pilot code acquisition and tracking logic. The associated pilot code acquisition logic includes an associated pilot code generator; a group of associated pilot code correlators for correlating code-phase delayed versions of the associated pilot signal with a receive CDM signal for producing a despread associated pilot signal. The code phase of the associated pilot signal is changed responsive to an acquisition signal value until a detector indicates the presence of the despread associated pilot code signal by changing the acquisition signal value. The associated pilot code signal is synchronized to the global pilot signal. The asso-

6

ciated pilot code tracking logic adjusts the associated pilot code signal in phase responsive to the acquisition signal so that the signal power level of the despread associated pilot code signal is maximized. Finally, the CDMA modem receiver includes a group of message signal acquisition circuits. Each message signal acquisition circuit includes a plurality of receive message signal correlators for correlating one of the local receive message code signals with the CDM signal to produce a respective despread receive message signal.

To generate large families of nearly mutually orthogonal codes used by the CDMA modems, the present invention includes a code sequence generator. The code sequences are assigned to a respective logical channel of the spread-spectrum communication system, which includes In-phase (I) and Quadrature (Q) transmission over RF communication channels. One set of sequences is used as pilot sequences which are code sequences transmitted without modulation by a data signal. The code sequence generator circuit includes a long code sequence generator including a linear feedback shift register, a memory which provides a short, even code sequence, and a plurality of cyclic shift, feedforward sections which provide other members of the code family which exhibit minimal correlation with the code sequence applied to the feedforward circuit. The code sequence generator further includes a group of code sequence combiners for combining each phase shifted version of the long code sequence with the short, even code sequence to produce a group, or family, of nearly mutually orthogonal codes.

Further, the present invention includes several methods for efficient utilization of the spread-spectrum channels. First, the system includes a bearer channel modification system which comprises a group of message channels between a first transceiver and second transceiver. Each of the group of message channels supports a different information signal transmission rate. The first transceiver monitors a received information signal to determine the type of information signal that is received, and produces a coding signal relating to the coding signal. If a certain type of information signal is present, the first transitive switches transmission from a first message channel to a second message channel to support the different transmission rate. The coding signal is transmitted by the first transitive to the second transitive, and the second transitive switches to the second message channel to receive the information signal at a different transmission rate.

Another method to increase efficient utilization of the bearer message channels is the method of idle-code suppression used by the present invention. The spread-spectrum transitive receives a digital data information signal including a predetermined flag pattern corresponding to an idle period. The method includes the steps of: 1) delaying and monitoring the digital data signal; 2) detecting the predetermined flag pattern; 3) suspending transmission of the digital data signal when the flag pattern is detected; and 4) transmitting the data signal as a spread-spectrum signal when the flag pattern is not detected.

The present invention includes a system and method for closed loop automatic power control (AC) for the RCS and SUs of the spread-spectrum communication system. The SUs transmit spread-spectrum signals, the RCS acquires the spread-spectrum signals, and the RCS detects the received power level of the spread-spectrum signals plus any interfering signal including noise. The AC system includes the RCS and a plurality of SUs, wherein the RCS transmits a plurality of forward channel information signals to the SUs

as a plurality of forward channel spread-spectrum signals having a respective forward transmit power level, and each SU transmits to the base station at least one reverse spread-spectrum signal having a respective reverse transmit power level and at least one reverse channel spread-spectrum signal which includes a reverse channel information signal.

The AC includes an automatic forward power control (AFPC) system, and an automatic reverse power control (ARPC) system. The AFPC system operates by measuring, at the SU, a forward signal-to-noise ratio of the respective forward channel information signal, generating a respective forward channel error signal corresponding to a forward error between the respective forward signal-to-noise ratio and a pre-determined signal-to-noise value, and transmitting the respective forward channel error signal as part of a respective reverse channel information signal from the SU to the RCS. The RCS includes a plural number of AFPC receivers for receiving the reverse channel information signals and extracting the forward channel error signals from the respective reverse channel information signals. The RCU also adjusts the respective forward transmit power level of each one of the respective forward spread-spectrum signals responsive to the respective forward error signal.

The ARPC system operates by measuring, in the RCS, a reverse signal-to-noise ratio of each of the respective reverse channel information signals, generating a respective reverse channel error signal representing an error between the respective reverse channel signal-to-noise ratio and a respective pre-determined signal-to-noise value, and transmitting the respective reverse channel error signal as a part of a respective forward channel information signal to the SU. Each SU includes an ARPC receiver for receiving the forward channel information signal and extracting the respective reverse error signal from the forward channel information signal. The SU adjusts the reverse transmit power level of the respective reverse spread-spectrum signal responsive to the respective reverse error signal.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a code division multiple access communication system according to the present invention.

FIG. 2a is a block diagram of a 36 stage linear shift register suitable for use with long spreading code of the code generator of the present invention.

FIG. 2b is a block diagram of circuitry which illustrates the feed) forward operation of the code generator.

FIG. 2c is a block diagram of an exemplary code generator of the present invention including circuitry for generating spreading code sequences from the long spreading codes and the short spreading codes.

FIG. 2d is an alternate embodiment of the code generator circuit to including delay elements to compensate for electrical circuit delays.

FIG. 3a is a graph of the constellation points of the pilot spreading code QPSK signal.

FIG. 3b is a graph of the constellation points of the message channel QPSK signal.

FIG. 3c is a block diagram of exemplary circuitry which implements the method of tracking the received spreading code phase of the present invention.

FIG. 4 is a block diagram of the tracking circuit that tracks the median of the received multipath signal components.

FIG. 5a is a block diagram of the tracking circuit that tracks the centroid of the received multipath signal components.

FIG. 5b is a block diagram of the Adaptive Vector Correlator.

FIG. 6 is a block diagram of exemplary circuitry which implements the acquisition decision method of the correct spreading code phase of the received pilot code of the present invention.

FIG. 7 is a block diagram of an exemplary pilot rake filter which includes the tracking circuit and digital phase locked loop for despreading the pilot spreading code, and generator of the weighting factors of the present invention.

FIG. 8a is a block diagram of an exemplary adaptive vector correlator and matched filter for despreading and combining the multipath components of the present invention.

FIG. 8b is a block diagram of an alternative implementation of the adaptive vector correlator and adaptive matched filter for despreading and combining the multipath components of the present invention.

FIG. 8c is a block diagram of an alternative embodiment of the adaptive vector correlator and adaptive matched filter for despreading and combining the multipath components of the present invention.

FIG. 8d is a block diagram of the Adaptive Matched Filter of one embodiment of the present invention.

FIG. 9 is a block diagram of the elements of an exemplary radio carrier station (RCS) of the present invention.

FIG. 10 is a block diagram of the elements of an exemplary multiplexer suitable for use in the RCS shown in FIG. 9.

FIG. 11 is a block diagram of the elements of an exemplary wireless access controller (WAC) of the RCS shown in FIG. 9.

FIG. 12 is a block diagram of the elements of an exemplary modem interface unit (MIU) of the RCS shown in FIG. 9.

FIG. 13 is a high level block diagram showing the transmit, receive, control, and code generation circuitry of the CDMA modem.

FIG. 14 is a block diagram of the transmit section of the CDMA modem.

FIG. 15 is a block diagram of an exemplary modem input signal receiver.

FIG. 16 is a block diagram of an exemplary convolutional encoder as used in the present invention.

FIG. 17 is a block diagram of the receive section of the CDMA modem.

FIG. 18 is a block diagram of an exemplary adaptive matched filter as used in the CDMA modem receive section.

FIG. 19 is a block diagram of an exemplary pilot rake as used in the CDMA modem receive section.

FIG. 20 is a block diagram of an exemplary auxiliary pilot rake as used in the CDMA modem receive section.

FIG. 21 is a block diagram of an exemplary video distribution circuit (VDC) of the RCS shown in FIG. 9.

FIG. 22 is a block diagram of an exemplary RF transmitter/receiver and exemplary power amplifiers of the RCS shown in FIG. 9.

FIG. 23 is a block diagram of an exemplary subscriber unit (SU) of the present invention.

FIG. 24 is a flow-chart diagram of an exemplary call establishment algorithm for an incoming call request used by the present invention for establishing a bearer channel between an RCS and an SU.

FIG. 25 is a flow-chart diagram of an exemplary call establishment algorithm for an outgoing call request used by the present invention for establishing a bearer channel between an RCS and an SU.

FIG. 26 is a flow-chart diagram of an exemplary maintenance power control algorithm of the present invention.

FIG. 27 is a flow-chart diagram of an exemplary automatic forward power control algorithm of the present invention.

FIG. 28 is a flow-chart diagram of an exemplary automatic reverse power control algorithm of the present invention.

FIG. 29 is a block diagram of an exemplary closed loop power control system of the present invention when the bearer channel is established.

FIG. 30 is a block diagram of an exemplary closed loop power control system of the present invention during the process of establishing the bearer channel.

GLOSSARY OF ACRONYMS

Acronym	Definition
AC	Assigned Channels
AID	Analog-to-Digital
ADPCM	Adaptive Differential Pulse Code Modulation
AFPC	Automatic Forward Power Control
AGC	Automatic Gain Control
AMF	Adaptive Matched Filter
APC	Automatic Power Control
ARPC	Automatic Reverse Power Control
ASPT	Assigned Pilot
AVC	Adaptive Vector Correlator
AXCH	Access Channel
B-CDMA	Broadband Code Division Multiple Access
BCM	Bearer Channel Modification
BER	Bit Error Rate
BS	Base Station
CC	Call Control
CDM	Code Division Multiplex
CDMA	Code Division Multiple Access
CLK	Clock Signal Generator
CO	Central Office
CTCH	Control Channel
CUCH	Check-Up Channel
dB	Decibels
DCC	Data Combiner Circuitry
DI	Distribution Interface
DLL	Delay Locked Loop
DM	Delta Modulator
DS	Direct Sequence
EPIC	Extended PCM Interface Controller
FBCH	Fast Broadcast Channel
FDM	Frequency Division Multiplex
FD/TDMA	Frequency & Time Division Systems
FDMA	Frequency Division Multiple Access
FEC	Forward Error Correction
FSK	Frequency Shift Keying
FSU	Fixed Subscriber Unit
GC	Global Channel
GLPT	Global Pilot
GPC	Global Pilot Code
GPSK	Gaussian Phase Shift Keying
GPS	Global Positioning System
HPPC	High Power Passive Components
HSB	High Speed Bus
I	In-Phase
IC	Interface Controller
ISDN	Integrated Services Digital Network
ISST	Initial System Signal Threshold
LAXPT	Long Access Pilot
LAPD	Link Access Protocol
LCT	Local Craft Terminal
LE	Local Exchange
LFSR	Linear Feedback Shift Register

-continued

GLOSSARY OF ACRONYMS

Acronym	Definition
LI	Line Interface
LMS	Least Mean Square
LOL	Loss of Code Lock
LPF	Low Pass Filter
LSR	Linear Shift Register
MISR	Modern Input Signal Receiver
MIU	Modern Interface Unit
MM	Mobility Management
MOI	Modern Output Interface
MPC	Maintenance Power Control
MPSK	M-ary Phase Shift Keying
MSK	Minimum Shift Keying
MSU	Mobile Subscriber Unit
NE	Network Element
OMS	Operation and Maintenance System
OS	Operations System
OQPSK	Offset Quadrature Phase Shift Keying
OW	Order Wire
PARK	Portable Access Rights Key
PBX	Private Branch Exchange
PCM	Pulse Coded Modulation
PCS	Personal Communication Services
PG	Pilot Generator
PLL	Phase Locked Loop
PLT	Pilot
PN	Pseudonoise
POTS	Plain Old Telephone Service
PSTN	Public Switched Telephone Network
Q	Quadrature
QPSK	Quadrature Phase Shift Keying
RAM	Random Access Memory
RCS	Radio Carrier Station
RDI	Receiver Data Input Circuit
RDU	Radio Distribution Unit
RF	Radio Frequency
RLL	Radio Local Loop
SAXPT	Short Access Channel Pilots
SBCH	Slow Broadcast Channel
SHF	Super High Frequency
SIR	Signal Power to Interface Noise Power Ratio
SHC	Subscriber Line Interface Circuit
SNR	Signal-to-Noise Ratio
SPC	Service PC
SPRT	Sequential Probability Ratio Test
STCH	Status Channel
SU	Subscriber Unit
TDM	Time Division Multiplexing
TMN	Telecommunication Management Network
TRCH	Traffic Channels
TSI	Time-Slot Interchanger
TX	Transmit
TXIDAT	I-Modern Transmit Data Signal
TXQDAT	Q-Modern Transmit Data Signal
UHF	Ultra High Frequency
VCO	Voltage Controlled Oscillator
VDC	Video Distribution Circuit
VGA	Variable Gain Amplifier
VHF	Very High Frequency
WAC	Wireless Access Controller

DESCRIPTION OF THE EXEMPLARY EMBODIMENT

General System Description

The system of the present invention provides local-loop telephone to service using radio links between one or more base stations and multiple remote subscriber units. In the exemplary embodiment, a radio link is described for a base station communicating with a fixed subscriber unit (FSU), but the system is equally applicable to systems including multiple base stations with radio links to both FSUs and Mobile Subscriber Units (MSUs). Consequently, the remote subscriber units are referred to herein as Subscriber Units (SUs).

Referring to FIG. 1, Base Station (BS) 101 provides call connection to a local exchange (LE) 103 or any other telephone network switching interface, such as a private branch exchange (PBX) and includes a Radio Carrier Station (RCS) 104. One or more RCSs 104, 105, 110 connect to a Radio Distribution Unit (RDU) 102 through links 131, 132, 137, 138, 139, and RDU 102 interfaces with LE 103 by transmitting and receiving call set-up, control, and information signals through telco links 141, 142, 150. SUs 116, 119 communicate with the RCS 104 through radio links 161, 162, 163, 164, 165. Alternatively, another embodiment of the invention includes several SUs and a "master" SU with functionality similar to the RCS. Such an embodiment may or may not have connection to a local telephone network.

The radio links 161 to 165 operate within the frequency bands of the DCS1800 standard (1.71–1.785 GHz and 1.805–1.880 GHz); the US-PCS standard (1.85–1.99 GHz); and the CEPT standard (2.0–2.7 GHz). Although these bands are used in described embodiment, the invention is equally applicable to the entire UHF to SHF bands, including bands from 2.7 GHz to 5 GHz. The transmit and receive bandwidths are multiples of 3.5 MHz starting at 7 MHz, and multiples of 5 MHz starting at 10 MHz, respectively. The described system includes bandwidths of 7, 10, 10.5, 14 and 15 MHz. In the exemplary embodiment of the invention, the minimum guard band between the Uplink and Downlink is 20 MHz, and is desirably at least three times the signal bandwidth. The duplex separation is between 50 to 175 MHz, with the described invention using 50, 75, 80, 95, and 175 MHz. Other frequencies may also be used.

Although the described embodiment uses different spread-spectrum bandwidths centered around a carrier for the transmit and receive spread-spectrum channels, the present method is readily extended to systems using multiple spread-spectrum bandwidths for the transmit channels and multiple spread-spectrum bandwidths for the receive channels. Alternatively, because spread-spectrum communication systems have the inherent feature that one user's transmission appears as noise to another user's despreading receiver, an embodiment may employ the same spread-spectrum channel for both the transmit and receive path channels. In other words, Uplink and Downlink transmissions can occupy the same frequency band. Furthermore, the present method may be readily extended to multiple CDMA frequency bands, each conveying a respectively different set of messages, uplink, downlink or uplink and downlink.

The spread binary symbol information is transmitted over the radio links 161 to 165 using Quadrature Phase Shift Keying (QPSK) modulation with Nyquist Pulse Shaping in the present embodiment, although other modulation techniques may be used, including, but not limited to, Offset QPSK (OQPSK) and Minimum Shift Keying (MSK). Gaussian Phase Shift Keying (GPSK) and M-ary Phase Shift Keying (MPSK)

The radio links 161 to 165 incorporate Broadband Code Division Multiple Access (B-CDMA™) as the mode of transmission in both the Uplink and Downlink directions. CDMA (also known as Spread Spectrum) communication techniques used in multiple access systems are well-known, and are described in U.S. Pat. No. 5,228,056 entitled SYNCHRONOUS SPREAD-SPECTRUM COMMUNICATION SYSTEM AND METHOD by Donald T Schilling. The system described utilizes the Direct Sequence (DS) spreading technique. The CDMA modulator performs the spread-spectrum spreading code sequence generation, which can be a pseudonoise (PN) sequence; and complex DS modulation of the QPSK signals with spreading code sequences for the

In-phase (I) and Quadrature (Q) channels. Pilot signals are generated and transmitted with the modulated signals, and pilot signals of the present embodiment are spreading codes not modulated by data. The pilot signals are used for synchronization, carrier phase recovery, and for estimating the impulse response of the radio channel. Each SU includes a single pilot generator and at least one CDMA modulator and demodulator, together known as a CDMA modem. Each RCS 104, 105, 110 has a single pilot generator plus sufficient CDMA modulators and demodulators for all of the logical channels in use by all SUs.

The CDMA demodulator despreads the signal with appropriate processing to combat or exploit multipath propagation effects. Parameters concerning the received power level are used to generate the Automatic Power Control (AC) information which, in turn, is transmitted to the other end of the communication link. The AC information is used to control transmit power of the automatic forward power control (AFPC) and automatic reverse power control (ARPC) links. In addition, each RCS 104, 105 and 110 can perform Maintenance Power Control (MPC), in a manner similar to AC, to adjust the initial transmit power of each SU 111, 112, 115, 117 and 118. Demodulation is coherent where the pilot signal provides the phase reference.

The described radio links support multiple traffic channels with data rates of 8, 16, 32, 64, 128, and 144 kb/s. The physical channel to which a traffic channel is connected operates with a 64 k symbol/sec rate. Other data rates may be supported, and Forward Error Correction (FEC) coding can be employed. For the described embodiment, FEC with coding rate of $\frac{1}{2}$ and constraint length 7 is used. Other rates and constraint lengths can be used consistent with the code generation techniques employed.

Diversity combining at the radio antennas of RCS 104, 105 and 110 is not necessary because CDMA has inherent frequency diversity due to the spread bandwidth. Receivers include Adaptive Matched Filters (AMFs) (not shown in FIG. 1) which combine the multipath signals. In the present embodiment, the exemplary AMFs perform Maximal Ratio Combining.

Referring to FIG. 1, RCS 104 interfaces to RDU 102 through links 131, 132, 137 with, for example, 1.544 Mb/s DS 1, 2.048 Mb/s E1; or HDSL Formats to receive and send digital data signals. While these are typical telephone company standardized interfaces, the present invention is not limited to these digital data formats only. The exemplary RCS line interface (not shown in FIG. 1) translates the line coding (such as HDB3, B8ZS, AMI) and extracts or produces framing information, performs Alarms and Facility signaling functions, as well as channel specific loop-back and parity check functions. The interfaces for this description provide 64 kb/s PCM encoded or 32 kb/s ADPCM encoded telephone traffic channels or ISDN channels to the RCS for processing. Other ADPCM encoding techniques can be used consistent with the sequence generation techniques.

The system of the present invention also supports bearer rate modification between the RCS 104 and each SU 111, 112, 115, 117 and 118 communicating with RCS 104 in which a CDMA message channel supporting 64 kb/s may be assigned to voiceband data or FAX when rates above 4.8 kb/s are present. Such 64 kb/s bearer channel is considered an unencoded channel. For ISDN, bearer rate modification may be done dynamically, based upon the D channel messages.

In FIG. 1, each SU 111, 112, 115, 117 and 118 either includes or interfaces with a telephone unit 170, or interfaces

with a local switch (PBX) 171. The input from the telephone unit may include voice, voiceband data and signaling. The SU translates the analog signals into digital sequences, and may also include a Data terminal 172 or an ISDN interface 173. The SU can differentiate voice input, voiceband data or FAX and digital data. The SU encodes voice data with techniques such as ADPCM at 32 kb/s or lower rates, and detects voiceband data or FAX with rates above 4.8 kb/s to modify the traffic channel (bearer rate modification) for unencoded transmission. Also, A-law, u-law, or no companding of the signal may be performed before transmission. For digital data, data compression techniques, such as idle flag removal, may also be used to conserve capacity and minimize interference.

The transmit power levels of the radio interface between RCS 104 and SUs 111, 112, 115, 117 and 118 are controlled using two different closed loop power control methods. The Automatic Forward Power Control (AFPC) method determines the Downlink transmit power level, and the Automatic Reverse Power Control (ARPC) method determines the Uplink transmit power level. The logical control channel by which SU 111 and RCS 104, for example, transfer power control information operates at least a 16 kHz update rate. Other embodiments may use a faster or slower update rate for example 64 kHz. These algorithms ensure that the transmit power of a user maintains an acceptable Bit-Error Rate (BER), maintains the system power at a minimum to conserve power, and maintains the power level of all SUs 111, 112, 115, 117 and 118 received by RCS 104 at a nearly equal level.

In addition, the system uses an optional maintenance power control method during the inactive mode of a SU. When SU 111 is inactive or powered-down to conserve power, the unit occasionally activates to adjust its initial transmit power level setting in response to a maintenance power control signal from RCS 104. The maintenance power signal is determined by the RCS 104 by measuring the received power level of SU 111 and present system power level and, from this, calculates the necessary initial transmit power. The method shortens the channel acquisition time of SU 111 to begin a communication. The method also prevents the transmit power level of SU 111 from becoming too high and interfering with other channels during the initial transmission before the closed loop power control reduces the transmit power.

RCS 104 obtains synchronization of its clock from an interface line such as, but not limited to, E1, T1, or HDSL interfaces. RCS 104 can also generate its own internal clock signal from an oscillator which may be regulated by a Global Positioning System (GPS) receiver. RCS 104 generates a Global Pilot Code, a channel with a spreading code but no data modulation, which can be acquired by remote SUs 111 through 118. All transmission channels of the RCS are synchronized to the Pilot channel, and spreading code phases of code generators (not shown) used for Logical communication channels within RCS 104 are also synchronized to the Pilot channel's spreading code phase. Similarly, SUs 111 through 118 which receive the Global Pilot Code of RCS 104 synchronize the spreading and de-spreading code phases of the code generators (not shown) of the SUs to the Global Pilot Code.

RCS 104, SU 111, and RDU 102 may incorporate system redundancy of system elements and automatic switching between internal functional system elements upon a failure event to prevent loss or drop-out of a radio link, power supply, traffic channel, or group of traffic channels.

Logical Communication Channels

A 'channel' of the prior art is usually regarded as a communications path which is part of an interface and which

can be distinguished from other paths of that interface without regard to its content. However, in the case of CDMA, separate communications paths are distinguished only by their content. The term 'logical channel' is used to distinguish the separate data streams, which are logically equivalent to channels in the conventional sense. All logical channels and sub-channels of the present invention are mapped to a common 64 kilo-symbols per second (ksym/s) QPSK stream. Some channels are synchronized to associated pilot codes which are generated from, and perform a similar function to the system Global Pilot Code (GPC). The system pilot signals are not, however, considered logical channels.

Several logical communication channels are used over the RF communication link between the RCS and SU. Each logical communication channel either has a fixed, pre-determined spreading code or a dynamically assigned spreading code. For both pre-determined and assigned codes, the code phase is synchronized with the Pilot Code. Logical communication channels are divided into two groups: the Global Channel (GC) group includes channels which are either transmitted from the base station RCS to all remote SUs or from any SU to the RCS of the base station regardless of the SU's identity. The channels in the GC group may contain information of a given type for all users including those channels used by SUs to gain system access. Channels in the Assigned Channels (AC) group are those channels dedicated to communication between the RCS and a particular SU.

The Global Channels (GC) group provides for 1) Broadcast Control logical channels, which provide point to multipoint services for broadcasting messages to all SUs and paging messages to SUs; and 2) Access Control logical channels which provide point-to-point services on global channels for SUs to access the system and obtain assigned channels.

The RCS of the present invention has multiple Access Control logical channels, and one Broadcast Control group. An SU of the present invention has at least one Access Control channel and at least one Broadcast Control logical channel.

The Global logical channels controlled by the RCS are the Fast Broadcast Channel (FBCH) which broadcasts fast changing information concerning which services and which access channels are currently available, and the Slow Broadcast Channel (SBCH) which broadcasts slow changing system information and paging messages. The Access Channel (AXCH) is used by the SUs to access an RCS and gain access to assigned channels. Each AXCH is paired with a Control Channel (CTCH). The CTCH is used by the RCS to acknowledge and reply to access attempts by SUs. The Long Access Pilot (LAXPT) is transmitted synchronously with AXCH to provide the RCS with a time and phase reference.

An Assigned Channel (AC) group contains the logical channels that control a single telecommunication connection between the RCS and an SU. The functions developed when an AC group is formed include a pair of power control logical message channels for each of the Uplink and Downlink connections, and depending on the type of connection, one or more pairs of traffic channels. The Bearer Control function performs the required forward error control, bearer rate modification, and encryption functions.

Each SU 111, 112, 115, 117 and 118 has at least one AC group formed when a telecommunication connection exists, and each RCS 104, 105 and 110 has multiple AC groups formed, one for each connection in progress. An AC group

of logical channels is created for a connection upon successful establishment of the connection. The AC group includes encryption, FEC coding, and multiplexing on transmission, and FEC decoding, decryption and demultiplexing on reception.

Each AC group provides a set of connection oriented point-to-point services and operates in both directions between a specific RCS, for example, RCS 104 and a specific SU, for example, SU 111. An AC group formed for a connection can control more than one bearer over the RF communication channel associated with a single connection. Multiple bearers are used to carry distributed data such as, but not limited to, ISDN. An AC group can provide for the duplication of traffic channels to facilitate switch over to 64 kb/s PCM for high speed facsimile and modem services for the bearer rate modification function.

The assigned logical channels formed upon a successful call connection and included in the AC group are a dedicated signaling channel [order wire (OW)], an AC channel, and one or more Traffic channels (TRCH) which are bearers of 8, 16, 32, or 64 kb/s depending on the service supported. For voice traffic, moderate rate coded speech, ADPCM, or PCM can be supported on the Traffic channels. For ISDN service types, two 64 kb/s TRCHs form the B channels and a 16 kb/s TRCH forms the D channel. Alternatively, the AC sub-channel may either be separately modulated on its own CDMA channel, or may be time division multiplexed with a traffic channel or OW channel.

Each SU 111, 112, 115, 117 and 118 of the present invention supports up to three simultaneous traffic channels. The mapping of the three logical channels for TRCHs to the user data is shown below in Table 1:

TABLE 1

Mapping of service types to the three available TRCH channels			
Service	TRCH(0)	TRCH(1)	TRCH(2)
16 kb/s POTS	TRCH/16	not used	not used
32 + 64 kb/s POTS (during BCM)	TRCH/32	TRCH/64	not used
32 kb/s POTS	TRCH/32	not used	not used
64 kb/s POTS	not used	TRCH/64	not used
ISDN D	not used	not used	TRCH/16
ISDN B + D	TRCH/64	not used	TRCH/16
ISDN 2B + D	TRCH/64	TRCH/64	TRCH/16
Digital LL @ 64 kb/s	TRCH/64	not used	not used
Digital LL @ 2 × 64 kb/s	TRCH/64	TRCH/64	not used
Analog LL @ 64 kb/s	TRCH/64	not used	not used

The AC data rate is sent at 64 kb/s. The AC logical channel is not FEC coded to avoid delay and is transmitted at a relatively low power level to minimize capacity used for AC. Alternatively, the AC and OW may be separately modulated using complex spreading code sequences, or they may be time division multiplexed.

The OW logical channel is FEC coded with a rate 1/2 convolutional code. This logical channel is transmitted in bursts when signaling data is present to reduce interference. After an idle period, the OW signal begins with at least 35 symbols prior to the start of the data frame. For silent maintenance call data, the OW is transmitted continuously between frames of data. Table 2 summarizes the logical channels used in the exemplary embodiment:

TABLE 2

Logical Channels and sub-channels of the B-CDMA Air Interface							
Channel name	Abbr.	Brief Description	Direction (forward or reverse)	Bit rate	Max BER	Power level	Pilot
Global Channels							
Fast Broadcast Channel	FBCH	Broadcasts fast-changing system information	F	16 kb/s	1e-4	Fixed	GLPT
Slow Broadcast Channel	SBCH	Broadcasts paging messages to FSUs and slow-changing system information	F	16 kb/s	1e-7	Fixed	GLPT
Access Channels	AXCH(i)	For initial access attempts by FSUs	R	32 kb/s	1e-7	Controlled by APC	LAXPT(i)
Control Channels	CTCH(i)	For granting access	F	32 kb/s	1e-7	Fixed	GLPT
Assigned Channels							
16 kb/s POTS	TRCH/16	General POTS use	F/R	16 kb/s	1e-4	Controlled by APC	F-GLPT R-ASPT
32 kb/s POTS	TRCH/32	General POTS use	F/R	32 kb/s	1e-4	Controlled by APC	F-GLPT R-ASPT
64 kb/s POTS	TRCH/64	POTS use for in-band modems/fax	F/R	64 kb/s	1e-4	Controlled by APC	F-GLPT R-ASPT
D channel	TRCH/16	ISDN D channel	F/R	16 kb/s	1e-7	Controlled by APC	F-GLPT R-ASPT
Order	OW	assigned	F/R	32	1e-7	Controlled	F-GLPT

Logical Channels and sub-channels of the B-CDMA Air Interface

<u>Logical Channels and sub-channels of the B-CDMA Air Interface</u>							
Channel name	Abbr.	Brief Description	Direction (forward or reverse)	Bit rate	Max BER	Power level	Pilot
wire channel		signaling channel		kb/s		by APC	R-ASPT
APC channel	APC	carries APC commands	F/R	64 kb/s	2e-1	Controlled by APC	F-GLPT R-ASPT

The CDMA code generators used to encode the logical channels of the present invention employ Linear Shift Registers (LSRs) with feedback logic which is a method well known in the art. The code generators of the present embodiment of the invention generate 64 synchronous unique sequences. Each RF communication channel uses a pair of these sequences for complex spreading (in-phase and quadrature) of the logical channels, so the generator gives 32 complex spreading sequences. The sequences are generated by a single seed which is initially loaded into a shift register circuit.

The spreading code period of the present invention is defined as an integer multiple of the symbol duration, and the beginning of the code period is also the beginning of the symbol. The relation between bandwidths and the symbol lengths chosen for the exemplary embodiment of the present invention is:

BW (MHZ)	L(chips/symbol)
7	91
10	130
10.5	133
14	182
15	195

It has been determined that the spreading code length of chip values of the present invention is:

$$128 \times 233415 = 29877120 \quad (1)$$

15 The FBCH channel of the exemplary embodiment is an exception because it is not coded with the 128 length sequence, so the FBCH channel spreading code has period 233415.

The nonlinear sequence of length 128 is implemented as a fixed sequence loaded into a shift register with a feed-back connection. The fixed sequence can be generated by an m-sequence of length 127 padded with an extra logic 0, 1, or random value as is well known in the art.

25 The linear sequence of length $L=233415$ is generated using a linear feedback shift register (LFSR) circuit with 36 stages. The feedback connections correspond to a irreducible polynomial $h(n)$ of degree 36. The polynomial $h(x)$ chosen for the exemplary embodiment of the present invention is

30
$$h(x) = x^{36} + x^{35} + x^{30} + x^{28} + x^{26} + x^{25} + x^{22} + x^{20} + x^{19} + x^{17} + x^{16} + x^{15} + x^{14} + x^{12} + x^{11} + x^9 + x^8 + x^4 + x^3 + x^2 + 1$$

or, in binary notation

35 $h(x)=(1100001010110010110111101101100011101)$ (2)

A group of "seed" values for a LFSR representing the polynomial $h(x)$ of equation (2) which generates code sequences that are nearly orthogonal with each other is determined. The first requirement of the seed values is that the seed values do not generate two code sequences which are simply cyclic shifts of each other.

The seeds are represented as elements of $GF(2^{36})$ which is the field of residue classes modulo $h(x)$. This field has a
45 primitive element $\delta = x^2 + x + 1$. The binary representation of δ is

[illegible]

50 Every element of $GF(2^{36})$ can also be written as a power of δ reduced modulo $h(x)$. Consequently, the seeds are represented as powers of δ , the primitive element.

The solution for the order of an element does not require a search of all values; the order of an element divides the order of the field ($\text{GF}(2^{36})$). When δ is any element of $\text{GF}(2^{36})$ with

$$x^e \equiv 1 \quad (4)$$

for some e , then $e|2^{36}-1$. Therefore, the order of any element
60 in $GF(2^{36})$ divides $2^{36}-1$.

Using these constraints, it has been determined that a numerical search generates a group of seed values, n , which are powers of δ , the primitive element of $h(x)$.

The present invention includes a method to increase the number of available seeds for use in a CDMA communication system by recognizing that certain cyclic shifts of the previously determined code sequences may be used simul-

taneously. The round trip delay for the cell sizes and bandwidths of the present invention are less than 3000 chips. In one embodiment of the present invention, sufficiently separated cyclic shifts of a sequence can be used within the same cell without causing ambiguity for a receiver attempting to determine the code sequence. This method enlarges the set of sequences available for use.

By implementing the tests previously described, a total of 3879 primary seeds were determined through numerical computation. These seeds are given mathematically as

$$\delta^n \text{ modulo } h(x) \quad (5)$$

where 3879 values of n are listed in the Appendix A, with $\delta=(00...00111)$ as before in (3).

When all primary seeds are known, all secondary seeds of the present invention are derived from the primary seeds by shifting them multiples of 4095 chips modulo $h(x)$. Once a family of seed values is determined, these values are stored in memory and assigned to logical channels as necessary. Once assigned, the initial seed value is simply loaded into LFSR to produce the required spreading code sequence associated with the seed value.

Rapid Acquisition Feature of Long and Short Codes.

Rapid acquisition of the correct code phase by a spread-spectrum receiver is improved by designing spreading codes which are faster to detect. The present embodiment of the invention includes a new method of generating code sequences that have rapid acquisition properties by using one or more of the following methods. First, a long code may be constructed from two or more short codes. The new implementation uses many code sequences, one or more of which are rapid acquisition sequences of length L that have average acquisition phase searches $r=\log 2L$. Sequences with such properties are well known to those practiced in the art. The average number of acquisition test phases of the resulting long sequence is a multiple of $r=\log 2L$ rather than half of the number of phases of the long sequence.

Second, a method of transmitting complex valued spreading code sequences (In-phase (I) and Quadrature (Q) sequences) in a pilot spreading code signal may be used rather than transmitting real valued sequences. Two or more separate code sequences may be transmitted over the complex channels. If the sequences have different phases, an acquisition may be done by acquisition circuits in parallel over the different code sequences when the relative phase shift between the two or more code channels is known. For example, for two sequences, one can be sent on an In phase (I) channel and one on the Quadrature (Q) channel. To search the code sequences, the acquisition detection means searches the two channels, but begins the (Q) channel with an offset equal to one-half of the spreading code sequence length. With code sequence length of N , the acquisition means starts the search at $N/2$ on the (Q) channel. The average number of tests to find acquisition is $N/2$ for a single code search, but searching the (I) and phase delayed (Q) channel in parallel reduces the average number of tests to $N/4$. The codes sent on each channel could be the same code, the same code with one channel's code phase delayed, or different code sequences.

Epoch and Sub-epoch Structures

The long complex spreading codes used for the exemplary system of the present invention have a number of chips after which the code repeats. The repetition period of the spread-

ing sequence is called an epoch. To map the logical channels to CDMA spreading codes, the present invention uses an Epoch and Sub-epoch structure. The code period for the CDMA spreading code to modulate logical channels is 29877120 chips/code period which is the same number of chips for all bandwidths. The code period is the epoch of the present invention, and Table 3 below defines the epoch duration for the supported chip rates. In addition, two subepochs are defined over the spreading code epoch and are 233415 chips and 128 chips long.

The 233415 chip sub-epoch is referred to as a long sub-epoch, and is used for synchronizing events on the RF communication interface such as encryption key switching and changing from global to assigned codes. The 128 chip short epoch is defined for use as an additional timing reference. The highest symbol rate used with a single CDMA code is 64 ksym/s. There is always an integer number of chips in a symbol duration for the supported symbol rates 64, 32, 16, and 8 ksym/s.

TABLE 3

Bandwidths, Chip Rates, and Epochs

Bandwidth (MHz)	Chip Rate, CompTex (Mchip/sec)	number of chips in a 64 kbit/sec symbol	128 chip sub-epoch duration* (μ s)	233415 chip sub-epoch duration* (ms)	Epoch duration (sec)
7	5.824	91	21.978	40.078	5.130
10	8.320	130	15.385	28.055	3.591
10.5	8.512	133	15.038	27.422	3.510
14	11.648	182	10.989	20.039	2.565
15	12.480	195	10.256	18.703	2.394

*numbers in these columns are rounded to 5 digits.

Mapping of the Logical Channels to Epochs and Sub-epochs

The complex spreading codes are designed such that the beginning of the sequence epoch coincides with the beginning of a symbol for all of the bandwidths supported. The present invention supports bandwidths of 7, 10, 10.5, 14, and 15 MHz. Assuming nominal 20% roll-off, these bandwidths correspond to the following chip rates in Table 4.

TABLE 4

Supported Bandwidths and Chip Rates for CDMA.

BW (MHz)	R_c (Complex Mchips/sec)	Excess BW, %	$L: (R_c/L) = 64 \text{ k}$	Factorization of L
7	5.824	20.19	91	7×13
10	8.320	20.19	130	$2 \times 5 \times 13$
10.5	8.512	23.36	133	7×19
14	11.648	20.19	182	$2 \times 7 \times 13$
15	12.480	20.19	195	$3 \times 5 \times 13$

The number of chips in an epoch is:

$$N=29877120=2^7 \times 3^3 \times 5 \times 7 \times 13 \times 19 \quad (6)$$

If interleaving is used, the beginning of an interleaver period coincides with the beginning of the sequence epoch. The spreading sequences generated using the method of the present invention can support interleaver periods that are multiples of 1.5 ms for various bandwidths.

Cyclic sequences of the prior art are generated using linear feedback shift register (LFSR) circuits. However, this method does not generate sequences of even length. One

embodiment of the spreading code sequence generator using the code seeds generated previously is shown in FIG. 2a, FIG. 2b, and FIG. 2c. The present invention uses a 36 stage LFSR 201 to generate a sequence of period $N'=233415=3^3 \times 5 \times 7 \times 13 \times 19$, which is C_0 in FIG. 2a. In FIGS. 2a, 2b, and 2c, the symbol \oplus represents a binary addition (EXCLUSIVE-OR). A sequence generator designed as above generates the in-phase and quadrature parts of a set of complex sequences. The tap connections and initial state of the 36 stage LFSR determine the sequence generated by this circuit. The tap coefficients of the 36 stage LFSR are determined such that the resulting sequences have the period 233415. Note that the tap connections shown in FIG. 2a correspond to the polynomial given in equation (2). Each resulting sequence is then overlaid by binary addition with the 128 length sequence C^* to obtain the epoch period 29877120.

FIG. 2b shows a Feed Forward (FF) circuit 202 which is used in the code generator. The signal $X[n-1]$ is output of the chip delay 211, and the input of the chip delay 211 is $X[n]$. The code chip $C[n]$ is formed by the logical adder 212 from the input $X[n]$ and $X[n-1]$. FIG. 2c shows the complete spreading code generator. From the LFSR 201, output signals go through a chain of up to 63 single stage FFs 203 cascaded as shown. The output of each FF is overlaid with the short, even code sequence C^* period $128=2^7$ which is stored in code memory 222 and which exhibits spectral characteristics of a pseudorandom sequence to obtain the epoch $N=29877120$. This sequence of 128 is determined by using an m-sequence (PN sequence) of length $127=2^7-1$ and adding a bit-value, such as logic 0, to the sequence to increase the length to 128 chips. The even code sequence C^* is input to the even code shift register 221, which is a cyclic register, that continually outputs the sequence. The short sequence is then combined with the long sequence using an EXCLUSIVE-OR operation 213, 214, 220.

As shown in FIG. 2c, up to 63 spreading code sequences C_0 through C_{63} are generated by tapping the output signals of FFs 203 and logically adding the short sequence C^* in binary adders 213, 214, and 220, for example. One skilled in the art would realize that the implementation of FF 203 will create a cumulative delay effect for the code sequences produced at each FF stage in the chain. This delay is due to the nonzero electrical delay in the electronic components of the implementation. The timing problems associated with the delay can be mitigated by inserting additional delay elements into the FF chain in one version of the embodiment of the invention. The FF chain of FIG. 2c with additional delay elements is shown in FIG. 2d.

The code-generators in the exemplary embodiment of the present invention are configured to generate either global codes, or assigned codes. Global codes are CDMA codes that can be received or transmitted by all users of the system. Assigned codes are CDMA codes that are allocated for a particular connection. When a set of sequences are generated from the same generator as described, only the seed of the 36 stage LFSR is specified to generate a family of sequences. Sequences for all the global codes, are generated using the same LFSR circuit. Therefore, once an SU has synchronized to the Global pilot signal from an RCS and knows the seed for the LFSR circuit for the Global Channel codes, it can generate not only the pilot sequence but also all other global codes used by the RCS.

The signal that is upconverted to RF is generated as follows. The output signals of the above shift register circuits are converted to an antipodal sequence (0 maps into +1, 1 maps into -1). The Logical channels are initially converted to QPSK signals, which are mapped as constel-

lation points as is well known in the art. The In-phase and Quadrature channels of each QPSK signal form the real and imaginary parts of the complex data value. Similarly, two spreading codes are used to form complex spreading chip values. The complex data are spread by being multiplied by the complex spreading code. Similarly, the received complex data is correlated with the conjugate of the complex spreading code to recover despread data.

Short Codes

Short codes are used for the initial ramp-up process when an SU accesses an RCS. The period of the short codes is equal to the symbol duration and the start of each period is aligned with a symbol boundary. Both SU and RCS derive the real and imaginary parts of the short codes from the last eight feed-forward sections of the sequence generator producing the global codes for that cell.

The short codes that are in use in the exemplary embodiment of the invention are updated every 3 ms. Other update times that are consistent with the symbol rate may be used. Therefore, a change-over occurs every 3 ms starting from the epoch boundary. At a change-over, the next symbol length portion of the corresponding feed-forward output becomes the short code. When the SU needs to use a particular short code, it waits until the first 3 ms boundary of the next epoch and stores the next symbol length portion output from the corresponding FF section. This shall be used as the short code until the next change-over, which occurs 3 ms later.

The signals represented by these short codes are known as Short Access Channel pilots (SAXPTs).

Mapping of Logical Channels to Spreading Codes

The exact relationship between the spreading code sequences and the CDMA logical channels and pilot signals is documented in Table 5a and Table 5b. Those signal names ending in '-CH' correspond to logical channels. Those signal names ending in '-PT' correspond to pilot signals, which are described in detail below.

TABLE 5a

Spreading code sequences and global CDMA codes

Sequence	Quadrature	Logical Channel or Pilot Signal	Direction
C_0	I	FPCH	Forward (F)
C_1	Q	FBCH	F
$C_2 \oplus C^*$	I	GLPT	F
$C_3 \oplus C^*$	Q	GLPT	F
$C_4 \oplus C^*$	I	SBCH	F
$C_5 \oplus C^*$	Q	SBCH	F
$C_6 \oplus C^*$	I	CTCH(0)	F
$C_7 \oplus C^*$	Q	CTCH (0)	F
$C_8 \oplus C^*$	I	APCH (1)	F
$C_9 \oplus C^*$	Q	APCH (1)	F
$C_{10} \oplus C^*$	I	CTCH (1)	F
$C_{11} \oplus C^*$	Q	CTCH(1)	F
$C_{12} \oplus C^*$	I	APCH(1)	F
$C_{13} \oplus C^*$	Q	APCH (1)	F
$C_{14} \oplus C^*$	I	CTCH (2)	F
$C_{15} \oplus C^*$	Q	CTCH (2)	F
$C_{16} \oplus C^*$	I	APCH (2)	F
$C_{17} \oplus C^*$	Q	APCH (2)	F
$C_{18} \oplus C^*$	I	CTCH (3)	F
$C_{19} \oplus C^*$	Q	CTCH (3)	F
$C_{20} \oplus C^*$	I	APCH (3)	F
$C_{21} \oplus C^*$	Q	APCH (3)	F
$C_{22} \oplus C^*$	I	reserved	—

TABLE 5a-continued

Spreading code sequences and global CDMA codes			
Sequence	Quadrature	Logical Channel or Pilot Signal	Direction
C ₂₃ ⊕C*	Q	reserved	—
...
C ₄₀ ⊕C*	I	reserved	—
C ₄₁ ⊕C*	Q	reserved	—
C ₄₂ ⊕C*	I	AXCH(3)	Reverse (R)
C ₄₃ ⊕C*	Q	AXCH(3)	R
C ₄₄ ⊕C*	I	LAXPT(3)	R
		SAXPT(3) seed	
C ₄₅ ⊕C*	Q	LAXPT(3)	R
		SAXPT(3) seed	
C ₄₆ ⊕C*	I	AXCH(2)	R
C ₄₇ ⊕C*	Q	AXCH(2)	R
C ₄₈ ⊕C*	I	LAXPT(2)	R
		SAXPT(2) seed	
C ₄₉ ⊕C*	Q	LAXPT(2)	R
		SAXPT(2) seed	
C ₅₀ ⊕C*	I	AXCH(1)	R
C ₅₁ ⊕C*	Q	AXCH(1)	R
C ₅₂ ⊕C*	I	LAXPT(1)	R
		SAXPT(1) seed	
C ₅₃ ⊕C*	Q	LAXPT(1)	R
		SAXPT(1) seed	
C ₅₄ ⊕C*	I	AXCH(0)	R
C ₅₅ ⊕C*	Q	AXCH(0)	R
C ₅₆ ⊕(00ab)C*	I	LAXPT(0)	R
		SAXPT(0) seed	
C ₅₇ ⊕C*	Q	LAXPT(0)	R
		SAXPT(0) seed	
C ₅₈ ⊕C*	I	IDLE	—
C ₅₉ ⊕C*	Q	IDLE	—
C ₆₀ ⊕C*	I	AUX	R
C ₆₁ ⊕C*	Q	AUX	R
C ₆₂ ⊕C*	I	reserved	—
C ₆₃ ⊕C*	Q	reserved	—

TABLE 5b

Spreading code sequences and assigned CDMA codes			
Sequence	Quadrature	Logical Channel or Pilot Signal	Direction
C ₀ ⊕C*	I	ASPT	Reverse (R)
C ₁ ⊕C*	Q	ASPT	R
C ₂ ⊕C*	I	APCH	R
C ₃ ⊕C*	Q	APCH	R
C ₄ ⊕C*	I	OWCH	R
C ₅ ⊕C*	Q	OWCH	R
C ₆ ⊕C*	I	TRCH(0)	R
C ₇ ⊕C*	Q	TRCH(0)	R
C ₈ ⊕C*	I	TRCH(1)	R
C ₉ ⊕C*	Q	TRCH(1)	R
C ₁₀ ⊕C*	I	TRCH(2)	R
C ₁₁ ⊕C*	Q	TRCH(2)	R
C ₁₂ ⊕C*	I	TRCH(3)	R
C ₁₃ ⊕C*	Q	TRCH(3)	R
C ₁₄ ⊕C*	I	reserved	—
C ₁₅ ⊕C*	Q	reserved	—
...
C ₄₄ ⊕C*	I	reserved	—
C ₄₅ ⊕C*	Q	reserved	—
C ₄₆ ⊕C*	I	TRCH(3)	Forward (F)
C ₄₇ ⊕C*	Q	TRCH(3)	F
C ₄₈ ⊕C*	I	*TRCH(2)	F
C ₄₉ ⊕C*	Q	TRCH(2)	F
C ₅₀ ⊕C*	I	TRCH(1)	F
C ₅₁ ⊕C*	Q	TRCH(1)	F
C ₅₂ ⊕C*	I	TRCH(0)	F
C ₅₃ ⊕C*	Q	TRCH(0)	F

TABLE 5b-continued

Spreading code sequences and assigned CDMA codes			
Sequence	Quadrature	Logical Channel or Pilot Signal	Direction
C ₅₄ ⊕C*	I	OWCH	F
C ₅₅ ⊕C*	Q	OWCH	F
C ₅₆ ⊕C*	I	APCH	F
C ₅₇ ⊕C*	Q	APCH	F
C ₅₈ ⊕C*	I	IDLE	—
C ₅₉ ⊕C*	Q	IDLE	—
C ₆₀ ⊕C*	I	reserved	—
C ₆₁ ⊕C*	Q	reserved	—
C ₆₂ ⊕C*	I	reserved	—
C ₆₃ ⊕C*	Q	reserved	—

For global codes, the seed values for the 36 bit shift register are chosen to avoid using the same code, or any cyclic shift of the same code, within the same geographical area to prevent ambiguity or harmful interference. No assigned code is equal to, or a cyclic shift of a global code.

Pilot Signals

The pilot signals are used for synchronization, carrier phase recovery, and for estimating the impulse response of the radio channel.

The RCS 104 transmits a forward link pilot carrier reference as a complex pilot code sequence to provide time and phase reference for all SUs 111, 112, 115, 117 and 118 in its service area. The power level of the Global Pilot (GLPT) signal is set to provide adequate coverage over the whole RCS service area, which area depends on the cell size. With only one pilot signal in the forward link, the reduction in system capacity due to the pilot energy is negligible.

The SUs 111, 112, 115, 117 and 118 each transmits a pilot carrier reference as a quadrature modulated (complex-valued) pilot spreading code sequence to provide a time and phase reference to the RCS for the reverse link. The pilot signal transmitted by the SU of one embodiment of the invention is 6 dB lower than the power of the 32 kb/s POTS traffic channel. The reverse pilot channel is subject to APC. The reverse link pilot associated with a particular connection is called the Assigned Pilot (ASPT). In addition, there are pilot signals associated with access channels. These are called the Long Access Channel Pilots (LAXPTs). Short access channel pilots (SAXPTs) are also associated with the access channels and used for spreading code acquisition and initial power ramp-up.

All pilot signals are formed from complex codes, as defined below:

$$\text{GLPT (forward)} = \{C_2 \oplus C^* + j(C_3 \oplus C^*)\} \cdot \{(1) + j(0)\} \\ \{\text{Complex Code}\} \cdot \{\text{Carrier}\}$$

The complex pilot signals are de-spread by multiplication with conjugate spreading codes: $\{(C_2 \oplus C^*) - j(C_3 \oplus C^*)\}$. By contrast, traffic channels are of the form:

$$\text{TRCH}_n(\text{forward/reverse}) = \{(C_k \oplus C^*) + j \cdot \\ (C_l \oplus C^*)\} \cdot \{(\pm 1) + j(\pm 1)\} \{\text{Complex Codes}\} \cdot \{\text{Data Symbol}\}$$

which thus form a constellation set at $\pi/4$ radians with respect to the pilot signal constellations.

The GLPT constellation is shown in FIG. 3a, and the TRCH_n traffic channel constellation is shown in FIG. 3b.

Logical Channel Assignment of the FBCH, SBCH, and Traffic Channels

The FBCH is a global forward link channel used to broadcast dynamic information about the availability of

services and AXCHs. Messages are sent continuously over this channel, and each message lasts approximately 1 ms. The FBCH message is 16 bits long, repeated continuously, and is epoch aligned. The FBCH is formatted as defined in Table 6.

TABLE 6

PBCH format	
Bit	Definition
0	Traffic Light 0
1	Traffic Light 1
2	Traffic Light 2
3	Traffic Light 3
4-7	service indicator bits
8	Traffic Light 0
9	Traffic Light 1
10	Traffic Light 2
11	Traffic Light 3
12-15	service indicator bits

For the FBCH, bit 0 is transmitted first. As used in Table 6, a traffic light corresponds to an Access Channel (AXCH) and indicates whether the particular access channel is currently in use (a red) or not in use (a green). A logic '1' indicates that the traffic light is green, and a logic '0' indicates the traffic light is red. The values of the traffic light bits may change from octet to octet, and each 16 bit message contains distinct service indicator bits which describe the types of services that are available for the AXCHs.

One embodiment of the present invention uses service indicator bits as follows to indicate the availability of services or AXCHs. The service indicator bits {4,5,6,7,12,13,14,15} taken together may be an unsigned binary number, with bit 4 as the MSB and bit 15 as the LSB. Each service type increment has an associated nominal measure of the capacity required, and the FBCH continuously broadcasts the available capacity. This is scaled to have a maximum value equivalent to the largest single service increment possible. When an SU requires a new service or an increase in the number of bearers, it compares the capacity required to that indicated by the FBCH, and then considers itself blocked if the capacity is not available. The FBCH and the traffic channels are aligned to the epoch.

Slow Broadcast Information frames contain system or other general information that is available to all SUs and Paging Information frames contain information about call requests for particular SUs. Slow Broadcast Information frames and Paging Information frames are multiplexed together on a single logical channel which forms the Slow Broadcast Channel (SBCH). As previously defined, the code epoch is a sequence of 29 877 20 chips having an epoch duration which is a function of the chip rate defined in Table 7 below. In order to facilitate power saving, the channel is divided into N "Sleep" Cycles, and each Cycle is subdivided into M Slots, which are 19 ms long, except for 10.5 Mhz bandwidth which has slots of 18 ms.

TABLE 7

SBCH Channel Format Outline						
Bandwidth (MHz)	Spreading Code Rate (MHz)	Epoch Length (ms)	Cycles/ Epoch N	Cycle Length (ms)	Slots/ Cycle M	Slot Length (ms)
7.0	5.824	5130	5	1026	54	19
10.0	8.320	3591	3	1197	63	19
10.5	8.512	3510	3	1170	65	18

TABLE 7-continued

SBCH Channel Format Outline						
Bandwidth (MHz)	Spreading Code Rate (MHz)	Epoch Length (ms)	Cycles/ Epoch N	Cycle Length (ms)	Slots/ Cycle M	Slot Length (ms)
14.0	11.648	2565	3	855	45	19
15.0	12.480	2394	2	1197	63	19

Sleep Cycle Slot #1 is always used for slow broadcast information. Slots #2 to #M-1 are used for paging groups unless extended slow broadcast information is inserted. The pattern of cycles and slots in one embodiment of the present invention run continuously at 16 kb/s.

Within each Sleep Cycle the SU powers-up the receiver and re-acquires the pilot code. It then achieves carrier lock to a sufficient precision for satisfactory demodulation and Viterbi decoding. The settling time to achieve carrier lock may be up to 3 Slots in duration. For example, an SU assigned to Slot #7 powers up the Receiver at the start of Slot #4. Having monitored its Slot the SU will have either recognized its Paging Address and initiated an access request, or failed to recognize its Paging Address in which case it reverts to the Sleep mode. Table 8 shows duty cycles for the different bandwidths, assuming a wake-up duration of 3 Slots.

TABLE 8

Sleep-Cycle Power Saving		
Bandwidth (MHz)	Slots/Cycle	Duty Cycle
7.0	54	7.4%
10.0	63	6.3%
10.5	65	6.2%
14.0	45	8.9%
15.0	63	6.3%

Spreading Code Tracking and AMF Detection in Multipath Channels

Spreading Code Tracking

Three CDMA spreading code tracking methods in multipath fading environments are described which track the code phase of a received multipath spread-spectrum signal. The first is the prior art tracking circuit which simply tracks the spreading code phase with the highest detector output signal value, the second is a tracking circuit that tracks the median value of the code phase of the group of multipath signals, and the third is the centroid tracking circuit which tracks the code-phase of an optimized, least mean squared weighted average of the multipath signal components. The following describes the algorithms by which the spreading code phase of the received CDMA signal is tracked.

A tracking circuit has operating characteristics that reveal the relationship between the time error and the control voltage that drives a Voltage Controlled Oscillator (VCO) of a spreading code phase tracking circuit. When there is a positive timing error, the tracking circuit generates a negative control voltage to offset the timing error. When there is a negative timing error, the tracking circuit generates a positive control voltage to offset the timing error. When the tracking circuit generates a zero value, this value corresponds to the perfect time alignment called the 'lock-point'.

FIG. 3 shows the basic tracking circuit. Received signal $r(t)$ is applied to matched filter 301, which correlates $r(t)$ with a local code-sequence $c(t)$ generated by Code Generator 303. The output signal of the matched filter $x(t)$ is sampled at the sampler 302 to produce samples $x|nT|$ and $x|nT+T/2|$. The samples $x|nT|$ and $x|nT+T/2|$ are used by a tracking circuit 304 to determine if the phase of the spreading code $c(t)$ of the code generator 303 is correct. The tracking circuit 304 produces an error signal $e(t)$ as an input to the code generator 303. The code generator 303 uses this signal $e(t)$ as an input signal to adjust the code-phase it generates.

In a CDMA system, the signal transmitted by the reference user is written in the low-pass representation as

$$s(t) = \sum_{k=-\infty}^{\infty} c_k P_{T_c}(t - kT_c) \quad (7)$$

where c_k represents the spreading code coefficients, $P_{T_c}(t)$ represents the spreading code chip waveform, and T_c is the chip duration. Assuming that the reference user is not transmitting data so that only the spreading code modulates the carrier. Referring to FIG. 3c, the received signal is

$$r(t) = \sum_{i=1}^M a_i s(t - \tau_i) \quad (8)$$

Here, a_i is due to fading effect of the multipath channel on the i -th path and τ_i is the random time delay associated with the same path. The receiver passes the received signal through a matched filter, which is implemented as a correlation receiver and is described below. This operation is done in two steps: first the signal is passed through a chip matched filter and sampled to recover the spreading code chip values, then this chip sequence is correlated with the locally generated code sequence.

FIG. 3c shows the chip matched filter 301, matched to the chip waveform $P_{T_c}(t)$, and the sampler 302. Ideally, the signal $x(t)$ at the output terminal of the chip matched filter is

$$x(t) = \sum_{i=1}^M \sum_{k=-\infty}^{\infty} a_i c_k g(t - \tau_i - kT_c) \quad (9)$$

where

$$g(t) = P_{T_c}(t) * h_R(t) \quad (10)$$

Here, $h_R(t)$ is the impulse response of the chip matched filter and '*' denotes convolution. The order of the summations can be rewritten as

$$x(t) = \sum_{k=-\infty}^{\infty} c_k g(t - kT_c) \quad (11)$$

where

$$f(t) = \sum_{i=1}^M a_i g(t - \tau_i) \quad (12)$$

In the multipath channel described above, the sampler samples the output signal of the matched filter to produce $x(nT)$ at the maximum power level points of $g(t)$. In practice, however, the waveform $g(t)$ is severely distorted because of the effect of the multipath signal reception, and a perfect time alignment of the signals is not available.

When the multipath distortion in the channel is negligible and a perfect estimate of the timing is available, i.e., $a_1=1$, $\tau_1=0$, and $a_i=0$, $i=2, \dots, M$, the received signal is $r(t)=s(t)$. Then, with this ideal channel model, the output of the chip matched filter becomes

$$x(t) = \sum_{k=-\infty}^{\infty} c_k g(t - kT_c) \quad (13)$$

When there is multipath fading, however, the received spreading code chip value waveform is distorted, and has a number of local maxima that can change from one sampling interval to another depending on the channel characteristics.

For multipath fading channels with quickly changing channel characteristics, it is not practical to try to locate the maximum of the waveform $f(t)$ in every chip period interval. Instead, a time reference may be obtained from the characteristics of $f(t)$ that may not change as quickly. Three tracking methods are described based on different characteristics of $f(t)$.

Prior Art Spreading Code Tracking Method:

Prior art tracking methods include a code tracking circuit in which the receiver attempts to determine the timing of the maximum matched filter output value of the chip waveform occurs and sample the signal accordingly. However, in multipath fading channels, the receiver despread code waveform can have a number of local maxima, especially in a mobile environment. In the following, $f(t)$ represents the received signal waveform of the spreading code chip convolved with the channel impulse response. The frequency response characteristic of $f(t)$ and the maximum of this characteristic can change rather quickly making it impractical to track the maximum of $f(t)$.

Define τ to be the time estimate that the tracking circuit calculates during a particular sampling interval. Also, define the following error function

$$\epsilon = \begin{cases} \int_{\{t: |\tau - t| > \delta\}} f(t) dt, & |\tau - t| > \delta \\ 0, & |\tau - t| < \delta \end{cases} \quad (14)$$

The tracking circuits of the prior art calculate a value of the input signal that minimizes the error ϵ . One can write

$$\text{mine} = 1 - \max_{\tau} \int_{\tau - \delta}^{\tau + \delta} f(t) dt \quad (15)$$

Assuming $f(\tau)$ has a smooth shape in the values given, the value of τ for which $f(\tau)$ is maximum minimizes the error ϵ , so the tracking circuit tracks the maximum point of $f(t)$.

Median Weighted Value Tracking Method:

The Median Weighted Tracking Method of one embodiment of the present invention, minimizes the absolute weighted error, defined as

$$\epsilon = \int_{-\infty}^{\infty} |t - \tau| f(t) dt \quad (16)$$

This tracking method calculates the 'median' signal value of $f(t)$ by collecting information from all paths, where $f(t)$ is as in equation 12. In a multipath fading environment, the waveform $f(t)$ can have multiple local maxima, but only one median.

To minimize ϵ , take the derivative of equation (16) is taken with respect to τ and the result is equated to zero, which gives

$$\int_{-\infty}^{\tau} f(t)dt = \int_{\tau}^{\infty} f(t)dt \quad (17)$$

The value of τ that satisfies (17) is called the 'median' of $f(t)$. Therefore, the Median Tracking Method of the present embodiment tracks the median of $f(t)$. FIG. 4 shows an implementation of the tracking circuit based on minimizing the absolute weighted error defined above. The signal $x(t)$ and its one-half chip offset version $x(t+T/2)$ are sampled by the A/D 401 at a rate $1/T$. The following equation determines the operating characteristic of the circuit in FIG. 4:

$$\epsilon(\tau) = \sum_{n=1}^{2L} [f(\tau - nT/2) - f(\tau + nT/2)] \quad (18)$$

Tracking the median of a group of multipath signals keeps the received energy of the multipath signal components substantially equal on the early and late sides of the median point of the correct locally generated spreading code phase c_n . The tracking circuit consists of an A/D 401 which samples an input signal $x(t)$ to form the half-chip offset samples. The half chip offset samples are alternatively grouped into even samples called an early set of samples $x(nT+\tau)$ and odd samples called a late set of samples $x(nT+(T/2)+\tau)$. The first correlation bank adaptive matched filter 402 multiplies each early sample by the spreading code phases $c(n+1), c(n+2), \dots, c(n+L)$, where L is small compared to the code length and approximately equal to number of chips of delay between the earliest and latest multipath signal. The output of each correlator is applied to a respective first sum-and-dump bank 404. The magnitudes of the output values of the L sum-and-dumps are calculated in the calculator 406 and then summed in summer 408 to give an output value proportional to the signal energy in the early multipath signals. Similarly, a second correlation bank adaptive matched filter 403 operates on the late samples, using code phases $c(n-1), c(n-2), \dots, c(n-L)$, and each output signal is applied to a respective sum-and-dump circuit in an integrator 405. The magnitudes of the L sum-and-dump output signals are calculated in calculator 407 and then summed in summer 409 to give a value for the late multipath signal energy. Finally, the subtractor 410 calculates the difference and produces error signal $\epsilon(t)$ of the early and late signal energy values.

The tracking circuit adjusts by means of error signal $\epsilon(t)$ the locally generated code phases $c(t)$ to cause the difference between the early and late values to tend toward 0.

Centroid Tracking Method

The optimal spreading code tracking circuit of one embodiment of the present invention is called the squared weighted tracking (or centroid) circuit. Defining τ to denote the time estimate that the tracking circuit calculates, based on some characteristic of $f(t)$, the centroid tracking circuit minimizes the squared weighted error defined as

$$\epsilon = \int_{-\infty}^{\infty} t^2 r - \tau^2 f(t) dt \quad (19)$$

This function inside the integral has a quadratic form, which has a unique minimum. The value of τ that minimizes ϵ can be found by taking the derivative of the above equation with respect to τ and equating to zero, which gives

$$\int_{-\infty}^{\infty} (-2t + 2\tau) f(t) dt = 0 \quad (20)$$

Therefore, the value of τ that satisfies equation (21)

$$\tau - \frac{1}{\beta} \int_{-\infty}^{\infty} t f(t) dt = 0 \quad (21)$$

is the timing estimate that the tracking circuit calculates, where β is a constant value.

Based on these observations, a realization of an exemplary tracking circuit which minimizes the squared weighted error is shown in FIG. 5a. The following equation determines the error signal $\epsilon(\tau)$ of the centroid tracking circuit:

$$\epsilon(\tau) = \sum_{n=1}^{2L} n [f(\tau - nT/2) - f(\tau + nT/2)] = 0 \quad (22)$$

The value that satisfies $\epsilon(\tau)=0$ is the perfect estimate of the timing.

The early and late multipath signal energy on each side of the centroid point are equal. The centroid tracking circuit shown in FIG. 5a consists of an A/D converter 501 which samples an input signal $x(t)$ to form the half-chip offset samples. The half chip offset samples are alternatively grouped as an early set of samples $x(nT+\tau)$ and a late set of samples $x(nT+(T/2)+\tau)$. The first correlation bank adaptive matched filter 502 multiplies each early sample and each late sample by the positive spreading code phases $c(n+1), c(n+2), \dots, c(n+L)$, where L is small compared to the code length and approximately equal to number of chips of delay between the earliest and latest multipath signal. The output signal of each correlator is applied to a respective one of L sum-and-dump circuits of the first sum and dump bank 504. The magnitude value of each sum-and-dump circuit of the sum and dump bank 504 is calculated by the respective calculator in the calculator bank 506 and applied to a corresponding weighting amplifier of the first weighting bank 508. The output signal of each weighting amplifier represents the weighted signal energy in a multipath component signal.

The weighted early multipath signal energy values are summed in sample adder 510 to give an output value proportional to the signal energy in the group of multipath signals corresponding to positive code phases which are the early multipath signals. Similarly, a second correlation bank adaptive matched filter 503 operates on the early and late samples, using the negative spreading code phases $c(n-1), c(n-2), \dots, c(n-L)$; each output signal is provided to a respective sum-and-dump circuit of discrete integrator 505. The magnitude value of the L sum-and-dump output signals are calculated by the respective calculator of calculator bank 507 and then weighted in weighting bank 509. The weighted late multipath signal energy values are summed in sample adder 511 to give an energy value for the group of multipath signals corresponding to the negative code phases which are the late multipath signals. Finally, the adder 512 calculates the difference of the early and late signal energy values to produce error sample value $\epsilon(\tau)$.

The tracking circuit of FIG. 5a produces error signal $\epsilon(\tau)$ which is used to adjust the locally generated code phase $c(nT)$ to keep the weighted average energy in the early and late multipath signal groups equal. The embodiment shown uses weighting values that increase as the distance from the centroid increases. The signal energy in the earliest and latest multipath signals is probably less than the multipath

signal values near the centroid. Consequently, the difference calculated by the adder 510 is more sensitive to variations in delay of the earliest and latest multipath signals.

Quadratic Detector for Tracking

In the new embodiment of the tracking method, the tracking circuit adjusts sampling phase to be "optimal" and robust to multipath. Let $f(t)$ represent the received signal waveform as in equation 12 above. The particular method of optimizing starts with a delay locked loop with an error signal $\epsilon(\tau)$ that drives the loop. The function $\epsilon(\tau)$ must have only one zero at $\tau=\tau_0$ where τ_0 is optimal. The optimal form for $\epsilon(\tau)$ has the canonical form:

$$\epsilon(\tau) = \int_{-\infty}^{\infty} w(t, \tau) f(t) \rho dt \quad (23)$$

where $w(t, \tau)$ is a weighting function relating $f(t)$ to the error $\epsilon(\tau)$, and the relationship indicated by equation (24) also holds

$$\epsilon(\tau + \tau_0) = \int_{-\infty}^{\infty} w(t, \tau + \tau_0) f(t) \rho dt \quad (24)$$

It follows from equation (24) that $w(t, \tau)$ is equivalent to $w(t-\tau)$. Considering the slope M of the error signal in the neighborhood of a lock point τ_0 :

$$M = \frac{d\epsilon(\tau)}{d\tau} \Big|_{\tau_0} = - \int_{-\infty}^{\infty} w'(t-\tau_0) g(t) \rho dt \quad (25)$$

where $w'(t, \tau)$ is the derivative of $w(t, \tau)$ with respect to τ , and $g(t)$ is the average of $ff(t)^2$.

The error $\epsilon(\tau)$ has a deterministic part and a noise part. Let z denote the noise component in $\epsilon(\tau)$, then $|z|^2$ is the average noise power in the error function $\epsilon(\tau)$. Consequently, the optimal tracking circuit maximizes the ratio

$$F = \frac{M^2}{|z|^2} \quad (26)$$

The implementation of the Quadratic Detector is now described. The discrete error value e of an error signal $\epsilon(\tau)$ is generated by performing the operation

$$e = y^T B y \quad (27)$$

where the vector y represents the received signal components $y_i, i=0, 1, \dots, L-1$, as shown in FIG. 5b. The matrix B is an L by L matrix and the elements are determined by calculating values such that the ratio F of equation (26) is maximized.

The Quadratic Detector described above may be used to implement the centroid tracking system described above with reference to FIG. 5a. For this implementation, the vector y is the output signal of the sum and dump circuits 504:

$$y = \{f(\tau-LT), f(\tau-LT+T/2), f(\tau-(L-1)T), \dots, f(\tau), f(\tau+T/2), f(\tau+T), \dots, f(\tau+LT)\}$$

and the matrix B is set forth in table 9.

TABLE 9

B matrix for quadratic form of Centroid Tracking System											
L	0	0	0	0	0	0	0	0	0	0	0
0	L-1/2	0	0	0	0	0	0	0	0	0	0
0	0	L-1	0	0	0	0	0	0	0	0	0
.
.
10	0	0	0	0	1/2	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	-1/2	0	0	0	0	0
.
.
15	0	0	0	0	0	0	0	-L+1	0	0	0
0	0	0	0	0	0	0	0	0	-L+1/2	0	0
0	0	0	0	0	0	0	0	0	0	-L	-L

Determining the Minimum Value of L needed:

The value of L in the previous section determines the minimum number of correlators and sum-and-dump elements. L is chosen as small as possible without compromising the functionality of the tracking circuit.

The multipath characteristic of the channel is such that the received chip waveform $f(t)$ is spread over QT_c seconds, or the multipath components occupy a time period of Q chips duration. The value of L chosen is $L=Q$. Q is found by measuring the particular RF channel transmission characteristics to determine the earliest and latest multipath component signal propagation delay. QT_c is the difference between the earliest and latest multipath component arrival time at a receiver.

Adaptive Vector Correlator

An embodiment of the present invention uses an adaptive vector correlator (AVC) to estimate the channel impulse response and to obtain a reference value for coherent combining of received multipath signal components. The described embodiment employs an array of correlators to estimate the complex channel response affecting each multipath component. The receiver compensates for the channel response and coherently combines the received multipath signal components. This approach is referred to as maximal ratio combining.

Referring to FIG. 6, the input signal $x(t)$ to the system includes interference noise of other message channels, multipath signals of the message channels, thermal noise, and multipath signals of the pilot signal. The signal is provided to AVC 601 which, in the exemplary embodiment, includes a despreading means 602, channel estimation means for estimating the channel response 604, correction means for correcting a signal for effects of the channel response 603, and adder 605. The AVC despreading means 602 is composed of multiple code correlators, with each correlator using a different phase of the pilot code $c(t)$ provided by the pilot code generator 608. The output signal of this despreading means corresponds to a noise power level if the local pilot code of the despreading means is not in phase with the input code signal. Alternatively, it corresponds to a received pilot signal power level plus noise power level if the phases of the input pilot code and locally generated pilot code are the same. The output signals of the correlators of the despreading means are corrected for the channel response by the correction means 603 and are applied to the adder 605 which collects all multipath pilot signal power. The channel response estimation means 604 receives the combined pilot

signal and the output signals of the despreading means 602, and provides a channel response estimate signal, $w(t)$, to the correction means 603 of the AVC, and the estimate signal $w(t)$ is also available to the adaptive matched filter (AMF) described below. The output signal of the despreading means 602 is also provided to the acquisition decision means 606 which decides, based on a particular algorithm such as a sequential probability ratio test (SPRT), if the present output levels of the despreading circuits correspond to synchronization of the locally generated code to the desired input code phase. If the detector finds no synchronization, then the acquisition decision means sends a control signal $a(t)$ to the local pilot code generator 608 to offset its phase by one or more chip period. When synchronization is found, the acquisition decision means informs tracking circuit 607, which achieves and maintains a close synchronization between the received and locally generated code sequences.

An exemplary implementation of the Pilot AVC used to despread the pilot spreading code is shown in FIG. 7. The described embodiment assumes that the input signal $x(t)$ has been sampled with sampling period T to form samples $x(nT+\tau)$, and is composed of interference noise of other message channels, multipath signals of message channels, thermal noise, and multipath signals of the pilot code. The signal $x(nT+\tau)$ is applied to L correlators, where L is the number of code phases over which the uncertainty within the multipath signals exists. Each correlator 701, 702, 703 comprises a multiplier 704, 705, 706, which multiplies the input signal with a particular phase of the Pilot spreading code signal $c((n-i)T)$, and sum-and-dump circuits 708, 709, 710. The output signal of each multiplier 704, 705, 706 is applied to a respective sum-and dump circuit 708, 709, 710 to perform discrete integration. Before summing the signal energy contained in the to outputs of the correlators, the AVC compensates for the channel response and the carrier phase rotation of the different multipath signals. Each output of each sum-and-dump 708, 709, 710 is multiplied with a derotation phaser [complex conjugate of $ep(nT)$] from digital phase lock loop (DPLL) 721 by the respective multiplier 714, 715, 716 to account for the phase and frequency offset of the carrier signal. The Pilot Rake AMF calculates the weighting factors w_k , $k=1, \dots, L$, for each multipath signal by passing the output of each multiplier 714, 715, 716 through a low pass filter (LPF) 711, 712, 713. Each despread multipath signal is multiplied by its corresponding weighting factor in a respective multiplier 717, 718, 719. The output signals of the multipliers 717, 718, 719 are summed in a master adder 720, and the output signal $p(nT)$ of the accumulator 720 consists of the combined despread multipath pilot signals in noise. The output signal $p(nT)$ is also input to the DPLL 721 to produce the error signal $ep(nT)$ for tracking of the carrier phase.

FIGS. 8a and 8b show alternate embodiments of the AVC which can be used for detection and multipath signal component combining. The message signal AVCs of FIGS. 8a and 8b use the weighting factors produced by the Pilot AVC to correct the message data multipath signals. The spreading code signal, $c(nT)$ is the spreading code spreading sequence used by a particular message channel and is synchronous with the pilot spreading code signal. The value L is the number of correlators in the AVC circuit.

The circuit of FIG. 8a calculates the decision variable Z which is given by

$$Z = w_1 \sum_{i=1}^N x(iT + \tau) c(iT) + w_2 \sum_{i=1}^N x(iT + \tau) c((i+1)T) + \dots + w_L \sum_{i=1}^N x(iT + \tau) c((i+L)T) \quad (28)$$

where N is the number of chips in the correlation window. Equivalently, the decision statistic is given by

$$Z = x(T + \tau) \sum_{i=1}^L w_k c(iT) + x(2T + \tau) \sum_{i=1}^L w_k c((i+1)T) + \dots + x(NT + \tau) \sum_{i=1}^L w_k c((i+N)T) = \sum_{k=1}^N x(kT - \tau) \sum_{i=1}^L w_k c((i+k-1)T) \quad (29)$$

The alternative implementation that results from equation (29) is shown in FIG. 8b.

Referring to FIG. 8a, the input signal $x(t)$ is sampled to form $x(nT+\tau)$, and is composed of interference noise of other message channels, multipath signals of message channels, thermal noise, and multipath signals of the pilot code. The signal $x(nT+\tau)$ is applied to L correlators, where L is the number of code phases over which the uncertainty within the multipath signals exists. Each correlator 801, 802, 803 comprises a multiplier 804, 805, 806, which multiplies the input signal by a particular phase of the message channel spreading code signal, and a respective sum-and-dump circuit 808, 809, 810. The output signal of each multiplier 804, 805, 806 is applied to a respective sum-and dump circuit 808, 809, 810 which performs discrete integration. Before summing the signal energy contained in the output signals of the correlators, the AVC compensates for the different multipath signals. Each despread multipath signal and its corresponding weighting factor, which is obtained from the corresponding multipath weighting factor of the pilot AVC, are multiplied in a respective multiplier 817, 818, 819. The output signals of multipliers 817, 818, 819 are summed in a master adder 820, and the output signal $z(nT)$ of the accumulator 820 consists of sampled levels of a despread message signal in noise.

The alternative embodiment of the invention includes a new implementation of the AVC despreading circuit for the message channels which performs the sum-and-dump for each multipath signal component simultaneously. The advantage of this circuit is that only one sum-and dump circuit and one adder is necessary. Referring to FIG. 8b, the message code sequence generator 830 provides a message code sequence to shift register 831 of length L . The output signal of each register 832, 833, 834, 835 of the shift register 831 corresponds to the message code sequence shifted in phase by one chip. The output value of each register 832, 833, 834, 835 is multiplied in multipliers 836, 837, 838, 839 with the corresponding weighting factor w_k , $k=1, \dots, L$ obtained from the Pilot AVC. The output signals of the L multipliers 836, 837, 838, 839 are summed by the adding circuit 840. The adding circuit output signal and the receiver input signal $x(nT + \tau)$ are then multiplied in the multiplier 841 and integrated by the sum-and-dump circuit 842 to produce message signal $z(nT)$.

A third embodiment of the adaptive vector correlator is shown in FIG. 8c. The embodiment shown uses the least mean square (LMS) statistic to implement the vector correlator and determines the derotation factors for each multipath component from the received multipath signal. The AVC of FIG. 8c is similar to the exemplary implementation of the Pilot AVC used to despread the pilot spreading code shown in FIG. 7. The digital phase locked loop 721 is

replaced by the phase locked loop 850 having voltage controlled oscillator 851, loop filter 852, limiter 853, and imaginary component separator 854. The difference between the corrected despread output signal dos and an ideal despread output signal is provided by adder 855, and the difference signal is a despread error value ide which is further used by the derotation circuits to compensate for errors in the derotation factors.

In a multipath signal environment, the signal energy of a transmitted symbol is spread out over the multipath signal components. The advantage of multipath signal addition is that a substantial portion of signal energy is recovered in an output signal from the AVC. Consequently, a detection circuit has an input signal from the AVC with a higher signal-to-noise ratio (SNR), and so can detect the presence of a symbol with a lower bit-error ratio (BER). In addition, measuring the output of the AVC is a good indication of the transmit power of the transmitter, and a good measure of the system's interference noise.

Adaptive Matched Filter

One embodiment of the current invention includes an Adaptive Matched Filter (AMF) to optimally combine the multipath signal components in a received spread spectrum message signal. The AMF is a tapped delay line which holds shifted values of the sampled message signal and combines these after correcting for the channel response. The correction for the channel response is done using the channel response estimate calculated in the AVC which operates on the Pilot sequence signal. The output signal of the AMF is the combination of the multipath components which are summed to give a maximum value. This combination corrects for the distortion of multipath signal reception. The various message despreading circuits operate on this combined multipath component signal from the AMF.

FIG. 8d shows an exemplary embodiment of the AMF. The sampled signal from the A/D converter 870 is applied to the L-stage delay line 872. Each stage of this delay line 872 holds the signal corresponding to a different multipath signal component. Correction for the channel response is applied to each delayed signal component by multiplying the component in the respective multiplier of multiplier bank 874 with the respective weighting factor w_1, w_2, \dots, w_L from the AVC corresponding to the delayed signal component. All weighted signal components are summed in the adder 876 to give the combined multipath component signal $y(t)$.

The combined multipath component signal $y(t)$ does not include the correction due to phase and frequency offset of the carrier signal. The correction for the phase and frequency offset of the carrier signal is made to $y(t)$ by multiplying $y(t)$ with carrier phase and frequency correction (derotation phasor) in multiplier 878. The phase and frequency correction is produced by the AVC as described previously. FIG. 8d shows the correction as being applied before the despreading circuits 880, but alternate embodiments of the invention can apply the correction after the despreading circuits.

Method to Reduce Re-Acquisition Time with Virtual Location

One consequence of determining the difference in code phase between the locally generated pilot code sequence and a received spreading code sequence is that an approximate value for the distance between the base station and a subscriber unit can be calculated. If the SU has a relatively fixed position with respect to the RCS of the base station, the

uncertainty of received spreading code phase is reduced for subsequent attempts at re-acquisition by the SU or RCS. The time required for the base station to acquire the access signal of a SU that has gone "off-hook" contributes to the delay between the SU going off-hook and the receipt of a dial tone from the PSTN. For systems that require a short delay, such as 150 msec for dial tone after off-hook is detected, a method which reduces the acquisition and bearer channel establishment time is desirable. One embodiment of the present invention uses such a method of reducing re-acquisition by use of virtual locating. Additional details of this technique are described in U.S. patent application entitled "VIRTUAL LOCATING OF A FIXED SUBSCRIBER UNIT TO REDUCE RE-ACQUISITION TIME" filed on even date herewith and incorporated herein by reference.

The RCS acquires the SU CDMA signal by searching only those received code phases corresponding to the largest propagation delay of the particular system. In other words, the RCS assumes that all SUs are at a predetermined, fixed distance from the RCS. The first time the SU establishes a channel with the RCS, the normal search pattern is performed by the RCS to acquire the access channel. The normal method starts by searching the code phases corresponding to the longest possible delay, and gradually adjusts the search to the code phases with the shortest possible delay. However, after the initial acquisition, the SU can calculate the delay between the RCS and the SU by measuring the time difference between sending a short access message to the RCS and receiving an acknowledgment message, and using the received Global Pilot channel as a timing reference. The SU can also receive the delay value by having the RCS calculate the round trip delay difference from the code phase difference between the Global Pilot code generated at the RCS and the received assigned pilot sequence from the SU, and then sending the SU the value on a predetermined control channel. Once the round trip delay is known to the SU, the SU may adjust the code phase of the locally generated assigned pilot and spreading code sequences by adding the delay required to make the SU appear to the RCS to be at the predetermined fixed distance from the RCS. Although the method is explained for the largest delay, a delay corresponding to any predetermined location in the system can be used.

A second advantage of the method of reducing re-acquisition by virtual locating is that a conservation in SU power use can be achieved. Note that a SU that is "powered down" or in a sleep mode needs to start the bearer channel acquisition process with a low transmit power level and ramp-up power until the RCS can receive its signal in order to minimize interference with other users. Since the subsequent re-acquisition time is shorter, and because the SU's location is relatively fixed in relation to the RCS, the SU can ramp-up transmit power more quickly because the SU will wait a shorter period of time before increasing transmit power. The SU waits a shorter period because it knows, within a small error range, when it should receive a response from the RCS if the RCS has acquired the SU signal.

The Spread Spectrum Communication System

The Radio Carrier Station (RCS)

The Radio Carrier Station (RCS) of the present invention acts as a central interface between the SU and the remote processing control network element, such as a Radio Distribution Unit (RDU). The interface to the RDU of the present embodiment follows the G.704 standard and an interface according to a modified version of DECT V5.1, but

the present invention can support any interface that can exchange call control and traffic channels. The RCS receives information channels from the RDU including call control data, and traffic channel data such as, but not limited to, 32 kb/s ADPCM, 64 kb/s PCM, and ISDN, as well as system configuration and maintenance data. The RCS also terminates the CDMA radio interface bearer channels with SUs, which channels include both control data, and traffic channel data. In response to the call control data from either the RDU or a SU, the RCS allocates traffic channels to bearer channels on the RF communication link and establishes a communication connection between the SU and the telephone network through an RDU.

As shown in FIG. 9, the RCS receives call control and message information data into the MUXs 905, 906 and 907 through interface lines 901, 902 and 903. Although E1 format is shown, other similar telecommunication formats can be supported in the same manner as described below. The MUXs shown in FIG. 9 may be implemented using circuits similar to that shown in FIG. 10. The MUX shown in FIG. 10 includes system clock signal generator 1001 consisting of phase locked oscillators (not shown) which generate clock signals for the Line PCM highway 1002 (which is part of PCM Highway 910), and high speed bus (HSB) 970; and the MUX Controller 1010 which synchronizes the system clock 1001 to interface line 1004. It is contemplated that the phase lock oscillators can provide timing signals for the RCS in the absence of synchronization to a line. The MUX Line Interface 1011 separates the call control data from the message information data. Referring to FIG. 9, each MUX provides a connection to the Wireless Access Controller (WAC) 920 through the PCM highway 910. The MUX controller 1010 also monitors the presence of different tones present in the information signal by means of tone detector 1030.

Additionally, the MUX Controller 1010 provides the ISDN D channel network signaling locally to the RDU. The MUX line interface 1011, such as a FALC 54, includes an E1 interface 1012 which consists of a transmit connection pair (not shown) and a receive connection pair (not shown) of the MUX connected to the RDU or Central Office (CO) ISDN Switch at the data rate of 2.048 Mbps. The transmit and receive connection pairs are connected to the E1 interface 1012 which translates differential tri-level transmit/receive encoded pairs into levels for use by the Framer 1015. The line interface 1011 uses internal phase-locked-loops (not shown) to produce E1-derived 2.048 MHz, and 4.096 MHz clocks as well as an 8 KHz frame-sync pulse. The line interface can operate in clock-master or clock-slave mode. While the exemplary embodiment is shown as using an E1 Interface, it is contemplated that other types of telephone lines which convey multiple calls may be used, for example, T1 lines or lines which interface to a Private Branch Exchange (PBX).

The line interface framer 1015 frames the data streams by recognizing the framing patterns on channel-1 (time-slot 0) of the incoming line, and inserts and extracts service bits, generates/checks line service quality information.

As long as a valid E1 signal appears at the E1 Interface 1012, the FALC 54, recovers a 2.048 MHz PCM clock signal from the E1 line. This clock, via System Clock 1001, is used system wide as a PCM Highway Clock signal. If the E1 Line fails, the FALC 54 continues to deliver a PCM Clock derived from an oscillator signal $\phi(t)$ connected to the sync input (not shown) of the FALC 54. This PCM Clock serves the RCS system until another MUX with an operational E1 line assumes responsibility for generating the system clock signals.

The framer 1015 generates a Received Frame Sync Pulse, which in turn can be used to trigger the PCM Interface 1016 to transfer data onto the line PCM Highway 1002 and into the RCS System for use by other elements. Since all E1 lines are frame synchronized, all Line PCM Highways are also frame synchronized. From this 8 kHz PCM Sync pulse, the system clock signal generator 1001 of the MUX uses a Phase Locked Loop (not shown) to synthesize the $PN \times 2$ clock [e.g., $15.96 \text{ MHz} \times (W_o(t))$]. The frequency of this clock signal is different for different transmission bandwidths, as described in Table 7.

The MUX includes a MUX Controller 1010, such as a 25 MHz Quad Integrated Communications Controller, containing a microprocessor 1020, program memory 1021, and Time Division Multiplexer (TDM) 1022. The TDM 1022 is coupled to receive the signal provided by the Framer 1015, and extracts information placed in time slots 0 and 16. The extracted information governs how the MUX controller 1010 processes the Link Access Protocol-D (LAPD) data link. The call control and bearer modification messages, such as those defined as V5.1 Network layer messages, are either passed to the WAC, or used locally by the MUX controller 1010.

The RCS Line PCM Highway 1002 is connected to and originates with the Framer 1015 through PCM Interface 1016, and comprises of a 2.048 MHz stream of data in both the transmit and receive direction. The RCS also contains a High Speed Bus (HSB) 970 which is the communication link between the MUX, WAC, to and MIUs. The HSB 970 supports a data rate of, for example, 100 Mbit/sec. Each of the MUX, WAC, and MIU access the HSB using arbitration. The RCS of the present invention also can include several MUXs requiring one board to be a "master" and the rest "slaves". Details on the implementation of the HSB may be found in a U.S. patent application entitled PARALLEL PACKETIZED INTERMODULE ARBITRATED HIGH SPEED CONTROL AND DATA BUS, filed on even date herewith, which is hereby incorporated by reference.

Referring to FIG. 9, the Wireless Access Controller (WAC) 920 is the RCS system controller which manages call control functions and interconnection of data streams between the MUXs 905, 906, 907, Modem Interface Units (MIUs) 931, 932, 933. The WAC 920 also controls and monitors other RCS elements such as the VDC 940, RF 950, and Power Amplifiers 960. The WAC 920 as shown in FIG. 11, allocates bearer channels to the modems on each MIU 931, 932, 933 and allocates the message data on line PCM Highway 910 from the MUXs 905, 906, 907 to the modems on the MIUs 931, 932, 933. This allocation is made through the System PCM Highway 911 by means of a time slot interchange on the WAC 920. If more than one WAC is present for redundancy purposes, the WACs determines the Master-Slave relationship with a second WAC. The WAC 920 also generates messages and paging information responsive to call control signals from the MUXs 905, 906, 907 received from a remote processor, such as an RDU; generates Broadcast Data which is transmitted to the MIU master modem 934; and controls the generation by the MIU MM 934 of the Global system Pilot spreading code sequence. The WAC 920 also is connected to an external Network Manager (NM) 980 for craftperson or user access.

Referring to FIG. 11, the WAC includes a time-slot interchanger (TSI) 1101 which transfers information from one time slot in a Line PCM Highway or System PCM Highway to another time slot in either the same or different Line PCM Highway or System PCM Highway. The TSI 1101 is connected to the WAC controller 1111 of FIG. 11

which controls the assignment or transfer of information from one time slot to another time slot and stores this information in memory 1120. The exemplary embodiment of the invention has four PCM Highways 1102, 1103, 1104, 1105 connected to the TSL. The WAC also is connected to the HSB 970, through which WAC communicates to a second WAC (not shown), to the MUXs and to the MIUs.

Referring to FIG. 11, the WAC 920 includes a WAC controller 1111 employing, for example, a microprocessor 1112, such as a Motorola MC68040 and a communications processor 1113, such as the Motorola MC68360 QUICC communications processor, and a clock oscillator 1114 which receives a clock synch signal $w_o(t)$ from the system clock generator. The clock generator is located on a MUX (not shown) to provide timing to the WAC controller 1111. The WAC controller 1111 also includes memory 1120 including Flash Prom 1121 and SRAM memory 1122. The Flash Prom 1121 contains the program code for the WAC controller 1111, and is reprogrammable for new software programs downloaded from an external source. The SRAM 1122 is provided to contain the temporary data written to and read from memory 1120 by the WAC controller 1111.

A low speed bus 912 is connected to the WAC 920 for transferring control and status signals between the RF Transmitter/Receiver 950, VDC 940, RF 950 and Power Amplifier 960 as shown in FIG. 9. The control signals are sent from the WAC 920 to enable or disable the RF Transmitters/Receiver 950 or Power amplifier 960, and the status signals are sent from the RF Transmitters/Receiver 950 or Power amplifier 960 to monitor the presence of a fault condition.

Referring to FIG. 9, the exemplary RCS contains at least one MIU 931, which is shown in FIG. 12 and now described in detail. The MIU of the exemplary embodiment includes six CDMA modems, but the invention is not limited to this number of modems. The MIU includes a System PCM Highway 1201 connected to each of the CDMA Modems 1210, 1211, 1212, 1215 through a PCM Interface 1220, a Control Channel Bus 1221 connected to MIU controller 1230 and each of the CDMA Modems 1210, 1211, 1212, 1213, an MIU clock signal generator (CLK) 1231, and a modem output combiner 1232. The MIU provides the RCS with the following functions: the MIU controller receives CDMA Channel Assignment Instructions from the WAC and assigns a modem to a user information signal which is applied to the line interface of the MUX and a modem to receive the CDMA channel from the SU; it also combines the CDMA Transmit Modem Data for each of the MIU CDMA modems; multiplexes I and Q transmit message data from the CDMA modems for transmission to the VDC; receives Analog I and Q receive message data from the VDC; distributes the I and Q data to the CDMA modems; transmits and receives digital AGC Data; distributes the AGC data to the CDMA modems; and sends MIU Board Status and Maintenance Information to the WAC 920.

The MIU controller 1230 of the exemplary embodiment of the present invention contains one communication microprocessor 1240, such as the MC68360 "QUICC" Processor, and includes a memory 1242 having a Flash Prom memory 1243 and a SRAM memory 1244. Flash Prom 1243 is provided to contain the program code for the Microprocessors 1240, and the memory 1243 is downloadable and reprogrammable to support new program versions. SRAM 1244 is provided to contain the temporary data space needed by the MC68360 Microprocessor 1240 when the MIU controller 1230 reads or writes data to memory. The MIU CLK circuit 1231 provides a timing signal to the MIU

controller 1230, and also provides a timing signal to the CDMA modems. The MIU CLK circuit 1231 receives and is synchronized to the system clock signal $w_o(t)$. The controller clock signal generator 1213 also receives and synchronizes to the spreading code clock signal $pn(t)$ which is distributed to the CDMA modems 1210, 1211, 1212, 1215 from the MUX.

The RCS of the present embodiment includes a System Modem 1210 contained on one MIU. The System Modem 1210 includes a Broadcast spreader (not shown) and a Pilot Generator (not shown). The Broadcast Modem provides the broadcast information used by the exemplary system, and the broadcast message data is transferred from the MIU controller 1230 to the System Modem 1210. The System Modem also includes four additional modems (not shown) which are used to transmit the signals CT1 through CT4 and AX1 through AX4. The System Modem 1210 provides unweighted I and Q Broadcast message data signals which are applied to the VDC. The VDC adds the Broadcast message data signal to the MIU CDMA Modem Transmit Data of all CDMA modems 1210, 1211, 1212, 1215, and the Global Pilot signal.

The Pilot Generator (PG) 1250 provides the Global Pilot signal which is used by the present invention, and the Global Pilot signal is provided to the CDMA modems 1210, 1211, 1212, 1215 by the MIU controller 1230. However, other embodiments of the present invention do not require the MIU controller to generate the Global Pilot signal, but include a Global Pilot signal generated by any form of CDMA Code Sequence generator. In the described embodiment of the invention, the unweighted I and Q Global Pilot signal is also sent to the VDC where it is assigned a weight, and added to the MIU CDMA Modem transmit data and Broadcast message data signal.

System timing in the RCS is derived from the E1 interface. There are four MUXs in an RCS, three of which (905, 906 and 907) are shown in FIG. 9. Two MUXs are located on each chassis. One of the two MUXs on each chassis is designated as the master, and one of the masters is designated as the system master. The MUX which is the system master derives a 2.048 Mhz PCM clock signal from the E1 interface using a phase locked loop (not shown). In turn, the system master MUX divides the 2.048 Mhz PCM clock signal in frequency by 16 to derive a 128 KHz reference clock signal. The 128 KHz reference clock signal is distributed from the MUX that is the system master to all the other MUXs. In turn, each MUX multiplies the 128 KHz reference clock signal in frequency to synthesize the system clock signal which has a frequency that is twice the frequency of the PN-clock signal. The MUX also divides the 128 KHz clock signal in frequency by 16 to generate the 8 KHz frame synch signal which is distributed to the MIUs. The system clock signal for the exemplary embodiment has a frequency of 11.648 Mhz for a 7 MHz bandwidth CDMA channel. Each MUX also divides the system clock signal in frequency by 2 to obtain the PN-clock signal and further divides the PN-clock signal in frequency by 29 877 120 (the PN sequence length) to generate the PN-synch signal which indicates the epoch boundaries. The PN-synch signal from the system master MUX is also distributed to all MUXs to maintain phase alignment of the internally generated clock signals for each MUX. The PN-synch signal and the frame synch signal are aligned. The two MUXs that are designated as the master MUXs for each chassis then distribute both the system clock signal and the PN-clock signal to the MIUs and the VDC.

The PCM Highway Interface 1220 connects the System PCM Highway 911 to each CDMA Modem 1210, 1211,

1212, 1215. The WAC controller transmits Modem Control information, including traffic message control signals for each respective user information signal, to the MIU controller **1230** through the HSB **970**. Each CDMA Modem **1210, 1211, 1212, 1215** receives a traffic message control signal, which includes signaling information, from the MIU controller **1111**. Traffic message control signals also include call control (CC) information and spreading code and despreading code sequence information.

The MIU also includes the Transmit Data Combiner **1232** which adds weighted CDMA modem transmit data including In-phase (I) and Quadrature (Q) modem transmit data from the CDMA modems **1210, 1211, 1212, 1215** on the MIU. The I modem transmit data is added separately from the Q modem transmit data. The combined I and Q modem transmit data output signal of the Transmit Data Combiner **1232** is applied to the I and Q multiplexer **1233** that creates a single CDMA transmit message channel composed of the I and Q modem transmit data multiplexed into a digital data stream.

The Receiver Data Input Circuit (RDI) **1234** receives the Analog Differential I and Q Data from the Video Distribution Circuit (VDC) **940** shown in FIG. 9 and distributes Analog Differential I and Q Data to each of the CDMA Modems **1210, 1211, 1212, 1215** of the MIU. The Automatic Gain Control Distribution Circuit (AGC) **1235** receives the AGC Data signal from the VDC and distributes the AGC Data to each of the CDMA Modems of the MIU. The TRL circuit **1233** receives the Traffic lights information and similarly distributes the Traffic light data to each of the Modems **1210, 1211, 1212, 1215**.

The CDMA Modem

The CDMA modem provides for generation of CDMA spreading code sequences and synchronization between transmitter and receiver. It also provides four full duplex channels (TR0, TR1, TR2, TR3) programmable to 64, 32, 16, and 8 ksym/sec. each, for spreading and transmission at a specific power level. The CDMA mode measures the received signal strength to allow Automatic Power Control, it generates and transmits pilot signals, and encodes and decodes using the signal for forward error correction (FEC). The modem in an SU also performs transmitter spreading code pulse shaping using an FIR filter. The CDMA modem is also used by the Subscriber Unit (SU), and in the following discussion those features which are used only by the SU are distinctly pointed out. The operating frequencies of the CDMA modem are given in Table 10.

TABLE 10

Operating Frequencies			
Bandwidth (MHz)	Chip Rate (MHz)	Symbol Rate (KHz)	Gain (Chips/Symbol)
7	5.824	64	91
10	8.320	64	130
10.5	8.512	64	133
14	11.648	64	182
15	12.480	64	195

Each CDMA modem **1210, 1211, 1212, 1215** of FIG. 12, and as shown in FIG. 13, is composed of a transmit section **1301** and a receive section **1302**. Also included in the CDMA modem is a control center **1303** which receives control messages CNTRL from the external system. These messages are used, for example, to assign particular spread-

ing codes, activate the spreading or despreading, or to assign transmission rates. In addition, the CDMA modem has a code generator means **1304** used to generate the various spreading and despreading codes used by the CDMA modem. The transmit section **1301** is for transmitting the input information and control signals $mn(t)$, $i=1,2,\dots,I$ as spread-spectrum processed user information signals $sc_i(t)$, $j=1,2,\dots,J$. The transmit section **1301** receives the global pilot code from the code generator **1304** which is controlled by the control means **1303**. The spread spectrum processed user information signals are ultimately added to other similar processed signals and transmitted as CDMA channels over the CDMA RF forward message link, for example to the SUs. The receive section **1302** receives CDMA channels as $rt(t)$ and despreads and recovers the user information and control signals $rc_k(t)$, $k=1,2,\dots,K$ transmitted over the CDMA RF reverse message link, for example to the RCS from the SUs.

CDMA Modem Transmitter Section

Referring to FIG. 14, the code generator means **1304** includes Transmit Timing Control Logic **1401** and spreading code PN-Generator **1402**, and the Transmit Section **1301** includes Modem Input Signal Receiver (MISR) **1410**, Convolution Encoders **1411, 1412, 1413, 1414**, Spreaders **1420, 1421, 1422, 1423, 1424**, and Combiner **1430**. The Transmit Section **1301** receives the message data channels MESSAGE, convolutionally encodes each message data channel in the respective convolutional encoder **1411, 1412, 1413, 1414**, modulates the data with random spreading code sequence in the respective spreader **1420, 1421, 1422, 1423, 1424**, and combines modulated data from all channels, including the pilot code received in the described embodiment from the code generator, in the combiner **1430** to generate I and Q components for RF transmission. The Transmitter Section **1301** of the present embodiment supports four (TR0, TR1, TR2, TR3) 64, 32, 16, 8 kb/s programmable channels. The message channel data is a time multiplexed signal received from the PCM highway **1201** through PCM interface **1220** and input to the MISR **1410**.

FIG. 15 is a block diagram of an exemplary MISR **1410**. For the exemplary embodiment of the present invention, a counter is set by the 8 KHz frame synchronization signal MPCMSYNC and is incremented by 2.048 MHz MPCM-CLK from the timing circuit **1401**. The counter output is compared by comparator **1502** against TRCFG values corresponding to slot time location for TR0, TR1, TR2, TR3 message channel data; and the TRCFG values are received from the MIU Controller **1230** in MCTRL. The comparator sends count signal to the registers **1505, 1506, 1507** and **1508** which clocks message channel data into buffers **1510, 1511, 1512, 1513** using the TXPCNCLK timing signal derived from the system clock. The message data is provided from the signal MSGDAT from the PCM highway signal MESSAGE when enable signals TR0EN, TRIEN, TR2EN and TR3EN from Timing Control Logic **1401** are active. In further embodiments, MESSAGE may also include signals that enable registers depending upon an encryption rate or data rate. If the counter output is equal to one of the channel location addresses, the specified transmit message data in registers **1510, 1511, 1512, 1513** are input to the convolutional encoders **1411, 1412, 1413, 1414** shown in FIG. 14.

The convolutional encoder enables the use of Forward Error Correction (FEC) techniques, which are well known in the art. FEC techniques depend on introducing redundancy in generation of data in encoded form. Encoded data is transmitted and the redundancy in the data enables the

receiver decoder device to detect and correct errors. One embodiment of the present invention employs convolutional encoding. Additional data bits are added to the data in the encoding process and are the coding overhead. The coding rate is expressed as the ratio of data bits transmitted to the total bits (code data+redundant data) transmitted and is called the rate "R" of the code.

Convolution codes are codes where each code bit is generated by the convolution of each new uncoded bit with a number of previously coded bits. The total number of bits used in the encoding process is referred to as the constraint length, "K", of the code. In convolutional coding, data is clocked into a shift register of K bits length so that an incoming bit is clocked into the register, and it and the existing K-1 bits are convolutionally encoded to create a new symbol. The convolution process consists of creating a symbol consisting of a module-2 sum of a certain pattern of available bits, always including the first bit and the last bit in at least one of the symbols.

FIG. 16 shows the block diagram of a K=7, R=1/2 convolution encoder suitable for use as the encoder 1411 shown in FIG. 14. This circuit encodes the TR0 Channel as used in one embodiment of the present invention. Seven-Bit Register 1601 with stages Q1 through Q7 uses the signal TXPNCLK to clock in TR0 data when the TROEN signal is asserted. The output value of stages Q1, Q2, Q3, Q4, Q6,

the In-phase component I of the result being composed of (I xor PNI) and (-Qxor PNQ). Quadrature component Q of the result is (Q xor PNI) and (I xor PNQ). Since there is no channel data input to the pilot channel logic (I=1, Q values are prohibited), the spread output signal for pilot channels yields the respective sequences PNI for I component and PNQ for Q component.

The combiner 1430 receives the I and Q spread transmit data channels and combines the channels into an I modem transmit data signal (TXIDAT) and a Q modem transmit data signal (TXQDAT). The I-spread transmit data and the Q spread transmit data are added separately.

For an SU, the CDMA modem Transmit Section 1301 includes the FIR filters to receive the I and Q channels from the combiner to provide pulse shaping, close-in spectral control and $x/\sin(x)$ correction for the transmitted signal. Separate but identical FIR filters receive the I and Q spread transmit data streams at the chipping rate, and the output signal of each of the filters is at twice the chipping rate. The exemplary FIR filters are 28 tap even symmetrical filters, which upsample (interpolate) by 2. The upsampling occurs before the filtering, so that 28 taps refers to 28 taps at twice the chipping rate, and the upsampling is accomplished by setting every other sample a zero. Exemplary coefficients are shown in Table 11.

TABLE 11

Coefficient Values													
Coeff. No.:	0	1	2	3	4	5	6	7	8	9	10	11	12
Value:	3	-11	-34	-22	19	17	-32	-19	52	24	-94	-31	277
Coeff. No.	14	15	16	17	18	19	20	21	22	24	25	26	27
Value	277	-31	-94	24	52	-19	-32	17	19	-22	-34	-11	3

and Q7 are each combined using EXCLUSIVE-OR Logic 1602, 1603 to produce respective I and Q channel FEC data for the TR0 channel FECTRODI and FECTRODQ.

Two output symbol streams FECTRODI and FECTRODQ are generated. The FECTRODI symbol stream is generated by EXCLUSIVE OR Logic 1602 of shift register outputs corresponding to bits 6, 5, 4, 3, and 0, (Octal 171) and is designated as In phase component "I" of the transmit message channel data. The symbol stream FECTRODQ is likewise generated by EXCLUSIVE-OR logic 1603 of shift register outputs from bits 6, 4, 3, 1 and 0, (Octal 133) and is designated as Quadrature component "Q" of the transmit message channel data. Two symbols are transmitted to represent a single encoded bit creating the redundancy necessary to enable error correction to take place on the receiving end.

Referring to FIG. 14, the shift enable clock signal for the transmit message channel data is generated by the Control Timing Logic 1401. The convolutionally encoded transmit message channel output data for each channel is applied to the respective spreader 1420, 1421, 1422, 1423, 1424 which multiplies the transmit message channel data by its preassigned spreading code sequence from code generator 1402. This spreading code sequence is generated by control 1303 as previously described, and is called a random pseudonoise signature sequence (PN-code).

The output signal of each spreader 1420, 1421, 1422, 1423, 1424 is a spread transmit data channel. The operation of the spreader is as follows: the spreading of channel output (I+jQ) multiplied by a random sequence (PNI-jPNQ) yields

CDMA Modem Receiver Section

Referring to FIGS. 9 and 12, the RF receiver 950 of the present embodiment accepts analog input I and Q CDMA channels, which are transmitted to the CDMA modems 1210, 1211, 1212, 1215 through the MIUs 931, 932, 933 from the VDC 940. These I and Q CDMA channel signals are sampled by the CDMA modem receive section 1302 (shown in FIG. 13) and converted to I and Q digital receive message signal using an Analog to Digital (AID) converter 1730, shown in FIG. 17. The sampling rate of the A/D converter of the exemplary embodiment of the present invention is equivalent to the despreading code rate. The I and Q digital receive message signals are then despread with correlators using six different complex spreading code sequences corresponding to the despreading code sequences of the four channels (TR0, TR1, TR2, TR3), APC information and the pilot code.

Time synchronization of the receiver to the received signal is separated into two phases; there is an initial acquisition phase and then a tracking phase after the signal timing has been acquired. The initial acquisition is done by shifting the phase of the locally generated pilot code sequence relative to the received signal and comparing the output of the pilot despread to a threshold. The method used is called sequential search. Two thresholds (match and dismiss) are calculated from the auxiliary despread. Once the signal is acquired, the search process is stopped and the tracking process begins. The tracking process maintains the code generator 1304 (shown in FIGS. 13 and 17) used by the receiver in synchronization with the incoming signal. The

tracking loop used is the Delay-Locked Loop (DLL) and is implemented in the acquisition & track 1701 and the IPM 1702 blocks of FIG. 17.

In FIG. 13, the modem controller 1303 implements the Phase Lock Loop (PLL) as a software algorithm in SW PLL logic 1724 of FIG. 17 that calculates the phase and frequency shift in the received signal relative to the transmitted signal. The calculated phase shifts are used to derotate the phase shifts in rotate and combine blocks 1718, 1719, 1720, 1721 of the multipath data signals for combining to produce output signals corresponding to receive channels TR0', TR1', TR2', TR3'. The data is then Viterbi decoded in Viterbi Decoders 1713, 1714, 1715, 1716 to remove the convolutional encoding in each of the received message channels.

FIG. 17 indicates that the Code Generator 1304 provides the code sequences $P_n(t)$, $i=1,2,\dots,I$ used by the receive channel despreaders 1703, 1704, 1705, 1706, 1707, 1708, 1709. The code sequences generated are timed in response to the SYNK signal of the system clock signal and are determined by the CCNTRL signal from the modem controller 1303 shown in FIG. 13. Referring to FIG. 17, the CDMA modem receiver section 1302 includes Adaptive Matched Filter (AMF) 1710, Channel despreaders 1703, 1704, 1705, 1706, 1707, 1708, 1709, Pilot AVC 1711, Auxiliary AVC 1712, Viterbi decoders 1713, 1714, 1715, 1716, Modem output interface (MOI) 1717, Rotate and Combine logic 1718, 1719, 1720, 1721, AMF Weight Generator 1722, and Quantile Estimation logic 1723.

In another embodiment of the invention, the CDMA modem receiver also includes a Bit error Integrator to measure the BER of the channel and idle code insertion logic between the Viterbi decoders 1713, 1714, 1715, 1716 and the MOI 1717 to insert idle codes in the event of loss of the message data.

The Adaptive Matched Filter (AMF) 1710 resolves multipath interference introduced by the air channel. The exemplary AMF 1710 uses an 11 stage complex FIR filter as shown in FIG. 18. The received I and Q digital message signals are received at the register 1820 from the A/D 1730 of FIG. 17 and are multiplied in multipliers 1801, 1802, 1803, 1810, 1811 by I and Q channel weights W1 to W11 received from AMF weight generator 1722 of FIG. 17. In the exemplary embodiment, the A/D 1730 provides the I and Q digital receive message signal data as 2's complement values, 6 bits for I and 6 bits for Q which are clocked through an 11 stage shift register 1820 responsive to the receive spreading-code clock signal RXPNCCLK. The signal RXPNCCLK is generated by the timing section 1401 of code generation logic 1304. Each stage of the shift register is tapped and complex multiplied in the multipliers 1801, 1802, 1803, 1810, 1811 by individual (6-bit I and 6-bit Q) weight values to provide 11 tap-weighted products which are summed in adder 1830, and limited to 7-bit I and 7-bit Q values.

The CDMA modem receive section 1302 (shown in FIG. 13) provides independent channel despreaders 1703, 1704, 1705, 1706, 1707, 1708, 1709 (shown in FIG. 17) for despreading the message channels. The described embodiment despreads 7 message channels, each despreaders accepting a 1-bit I by 1-bit Q despreading code signal to perform a complex correlation of this code against a 8-bit I by 8-bit Q data input. The 7 despreaders correspond to the 7 channels: Traffic Channel 0 (TR0'), TR1', TR2, TR3', AUX (a spare channel), Automatic Power Control (APC) and pilot (PLT).

The Pilot AVC 1711 shown in FIG. 19 receives the I and Q Pilot Spreading code sequence values PCI and PCQ into

shift register 1920 responsive to the timing signal RXPNCCLK, and includes 11 individual despreaders 1901 through 1911 each correlating the I and Q digital receive message signal data with a one chip delayed version of the same pilot code sequence. Signals OE1, OE2, . . . OE11 are used by the modem control 1303 to enable the despreading operation. The output signals of the despreaders are combined in combiner 1920 forming correlation signal DSPRDAT of the Pilot AVC 1711, which is received by the ACQ & Track logic 1701 (shown in FIG. 17), and ultimately by modem controller 1303 (shown in FIG. 13). The ACQ & Track logic 1701 uses the correlation signal value to determine if the local receiver is synchronized with its remote transmitter.

The Auxiliary AVC 1712 also receives the I and Q digital receive message signal data and, in the described embodiment, includes four separate despreaders 2001, 2002, 2003, 2004 as shown in FIG. 20. Each despreaders receives and correlates the I and Q digital receive message data with delayed versions of the same despreading code sequence PARI and PARQ which are provided by code generator 1304 input to and contained in shift register 2020. The output signals of the despreaders 2001, 2002, 2003, 2004 are combined in combiner 2030 which provides noise correlation signal ARDSPRDAT. The auxiliary AVC spreading code sequence does not correspond to any transmit spreading code sequence of the system. Signals OE1, OE2, . . . OE4 are used by the modem control 1303 to enable the despreading operation. The Auxiliary AVC 1712 provides a noise correlation signal ARDSPRDAT from which quantile estimates are calculated by the Quantile estimator 1733, and provides a noise level measurement to the ACQ & Track logic 1701 (shown in FIG. 17) and modem controller 1303 (shown in FIG. 13).

Each despread channel output signal corresponding to the received message channels TR0', TR1', TR2', and TR3' is input to a corresponding Viterbi decoder 1713, 1714, 1715, 1716 shown in FIG. 17 which performs forward error correction on convolutionally encoded data. The Viterbi decoders of the exemplary embodiment have a constraint length of $K=7$ and a rate of $R=1/2$. The decoded despread message channel signals are transferred from the CDMA modem to the PCM Highway 1201 through the MOI 1717. The operation of the MOI is essentially the same as the operation of the MISR of the transmit section 1301 (shown in FIG. 13) except in reverse.

The CDMA modem receiver section 1302 implements several different algorithms during different phases of the acquisition, tracking and despreading of the receive CDMA message signal.

When the received signal is momentarily lost (or severely degraded) the idle code insertion algorithm inserts idle codes in place of the lost or degraded receive message data to prevent the user from hearing loud noise bursts on a voice call. The idle codes are sent to the MOI 1717 (shown in FIG. 17) in place of the decoded message channel output signal from the Viterbi decoders 1713, 1714, 1715, 1716. The idle code used for each traffic channel is programmed by the Modem Controller 1303 by writing the appropriate pattern IDLE to the MOI, which in the present embodiment is a 8 bit word for a 64 kb/s stream, 4 bit word for a 32 kb/s stream.

Modem Algorithms for Acquisition and Tracking of Received Pilot Signal

The acquisition and tracking algorithms are used by the receiver to determine the approximate code phase of a

received signal, synchronize the local modem receiver despreaders to the incoming pilot signal, and track the phase of the locally generated pilot code sequence with the received pilot code sequence. Referring to FIGS. 13 and 17, the algorithms are performed by the Modem controller 1303, which provides clock adjust signals to code generator 1304. These adjust signals cause the code generator for the despreaders to adjust locally generated code sequences in response to measured output values of the Pilot Rake 1711 and Quantile values from quantile estimators 1723B. Quantile values are noise statistics measured from the In-phase and Quadrature channels from the output values of the AUX Vector Correlator 1712 (shown in FIG. 17). Synchronization of the receiver to the received signal is separated into two phases; an initial acquisition phase and a tracking phase. The initial acquisition phase is accomplished by clocking the locally generated pilot spreading code sequence at a higher or lower rate than the received signal's spreading code rate, sliding the locally generated pilot spreading code sequence and performing sequential probability ratio test (SPRT) on the output of the Pilot Vector correlator 1711. The tracking phase maintains the locally generated spreading code pilot sequence in synchronization with the incoming pilot signal. Details of the quantile estimators 1723B may be found in U.S. patent application Ser. No. 08/218,198 entitled "ADAPTIVE POWER CONTROL FOR A SPREAD SPECTRUM COMMUNICATIONS SYSTEM" which is incorporated by reference herein for its teachings on adaptive power control systems.

The SU cold acquisition algorithm is used by the SU CDMA modem when it is first powered up, and therefore has no knowledge of the correct pilot spreading code phase, or when an SU attempts to reacquire synchronization with the incoming pilot signal but has taken an excessive amount of time. The cold acquisition algorithm is divided into two sub-phases. The first subphase consists of a search over the length 233415 code used by the FBCH. Once this sub-code phase is acquired, the pilot's 233415×128 length code is known to within an ambiguity of 128 possible phases. The second subphase is a search of these remaining 128 possible phases. In order not to lose synch with the FBCH, in the second phase of the search, it is desirable to switch back and forth between tracking of the FBCH code and attempting acquisition of the pilot code.

The RCS acquisition of short access pilot (SAXPT) algorithm is used by an RCS CDMA modem to acquire the SAXPT pilot signal of an SU. Additional details of this technique are described in U.S. patent application entitled "A METHOD OF CONTROLLING INITIAL POWER RAMP-UP IN CDMA SYSTEMS BY USING SHORT CODES" filed on even date herewith and herein incorporated by reference. The algorithm is a fast search algorithm because the SAXPT is a short code sequence of length N, where N=chips/symbol, and ranges from 45 to 195, depending on the system's bandwidth. The search cycles through all possible phases until acquisition is complete.

The RCS acquisition of the long access pilot (LAXPT) algorithm begins immediately after acquisition of SAXPT. The SU's code phase is known within a multiple of a symbol duration, so in the exemplary embodiment of the invention there may be 7 to 66 phases to search within the round trip delay from the RCS. This bound is a result of the SU pilot signal being synchronized to the RCS Global pilot signal.

The re-acquisition algorithm begins when loss of code lock (LOL) occurs. A Z-search algorithm is used to speed the process on the assumption that the code phase has not drifted far from where it was the last time the system was locked.

The RCS uses a maximum width of the Z-search windows bounded by the maximum round trip propagation delay.

The Pre-Track period immediately follows the acquisition or re-acquisition algorithms and immediately precedes the tracking algorithm. Pre-track is a fixed duration period during which the receive data provided by the modem is not considered valid. The Pre-Track period allows other modem algorithms, such as those used by the ISW PLL 1724, ACQ & Tracking, AMF Weight GEN 1722, to prepare and adapt to the current channel. The Pre-Track period is two parts. The first part is the delay while the code tracking loop pulls in. The second part is the delay while the AMF tap weight calculations are performed by the AMF Weight Gen 1722 to produce settled weighting coefficients. Also in the second part of the Pre-Track period, the carrier tracking loop is allowed to pull in by the SW PLL 1724, and the scalar quantile estimates are performed in the Quantile estimator 1723A.

The Tracking Process is entered after the Pre-Track period ends. This process is actually a repetitive cycle and is the only process phase during which receive data provided by the modem may be considered valid. The following operations are performed during this phase: AMF Tap Weight Update, Carrier Tracking, Code Tracking, Vector Quantile Update, Scalar Quantile Update, Code Lock Check, Derotation and Symbol Summing, and Power Control (forward and reverse)

If LOL is detected, the modem receiver terminates the Track algorithm and automatically enters the reacquisition algorithm. In the SU, a LOL causes the transmitter to be shut down. In the RCS, LOL causes forward power control to be disabled with the transmit power held constant at the level immediately prior to loss of lock. It also causes the return power control information being transmitted to assume a 010101... pattern, causing the SU to hold its transmit power constant. This can be performed using the signal lock check function which generates the reset signal to the acquisition and tracking circuit 1701.

Two sets of quantile statistics are maintained, one by Quantile estimator 1723B and the other by the scalar Quantile Estimator 1723A. Both are used by the modem controller 1303. The first set is the "vector" quantile information, so named because it is calculated from the vector of four complex values generated by the AUX AVC receiver 1712. The second set is the scalar quantile information, which is calculated from the single complex value AUX signal that is output from the AUX Despreader 1707. The two sets of information represent different sets of noise statistics used to maintain a pre-determined Probability of False Alarm (P_{fa}). The vector quantile data is used by the acquisition and reacquisition algorithms implemented by the modem controller 1303 to determine the presence of a received signal in noise, and the scalar quantile information is used by the code lock check algorithm.

For both the vector and scalar cases, quantile information consists of calculated values of lambda0 through lambda2, which are boundary values used to estimate the probability distribution function (p.d.f) of the despread receive signal and determine whether the modem is locked to the PN code. The Aux_Power value used in the following C-subroutine is the magnitude squared of the AUX signal output of the scalar correlator array for the scalar quantiles, and the sum of the magnitudes squared for the vector case. In both cases the quantiles are then calculated using the following C-subroutine:

```

for (n = 0; n < 3; n++) {
    lambda[n] += (lambda[n] < Aux_Power) ? CG[n] : GM[n];
}

```

where $CG[n]$ are positive constants and $GM[n]$ are negative constants (different values are used for scalar and vector quantiles).

During the acquisition phase, the search of the incoming pilot signal with the locally generated pilot code sequence employs a series of sequential tests to determine if the locally generated pilot code has the correct code phase relative to the received signal. The search algorithms use the Sequential Probability Ratio Test (SPRT) to determine whether the received and locally generated code sequences are in phase. The speed of acquisition is increased by parallelism resulting from having a multi-fingered receiver. For example, in the described embodiment of the invention the main Pilot Rake 1711 has a total of 11 fingers representing a total phase period of 11 chip periods. For acquisition 8 separate sequential probability ratio tests (SPRTs) are implemented, with each SPRT observing a 4 chip window. Each window is offset from the previous window by one chip, and in a search sequence any given code phase is covered by 4 windows. If all 8 of the SPRT tests are rejected, then the set of windows is moved by 8 chips. If any of the SPRT's is accepted, then the code phase of the locally generated pilot code sequence is adjusted to attempt to center the accepted SPRT's phase within the Pilot AVC. It is likely that more than one SPRT reaches the acceptance threshold at the same time. A table lookup is used cover all 256 possible combinations of accept/reject and the modem controller uses the information to estimate the correct center code phase within the Pilot Rake 1711. Each SPRT is implemented as follows (all operations occur at 64 k symbol rate): Denote the fingers' output level values as $I_Finger[n]$ and $Q_Finger[n]$, where $n=0 \dots 10$ (inclusive, 0 is earliest (most advanced) finger), then the power of each window is:

$$\text{Power Window}[i] = \sum_n (I_Finger^2[n] + Q_Finger^2[n])$$

To implement the SPRT's the modem controller then performs for each of the windows the following calculations which are expressed as a pseudo-code subroutine:

```

/* find bin for Power */
tmp = SIGMA[0];
for (k = 0; k < 3; k++) {
    if (Power > lambda[k]) tmp = SIGMA[k+1];
}
test_statistic += tmp; /* update statistic */
if (test_statistic > ACCEPTANCE_THRESHOLD) you've got ACQ;
else if (test_statistic < DISMISSAL_THRESHOLD) {
    forget this code phase;
} else keep trying - get more statistics;

```

where $\lambda[k]$ are as defined in the above section on quantile estimation, and $SIGMA[k]$, $ACCEPTANCE_THRESHOLD$ and $DISMISSAL_THRESHOLD$ are pre-determined constants. Note that $SIGMA[k]$ is negative for values for low values of k , and positive for right values of k , such that the acceptance and dismissal thresholds can be constants rather than a function of how many symbols worth of data have been accumulated in the statistic.

The modem controller determines which bin delimited by the values of $\lambda[k]$ the Power level falls into which allows the modem controller to develop an approximate statistic.

For the present algorithm, the control voltage is formed as $e=y^*y$. By, where y is a vector formed from the complex valued

output values of the Pilot Vector correlator 1711, and B is a matrix consisting of the constant values pre-determined to maximize the operating characteristics while minimizing the noise as described previously with reference to the Quadratic Detector.

To understand the operation of the Quadratic Detector, it is useful to consider the following. A spread spectrum (CDMA) signal, $s(t)$ is passed through a multipath channel with an impulse response $h_c(t)$. The baseband spread signal is described by equation (30).

$$s(t) = \sum_i C_i p(t - iT_c) \quad (30)$$

where C_i is a complex spreading code symbol, $p(t)$ is a predefined chip pulse and T_c is the chip time spacing, where $T_c = 1/R_c$ and R_c is the chip rate.

The received baseband signal is represented by equation (31)

$$r(t) = \sum_i C_i q(t - iT_c - \tau) + n(t) \quad (31)$$

where $q(t) = p(t) * h_c(t)$, τ is an unknown delay and $n(t)$ is additive noise. The received signal is processed by a filter, $h_R(t)$, so the waveform, $x(t)$, to be processed is given by equation (32).

$$x(t) = \sum_i C_i f(t - iT_c - \tau) + z(t) \quad (32)$$

where $f(t) = q(t) * h_R(t)$ and $z(t) = n(t) * h_R(t)$.

In the exemplary receiver, samples of the received signal are taken at the chip rate, that is to say, $1/T_c$. These samples, $x(mT_c + \tau')$, are processed by an array of correlators that compute, during the r^{th} correlation period, the quantities given by equation (33)

$$y_k^{(r)} = \sum_{m=rL}^{rL+L-1} x(mT_c + \tau') C_{mk}^* \quad (33)$$

These quantities are composed of a noise component $W_k^{(r)}$ and a deterministic component $y_k^{(r)}$ given by equation (34).

$$y_k^{(r)} = E[y_k^{(r)}] = L f(kT_c + \tau') \quad (34)$$

In the sequel, the time index r may be suppressed for ease of writing, although it is to be noted that the function $f(t)$ changes slowly with time.

The samples are processed to adjust the sampling phase, τ' , in an optimum fashion for further processing by the receiver, such as matched filtering. This adjustment is described below. To simplify the representation of the process, it is helpful to describe it in terms of the function $f(t+\tau)$, where the time-shift, τ , is to be adjusted. It is noted that the function $f(t+\tau)$ is measured in the presence of noise. Thus, it may be problematical to adjust the phase τ' based on measurements of the signal $f(t+\tau)$. To account for the noise, the function $v(t)$: $v(t) = f(t) + m(t)$ is introduced, where the term $m(t)$ represents a noise process. The system processor may be derived based on considerations of the function $v(t)$.

The process is non-coherent and therefore is based on the envelope power function $|v(t+\tau)|^2$. The functional $e(\tau')$ given in equation (35) is helpful for describing the process.

$$e(\tau') = \int_{-\infty}^0 |v(t + \tau' - \tau)|^2 dt - \int_0^{\infty} |v(t + \tau' - \tau)|^2 dt \quad (35)$$

The shift parameter is adjusted for $e(\tau')=0$, which occurs when the energy on the interval $(-\infty, \tau' - \tau]$ equals that on the

interval $[\tau' - \tau, \infty)$. The error characteristic is monotonic and therefore has a single zero crossing point. This is the desirable quality of the functional. A disadvantage of the functional is that it is ill-defined because the integrals are unbounded when noise is present. Nevertheless, the functional $e(\tau')$ may be cast in the form given by equation (36).

$$e(\tau') = \int_{-\infty}^{\infty} w(t) v(t + \tau' - \tau) \rho dt \quad (36)$$

where the characteristic function $w(t)$ is equal to $\text{sgn}(t)$, the signum function.

To optimize the characteristic function $w(t)$, it is helpful to define a figure of merit, F , as set forth in equation (37).

$$F = \frac{[e(\tau'_0) + T_A] - e(\tau'_0 - T_A)]^2}{\text{VAR}\{e(\tau'_0)\}} \quad (37)$$

The numerator of F is the numerical slope of the mean error characteristic on the interval $[-T_A, T_A]$ surrounding the tracked value, τ'_0 . The statistical mean is taken with respect to the noise as well as the random channel, $h_c(t)$. It is desirable to specify a statistical characteristic of the channel in order to perform this statistical average. For example, the channel may be modeled as a Wide Sense Stationary Uncorrelated Scattering (WSSUS) channel with impulse response $h_c(t)$ and a white noise process $U(t)$ that has an intensity function $g(t)$ as shown in equation (38).

$$h_c(t) = \sqrt{g(t)} U(t) \quad (38)$$

The variance of $e(\tau)$ is computed as the mean square value of the fluctuation

$$e'(\tau) = e(\tau) - \langle e(\tau) \rangle \quad (39)$$

where $\langle e(\tau) \rangle$ is the average of $e(\tau)$ with respect to the noise.

Optimization of the figure of merit F with respect to the function $w(t)$ may be carried out using well-known Variational methods of optimization.

Once the optimal $w(t)$ is determined, the resulting processor may be approximated accurately by a quadratic sample processor which is derived as follows.

By the sampling theorem, the signal $v(t)$, bandlimited to a bandwidth W may be expressed in terms of its samples as shown in equation (40).

$$v(t) = \sum v(k/W) \sin c[(Wt - k)\pi] \quad (40)$$

substituting this expansion into equation (z+6) results in an infinite quadratic form in the samples $v(k/W + \tau' - \tau)$. Making the assumption that the signal bandwidth equals the chip rate allows the use of a sampling scheme that is clocked by the chip clock signal to be used to obtain the samples. These samples, V_k are represented by equation (41).

$$v_k = v(kT_c + \tau' - \tau) \quad (41)$$

This assumption leads to a simplification of the implementation. It is valid if the aliasing error is small.

In practice, the quadratic form that is derived is truncated. An example normalized B matrix is given below in Table 12. For this example, an exponential delay spread profile $g(t) = \exp(-t/\tau)$ is assumed with τ equal to one chip. An aperture parameter T_A equal to one and one-half chips has also been assumed. The underlying chip pulse has a raised cosine spectrum with a 20% excess bandwidth.

TABLE 12

Example B matrix										
0	0	0	0	0	0	0	0	0	0	0
0	0	-0.1	0	0	0	0	0	0	0	0
0	-0.1	0.22	0.19	-0.19	0	0	0	0	0	0
0	0	0.19	1	0.45	-0.2	0	0	0	0	0
0	0	-0.19	0.45	0.99	0.23	0	0	0	0	0
0	0	0	-0.2	0.23	0	-0.18	0.17	0	0	0
0	0	0	0	0	-0.18	-0.87	-0.42	0.18	0	0
0	0	0	0	0	0.17	-0.42	-0.92	-0.16	0	0
0	0	0	0	0	0	0.18	-0.16	-0.31	0	0
0	0	0	0	0	0	0	0	0	-0.13	0
0	0	0	0	0	0	0	0	0	0	0

Code tracking is implemented via a loop phase detector that is implemented as follows. The vector y is defined as a column vector which represents the 11 complex output level values of the Pilot AVC 1711, and B denotes an 11×11 symmetric real valued coefficient matrix with predetermined values to optimize performance with the non-coherent Pilot AVC output values y . The output signal e of the phase detector is given by equation (42):

$$e = y^T B y \quad (42)$$

The following calculations are then performed to implement a proportional plus integral loop filter and the VCO:

$$\begin{aligned} x[n] &= x[n-1] + \beta e \\ z[n] &= z[n-1] + x[n] + \alpha e \end{aligned}$$

for β and α which are constants chosen from modeling the system to optimize system performance for the particular transmission channel and application, and where $x[n]$ is the loop filter's integrator output value and $z[n]$ is the VCO output value. The code phase adjustments are made by the modem controller the following C-subroutine:

```

if (z > zmax) {
    delay phase 1/16 chip;
    z -= zmax;
} else if (z < -zmax) {
    advance phase 1/16 chip;
    z += zmax;
}

```

A different delay phase could be used in the above pseudo-code consistent with the present invention.

The AMF Tap-Weight Update Algorithm of the AMF Weight Gen 1722 occurs periodically to de-rotate and scale the phase of each finger value of the Pilot Rake 1711 by performing a complex multiplication of the Pilot AVC finger value with the complex conjugate of the current output value of the carrier tracking loop and applying the product to a low pass filter and form the complex conjugate of the filter values to produce AMF tap-weight values, which are periodically written into the AMF filters of the CDMA modem.

The lock check algorithm, shown in FIG. 17, is implemented by the modem controller 1303 performing SPRT operations on the output signal of the scalar correlator array. The SPRT technique is the same as that for the acquisition algorithms, except that the acceptance and rejection thresholds are changed to increase the probability of detection of lock.

Carrier tracking is accomplished via a second order loop that operates on the pilot output values of the scalar correlated array. The phase detector output is the hard limited version of the quadrature component of the product of the

(complex valued) pilot output signal of the scalar correlated array and the VCO output signal. The loop filter is a proportional plus integral design. The VCO is a pure summation, accumulated phase error ϕ , which is converted to the complex phasor $\cos \phi + j \sin \phi$ using a look-up table in memory.

The previous description of acquisition and tracking algorithm focuses on a non-coherent method because the acquisition and tracking algorithm described requires non-coherent acquisition following by non-coherent tracking because during acquisition a coherent reference is not available until the AMF, Pilot AVC, Aux AVC, and DPLL are in an equilibrium state. However, it is known in the art that coherent tracking and combining is always optimal because in non-coherent tracking and combining the output phase information of each Pilot AVC finger is lost. Consequently, another embodiment of the invention employs a two step acquisition and tracking system, in which the previously described non-coherent acquisition and tracking algorithm is implemented first, and then the algorithm switches to a coherent tracking method. The coherent combining and tracking method is similar to that described previously, except that the error signal tracked is of the form:

$$\epsilon = y^T A y \quad (43)$$

where y is defined as a column vector which represents the 11 complex output level values of the Pilot AVC 171 1, and A denotes an 11×11 symmetric real valued coefficient matrix with pre-determined values to optimize performance with the coherent Pilot AVC outputs y . An exemplary A matrix is shown below.

$$A = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 \end{bmatrix} \quad (44)$$

Referring to FIG. 9, the Video Distribution Controller Board (VDC) 940 of the RCS is connected to each MIU 931, 932, 933 and the RF Transmitters/Receivers 950. The VDC 940 is shown in FIG. 21. The Data Combiner Circuitry (DCC) 2150 includes a Data Demultiplexer 2101, Data Summer 2102, FIR Filters 2103, 2104, and a Driver 2111. The DCC 2150 1) receives the weighted CDMA modem I and Q data signal MDAT from each of the MIUs, 931, 932, 933, 2) sums the I and Q data with the digital bearer channel data from each MIU 931, 932, 933, 3) and sums the result with the broadcast data message signal BCAST and the Global Pilot spreading code GPILOT provided by the master modem 1210, 4) band shapes the summed signals for transmission, and 5) produces analog data signal for transmission to the RF Transmitter/Receiver.

FIR Filters 2103, 2104 are used to modify the MIU CDMA Transmit I and Q Modem Data before transmission. The WAC transfers FIR Filter Coefficient data through the Serial Port link 912 through the VDC Controller 2120 and to the FIR filters 2103, 2104. Each FIR Filter 2103, 2104 is Configured separately. The FIR Filters 2103, 2104 employ Up-Sampling to operate at twice the chip rate so zero data values are sent after every MIU CDMA Transmit Modem DATI and DATQ value to produce FTXI and FTXQ

The VDC 940 distributes the AGC signal AGCDATA from the AGC 1750 of the MIUs 931, 932, 933 to the RF

Transmitter/Receiver 950 through the Distribution interface (DI) 2110. The VDC DI 2110 receives data RXI and RXQ from the RF Transmitter/Receiver and distributes the signal as VDATAI and VDATAQ to MIUs 931, 932, 933.

Referring to FIG. 21, the VDC 940 also includes a VDC controller 2120 which monitors status and fault information signals MIUSTAT from MIUs and connects to the serial link 912 and HSBS 970 to communicate with WAC 920 shown in FIG. 9. The VDC controller 2120 includes a microprocessor, such as an Intel 8032 Microcontroller, an oscillator (not shown) providing timing signals, and memory (not shown). The VDC controller memory includes a Flash Prom (not shown) to contain the controller program code for the 8032 Microprocessor, and an SRAM (not shown) to contain the temporary data written to and read from memory by the microprocessor.

Referring to FIG. 9, the present invention includes a RF Transmitter/Receiver 950 and power amplifier section 960. Referring to FIG. 22 the RF Transmitter/Receiver 950 is divided into three sections: the transmitter module 2201, the receiver module 2202, and the Frequency Synthesizer 2203. Frequency Synthesizer 2203 produces a transmit carrier frequency TFREQ and a receive carrier frequency RFREQ in response to a Frequency control signal FREQCTRL received from the WAC 920 on the serial link 912. In the transmitter module 2201, the input analog I and Q data signals TXI and TXQ from the VDC applied to the Quadrature modulator 2220, which also receives a transmit carrier frequency signal TFREQ from the Frequency Synthesizer 2203 to produce a quadrature modulated transmit carrier signal TX. The analog transmit carrier modulated signal, an upconverted RF signal, TX is then applied to the Transmit Power Amplifier 2252 of the Power Amplifier 960. The amplified transmit carrier signal is then passed through the High Power Passive Components (HPPC) 2253 to the Antenna 2250, which transmits the upconverted RF signal to the communication channel as a CDMA RF signal. In one embodiment of the invention, the Transmit Power Amplifier 2252 comprises eight amplifiers of approximately 60 watts peak-to-peak each.

The HPPC 2253 comprises a lightning protector, an output filter, a 10 dB directional coupler, an isolator, and a high power termination attached to the isolator.

A receive CDMA RF signal is received at the antenna 2250 from the RF channel and passed through the HPPC 2253 to the Receive Power Amplifier 2251. The receive power amplifier 2251 includes, for example, a 30 watt power transistor driven by a 5 watt transistor. The RF receive module 2202 has quadrature modulated receive carrier signal RX from the receive power amplifier. The receive module 2202 includes a Quadrature demodulator 2210 which takes the receive carrier modulated signal RX and the receive carrier frequency signal RFREQ from the Frequency Synthesizer 2203, synchronously demodulates the carrier, and analog I and Q channels. These channels are filtered to produce the signals RXI and RXQ, which are transferred to the VDC 940.

The Subscriber Unit

FIG. 23 shows the Subscriber Unit (SU) of one embodiment of the present invention. As shown, the SU includes an RF section 2301 including a RF modulator 2302, RF demodulator 2303, and splitter/isolator 2304 which receive Global and Assigned logical channels including traffic and control messages and Global Pilot signals in the Forward link CDMA RF channel signal, and transmit Assigned Channels and Reverse Pilot signals in the Reverse Link

CDMA RF channel. The Forward and Reverse links are received and transmitted respectively through antenna 2305. The RF section employs, in one exemplary embodiment, a conventional dual conversion superheterodyne receiver having a synchronous demodulator responsive to the signal ROSC. Selectivity of such a receiver is provided by a 70 MHz transversal SAW filter (not shown). The RF modulator includes a synchronous modulator (not shown) responsive to the carrier signal TOSC to produce a quadrature modulated carrier signal. This signal is stepped up in frequency by an offset mixing circuit (not shown).

The SU further includes a Subscriber Line Interface 2310, including the functionality of a control (CC) generator, a Data Interface 2320, an ADPCM encoder 2321, an ADPCM decoder 2322, an SU controller 2330, an SU clock signal generator 2331, memory 2332, and a CDMA modem 2340, which is essentially the same as the CDMA modem 1210 described above with reference to FIG. 13. It is noted that data interface 2320, ADPCM Encoder 2321 and ADPCM Decoder 2322 are typically provided as a standard ADPCM Encoder/Decoder chip.

The Forward Link CDMA RF Channel signal is applied to the RF demodulator 2303 to produce the Forward link CDMA signal. The Forward Link CDMA signal is provided to the CDMA modem 2340, which acquires synchronization with the Global pilot signal, produces global pilot synchronization signal to the Clock 2331, to generate the system timing signals, and despreads the plurality of logical channels. The CDMA modem 2340 also acquires the traffic messages RMESS and control messages RCTRL and provides the traffic message signals RMESS to the Data Interface 2320 and receive control message signals RCTRL to the SU Controller 2330.

The receive control message signals RCTRL include a subscriber identification signal, a coding signal, and bearer modification signals. The RCTRL may also include control and other telecommunication signaling information. The receive control message signal RCTRL is applied to the SU controller 2330, which verifies that the call is for the SU from the Subscriber identification value derived from RCTRL. The SU controller 2330 determines the type of user information contained in the traffic message signal from the coding signal and bearer rate modification signal. If the coding signal indicates the traffic message is ADPCM coded, the traffic message RVMESS is sent to the ADPCM decoder 2322 by sending a select message to the Data Interface 2320. The SU controller 2330 outputs an ADPCM coding signal and bearer rate signal derived from the coding signal to the ADPCM decoder 2322. The traffic message signal RVMESS is the input signal to the ADPCM decoder 2322, where the traffic message signal is converted to a digital information signal RINF in response to the values of the input ADPCM coding signal.

If the SU controller 2330 determines the type of user information contained in the traffic message signal from the coding signal is not ADPCM coded, then RDMESS passes through the ADPCM encoder transparently. The traffic message RDMESS is transferred from the Data Interface 2320 directly to the Interface Controller (IC) 2312 of the subscriber line interface 2310.

The digital information signal RINF or RDMESS is applied to the subscriber line interface 2310, including a interface controller (IC) 2312 and Line Interface (LI) 2313. For the exemplary embodiment the IC is an Extended PCM Interface Controller (EPIC) and the LI is a Subscriber Line Interface Circuit (SLIC) for POTS which corresponds to

RINF type signals, and a ISDN Interface for ISDN which corresponds to RDMESS type signals. The EPIC and SLIC circuits are well known in the art. The subscriber line interface 2310 converts the digital information signal RINF or RDMESS to the user defined format. The user defined format is provided to the IC 2312 from the SU Controller 2330. The LI 2310 includes circuits for performing such functions as A-law or μ -law conversion, generating dial tone and, and generating or interpreting signaling bits. The line interface also produces the user information signal to the SU User 2350 as defined by the subscriber line interface, for example POTS voice, voiceband data or ISDN data service.

For a Reverse Link CDMA RF Channel, a user information signal is applied to the LI 2313 of the subscriber line interface 2310, which outputs a service type signal and an information type signal to the SU controller. The IC 2312 of the subscriber line interface 2310 produces a digital information signal TINF which is the input signal to the ADPCM encoder 2321 if the user information signal is to be ADPCM encoded, such as for POTS service. For data or other non-ADPCM encoded user information, the IC 2312 passes the data message TDMESS directly to the Data Interface 2320. The Call control module (CC), including in the subscriber line interface 2310, derives call control information from the User information signal, and passes the call control information CCINF to the SU controller 2330. The ADPCM encoder 2321 also receives coding signal and bearer modification signals from the SU controller 2330 and converts the input digital information signal into the output message traffic signal TVMESS in response to the coding and bearer modification signals. The SU controller 2330 also outputs the reverse control signal which includes the coding signal call control information, and bearer channel modification signal, to the CDMA modem. The output message signal TVMESS is applied to the Data Interface 2320. The Data Interface 2320 sends the user information to the CDMA modem 2340 as transmit message signal TMESS. The CDMA modem 2340 spreads the output message and reverse control channels TCTRL received from the SU controller 2330, and produces the reverse link CDMA Signal. The Reverse Link CDMA signal is provided to the RF transmit section 2301 and modulated by the RF modulator 2302 to produce the output Reverse Link CDMA RF channel signal transmitted from antenna 2305.

Call Connection and Establishment Procedure

The process of bearer channel establishment consists of two procedures: the call connection process for a call connection incoming from a remote call processing unit such as an RDU (Incoming Call Connection), and the call connection process for a call outgoing from the SU (Outgoing Call Connection). Before any bearer channel can be established between an RCS and a SU, the SU must register its presence in the network with the remote call processor such as the RDU. When the off-hook signal is detected by the SU, the SU not only begins to establish a bearer channel; but also initiates the procedure for an RCS to obtain a terrestrial link between the RCS and the remote processor. As incorporated herein by reference, the process of establishing the RCS and RDU connection is detailed in the DECT V5.1 standard.

For the Incoming Call Connection procedure shown in FIG. 24, first 2401, the WAC 920 (shown in FIG. 9) receives, via one of the MUXs 905, 906 and 907, an incoming call request from a remote call processing unit. This request identifies the target SU and that a call connection to the SU is desired. The WAC periodically outputs the SBCH channel

with paging indicators for each SU and periodically outputs the FBCH traffic lights for each access channel. In response to the incoming call request, the WAC, at step 2420, first checks to see if the identified SU is already active with another call. If so, the WAC returns a busy signal for the SU to the remote processing unit through the MUX, otherwise the paging indicator for the channel is set.

Next, at step 2402, the WAC checks the status of the RCS modems and, at step 2421, determines whether there is an available modem for the call. If a modem is available, the traffic lights on the FBCH indicate that one or more AXCH channels are available. If no channel is available after a certain period of time, then the WAC returns a busy signal for the SU to the remote processing unit through the MUX. If an RCS modem is available and the SU is not active (in Sleep mode), the WAC sets the paging indicator for the identified SU on the SBCH to indicate an incoming call request. Meanwhile, the access channel modems continuously search for the Short Access Pilot signal (SAXPT) of the SU.

At step 2403, an SU in Sleep mode periodically enters awake mode. In awake mode, the SU modem synchronizes to the Downlink Pilot signal, waits for the SU modem AMF filters and phase locked loop to settle, and reads the paging indicator in the slot assigned to it on the SBCH to determine if there is a call for the SU 2422. If no paging indicator is set, the SU halts the SU modem and returns to sleep mode. If a paging indicator is set for an incoming call connection, the SU modem checks the service type and traffic lights on FBCH for an available AXCH.

Next, at step 2404, the SU modem selects an available AXCH and starts a fast transmit power ramp-up on the corresponding SAXPT. For a period the SU modem continues fast power ramp-up on SAXPT and the access modems continue to search for the SAXPT.

At step 2405, the RCS modem acquires the SAXPT of the SU and begins to search for the SU LAXPT. When the SAXPT is acquired, the modem informs the WAC controller, and the WAC controller sets the traffic lights corresponding to the modem to "red" to indicate the modem is now busy. The traffic lights are periodically output while continuing to attempt acquisition of the LAXPT.

The SU modem monitors, at step 2406, the FBCH AXCH traffic light. When the AXCH traffic light is set to red, the SU assumes the RCS modem has acquired the SAXPT and begins transmitting LAXPT. The SU modem continues to ramp-up power of the LAXPT at a slower rate until Sync-Ind messages are received on the corresponding CTCH. If the SU is mistaken because the traffic light was actually set in response to another SU acquiring the AXCH, the SU modem times out because no Sync-Ind messages are received. The SU randomly waits a period of time, picks a new AXCH channel, and steps 2404 and 2405 are repeated until the SU modem receives Sync-Ind messages. Details of the power ramp up method used in the exemplary embodiment of this invention may be found in the U.S. patent application entitled METHOD OF CONTROLLING INITIAL POWER RAMP-UP IN CDMA SYSTEMS BY USING SHORT CODES filed on even date herewith, which is hereby incorporated by reference.

Next, at step 2407, the RCS modem acquires the LAXPT of the SU and begins sending Sync-Ind messages on the corresponding CTCH. The modem waits 10 msec for the Pilot and AUX Vector correlator filters and Phase locked loop to settle, but continues to send Sync-Ind messages on the CTCH. The modem then begins looking for a request

message for access to a bearer channel (MAC_ACC_REQ), from the SU modem.

The SU modem, at step 2408, receives the Sync-Ind message and freezes the LAXPT transmit power level. The SU modem then begins sending repeated request messages for access to a bearer traffic channel (MAC_ACC_REQ) at fixed power levels, and listens for a request confirmation message (MAC_BEARER_CFM) from the RCS modem.

Next, at step 2409, the RCS modem receives a MAC_ACC_REQ message; the modem then starts measuring the AXCH power level, and starts the APC channel. The RCS modem then sends the MAC_BEARER_CFM message to the SU and begins listening for the acknowledgment MAC_BEARER_CFM_ACK of the MAC_BEARER_CFM message.

At step 2410, the SU modem receives the MAC_BEARER_CFM message and begins obeying the APC power control messages. The SU stops sending the MAC_ACC_REQ message and sends the RCS modem the MAC_BEARER_CFM_ACK message. The SU begins sending the null data on the AXCH. The SU waits 10 msec for the uplink transmit power level to settle.

The RCS modem, at step 2411, receives the MAC_BEARER_CFM_ACK message and stops sending the MAC_BEARER_CFM messages. APC power measurements continue.

Next, at step 2412, both the SU and the RCS modems have synchronized the sub-epochs, obey APC messages, measure receive power levels, and compute and send APC messages. The SU waits 10 msec for downlink power level to settle.

Finally, at step 2413, Bearer channel is established and initialized between the SU and RCS modems. The WAC receives the bearer establishment signal from the RCS modem, re-allocates the AXCH channel and sets the corresponding traffic light to green.

For the Outgoing Call Connection shown in FIG. 25, the SU is placed in active mode by the off-hook signal at the user interface at step 2501.

Next, at step 2502, the RCS indicates available AXCH channels by setting the respective traffic lights.

At step 2503, the SU synchronizes to the Downlink Pilot, waits for the SU modem Vector correlator filters and phase lock loop to settle, and the SU checks service type and traffic lights for an available AXCH.

Steps 2504 through 2513 are identical to the procedure steps 2404 through 2413 for the Incoming Call Connection procedure of FIG. 24, and so are not explained in detail.

In the previous procedures for Incoming Call Connection and Outgoing Call Connection, the power Ramping-Up process consists of the following events. The SU starts from very low transmit power and increases its power level while transmitting the short code SAXPT; once the RCS modem detects the short code it turns off the traffic light. Upon detecting the changed traffic light, the SU continues ramping-up at a slower rate this time sending the LAXPT. Once the RCS modem acquires the LAXPT and sends a message on CTCH to indicate this, the SU keeps its transmit (TX) power constant and sends the MAC-Access-Request message. This message is answered with a MAC_BEARER_CFM message on the CTCH. Once the SU receives the MAC_BEARER_CFM message it switches to the traffic channel (TRCH) which is the dial tone for POTS.

When the SU captures a specific user channel AXCH, the RCS assigns a code seed for the SU through the CTCH. The

code seed is used by the spreading code generator in the SU modem to produce the assigned code for the reverse pilot of the subscriber, and the spreading codes for associated channels for traffic, call control, and signaling. The SU reverse pilot spreading code sequence is synchronized in phase to the RCS system Global Pilot spreading code sequence, and the traffic, call control, and signaling spreading codes are synchronized in phase to the SU reverse pilot spreading code sequence.

If the Subscriber unit is successful in capturing a specific user channel, the RCS establishes a terrestrial link with the remote processing unit to correspond to the specific user channel. For the DECT V5.1 standard, once the complete link from the RDU to the LE is established using the V5.1 ESTABLISHMENT message, a corresponding V5.1 ESTABLISHMENT ACK message is returned from the LE to the RDU, and the Subscriber Unit is sent a CONNECT message indicating that the transmission link is complete.

Support of Special Service Types

The system of the present invention includes a bearer channel modification feature which allows the transmission rate of the user information to be switched from a lower rate to a maximum of 64 kb/s. The Bearer Channel Modification (BCM) method is used to change a 32 kb/s ADPCM channel to a 64 kb/s PCM channel to support high speed data and fax communications through the spread-spectrum communication system of the present invention. Additional details of this technique are described in U.S. patent application entitled "CDMA COMMUNICATION SYSTEM WHICH SELECTIVELY SUPPRESSES DATA TRANSMISSION DURING ESTABLISHMENT OF A COMMUNICATION CHANNEL" filed on even date herewith and incorporated herein by reference.

First, a bearer channel on the RF interface is established between the RCS and SU, and a corresponding link exists between the RCS terrestrial interface and the remote processing unit, such as an RDU. The digital transmission rate of the link between the RCS and remote processing unit normally corresponds to a data encoded rate, which may be, for example, ADPCM at 32 kb/s. The WAC controller of the RCS monitors the encoded digital data information of the link received by the Line Interface of the MUX. If the WAC controller detects the presence of the 2100 Hz tone in the digital data, the WAC instructs the SU through the assigned logical control channel and causes a second, 64 kb/s duplex link to be established between the RCS modem and the SU. In addition, the WAC controller instructs the remote processing unit to establish a second 64 kb/s duplex link between the remote processing unit and the RCS. Consequently, for a brief period, the remote processing unit and the SU exchange the same data over both the 32 kb/s and the 64 kb/s links through the RCS. Once the second link is established, the remote processing unit causes the WAC controller to switch transmission only to the 64 kb/s link, and the WAC controller instructs the RCS modem and the SU to terminate and tear down the 32 kb/s link. Concurrently, the 32 kb/s terrestrial link is also terminated and torn down.

Another embodiment of the BCM method incorporates a negotiation between the external remote processing unit, such as the RDU, and the RCS to allow for redundant channels on the terrestrial interface, while only using one bearer channel on the RF interface. The method described is a synchronous switchover from the 32 kb/s link to the 64 kb/s link over the air link which takes advantage of the fact

that the spreading code sequence timing is synchronized between the RCS modem and SU. When the WAC controller detects the presence of the 2100 Hz tone in the digital data, the WAC controller instructs the remote processing unit to establish a second 64 kb/s duplex link between the remote processing unit and the RCS. The remote processing unit then sends 32 kb/s encoded data and 64 kb/s data concurrently to the RCS. Once the remote processing unit has established the 64 kb/s link, the RCS is informed and the 32 kb/s link is terminated and torn down. The RCS also informs the SU that the 32 kb/s link is being torn down and to switch processing to receive unencoded 64 kb/s data on the channel. The SU and RCS exchange control messages over the bearer control channel of the assigned channel group to identify and determine the particular subepoch of the bearer channel spreading code sequence within which the RCS will begin transmitting 64 kbit/sec data to the SU. Once the subepoch is identified, the switch occurs synchronously at the identified subepoch boundary. This synchronous switchover method is more economical of bandwidth since the system does not need to maintain capacity for a 64 kb/s link in order to support a switchover.

The previously described embodiments of the BCM feature, the RCS will tear down the 32 kb/s link first, but one skilled in the art would know that the RCS could tear down the 32 kb/s link after the bearer channel has switched to the 64 kb/s link.

As another special service type, the system of the present invention includes a method for conserving capacity over the RF interface for ISDN types of traffic. This conservation occurs while a known idle bit pattern is transmitted in the ISDN D-channel when no data information is being transmitted. The CDMA system of the present invention includes a method to prevent transmission of redundant information carried on the D-channel of ISDN networks for signals transmitted through a wireless communication link. The advantage of such method is that it reduces the amount of information transmitted and consequently the transmit power and channel capacity used by that information. The method is described as it is used in the RCS. In the first step, the controller, such as the WAC of the RCS or the SU controller of the SU, monitors the output D-channel from the subscriber line interface for a pre-determined channel idle pattern. A delay is included between the output of the line interface and the CDMA modem. Once the idle pattern is detected, the controller inhibits the transmission of the spread message channel through a message included in the control signal to the CDMA modem. The controller continues to monitor the output D-channel of the line interface until the presence of data information is detected. When data information is detected, the spread message channel is activated. Because the message channel is synchronized to the associated pilot which is not inhibited, the corresponding CDMA modem of the other end of the communication link does not have to reacquire synchronization to the message channel.

Drop Out Recovery

The RCS and SU each monitor the CDMA bearer channel signal to evaluate the quality of the CDMA bearer channel connection. Link quality is evaluated using the sequential probability ratio test (SPRT) employing adaptive quantile estimation. The SPRT process uses measurements of the received signal power; and if the SPRT process detects that the local spreading code generator has lost synchronization with the received signal spreading code or if it detects the absence or low level of a received signal, the SPRT declares loss of lock (LOL).

When the LOL condition is declared, the receiver modem of each RCS and SU begins a Z-search of the input signal with the local spreading code generator. Z-search is well known in the art of CDMA spreading code acquisition and detection and is described in *Digital Communications and Spread Spectrum Systems*, by to Robert E. Ziemer and Roger L. Peterson, at pages 492-94 which is incorporated herein by reference. The Z-search algorithm of the present invention tests groups of eight spreading code phases ahead and behind the last known phase in larger and larger spreading code phase increments.

During the LOL condition detected by the RCS, the RCS continues to transmit to the SU on the Assigned Channels, and continues to transmit power control signals to the SU to maintain SU transmit power level. The method of transmitting power control signals is described below. Successful reacquisition desirably takes place within a specified period of time. If reacquisition is successful, the call connection continues, otherwise the RCS tears down the call connection by deactivating and deallocating the RCS modem assigned by the WAC, and transmits a call termination signal to a remote call processor, such as the RDU, as described previously.

When the LOL condition is detected by the SU, the SU stops transmission to the RCS on the Assigned Channels which forces the RCS into a LOL condition, and starts the reacquisition algorithm. If reacquisition is successful, the call connection continues, and if not successful, the RCS tears down the call connection by deactivating and deallocating the SU modem as described previously.

POWER CONTROL

General

The power control feature of the present invention is used to minimize the amount of transmit power used by an RCS and the SUs of the system, and the power control subfeature that updates transmit power during bearer channel connection is defined as automatic power control (APC). AC data is transferred from the RCS to an SU on the forward APC channel and from an SU to the RCS on the reverse APC channel. When there is no active data link between the two, the maintenance power control (MPC) subfeature updates the SU transmit power.

Transmit power levels of forward and reverse assigned channels and reverse global channels are controlled by the APC algorithm to maintain sufficient signal power to interference noise power ratio (SIR) on those channels, and to stabilize and minimize system output power. The present invention uses a closed loop power control mechanism in which a receiver decides that the transmitter should incrementally raise or lower its transmit power. This decision is conveyed back to the respective transmitter via the power control signal on the APC channel. The receiver makes the decision to increase or decrease the transmitter's power based on two error signals. One error signal is an indication of the difference between the measured and desired despread signal powers, and the other error signal is an indication of the average received total power.

As used in the described embodiment of the invention, the term near-end power control is used to refer to adjusting the transmitter's output power in accordance with the APC signal received on the APC channel from the other end. This means the reverse power control for the SU and forward power control for the RCS; and the term far-end APC is used to refer to forward power control for the SU and reverse

power control for the RCS (adjusting the opposite end's transmit power).

In order to conserve power, the SU modem terminates transmission and powers-down while waiting for a call, defined as the sleep phase. Sleep phase is terminated by an awaken signal from the SU controller. The SU modem acquisition circuit automatically enters the reacquisition phase, and begins the process of acquiring the downlink pilot, as described previously.

Closed Loop Power Control Algorithms

The near-end power control consists of two steps: first, the initial transmit power is set; and second, the transmit power is continually adjusted according to information received from the far-end using APC.

For the SU, initial transmit power is set to a minimum value and then ramped up, for example, at a rate of 1 dB/ms until either a ramp-up timer expires (not shown) or the RCS changes the corresponding traffic light value on the FBCH to "red" indicating that the RCS has locked to the SU's short pilot SAXPT. Expiration of the timer causes the SAXPT transmission to be shut down, unless the traffic light value is set to red first, in which case the SU continues to ramp-up transmit power but at a much lower rate than before the "red" signal was detected.

For the RCS, initial transmit power is set at a fixed value, corresponding to the minimum value necessary for reliable operation as determined experimentally for the service type and the current number of system users. Global channels, such as Global Pilot or, FBCH, are always transmitted at the fixed initial power, whereas traffic channels are switched to APC.

The APC bits are transmitted as one bit up or down signals on the APC channel. In the described embodiment, the 64 kb/s APC data stream is not encoded or interleaved.

Far-end power control consists of the near-end transmitting power control information for the far-end to use in adjusting its transmit power.

The APC algorithm causes the RCS or the SU to transmit +1 if the following inequality holds, otherwise -1.

$$\alpha_1 e_1 - \alpha_2 e_2 > 0 \quad (45)$$

Here, the error signal e_1 is calculated as

$$e_1 = P_d - (1 + \text{SNR}_{REQ}) P_N \quad (46)$$

where P_d is the despread signal plus noise power, P_N is the despread noise power, and SNR_{REQ} is the desired despread signal to noise ratio for the particular service type; and

$$e_2 = P_r - P_o \quad (47)$$

where P_r is a measure of the received power and P_o is the automatic gain control (AGC) circuit set point. The weights α_1 and α_2 in equation (33) are chosen for each service type and APC update rate.

Maintenance Power Control

During the sleep phase of the SU, the interference noise power of the CDMA RF channel may change. The present invention includes a maintenance power control feature (MPC) which periodically adjusts the SU's initial transmit power with respect to the interference noise power of the CDMA channel. The MPC is the process whereby the transmit power level of an SU is maintained within close

proximity of the minimum level for the RCS to detect the SU's signal. The MPC process compensates for low frequency changes in the required SU transmit power.

The maintenance control feature uses two global channels: one is called the status channel (STCH) on reverse link, and the other is called the check-up channel (CUCH) on forward link. The signals transmitted on these channels carry no data and they are generated the same way the short codes used in initial power ramp-up are generated. The STCH and CUCH codes are generated from a "reserved" branch of the global code generator.

The MPC process is as follows. At random intervals, the SU sends a symbol length spreading code periodically for 3 ms on the status channel (STCH). If the RCS detects the sequence, it replies by sending a symbol length code sequence within the next 3 ms on the check-up channel (CUCH). When the SU detects the response from the RCS, it reduces its transmit power by a particular step size. If the SU does not see any response from the RCS within that 3 ms period, it increases its transmit power by the step size. Using this method, the RCS response is transmitted at a power level that is enough to maintain a 0.99 detection probability at all SU's.

The rate of change of traffic load and the number of active users is related to the total interference noise power of the CDMA channel. The update rate and step size of the maintenance power update signal for the present invention is determined by using queuing theory methods well known in the art of communication theory, such as outlined in "*Fundamentals of Digital Switching*" (Plenum-New York) edited by McDonald and incorporated herein by reference. By modeling the call origination process as an exponential random variable with mean 6.0 mins, numerical computation shows the maintenance power level of a SU should be updated once every 10 seconds or less to be able to follow the changes in interference level using 0.5 dB step size. Modeling the call origination process as a Poisson random variable with exponential interarrival times, arrival rate of 2×10^{-4} per second per user, service rate of $1/360$ per second, and the total subscriber population is 600 in the RCS service area also yields by numerical computation that an update rate of once every 10 seconds is sufficient when 0.5 dB step size is used.

Maintenance power adjustment is performed periodically by the SU which changes from sleep phase to awake phase and performs the MPC process. Consequently, the process for the MPC feature is shown in FIG. 26 and is as follows: First, at step 2601, signals are exchanged between the SU and the RCS maintaining a transmit power level that is close to the required level for detection: the SU periodically sends a symbol length spreading code in the STCH, and the RCS periodically sends a symbol length spreading code in the CUCH as response.

Next, at step 2602, if the SU receives a response within 3 ms after the STCH message it sent, it decreases its transmit power by a particular step size at step 2603; but if the SU does not receive a response within 3 ms after the STCH message, it increases its transmit power by the same step size at step 2604.

The SU waits, at step 2605, for a period of time before sending another STCH message, this time period is determined by a random process which averages 10 seconds.

Thus, the transmit power of the STCH messages from the SU is adjusted based on the RCS response periodically, and the transmit power of the CUCH messages from the RCS is fixed.

Mapping of Power Control Signal to Logical Channels For APC

Power control signals are mapped to specified Logical Channels for controlling transmit power levels of forward and reverse assigned channels. Reverse global channels are also controlled by the APC algorithm to maintain sufficient signal power to interference noise power ratio (SIR) on those reverse channels, and to stabilize and minimize system output power. The present invention uses a closed loop power control method in which a receiver periodically decides to incrementally raise or lower the output power of the transmitter at the other end. The method also conveys that decision back to the respective transmitter.

TABLE 13

APC Signal Channel Assignments			
Link Channels and Signals	Call/Connection Status	Power Control Method	
		Initial Value	Continuous
Reverse link AXCH	Being Established	as determined by power ramping	APC bits in forward APC channel
AXPT			
Reverse link APC, OW, TRCH, pilot signal	In-Progress	level established during call set-up	APC bits in forward APC channel
Forward link APC, OW, TRCH	In-Progress	fixed value	APC bits in reverse APC channel

Forward and reverse links are independently controlled. For a call/connection in process, forward link (TRCHs APC, and OW) power is controlled by the APC bits transmitted on the reverse APC channel. During the call/connection establishment process, reverse link (AXCH) power is also controlled by the APC bits transmitted on the forward APC channel. Table 13 summarizes the specific power control methods for the controlled channels.

The required SIRs of the assigned channels TRCH, APC and OW and reverse assigned pilot signal for any particular SU are fixed in proportion to each other and these channels are subject to nearly identical fading, therefore, they are power controlled together.

Adaptive Forward Power Control

The AFPC process attempts to maintain the minimum required SIR on the forward channels during a call/connection. The AFPC recursive process, shown in FIG. 27, consists of the steps of having an SU form the two error signals e_1 and e_2 in step 2701 where

$$e_1 = P_d - (1 + \text{SNR}_{REQ})P_N \quad (36)$$

$$e_2 = P_r - P_o \quad (37)$$

and P_d is the despread signal plus noise power, P_N is the despread noise power, SNR_{REQ} is the required signal to noise ratio for the service type, P_r is a measure of the total received power, and P_o is the AGC set point. Next, the SU modem forms the combined error signal $\alpha_1 e_1 + \alpha_2 e_2$ in step 2702. Here, the weights α_1 and α_2 are chosen for each service type and APC update rate. In step 2703, the SU hard limits the combined error signal and forms a single APC bit. The SU transmits the APC bit to the RCS in step 2704 and RCS modem receives the bit in step 2705. The RCS increases or decreases its transmit power to the SU in step 2706 and the algorithm repeats starting from step 2701.

Adaptive Reverse Power Control

The ARPC process maintains the minimum desired SIR on the reverse channels to minimize the total system reverse output power, during both call/connection establishment and while the call/connection is in progress. The recursive ARPC process, shown in FIG. 28, begins at step 2801 where the RCS modem forms the two error signals e_1 and e_2 in step 2801 where

$$e_1 = P_d - (1 + \text{SNR}_{REQ}) P_N \quad (38)$$

$$e_2 = P_{\pi} - P_o \quad (39)$$

and P_d is the despread signal plus noise power, P_N is the despread noise power, SNR_{REQ} is the desired signal to noise ratio for the service type, P_{π} is a measure of the average total power received by the RCS, and P_o is the AGC set point. The RCS modem forms the combined error signal $\alpha_1 e_1 + \alpha_2 e_2$ in step 2802 and hard limits this error signal to determine a single APC bit in step 2803. The RCS transmits the APC bit to the SU in step 2804, and the bit is received by the SU in step 2805. Finally, the SU adjusts its transmit power according to the received APC bit in step 2806, and the algorithm repeats starting from step 2801.

TABLE 14

Symbols/Thresholds Used for APC Computation		
Service or Call Type	Call/Connection Status	Symbol (and Threshold) Used for APC Decision
Don't care	Being Established	AXCH
ISDN D SU	In-Progress	one 1/64-kb/s symbol from TRCH (ISDN-D)
ISDN 1B + D SU	In-Progress	TRCH (ISDN-B)
ISDN 2B + D SU	In-Progress	TRCH (one ISDN-B)
POTS SU (64 KBPS PCM)	In-Progress	one 1/64-KBPS symbol from TRCH, use 64 KBPS PCM threshold
POTS SU (32 KBPS ADPCM)	In-Progress	one 1/64-KBPS symbol from TRCH, use 32 KBPS ADPCM threshold
Silent Maintenance Call (any SU)	In-Progress	OW (continuous during a maintenance call)

SIR and Multiple Channel Types

The required SIR for channels on a link is a function of channel format (e.g. TRCH, OW), service type (e.g. ISDN B, 32 KBPS ADPCM POTS), and the number of symbols over which data bits are distributed (e.g. two 64 kb/s symbols are integrated to form a single 32 kb/s ADPCM POTS symbol). Despreader output power corresponding to the required SIR for each channel and service type is predetermined. While a call/connection is in progress, several user CDMA logical channels are concurrently active; each of these channels transfers a symbol every symbol period. The SIR of the symbol from the nominally highest SIR channel is measured, compared to a threshold and used to determine the APC step up/down decision each symbol period. Table 14 indicates the symbol (and threshold) used for the APC computation by service and call type.

APC Parameters

APC information is always conveyed as a single bit of information, and the APC Data Rate is equivalent to the APC Update Rate. The APC update rate is 64 kb/s. This rate is high enough to accommodate expected Rayleigh and Doppler fades, and allow for a relatively high (~0.2) Bit Error

Rate (BER) in the Uplink and Downlink APC channels, which minimizes capacity devoted to the APC.

The power step up/down indicated by an APC bit is nominally between 0.1 and 0.01 dB. The dynamic range for power control is 70 dB on the reverse link and 12 dB on the forward link for the exemplary embodiment of the present system.

Alternative Embodiment of Multiplexing of APC Information

The dedicated APC and OW logical channels described previously can also be multiplexed together in one logical channel. The APC information is transmitted at 64 kb/s, continuously whereas the OW information occurs in data bursts. The alternative multiplexed logical channel includes the unencoded, non-interleaved 64 kb/s. APC information on, for example, the In-phase channel and the OW information on the Quadrature channel of the QPSK signal.

Closed Loop Power Control Implementation

The closed loop power control during a call connection responds to two different variations in overall system power. First, the system responds to local behavior such as changes in power level of an SU, and second, the system responds to changes in the power level of the entire group of active users in the system.

The Power Control system of the exemplary embodiment of the present invention is shown in FIG. 29. As shown, the circuitry used to adjust the transmitted power is similar for the RCS (shown as the RCS power control module 2901) and SU (shown as the SU power control module 2902). Beginning with the RCS power control module 2901, the reverse link RF channel signal is received at the RF antenna and demodulated to produce the reverse CDMA signal RMCH. The signal RMCH is applied to the variable gain amplifier (VGA1) 2910 which produces an input signal to the Automatic Gain Control (AGC) Circuit 2911. The AGC 2911 produces a variable gain amplifier control signal into the VGA1 2910. This signal maintains the level of the output signal of VGA1 2910 at a near constant value. The output signal of VGA1 is despread by the despread-demultiplexer (demux) 2912, which produces a despread user message signal MS and a forward APC bit. The forward APC bit is applied to the integrator 2913 to produce the Forward APC control signal. The Forward APC control signal controls the Forward Link VGA2 2914 and maintains the Forward Link RF channel signal at a minimum desired level for communication.

The signal power of the despread user message signal MS of the RCS power module 2901 is measured by the power

measurement circuit 2915 to produce a signal power indication. The output of the VGA1 is also despread by the AUX despreader which despreads the signal by using an uncorrelated spreading code, and hence obtains a despread noise signal. The power measurement of this signal is multiplied by 1 plus the desired signal to noise ratio (SNR_R) to form the threshold signal S1. The difference between the despread signal power and the threshold value S1 is produced by the subtracter 2916. This difference is the error signal ES1, which is an error signal relating to the particular SU transmit power level. Similarly, the control signal for the VGA1 2910 is applied to the rate scaling circuit 2917 to reduce the rate of the control signal for VGA1 2910. The output signal of scaling circuit 2917 is a scaled system power level signal SP1. The Threshold Compute logic 2918 calculates the System Signal Threshold value SST from the RCS user channel power data signal RCSUSR. The complement of the Scaled system power level signal, SP1, and the System Signal Power Threshold value SST are applied to the adder 2919 which produces second error signal ES2. This error signal is related to the system transmit power level of all active SUs. The input Error signals ES1 and ES2 are combined in the combiner 2920 produce a combined error signal input to the delta modulator (DM1) 2921, and the output signal of the DM1 is the reverse APC bit stream signal, having bits of value +1 or -1, which for the present invention is transmitted as a 64 kb/sec signal.

The Reverse APC bit is applied to the spreading circuit 2922, and the output signal of the spreading circuit 2922 is the spread-spectrum forward APC message signal. Forward OW and Traffic signals are also provided to spreading circuits 2923, 2924, producing forward traffic message signals 1, 2, . . . N. The power level of the forward APC signal, the forward OW, and traffic message signals are adjusted by the respective amplifiers 2925, 2926 and 2927 to produce the power level adjusted forward APC, OW, and TRCH channels signals. These signals are combined by the adder 2928 and applied to the VAG2 2914, which produces forward link RF channel signal.

The forward link RF channel signal including the spread forward APC signal is received by the RF antenna of the SU, and demodulated to produce the forward CDMA signal FMCH. This signal is provided to the variable gain amplifier (VGA3) 2940. The output signal of VGA3 is applied to the Automatic Gain Control Circuit (AGC) 2941 which produces a variable gain amplifier control signal to VGA3 2940. This signal maintains the level of the output signal of VGA3 at a near constant level. The output signal of VAG3 2940 is despread by the despread demux 2942, which produces a despread user message signal SUMS and a reverse APC bit. The reverse APC bit is applied to the integrator 2943 which produces the Reverse APC control signal. This reverse APC control signal is provided to the Reverse APC VGA4 2944 to maintain the Reverse link RF channel signal at a minimum power level.

The despread user message signal SUMS is also applied to the power measurement circuit 2945 producing a power measurement signal, which is added to the complement of threshold value S2 in the adder 2946 to produce error signal ES3. The signal ES3 is an error signal relating to the RCS transmit power level for the particular SU. To obtain threshold S2, the despread noise power indication from the AUX despreader is multiplied by 1 plus the desired signal to noise ratio SNR_R . The AUX despreader despreads the input data using an uncorrelated spreading code, hence its output is an indication of the despread noise power.

Similarly, the control signal for the VGA3 is applied to the rate scaling circuit to reduce the rate of the control signal for

VGA3 in order to produce a scaled received power level RP1 (see FIG. 29). The threshold compute circuit computes the received signal threshold RST from the SU measured power signal SUUSR. The complement of the scaled received power level RP1 and the received signal threshold RST are applied to the adder which produces error signal ES4. This error is related to the RCS transmit power to all other SUs. The input error signals ES3 and ES4 are combined in the combiner and input to the delta modulator DM2 2947. The output signal of DM2 2947 is the forward APC bit stream signal, with bits having value of value +1 or -1. In the exemplary embodiment of the present invention, this signal is transmitted as a 64 kb/sec signal.

The Forward APC bit stream signal is applied to the spreading circuit 2948, to produce the output reverse spread-spectrum APC signal. Reverse OW and Traffic signals are also input to spreading circuits 2949, 2950, producing reverse OW and traffic message signals 1, 2, . . . N, and the reverse pilot is generated by the reverse pilot generator 2951. The power level of the reverse APC message signal, reverse OW message signal, reverse pilot, and the reverse traffic message signals are adjusted by amplifiers 2952, 2953, 2954, 2955 to produce the signals which are combined by the adder 2956 and input to the reverse APC VGA4 2944. It is this VGA4 2944 which produces the reverse link RF channel signal.

During the call connection and bearer channel establishment process, the closed loop power control of the present invention is modified, and is shown in FIG. 30. As shown, the circuits used to adjust the transmitted power are different for the RCS, shown as the Initial RCS power control module 3001; and for the SU, shown as the Initial SU power control module 3002. Beginning with the Initial RCS power control module 3001, the reverse link RF channel signal is received at the RF antenna and demodulated producing the reverse CDMA signal IRMCH which is received by the first variable gain amplifier (VGA1) 3003. The output signal of VGA1 is detected by the Automatic Gain Control Circuit (AGC1) 3004 which provides a variable gain amplifier control signal to VGA1 3003 to maintain the level of the output signal of VAG1 at a near constant value. The output signal of VGA1 is despread by the despread demultiplexer 3005, which produces a despread user message signal IMS. The Forward APC control signal, ISET, is set to a fixed value, and is applied to the Forward Link Variable Gain Amplifier (VGA2) 3006 to set the Forward Link RF channel signal at a predetermined level.

The signal power of the despread user message signal IMS of the Initial RCS power module 3001 is measured by the power measure circuit 3007, and the output power measurement is subtracted from a threshold value S3 in the subtracter 3008 to produce error signal ES5, which is an error signal relating to the transmit power level of a particular SU. The threshold S3 is calculated by multiplying the despread power measurement obtained from the AUX despreader by 1 plus the desired signal to noise ratio SNR_R . The AUX despreader despreads the signal using an uncorrelated spreading code, hence its output signal is an indication of despread noise power. Similarly, the VGA1 control signal is applied to the rate scaling circuit 3009 to reduce the rate of the VGA1 control signal in order to produce a scaled system power level signal SP2. The threshold computation logic 3010 determines an Initial System Signal Threshold value (ISST) computed from the user channel power data signal (IRCSUSR). The complement of the Scaled system power level signal SP2 and the ISST are provided to the adder 3011 which produces a second error signal ES6, which

is an error signal relating to the system transmit power level of all active SUs. The value of ISST is the desired transmit power for a system having the particular configuration. The input Error signals ES5 and ES6 are combined in the combiner 3012 produce a combined error signal input to the delta modulator (DM3) 3013. DM3 produces the initial reverse APC bit stream signal, having bits of value +1 or -1, which in the exemplary embodiment is transmitted as a 64 kb/s signal.

The Reverse APC bit stream signal is applied to the spreading circuit 3014, to produce the initial spread-spectrum forward APC signal. The CTCH information is spread by the spreader 3016 to form the spread CTCH message signal. The spread APC and CTCH signals are scaled by the amplifiers 3015 and 3017, and combined by the combiner 3018. The combined signal is applied to VAG2 3006, which produces the forward link RF channel signal.

The forward link RF channel signal including the spread forward APC signal is received by the RF antenna of the SU and demodulated to produce the initial forward CDMA signal (IFMCH) which is applied to the variable gain amplifier (VGA3) 3020. The output signal of VGA3 is detected by the Automatic Gain Control Circuit (AGC2) 3021 which produces a variable gain amplifier control signal for the VGA3 3020. This signal maintains the output power level of the VGA3 3020 at a near constant value. The output signal of VAG3 is despread by the despread demultiplexer 3022, which produces an initial reverse APC bit that is dependent on the output level of VGA3. The reverse APC bit is processed by the integrator 3023 to produce the Reverse APC control signal. The Reverse APC control signal is provided to the Reverse APC VGA4 3024 to maintain Reverse link RF channel signal at a defined power level.

The global channel AXCH signal is spread by the spreading circuits 3025 to provide the spread AXCH channel signal. The reverse pilot generator 3026 provides a reverse pilot signal, and the signal power of AXCH and the reverse pilot signal are adjusted by the respective amplifiers 3027 and 3028. The spread AXCH channel signal and the reverse pilot signal are summed by the adder 3029 to produce reverse link CDMA signal. The reverse link CDMA signal is received by the reverse APC VGA4 3024, which produces the reverse link RF channel signal output to the RF transmitter.

System Capacity Management

The system capacity management algorithm of the present invention optimizes the maximum user capacity for an RCS area, called a cell. When the SU comes within a certain value of maximum transmit power, the SU sends an alarm message to the RCS. The RCS sets the traffic lights which control access to the system, to "red" which, as previously described, is a flag that inhibits access by the SU's. This condition remains in effect until the call to the alarming SU terminates, or until the transmit power of the alarming SU, measured at the SU, is a value less than the maximum transmit power. When multiple SUs send alarm messages, the condition remains in effect until either all calls from alarming SUs terminate, or until the transmit power of the alarming SU, measured at the SU, is less than the maximum transmit power. An alternative embodiment monitors the bit error rate measurements from the FEC decoder, and holds the RCS traffic lights at "red" until the bit error rate is less than a predetermined value.

The blocking strategy of the present invention includes a method which uses the power control information transmit-

ted from the RCS to an SU, and the received power measurements at the RCS. The RCS measures its transmit power level, detects that a maximum value is reached, and determines when to block new users. An SU preparing to enter the system blocks itself if the SU reaches the maximum transmit power before successful completion of a bearer channel assignment.

Each additional user in the system has the effect of increasing the noise level for all other users, which decreases the signal to noise ratio (SNR) that each user experiences. The power control algorithm maintains a desired SNR for each user. Therefore, in the absence of any other limitations, addition of a new user into the system has only a transient effect and the desired SNR is regained.

The transmit power measurement at the RCS is done by measuring either the root mean square (rms) value of the baseband combined signal or by measuring the transmit power of the RF signal and feeding it back to digital control circuits. The transmit power measurement may also be made by the SUs to determine if the unit has reached its maximum transmit power. The SU transmit power level is determined by measuring the control signal of the RF amplifier, and scaling the value based on the service type, such as POTS, FAX, or ISDN.

The information that an SU has reached the maximum power is transmitted to the RCS by the SU in a message on the Assigned Channels. The RCS also determines the condition by measuring reverse APC changes because, if the RCS sends APC messages to the SU to increase SU transmit power, and the SU transmit power measured at the RCS is not increased, the SU has reached the maximum transmit power.

The RCS does not use traffic lights to block new users who have finished ramping-up using the short codes. These users are blocked by denying them the dial tone and letting them time out. The RCS sends all 1's (go down commands) on the APC Channel to make the SU lower its transmit power. The RCS also sends either no CTCH message or a message with an invalid address which would force the FSU to abandon the access procedure and start over. The SU, however, does not start the acquisition process immediately because the traffic lights are red.

When the RCS reaches its transmit power limit, it enforces blocking in the same manner as when an SU reaches its transmit power limit. The RCS turns off all the traffic lights on the FBCH, starts sending all 1 APC bits (go down commands) to those users who have completed their short code ramp-up but have not yet been given a dial tone, and either sends no CTCH message to these users or sends messages with invalid addresses to force them to abandon the access process.

The self blocking process of the SU is as follows. When the SU starts transmitting the AXCH, the APC starts its power control operation using the AXCH and the SU transmit power increases. While the transmit power is increasing under the control of the APC, it is monitored by the SU controller. If the transmit power limit is reached, the SU abandons the access procedure and starts over.

System Synchronization

The RCS is synchronized either to the PSTN Network Clock signal through one of the Line interfaces, as shown in FIG. 10, or to the RCS system clock oscillator, which free-runs to provide a master timing signal for the system. The Global Pilot Channel, and therefore all Logical channels within the CDMA channel, are synchronized to the system

clock signal of the RCS. The Global Pilot (GLPT) is transmitted by the RCS and defines the timing at the RCS transmitter.

The SU receiver is synchronized to the GLPT, and so behaves as a slave to the Network Clock oscillator. However, the SU timing is retarded by the propagation delay. In the present embodiment of the invention, the SU modem extracts a 64 KHz and 8 KHz clock signal from the CDMA RF Receive channel, and a PLL oscillator circuit creates 2 MHz and 4 MHz clock signals

The SU transmitter and hence the LAXPT or ASPT are slaved to the timing of the SU receiver.

The RCS receiver is synchronized to the LAXPT or the ASPT transmitted by the SU, however, its timing may be retarded by the propagation delay. Hence, the timing of the

RCS receiver is that of the RCS transmitter retarded by twice the propagation delay.

Furthermore, the system can be synchronized via a reference received from a Global Positioning System receiver (GPS). In a system of this type, a GPS receiver in each RCS provides a reference clock signal to all submodules of the RCS. Because each RCS receives the same time reference from the GPS, all of the system clock signals in all of the RCSs are synchronized.

Although the invention has been described in terms of multiple exemplary embodiments, it is understood by those skilled in the art that the invention may be practiced with modifications to the embodiments that are within the scope of the invention as defined by the following claims.

APPENDIX A

0	75	150	225	300	375	450	525	600	675	750	825
1	76	151	226	301	376	451	526	601	676	751	826
2	77	152	227	302	377	452	527	602	677	752	827
3	78	153	228	303	378	453	528	603	678	753	828
4	79	154	229	304	379	454	529	604	679	754	829
5	80	155	230	305	380	455	530	605	680	755	830
6	81	156	231	306	381	456	531	606	681	756	831
7	82	157	232	307	382	457	532	607	682	757	832
8	83	158	233	308	383	458	533	608	683	758	833
9	84	159	234	309	384	459	534	609	684	759	834
10	85	160	235	310	385	460	535	610	685	760	835
11	86	161	236	311	386	461	536	611	686	761	836
12	87	162	237	312	387	462	537	612	687	762	837
13	88	163	238	313	388	463	538	613	688	763	838
14	89	164	239	314	389	464	539	614	689	764	839
15	90	165	240	315	390	465	540	615	690	765	840
16	91	166	241	316	391	466	541	616	691	766	841
17	92	167	242	317	392	467	542	617	692	767	842
18	93	168	243	318	393	468	543	618	693	768	843
19	94	169	244	319	394	469	544	619	694	769	844
20	95	170	245	320	395	470	545	620	695	770	845
21	96	171	246	321	396	471	546	621	696	771	846
22	97	172	247	322	397	472	547	622	697	772	847
23	98	173	248	323	398	473	548	623	698	773	848
24	99	174	249	324	399	474	549	624	699	774	849
25	100	175	250	325	400	475	550	625	700	775	850
26	101	176	251	326	401	476	551	626	701	776	851
27	102	177	252	327	402	477	552	627	702	777	852
28	103	178	253	328	403	478	553	628	703	778	853
29	104	179	254	329	404	479	554	629	704	779	854
30	105	180	255	330	405	480	555	630	705	780	855
31	106	181	256	331	406	481	556	631	706	781	856
32	107	182	257	332	407	482	557	632	707	782	857
33	108	183	258	333	408	483	558	633	708	783	858
34	109	184	259	334	409	484	559	634	709	784	859
35	110	185	260	335	410	485	560	635	710	785	860
36	111	186	261	336	411	486	561	636	711	786	861
37	112	187	262	337	412	487	562	637	712	787	862
38	113	188	263	338	413	488	563	638	713	788	863
39	114	189	264	339	414	489	564	639	714	789	864
40	115	190	265	340	415	490	565	640	715	790	865
41	116	191	266	341	416	491	566	641	716	791	866
42	117	192	267	342	417	492	567	642	717	792	867
43	118	193	268	343	418	493	568	643	718	793	868
44	119	194	269	344	419	494	569	644	719	794	869
45	120	195	270	345	420	495	570	645	720	795	870
46	121	196	271	346	421	496	571	646	721	796	871
47	122	197	272	347	422	497	572	647	722	797	872
48	123	198	273	348	423	498	573	648	723	798	873
49	124	199	274	349	424	499	574	649	724	799	874
50	125	200	275	350	425	500	575	650	725	800	875
51	126	201	276	351	426	501	576	651	726	801	876
52	127	202	277	352	427	502	577	652	727	802	877
53	128	203	278	353	428	503	578	653	728	803	878
54	129	204	279	354	429	504	579	654	729	804	879
55	130	205	280	355	430	505	580	655	730	805	880
56	131	206	281	356	431	506	581	656	731	806	881
57	132	207	282	357	432	507	582	657	732	807	882

-continued

APPENDIX A

58	133	208	283	358	433	508	583	658	733	808	883
59	134	209	284	359	434	509	584	659	734	809	884
60	135	210	285	360	435	510	585	660	735	810	885
61	136	211	286	361	436	511	586	661	736	811	886
62	137	212	287	362	437	512	587	662	737	812	887
63	138	213	288	363	438	513	588	663	738	813	888
64	139	214	289	364	439	514	589	664	739	814	889
65	140	215	290	365	440	515	590	665	740	815	890
66	141	216	291	366	441	516	591	666	741	816	891
67	142	217	292	367	442	517	592	667	742	817	892
68	143	218	293	368	443	518	593	668	743	818	893
69	144	219	294	369	444	519	594	669	744	819	894
70	145	220	295	370	445	520	595	670	745	820	895
71	146	221	296	371	446	521	596	671	746	821	896
72	147	222	297	372	447	522	597	672	747	822	897
73	148	223	298	373	448	523	598	673	748	823	898
74	149	224	299	374	449	524	599	674	749	824	899
900	975	1050	2227	2302	2377	2452	2527	2602	2677	2752	2827
901	976	1051	2228	2303	2378	2453	2528	2603	2678	2753	2828
902	977	1052	2229	2304	2379	2454	2529	2604	2679	2754	2829
903	973	1053	2230	2305	2380	2455	2530	2605	2680	2755	2830
904	979	1054	2231	2306	2381	2456	2531	2606	2681	2756	2831
905	980	1055	2232	2307	2382	2457	2532	2607	2682	2757	2832
906	981	1056	2233	2308	2383	2458	2533	2608	2683	2758	2833
907	982	1057	2234	2309	2384	2459	2534	2609	2684	2759	2834
908	983	1058	2235	2310	2385	2460	2535	2610	2685	2760	2835
909	984	1059	2236	2311	2386	2461	2536	2611	2686	2761	2836
910	985	1060	2237	2312	2387	2462	2537	2612	2687	2762	2837
911	986	1061	2238	2313	2388	2463	2538	2613	2688	2763	2838
912	987	1062	2239	2314	2389	2464	2539	2614	2689	2764	2839
913	988	1063	2240	2315	2390	2465	2540	2615	2690	2765	2840
914	989	1064	2241	2316	2391	2466	2541	2616	2691	2766	2841
915	990	1065	2242	2317	2392	2467	2542	2617	2692	2767	2842
916	991	1066	2243	2318	2393	2468	2543	2618	2693	2768	2843
917	992	1067	2244	2319	2394	2469	2544	2619	2694	2769	2844
918	993	1068	2245	2320	2395	2470	2545	2620	2695	2770	2845
919	994	1069	2246	2321	2396	2471	2546	2621	2696	2771	2846
920	995	1070	2247	2322	2397	2472	2547	2622	2697	2772	2847
921	996	1071	2248	2323	2398	2473	2548	2623	2698	2773	2848
922	997	1072	2249	2324	2399	2474	2549	2624	2699	2774	2849
923	998	1073	2250	2325	2400	2475	2550	2625	2700	2775	2850
924	999	1074	2251	2326	2401	2476	2551	2626	2701	2776	2851
925	1000	1075	2252	2327	2402	2477	2552	2627	2702	2777	2852
926	1001	1076	2253	2328	2403	2478	2553	2628	2703	2778	2853
927	1002	1077	2254	2329	2404	2479	2554	2629	2704	2779	2854
928	1003	1078	2255	2330	2405	2480	2555	2630	2705	2780	2855
929	1004	1079	2256	2331	2406	2481	2556	2631	2706	2781	2856
930	1005	1080	2257	2332	2407	2482	2557	2632	2707	2782	2857
931	1006	1081	2258	2333	2408	2483	2558	2633	2708	2783	2858
932	1007	1082	2259	2334	2409	2484	2559	2634	2709	2784	2859
933	1008	1083	2260	2335	2410	2485	2560	2635	2710	2785	2860
934	1009	1084	2261	2336	2411	2486	2561	2636	2711	2786	2861
935	1010	1085	2262	2337	2412	2487	2562	2637	2712	2787	2862
936	1011	1086	2263	2338	2413	2488	2563	2638	2713	2788	2863
937	1012	1087	2264	2339	2414	2489	2564	2639	2714	2789	2864
938	1013	1088	2265	2340	2415	2490	2565	2640	2715	2790	2865
939	1014	1089	2266	2341	2416	2491	2566	2641	2716	2791	2866
940	1015	1090	2267	2342	2417	2492	2567	2642	2717	2792	2867
941	1016	1091	2268	2343	2418	2493	2568	2643	2718	2793	2868
942	1017	1092	2269	2344	2419	2494	2569	2644	2719	2794	2869
943	1018	1093	2270	2345	2420	2495	2570	2645	2720	2795	2870
944	1019	1094	2271	2346	2421	2496	2571	2646	2721	2796	2871
945	1020	1095	2272	2347	2422	2497	2572	2647	2722	2797	2872
946	1021	1096	2273	2348	2423	2498	2573	2648	2723	2798	2873
947	1022	1097	2274	2349	2424	2499	2574	2649	2724	2799	2874
948	1023	1098	2275	2350	2425	2500	2575	2650	2725	2800	2875
949	1024	1099	2276	2351	2426	2501	2576	2651	2726	2801	2876
950	1025	1100	2277	2352	2427	2502	2577	2652	2727	2802	2877
951	1026	1101	2278	2353	2428	2503	2578	2653	2728	2803	2878
952	1027	1102	2279	2354	2429	2504	2579	2654	2729	2804	2879
953	1028	1103	2280	2355	2430	2505	2580	2655	2730	2805	2880
954	1029	1104	2281	2356	2431	2506	2581	2656	2731	2806	2881
955	1030	1105	2282	2357	2432	2507	2582	2657	2732	2807	2882
956	1031	1106	2283	2358	2433	2508	2583	2658	2733	2808	2883
957	1032	1107	2284	2359	2434	2509	2584	2659	2734	2809	2884
958	1033	1108	2285	2360	2435	2510	2585	2660	2735	2810	2885
959	1034	1109	2286	2361	2436	2511	2586	2661	2736	2811	2886

-continued

APPENDIX A											
960	1035	2212	2287	2362	2437	2512	2587	2662	2737	2812	2887
961	1036	2213	2288	2363	2438	2513	2588	2663	2738	2813	2888
962	1037	2214	2289	2364	2439	2514	2589	2664	2739	2814	2889
963	1038	2215	2290	2365	2440	2515	2590	2665	2740	2815	2890
964	1039	2216	2291	2366	2441	2516	2591	2666	2741	2816	2891
965	1040	2217	2292	2367	2442	2517	2592	2667	2742	2817	2892
966	1041	2218	2293	2368	2443	2518	2593	2668	2743	2818	2893
967	1042	2219	2294	2369	2444	2519	2594	2669	2744	2819	2894
968	1043	2220	2295	2370	2445	2520	2595	2670	2745	2820	2895
969	1044	2221	2296	2371	2446	2521	2596	2671	2746	2821	2896
970	1045	2222	2297	2372	2447	2522	2597	2672	2747	2822	2897
971	1046	2223	2298	2373	2448	2523	2598	2673	2748	2823	2898
972	1047	2224	2299	2374	2449	2524	2599	2674	2749	2824	2899
973	1048	2225	2300	2375	2450	2525	2600	2675	2750	2825	2900
974	1049	2226	2301	2376	2451	2526	2601	2676	2751	2826	2901
2902	2977	3052	3127	3202	3277	4454	4529	4604	4679	4754	4829
2903	2978	3053	3128	3203	3278	4455	4530	4605	4680	4755	4830
2904	2979	3054	3129	3204	3279	4456	4531	4606	4681	4756	4831
2905	2980	3055	3130	3205	3280	4457	4532	4607	4682	4757	4832
2906	2981	3056	3131	3206	3281	4458	4533	4608	4683	4758	4833
2907	2982	3057	3132	3207	3282	4459	4534	4609	4684	4759	4834
2908	2983	3058	3133	3208	3283	4460	4535	4610	4685	4760	4835
2909	2984	3059	3134	3209	3284	4461	4536	4611	4686	4761	4836
2910	2985	3060	3135	3210	3285	4462	4537	4612	4687	4762	4837
2911	2986	3061	3136	3211	3286	4463	4538	4613	4688	4763	4838
2912	2987	3062	3137	3212	3287	4464	4539	4614	4689	4764	4839
2913	2988	3063	3138	3213	3288	4465	4540	4615	4690	4765	4840
2914	2989	3064	3139	3214	3289	4466	4541	4616	4691	4766	4841
2915	2990	3065	3140	3215	3290	4467	4542	4617	4692	4767	4842
2916	2991	3066	3141	3216	3291	4468	4543	4618	4693	4768	4843
2917	2992	3067	3142	3217	3292	4469	4544	4619	4694	4769	4844
2918	2993	3068	3143	3218	3293	4470	4545	4620	4695	4770	4845
2919	2994	3069	3144	3219	3294	4471	4546	4621	4696	4771	4846
2920	2995	3070	3145	3220	3295	4472	4547	4622	4697	4772	4847
2921	2996	3071	3146	3221	3296	4473	4548	4623	4698	4773	4848
2922	2997	3072	3147	3222	3297	4474	4549	4624	4699	4774	4849
2923	2998	3073	3148	3223	3298	4475	4550	4625	4700	4775	4850
2924	2999	3074	3149	3224	3299	4476	4551	4626	4701	4776	4851
2925	3000	3075	3150	3225	3300	4477	4552	4627	4702	4777	4852
2926	3001	3076	3151	3226	3301	4478	4553	4628	4703	4778	4853
2927	3002	3077	3152	3227	3302	4479	4554	4629	4704	4779	4854
2928	3003	3078	3153	3228	3303	4480	4555	4630	4705	4780	4855
2929	3004	3079	3154	3229	3304	4481	4556	4631	4706	4781	4856
2930	3005	3080	3155	3230	3305	4482	4557	4632	4707	4782	4857
2931	3006	3081	3156	3231	4408	4483	4558	4633	4708	4783	4858
2932	3007	3082	3157	3232	4409	4484	4559	4634	4709	4784	4859
2933	3008	3083	3158	3233	4410	4485	4560	4635	4710	4785	4860
2934	3009	3084	3159	3234	4411	4486	4561	4636	4711	4786	4861
2935	3010	3085	3160	3235	4412	4487	4562	4637	4712	4787	4862
2936	3011	3086	3161	3236	4413	4488	4563	4638	4713	4788	4863
2937	3012	3087	3162	3237	4414	4489	4564	4639	4714	4789	4864
2938	3013	3088	3163	3238	4415	4490	4565	4640	4715	4790	4865
2939	3014	3089	3164	3239	4416	4491	4566	4641	4716	4791	4866
2940	3015	3090	3165	3240	4417	4492	4567	4642	4717	4792	4867
2941	3016	3091	3166	3241	4418	4493	4568	4643	4718	4793	4868
2942	3017	3092	3167	3242	4419	4494	4569	4644	4719	4794	4869
2943	3018	3093	3168	3243	4420	4495	4570	4645	4720	4795	4870
2944	3019	3094	3169	3244	4421	4496	4571	4646	4721	4796	4871
2945	3020	3095	3170	3245	4422	4497	4572	4647	4722	4797	4872
2946	3021	3096	3171	3246	4423	4498	4573	4648	4723	4798	4873
2947	3022	3097	3172	3247	4424	4499	4574	4649	4724	4799	4874
2948	3023	3098	3173	3248	4425	4500	4575	4650	4725	4800	4875
2949	3024	3099	3174	3249	4426	4501	4576	4651	4726	4801	4876
2950	3025	3100	3175	3250	4427	4502	4577	4652	4727	4802	4877
2951	3026	3101	3176	3251	4428	4503	4578	4653	4728	4803	4878
2952	3027	3102	3177	3252	4429	4504	4579	4654	4729	4804	4879
2953	3028	3103	3178	3253	4430	4505	4580	4655	4730	4805	4880
2954	3029	3104	3179	3254	4431	4506	4581	4656	4731	4806	4881
2955	3030	3105	3180	3255	4432	4507	4582	4657	4732	4807	4882
2956	3031	3106	3181	3256	4433	4508	4583	4658	4733	4808	4883
2957	3032	3107	3182	3257	4434	4509	4584	4659	4734	4809	4884
2958	3033	3108	3183	3258	4435	4510	4585	4660	4735	4810	4885
2959	3034	3109	3184	3259	4436	4511	4586	4661	4736	4811	4886
2960	3035	3110	3185	3260	4437	4512	4587	4662	4737	4812	4887
2961	3036	3111	3186	3261	4438	4513	4588	4663	4738	4813	4888
2962	3037	3112	3187	3262	4439	4514	4589	4664	4739	4814	4889
2963	3038	3113	3188	3263	4440	4515	4590	4665	4740	4815	4890

-continued

APPENDIX A

2964	3039	3114	3189	3264	4441	4516	4591	4666	4741	4816	4891
2965	3040	3115	3190	3265	4442	4517	4592	4667	4742	4817	4892
2966	3041	3116	3191	3266	4443	4518	4593	4678	4743	4818	4893
2967	3042	3117	3192	3267	4444	4519	4594	4679	4744	4819	4894
2968	3043	3118	3193	3268	4445	4520	4595	4680	4745	4820	4895
2969	3044	3119	3194	3269	4446	4521	4596	4681	4746	4821	4896
2970	3045	3120	3195	3270	4447	4522	4597	4682	4747	4822	4897
2971	3046	3121	3196	3271	4448	4523	4598	4683	4748	4823	4898
2972	3047	3122	3197	3272	4449	4524	4599	4684	4749	4824	4899
2973	3048	3123	3198	3273	4450	4525	4600	4685	4750	4825	4900
2974	3049	3124	3199	3274	4451	4526	4601	4686	4751	4826	4901
2975	3050	3125	3200	3275	4452	4527	4602	4687	4752	4827	4902
2976	3051	3126	3201	3276	4453	4528	4603	4688	4753	4828	4903
4904	4979	5054	5129	5204	5279	5354	5429	5504	6681	6756	6831
4905	4980	5055	5130	5205	5280	5355	5430	5505	6682	6757	6832
4906	4981	5056	5131	5206	5281	5356	5431	5506	6683	6758	6833
4907	4982	5057	5132	5207	5282	5357	5432	5507	6684	6759	6834
4908	4983	5058	5133	5208	5283	5358	5433	5508	6685	6760	6835
4909	4984	5059	5134	5209	5284	5359	5434	5509	6686	6761	6836
4910	4985	5060	5135	5210	5285	5360	5435	5510	6687	6762	6837
4911	4986	5061	5136	5211	5286	5361	5436	5511	6688	6763	6838
4912	4987	5062	5137	5212	5287	5362	5437	5512	6689	6764	6839
4913	4988	5063	5138	5213	5288	5363	5438	5513	6690	6765	6840
4914	4989	5064	5139	5214	5289	5364	5439	5514	6691	6766	6841
4915	4990	5065	5140	5215	5290	5365	5440	5515	6692	6767	6842
4916	4991	5066	5141	5216	5291	5366	5441	5516	6693	6768	6843
4917	4992	5067	5142	5217	5292	5367	5442	5517	6694	6769	6844
4918	4993	5068	5143	5218	5293	5368	5443	5518	6695	6770	6845
4919	4994	5069	5144	5219	5294	5369	5444	5519	6696	6771	6846
4920	4995	5070	5145	5220	5295	5370	5445	5520	6697	6772	6847
4921	4996	5071	5146	5221	5296	5371	5446	5521	6698	6773	6848
4922	4997	5072	5147	5222	5297	5372	5447	5522	6699	6774	6849
4923	4998	5073	5148	5223	5298	5373	5448	5523	6700	6775	6850
4924	4999	5074	5149	5224	5299	5374	5449	5524	6701	6776	6851
4925	5000	5075	5150	5225	5300	5375	5450	5525	6702	6777	6852
4926	5001	5076	5151	5226	5301	5376	5451	5526	6703	6778	6853
4927	5002	5077	5152	5227	5302	5377	5452	5527	6704	6779	6854
4928	5003	5078	5153	5228	5303	5378	5453	5528	6705	6780	6855
4929	5004	5079	5154	5229	5304	5379	5454	5529	6706	6781	6856
4930	5005	5080	5155	5230	5305	5380	5455	5530	6707	6782	6857
4931	5006	5081	5156	5231	5306	5381	5456	5531	6708	6783	6858
4932	5007	5082	5157	5232	5307	5382	5457	5532	6709	6784	6859
4933	5008	5083	5158	5233	5308	5383	5458	5533	6710	6785	6860
4934	5009	5084	5159	5234	5309	5384	5459	5534	6711	6786	6861
4935	5010	5085	5160	5235	5310	5385	5460	5535	6712	6787	6862
4936	5011	5086	5161	5236	5311	5386	5461	5536	6713	6788	6863
4937	5012	5087	5162	5237	5312	5387	5462	5537	6714	6789	6864
4938	5013	5088	5163	5238	5313	5388	5463	5538	6715	6790	6865
4939	5014	5089	5164	5239	5314	5389	5464	5539	6716	6791	6866
4940	5015	5090	5165	5240	5315	5390	5465	5540	6717	6792	6867
4941	5016	5091	5166	5241	5316	5391	5466	5541	6718	6793	6868
4942	5017	5092	5167	5242	5317	5392	5467	5542	6719	6794	6869
4943	5018	5093	5168	5243	5318	5393	5468	5543	6720	6795	6870
4944	5019	5094	5169	5244	5319	5394	5469	5544	6721	6796	6871
4945	5020	5095	5170	5245	5320	5395	5470	5545	6722	6797	6872
4946	5021	5096	5171	5246	5321	5396	5471	5546	6723	6798	6873
4947	5022	5097	5172	5247	5322	5397	5472	5547	6724	6799	6874
4948	5023	5098	5173	5248	5323	5398	5473	5548	6725	6800	6875
4949	5024	5099	5174	5249	5324	5399	5474	5549	6726	6801	6876
4950	5025	5100	5175	5250	5325	5400	5475	5550	6727	6802	6877
4951	5026	5101	5176	5251	5326	5401	5476	5551	6728	6803	6878
4952	5027	5102	5177	5252	5327	5402	5477	5552	6729	6804	6879
4953	5028	5103	5178	5253	5328	5403	5478	5553	6730	6805	6880
4954	5029	5104	5179	5254	5329	5404	5479	5554	6731	6806	6881
4955	5030	5105	5180	5255	5330	5405	5480	5555	6732	6807	6882
4956	5031	5106	5181	5256	5331	5406	5481	5556	6733	6808	6883
4957	5032	5107	5182	5257	5332	5407	5482	5557	6734	6809	6884
4958	5033	5108	5183	5258	5333	5408	5483	5558	6735	6810	6885
4959	5034	5109	5184	5259	5334	5409	5484	5559	6736	6811	6886
4960	5035	5110	5185	5260	5335	5410	5485	5560	6737	6812	6887
4961	5036	5111	5186	5261	5336	5411	5486	5561	6738	6813	6888
4962	5037	5112	5187	5262	5337	5412	5487	5562	6739	6814	6889
4963	5038	5113	5188	5263	5338	5413	5488	5563	6740	6815	6890
4964	5039	5114	5189	5264	5339	5414	5489	5564	6741	6816	6891
4965	5040	5115	5190	5265	5340	5415	5490	5565	6742	6817	6892
4966	5041	5116	5191	5266	5341	5416	5491	5566	6743	6818	6893
4967	5042	5117	5192	5267	5342	5417	5492	5567	6744	6819	6894

-continued

APPENDIX A

4968	5043	5118	5193	5268	5343	5418	5493	6670	6735	6820	6895
4969	5044	5119	5194	5269	5344	5419	5494	6671	6736	6821	6896
4970	5045	5120	5195	5270	5345	5420	5495	6672	6737	6822	6897
4971	5046	5121	5196	5271	5346	5421	5496	6673	6738	6823	6898
4972	5047	5122	5197	5272	5347	5422	5497	6674	6739	6824	6899
4973	5048	5123	5198	5273	5348	5423	5498	6675	6740	6825	6900
4974	5049	5124	5199	5274	5349	5424	5499	6676	6741	6826	6901
4975	5050	5125	5200	5275	5350	5425	5500	6677	6742	6827	6902
4976	5051	5126	5201	5276	5351	5426	5501	6678	6743	6828	6903
4977	5052	5127	5202	5277	5352	5427	5502	6679	6744	6829	6904
4978	5053	5128	5203	5278	5353	5428	5503	6680	6745	6830	6905
<hr/>											
6906	6930	6954	6978	7002	7026	7050	7074	7098	7122	7146	7170
6907	6931	6955	6979	7003	7027	7051	7075	7099	7123	7147	7171
6908	6932	6956	6980	7004	7028	7052	7076	7100	7124	7148	7172
6909	6933	6957	6981	7005	7029	7053	7077	7101	7125	7149	7173
6910	6934	6958	6982	7006	7030	7054	7078	7102	7126	7150	7174
6911	6935	6959	6983	7007	7031	7055	7079	7103	7127	7151	7175
6912	6936	6960	6984	7008	7032	7056	7080	7104	7128	7152	7176
6913	6937	6961	6985	7009	7033	7057	7081	7105	7129	7153	7177
6914	6938	6962	6986	7010	7034	7058	7082	7106	7130	7154	7178
6915	6939	6963	6987	7011	7035	7059	7083	7107	7131	7155	7179
6916	6940	6964	6988	7012	7036	7060	7084	7108	7132	7156	7180
6917	6941	6965	6989	7013	7037	7061	7085	7109	7133	7157	7181
6918	6942	6966	6990	7014	7038	7062	7086	7110	7134	7158	7182
6919	6943	6967	6991	7015	7039	7063	7087	7111	7133	7159	7183
6920	6944	6968	6992	7016	7040	7064	7088	7112	7134	7160	7184
6921	6945	6969	6993	7017	7041	7065	7089	7113	7135	7161	
6922	6946	6970	6994	7018	7042	7066	7090	7114	7136	7162	
6923	6947	6971	6995	7019	7043	7067	7091	7115	7137	7163	
6924	6948	6972	6996	7020	7044	7068	7092	7116	7138	7164	
6925	6949	6973	6997	7021	7045	7069	7093	7117	7139	7165	
6926	6950	6974	6998	7022	7046	7070	7094	7118	7140	7166	
6927	6951	6975	6999	7023	7047	7071	7095	7119	7141	7167	
6928	6952	6976	7000	7024	7048	7072	7096	7120	7142	7168	
6929	6953	6977	7001	7025	7049	7073	7097	7121	7143	7169	

The invention claimed is:

1. A multiple access, spread-spectrum communication system for processing a plurality of telecommunication information signals received simultaneously for simultaneous transmission over a radio frequency (RF) channel as a code-division-multiplexed (CDM) signal, the system comprising:

means for receiving a call request signal corresponding to a telecommunication line information signal, and a user identification signal identifying a user to which the call request and information signal are addressed;

a plurality of modem processing means, one of the plurality of modem processing means providing a global pilot code signal, and each of the modem processing means providing a respective message code signal and combining one of the plurality of information signals with the respective message code signal to provide a spread-spectrum processed message signal, the plurality of message code signals of the plurality of modem processing means being synchronized to the global pilot code signal;

assignment means responsive to a channel assignment signal for coupling the information signals received on the telecommunication lines to respective indicated ones of the plurality of modem means;

a system channel controller, coupled to a remote call-processing means and responsive to the user identification signal, for providing the channel assignment signal; and

an RF transmitter means, connected to each of the plurality of modem processing means, for combining the plurality of spread-spectrum processed message signals

with the global pilot code signal to generate a CDM signal; for modulating a carrier signal with the CDM signal and for transmitting the modulated carrier signal through an RF communication channel.

2. The multiple-access spread-spectrum communication system of claim 1, wherein one of the plurality of modem processing means further comprises:

a) code generation means comprising a generic pilot code means providing a pilot code signal, and a message means for generating a plurality of message code signals; and

b) spreading means coupled to the message means for combining each of the information signals, user identification signals, and call type signals with a respective one of the plurality of message code signals to generate a plurality of spread-spectrum processed message signals.

3. The multiple access spread-spectrum-communication system of claim 2, wherein:

the generic pilot code means provides the global pilot code signal, and the message means is responsive to a timing signal which is synchronous with the global pilot code signal, such that each of the plurality of message code signals of the plurality of modem processing means is synchronous with the global pilot code signal.

4. The multiple access spread-spectrum communication system of claim 1, wherein:

each of the plurality of information signals has several different channel rates; and

each of the plurality of message code signals supports a pre-determined information channel rate;

81

and the system further comprises:

remote call-processing means for providing a call type signal corresponding to the information signal rate for each of the information signals; and information channel mode modification means, connected to the system channel controller and to the plurality of modem means and responsive to the call type signal, for changing the combination of the information signals and the respective message code signal to another pre-determined one of the message code signals to support a different information channel rate for the message signal.

5. A subscriber unit for a multiple access, spread-spectrum communication system that receives and processes a code-division multiplexed (CDM) signal which modulates a carrier signal in a radio frequency (RF) channel to reconstruct a transmitted information signal assigned to a subscriber comprising:

receiving means for receiving the modulated carrier signal from the RF channel and for demodulating the CDM signal from the carrier signal;

a subscriber unit controller;

modem processing means comprising:

- a) global pilot code acquisition means comprising a global pilot code generation means for providing a global pilot code signal; a plurality of global pilot code-phase delayed correlation means for correlating the global pilot code signal with the CDM signal to produce a despread global pilot code signal, the code phase of the global pilot signal being changed responsive to an acquisition signal; and means for determining whether the despread global pilot signal is present to produce an acquisition signal;
- b) a plurality of message code generators which produce a plurality of message code signals synchronized to the global pilot code signal; and
- c) global pilot code tracking means for producing an error signal responsive to the acquisition signal;
- d) means for adjusting the global pilot code signal in phase, responsive to the error signal in a sense to produce the acquisition signal which corresponds to an increased level of the despread global pilot signal; and

82

e) a plurality of message signal acquisition means for providing a plurality of despread receive message signals, each acquisition means including a plurality of message signal correlators, each message signal correlator correlating a respective one of the message code signals with the CDM signal to produce a respective despread receive message signal.

6. The subscriber unit of claim 5, wherein:

the signal from the radio frequency (RF) channel includes a user identification signal and the call type signal each associated with the information signal and assigned to a subscriber unit.

7. The subscriber unit of claim 6, wherein:

the despread message signals include the user identification signal and the call type signal; and

the subscriber controller is responsive to the user identification signal to provide the call type signal for the received information signal and the despread information signal to the local subscriber.

8. The subscriber unit of claim 5, wherein:

one of the despread receive message signals includes an information signal and a message type signal corresponding to the information signal rate of one of the information signals; and the subscriber unit further comprises:

information channel mode modification means responsive to the message type signal received with the despread receive message signal for changing a received information signal from a first message code to a second pre-determined message code which second message code supports a different despread information channel rate than the first message code; and

signal conversion means responsive to the message type signal for selectively converting the despread information signal into a sampled data digital signal.

9. A multiple access, spread-spectrum communication system according to claim 1, wherein the global pilot code signal and each message code signal are generated from, and related by, at least one of a family of code generation seeds.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 5,799,010 Page 1 of 4
DATED : August 25, 1998
INVENTOR(S) : Lomp et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below: On the title page:

On page 2, under other publications, please insert
--Raymond W. Nettleton, "Spectral Efficiency in Cellular Land-Mobile Communications: A Spread-Spectrum Approach", UMI Dissertation Information Service (1978) 204 pp.

Hossein Al Avi, "Power Control and Interference Management in a Spread-Spectrum Cellular Mobile Radio System," UMI Dissertation Information Services, (1984). 129 pp.--

At column 6, line 65, delete "AC" and insert therefor
--APC--.

At column 7, line 7, delete "AC" and insert therefor
--APC--.

At column 9, line 26, delete "AID" and insert therefor
--A/D--.

At column 10, line 38, delete "SHC" and insert therefor
--SLIC--.

At column 11, line 18, after "these" delete "to".

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 5,799,010
DATED : August 25, 1998 Page 2 of 4
INVENTOR(S) : Lomp et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

At column 12, line 15 delete "AC" and insert therefor
--APC--.

At column 12, line 17 delete "AC" and insert therefor
--APC--.

At column 12, line 22 delete "AC" and insert therefor
--APC--.

At column 15, line 6 delete "AC" and insert therefor
--APC--.

At column 15, line 25 delete "AC" and insert therefor
--APC--.

At column 16, line 18 delete "AC" each (each occurrence)
and insert therefor --APC--.

At column 16, line 21 delete "AC" and insert therefor
--APC--.

At column 47, line 31 delete "tip" and insert therefor
--up--.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 5,799,010

DATED : August 25, 1998

Page 3 of 4

INVENTOR(S) : Lomp et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

At column 61, line 40 delete "AC" and insert therefor
--APC--.

At column 50, line 37 delete " $C_{m\&k}^*$ " and insert therefor
-- $C_{m\&k}^*$ --.

At column 77 and 78, within subcolumn 10, delete the series of numbers starting with the second instance of "6692" and ending with the "6743" and insert therefor a series of numbers starting with 6694 and ending with 6755 in increments of one.
increments of one.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

Page 4 of 4

PATENT NO. : 5,799,010
DATED : August 25, 1998
INVENTOR(S) : Lomp et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

At column 80, within subcolumn 10 delete the series of numbers starting with the second instance of "7133" and ending with "7143" and insert therefor a series of numbers starting with 7135 and ending with 7145 in increments of one.

Signed and Sealed this

Twenty-second Day of February, 2000

Attest:



Q. TODD DICKINSON

Attesting Officer

Commissioner of Patents and Trademarks