



US 20130176700A1

(19) **United States**

(12) **Patent Application Publication**  
**Stevens et al.**

(10) **Pub. No.: US 2013/0176700 A1**

(43) **Pub. Date: Jul. 11, 2013**

(54) **ELECTRONIC DEVICES WITH INTERNAL  
MOISTURE RESISTANT COATINGS**

**Publication Classification**

(71) Applicants: **Blake Stevens**, Morristown, NJ (US);  
**Max Sorenson**, Cottonwood Heights,  
UT (US); **Alan Rae**, Wilson, NY (US);  
**Marc Chason**, Schaumburg, IL (US)

(51) **Int. Cl.**  
**H05K 1/18** (2006.01)  
**H05K 13/00** (2006.01)  
(52) **U.S. Cl.**  
CPC ..... **H05K 1/185** (2013.01); **H05K 13/0023**  
(2013.01)  
USPC ..... **361/760**; 29/592.1; 174/251

(72) Inventors: **Blake Stevens**, Morristown, NJ (US);  
**Max Sorenson**, Cottonwood Heights,  
UT (US); **Alan Rae**, Wilson, NY (US);  
**Marc Chason**, Schaumburg, IL (US)

(73) Assignee: **HZO, INC.**, Draper, UT (US)

(21) Appl. No.: **13/735,862**


(22) Filed: **Jan. 7, 2013**

**Related U.S. Application Data**

(60) Provisional application No. 61/584,929, filed on Jan.  
10, 2012.

(57) **ABSTRACT**

A moisture-resistant electronic device includes at least one electronic component at least partially covered by a moisture-resistant coating. The moisture-resistant coating may be located within an interior of the electronic device. The moisture-resistant coating may cover only portions of a boundary of an internal space within the electronic device. A moisture-resistant-coating may include one or more discernible boundaries, or seams, which may be located at or adjacent to locations where two or more components of the electronic device interface with each other. Assembly methods are also disclosed.








FIG. 4




FIG. 5




FIG. 6




FIG. 7

## ELECTRONIC DEVICES WITH INTERNAL MOISTURE RESISTANT COATINGS

### CROSS-REFERENCE TO RELATED APPLICATION

**[0001]** A claim for the benefit of priority under 35 U.S.C. §119(e) is hereby made to U.S. Provisional Patent Application No. 61/584,929, filed on Jan. 10, 2012 and titled ELECTRONIC DEVICES WITH INTERNAL WATER-RESISTANT COATINGS (“the ’929 Provisional Application”). The entire disclosure of the ’929 Provisional Application is hereby incorporated herein.

### TECHNICAL FIELD

**[0002]** This disclosure relates generally to electronic devices and, more specifically, to electronic devices with protective coatings. In some embodiments, the protective coatings may comprise coatings that are resistant to moisture, including liquids and vapors of a variety of materials, such as water, aqueous solutions and organic materials. In particular, this disclosure relates to electronic devices with internal protective coatings, including protective coatings on exterior surfaces of internally located electronic components.

### SUMMARY

**[0003]** An electronic device according to this disclosure includes at least one electronic component at least partially covered by a protective coating. The protective coating may comprise a coating that may protect an electronic device, its components or their features from potentially damaging conditions, including, but not limited to, exposure to moisture. This disclosure, in describing protective coatings, electronic devices that include protective coatings, and processes for applying protective coatings and assembling electronic devices, refers primarily to “moisture-resistant” coatings. The teachings of this disclosure are, however, also applicable to other types of protective coatings that may be useful on or in electronic devices.

**[0004]** The term “moisture-resistant” is used throughout this disclosure to refer to the ability of a coating to prevent exposure of a coated element or feature to moisture. A moisture-resistant coating may resist wetting or penetration by one or more types of moisture, or it may be impermeable or substantially impermeable to one or more types of moisture. A moisture-resistant coating may repel one or more types of moisture. In some embodiments, a moisture-resistant coating may be impermeable to, substantially impermeable or repel water, an aqueous solution (e.g., salt solutions, acidic solutions, basic solutions, drinks, etc.) or vapors of water or other aqueous materials (e.g., humidity, fogs, mists, etc.). Use of the term “moisture-resistant” to modify the term “coating” should not be considered to limit the scope of materials against which the coating protects one or more components of an electronic device. The term “moisture-resistant” may also refer to the ability of a coating to restrict permeation of or repel organic liquids or vapors (e.g., organic solvents, low molecular weight organic materials, electrically conductive organic materials, etc.), as well as a variety of other substances or conditions that might pose a threat to an electronic device or its components.

**[0005]** The moisture-resistant coating may be located at least partially within an interior of the electronic device, on a surface of an electronic component that resides within or is

otherwise exposed to (e.g., defines a boundary of, etc.) the interior of the electronic device. Accordingly, for purposes of this disclosure, a portion of the moisture-resistant coating that is exposed to (e.g., resides within, defines a boundary of, etc.) an interior of an electronic device is said to be “internally confined.” In some embodiments, all of the moisture-resistant coatings of an electronic device assembled in accordance with teachings of this disclosure may be internally confined. Stated another way, all of the moisture-resistant coatings of an electronic device may consist of moisture-resistant coatings that are internally confined within the electronic device.

**[0006]** An internally confined moisture-resistant coating may be positioned and/or configured to limit the exposure of one or more features of an electronic device to undesirable conditions. The moisture-resistant coating may comprise a conformal coating, with no gaps or substantially no gaps existing between the moisture-resistant coating and the surface(s) that the moisture-resistant coating covers. In some implementations, a moisture-resistant coating may cover electrically conductive features (e.g., intermediate conductive elements, such as leads, solder bonds and the like; terminals and exposed conductive traces on a circuit board; etc.), preventing their exposure to moisture and, thus, making them less likely to participate in electrical shorting that might otherwise be caused as moisture (e.g., water, an aqueous solution, water vapor, vapor of an aqueous solution, an electrically conductive organic liquid, etc.) within the interior of the electronic device extends between two or more electrically conductive elements. In addition, the water-resistant coating may prevent or eliminate corrosion that might otherwise detrimentally affect the performance of various features of the electronic device (e.g., electrically conductive features, moving features, etc.).

**[0007]** In a specific embodiment, a moisture-resistant coating may cover electrically conductive features that are exposed on the surface of a circuit board. Without limitation, the electrically conductive features of a circuit board that may be covered with a moisture-resistant coating include various conductive elements of the circuit board, including conductive traces, conductive vias, leads, terminals and other conductive pads.

**[0008]** In another specific embodiment, a moisture-resistant coating may cover an intermediate conductive element (e.g., a lead, a solder ball, etc.) and portions of components (e.g., a circuit board, a semiconductor device, an electronic part, etc.) that are adjacent to the ends of the intermediate conductive element to prevent exposure of those components to moisture and, thus, to protect those components from the various types of damage that may be caused by moisture. Since these elements may include features that are located at different elevations from one another, a moisture-resistant coating that at least partially covers these elements may include portions located at a plurality of different elevations. On a larger scale, and without limitation, a moisture-resistant coating may at least partially cover a plurality of assembled electronic components (e.g., semiconductor devices; discrete components, such as resistors, capacitors, inductors, diodes and the like; etc.) and intermediate conductive elements (e.g., leads, solder balls, etc.) extending from the electronic components and adjacent portions of a circuit board. Providing a moisture-resistant coating over the entire intermediate conductive element and portions of the structures located adjacent to ends of the intermediate conductive element prevents moisture (e.g., water, an aqueous solution, water vapor, vapor

of an aqueous solution, etc.) from contacting the intermediate conductive element. Limiting exposure of the intermediate conductive element to moisture reduces the likelihood that the intermediate conductive element will participate in electrical shorting that might otherwise be caused by the moisture, as well as the likelihood that various features of the electronic device (e.g., electrical features, moving parts, etc.) will corrode.

**[0009]** An electronic device may include a moisture-resistant coating over at least one pair of complementary electrical connectors that have been assembled with one another, or that engage each other. When applied to a pair of complementary, engaged electrical connectors, a moisture-resistant coating may prevent the introduction of moisture (e.g., water, an aqueous solution, water vapor, vapor of an aqueous solution, electrically conductive organic liquid, etc.) into a junction between the engaged electrical connectors and, thus, limit the exposure of contacts of the electrical connectors to moisture.

**[0010]** In some embodiments, combinations of features, and even combinations of electrically coupled assemblies may be coated.

**[0011]** A particular embodiment of an electronic device includes at least one component of a wireless power system (e.g., a receiver of an inductive charger, etc.). At least one internally confined surface of such a component, and, optionally, electrical connections to and/or from such a component, may be at least partially covered with a moisture-resistant coating. In some embodiments, such an electronic device may lack externally accessible contacts for physically coupling with cables or other wires.

**[0012]** A moisture-resistant coating within an electronic device may coat some interior components, or even portions of some interior components, without coating surfaces of other components. Some surfaces that are exposed to a particular internal space within an electronic device may be covered with a moisture-resistant coating while other surfaces exposed to the same internal space remain uncoated, or they may be exposed laterally beyond a periphery of the moisture-resistant coating. Thus, one or more moisture-resistant coatings may be selectively applied to components or portions of components within the interior of an electronic device. In some embodiments, such selectivity may be achieved by actively directing material toward selected regions of an electronic device assembly or its components or by passively applying a moisture-resistant coating to an entire surface of the electronic device assembly, then removing portions of the moisture-resistant coating from selected regions of electronic device assembly.

**[0013]** An electronic device may include a plurality of different types of moisture-resistant coatings. In such embodiments, the different moisture-resistant coatings may have one or more properties or characteristics that differ from one another. These may include, but are not limited to, physical features (e.g., dimensions, textures, etc.), chemical characteristics (e.g., different materials may be used to form different moisture resistant coatings, etc.), or other characteristics (e.g., transparency/opacity, thermal conductivity, etc.), which may or may not be defined by some other property of the moisture-resistant coating.

**[0014]** Of course, methods for applying moisture-resistant coatings to electronic devices and assembling electronic devices that include one or more moisture-resistant coatings on components or features thereof are also within the scope of the disclosed subject matter. Such a method may include

applying a first coating to at least a portion of a surface of a first component (which may comprise a subassembly) or feature of an electronic device, applying a second coating to at least a portion of a surface of a second component (which may comprise a subassembly) or feature of the electronic device, and after the first and second coatings have been applied, assembling the first component and the second component. When such a method is used, discernible boundaries, or seams, may be present between the moisture-resistant coatings on adjacent assembled components; for example, at an interface between the assembled components.

**[0015]** Other aspects, as well as features and advantages of various aspects, of the disclosed subject matter will become apparent to those of skill in the art through consideration of the ensuing description, the accompanying drawings and the appended claims.

## BRIEF DESCRIPTION OF THE DRAWINGS

**[0016]** In the drawings,

**[0017]** FIG. 1 is a schematic representation of an embodiment of an electronic device that includes at least one internal moisture-resistant coating;

**[0018]** FIGS. 2 through 4 illustrate different embodiments of the manner in which one or more moisture-resistant coatings may cover surfaces within the interior of an electronic device;

**[0019]** FIGS. 5 and 6 schematically illustrate embodiment of electronic assemblies with moisture-resistant coatings on at least some features thereof; and

**[0020]** FIG. 7 depicts an embodiment of an electronic device in which various components, including a display, a power source and a radiofrequency (RF) device, are at least partially covered with moisture-resistant coatings.

## DETAILED DESCRIPTION

**[0021]** FIG. 1 provides a schematic representation of an electronic device 10 with a housing 12 and other external components 14, such as the display 16 and various other user interface components 18 (e.g., speakers, microphones, headphone jacks, communication ports, buttons, etc.) that are shown in FIG. 1. The housing 12 defines at least a portion of an exterior 11 of the electronic device 10. Externally accessible portions of external components 14 may also define part of the exterior 11 of the electronic device.

**[0022]** Within an interior 21 of the electronic device 10 are various internal components 24, as well as internally located (relative to the exterior of the electronic device 10) surfaces 17, 19 of components that are also exposed to the exterior 11 of the electronic device (e.g., of the display 16 and other user interface components 18, respectively). The interior 21 of an electronic device 10 may include one or more internal spaces 22. The boundaries 23 of each internal space 22 may be defined by surfaces 25 of one or more internal components 24 and, optionally, by internally located surfaces 17 of the display 16, the internally located surfaces 19 of one or more other user interface components 18 and/or internal surfaces 13 of one or more elements of the housing 12.

**[0023]** At least one moisture-resistant coating 30 may reside within the interior 21 of the electronic device. One or more moisture-resistant coating 30 may line at least portions of the boundaries of at least one internal space 22 within the electronic device 10. Thus, a moisture-resistant coating 30 may reside on the surface 25 of one or more of the internal

components **24** of the electronic device **10**, on the internally located surface **17** of the display **16**, on the internally located surface **19** of at least one other user interface component **18** and/or on one or more internal surfaces **13** of at least one element of the housing **12**.

[0024] FIG. 1 illustrates an embodiment of electronic device **10** in which a moisture-resistant coating **30** covers all of the surfaces that define the boundaries **23** of an internal space **22**. In embodiments where the boundaries **23** of the internal space **22** are defined by surfaces of a plurality of different components (which may also comprise subassemblies), the moisture-resistant coating **30** may include a plurality of different sections **32** and **34** formed prior to assembling the components with one another. Thus, a discernible boundary **33**, or seam, may exist between different sections **32** and **34** of the moisture-resistant coating **30**, at or adjacent to an interface between the assembled components.

[0025] Alternatively, as depicted by FIG. 2, an electronic device **10'** may include at least one internal space **22'** in which only some portions **23<sub>C</sub>'** of the surfaces that define its boundaries **23'** may be lined with a moisture-resistant coating **30**, while other portions **23<sub>U</sub>'** of the surfaces that define the boundaries **23'** may remain uncoated.

[0026] Referring now to FIG. 3, another embodiment of electronic device **10''** includes different internal spaces **22<sub>A</sub>''** and **22<sub>B</sub>''** that are lined with moisture-resistant coatings **30<sub>A</sub>''** and **30<sub>B</sub>''**, respectively, which have different characteristics from one another. In some embodiments, the moisture-resistant coatings **30<sub>A</sub>''** and **30<sub>B</sub>''** may differ physically (e.g., in thickness, in surface texture, etc.) from each other. Some embodiments of moisture-resistant coatings **30<sub>A</sub>''** and **30<sub>B</sub>''** may have different chemical properties (e.g., include different materials, etc.) from one another. Other characteristics (e.g., transparency/opacity, thermal conductivity, etc.) may also distinguish moisture-resistant coatings **30<sub>A</sub>''** and **30<sub>B</sub>''** from each other. In any event, each moisture-resistant coating **30<sub>A</sub>''**, **30<sub>B</sub>''** may completely line the surfaces that define the boundaries **23''** of its respective internal space **22<sub>A</sub>''**, **22<sub>B</sub>''** (see FIG. 1) or it may only line some of the surfaces, or portions of one or more of the surfaces, that define the boundaries **23''** of its respective internal space **22<sub>A</sub>''**, **22<sub>B</sub>''**.

[0027] Moisture resistant coatings **30<sub>A</sub>''** and **30<sub>B</sub>''** that differ from one another may cover different regions of an electronic device assembly (e.g., different components of an electronic device assembly, etc.), as illustrated by FIG. 3.

[0028] Alternatively, or in addition, as depicted by FIG. 3A, two or more moisture resistant coatings **30<sub>A</sub>''** and **30<sub>B</sub>''** may be at least partially superimposed relative to one another to form a multi-layered moisture-resistant coating. The various layers of such a coating may be discrete from one another; i.e., there may be a discernible boundary between them. Alternatively, a transition region, or gradient, may exist between them. In a specific embodiment, a lower of the moisture-resistant coatings **30<sub>A</sub>''** may comprise a substantially confluent film (e.g., a polymer, such as a poly(p-xylylene) polymer; a ceramic material; etc.), while an outer moisture resistant coating **30<sub>B</sub>''** may have moisture repellant properties (e.g., include so-called "lotus leaf" nanostructures, which are known to repel water and other aqueous materials; be formed from a moisture repellant material, such as a fluorinated polymer; etc.).

[0029] FIG. 4 illustrates an embodiment of electronic device **10'''** in which different portions of the boundaries **23<sub>A</sub>'''** and **23<sub>B</sub>'''** at least one internal space **22'''** are lined with dif-

ferent types of moisture-resistant coatings **30<sub>A</sub>'''** and **30<sub>B</sub>'''**, respectively. In some embodiments the moisture-resistant coatings **30<sub>A</sub>'''** and **30<sub>B</sub>'''** may differ physically (e.g., in thickness, in surface texture, etc.) from each other. Some embodiments of moisture-resistant coatings **30<sub>A</sub>'''** and **30<sub>B</sub>'''** may have different chemical properties (e.g., include different materials, etc.) from one another. Other characteristics may also distinguish moisture-resistant coatings **30<sub>A</sub>'''** and **30<sub>B</sub>'''** from each other. In some embodiments of electronic devices **10'''** that include different types of moisture-resistant coatings **30<sub>A</sub>'''** and **30<sub>B</sub>'''** at different locations, the boundaries **23<sub>A</sub>'''** and **23<sub>B</sub>'''** of an internal space **22'''** of the electronic device **10'''** may be completely lined with the moisture-resistant coatings **30<sub>A</sub>'''** and **30<sub>B</sub>'''**, in a manner similar to that illustrated by FIG. 1. In other embodiments, the different types of moisture-resistant coatings **30<sub>A</sub>'''** and **30<sub>B</sub>'''** may, collectively, only line parts of the boundaries **23<sub>A</sub>'''** and **23<sub>B</sub>'''** of the internal space **22'''**, with at least some surfaces that define the boundaries **23<sub>A</sub>'''** and **23<sub>B</sub>'''** remaining uncoated, in a manner similar to that depicted by FIG. 2.

[0030] In some embodiments, such as that illustrated by FIG. 1, all of the moisture-resistant coatings **30** of an electronic device **10** may reside within its interior **21**; none of the moisture-resistant coatings **30** of such an electronic device **10** are present on its exterior **11**. Alternatively, as shown in FIG. 4, an electronic device **10'''** may include one or more moisture-resistant coatings **30** that extend onto its exterior **11**.

[0031] Turning now to FIGS. 5 and 6, specific features that may be covered and/or protected by a moisture-resistant coating **30** are shown.

[0032] FIGS. 5 and 6 illustrate moisture-resistant coatings **30** that cover a plurality of assembled electronic components. Specifically, the assembly **100** illustrated by FIG. 5 includes a circuit board **110**, one or more semiconductor devices **120** and one or more discrete components **130** (e.g., resistors, capacitors, inductors, diodes, etc.), as well as a plurality of intermediate conductive elements **122**, **132** (e.g., leads, solder structures, etc.). In some instances components **130** may be embedded in the circuit board **110**.

[0033] The circuit board **110** includes a number of conductive traces **112**, terminals **116** and, optionally, conductive vias **114**. The conductive traces **112** and optional conductive vias **114** are configured to convey electrical signals from one terminal **116a** to another terminal **116b** (each terminal **116a**, **116b** may also, for the sake of simplicity, be referred to herein as a "terminal **116**") of the circuit board **110**. One or more of these electrically conductive features of the circuit board **110** may be electrically exposed.

[0034] Each semiconductor device **120** and/or discrete component **130** may be physically carried by the circuit board **110**. An intermediate conductive element **122**, **132** may electrically couple circuitry of each semiconductor device **120** and/or discrete component **130** (including, e.g., contact pads, leads, etc., as the case may be) to an appropriate terminal **116** of the circuit board **110**.

[0035] In addition to the foregoing, the assembly **100** includes at least one moisture-resistant coating **30**. The moisture-resistant coating **30** may cover any of the electrically conductive features of the assembly **100** (e.g., the intermediate conductive elements **122**, **132**; one or more conductive traces **112**, conductive vias **114** and/or terminals **114** of the circuit board; one or more contact pads, leads, etc., of a semiconductor device **120** and/or discrete component **130**; etc.). By covering an electrically conductive feature, the

moisture-resistant coating may prevent electrically conductive forms of moisture (e.g., water, aqueous solutions, water vapor, vapor of an aqueous solution, an electrically conductive organic liquid or vapor, etc.) from providing a conductive path between that electrically conductive feature and any other electrically conductive feature of the assembly **100**.

**[0036]** As shown, in addition to covering one or more electrically conductive features of the assembly **100**, the moisture-resistant coating **30** may extend onto other features that are adjacent to the electrically conductive features. By way of example, and not by way of limitation, as FIG. **5** further illustrates, the moisture-resistant coating **30** may extend over a portion of the circuit board **110**, a semiconductor device **120** on the circuit board **110** and/or any discrete components **130** on the circuit board **110**. In some embodiments, the moisture-resistant coating **30** may substantially cover each semiconductor device **120** and discrete component **130** of the assembly, as well as portions of the circuit board **110** that are not covered by another device or that do not need to be exposed to enable further electrical coupling.

**[0037]** The assembly **100'** shown in FIG. **6** includes at least two circuit boards **110a** and **110b** with an electrical connector **105** extending therebetween. The electrical connector **105** includes one or more conductive elements that enable electrical signals to be communicated from one of the circuit boards **110a**, **110b** to the other circuit board **110b**, **110a**. Although the electrical connector **105** is depicted as being a flex-type connector with a plurality of conductive elements, as will be apparent to those of ordinary skill in the art, other types and configurations of electrical connectors may be used to establish electrical communication between the circuit boards **110a** and **110b**. Each of the circuit board **110a**, the electrical connector **105**, the circuit board **110b** and junctions **106a**, **106b** between the electrical connector **105** and each of the circuit boards **110a**, **110b** may be at least partially covered with one or more moisture-resistant coatings **30**.

**[0038]** FIG. **7** depicts an embodiment of electronic device **200** (e.g., a portable electronic device, such as a mobile telephone or a smart phone; a mobile computing device, such as a tablet computer, a portable digital assistant; another electronic device that wirelessly receives and/or transmits signals; an electronic device that is expected to be used in an environment where exposure to moisture is likely or even expected; or any other electronic device) that includes a number of components with internal surfaces that are at least partially covered with moisture-resistant coatings **30**. As illustrated, internal surfaces **212**, **222** and **232** of, and, optionally, electrical connections to and from, a display **210**, a radiofrequency (RF) device **220** (e.g., one or more antennas, etc.), and a power source **230** (e.g., a battery, supercapacitor, fuel cell, etc.), respectively, of the electronic device **200** may be at least partially, or even completely, covered with a moisture-resistant coating **30**. In embodiments where the electronic device **200** receives power wirelessly (e.g., by way of a wireless receiver, such as a receiver of an inductive charging system that communicates with the power supply **230**, etc.) (including devices that lack externally accessible contacts for receiving communication cables or other wires, etc.), a surface of any component of the wireless power supply system **240** within the electronic device **200** and, optionally, any electrical connections between that component and the power supply **230**, may be at least partially, or even completely (particularly since the wireless power supply system **240** lacks electrical contacts), covered with a moisture-resistant

coating **30**. Of course other features (e.g., stationary vibration devices, digital imaging devices, optical signals (e.g., light-emitting diode (LED) flashers), camera flashes, speakers, microphones, switches, ports, jacks, communication ports (e.g., USB connectors, specialized connectors, etc.), etc.) with an electronic device **200** may also be at least partially coated with moisture-resistant coatings **30**.

**[0039]** The thickness of a moisture-resistant coating **30** may be sufficient to inhibit the passage of moisture through the moisture-resistant coating **30** to the elements that the moisture-resistant coating **30** is intended to protect. The thickness of the moisture-resistant coating **30** may be tailored to provide a specific degree of moisture resistance, or protection. In some embodiments, a moisture-resistant coating **30** may have a substantially uniform thickness across its entire area. Alternatively, the thickness of the moisture-resistant coating **30** may vary from location to location. A moisture-resistant coating **30** may include relatively thick regions located over features that are susceptible to damage from moisture of the type(s) against which the moisture-resistant coating **30** is configured to protect, as well as relatively thin regions located over features that are less susceptible to being damaged by that (those) type(s) of moisture.

**[0040]** Any of a variety of metrics may be used to quantify the moisture-resistance of each coating formed by an assembly system. For example, the ability of a coating to physically inhibit one or more types of moisture from contacting a coated feature may be considered to impart the coating with moisture-resistance. As another example, the moisture-resistance of a coating may be based on more quantifiable data, such as the rate at which one or more types of moisture permeate through the coating. In embodiments where a coating is configured to limit the penetration of water or another aqueous material, the moisture-resistance of that coating may be quantified in terms of its water vapor transfer rate. The water vapor transfer rate of a coating may be measured using known techniques in units of g/m<sup>2</sup>/day or in units of g/100 in<sup>2</sup>/day (e.g., less than 2 g/100 in<sup>2</sup>/day, about 1.5 g/100 in<sup>2</sup>/day or less, about 1 g/100 in<sup>2</sup>/day or less, about 0.5 g/100 in<sup>2</sup>/day or less, about 0.25 g/100 in<sup>2</sup>/day or less, about 0.15 g/100 in<sup>2</sup>/day or less, etc., through a film having an average thickness of about 1 mil (i.e., about 25.4 μm), at a temperature of 37° and at a relative humidity of 90%).

**[0041]** Another way in which the moisture-resistance of a coating may be determined is by measuring the contact angle of liquid that has been applied to a surface of the coating by an acceptable technique (e.g., the static sessile drop method, the dynamic sessile drop method, etc.). Contact angles may be used to determine the ability of a coating to repel a certain type of moisture (e.g., due to the material from which the coating is made, due to the surface energy of the material from which the coating is made, due to a microstructure or nanostructure of a surface of the coating, etc.). In embodiments where a coating is configured to prevent exposure of one or more components of an electronic device to aqueous moisture, the hydrophobicity of the surface may be measured by determining the angle the base of a water droplet makes with the surface, from beneath a base of the water droplet; for example, using the Young equation, i.e.:

$$\theta_O = \arccos \frac{r_A \cos \theta_A + r_R \cos \theta_R}{r_A + r_R},$$

where  $\theta_A$  is the highest, or advancing, contact angle;  $\theta_R$  is the lowest, or receding, contact angle;

$$r_A = \sqrt[3]{\frac{\sin^3 \theta_A}{2 - 3\cos\theta_A + \cos^3\theta_A}}; \text{ and } r_R = \sqrt[3]{\frac{\sin^3 \theta_R}{2 - 3\cos\theta_R + \cos^3\theta_R}}.$$

If the surface is hydrophilic, the water will spread somewhat, forming a water contact angle of less than 90° with the surface. In contrast, a hydrophobic surface, which, for purposes of this disclosure, may be considered to be moisture-resistant, will prevent the water from spreading, resulting in a water contact angle of 90° or greater. The more the water beads on a surface, the greater the water contact angle. When water droplets bead on a surface such that the water contact angle with the surface is about 120° or more, the surface is considered to be highly hydrophobic. When the angle at which water contacts a surface exceeds 150° (i.e., a water droplet on the surface is nearly spherical), the surface is said to be "super-hydrophobic." Similar techniques may be used to determine the ability of a coating to repel or otherwise control exposure of one or more components of an electronic device to other types of moisture, such as liquid organic materials.

**[0042]** Moisture-resistant coatings formed of different types of parylene (e.g., parylene N, parylene C, etc.) and having thicknesses of from about one micron to about ten microns exhibit water contact angles of about 90° or more. More specifically, the water contact angles of these films ranged from 87° to 99°. Accordingly, these films may be referred to as "hydrophobic coatings."

**[0043]** Of course, other measures of moisture resistance may also be employed to determine the ability of a coating to resist moisture (e.g., by impermeability, repellency, etc.).

**[0044]** Any of a variety of suitable materials, techniques and apparatus may be used to apply a moisture-resistant coating 30 to at least a portion of a subassembly or an assembly of electronic components. Without limitation, a moisture-resistant coating 30 may be formed from reactive monomers, which monomers may then be deposited onto and form polymers on one or more surfaces that are to be made moisture-resistant or moisture proof (e.g., waterproof, etc.). In specific embodiments, poly(p-xylylene) (i.e., Parylene), including unsubstituted and/or substituted units, may be deposited onto one or more surfaces that are to be rendered moisture-resistant (e.g., water-resistant, waterproof, etc.). Examples of processes for forming parylene coatings are described by U.S. patent application Ser. Nos. 12/104,080, 12/104,152 and 12/988,103, the entire disclosure of each of which is, by this reference, hereby incorporated herein. U.S. patent application Ser. Nos. 12/446,999, 12/669,074 and 12/740,119, the entire disclosures of all of which are, by this reference, hereby incorporated herein, disclose other embodiments of materials, techniques and equipment that may be used to form a moisture-resistant coating 30.

**[0045]** Other materials may also be used to form a moisture-resistant coating 30. Materials that may be used to form a moisture-resistant coating 30 include, but are certainly not limited to, organic materials, halogenated materials, ceramics (e.g., aluminum oxide, etc.) and other materials that may be applied to an electronic device assembly or a component thereof to provide a relatively thin moisture barrier. Non-limiting examples of organic materials include thermoplastic materials, curable materials (e.g., radiation-curable materials, one-part materials, two-part materials, thermoset materi-

als, room-temperature curable materials, etc.). Some organic materials that are used to form moisture-resistant coatings 30 may be halogenated (e.g., fluorinated polymers, such as fluorinated silanes, etc.).

**[0046]** A variety of processes may be used to form the moisture-resistant coating 30. A process may be selected on the basis of its usefulness for applying a desired type of material to an electronic device assembly or a component thereof, and based on its compatibility with the component or the electronic device assembly to which the material is to be applied. Examples of processes for forming moisture-resistant coatings 30 include, without limitation, physical application processes (e.g., printing, spraying, dipping, rolling, brushing, etc.), chemical vapor deposition (CVD), plasma-based coating processes, atomic layer deposition (ALD), physical vapor deposition (PVD) (e.g., evaporation deposition processes (including, but not limited to e-beam evaporation, sputtering, laser ablation, pulsed laser deposition, etc.), vacuum deposition processes, sputtering, etc.). Of course, other techniques may also be used to form a moisture-resistant coating 30.

**[0047]** With returned reference to FIGS. 1 through 4, the absence of a moisture-resistant coating 30; 30<sub>A</sub>", 30<sub>B</sub>"; 30<sub>A</sub>", 30<sub>B</sub>" on any portion of the boundaries 23, 23', 23", 23'" of an internal space 22, 22', 22", 22'" or the presence of different types of moisture-resistant coatings 30<sub>A</sub>" and 30<sub>B</sub>", 30<sub>A</sub>" and 30<sub>B</sub>" on different internal surfaces in the same electronic device 10, 10', 10", 10"', 100, 200 may be achieved by separately coating different components and/or subassemblies of the electronic device 10, 10', 10", 10"', 100, 200 before assembling those components and/or subassemblies with one another.

**[0048]** Although the foregoing description contains many specifics, these should not be construed as limiting the scope of any of the appended claims, but merely as providing information pertinent to some specific embodiments that may fall within the scopes of the appended claims. Features from different embodiments may be employed in combination. In addition, other embodiments of the disclosed subject matter may also be devised which lie within the scopes of the appended claims. The scope of each claim is, therefore, indicated and limited only by its plain language and the legal equivalents to each of its elements. All additions, deletions and modifications to the disclosed subject matter that fall within the meanings and scopes of the claims are to be embraced by the claims.

What is claimed:

1. An electronic subassembly, comprising:

a circuit board;  
an electronic component assembled with the circuit board;  
an intermediate conductive element electrically coupling a conductive element of the circuit board with a conductive element of the electronic component; and  
a moisture-resistant coating over at least an exposed portion of the conductive element of the circuit board, the intermediate conductive element and an exposed portion of the conductive element of the electronic component, at a least portion of the electronic component being exposed laterally beyond a periphery of the moisture-resistant coating.

2. The electronic subassembly of claim 1, wherein a surface of the moisture-resistant coating has a water contact angle of about 90° or greater.

3. The electronic subassembly of claim 1, wherein the moisture-resistant coating comprises a conformal coating of at least one of an organic material, a halogenated organic material or a ceramic material.

4. The electronic subassembly of claim 1, wherein the moisture-resistant coating substantially covers and conforms to a surface of the circuit board, all electronic components carried by the surface of the circuit board and all intermediate conductive elements extending across the surface of the circuit board.

5. The electronic subassembly of claim 4, wherein the moisture-resistant coating has a substantially uniform thickness.

6. The electronic subassembly of claim 4, wherein the moisture-resistant coating includes:

first regions of a first thickness located over first features; and

second regions of a second thickness located over second features, the first thickness exceeding the second thickness, the first features being more susceptible to damage from moisture than the second features.

7. An electronic device, comprising:

an exterior surface;

at least one interior space including boundaries defined by a internal surfaces of a plurality of components of the electronic device; and

a moisture-resistant coating on only portions of the boundaries of the at least one internal space.

8. The electronic device of claim 7, wherein a surface of the moisture-resistant coating has a water contact angle of about 90° or greater.

9. The electronic device of claim 7, further comprising:

another moisture-resistant coating on other portions of the boundaries of the at least one internal space.

10. The electronic device of claim 9, wherein the moisture-resistant coating and the another moisture-resistant coating reside on surfaces of different components of the electronic device.

11. The electronic device of claim 9, wherein at least one discernible boundary separates the moisture-resistant coating from the another moisture-resistant coating.

12. The electronic device of claim 9, wherein the moisture-resistant coating and the another moisture-resistant coating resist moisture in different ways.

13. The electronic device of claim 9, wherein the moisture-resistant coating and the another moisture-resistant coating at least partially overlap one another.

14. The electronic device of claim 13, wherein at least one discernible boundary separates the moisture-resistant coating from the another moisture-resistant coating.

15. The electronic device of claim 13, wherein the moisture-resistant coating and the another moisture-resistant coating have different properties.

16. The electronic device of claim 13, wherein the moisture-resistant coating provides a moisture barrier and the another moisture-resistant coating repels moisture.

17. An electronic device, comprising:

an exterior surface;

at least one interior space including boundaries defined by a internal surfaces of a plurality of components of the electronic device; and

a moisture-resistant coating on the boundaries of the at least one internal space, the moisture-resistant coating

including at least one discernible boundary at an interface between two or more components of the electronic device.

18. The electronic device of claim 17, wherein a surface of the moisture-resistant coating has a water contact angle of about 90° or greater.

19. The electronic device of claim 17, wherein the moisture-resistant coating comprises sections on opposite sides of the at least one discernible boundary, the sections of the moisture-resistant coating comprising different materials from one another.

20. An electronic device, comprising:

a housing defining at least a portion of an interior of an electronic device and at least a portion of an exterior of the electronic device;

a power supply including at least one internal surface exposed to an interior of the electronic device;

a radiofrequency device within the interior of the electronic device and including at least one internal surface exposed to the interior of the electronic device; and

at least one moisture-resistant coating on at least a portion of the at least one internal surface of the power supply and the at least one internal surface of the radiofrequency device.

21. The electronic device of claim 20, wherein a surface of the moisture-resistant coating has a water contact angle of about 90° or greater.

22. The electronic device of claim 20, further comprising:

a display assembled within the housing and including at least one internal surface exposed to the interior of the electronic device, the at least one moisture-resistant coating also being located on at least a portion of the at least one internal surface of the display.

23. The electronic device of claim 20, wherein the at least one moisture-resistant coating also covers at least portions of electrical connections to and from at least one of the display, the power supply and the radiofrequency device.

24. The electronic device of claim 20, further comprising:

a wireless power system, at least a portion of which includes at least one internal surface exposed to an interior of the electronic device, the at least one moisture-resistant coating covering at least a portion of the at least one internal surface.

25. The electronic device of claim 24, lacking externally accessible contacts.

26. An electronic subassembly, comprising:

a circuit board;

an electronic component assembled with the circuit board; conductive elements on the circuit board electrically coupled with corresponding conductive elements of the electronic component; and

a moisture-resistant coating over at least exposed portions of at least some of the conductive elements of the circuit board and over at least a portion of the electronic component, at least a portion of the electronic component being exposed laterally beyond a periphery of the moisture-resistant coating.

27. A method for assembling an electronic device, comprising:

applying a first moisture-resistant coating to at least a portion of a surface of a first component of an electronic device;

applying a second moisture-resistant coating to at least a portion of a surface of a second component of the electronic device; and

after applying the first and second moisture-resistant coatings, assembling the first component and the second component.

**28.** The method of claim **27**, wherein applying the first moisture-resistant coating comprises applying a first moisture-resistant coating with a surface having a water contact angle of about 90° or greater.

**29.** The method of claim **27**, further comprising:

assembling a third component of the electronic device, which third component lacks a moisture-resistant coating, with at least one of the first component and the second component.

**30.** The method of claim **29**, wherein applying the first and second moisture-resistant coatings comprise applying the same material to the surfaces of the first and second components.

**31.** The method of claim **29**, wherein applying the first and second moisture-resistant coatings comprise applying different materials to the surfaces of the first and second components.

**32.** The method of claim **27**, wherein applying the first and second moisture-resistant coatings comprises applying conformal coatings to at least portions of surfaces of the first component and the second component of the electronic device.

\* \* \* \* \*