

## **Challenged Claims of U.S. Pat. No. 9,742,866**

15. A method for fetching a content over the Internet from a first server identified in the Internet by a second identifier via a group of multiple devices, each identified in the Internet by an associated group device identifier, the method comprising the step of partitioning the content into a plurality of content slices, each content slice containing at least part of the content, and identified using a content slice identifier, and for each of the content slices, comprising the steps of:

- (a) selecting a device from the group;
  - (b) sending over the Internet a first request to the selected device using the group device identifier of the selected device, the first request including the content slice identifier and the second identifier;
  - (c) in response to receiving the sent first request by the selected device, receiving over the Internet the content slice from the selected device; and
- wherein the method further comprising the step of constructing the content from the received plurality of content slices, and
- wherein each of the devices in the group is a client device.

16. The method according to claim 15, wherein the content is composed of bits, nibbles, bytes, characters, words, or strings, and the partitioning is based on bit, nibble, byte, multi-byte, number, character, word, or string level.

17. The method according to claim 15, wherein the content is composed of files, or programs, and the partitioning is based on file or program level.

18. The method according to claim 17, wherein the content is a website content comprising multiple webpages, and the partitioning is based webpages level.

19. The method according to claim 15, wherein all of the parts of the content are included in all of the content slices.

20. The method according to claim 15, wherein all of the content slices have the same size.

23. The method according to claim 15, wherein the partitioning is sequential in the content.

24. The method according to claim 15, wherein the partitioning is non-sequential in the content.

27. The method according to claim 15, wherein the number of content slices is higher than the number of devices in the group.

28. The method according to claim 15, wherein the number of content slices is lower than the number of devices in the group.