



US009097860B2

(12) **United States Patent**
Yu et al.

(10) **Patent No.:** **US 9,097,860 B2**
(45) **Date of Patent:** **Aug. 4, 2015**

(54) **LENS ASSEMBLY**

(56) **References Cited**

(71) Applicant: **ABILITY OPTO-ELECTRONICS TECHNOLOGY CO., LTD.**, Taichung (TW)

U.S. PATENT DOCUMENTS

(72) Inventors: **Hung-Kuo Yu**, Taichung (TW);
Chao-Hsiang Yang, Taichung (TW)

8,014,080	B1	9/2011	Chen et al.
8,189,272	B1 *	5/2012	Huang et al. 359/715
2011/0128615	A1	6/2011	Tsai
2012/0044403	A1	2/2012	Tang et al.
2012/0099009	A1	4/2012	Hsu et al.
2012/0140339	A1	6/2012	Huang et al.
2012/0250164	A1	10/2012	Tsai et al.
2013/0070347	A1	3/2013	Tang et al.

(73) Assignee: **Ability Opto-Electronics Technology Co., LTD.**, Taichung (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/141,665**

JP	2004102234	A	4/2004
JP	2007178089	A	7/2007
JP	2009192819	A	8/2009
TW	201215941	A1	4/2012

(22) Filed: **Dec. 27, 2013**

* cited by examiner

(65) **Prior Publication Data**

US 2015/0062724 A1 Mar. 5, 2015

Primary Examiner — James Jones

(74) Attorney, Agent, or Firm — LeClairRyan

(30) **Foreign Application Priority Data**

Sep. 2, 2013 (TW) 102131525

(57) **ABSTRACT**


(51) **Int. Cl.**
G02B 3/02 (2006.01)
G02B 9/34 (2006.01)
G02B 13/00 (2006.01)
G02B 13/04 (2006.01)

A lens assembly includes a lens set which includes a first lens, a second lens, a third lens and a fourth lens arranged in sequence along an optical axis. The first lens has a positive optical power. The second lens has a positive optical power. The third lens has a negative optical power. The fourth lens has a positive optical power, and has an image-side surface, an object-side surface, and a peripheral surface interconnecting the two. At least one of the object-side and image-side surfaces has an inflection point located between the optical axis and the peripheral surface. The lens assembly satisfies $15 < \text{HFOV}/f < 50$, in which, HFOV represents one half of a maximum angle of view of the lens assembly, and f represents a focal length thereof.

(52) **U.S. Cl.**
CPC **G02B 9/34** (2013.01); **G02B 13/004** (2013.01); **G02B 13/04** (2013.01)

(58) **Field of Classification Search**
CPC **G02B 13/0045**
USPC 359/715
See application file for complete search history.

7 Claims, 9 Drawing Sheets






FIG.1




FIG. 2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9

1

LENS ASSEMBLY

CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority of Taiwanese Application No. 102131525, filed on Sep. 2, 2013.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a lens assembly, more particularly to a compact wide-angle four-piece imaging lens assembly.

2. Description of the Related Art

A conventional imaging lens assembly is frequently adopted in an electronic product, such as a mobile phone, a smart phone, a tablet computer, a notebook computer, a camera and so forth. With the continuous improvement of electronic products, a tendency toward compact design while maintaining high performance of the electronic products is desired. Accordingly, an imaging lens assembly is also developed toward a trend of being compact and having thin dimensions. Meanwhile, for the purpose of raising resolving power, an imaging lens assembly is required to progress to have a wider angle of view.

Even though conventional imaging lens assemblies, such as the optical lens assemblies disclosed in Taiwanese Patent Application Publication Numbers 201215941, 201224568 and 201239443, are provided with four-piece lens frameworks, these imaging lens assemblies may not further satisfy a desire for compact design and a wider angle of view.

Accordingly, in order to enable an electronic device to achieve effects of both compact design and high performance, a wide-angle imaging lens assembly capable of improving resolving power thereof and having miniature dimensions is desired on the market.

SUMMARY OF THE INVENTION

Therefore, an object of the present invention is to provide a four-piece imaging lens assembly which has compact and thin dimensions and which has a wider angle of view for improving resolving power thereof.

Accordingly, a lens assembly of the present invention comprises a lens set and a non-adjustable diaphragm. The lens set includes a first lens, a second lens, a third lens and a fourth lens arranged in sequence from an object side to an image side along an optical axis of the lens assembly. The first lens has a positive optical power adjacent to the optical axis, and has a convex object-side surface which faces the object side, and an image-side surface which faces the image side. At least one of the object-side surface and the image-side surface of the first lens is an aspherical surface. The second lens has a positive optical power adjacent to the optical axis, and has a convex image-side surface which faces the image side, and an object-side surface which faces the object side. At least one of the object-side surface and the image-side surface of the second lens is an aspherical surface. The third lens has a negative optical power adjacent to the optical axis, and has a concave object-side surface which faces the object side, and a convex image-side surface which faces the image side. At least one of the object-side surface and the image-side surface of the third lens is an aspherical surface. The fourth lens has a positive optical power adjacent to the optical axis, and has an image-side surface which faces the image side and which has a concave portion around the optical axis, an object-side sur-

2

face which faces the object side, and a peripheral surface which interconnects the object-side surface and the image-side surface. Each of the object-side surface and the image-side surface of the fourth lens is an aspherical surface. At least one of the object-side surface and the image-side surface of the fourth lens has an inflection point located between the optical axis and the peripheral surface. The non-adjustable diaphragm is located between the object side and the second lens of the lens set. The lens assembly satisfies

$$15 < HFOV/f < 50,$$

in which, HFOV represents one half of a maximum angle of view of the lens assembly and has a unit of degree, and f represents a focal length of the lens assembly and has a unit of millimeter.

BRIEF DESCRIPTION OF THE DRAWINGS

Other features and advantages of the present invention will become apparent in the following detailed description of the three preferred embodiments with reference to the accompanying drawings, of which:

FIG. 1 is a schematic diagram illustrating a first preferred embodiment of a lens assembly according to the present invention;

FIG. 2 illustrates simulation results of astigmatism aberration and distortion aberration of the first preferred embodiment;

FIG. 3 illustrates simulation result of spherical aberration of the first preferred embodiment;

FIG. 4 is a schematic diagram illustrating a second preferred embodiment of a lens assembly according to the present invention;

FIG. 5 illustrates simulation results of astigmatism aberration and distortion aberration of the second preferred embodiment;

FIG. 6 illustrates simulation result of spherical aberration of the second preferred embodiment;

FIG. 7 is a schematic diagram illustrating a third preferred embodiment of a lens assembly according to the present invention;

FIG. 8 illustrates simulation results of astigmatism aberration and distortion aberration of the third preferred embodiment; and

FIG. 9 illustrates simulation result of spherical aberration of the third preferred embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIG. 1, a first preferred embodiment of a lens assembly, according to the present invention, comprises a lens set 1, a non-adjustable diaphragm 2, and a filter lens 3.

The lens set 1 includes a first lens 11, a second lens 12, a third lens 13 and a fourth lens 14 arranged in sequence from an object side to an image side along an optical axis L of the lens assembly. The first lens 11 has a positive optical power adjacent to the optical axis L, and has a convex object-side surface 111 which faces the object side, and an image-side surface 112 which faces the image side. At least one of the object-side surface 111 and the image-side surface 112 of the first lens 11 is an aspherical surface. The second lens 12 has a positive optical power adjacent to the optical axis L, and has a convex image-side surface 121 which faces the image side, and an object-side surface 122 which faces the object side. At least one of the object-side surface 121 and the image-side

3

surface **122** of the second lens **12** is an aspherical surface. The third lens **13** has a negative optical power adjacent to the optical axis L, and has a concave object-side surface **131** which faces the object side, and a convex image-side surface **132** which faces the image side. At least one of the object-side surface **131** and the image-side surface **132** of the third lens **13** is an aspherical surface. The fourth lens **14** has a positive optical power adjacent to the optical axis L, and has an image-side surface **141** which faces the image side and which has a concave portion around the optical axis L, an object-side surface **142** which faces the object side, and a peripheral surface **143** which interconnects the object-side surface **141** and the image-side surface **142**. Each of the object-side surface **141** and the image-side surface **142** of the fourth lens **14** is an aspherical surface. At least one of the object-side surface **141** and the image-side surface **142** of the fourth lens **14** has an inflection point located between the optical axis L and the peripheral surface **143**.

The non-adjustable diaphragm **2** is located between the object side and the second lens **12** of the lens set **1**.

The lens assembly satisfies the following conditions:

$$15 < HFOV/f < 50, \quad (1)$$

$$0.8 < |f/f_3| < 2.5, \quad (2)$$

$$0.3 < ct_1/ct_2 < 2.0, \text{ and} \quad (3)$$

$$0 < ct_3/ct_4 < 1.0, \quad (4)$$

in which, HFOV represents one half of a maximum angle of view of the lens assembly and has a unit of degree, f represents a focal length of the lens assembly and has a unit of millimeter, f₃ is a focal length of the third lens **13** and has a unit of millimeter, ct₁ represents a center thickness of the first lens **11**, ct₂ represents a center thickness of the second lens **12**, ct₃ represents a center thickness of the third lens **13**, ct₄ represents a center thickness of the fourth lens **14**, and each of ct₁, ct₂, ct₃ and ct₄ has a unit of millimeter.

Preferably, the lens assembly of the present invention further satisfies the following conditions:

$$HFOV > 35^\circ, \text{ and} \quad (5)$$

$$f < 2.7 \text{ mm}. \quad (6)$$

The condition (1) explicates that a higher value of HFOV represents a wider angle of view of the lens assembly of the present invention so as to increase the resolving power thereof, while a lower value of the focal length f enables a more compact lens assembly. Conditions (5) and (6) further explicate advantages of the wider angle of view and the compact and thin dimensions of the lens assembly of the present invention.

It is noted that the lens assembly of the present invention further satisfies the following conditions:

4

$$Nd_3 > 1.56, \quad (7)$$

$$V_3 < 29, \quad (8)$$

$$Nd_2 < 1.56, \quad (9)$$

$$V_2 > 29, \quad (10)$$

in which, Nd₃ is a refractive index of the third lens **13** for light with a wavelength equal to 587 nanometers, V₃ is a coefficient of dispersion of the third lens **13** for light with a wavelength equal to 587 nanometers, Nd₂ is a refractive index of the second lens **12** for light with a wavelength equal to 587 nanometers, and V₂ is a coefficient of dispersion of the second lens **12** for light with a wavelength equal to 587 nanometers. Conditions (7) to (10) explicate that an absolute value of the optical power of the third lens **13** is greater than an absolute value of the optical power of the second lens **12** of the present invention.

Moreover, the aspherical surfaces of the lens assembly of the present invention satisfy:

$$z = \frac{ch^2}{1 + [1 - (k + 1)c^2h^2]^{0.5}} + Ah^4 + Bh^6 + Ch^8 + Dh^{10} + Eh^{12} + Fh^{14} + Gh^{16} + Hh^{18} + Jh^{20} + \dots$$

in which, z is a displacement, along the optical axis L, of the aspherical surface from a vertex of the aspherical surface at a distance h from the optical axis L, c is a reciprocal of the radius of curvature, k is the conic constant, and A, B, C, D, E, F, G, H, J and so forth are aspheric coefficients. Surface profiles of the aspherical surfaces are able to correct aberrations, reduce tolerance sensitivity and provide a wide-angle capability.

First Preferred Embodiment

Referring to FIG. 1 to FIG. 3, parameters of the first preferred embodiment of the lens assembly are summarized as follows: f₁=2.19 mm, f₂=2.05 mm, f₃=-1.16 mm, f₄=1.52 mm, f=1.60 mm, ct₁=0.284 mm, ct₂=0.368 mm, ct₃=0.190 mm, ct₄=0.472 mm, HFOV=44°.

The first preferred embodiment of the lens assembly satisfies condition (1) to condition (11), where: HFOV/f=27.5, |f/f₃|=1.38, ct₁/ct₂=0.77, ct₃/ct₄=0.40, Nd₂=1.535, Nd₃=1.636, V₂=56.07, V₃=23.89.

FIG. 2 illustrates astigmatism aberration and distortion aberration of the first preferred embodiment. FIG. 3 illustrates spherical aberration of the first preferred embodiment. Table 1 below shows the parameters of components of the first preferred embodiment, in which the filter lens **3** has an object-side surface **31** and an image-side surface **32**.

TABLE 1

First preferred embodiment					
Component/ Surface	Radius of curvature	Thickness/ Interspace	Refractive index	Abbe number	Focal length (mm)
Non-adjustable diaphragm 2	∞	-0.03			
First lens 11					
Object-side surface 111	1.361	0.284	1.535	56.07	2.19
Image-side surface 112	-8.119	0.194			

TABLE I-continued

First preferred embodiment						
Component/ Surface		Radius of curvature	Thickness/ Interspace	Refractive index	Abbe number	Focal length (mm)
Second lens 12	Object-side surface 121	-2.042	0.368	1.535	56.07	2.05
	Image-side surface 122	-0.760	0.159			
Third lens 13	Object-side surface 131	-0.289	0.190	1.636	23.89	-1.16
	Image-side surface 132	-0.596	0.038			
Fourth lens 14	Object-side surface 141	0.488	0.472	1.535	56.07	1.52
	Image-side surface 142	0.805	0.25			
Filter lens 3	Object-side surface 31	∞	0.21	1.517	64.17	
	Image-side surface 32	∞	0.332			

Coefficients for the aspherical surfaces of the first preferred embodiment are provided in Table 2 below.

TABLE 2

	First lens 11		Second lens 12	
	Object-side surface 111	Image-side surface 112	Object-side surface 121	Image-side surface 122
k	0	0	6.191788	-3.784132
A	-0.2065838	-0.7720604	-1.4905075	-1.1446487
B	-3.3390093	1.4937038	13.548352	-13.499105
C	45.617387	-48.87327	-222.85883	142.67618
D	-568.5172	417.56966	1762.543	-811.19607
E	3836.6411	-1866.3668	-7503.2608	2964.6502
F	-14300.609	3693.0414	17228.893	-6161.6996
G	22470.012	-1072.5651	-16174.808	5342.7346
	Third lens 13		Fourth lens 14	
	Object-side surface 131	Image-side surface 132	Object-side surface 141	Image-side surface 142
k	-3.838175	-1.077898	-7.06691	-2.241616
A	-4.9202522	-0.5217609	0.10412867	-0.3678477
B	18.914991	0.96784978	-1.6835431	0.10715581
C	-20.771041	12.065814	4.2811759	0.31062561
D	12.125511	-36.497597	-6.3438122	-0.5323217
E	-142.85927	22.957229	5.6351203	0.37789525
F	243.02698	33.940443	-2.7711759	-0.1331061
G	30.761799	-33.635537	0.58039414	0.018683511

Second Preferred Embodiment

Referring to FIG. 4 to FIG. 6, parameters of a second preferred embodiment of the lens assembly, according to the present invention, are summarized as follows: $f_1=2.39$ mm, $f_2=2.08$ mm, $f_3=-1.45$ mm, $f_4=1.85$ mm, $f=1.60$ mm, $ct_1=0.276$ mm, $ct_2=0.392$ mm, $ct_3=0.204$ mm, $ct_4=0.450$ mm, HFOV=44°, and are further tabulated in Table 3.

The second preferred embodiment of the lens assembly satisfies condition (1) to condition (11), where: HFOV/ $f=27.5$, $|f/f_3|=1.10$, $ct_1/ct_2=0.70$, $ct_3/ct_4=0.45$, $Nd_2=1.535$, $Nd_3=1.636$, $V_2=56.07$, $V_3=23.89$.

FIG. 5 illustrates astigmatism aberration and distortion aberration of the second preferred embodiment. FIG. 6 illustrates spherical aberration of the second preferred embodiment.

TABLE 3

Second preferred embodiment						
Component/ Surface		Radius of curvature	Thickness/ Interspace	Refractive index	Abbe number	Focal length (mm)
First lens 11	Object-side surface 111	1.172	0.276	1.535	56.07	2.39

TABLE 3-continued

Second preferred embodiment					
Component/ Surface	Radius of curvature	Thickness/ Interspace	Refractive index	Abbe number	Focal length (mm)
Image-side surface 112	12.524	0.002			
Non-adjustable diaphragm 2	∞	0.193			
Second lens 12	Object-side surface 121	-2.352	0.392	1.535	56.07
	Image-side surface 122	-0.800	0.165		2.08
Third lens 13	Object-side surface 131	-0.295	0.204	1.636	23.89
	Image-side surface 132	-0.550	0.022		-1.45
Fourth lens 14	Object-side surface 141	0.526	0.450	1.535	56.07
	Image-side surface 142	0.786	0.25		1.85
Filter lens 3	Object-side surface 31	∞	0.21	1.517	64.17
	Image-side surface 32	∞	0.352		

Coefficients for the aspherical surfaces of the second preferred embodiment are provided in the following Table 4.

TABLE 4

	First lens 11		Second lens 12	
	Object-side surface 111	Image-side surface 112	Object-side surface 121	Image-side surface 122
k	-27.67006	0	0	-0.1133277
A	1.9885098	-0.37701082	-0.96274237	-0.00025411
B	-16.754161	-0.49422655	2.5787486	-13.638266
C	121.87784	-25.697915	-75.20593	119.14826
D	-697.96568	372.82808	563.02784	-775.83633
E	2523.3236	-3090.4143	-2537.022	3121.5568
F	-5159.4588	12641.669	4107.643	-6765.6192
G	4272.9124	-20091.048	1821.596	6044.1686
	Third lens 13		Fourth lens 14	
	Object-side Surface 131	Image-side surface 132	Object-side Surface 141	Image-side surface 142
k	-3.670904	-1.681659	-7.045281	-3.872049
A	-3.9824733	-0.37652375	0.000309204	-0.15744128

TABLE 4-continued

B	9.3522783	-3.5402459	-1.3786241	-0.21216838
C	-14.277191	22.786238	3.9107049	0.6311134
D	58.628841	-34.875393	-6.1155891	-0.74118053
E	13.198369	-6.5038799	5.4923776	0.45196807
F	-631.1631	60.790568	-2.6266688	-0.14266076
G	956.17439	-37.919506	0.51902791	0.01825282

Third Preferred Embodiment

Referring to FIG. 7 to FIG. 9, parameters of a third preferred embodiment of the lens assembly, according to the present invention, are summarized as follows: $f_1=2.55$ mm, $f_2=0.86$ mm, $f_3=-0.61$ mm, $f_4=0.98$ mm, $f=1.13$ mm, $ct_1=0.239$ mm, $ct_2=0.266$ mm, $ct_3=0.187$ mm, $ct_4=0.429$ mm, HFOV=44°, and are further tabulated in Table 5.

The third preferred embodiment of the lens assembly satisfies condition (1) to condition (11), where: HFOV/ $f=39.0$, $|f/f_3|=1.85$, $ct_1/ct_2=0.90$, $ct_3/ct_4=0.44$, $Nd_2=1.535$, $Nd_3=1.636$, $V_2=56.07$, $V_3=23.89$.

FIG. 8 illustrates astigmatism aberration and distortion aberration of the third preferred embodiment. FIG. 9 illustrates spherical aberration of the third preferred embodiment.

TABLE 5

Third preferred embodiment					
Component/ Surface	Radius of curvature	Thickness/ Interspace	Refractive index	Abbe number	Focal length (mm)
Non-adjustable diaphragm 2	∞	-0.001			
First lens 11	Object-side surface 111	1.903	0.239	1.535	56.07
	Image-side surface 112	-4.616	0.062		2.55
Second lens 12	Object-side surface 121	3.029	0.266	1.535	56.07
	Image-side surface 122	-0.528	0.095		0.86
Third lens 13	Object-side surface 131	-0.184	0.187	1.636	23.89
	Image-side surface 132	-0.483	0.092		-0.61

TABLE 5-continued

Third preferred embodiment						
Component/ Surface	Radius of curvature	Thickness/ Interspace	Refractive index	Abbe number	Focal length (mm)	
Fourth lens 14	Object-side surface 141	0.430	0.429	1.535	56.07	0.98
	Image-side surface 142	1.549	0.125			
Filter lens 3	Object-side surface 31	∞	0.210	1.517	64.17	
	Image-side surface 32	∞	0.325			

15
Coefficients for the aspherical surfaces of the third preferred embodiment are provided in the following Table 6.

TABLE 6

First lens 11		Second lens 12	
Object-side surface 111	Image-side surface 112	Object-side Surface 121	Image-side surface 122
k	8.58328	-2824.922	42.97767
A	-1.2031657	-9.8439198	-7.1130345
B	12.223278	116.10956	4.0234552
C	-1918.3111	-1775.4567	-507.43521
D	6722.3948	-15124.178	-7707.7496
E	2123163.2	652775.39	80989.53
F	-52922573	-5158083.1	1130631.4
G	3.7786e+008	11596365	-8089358.7
			3411687.3
Third lens 13		Fourth lens 14	
Object-side Surface 131	Image-side surface 132	Object-side Surface 141	Image-side surface 142
k	-1.926854	-0.3569793	-5.810289
A	-4.0319876	-0.15762397	-0.05755995
B	-130.00916	8.7724173	-1.4813813
C	3983.5728	116.23539	9.9370396
D	-22497.967	-218.09901	-60.63752
E	-103474.15	-4855.6445	190.69088
F	1277642.5	24221.919	-287.85565
G	-3002346	-32489.178	163.69987
			-8.006268

To sum up, the effects of the present invention may be summarized as follows:

1. A feature of the present invention resides in that the lens assembly satisfies $15 < \text{HFOV}/f < 50$. Moreover, the lens assembly also satisfies condition (1) to condition (11) so as to increase the resolving power of the lens assembly, increase angle of view thereof, and reduce a thickness thereof to achieve a compact design.

2. A higher value of HFOV of the lens assembly represents a wider angle of view of the lens assembly so as to increase the resolving power thereof.

3. A lower value of the focal length f of the lens assembly enables smaller and thinner dimensions thereof.

Therefore, the lens assembly of the present invention may have compact and thin dimensions while exhibiting high performances.

While the present invention has been described in connection with what are considered the most practical and preferred embodiments, it is understood that this invention is not limited to the disclosed embodiments but is intended to cover various arrangements included within the spirit and scope of the broadest interpretation so as to encompass all such modifications and equivalent arrangements.

What is claimed is:

1. A lens assembly comprising:

a lens set which includes a first lens, a second lens, a third lens and a fourth lens arranged in sequence from an object side to an image side along an optical axis of said lens assembly, wherein

said first lens has a positive optical power adjacent to the optical axis, and has a convex object-side surface which faces the object side, and an image-side surface which faces the image side, at least one of said object-side surface and said image-side surface of said first lens being an aspherical surface,

said second lens has a positive optical power adjacent to the optical axis, and has a convex image-side surface which faces the image side, and a concave object-side surface which faces the object side, at least one of said object-side surface and said image-side surface of said second lens being an aspherical surface,

said third lens has a negative optical power adjacent to the optical axis, and has a concave object-side surface which faces the object side, and a convex image-side surface which faces the image side, at least one of said object-side surface and said image-side surface of said third lens being an aspherical surface,

11

said fourth lens has a positive optical power adjacent to the optical axis, and has an image-side surface which faces the image side and which has a concave portion around the optical axis, an object-side surface which faces the object side, and a peripheral surface which interconnects said object-side surface and said image-side surface, each of said object-side surface and said image-side surface of said fourth lens being an aspherical surface, at least one of said object-side surface and said image-side surface of said fourth lens having an inflection point located between the optical axis and said peripheral surface; and
 a non-adjustable diaphragm located between the object side and said second lens of said lens set;
 wherein said lens assembly satisfies

$$15 < HFOV/f < 50,$$

in which, HFOV represents one half of a maximum angle of view of said lens assembly and has a unit of degree, and f represents a focal length of said lens assembly and has a unit of millimeter.

2. The lens assembly as claimed in claim 1, further satisfying:

$$HFOV > 41^\circ.$$

3. The lens assembly as claimed in claim 1, further satisfying:

$$f < 2.7 \text{ mm},$$

$$f/f_4 > 0.54$$

in which, f_4 is a focal length of said fourth lens and has a unit of millimeter.

12

4. The lens assembly as claimed in claim 1, further satisfying:

$$Nd3 > 1.56, \text{ and}$$

$$V3 < 29,$$

in which, Nd3 is a refractive index of said third lens for light with a wavelength equal to 587 nanometers, and V3 is a coefficient of dispersion of said third lens for light with a wavelength equal to 587 nanometers.

5. The lens assembly as claimed in claim 4, further satisfying:

$$Nd2 < 1.56, \text{ and}$$

$$V2 > 29,$$

in which, Nd2 is a refractive index of said second lens for light with a wavelength equal to 587 nanometers, and V2 is a coefficient of dispersion of said second lens for light with a wavelength equal to 587 nanometers.

6. The lens assembly as claimed in claim 1, further satisfying:

$$0.8 < |f/f_3| < 2.5,$$

in which, f_3 is a focal length of said third lens and has a unit of millimeter.

7. The lens assembly as claimed in claim 1, further satisfying:

$$0.67 < ct1/ct2 < 2.0, \text{ and}$$

$$0 < ct3/ct4 < 1.0,$$

in which, ct1 represents a center thickness of said first lens, ct2 represents a center thickness of said second lens, ct3 represents a center thickness of said third lens, ct4 represents a center thickness of said fourth lens, and each of ct1, ct2, ct3 and ct4 has a unit of millimeter.

* * * * *