



US006151643A

**United States Patent** [19]  
**Cheng et al.**

[11] **Patent Number:** **6,151,643**  
[45] **Date of Patent:** **\*Nov. 21, 2000**

[54] **AUTOMATIC UPDATING OF DIVERSE SOFTWARE PRODUCTS ON MULTIPLE CLIENT COMPUTER SYSTEMS BY DOWNLOADING SCANNING APPLICATION TO CLIENT COMPUTER AND GENERATING SOFTWARE LIST ON CLIENT COMPUTER**

OTHER PUBLICATIONS

Bolte, Cray Computer Corp, "ftpget script", Jun. 1993.  
Anderson, P., "Towards a High-Level Machine Configuration System", 1994 Large Installation Systems Administration, pp. 19-26, Sep., 1994, San Diego, California.

(List continued on next page.)

[75] Inventors: **William Cheng**, San Gabriel; **Kenneth Hwang**, Los Angeles; **Ravi Kannan**, Los Angeles; **Babu Katchapalayam**, Los Angeles; **Bing Liu**, Alhambra; **Balaji Narasimhan**, Culver City; **Gopal Ramanujam**, Los Angeles; **Jonathan Tran**, Alhambra, all of Calif.

*Primary Examiner*—Thomas C. Lee  
*Assistant Examiner*—Rehana Perveen

[73] Assignee: **Networks Associates, Inc.**, Santa Clara, Calif.

[57] **ABSTRACT**

[\*] Notice: This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

A system and method update client computers of various end users with software updates for software products installed on the client computers, the software products manufactured by diverse, unrelated software vendors. The system includes a service provider computer system, a number of client computers and software vendor computer systems communicating on a common network. The service provider computer system stores in an update database information about the software updates of the diverse software vendors, identifying the software products for which software updates are available, their location on the network at the various software vendor computer systems, information for identifying in the client computers the software products stored thereon, and information for determining for such products, which have software updates available. Users of the client computers connect to the service provider computer and obtain a current version of portions of the database. The client computer determines that software products stored thereon, and using this information, determines from the database, which products have updates available, based on product name and release information for the installed products. The user selects updates for installation. The selected updates are downloaded from the software vendor computer systems and installed on the client computer. Payment for the software update and the service is mediated by the service provider computer. Authentication of the user ensures only registered users obtain software updates. Authentication of the software updates ensures that the software updates are virus free and uncorrupted. Changes to the client computer during installation are monitored and archived, allowing the updates to be subsequently removed by the user.

[21] Appl. No.: **08/660,488**  
[22] Filed: **Jun. 7, 1996**

[51] **Int. Cl.<sup>7</sup>** ..... **G06F 13/14; G06F 13/20**  
[52] **U.S. Cl.** ..... **710/36; 709/200; 709/206; 709/220; 709/224; 714/25**  
[58] **Field of Search** ..... 395/200.3, 200.36, 395/200.5, 200.54, 610, 614, 183.01, 616, 712; 709/200, 206, 220, 224, 36, 25

[56] **References Cited**

**U.S. PATENT DOCUMENTS**


4,558,413	12/1985	Schmidt et al.	364/300
4,584,641	4/1986	Guglielmino	364/200
4,646,229	2/1987	Boyle	364/200
4,674,055	6/1987	Ogaki et al.	364/479

(List continued on next page.)

**FOREIGN PATENT DOCUMENTS**

2291228	1/1996	United Kingdom	G06F 17/30
---------	--------	----------------	------------

**44 Claims, 25 Drawing Sheets**



4,796,181	1/1989	Wiedemer .....	364/406
5,008,814	4/1991	Mathur .....	364/200
5,155,847	10/1992	Kirouac et al. ....	395/600
5,263,164	11/1993	Kannady et al. ....	395/700
5,321,750	6/1994	Nadan .....	380/20
5,359,730	10/1994	Marron .....	395/650
5,386,369	1/1995	Christiano .....	364/464.01
5,434,999	7/1995	Goire et al. ....	395/575
5,450,589	9/1995	Maebayashi et al. ....	395/700
5,457,795	10/1995	Willman .....	395/600
5,459,506	10/1995	Bushnell .....	348/7
5,473,772	12/1995	Halliwell et al. ....	395/650
5,483,586	1/1996	Sussman .....	379/201
5,495,610	2/1996	Shing et al. ....	395/600
5,499,357	3/1996	Sonty et al. ....	395/500
5,528,490	6/1996	Hill .....	364/403
5,564,051	10/1996	Halliwell et al. ....	395/600
5,577,244	11/1996	Killebrew et al. ....	395/703
5,579,537	11/1996	Takahisa .....	455/66
5,581,764	12/1996	Fitzgerald et al. ....	395/703
5,600,834	2/1997	Howard .....	395/617
5,604,542	2/1997	Dedrick .....	348/552
5,625,818	4/1997	Zarmer et al. ....	395/615
5,630,116	5/1997	Takaya et al. ....	395/617
5,678,002	10/1997	Fawcett et al. ....	395/183.01
5,682,533	10/1997	Siljestroemer .....	395/616
5,694,546	12/1997	Reisman .....	395/200.9
5,694,596	12/1997	Campbell .....	395/610
5,761,499	6/1998	Sonderegger .....	395/610

## OTHER PUBLICATIONS

Anderson, P., "Managing Program Binaries in a Heterogeneous UNIX Network", Large Installation Systems Administration V, pp. 1-9, Sep./Oct., 1991, San Diego, California.

Cheng, H.S. and Sheu, J.P., "Design and Implementation of a Distributed File System", Software—Practice and Experience, vol. 2, No. 7, pp. 657-675, Jul., 1991.

Daniels, D. and Spector, A.Z., "An Algorithm for Replicated Directories", 2<sup>nd</sup> PODC Conference Proceedings, ACM, 1983.

Eirich, T., "Beam: A Tool for Flexible Software Update", 1994 Large Installation Systems Administration, pp. 75-82, Sep., 1994, San Diego, California.

Fuchs, W.K., Wu, K.L. and Abraham, J.A., "Low-Cost Comparison and Diagnosis of Large Remotely Located Files", Fifth Symposium on Reliability in Distributed Software and Database Systems, IEEE Computer Society, pp. 67-73, Jan., 1986, Los Angeles, California.

Gopal, I. And Segall, A., "Directories for Networks with Casually Connected Users", Computer Networks and ISDN Systems 18, pp. 255-262, 1989-1990, North Holland.

Grosse, E., "Repository Mirroring", ACM Transactions on Mathematical Software, vol. 21, No. 1, pp. 89-97, Mar., 1995.

Harlander, M., "Central System Administration in a Heterogeneous Unix Environment: GeNUAdmin", 1994 Large Installation Systems Administration, pp. 1-8, Sep., 1994, San Diego, California.

Hideyo, I., "OMNICONF—Making OS Upgrades and Disk Crash Recovery Easier", 1994 Large Installation Systems Administration, pp. 27-31, Sep., 1994, San Diego, California.

Howard, J.H., "Using Reconciliation to Share Files Between Occasionally Connected Computers", Fourth Workshop on Workstation Operating Systems, pp. 56-60, Oct., 1993, Napa, California.

Jia, X., Nakano, H., Shimizu, K., Maekawa, M., "Highly Concurrent Directory Management in the GALAXY Distributed System", 10<sup>th</sup> International Conference on Distributed Computing Systems, pp. 416-423, May/Jun., 1990, Paris, France.

Osel, P.W. and Gansheimer, W., "OpenDist—Incremental Software Distribution", LISA IX, pp. 181-193, Sep., 1995, Monterey, California.

Rich, K. and Leadley, S., "hobgoblin: A File and Directory Auditor", Large Installation Systems Administration V, pp. 199-207, Sep./Oct., 1991, San Diego, California.

Rouillard, J.P. and Martin, R.B., "Config: A Mechanism for Installing and Tracking System Configurations", 1994 Large Installation Systems Administration, pp. 9-17, Sep., 1994, San Diego, California.

Sarin, S., Floyd, R. and Phadnis, N., "A Flexible Algorithm for Replicated Directory Management", 9<sup>th</sup> International Conference on Distributed Computing System, pp. 456-464, Jun., 1989, Newport Beach, California.

Satdeva, B. and Moriarty, P.M., "Fdist: A Domain Based File Distribution System for a Heterogeneous Environment", Large Installation Systems Administration V, pp. 109-125, Sep./Oct., 1991, San Diego, California.

Sellens, J., "Software Maintenance in a Campus Environment: The Xhier Approach", Large Installation Systems Administration V, pp. 21-28, Sep./Oct., 1991, San Diego, California.

Wong, W.C., "Local Disk Depot—Customizing the Software Environment", 1993 Large Installation Systems Administration, pp. 51-55, Nov., 1993, Monterey, California.




FIG. 1




FIG. 2

300

CyberMedia Oil Change - Registration

Since this is your first time using Oil Change, please take the time to fill out the following information.

301 Name: Lorne Steiner

303 Password: \*\*\*\*\* Please Verify: \*\*\*\*\*

305 Company: CyberMedia, Inc.

Phone: 310-581-4700 Fax: 310-581-4700

Street Add: 3000 Ocean Park Blvd.

2nd Add: Suite 2001

City: Santa Monica State: CA

Country: United States ZipCode: 90405-2345

307 E-Mail: lsteiner@cybermedia.com


309 ☐ Notify me by E-Mail when Updates are Available

311 Credit Information

Type: Visa

Number: 0101 0101 0101 0101

Expiration: 12/96



Click Send to Continue

Send

Help

Cancel

FIG. 3




FIG. 4




FIG. 5





FIG. 6



**FIG. 7**




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12



**FIG. 13**

**CyberMedia®**

1300



Welcome to the *Oil Change* Software Update Page!

---

**DESCRIBE THE UPDATE**

*Please provide a brief description of this update:*

1301

*If available, provide URL where additional information regarding this update would be available*

1303

*What is the new version number?*

1305

*What is the new version number?*

*Which product does this update affect?*

*(If you are listing multiple products, please separate product names with a comma)*

1307

Oil Change allows you to choose one of four different updates:

- A Replacement Update affects a specific version already on the PC.
- A Cumulative Update does not require an existing version on the PC.
- A Point Update installs components without changing the version number.
- An Incremental Update only modifies certain portions of a specific version.

*Which type of update is this?*

1309

*Please list any known incompatibilities*

1311

**FIG. 13a**



SPECIFY WHEN THIS UPDATE IS APPLICABLE

In order to verify that the current product/version is updated, *Oil Change* provides a series of filters for use in establishing additional file criteria. If necessary, you may select one or more of these filters:

☐ LOCATE PREVIOUS VERSION OF THE FILE

Check here if you want the program to scan the full system for previous versions

What is the name of the file?

1313



Where is the file located?

Which version should *Oil Change* look for?

If you selected Specific Version,  
enter version to be verified:

If you selected Multiple Versions,  
enter the version numbers:   
(for multiple versions, enter the version numbers separated by a comma, i.e. 1.01, 1.02, etc.)

If you selected Version Range,  
enter versions in the range From:  To:   
(If searching for all subsequent versions, enter INFINITE in the To: field)

☐ CHECK DATE OF PREVIOUSLY INSTALLED FILE

Select this option if you would like the program to scan the system for the dates of previous versions

Enter name of file

1315



Where is the file located?

Which date should *Oil Change* look for?

FIG. 13b

If you chose a Specific Date,  
enter date here (mm/dd/yy)

If you selected Latest Date or Date Range, specify the range  
(inclusive) to be checked From:  To:   
(to search for any date prior to the To: field, specify 00/00/00 in the From: field)

---

☐ CHECK REGISTRY

Select this option if you would like the program to check the registry for product information

What is the MajorKey in the Registry?

HKEY\_CLASSES\_ROOT

1317

What is the MinorKey in the Registry?  
(i.e. System\CurrentControlSet\Control\MediaResources)

What is the Registry SubKey?  
(Enter \* If all SubKeys may be used)

What is the Registry SubKey Value Name?  
(Name of the value in the SubKey, e.g. Installer, driver, etc.)

What is the Registry SubKey Value Type?

SpecificVersion

If you selected Specific Version,  
enter the version number

If you selected Version Range,  
enter versions in the range From:  To:   
(If searching for all subsequent versions, enter INFINITE in the To: field)

If you selected Specific Date,  
enter date here (mm/dd/yy)

If you selected Date Range,  
enter range here From:  To:   
(to search for any date prior to the To: field, specify 00/00/00 in the From: field)

If you selected Specific String,  
how should the strings be compared?

Compare String-CASE SENSITIVE

FIG. 13c

Enter the full Registry String

(enter the identifying string your product creates in the Windows Registry)

WHERE CAN THE UPDATE BE DOWNLOADED FROM?

Enter the URL of the site where the file is available  
for download (If there are multiple files, use a comma to separate the URLs)

 1319

What file format is being used?

 1321

☐ Check here if you would like CyberMedia to store your update  
on our local FTP site.

Tell us how to install your product

Specify the installation steps in the order they are to be performed. Please note that some actions will  
require additional input. Once you have made a selection from the list box, follow the instructions noted  
on the list entry.

#### INSTALLATION-STEP 1

Select one:

A-SOURCE/FILE NAME

B-SOURCE DIRECTORY NAME

C-DEST. DIRECTORY NAME

D-COMMAND LINE PARAMETERS (optional)

1323

#### INSTALLATION-STEP 2

Select one:

A-SOURCE/FILE NAME

B-SOURCE DIRECTORY NAME

C-DEST. DIRECTORY NAME

D-COMMAND LINE PARAMETERS (optional)

#### INSTALLATION-STEP 3

Select one:

A-SOURCE/FILE NAME

B-SOURCE DIRECTORY NAME

C-DEST. DIRECTORY NAME

D-COMMAND LINE PARAMETERS (optional)

FIG. 13d

INSTALLATION-STEP 4

Select one:

A-SOURCE/FILE NAME <input type="text"/>	B-SOURCE DIRECTORY NAME <input type="text" value="RootDirectory(C:\)"/>
C-DEST. DIRECTORY NAME <input type="text" value="RootDirectory(C:\)"/>	D-COMMAND LINE PARAMETERS (optional) <input type="text"/>

[Return to Product Registration page](#)

[Return to Press Kit](#)

We welcome your [comments and suggestions](#)

©Copyright CyberMedia, Inc 1996. All Rights Reserved.

FIG. 13e




FIG. 14




FIG. 15





FIG. 16



**FIG. 17**

**CyberMedia®**

1700



Welcome to *Oil Change* Product Registration!

This is an example of the product registration form to be used for *Oil Change*. We welcome your comments and suggestions.

---

PRODUCT INFORMATION

Company Name:

1701

Product Name:

1703

What type of product is this?

DeviceDriver ☐

1705

How do you uniquely identify this product on a system?

SignatureFile ☐

1707

Identifying file name or character string:

1709

---

If you would like *Oil Change* to use additional product verification filters, please select one or more of the following:

Check Version

Check File Date

Check Registry Entry

Check for Directory

---

☐ CHECK VERSION

Select this option if you would like the program to scan the system for previous versions

FIG. 17a



What is the name of the file?

1709



Where is the file located?

Check for which version?

If you selected Specific Version,  
which version should we verify?

If you selected Multiple Versions,  
enter the version numbers:

(for multiple versions, enter the version numbers separated by a comma, i.e. 1.01, 1.02, etc.)

If you selected Version Range,

enter versions in the range

From: To: 

(If searching for all subsequent versions, enter INFINITE in the To: field)

---

☐ CHECK FILE DATE

Select this option if you would like the program to scan the system for the dates of previous versions

What is the name of the file?

1711



Where is this file located?

Which date should Oil Change check for?

If you choose a Specific Date,

enter date here

(mm/dd/yy)

If you selected Latest Date, what range

will the date fall between?

From: To: 

(to search for any date prior to the To: field, specify 00/00/00 in the From: field)

---

FIG. 17b

If you selected Version Range, enter versions

in the range From:  To:

(If searching for all subsequent versions, enter INFINITE in the To: field)

If you selected Specific Date,

enter date here (mm/dd/yy)

If you selected Date Range,

enter range here From:  To:

(to search for any date prior to the To: field, specify 00/00/00 in the From: field)

If you selected Specific String,  
how should the strings be compared?

Enter the full Registry String

(enter the identifying string your product creates in the Windows Registry)

---

☐ CHECK FOR EXISTING DIRECTORY

Select this option if you would like the program to scan for an existing directory

If you selected Version Range, enter versions

in the range From:  To:

(If searching for all subsequent versions, enter INFINITE in the To: field)

If you selected Specific Date,

enter date here (mm/dd/yy)

If you selected Date Range,

enter range here From:  To:

(to search for any date prior to the To: field, specify 00/00/00 in the From: field)

If you selected Specific String,  
how should the strings be compared?

Enter the full Registry String

(enter the identifying string your product creates in the Windows Registry)

---

☐ CHECK FOR EXISTING DIRECTORY

Select this option if you would like the program to scan for an existing directory

1713



FIG. 17c

Which directory name should be verified?

Where is the directory located?

---

*(Note: If you have multiple programs using the same information, you must submit a separate verification form for each. After submitting the initial form, use your browser's "back" button to return to this page, then click "Clear Entry" to reset the form. You may then enter new data for additional products.)*

[View the Update Registration page](#)

[Return to Press Kit](#)

We welcome your [comments and suggestions](#)

©Copyright CyberMedia, Inc 1996. All Rights Reserved.

FIG. 17d

**AUTOMATIC UPDATING OF DIVERSE  
SOFTWARE PRODUCTS ON MULTIPLE  
CLIENT COMPUTER SYSTEMS BY  
DOWNLOADING SCANNING APPLICATION  
TO CLIENT COMPUTER AND GENERATING  
SOFTWARE LIST ON CLIENT COMPUTER**

**BACKGROUND**

**1. Field of Invention**

The present invention relates to systems and methods for computer-based customer support, and more particularly, to systems, methods, and products for automatically updating software products from diverse software vendors on a plurality of end-user, client computer systems.

**2. Background of Invention**

The typical personal computer contains various categories of software products, such as operating system files, utilities, applications, and device drivers, code libraries, and other forms of computer readable or executable information. In some of these categories, such as applications, the personal computer may contain numerous programs in various sub-categories. For example, a user may have one or two word processing applications, several graphics applications, and numerous games. Most of these products will come from different software vendors. As used herein "software vendors" includes any entity that distributes software products, even if the entity also manufactures or distributes hardware or other non-software products. These software vendors frequently improve their products, by adding new features, or by fixing known problems, and make these software updates available to their users. These updates may or may not be free.

There are at least three significant problems that the vendors and users face in attempting to provide these updates to the user. First, vendors face difficulty and costs in attempting to inform users of their products that the updates are available, and users experience similar difficulties in attempting to ascertain what updates are available. Vendors typically send out mailings to registered users, place advertisements in relevant trade journals and magazines, and engage in other promotional activities.

For all of these efforts, many users may remain unaware of the many software updates applicable to their systems until they encounter problems and contact the vendors' technical support organizations. Other users only learn about updates by searching the Internet or on-line services for solutions to their technical problems. Just the sheer magnitude of the problem of updating all software products can be overwhelming. Given that a user will have many software products from numerous vendors on her computer, it would be nearly impossible for the user to frequently monitor all of the available distribution channels, journals, Internet forums, and the like, to determine for which of the many software products there are updates available.

For example, some vendors maintain sites on the World Wide Web, or electronic bulletin boards (BBS's) that include information about current updates and products, and enable a user to download such updates. However, such sites are obviously dedicated to a single software vendor, and provide information only about that software vendor's products, and certainly not about the products of numerous other vendors that may be of interest to a given user. Thus, the user would have to search the Internet, and possibly online services, to determine which vendors have such sites. The user would likely to have visit each of these sites individually and determine what software updates are available from each of

them. Similarly, even though some on-line services include forums or other mechanisms where users can learn about available updates, this still places the burden on the user to actively seek out this information. Directories or search engines on the Internet, such as Excite, Yahoo, Lycos, or Infoseek merely provide links to software vendor sites, but do not generally attempt to systematically determine which software updates are available, and provide this information to the user, let alone actually update the software on the user's machine.

Another problem is that even once an update has been identified, there is the need to install it in the user's computer. Many users purchase the software updates by mail order, or the like, and receive them on floppy diskettes. Other users may download the software updates via Internet from the computers of the software vendors, or from on-line services. In any of these cases installing a single update can be a tedious, time-consuming and error-prone process for many users due to the various formats and installation procedures required. Installing updates for all of the numerous software products on a user's system on a regular basis would be even more difficult and time consuming for the typical user.

Finally, many users have concerns about their privacy, and are often resistant to revealing complete information about their software configurations to one or more vendors. However, even for a single vendor, information about which of the vendor's products are installed on a user's computer system, and system configuration information is necessary for determining which updates are applicable to the user's computer system. For example, a certain software update to an accounting program from vendor A might be applicable if the user has a printer from vendor B, and a different software update is applicable if the printer comes from vendor C. The user might not want to let each vendor know about all the components on their system, but this configuration information is necessary to ensure the correct software updated is installed. Still, users are resistant to the prospect of a single vendor storing information profiling the software components that reside on their computer systems.

In summary, from the perspective of an individual vendor, the problems are identifying and notifying every user of the vendor's software of the availability of updates to the software on a timely and useful basis, and ensuring that the proper software updates are installed. From the perspective of the individual user, the problems are systematically and easily identifying which updates are currently available for every piece of software on her system, and resolving the technical difficulties in obtaining and installing such updates.

Accordingly, it is desirable to provide a system that automatically determines which software updates from numerous diverse software vendors are currently available, and which are applicable to a given user's computer system, and installs such user selected ones of such updates on the user's computer. Further, it is desirable to provide such a system without abridging the privacy of users by obtaining and storing system profile information.

**SUMMARY OF THE INVENTION**

In accordance with one aspect of the present invention, there is provided a system and method that automatically updates software components from numerous diverse software vendors on the computer systems of a plurality of end users. The system includes at least one database that stores software update information for a plurality of software

products manufactured by diverse software vendors. The database is maintained by a service provider on a service provider computer system. Alternatively, the database may be maintained by a set of software vendors of the software products in association with the service provider. The software update information in the database specifies the software update program or files and their network location on the computer system of the software vendors, which computer systems are connected over the network to the service provider computer system. The database further stores information that describes an installation process for installing the software update on a user's computer.

In the preferred embodiment the network is the Internet to which the diverse software vendor computer systems are connected, and make available updates for their software. The network location provided in the software update information is specified by one or more universal resource locators (URL). Thus, the update database does not store the software updates themselves, but information that is used to access the software from computer systems of the original vendors. In addition, the software update information includes a format description associated with specific installation programs or actions needed to install the software update.

On each user computer, or synonymously client computer, operating in accordance with one embodiment of the invention there is provided a client application that periodically connects over the network to the update database of the service provider computer system. The client application automatically downloads a portion of the database to the client computer, preferably to update a mirror of portions of database. From client database, the client application determines which software updates are applicable or relevant to the user's computer. This is preferably done by first determining the products that are installed in the client computer, and determining for each of these whether there is an update available for a more recent version of the software product than that installed on the client computer. The applicable software updates are identified to the user.

The user selects various software updates for installing on the client computer. Either the client application or the service provider computer then uses the network location specified in the database to connect to the computer system of the software vendor and download the software update from there to the client computer. The client application uses the format information to determine the appropriate installation process associated with the software update, and installs the software update using the proper installation process. During the installation process, the client application monitors all changes made to the client computer, such as the deletion, addition, or alteration of files or directories. The client application stores the state of the client computer prior to these changes. This may be done by saving copies of files to be altered or deleted, and noting pathnames of files or directories to be added. Once the installation is complete the stored state information, such as the copied files, is compressed and archived, and identified as being associated with the just installed software update. This stored state information allows the client application to "undo" the installation and restore the client computer to its state prior to the installation, including restoring any files that were deleted or altered. Multiple "undos" of multiple installations may be accomplished.

Where the vendor charges for the software update, the service provider computer may intermediate between the software vendor's computer and the client computer to enable an electronic payment by the user to the software

vendor. When the electronic payment is authorized, the client application downloads the software update and completes the installation as described. Additionally, the service provider computer may authenticate the software update and check to ensure that it is not corrupted, for example by computer viruses.

The service provider periodically updates the update database, monitoring URL information to ensure that it correctly identifies the location of software updates, identifies new software updates, or new products for inclusion in the database, and the like.

The above system allows numerous users to periodically and automatically update the software products on their computers from diverse software vendors through a single, update mechanism. The users need not invest the time and energy to identify currently available updates, nor engage in the potentially difficult process of manually (even electronically) obtaining and installing the software updates, and properly configuring their computer systems. Rather, all of the relevant information about the currently available updates is maintained for subscribing users in the service provider's database. Further, the above system provides these benefits without directly storing the software updates themselves, which would be undesirable for the service provider due to vast memory requirements needed for handling software updates from hundreds, or potentially thousands of software vendors, and the difficulty of ensuring that all such software updates were current.

As a further aspect of the invention, the update database stores promotional information for various software products in addition to the software update information. The promotional information includes product literature, advertising literature, technical information, product demonstration software and the like. This information is categorized into a number of product categories. Like the software update information, the promotional information itself is not stored in the update database, but rather, a network location is stored for each item of promotional information.

The client application determines on the client computer the product categories of the software products therein, and then selects promotional information from certain product categories, and retrieves this promotional information from the network location information associated with it. This enables the client application to direct promotional information to the client computer based on the software products thereon, and hence the user's likely product interests, without 1) storing large quantities of promotional information directly; and 2) disclosing the actual contents of the user computer to third parties.

The update database of software update information is preferably maintained by a supplier of the client application, who also maintains the service of providing software updates. This database is created by engaging with numerous software vendors to provide information for software updates of their products to the service provider. Preferably, the software vendors provide the service provider information describing the software update, including version information, file formats, configuration information, and network location.

Alternatively, software updates may be identified by systematically and periodically searching the Internet to identify the software vendors who are providing updates to their software products. These updates are then downloaded from the software vendor's Internet sites, and one or more network locations (URL) are identified for obtaining the download. The downloaded software update is then installed on

one or more target computers as typically configured by end users. The format of the software update is determined, along with the network location of the software update, and other descriptive information, such specific configuration actions to be taken during installation of the software update, useful descriptive text, and the like.

In another aspect of the present invention there is provided a client application that interacts with the update database. The client application is provided on each of a plurality of client computers. The client application is executed on a periodic basis and connects to a update database as described above to perform the operations of downloading the portions of the database, determining the relevant software updates to be retrieved, retrieving same from their network locations, installing the software updates on the client computer, and removing installed updates if desired.

In yet another aspect of the present invention, information about software updates or software products may be provided by the service provider to a client computer by email, upon request for email notification by a user. Users who subscribe to the service provider's service indicate the software products in which they are interested, either directly, or indirectly by their actions in using the service. As new software updates, or software products become available, the service providers determines which one match a particular user's interests, and notifies the user of such updates or products by email. The notification includes the network location of where the software product or software update is available. The user can then approve the installation of the product or update, and use the client application to download and install the software update or product.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an illustration of a system for providing software updates in accordance with the present invention.

FIG. 2 is a flowchart of the overall method for providing software updates to a client computer in accordance with the present invention.

FIG. 3 is an illustration of a user interface for registering a new user of the updating service.

FIG. 4 is an illustration of a user interface for selecting software updates for installation.

FIG. 5 is an illustration of a user interface for confirming installation of a software update.

FIG. 6 is an illustration of a user interface for undoing an installation of a software update.

FIG. 7 is an illustration of software architecture of the service provider computer system.

FIG. 8 is one embodiment of a schema for the update database of the service provider computer.

FIG. 9 is an illustration of the software architecture of an client computer.

FIG. 10 is a flowchart of further details of analyzing the client computer, determining software updates, and displaying update information.

FIG. 11 is a flowchart of the operation of the install monitor.

FIG. 12 is a flowchart of the operation of the URL monitor.

FIG. 13a-13e are illustrations of a user interface for registering a software update into the update database.

FIG. 14 is one embodiment of a schema for the user profile database.

FIG. 15 is one embodiment of a schema for the advertising information database.

FIG. 16 is a flowchart of the operation of the recovery module.

FIG. 17a-17d are illustrations of a user interface for registration a software product into the update database.

#### DETAILED DESCRIPTION OF THE INVENTION

##### System Architecture

Referring now to FIG. 1, there is shown the architecture of one embodiment of a system for updating diverse software products on user's computers in accordance with the present invention. In system 100, there are a plurality of client computers 101 communicatively coupled by a network 106 to a service provider computer 102. A number of software vendor computers 103 are also communicatively coupled over the network 106 to the service provider computer 102. The network 106 is preferably the Internet, or other similar wide area network.

Each client computer 101 is operated by an end user, and typically has a number of software products installed thereon, such as applications, drivers, utilities and the like. In accordance with the present invention, the client computers 101 includes a client application 104 that communicates with the service provider computer 102 to obtain software updates of software products installed on the client computer 101. The software architecture of a client computer 101 and client application 104 is further described below with respect to FIG. 7.

Each software vendor computer 103 coupled to the service provider computer 102 stores software update information, software products, information files, and the like. The software update information includes applications, binary files, text files, and the like, for updating software products installed on client computers 101, and advertising or other information about such products useful to users for evaluating potential software for updating. Other types of information useful to providing product support, technical service, or the like may also be beneficially provided. In addition, the software vendor computers 103 provide mechanisms for controlling distribution and payment of software updates, such as credit card payment front ends, code authentication and verification subsystems, and the like. These various mechanisms are understood in the art. For example, payment mechanisms may be implemented in compliance with various credit card or debit systems, as known in the art. Likewise, authentication and verification may be implemented using conventional encryption techniques.

In a preferred embodiment, the network 106 is the Internet, and more specifically, the World Wide Web portion thereof. The various computers thereby support the protocols for FTP, and HTTP, and provide for the display and rendering of HTML, VRML, or other text or interface description languages. Each computer 101, 102, 103 has a IP address that specifies its location on the network 106, thereby allowing such computers to communicate with each other in a conventional manner. Files, such as executables, binaries, and text files are identified within the various computers by universal resource locators (URLs) as known in the art.

##### Overall System Operation

Referring now to FIG. 2, there is shown an overall flow diagram of the process of updating a single client computer 101 in accordance with the present invention. The process here is described with respect to a single client computer

**101.** Given the client-server nature of the system, those of skill in the art understand that numerous other individual client computers **101** may interact with the service provider computer **102** in parallel.

The update process **200** is typically initiated on the client computer **101**. The user may manually initiate the process, or it may occur automatically, for example at preset periods, such as once a month. Alternatively, the process may be initiated by the service provider computer **102** prompting the client computer **101** at various intervals, or in response to particular events.

In each case, the user logs in **201** to the service provider computer **102** with the client application **104** in a conventional manner, providing a user ID, a password, and the like. This information may be manually entered by the user via the client application **104**, or more preferably, stored within the client application **104**, and automatically provided once a connection between the client computer **101** and service provider computer **102** is established. If the user is not registered, then the service provider computer **102** in conjunction with inputs by the user, registers **202** the new user of the system. FIG. 3 illustrates a basic user interface **300** for registering the user. The user identifies himself or herself by name **301** and selects a password **303**. The user may also provide a mailing address **305** and a payment mechanism such as a credit card data **311**, including a credit card number and expiration date, to pay for the services and for any for-fee software updates that the user may access in the course of using the service provided by the service provider computer **102**. An email address **307** is entered to allow the service provider to contact the user by email. The user may select check box **309** to indicate that they want to be notified by email when new software updates are available for software products installed on their computer. When the registration process **202** is completed, the service provider computer **102** returns a unique registration number to the user. This number may be stored on the client computer **101** and used during subsequent logins to identify the user to the service provider computer **102**.

The registered users are authenticated **203** by the service provider computer **102**, using conventional authentication mechanisms, such one or more passwords, digital signature, certificates, or the like. Authentication ensures that only users who are properly authorized by the service provider can obtain updates for software products.

The client application **104** then analyzes **204** the client computer **101** to determine a list of installed software products. The list of installed software products typically includes applications, system utilities, drivers, and other executables or resources. These software products will typically be from numerous diverse software vendors, a number of whom will maintain software vendor computers **103** on the network **106**.

For each of the installed software products on the list, the client application **104** determines **205** if there is an applicable, or relevant update for the software product. This determination is made in consultation with the service provider computer **102**, which maintains, as further described below, a database including a list of available software updates for numerous software products of diverse software vendors.

The client application **104** displays **206** the list of applicable software updates to the user, for review and selection thereof of updates for purchase and installation. FIG. 4 illustrates a sample user interface display **400** of applicable software updates. This display **400** includes the name **401** of each software product identified on the client computer **101**,

and remarks **403** displayed next to the name indicating whether the software product is already up-to-date, that is, there are no applicable updates, or, if the product is not current, the list of applicable updates (which may be for the software product itself, or for related products). In those cases where there is an applicable update, the remarks **403** briefly indicate the nature of the software update. In the example of FIG. 4, the remarks **403** for the software product Quicken 5.0® by Intuit Inc., indicates a update to provide new features. The user may obtain additional information by selecting a name or remark of a particular software product. The selected product name and remark is highlighted, as shown in FIG. 4, and the information about the software update is displayed **207** in an information window **405**. This information may be stored in the service provider computer **101**, or obtained directly from the software vendor computers **103** as needed using URLs associated with such information. The user may limit the list to only those software products that need updating, rather than all installed software products, by selecting check box **407**.

The user may select one or more software products to update. To update one of the software products, the user selects the software product for update by selecting (e.g. double-clicking) the line including the software product, or by single clicking on the line, and then clicking the retrieve button **409**. The user may select more than one software update by holding the control key on the keyboard down while single-clicking on the name of each desired software update, followed by selecting the retrieve button **409**. When all the desired updates have been selected, the user may click on the continue button **411** to begin the installation process.

For each selected software update, the client application **104** performs an installation process **208**. Referring to FIG. 5, the client application **104** displays information **505** for a selected software update, and provides the user the opportunity to confirm **501** or cancel **503** the installation. If confirmed, the client application **104** downloads **209** the software update, along with installation information, such as installation programs, files, and the like. This downloading may be directly from the software vendor computer **103**, using the URL data stored in the service provider computer **102** for the location of the software update on the network **106**.

In conjunction with the downloading process **209**, a payment transaction **210** may be conducted whereby the user of the client computer **101** pays for the software update if it is not a free update. The service provider computer **102** may intermediate in this transaction, or merely initiate the transaction by connecting the client application **104** to the computer **103** of the software vendor of the update. If payment information, such as credit card numbers, are stored in the client application **104**, then this information may be provided by the client application **104** to the software vendor computer **103**.

Once the download and applicable payment are complete, the software update is physically installed on the client computer **101**. Each software update is associated with information that describes the particulars for the installation, such as configuration, decompression or other information. The installation is performed in conformance with such information.

In the preferred embodiment, the client application **104** executes **211** an install monitor prior to actually installing the software update. The install monitor, as further described below, records the changes made to the client computer **101** as a result of the installation of the software update. This information is archived by the install monitor and allows the

user to “undo” or remove any number of installations, and restore the client computer **101** to its state prior to each such installation. Accordingly, the client application **104** performs **212** the installation, executing any necessary decompression, installation, or setup applications necessary to install the software update. During the installation process **212** the install monitor records **213** any changes made to the system configuration, including changes to various configuration files, additions or deletions of files, and additions or deletions of directories. The changes may be recorded in a variety of manners, such as building descriptions of the modifications of the files, or alternatively, storing copies of files prior to their alteration or deletion. Once the installation is complete, the install monitor archives **214** the changes. This process **208** is repeated for each software update to be installed.

Once all of the software updates have been installed, the client applications **104** logs out **215** of the service provider computer **102**, and any necessary payment information for the user may be updated, such as payment based on the number of software updates purchased, the online connection time, and the like. Alternatively, no payment may need to be directly made, as the cost of the service may be included in the cost of the software update charged by the software vendor, who then pays the service provider for the service of coordinating and linking end users to the software vendor’s computer system **103**.

At some subsequent point, the user may decide to undo a previous installation, for example, due to dissatisfaction with the software product. The user may use a recovery feature of the client application **104** to undo **216** the installation. A sample user interface **600** for the recovery function is illustrated in FIG. 6. The user interface **600** includes a field **601** indicating the previous update to be removed as selected by the user, along with an information window **603** describing the software update. The user confirms the removal of the software update by selecting the undo button **605**, or may cancel with cancel button **607**. The recovery function deletes the files installed for the software update, and using the archived information created by the install monitor during the installation of the product, restores the client computer system **101** to its configuration immediately before the installation of the product. This process **216** includes deleting files and directories that were added, restoring files and directories that were deleted, and restoring files that were otherwise changed. In one preferred embodiment, the recovery function is able to undo any installation in a given series of installations, accounting for changes to the configuration of the client computer **101** after a particular installation. In another preferred embodiment, the recovery function undoes installations in the reverse order of their installation. If any payments were originally required from the user for the cost of the software update and the associated service of downloading and installing it, the payments may be credited back to the user when the user undoes the installation.

#### Service Provider Computer

Referring now to FIG. 7, there is shown one embodiment of the service provider computer **102** in accordance with the present invention. In terms of hardware architecture, the service provider computer **102** is conventional server type computer, preferably supporting a relatively large number of multiple clients simultaneously for requests for data and other processing operations. The service provider computer **102** includes one or more conventional processors in a processor core **723**, and a suitable amount of addressable memory **700**, preferably on the order of 18–64 Mb. The service provider computer **102** may be implemented with an

Intel-based computer including one or more Pentium® processors, or other more powerful computer, such as various models of Sun Microsystems’ SparcStations using UltraSparc® processors. The service provider computer **102** executes a conventional operating system **721**, such as Windows NT® from Microsoft Corp., or one of various UNIX-based operating systems, such as Sun Microsystems’ Solaris 2.5. The service provider computer **102** further includes a network communication protocol layer **719** that implements the necessary TCP-IP communication functions for connecting to the network **106** and communicating with other computers.

In accordance with the present invention, the service provider computer **102** includes a number of executable components and database structures useful for managing the software update interactions with the client computer **101** and the software vendor computers **103**. These components include a security module **701**, a communications module **703**, a payment module **705**, database modification tools **707**, a update database **709**, a user profile database **711**, a reporting tools module **713**, a URL monitor module **715**, an advertising/information database **717**, and an activity log **718**. The update database **709** is described here; the remaining components are described further below.

#### Update Database

The update database **709** maintains information identifying a large number of software products, information about the software updates that are available from the diverse software product vendors for these software products, information for identifying software products installed on a client computer **101**, and for uniquely distinguishing the versions and names of installed software products.

In one embodiment, the update database **709** does not itself store the software updates, but rather stores information, such as URLs, that allows the service provider computer **102** or the client computers **101** to directly access the software updates from the software vendor computers **103**. This implementation is chosen for several reasons. The system **100** is designed to provide software updates for large numbers of software products, on the order of hundreds, and perhaps thousands of products. In this situation, extremely large amounts of storage would be required to store the relevant files. Further, by not storing the software updates themselves, but only links to the software vendor computers **103**, the service provider does not have to make sure that the software updates themselves are always current, but need only maintain the link information, which is administratively easier. In another embodiment, the software updates are stored in the updated database **709**. This implementation is useful, for example, to facilitate synchronization of updates of the database **709** itself with the releases of new software updates for software products, thereby ensuring that the entries in the database **709** are consistent with the current releases of new software updates.

Finally, the update database **709** may also store information describing an installation process for installing a software update. This information may include particular configuration, file format, or other data useful to performing the installation of the software update the client computer **101**. This information, if present, may be provided to the client computer **101** to use during the installation of the software update.

The update database **709** may be implemented in a variety of ways. Referring now to FIG. 8 there is shown one implementation of the update database **709**, illustrated as a schema for a relational database. In this embodiment, the update database **709** includes 4 tables: a method table **801**,



a product locator table **803**, an product table **805**, and an update table **807**. FIG. 9 illustrates a flowchart of the process of analyzing the client computer **101** using the tables of the update database **709**.

The method table **801** maintains information identifying various methods of analyzing a client computer **101** to determine which software products are installed thereon. The method table **801** includes scan methods **811** and parameters **812**. The various scan methods **812** are designed to cover the variety of different facilities of a client computer **101** that may identify the installed products. For example, in a client computer **101** using Microsoft's Windows95 or Windows NT operating system, there is provided a Registry which is designed to maintain indicia of installed software products. The Registry includes various methods that can be called to return information about the software products identified therein. Some of these methods are listed in the scan methods **811**. The parameters **812** are arguments to the Registry methods, for example, identifying specific aspects of the Registry to be searched.

While compliance with the Windows95 standard requires that a software vendor's installation procedure should update the Registry, not all software vendors comply. In this case, information identifying the installed software products is also maintained in the config.sys, system.ini, and the autoexec.bat files. Also, a client computer **101** may be using Microsoft Corp.'s MS-DOS or Windows 3.1 operating systems, which do not use the Registry. Accordingly, the scan methods **811** include methods for reviewing these system files and returning indicia of the installed software products.

Each of the scan methods **812** return indicia of the installed products in the form of a number of strings, here scan\_string. Each scan\_string identifies a product name or file name, or some other data. However, a scan\_string may not uniquely identify a product. For this reason, the scan\_string is resolved by the product locator table **803**.

The product locator table **803** associates individual scan\_strings **813** with a product name **815**, instructions **816** for determining a version number or release number, and one or more constraints **814**. The constraint is a rule that uniquely identifies the product given contextual information for the product where there are two entries having identical scan\_strings. Constraints include specific directories that include the product, additional entries in the system configuration file, the Registry or the like. If the specified information in these various locations matches the constraint values, then the product name associated with the constraint is the correct product name for the scan\_string. In one embodiment, the constraint **814** is an executable procedure that retrieves information in these various locations, and determines from this information whether the product name is a match with the scan\_string, according to whether the specified details of the constraint are found in the client computer **101**.

Since some of the installed software products will be in their most current version, it is not necessary to update all software products installed on the client computer **101**. Rather, from the list of installed software products, further analysis (**205**, FIG. 2) determines for which of these software products is there an applicable software update. A software update is applicable to a client computer **101** if version of the software update is more recent than the version of the installed software product.

Since not all of the software products installed on a client computer **101** need to be updated, the determination of the applicable software updates is usefully made with the product table **805**. The product table **805** associates a product

name **815** and a particular release **818** with an update ID **819** identifying a software update for that version of the product. The new version number **820** specifies the new version that would be produced by applying the software update specified by the update ID **819** to the software product identified by the product name and release number. The latest field **821** specifies (Y/N) whether applying the software update would bring the product to its most up-to-date version.

Finally, the update table **807** stores the information necessary for performing the software update itself. This table is usefully keyed by the update ID **819**. For each update, there is provided a URL list **823** which contains URLs for the various sites that store the actual binary files for the software update, typically the software vendor computer system **103**, and potentially mirror sites. The URL list **823** is comprised of a number of URL entries, each URL entry having a URL and a timestamp of the last time the URL was validated, and flag indicating whether the URL is valid. This allows the URL monitor **715** to ensure that current URL information is maintained in the database.

The current cost **824** of the software update is also stored to provide the user with cost information for the software update.

The format **825** specifies the file format of the software update files, and thereby indicates the type of processing needed to install the software update files. In one embodiment, there are six formats and accompanying installation procedures:

TABLE 1

Format	Installation Procedure
zip	1) Unzip file with unzip.exe 2) Run install.exe
zip	1) Unzip file with unzip.exe 2) Run setup.exe
self-extracting archive	1) Execute file to extract 2) Run install.exe
self-extracting archive file.exe	1) Execute file to extract 2) Run setup.exe
unknown	1) Execute file for self extraction and installation. 1) use script information to perform installation.

With respect to unknown or custom formats, the update table **807** stores in the script **826** either a handle to a custom installation program that is provided either by the software vendor for the update, or by the service provider. In addition, the script **826** also stores information about any conditions that are required for the installation, such as turning off anti-virus programs, or other conflicting programs during the installation process.

The description **827** field stores data associated with a description of the software update, such as describing the product features. The description is preferably a URL to a file on the software vendor computer system **103** that contains the description information. Again, the actual text need not be stored here, but merely a link to where that information is available on the network **106**.

The update database **709** has been described as a set of tables. Alternatively, the update database **709** may be implemented in an object oriented framework with each table being a class, and the fields of the tables being attributes and methods of the class. The class type is then usefully defined by the primary key of the table.

## Client Computer

Referring now to FIG. 9, there is shown an illustration of the hardware and software architecture of a client computer 101. A client computer 101 is of conventional design, and includes a processor core 918, an addressable memory 900, and other conventional features (not illustrated) such as a display, a local hard disk, input/output ports, and a network interface. The display is of conventional design, preferably color bitmapped, and provides output for a user interface for various applications, such as illustrated in FIGS. 3-6. The input/output ports support input devices, such as a keyboard, mouse, and the like, for inputting commands and data. The network interface and a network communication protocol 916 provide access to remotely situated mass storage devices, along with access to the Internet, with a TCP-IP type connection, or to other network embodiments, such as a WAN, LAN, MAN or the like.

In the preferred embodiment the client computer 101 may be implemented on a Intel-based computer operating under Microsoft Windows 3.1 or Windows95 operating system 917, or equivalent devices. The client computer 101 includes some number of configuration files 915, such as the Windows95 Registry, the system.ini, config.sys and other files.

The client computer 101 further has installed thereon software products in the form of applications 912, operating system utilities 913, and device drivers 914, and the like. These various software products are among those that will be updated by the service provider computer 102.

In accordance with the present invention, the client computer 101 executes the client application 104 in memory 900. The client application 104 is comprised of a number of executable code portions and data files. These include a security module 901, a communications module 903, a payment module 905, a registration module 904, an advertising and news module 906, a system analyzer 907, a recovery module 908, an install monitor 910, and data defining the current state 911 of the application. The client application 104 further maintains in a private area of the computer storage archive files 909 that archive the state of the client computer 101 prior to each update installation. The client application 104 may be provided to the client computer 101 on a computer readable media, such as a CD-ROM, diskette, 8mm tape, or by electronic communication over the network 106, for installation and execution thereon.

## Analysis of Installed Software Products and Determination of Applicable Updates

In the preferred embodiment, the analysis 204 is preferably performed by the client application 104 on the client computer 101. This reduces the network bandwidth required, and the potentially unreliability of non-stateless remote procedure call implementations by having the service provider computer 102 perform the analysis. It further increases the number of simultaneous users of the service provider computer 102. The analyze process is performed by the system analyzer 907 module of the client application 104.

In this embodiment then, the client computer 101 stores a local copy of the method table 801 and the product locator table 803 and uses these local copies to perform the analysis.

Referring now to FIG. 10 there is shown the process of the system analyzer 907 for analyzing 204 the client computer 101 to determine the list of installed software products.

The system analyzer 907 first synchronizes 1001 the method table 801 and the product locator table 803 in the client computer 101 with the current versions held by the service provider computer 102. Preferably each table is

replaced in its entirety; this is likely to be faster than comparing individual entries and updating only those that are out of date. The synchronization may be mandatory or conditioned by version on client computer 101 being older than the version on the service provider computer 102, as indicated by stored timestamp of last time the update table 709 in the service provider computer 102 was updated.

Once the tables are synchronized, the system analyzer 907 can operate locally, for improved efficiency. The system analyzer 907 traverses the entire method table 801, and invokes 1003 each scan method 812 to search the Registry and configuration files 915 of the client computer 101. Each scan method 811 outputs a scan\_string, as described, specifying some software product installed on the client computer 101.

The system analyzer 907 applies (1005) each of the scan\_strings to the product locator table 803. The product locator table 803 receives the scan\_string and resolves 1007 the scan\_string to determine a product name 815 and a release instruction 816 associated with it. In some cases, the scan\_string does not uniquely identify a product. name 815, but matches several product names of installed software products. Accordingly, for each matching entry, the system analyzer 907 obtains 1009 a constraint 814 from the product locator table 803, and resolves 1009 the constraint to determine whether product on the client computer 101 is in fact the product listed in the entry. The constraint 814 of one of the entries will be satisfied and uniquely identify the product name.

Once the specific entry with the correct product name is identified, the system analyzer 907 resolves 1011 the release instruction 816 for the entry to obtain the release or version number of the installed software product. The release instruction 816 is preferably an executable procedure that obtains the version number from the named software product, and thus not merely the actual data itself. Using an executable procedure here ensures that the obtained release or version number is actual value for the product.

The result obtained by the system analyzer 907 from the product locator table 803 is a list 1013 of the installed software products on the client computer 101, each product identified by name and the installed version. The system analyzer 907 uses this list to query the service provider computer 102 to determine 205 for which of these products there is an applicable update.

For each installed product (1002) the system analyzer 907 queries the service provider computer 102 to resolve 1004 the name 815 and release number 818 of the product and determine if there a current update 821 for the product. This may be done by passing in the entire list as name, value pairs, or individually quarrying the service provider computer 102. In either cases, the service provider computer 102 determines if there is an applicable update for a software product by comparing the product name 815 and release information 818 to the product table 805, and obtaining the information in the latest update field 821. If there is an update available, in that the release information in the table indicates a version later than the version that is installed on the client computer 101, then the service provider computer 102 returns 1006 a handle the update ID 819 to the system analyzer 907. If the release of the software product installed on the client computer 101 is the most recent version, then the service provider computer 102 checks the next entry. This process continues until all of the installed software products are checked.

## Selection of Software Updates

Once all of the installed software products have been reviewed against the product table 805, the system analyzer

## 15

907 will have a list 1007 of the applicable software updates, as those products for which it received an update ID 819 from the service provider computer 102. The system analyzer 907 can then display 206 the list to the user. An exemplary user interface is described above with respect to FIG. 4.

The system analyzer 907 can further display 207 additional information for a software update, as illustrated in FIG. 5, by querying the service provider computer 102 with the update ID 819 of a particular product to resolve 1008 the update ID 819 on the update table 807 and return information, such as cost, description, and the like.

Installation of Software Updates and the Install Monitor

The user selects one or more of the list software updates. For each selected update, system analyzer 907 returns the update ID 819 to the service provider computer 102. The service provider computer 102 resolves the update ID 819 against the update table 807 to obtain the record for this update, including the URL list 823 identifying the location of the relevant update files. This record is returned to the client computer 101. The client computer 101 accesses the identified URL(s) and downloads the software update files, typically from the software vendor computer 103, though downloads may be from mirror sites, or the like. The client computer 101 further downloads (from the received URLs) any additional installation files, such as installation executables, and scripts. The client computer 101 also verifies that the software update files are not corrupted.

In a preferred embodiment, the client computer 101 employs its security module 901 to verify the integrity of the files to make sure that they have not been corrupted.

The software update is then installed 212 by the client application 104 as described, using the format information 825 to determine the particular installation process, and the script 826 to control any custom installation or configuration information.

Installation 212 is monitored by the install monitor 910, which is executed prior to the actual installation. The install monitor 910 documents the state of the client computer 101 prior to installation and the changes made during the installation of a software update. The install monitor 910 operates in the background, and intercepts calls to the file system or other operating system calls that might result in changes to any files in the client computer 101. Depending on the specific call, the install monitor 910 takes action to preserve the state of the file before the change is made.

FIG. 11 illustrates a flowchart of the operation of the install monitor 910. The install monitor 910 receives operating system calls and messages from the client application 104. On trapping 1101 an operating system call, the install monitor 910 determines 1103 the type of call. There are three types of calls of interest: calls 1105 that delete a file or directory, calls 1107 that change an existing file by writing to it, and calls 1109 to add new a file or directory. When a file or directory is to be deleted, the install monitor 910 first makes 1113 a copy of the existing file or directory to a private area of the client computer's 101 hard disk or other storage device. The install monitor 910 then lets the operating system 917 delete the file or directory, and waits for the next call. When a file is to be changed 1107, the install monitor 910 determines 1115 whether this is the first write to the file. If so, then again, the install monitor 910 copies 1119 the file to the private area. If the file has been already changed during the installation, there is no need to copy it again. These copy operations 1113, 1119 preserve the configuration of the client computer 101 prior to the installation. Finally, if a new file or directory is to be added 1109, the

## 16

install monitor 910 stores 1117 the pathname of the new file or directory. This allows the new file or directory to be later deleted during an undo of the installation. For all other types 1111 of operating system calls, the install monitor 910 passes them through without action.

The install monitor 910 waits for installation process 212 to complete, preferably indicated by a message from the client application 104. At this point the complete prior configuration of the client computer 101 is known from the copied files and pathname information. These files and information are compressed 1121 into an archive file 909 and saved on the client computer 101, along with information identifying the software product installation to which it belongs. This identifying information allows the recovery module 908 to retrieve the archived information and restore the configuration of the client computer 101.

Other Service Provider Software Architecture

Referring again to FIG. 7, the remaining modules of the service provider computer 102 are now explained. Communication

The communications module 703 provides for the establishment, maintenance and termination of network connections between the service provider computer 102 and either the software vendor computers 103 or the client computers 101. The communications module 703 supports the FTP and HTTP protocols for sending and receiving data over the Internet and the World Wide Web. The communications module 703 generally maintains and establishes separate streams for each connection it maintains. Preferably, the service provider computer 102 supports a large number of connections, possibly several hundred or thousands, at a time. In the event the customer base is so large that an even larger number of simultaneous connections may be required, multiple servers with mirror images of the update database 709 may be used. The communications module 703 also handles login and logout in a conventional manner, though these functions may be incorporated into the security module 701, below.

Security

The security module 701 handles the authentication of the user as an authorized user of the service provider computer 102. The security module 701 may be implemented with conventional authentication mechanisms based on digital signatures, such as public key systems supporting digital signatures, certificates and the like. Suitable security mechanisms include VeriSign Inc.'s Digital ID Center, which incorporates the login and logout functions from the communications module 703.

Additionally, the security module 701 provides for verification of the integrity of software updates that are downloaded from software vendor computers 103 to ensure that such updates have not been altered or infected by computer viruses or other unauthorized modifications. This module may be used, for example, to compute a checksum of the updates and the checksum may be stored in the update database 709. The checksum may be a simple one, or a cryptographically secure one such as any of the Message Digest (MD) algorithms proposed by Professor Ronald Rivest and commonly available in programming API's such as Microsoft's Cryptographic API standard. Whenever an update is later downloaded to a client computer 101 from a software vendor computer 103, the checksum of the update may be computed and compared against the one stored in the update database 709. If the two match, it may reasonably be inferred that the software update was downloaded to the client computer 101 correctly. The security module 701 may also be used to scan for viruses in the software updates stored on the various software vendor computers 103.

## Payment

The payment module **705** handles payment by the end user to the service provider for the service of providing software updates. The service provider computer **102** maintains a database of its users. This database may be the user profile database **711** or other databases. Each user is charged a service fee for using the service provider computer **102** to download software updates. The fee may be based on a variety of different schedules, such as connection time, number of software updates purchased, annual or monthly subscription fee, or a combination of any of these or other pricing formulas. However charged, the payment module **705** tracks the user's usage of the service, for example, total the connection time, and maintains a count of the number of software updates downloaded, until the user logs out of the service provider computer **102**. Payment is then charged to the user's credit card, which was previously supplied by the user during registration. Suitable implementations of the payment module **705** may be created in conformance with the Secure Electronic Transaction specification of MasterCard and Visa.

A user's subscription to the service may be enforced by the payment module **705** in various ways. One example of an algorithm to enforce term subscription is as follows:

The user logs in from the client computer **101** to the service provider computer **102**. The payment module **705** determines if the user's account is current, and if so, accepts the connection to the client computer **101**. If the user's account is about to expire, for example, within 30 days, or has expired, the payment module **705** prompts the user to renew the subscription. If the user agrees, the subscription fee is charged to the user's credit card account, and the connection to the client computer **101** is established, allowing the user to use the service as described. If the users refuses to renew, the connection is refused.

Fees may also be charged on a per-transaction basis. In this scenario, the fees may be attached to selected transactions. Once example of an algorithm to enforce per-transaction fees is as follows:

The client application **104** requests, for a software product to be updated, a transaction permission from the service provider computer **102**. The payment module **705** determines from the update database **705** a specific fee for the transaction, and returns this information, along with a permission, to the client application **104**. The client application **104** displays the fee to the user, who either confirms the transaction or cancels the software update. If the transaction is confirmed, the client application **104** performs the installation process. The payment module **705** is notified if the transaction and installation is successful, and then adds the transaction fee to a running total of fees for the current session. When the user's session is complete, the running total of transaction fees is charged to the user's credit card, and the charges provided to the client application **104** which displays them to the user.

In cases where an update is going to be undone by the recovery module **908**, the transaction fees should be credited back to the user's credit card account. Here, the client application **104** informs the service provider computer **102** that a software update is to be undone, providing the update ID **819** of the software update. The payment module **705** uses the update ID **819** to determine the transaction fee (cost **824**) to be credited. This amount is passed back to the client application **104** and displayed to the user. The software update is removed by the recovery module **908**, and the payment module **705** is notified of the successful removal. The payment module **705** then subtracts the transaction fee

from any current running total of fees. At the close of the session, the payment module **705** either charges or credits the user's credit card account, as appropriate.

## Database Modification

The database modification tools **707** provide for the maintenance and updating of the update database **709** to include new software updates from various software vendors. The tools **707** provide for the addition of new entries, and the deletion or alternation of existing entries in any of the tables of the update database **709**.

Of the various tables, the update table **807**, which contains the information about the current updates for the software products, and the product table **805**, which identifies the various software products for which their are updates, are the most frequently modified.

As new software updates become available, either the service provider or the software vendors access the database modification tools **707** to update the database. This is preferably done by completing forms that capture the information used in the tables of the database. FIG. **13** illustrates a sample form for specifying new update information, or changing existing update information. The form **1300** includes fields for providing the remark **1301** used in describing the update, a URL **1303** for the information on the software update, version information **1305**, software products **1307** affected by the update, the type of update **1309**, known incompatibilities **1311**, filters for locating prior versions of the software product to be updated based on version information **1313**, date information **1315**, and Registry information **1317** (for identifying the software product in the Registry files of the **915** of the client computer **101**). In addition, the file format **1321** of the update is specified along with a URL **1319** for the network location of software update itself. Finally, the installation procedures **1323** are specified for use in an installation script **826**. This information readily processed in a conventional manner and updated to the appropriate tables of the update database **709**.

In order to be supported by the update service of the service provider, software products and the updates to the software products have to be registered in the update database **709**.

Registering a software product has the goal of specifying sufficient information to identify a product and its version if the product has been installed on a given client computer **101**. FIG. **17** illustrates a form for registering a software product into the update database **709** for the first time. The registration form **1700** contains fields for the software vendor's company name **1701**, software product name **1703**, product type **1705**, a method **1707** to identify the software product on the client computer **101**, a unique file name **1707** or character string identifying the product, methods **1709** for verifying version information, file dates **1711**, and directories **1713** on the client computer **101**.

The product type **1705** can be a device driver, an application, a plug in (a product which extends the capabilities of another product such as an Internet browser) or an operating system file.

The method **1707** to identify the software product preferably specifies a unique file name or a character string and the location of the file name or string. For example, on the Windows 95 operating system, the name of a sound driver is specified in the Registry location `\HKEY_LOCAL_MACHINE\System\CurrentControlSet\control\Media Resources\midi`. In this case, the filename of the driver is found in this Registry location. A software product could also be identified by the presence of unique directory names. As noted, in some instances, product names are not unique.

The version of the software product that is installed on a client computer **101** may be obtained in one of several ways. It may be the version number, the last modification time-stamp of a file, or it may be specified explicitly in the Registry. The information provided in the registration form is processed after submission and added to the appropriate tables of the update database **709**.

Software updates may be identified for inclusion in the update database **709** by the service provider periodically searching the Internet to identify software vendors providing updates of software products. Most software vendors will maintain Internet sites that indicate the presence of new software updates. For each identified software vendor, the service provider downloads the software updates to the updates database **709**. A file format of the software update is determined, and an installation process specified according to the file format of the software update. Finally, the service provider creates an entry in the update database **709** including the URL or network location of the software vendor's computer system **103** storing the software update, the file format of the software update, and a specification of the installation process.

Alternatively, software vendors who contract with the service provider may provide the information about their software products and software updates, e.g. name, file format, and so forth, directly to the service provider, or to the update database **709**.

However provided to the update database **709**, registering an update consists of specifying the properties of the software update and the software products and their versions to which the software update is applicable. The properties of the software update preferably include the new version number **820** that results if the software update is applied to the product, the format **825** of the software update—zip file, self-extracting archive, and the like, and the installation steps (script **826**) required to install the software update on the client computer **101**. The product versions to which the software update is applicable are specified as the products themselves are specified earlier in this section. Also, a URL to a brief description and a full description of the software update—the problems it fixes and features it might add is preferably included, or the information may be directly stored.

As each new update becomes available, a new update entry is created.

Either the software vendor or the service provider specifies the product and the software update database entries in conformance with the properties of the software update.

#### User Profile Database

The user profile database **711** maintains a profile for each user containing information about which products the user has shown an interest, for example by requesting notification about software updates for specific products, or about new software products. This information is then used to deliver notifications about new updates available for these products to the user, for example by email, or other electronic communications mechanisms. This optional feature of the service provider computer **102** further enhances the value of the service to the user, ensuring timely notification of the availability of software updates and new software products.

In this regard, one alternate embodiment of the present invention is the use of email to notify users about new software update information, and new software products for which the user has expressed an interest. Specifically, when a new software update or software product is available, the service provider computer **102** sends an email to those users who have requested notification by email. The email con-

tains information about the software update, and may include the record from the update table **807** about the software update, including the URL data **823** used to access the software update files. The client application **104** would then read the update information, and verify that the software update is indeed applicable to the client computer **101**, and that the client computer **101** satisfies any conditions for installation. If the software updates are approved by the user, the client application **104** downloads the software update, verifies its integrity, and installs the software update directly, without having to login **201** to the service provider computer **102**, and analyze **204** the software products installed on the client computer **101**. In the case of notifications about new software products in which the user had expressed interest, the client application **104** would verify that the user is still interested in the software product and proceed to purchase, download and install it.

As a further enhancement of the e-mail notification embodiment, the email sent by the service provider computer **102** includes a specification of conditions a client computer **101** must satisfy for the software update or software product to be installed. This information is essentially the same as that used by the client application **104** to determine the relevant software updates for the client computer **101**. For example, this information includes, for a software update, the older versions of the software product to which it is applicable. This additional information in the email notification is used by the client application **104**, for example, to ensure that the software update is used only once by the user, and can be repeatedly applied.

The user profile database **711** generally stores information descriptive of each user. This information may include the user ID, password, digital signature, credit card numbers and the like, for use by the security **701**, communications **703**, and payment **705** modules. FIG. **14** specifies one exemplary schema of the user profile database **711**. In a user table **1400**, each user is identified by user ID **1401**, name **1403**, email address **1405**, the start date **1407** of their subscription to the service, the end or termination date **1409** of the subscription, credit card information **1411** such as number, issuer and expiration date, a user selected password **1413**, and a public key **1415** or other authentication token. As illustrated in FIG. **3**, the user has the option **309** of requesting notification by email of such software updates. The user table **1400** thus also includes a flag **1416** indicating whether the user so desires to be notified by email. The user table **1400** is keyed by the user ID **1401** to a notification table **1417** that associates the user with selected product names **1419** and their current version **1421**. When a software vendor or the service provider updates the update database **709** with information for a new software update, the notification table **1417** may be scanned to identify those users by user ID **1401** to notify about the update. The email flag **1416** for a user is checked, and if true, the user's email address **1405** is obtained from the user table **1400** and the user notified by email with information identifying the new software update.

#### Activity Log

The service provider computer **102** may be used to log all activities it performs with respect to the service in the activity log **718**. Of particular interest are the activities the computer performs in response to user requests for software updates and the like. An illustrative format for the activity log **718** is shown in Table 2.

TABLE 2

Activity Log 718					
Transaction Id	Activity Type	Date-Time	User Id	Parameters	Response
00000001	Login	031296 093540	20198312	password	Success
00000002	GetMethods DB	031296 093606	20198312	last version	Methods DB or Up-to-date
00000003	GetProducts Locator DB	031296 093649	20198312	last version	Products-Locator DB or Up-to-date
00000004	Query Product DB	031296 093723	20198312	Sound Blaster16, 2.0	Up-to-date
	Query Product DB	031296 093727	20198312	Myst 1.0	
00000005	GetUpdate Entry	031296 093751	20198312	sb16-2.02	Update Entry
00000006	Download Done	031296 093807	20198312	sb16-2.02	Success
00000007	Installed Update	031296 094532	20198312	sb16-2.02	Success
00000008	Logout	031296 094730	20198312	—	Success

In this example, the user logged in on Mar. 12, 1996 at 09:35:40 a.m., synchronized their method table 801 and product locator table 803, queried if software updates for SoundBlaster16 2.0 and Myst 1.0 newer than these product's last version were available. The responses indicate that Myst 1.0 was update to date, but the current version of SoundBlaster16 was version 2.02. The user then obtained the update entry for the new version of SoundBlaster16 describing the software update, downloaded the software update, installed it, and logged out.

Activity types not represented in the example above include Undo of Updates by the recovery module 908, registering for service, and registering for notification for updates to specific products.

In this example, the activities of a single user are represented in the activity log. In an actual system, the activities of several different users would be interspersed in the activity log.

Reporting Tools

The reporting tools 713 provide support for querying the update database 709, the user profile database 711 and the activity log 718. The queries may be about the software products and updates, about the correlation between the types of software updates accessed by various users, and about aggregate data. The databases 709, 711 and the activity log 718 together have the potential to provide precise descriptions of the software product profiles of the users. For example, statistical information may be retrieved indicating the number of users of one product, such as SoundBlaster16, who also own a second product, such as Myst. This information may be collected and analyzed without necessarily violating the privacy of the individual users.

URL Monitor

The URL monitor 715 compiles the list of URLs in the update database 709 and verifies on a periodic basis whether they have changed. This is done to ensure that the URL information for the software updates is always valid. FIG. 12 illustrates a flowchart of the URL monitor 715. The URL monitor 715 traverses 1201 each entry in the update table 807. This may be done simply in serial order, or by more

complex approaches, such as oldest entries first, or some other fashion. For each entry, the URL monitor 715 obtains 1203 the URL entries in the URL list 823, each entry as noted above having a timestamp. The URL monitor 715 links 1205 to the URL in an attempt to connect to the identified site or file via the Internet.

The attempted link may fail, and may be repeated some number of times in order to confirm that the URL is actually absent or otherwise incorrect, as opposed to merely a failure of the network service provider or the like. Once it is determined 1207 that the URL is not present, the URL is marked 1209 in the update table 807 as being invalid.

If the URL is present, then the timestamp of the URL at the host site is checked, typically by checking the timestamp of the file associated with the URL, or the timestamp of the file that includes the URL, or whichever is later. If the timestamp at the host is newer than the timestamp held in the update table 807, then it is possible that the underlying file has been changed, and the URL is no longer valid. Again, the URL is marked 1209 as being invalid. If the timestamp of the host is not newer, then the URL monitor 715 continues with the next URL in the URL list 823. Once all of the URLs in the update table 807 (or the desired number of old ones) have been processed, then the URL monitor 715 notifies 1213 the system administrator of the potentially invalid URLs. The system administrator can then verify the URLs and update them if necessary, resetting the valid flag as the URLs are updated.

Advertising & Information Database

The access that the service provider computer 102 has to the software profile of the client computers 101 lends itself to sending information, advertisements, and other promotional material that would be appropriate to each specific user, based on the software installed on the user's computer. Basing information delivery on the installed software products increases the saliency of the information since the user has already manifested an interest in the products. Thus, advertising or promotional information that is derived from or associated with such software products is most likely to be of interest to the user. The service provider computer 102 associates software products with advertising information, and enables this advertising information to be periodically delivered to the user.

Furthermore, the nature of downloading and installing software updates is inherently time-consuming; the risks that users perceive in updating usually would mean that they would seldom perform the updates on unattended computers. These factors create an opportunity to the service provider to direct targeted advertisements at the user at appropriate moments when the user runs the client application 104 to update their software, at which time they are present at their computer but not engaged in other activities. The advertisements themselves may be about for-fee software updates (upgrades) that the user may be able to purchase from the service provider or other third parties. Delivery of advertising information during the update process 212 is on the client computer 101 by the advertising/news module 906.

The advertising and information database 717 accordingly associates software products with advertising and promotional information. This association may be made in a number of different ways. One mechanism of association is categorizing software products and advertisements. FIG. 15 illustrates an exemplary schema for the advertising and information database 717 for associating advertising information and software products.

The ad table 1500 includes for each advertisement an ad number 1501, a URL 1503 to the advertisement or infor-

mation item, and a list **1505** of categories for the advertisement, such as "word processing," "desktop publishing," "graphics," "adventure games," "communications," "Internet" and the like. An advertisement or information item may have any number or variety of categories associated with it. The product-category table **1507** lists products names **1511**, product IDs **1509**, and again, a list **1513** of categories for the product.

If a user has requested updates to a specific installed product, then presumably the user would be interested in advertisements or information for other products that are categorized in the same categories as the installed product. For example, if the user requests an update to an installed copy of Myst 1.0, then this product name is matched against the product name **1511** in the product-category table **1507**, and the categories **1513** for it, such as "interactive game," are retrieved. The categories **1505** in the category list **1505** of the ad table **1500** are matched against this category, and the URLs **1503** for matching entries retrieved and accessed, with the information being delivered to the user by the client application **104**. The information is preferably presented on the client computer **101** during the installation process **208-214**. If there are many matches, then a weighting may be applied to select only those advertisements that match a certain percentage, or number, of categories of the installed products. Other selection criteria may also be applied. The schema of FIG. **15** is merely illustrative, and implementations other categorization may be used to associate advertising information with software products for delivery to users having such products installed on their computers.

Client Application Software Architecture

Referring again to FIG. **9**, the remaining modules of the client application **104** are now explained.

Communication

The communications module **903** provides complementary functions to the communications module **703** of the service provider computer **102**, including establishing and terminating connection streams, login and logout functions, FTP functions, and HTTP protocol compliance. All of these functions may be implemented in a conventional manner.

Security

The security module **901** provides an interface to the security module **701** of the service provider computer **102**, for authentication of the user password, digital signatures, certificates, or the like. User passwords or other authentication information are assigned to the user in a conventional manner. The security module **901** may store the authentication information, or the user may be required to manually input the authentication information during login.

Payment

The payment module **905** provides an interface to the payment module **705** of the service provider computer **102** to effect payment for use of the update service. Payment schedules may vary as described above. Preferably payment is made by credit card authorization. Given one or more payment schedules for use of the service, such as per update, periodic fees, or the like, the payment module may be implemented in a conventional manner.

Registration

The registration module **904** is used to register new users to the service provider computer **102**. A sample user interface for the registration module **904** is shown in FIG. **3**.

The registration module **904** obtained the user's name, address, credit card information, and a user-selected password. The password is entered by the user twice and the two entries matched to ensure that the user did not mistype the password unintentionally. This information is stored in the

current state **911** data. The registration module **904** also sends this information to the service provider computer **102**. There the information is verified and a unique registration number assigned to the user and the number is returned to the client application **104**, where the registration module **904** displays the number to the user, and stores the number internally in the current state **911** data.

Advertising & News

The advertising and news module **906** provides customized information to each user of the service based on their prior interests in various software products and updates, as monitored and stored in the user profile database. The advertising and news module **906** interfaces with the advertising database **717** of the service provider computer **102** to deliver advertising and promotional information the user based on the installed software products on the user's computer **101**.

The advertising and news module **906** provides information in various different modes. In one mode, the advertising and news module **906** obtains ads from the advertising database **717** on a periodic basis, such as once every several hours, according to the installed software products on the client computer **101**, as described above, and caches them locally. If an ad (here including other types of information or promotional data) is already present in the cache, it is marked as new, otherwise, the URL of the ad (as determined from the database **717**) is accessed, and the ad saved in the cached. Ads not marked as new are purged.

In a second, complementary mode, the advertising and news module **906** then selects ads from the cache and displays them to the user for a predetermined duration when no other user activity is occurring, such as during the installation process described above, or during an undo operation by the recovery module **908**.

Current State

The current state **911** is a data store of data describing the present operation of the client application **104**, including for example, user specific information, such as name, address, credit card number, registration or serial number, and which updates have been downloaded and which have been installed. The registration number is used each time the user logs in to the service provider computer **101**. The information about which updates have been downloaded and installed is used to provide the undo capability of the recovery module **908**.

Recovery

The recovery module **908** provides for undoing, or de-installing previously installed software updates using the archive files **909**.

Recovery is an action initiated by the user when he or she is dissatisfied with a software update. When initiated, the effects of a software update previously installed are reversed. The ability of the recovery module **908** to perform the recovery is based on the presence of the archive files **909** created by the install monitor **910** when the software update was first installed. The archive files **909** contain a copy of each file which was deleted or modified during installation along with its original pathname and a list of pathnames of files added during the installation. The archives **909** are preferably kept in a compressed format for space efficiency. Generally, given a specific software update to remove, the recovery module **908** reads the archive file **909** associated with that software update, restores the deleted or modified files to their directories, and deletes the added files or directories.

FIG. **16** illustrates one embodiment of the operation of the recovery module **908**. The recovery module **908** receives, as

## 25

shown in FIG. 6, an input of the name of the software update to be removed. This name is associated in the current state information 911 with the particular archive file 909 for that installation. The recovery module 908 closes 1601 all executing applications. Using the name of the software update, or other identifying indicia, the recovery module 908 obtains the archive file 909 associated with the update, and uncompresses 1602 it. For each file that is stored in the archive in compressed form, representing a file that was deleted, the recovery module 908 copies 1603 that file to its original location in the client computer 101. For each file or directory that is listed as being new, the recovery module 908 deletes 1604 that file or directory. Finally, the recovery module 908 reboots 1605 the client computer 101.

In summary, the present invention enables a useful mechanism for providing updates of various software products from diverse software vendors to a plurality of users, each user having different ones of the software products installed on their computers. The system of the present invention enables the software updates to be continually maintained and verified for correctness, while alleviating both users and software vendors of a substantial burden is communicating with each. The system enables any software vendor to provide software updates to the service provider, ensuring that subscribing users have the software update on a timely basis. Likewise, subscribing users are ensured that they are notified about software updates for all of the software products installed on their computers, without having to individually search out information for each such product. In addition, the present invention enables advertising and other information to be targeted to users based on their interests and preferences and expressed in the software products installed on their computers.

We claim:

1. A computer-implemented method of providing information for software residing on a client computer, comprising:

- maintaining a service provider computer on a network, the client computer accessible over the network by the service provider computer;
- maintaining on the service provider computer a database, the database containing references to network locations where information relating to software from a plurality of software vendors can be obtained;
- maintaining on the service provider computer a downloadable application, the application being capable of performing a scan of the client computer to identify one or more software products residing on the client computer;
- establishing a communication link between client computer and the service provider computer over the network;
- downloading the application to the client computer over the communication link;
- scanning the client computer with the application;
- as a result of the scan, generating a list of software residing on the client computer for which the service provider has information; and
- for at least one product on the list, downloading to the client computer at least a portion of the information for that product that is available to the service provider.

2. A method according to claim 1, wherein the network is the Internet and the network locations are URLs.

3. A method according to claim 1, wherein the information comprises a software update for updating a software product residing on the client computer.

## 26

4. A method according to claim 3, wherein the database further contains for each software update a specification for an installation process for installing the software update on the client computer.

5. A method according to claim 4 further comprising installing the software update in accordance with the installation process.

6. A method according to claim 5, wherein the installation process is specified in accordance with a file format of the software update.

7. A method according to claim 1, wherein the information comprises at least one additional software product, the additional software product not presently residing on the client computer but compatible with software residing on the client computer.

8. A method according to claim 7, further comprising downloading to and installing on the client computer the additional software product.

9. A method according to claim 8, wherein the database further comprises for each additional software product a specification for an installation process for installing the software update on the client computer.

10. A method according to claim 9, wherein the installation process is specified in accordance with a file format of the software update.

11. A method according to claim 1, wherein the information comprises promotional information.

12. A computer-implemented method of providing relevant information for updating software residing on a client computer, comprising:

- maintaining a service provider computer on a network with the client computer;
- maintaining on the service provider computer a database, the database containing information relating to software updates of diverse software vendors;
- establishing a communication link between the client computer and the service provider computer;
- downloading to the client computer an application, the application having a function for scanning the client computer to determine which software products reside on the client computer;
- scanning the client computer with the application;
- as a result of the scan, generating a list of software residing on the client computer for which the service provider has relevant information; and
- for at least one product on the list, downloading to the client computer at least a portion of the relevant information that is available to the service provider.

13. A method according to claim 12, wherein the network is the Internet.

14. A method according to claim 13, wherein the relevant information comprise a software update.

15. A method according to claim 14, further comprising downloading the software update to the client computer over the network.

16. A method according to claim 15, wherein the software update is downloaded from a computer on the network that is distinct from the service provider computer.

17. A method according to claim 15, further comprising installing the software update on the client computer.

18. A computer-implemented method of providing additional software products that are relevant to software residing on a client computer, comprising:

- maintaining a service provider site on a network with the client computer, the service provider establishing a contractual relationship with a plurality of software



27

vendors so that the software vendors receive compensation if their software is downloaded to the client computer;

maintaining on a service provider computer a database, the database containing information relating to software products of diverse software vendors;

maintaining on the service provider computer a downloadable application, the application having a function for scanning the client computer to determine which installed software products reside on the client computer;

establishing a communication link between client computer and the service provider computer;

downloading the application to the client computer over the communication link;

scanning the client computer with the application;

as a result of the scan, generating a first list of software products residing on the client computer;

comparing the first list with the information in the database to generate a second list, the second list containing software products that are compatible with the software residing on the client computer;

downloading to the client computer at least one product on the second list; and paying the software vendor compensation relating to the download.

19. A method as recited in claim 18, wherein the network is the Internet.

20. A method as recited in claim 19, wherein the additional software comprises a software update for at least some of the software residing on the client computer.

21. A method as recited in claim 20, wherein the database further comprises for each software update a specification for an installation process for installing the software update on the client computer.

22. A method as recited in claim 21, further comprising installing the software update in accordance with the installation process.

23. A method as recited in claim 22, wherein the installation process is specified in accordance with a file format of the software update.

24. A method according to claim 18, wherein the additional software is a software product not presently residing on the client computer.

25. A computer-implemented method of providing relevant information for software residing on a client computer, comprising:

maintaining a service provider site on a network with the client computer;

maintaining on a service provider computer a database, the database containing information relating to software products of diverse software vendors, the information being obtained by periodically scanning a public network;

maintaining on the service provider computer a downloadable application, the application having a function for scanning the client computer to determine which software products reside on the client computer;

establishing a communication link between client computer and the service provider computer;

downloading the application to the client computer over the communication link;

scanning the client computer with the application;

as a result of the scan, identifying software products residing on the client computer for which the service provider has information; and

28

for at least one product identified as a result of the scan, downloading to the client computer a portion of the relevant information that is available.

26. A method as recited in claim 25, wherein the network is the Internet.

27. A method as recited in claim 26, wherein the database comprises network locations where relevant information can be found.

28. A method as recited in claim 27, wherein the network locations are URLs.

29. A method as recited in claim 27, wherein the relevant information is downloaded to the client computer from a network location specified in the database.

30. A method as recited in claim 29, wherein the relevant information comprises a software update.

31. A method as recited in claim 26, wherein the database contains software products.

32. A method as recited in claim 31, further comprising downloading a software product from the database to the client computer and installing the software product on the client computer.

33. A method as recited in claim 31, wherein the database further comprises for each software product a specification for an installation process for installing the software product on the client computer.

34. A method as recited in claim 33, wherein the installation of the software product is done in accordance with the installation process.

35. A method as recited in claim 30, wherein the database further comprises for each software update a specification for an installation process for installing the software update on the client computer.

36. A method as recited in claim 35, further comprising installing the software update to the client computer, the installation of the software update done in accordance with the installation process.

37. A computer-implemented method of providing at least one software update on a client computer containing a plurality of software products, comprising:

maintaining on a service provider computer a database containing update information about a plurality of software products, the information including a network address for at least one software vendor server on the network that is separate from the service provider computer and contains at least one software update;

maintaining on the service provider computer a downloadable application, the application having a function for scanning the client computer to determine which software products reside on the client computer;

downloading the application to the client computer over a first communication path;

scanning the client computer with the application;

downloading a portion of the update information from the database to the client computer;

as a result of the scan, identifying software products that have been installed on the client computer for which updates are available;

ending client computer communications with the service provider computer;

selecting one identified software product to update;

downloading from the software vendor server to the client computer an update for at least one software product over a second communication path;

terminating communications between the software vendor server and the client computer; and

29

installing the software update on the client computer;  
wherein the service provider computer is not required to  
contain any software updates.

38. A method as recited in claim 37, wherein the appli-  
cation automatically downloads at least one software update  
on the client computer.

39. A method as recited in claim 37, further comprising:  
monitoring any changes made to the client computer  
during installation;

for each change to the client computer, storing data  
descriptive of the change; and

archiving the stored data as relating to the software  
update.

40. A method according to claim 39, further comprising:  
receiving a user selection of an installed software update  
to remove from the client computer;

retrieving archive files associated with the installed soft-  
ware update;

restoring from the archive files the client computer to a  
state prior to the installation of the software update by  
undoing the changes described in the archive files.

41. A method according to claim 37, wherein the appli-  
cation further comprises function for:

determining whether a file existing on the user computer  
is to be deleted or altered, or a new file added to the  
client computer;

saving a copy of files to be deleted before deleting them;

saving a copy of files to be altered before altering them;

storing a pathname of a file to be added before adding the  
file, and

archiving the copied files and stored pathnames in at least  
one archive file that is associated with the installed  
software update.

42. A method according to claim 37, wherein the appli-  
cation further comprises functions for:

identifying a version of each installed software product;  
and

30

determining whether the available update is later than the  
version installed on the user computer.

43. A computer-implemented method of providing soft-  
ware products from a plurality of software vendors to at least  
one client computer, comprising:

maintaining a service provider computer on a network  
with the client computer;

maintaining on the service provider computer an appli-  
cation that is capable of scanning the client computer  
and determining which software products would be of  
interest to a user of the client computer;

maintaining on the service provider computer a database  
containing information about users on the network;

downloading the application to the client computer;

scanning the client computer with the application;

determining from the scan of the client computer one or  
more software products of interest to the user;

creating a list of the software products of interest to the  
user;

storing the list in the database;

scanning the network for software products of interest to  
the user;

notifying the user by an electronic communication of the  
availability of the software product of interest to the  
user;

obtaining from the user an approval to install the software  
product of interest;

downloading to the client computer the software product  
of interest;

installing on the client computer the software product of  
interest.

44. A method according to claim 43, where in the software  
products are software updates for existing products.

\* \* \* \* \*