



US005961424A

[54] **FREE WHEEL CLUTCH MECHANISM FOR BICYCLE DRIVE TRAIN**

[75] Inventors: **Patrick Warner; Michael H. Harding,**
both of Boulder, Colo.; **Mu-Chuan Wu,** Tainan, Taiwan

[73] Assignee: **Schwinn Cycling & Fitness Inc.,**
Boulder, Colo.

[21] Appl. No.: **08/919,695**

[22] Filed: **Aug. 28, 1997**

Related U.S. Application Data

[60] Provisional application No. 60/038,726, Feb. 18, 1997.

[51] **Int. Cl.⁶** **A63B 21/00;** A63B 69/16

[52] **U.S. Cl.** **482/63;** 482/119

[58] **Field of Search** 482/51–53, 57,
482/63, 119, 62

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,854,561	12/1974	Conde .	
4,266,794	5/1981	Bals	482/62
4,338,798	7/1982	Gilman .	
4,371,185	2/1983	Bals	482/57
4,645,472	2/1987	Heidenreich .	
4,671,396	6/1987	Kotamaki .	
4,757,988	7/1988	Szymiski	482/62

FOREIGN PATENT DOCUMENTS


1469363 4/1977 United Kingdom .

Primary Examiner—Stephen R. Crow
Attorney, Agent, or Firm—Holland & Mart LLP

[57] **ABSTRACT**

An exercise bicycle including a frame having a seat and handlebars, a high-inertia flywheel having a hub at a center of rotation, the flywheel being rotatably supported on the frame at the hub, and a drive train including a drive sprocket, a crank arm attached to and extending from the drive sprocket, and a pedal attached to the crank arm, the drive train being rotatably supported by the frame. The drive train also includes a slave sprocket fixed to the flywheel at the hub, with the drive and slave sprockets connected in a direct-drive relationship, the drive train driveable in a forward and rearward directions to cause the flywheel to rotate. A clutch mechanism is positioned in engagement with the slave sprocket and the hub to create a frictional engagement between the sprocket and the hub, and to establish a break-free force threshold. When the drive train is actuated in the forward direction, the slave sprocket and the hub move together, and when the drive train is actuated in the rearward direction under the influence of a force greater than the break-free force threshold, the clutch mechanism slips between the slave sprocket and the hub, allowing the slave sprocket and the flywheel to move independently of one another.

14 Claims, 22 Drawing Sheets






Fig. 1




Fig. 2




Fig. 4




Fig. 3




Fig. 5B




Fig. 5A




Fig. 5C




Fig. 6




Fig. 7




Fig. 8




Fig. 9











Fig. 12

Fig. 13








Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24





Fig. 25

**Fig. 26**





Fig. 27

**Fig. 28**




Fig. 29




Fig.30

1

FREE WHEEL CLUTCH MECHANISM FOR BICYCLE DRIVE TRAIN

This application claims benefit of Provisional Application 60/038,726 filed Feb. 18, 1997.

FIELD OF THE INVENTION

This invention relates generally to free wheeling devices, and more particularly to a free wheel clutch mechanism useful with crank operated exercise bicycles employing an inertia flywheel.

BACKGROUND

The benefit of exercising on a direct drive exercise bicycle is well known. Direct drive exercise bicycles typically utilize a high-inertia flywheel driven by a fixed-gear drive train. The flywheel is driven by the rider up to relatively high revolutions per minute (rpm). Because of the direct drive feature, the drive train must rotate at a fixed ratio of rpm as compared to the flywheel based on the gear ratio. One benefit of the direct drive exercise bicycle is that the direct drive gear train provides "pedal-through assistance" for the rider. The "pedal-through" feature assists the rider by pushing the pedal through the top and bottom dead center pedal positions to help make the transition smooth and efficient. Other benefits are derived from the direct drive interaction between the inertia flywheel and the crank arms to which the rider's feet are attached. The inertia flywheel provides a smooth, non-jerky pedaling rhythm which provides an efficient and rigorous exercise for the rider, especially at relatively high rpms, such as 60 to 100 rpm.

In the application of this invention to an inertia flywheel exercise bicycle, positive drive is required to rotate the inertia wheel in order to overcome regulated retardation torque applied by brake means used to provide resistance against which the rider/operator works. The inertia wheel provides means for continued drive train (wheel to crank to leg) movements during those periods when the crank is in top dead center or bottom dead center positions, where the rider's legs are somewhat weaker in providing rotary motion to the activating crank arms. The flywheel affords smooth and steady operation for the rider.

The direct drive relationship between the flywheel and the drive train is also a drawback of exercising on this type of bicycle. The direct drive relationship is inconvenient when the rider wishes to quickly stop the pedals, or loses the pedaling rhythm required to keep up with the rotating flywheel. In the usual flywheel exerciser employing such a direct drive relationship, it is necessary for the rider/operator to gradually decrease his cranking rate in order to slow down the inertia wheel. The rider cannot suddenly stop pedaling inasmuch as the inertia flywheel continues to drive the crank arms.

Of similar importance is the desirability of providing pedal assist to the rider/operator's legs when cranking at a speed slower than that necessary to positively drive the flywheel, and providing for a gradual reengagement and lockup between the pedal actuated drive shaft and the free wheeling flywheel in order to avoid abrupt impact when reengaging the moving flywheel.

It is with these issues in mind that the present invention was developed.

SUMMARY OF THE INVENTION

The present invention in general terms concerns a clutch mechanism for use on an exercise bicycle, and consequently,

2

the present invention recognizes that it is desirable to have a free wheeling mechanism for an exerciser of the inertia flywheel type which provides means for selectively disengaging the flywheel from the drive means. The clutch mechanism allows for the beneficial direct-drive connection between the drive train and the flywheel, and also allows the drive train and flywheel to move independently from one another, or "break free", when a sufficient force is applied to the drive train or the flywheel.

In general, the invention is an exercise bicycle including a frame having a seat and handlebars, a high-inertia flywheel having a hub at a center of rotation, the flywheel being rotatably supported on the frame at the hub, and a drive train including a drive sprocket, a crank arm attached to and extending from the drive sprocket, and a pedal attached to the crank arm, the drive train being rotatably supported by the frame. The drive train also includes a slave sprocket fixed to the flywheel at the hub, with the drive and slave sprockets connected in a direct-drive relationship, the drive train driveable in a forward and rearward directions to cause the flywheel to rotate. A clutch mechanism is positioned in engagement with the slave sprocket and the hub to create a frictional engagement between the sprocket and the hub, and to establish a break-free force. When the drive train is actuated in the forward direction, the slave sprocket and the hub move together under a mechanical engagement, and when the drive train is actuated in the rearward direction under the influence of a force greater than the break-free force, the clutch mechanism slips between the slave sprocket and the hub, allowing the slave sprocket and the flywheel to move independently of one another. There is no mechanical engagement between the sprocket and the hub in the rearward direction as there is in the forward direction, established by the one-way bearing.

More specifically, the slave sprocket defines a sprocket collar mounted on the hub and also includes an engagement collar. A one-way bearing is mounted between the sprocket collar and the hub to allow the sprocket collar to drive the hub when the sprocket collar is driven in a forward direction, and to allow the sprocket collar to spin independently of the hub when the sprocket collar is driven in the rearward direction. An engagement flange fixedly mounted on the hub corresponds to the engagement collar, and compression means are mounted on the flywheel to bias the flange and the collar towards one another. A clutch material member is positioned between the engagement flange and the collar, and is clamped therebetween by the compression means to cause the engagement flange to move in conjunction with the sprocket collar. The engagement creates a break-free force required to cause the sprocket collar to move independently of the engagement flange. When the drive train is actuated in the forward direction, the sprocket collar and the engagement flange move together, and when the drive train is actuated in the rearward direction and overcomes the break-free force, the engagement flange slips with respect to the collar, allowing the sprocket collar and the flywheel to move independently of one another.

In another embodiment, the slave sprocket defines a sprocket collar mounted on the hub and defines an inner and outer engagement collars. A one-way bearing is mounted between the sprocket collar and the hub to allow the sprocket collar to drive the hub when the sprocket collar is driven in a forward direction, and to allow the sprocket collar to spin freely on the hub when the sprocket collar is driven in the rearward direction. An inner engagement flange is fixedly mounted on the hub corresponding to the inner engagement collar, and an outer engagement flange is fixedly mounted on

the hub corresponding to the outer engagement collar. Compression means are mounted on the flywheel to bias the inner flange and the inner collar towards one another, and to bias the outer flange and the outer collar towards one another. A clutch material member is positioned between the outer engagement flange and the outer collar, and between the inner engagement flange and the inner collar, and clamped therebetween by the compression means to cause the inner and outer engagement flanges to move in conjunction with the sprocket collar. The engagement creates a break-free force required to cause the sprocket collar to move independently of inner and outer engagement flanges. When the drive train is actuated in the forward direction, the sprocket collar and the inner and outer flanges move together, and when the drive train is actuated in the rearward direction and overcomes the break-free force, the inner and outer engagement flanges slip with respect to the inner and outer collars, allowing the sprocket collar and the flywheel to move independently of one another. There are other embodiments of the invention disclosed which perform the same function with very similar structure.

Also, the invention includes an exercise bicycle frame for use with the clutch mechanism. The frame includes a front support, a rear support, and a brace member extending between the front and rear ground supports. In addition, front forks are included that have a top end and a bottom end, and are attached at the bottom end to the front ground support. The front forks rotatably support a high-inertia flywheel. A rear post is included that has a top member and a bottom member, the top member attaching to the bottom member in a rear offset overlapping manner, the rear post defining a top end and a bottom end. The rear post is attached at the bottom end to the brace member. An articulated beam is attached to and extends from the top end of the front forks downwardly and rearwardly to a midpoint between the front forks and the rear post, then extends horizontally to the rear post at the intersection of the top and bottom members of the rear post. A rear truss extends from the top member of the rear post to the rear support. A handlebar is attached at the top end of the front forks, and a seat is attached at the top end of the rear post. A front area is defined by the front forks, articulated beam, rear post and brace member forming a five-sided polygon, and a rear area is defined by the rear post, rear truss, and brace member forming a five-sided polygon.

Accordingly, it is a primary object of the present invention to provide a free-wheeling clutch mechanism that allows an exercise bike to include the direct-drive relationship between the drive train and the flywheel, and at the same time allow the drive train and the flywheel to turn independently from one another under certain conditions.

Other aspects, features and details of the present invention can be more completely understood by reference to the following detailed description in conjunction with the drawings, and from the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an exercise bicycle incorporating the clutch mechanism of the present invention.

FIG. 2 is a schematic representation of the drive train of the exercise bicycle shown in FIG. 1.

FIG. 3 is a schematic representation of the drive train of the exercise bicycle shown in FIG. 1.

FIG. 4 is a section taken along line 4—4 of FIG. 3.

FIG. 5A is a section taken along line 5A—5A of FIG. 2

FIG. 5B is a representative section similar to FIG. 5A showing the effects of worn clutch material.

FIG. 5C is a representative section similar to FIG. 5A showing a different type of compression member.

FIG. 6 is a perspective view of a high-inertia flywheel incorporating one embodiment of the clutch mechanism of the present invention.

FIG. 7 is an exploded view of the flywheel of FIG. 6.

FIGS. 8 and 9 are elevation and perspective views, respectively, of a portion of the clutch mechanism.

FIG. 10 is a side view of the sprocket collar member of the clutch mechanism of the present invention.

FIG. 11 is a top view of the sprocket collar shown in FIG. 10.

FIG. 12 is a section taken along line 12—12 of FIG. 10.

FIG. 13 is an enlarged front perspective view of the sprocket collar of FIG. 10.

FIG. 14 is a side view of the clutch plate collar member of the clutch mechanism of the present invention.

FIG. 15 is a section taken along line 15—15 of FIG. 14.

FIG. 16 is a front perspective view of the clutch plate collar member of the clutch mechanism of the present invention.

FIG. 17 is a perspective view of a high-inertia flywheel incorporating an alternative embodiment of the clutch mechanism of the present invention.

FIG. 18 is an enlarged perspective view of the embodiment of the present invention as shown in FIG. 17.

FIG. 19 is a section taken along line 19—19 of FIG. 18.

FIG. 20 is a representative section of the embodiment shown in FIG. 19, showing the effect of worn clutch material.

FIG. 21 is an enlarged perspective view of another embodiment of the present invention.

FIG. 22 is a section taken along line 22—22 of FIG. 21.

FIG. 23 is a section taken along line 23—23 of FIG. 22.

FIG. 24 is a representative section of an alternative embodiment similar to that shown in FIGS. 22, 23 and 24.

FIG. 25 is an elevation view of another embodiment of the present invention.

FIG. 26 is a section taken along line 26—26 of FIG. 25.

FIG. 27 is an elevation view of another embodiment of the present invention.

FIG. 28 is a section taken along line 28—28 of FIG. 27.

FIG. 29 is a section taken along line 29—29 of FIG. 28.

FIG. 30 is a representative section of another embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In light of the above items, a free wheel clutch mechanism 40 has been developed for use on direct-drive exercise bicycles 42 utilizing an inertia flywheel 44 (FIGS. 1—4). While the present invention is described below associated with an exercise bicycle, it is contemplated that it could be used on normal bicycles or other exercise equipment, including magnetic resistive bicycles, air-resistance bicycles and other non-bicycle exercisers (such as upper body exercisers), each having rotary-driven mechanisms (wheels, etc.), in the proper circumstances. The free wheel clutch mechanism works in a direct-drive manner when the rider pedals the bicycle in the forward direction (counterclockwise in FIGS. 1 and 2, clockwise in FIG. 3), but has a release, or free wheel, characteristic when the rider applies

5

a required force on the pedal (or to the drive train somewhere) opposite or against the forward pedaling direction. Upon application of the appropriate opposite force ("break free force threshold"), the drive train free-wheels to allow the pedals to turn in the opposite direction with respect to, or more slowly than, the rotation of the flywheel. The rider can then either simply drive the pedals at a relatively lower rpm than the normal gear ratio to the flywheel, stop the pedals, or can rotate the pedals backwards.

The opposite force required to be applied to the pedals to cause the free wheeling action can be adjusted based on the design of the free wheel clutch mechanism, and is typically between 0.00 and 100 pounds, preferably 55 pounds at the pedals, depending on the application. The break free force threshold is based on the static frictional engagement between the clutch material and the clutch plates which the clutch material is clamped between, as well as the mechanical advantage provided through the drive train. The clutch plates, as defined below, are on different members that in normal circumstances are to rotate together. The friction force between the clutch material and the clutch plates facilitates this relationship. At a certain point (the break free force threshold), the opposing clutch plates overcome the static frictional force and spin at different speeds (r.p.m.'s) in the same direction, or in the opposite direction. The surface area of the clutch plates and the clutch plate material, the material property of the clutch plates and the clutch material, and the force at which the clutch plates clamp the clutch material are all factors that can be specifically designed to affect the break free force threshold. The break free force (as measured at the pedal) is affected also by the gear ratio and the length of the crank-arms.

The free wheel clutch mechanism 40 is integral to the drive train of the exercise bicycle. The drive or gear train includes the drive sprocket 46, the crank arms 48 and associated pedals 50 attached to the drive sprocket, the drive axle assembly 52, the slave sprocket 54, and the chain or belt 56 that interconnects the drive and slave sprockets, as shown in FIG. 3. Typically, the drive sprocket is rigidly mounted to one of the crank arms, and each crank arm is removably mounted to the drive axle assembly. The drive axle assembly is positioned in the hub on the frame to allow rotating movement, in either direction of the crank arms.

As shown in FIG. 4, the free wheel clutch mechanism 40 includes a sprocket collar 58 rotatably mounted on a slave axle assembly 60. The slave sprocket 54 is attached to the flywheel 44 adjacent to the hub 62. The slave axle assembly is mounted in the hub, and attaches to the frame to allow the flywheel to rotate with respect to the frame, under the force of the drive train through the movement of the slave axle assembly. The slave axle assembly is actually mounted in the hub, and includes an axle housing. Typically, the slave sprocket is mounted on the axle housing.

The free wheel clutch mechanism can be mounted in association with the drive sprocket, cranks and drive axle assembly, or can be mounted in association with the slave sprocket, slave axle assembly and flywheel. The placement of the free wheel clutch mechanism is a matter of choice dependent on the particular implementation. The only difference between the two positions of the free wheel clutch mechanism is that when mounted in association with the slave sprocket, the actuation of the free wheel clutch mechanism affects the movement of the chain and drive sprocket (slow down, stop or reverse). When the free wheel clutch mechanism is mounted in association with the drive sprocket, the actuation of the free wheel clutch mechanism allows the pedals and cranks to be slowed down, stopped, or

6

reversed while the drive sprocket, chain and slave sprocket and flywheel continue to rotate. As described herein, the free wheel clutch mechanism is mounted in association with the slave sprocket.

More specifically as shown in FIGS. 4 and 5A, the free wheel clutch mechanism includes a sprocket collar 58 (in this case a "slave" sprocket collar) that is mounted in a one-way drive relationship with the axle housing 64 such that the rotation of the slave sprocket collar in one direction directly drives the axle housing, and the rotation of the slave sprocket collar in the reverse direction does not drive the axle housing (allows "free wheeling"). This free wheeling relationship is established by one-way bearings 66 or a ratchet and pawl structure used between the slave sprocket collar and the axle housing.

The free wheeling motion of the slave sprocket collar 58 with respect to the axle housing 64 (and hence hub 62 and flywheel 44) is tempered, or reduced, by clutch plates 68 and clutch or braking material 70 acting upon the slave sprocket collar. A clutch plate collar 69 is secured to the axle housing 64 to fixedly position one end of the free wheel clutch mechanism 40. The clutch plates 68 are rigidly mounted to turn with the axle housing (and hence the hub and flywheel), and are forced into contact with the sprocket collar 58 by a biasing means, such as a spring member 72. The braking material 70 is positioned between the sprocket collar and the clutch plates to provide a frictional interface between the two. The braking material can be mounted to either the sprocket collar, the clutch plates, or can be free-floating. The area of contact between the clutch plate and the sprocket collar (through the braking material) in combination with the compression force applied by the biasing means 72, creates the "break free" force required to be applied through the sprocket collar to allow the sprocket collar to "free wheel" on the axle housing. If the applied force is not sufficient to overcome the "break free" force, then the sprocket collar is not able to free wheel on the axle housing.

The free wheeling clutch mechanism is self-adjusting under the bias force to accommodate for the reduction in thickness of the braking material 70 wearing out through use. The clutch plates 68 "float" on the axle housing to adjust and maintain contact with the sprocket collar as the braking material becomes thinner.

Particular embodiments of the free wheeling clutch mechanism are described in more detail below.

An exercise bicycle 42 incorporating the present invention is shown in FIG. 1. The bicycle includes a frame 80 supported on a support surface by ground engagement members 82, an adjustable seat 84, adjustable handlebars 86, a flywheel 44 rotatably positioned between a pair of front forks 88 of the frame, and a gear train 54 attached to the frame adjacent to and below the seat.

The frame 80, as shown in FIG. 1, includes front and rear ground supports 90 attached by a horizontal frame brace member 92 extending there between, front forks 88, and a rear post 94. The front forks and rear post are attached by an articulated beam 96 sloping from the top of the front forks down to approximately midway between the front forks and the rear post, at which point the articulated beam extends horizontally rearwardly to engage the rear post. The articulated beam thus includes two members connected at an angle to one another, and extends between the top of the forks to the approximate midpoint of the rear post.

An aperture is formed at the top of the forks to receive a handlebar post 98, the handlebar post being vertically adjustable in the top of the forks by a pop-pin structure, as

is known in the industry. Handlebars are attached to the top of the handlebar post in any known manner for use by the rider. An aperture is formed in the top of the rear post for receiving a seat post **100**. The seat post is vertically adjustable in the rear post by a pop-pin structure, as is well known in the art. The seat can be forwardly and rearwardly adjusted on the seat post, such as by the mechanism disclosed in U.S. Pat. No. 4,772,069 to Szymiski, incorporated herein by reference, in addition to being vertically adjustable.

The rear post **94** includes a top member **102** and a bottom member **104**. The top member **102** is attached to extend from the rear side of the bottom member **104**, and extends beyond the top of the bottom member **104** in a rear-offset overlapping manner. The articulated beam **96** is affixed to the rear post **94** at the top of the bottom member **104** and the front side of the top member **102**. This attachment of the articulated beam to the rear post forms a strong structural connection.

The crank arms **48** for each of the pedals **50** are attached to a hub **106** which is supported by the rear post at a location along the height of the rear post where the bottom and top members of the rear post coextend. The rear post **94** attaches to the horizontal frame member **92** about midway between the front and rear ground support members **90**. A rear truss **106** extends at an angle from the rear post **94** down to the rear ground support member **90** for added strength. The frame is constructed of rectangular or hollow cylindrical steel tubing, as is known in the art. Rectangular tubing is preferred.

The front area defined by the forks **88**, articulated beam **96**, rear post **94**, and horizontal frame member **92** is a five-sided polygon. The rear area defined by the rear post **94**, rear truss **106** and horizontal frame member **92** is also a five-sided polygon. A friction break **108** is mounted adjacent to the top of the front forks to selectively engage the opposing outer rims of the flywheel **44** to provide an additional friction load against which the rider must work in exercising on the exercise bicycle. This frame design, to the geometry of the frame structure, is very strong and durable, and is capable of withstanding the rigors of frequent use. The portion of the frame that supports the crank arms and chain ring is especially strong and durable in this design as a result of the overlapped construction of the rear post **94**.

As shown in FIGS. **1**, **2** and **3**, the drive or gear train (as described above) includes a drive sprocket **46** rotatably mounted on the frame, crank arms **48** and associated pedals **50** attached to the drive sprocket for driving the drive sprocket, a free wheel clutch assembly **40**, a slave sprocket **54** attached on the flywheel **44**, and a chain **56** connecting the drive sprocket to the slave sprocket, and to the free wheel clutch assembly. The chain could be replaced by a belt with accommodating modifications made to the drive and slave sprockets, with no adverse affect on the operation of the free-wheeling clutch mechanism of the present invention.

As with a standard direct drive exercise bicycle, the rider pedals the exercise bicycle using the crank arms and pedals, to drive the drive sprocket **46**. The chain **56**, engaged between the drive sprocket and slave sprocket **54**, causes the flywheel **44** to rotate at the given rpms based on the gear ratio between the drive sprocket and the slave sprocket.

The free wheel clutch mechanism **40** engages the flywheel, as is described below, to allow the transfer of rotational movement from the slave sprocket **54** to the flywheel **44** in a direct-drive relationship when driven in the forward direction. Normal pedaling circumstances include the use of the exercise bicycle during an organized exercise

class or individually, and include starting at 0.00 rpms and increasing and decreasing the rpms as is required or desired for certain exercise programs, whether the rider is standing, sitting or alternating during use. The free wheel clutch mechanism **40** of the present invention maintains the "pedal-through" benefit of standard direct drive exercise bicycles. The pedal-through benefit helps the rider pedal continuously and smoothly through the top and bottom pedal positions where riders typically are weakest.

The free wheel clutch mechanism **40** converts the direct drive relationship between the pedal revolutions and the flywheel revolutions to a "free wheel" relationship to allow the pedals **50** to be stopped, reversed in direction, or rotated more slowly than the flywheel **44**, when a sufficient force is applied in the reverse direction to either of the pedals or anywhere on the drive train (where the clutch mechanism is positioned on the inertia wheel). Examples of the application of an opposite force include, but are not limited to, the intentional application of the reverse force by the rider while pedaling, for instance due to fatigue, or the contact of the pedal on the rider's lower leg when a foot is accidentally released from the pedal.

As shown in FIGS. **4**, **5A**, **5B**, **6** and **7**, the free wheel clutch mechanism **40** mounts on the slave axle assembly **60** adjacent to the hub **62** of the flywheel **44**. A cylindrical slave axle housing **64** is press-fit into a cylindrical axial bore formed through the hub **62** of the flywheel. The end of the axle housing extending from the hub is externally threaded to receive the clutch plate collar **69**.

In the description below, the terms "inside" and "inner" refer to the end closest to the flywheel **44**, and the terms "outside" and "outer" refer to the end farthest from the flywheel. The clutch plate collar **69** includes a hollow cylindrical main body **118** with internal threads at one end for engagement with the external threads on the outer end of the axle housing **64**. The clutch plate collar **69** has an outer radially extending engagement flange **120** attached to the outside end of the cylindrical main body **118**, and an inner radially extending engagement flange **122** moveably attached to the inside end of the cylindrical main body.

Referring to FIGS. **5A** and **5B**, the inner flange **122** is able to move axially (longitudinally) along the all or a portion of the length of the cylindrical main body **118** of the clutch plate collar **69**. Referring to FIGS. **7**, **8** and **9**, the inner flange **122** has a central bore **124**, defining a plurality of radially inwardly extending keys **126**. Corresponding longitudinally extending slots **128** are formed on the surface of the cylindrical main body of the clutch plate collar **69** at its inner end, and extend at least partially along the length of the main body, to receive the keys **126** and allow the inner flange **122** to move (float) axially along the length of the cylindrical main body, to the extent of the length of the slots. The benefit of the axial movement of the inner flange of the clutch plate collar **69** is described in more detail below. When the cylindrical main body **118** is threadedly connected to the axle housing **64**, the inner flange is positioned so the keys are slidably received in the slots, and the inner flange is retained on the end of the cylindrical main body by the hub **62** or the axle housing (by end of axle housing as shown in FIG. **5A**). The intersection of the keys **126** in the slots **128** make the inner flange turn with the cylindrical main body **118**.

A one-way bearing **66**, such as an INA shell-type roller clutch as found in the INA Bearing Company, Inc. of Fort Mill, S.C., catalog #305, 1988 at page 164, is mounted on the cylindrical main body **118** of the clutch plate collar **69** between the end of the slots **128** and the outer flange **120**.

The rollers of the bearing **66** engage the outer surface of the cylindrical main body member **118**, and can slide (float) along the length of the main body, as described in more detail below. The one-way bearing permits direct-drive in one direction, and free-wheeling in the other rotational direction, also described in more detail below.

Referring to FIGS. **5A**, **7**, and **10–13**, a sprocket collar **58** defines a central bore and is positioned concentrically over the cylindrical main body member **118** of the clutch plate collar **69**, and is attached to the outer race of the one-way bearing. The sprocket collar **58** defines an outer radially extending engagement collar **130** spaced away but substantially coextensive with the outer flange **120** of the clutch plate collar **69**, an inner radially extending engagement collar **132** spaced away from but substantially coextensive with the inner flange **122** of the clutch plate collar **69**, and the slave sprocket **54** formed about the outer surface of the sprocket collar **58** and between the inner and outer extending collars **130** and **132**. The chain **56** engages the slave sprocket **54**. The engagement collars **130** and **132** are extensions of the sidewalls of the sprocket collar, and provide more surface area if needed for the clutch-function they perform, as defined below.

The following explains the relative movement and drive characteristics of the clutch plate collar **69**, sprocket collar **58**, and flywheel **44** with the structure described at this point. When the slave sprocket **54** is driven in the forward direction (clockwise with respect to FIG. **3**, counter-clockwise with respect to FIGS. **1** and **2**) by the chain **56**, the one-way bearing **66** engages and causes the the slave sprocket **54** to rotate the sprocket collar **58**, in turn rotating the clutch plate collar **69**, which in turn rotates the axle housing **64**, which causes the flywheel to turn. If the slave sprocket **54** is caused to move in the opposite direction (counter-clockwise in FIG. **3**, clockwise in FIGS. **1** and **2**), the one-way bearing would allow the sprocket collar **58** to free-wheel on the clutch plate collar **69**.

Ideally a friction clutch or braking material **70** in the form of a flat washer (a disk with a central aperture formed therein) is positioned between the outer flange **120** of the clutch plate collar **69** and the outer collar **130** of the sprocket collar **58**, and between the inner flange **122** of the clutch plate collar **69** and the inner collar **132** of the sprocket collar, as best shown in FIGS. **5A**, **5B**, and **7**. The friction clutch material **70** can be attached to either the outer flange **120** or the outer collar **130**, and the friction clutch material **70** can be attached to either the inner flange **122** or the inner collar **132**, to anchor the clutch material. The clutch material **70** can be felt, cork, standard brake material, or any material that provides a sufficient frictional relationship between the coextensive flanges and collars. Preferably, clutch facing, as shown in McMaster-Carr Company catalog number 101, 1995, at page 2530, is used at a thickness of approximately 2.0 mm. Insert description for collar for inside diameter for free-floating and not connected to either side. In some instances, such as when the clutch material is not attached to either the clutch plate collar or the sprocket collar, but instead just floats between the two, a bearing washer is attached to the perimeter of the central aperture to help support the clutch material on the axle housing.

Compression means, such as a compression spring **72**, is positioned around the hub **62** of the flywheel **44** to engage the inner flange **122** of the clutch plate collar **69** to bias the inner flange toward the outer flange **120** of the clutch plate collar. The spring **72**, such as a jumbo compression spring in the McMaster-Carr catalog number 101, biases the inner flange **122** outwardly to clamp the clutch material **70**

between it and the inner collar **132**, and also clamps the clutch material **70** between the outer collar **130** and the outer flange **120**. The designed axial movement of the inner race (such as by sliding) on the cylindrical main bearing **66** (keys **126** sliding in the slots **128**) allows the sprocket collar **58** to float and transmit the force of the spring **72** to the outer flange **120**. The combination of the bias force created by the spring **72**, and the engagement of the clutch plate collar **69** and the sprocket collar **58** with the clutch material **70** inbetween creates a friction force having an upper limit (“break free”) force required to cause the sprocket collar **58** to move independently of the clutch plate collar in the reverse direction.

For instance, where the spring force is approximately 225 pounds when fully compressed, and the clutch material has an inner diameter of 1.65 inches and an outer diameter of 2.52 inches, where two clutch material disks were used (FIG. **5B**), the break free force has been tested to be approximately 55 pounds at the pedal. It has been found that as the spring extends due to wear of the clutch material, the spring force reduces to approximately 200 pounds, and the break free force actually increases. This is believed to be due to the fact that the engaging surfaces clamping the clutch material become polished and increase the surface area, thus increasing the static friction force to be overcome.

The following explains the relative movement of the clutch plate collar **69**, sprocket collar **58** and flywheel **44** given the structure described to this point. When the slave sprocket **54** is driven in the forward direction, as defined above, the one-way bearing creates the direct-drive relationship with the flywheel **44** desired for this type of exercise bicycle. When the slave sprocket **54** is driven in the backward direction, or there is a reverse force applied to the slave sprocket to attempt to rotate it in a direction opposite the direction of rotation of the flywheel, the one-way bearing does not drive the flywheel **44**, but instead allows the pedals to free wheel. However, the friction force generated between the clutch plate collar **69** and the sprocket collar **58** due to the engagement of the outer flange **120** and the outer collar **130** with the inter-positioned clutch material **70**, and the inner flange **122** and inner collar **132** with the inter-positioned clutch material **70**, acts to create a threshold friction force that must be overcome to allow the rider to drive the sprocket collar **58** independent of the flywheel **44**. If the force applied by the rider to the pedals is large enough to overcome the friction (“break free”) force, then the pedals cause the sprocket collar **58** to turn independently of the clutch plate collar **69**, with the clutch material **70** being rubbed and worn down in the process.

As the clutch material **70** wears down and becomes thinner, the spring **72** extends to push the inner flange **122** (floating) along the slots to maintain the appropriate force on the clutch material **70**. The sprocket collar **58** is also pushed outwardly to maintain the desired force, and resulting “break free” characteristics. The spring **72** thus allows for automatic adjustment to compensate for the wear of the clutch material **70**. The spring **72** must be selected to have a relatively predictable and stable spring constant along its length of extension to insure the development of the proper friction forces. The spring can be replaced with an elastomeric tube **73** having sufficient spring properties in the axial direction, such as is shown in FIG. **5C**. Some elastomeric materials have very stable spring constants. One such suitable elastomeric material is a polyurethane made by Kryptonics Inc. of Louisville, Colo. Preferably, the tube **73** is approximately 1 inch long, 0.887 inches when initially compressed, and has a wall thickness of approximately 0.225 inches. In addition,

an adjustable compression spring could also be used that would allow the spring force to be adjusted to modify the break free force when desired.

The inner or outer clutch material **70** can be replaced by a bearing if it is desired to use only one clutch material **70**. The break-free force threshold may be modified accordingly as a result.

Similar relative movement is found when the exercise bicycle incorporating the present invention is in use, and more clearly depicts the advantages of the free wheel clutch mechanism of the present invention. When a rider is exercising on the exercise bicycle, the forward drive of the drive train causes the slave sprocket **54** to drive the sprocket collar **58** in the direction of engagement of the one-way bearing, in the end to drive the flywheel **44** in a direct drive manner. If the rider desires, by applying a force of approximately 50 pounds in the opposite direction, the threshold friction force between the clutch plate collar **69**, the sprocket collar **58** and the clutch material **70** is overcome (the "break free" force), and the sprocket collar **58** can free wheel with respect to the clutch plate collar **69** and the flywheel **44**. The sprocket collar **58** thus moves in the opposite direction with respect to the direction of rotation of the flywheel **44**. The rider can thus pedal irrespective of the movement of the flywheel **44** until the friction between the clutch plate collar and the sprocket collar (caused by the clutch material) reduces the rpms of the flywheel to a point where, based on the gear ratio, the rpms match to cause "lock-up".

In a more extreme situation, if the foot of the rider slips off the pedal and the pedal strikes the rider's leg, a sufficient force is generated to overcome the "break free" force and the pedals can stop to reduce the chance of serious injury, letting the flywheel continue to rotate until the friction force stops the rotation of the flywheel.

An axle **134** (FIG. 5A and 5B) is positioned associated in the hub, with associated bearings to support the flywheel **44** and allow it to rotate as driven by the gear train.

The one-way bearing is not necessary for the application to work on an exercise bicycle. However, without the one-way bearing the sprocket collar would "free wheel" in the forward direction too when the drive force was greater than the "break free" force, thus limiting the amount of force the rider could apply while pedaling the bicycle in the forward direction.

The one-way bearing **66** can be replaced by a spring-loaded ratchet and pawl drive mechanism found in normal bicycle applications, or other one way drive mechanisms that can functionally replace the one-way bearing described above. One such suitable commonly available ratchet and pawl mechanism is the LMA-8 from the LIDA Machinery Company, Ltd. of Taoyuan, Taiwan, as shown in the Taiwan Bicycle Source 1997-98 catalog at p. 370.

FIGS. 8 through 16 show details of some of the components described above.

An alternative embodiment of the free wheel clutch mechanism is shown in FIGS. 17-20. This alternative embodiment works on the same principle as the first embodiment described above, except basically replaces the single large spring surrounding the hub **150** with the plurality of smaller springs **152** positioned between the flywheel **154** and the inner clutch plate **156**. These plurality of springs **152** act to push the inner clutch plate **156** outwardly as the clutch material **158** wears down from use. As can best be seen in FIGS. 19 and 20, each of the plurality of springs surrounds a guide rod **160** mounted to the flywheel **154** which is received in a guide bore **162** mounted to and

extending from the inside side of the inner clutch plate **156**. The sliding interaction between the guide rod **160** and the guide bore **162** helps ensure that the inner clutch plate **156** is squarely moved outwardly under the bias of the springs as the clutch material wears as a result of use. The interaction of the guide rod with the guide bore also causes the inner clutch plate **156** to turn with the flywheel **154** because the guide rods are laterally fixed in position inside the guide bores, and as the guide rods turn with the movement of the flywheel, they cause the inner clutch plate to turn also.

The axle housing **164** is press-fit into the hub **150** and extends from the flywheel **154**, and has an outer end **166** with external threads. After the inner clutch plate **156** and associated compression springs **152** are mounted over the axle housing and positioned adjacent the hub, the slave gear collar **170** is positioned to engage the outer surface of the axle housing **164** as in the previous embodiment, including having the same bearing structure **172**. The slave gear collar has an inner surface **174** adjacent the outer surface **176** of the inner clutch plate, between which is positioned an inner clutch material washer **178**. The inner clutch material washer **178** is preferably fixed to either the outer surface of the inner clutch plate **156** or the inner surface of the slave gear collar **170**. A set of gear teeth **180** are formed about the outer circumference of the slave gear collar **170** for receiving the chain used to drive the flywheel.

The outer clutch plate **182** (or anchor plate) is then threaded on to the externally threaded outer end **184** of the axle housing. An outer clutch material washer **186** is positioned between the outer surface of the slave gear collar **170** and the inner surface of the outer clutch plate **182**. Preferably, the outer clutch material washer **186** is fixed to either the outer surface of the slave gear collar **170** or the inner surface of the outer clutch plate **182**. The outer clutch plate is fixed to the axle housing by a lock-nut **188** to keep the outer clutch plate from turning loose under the force of the free wheel mechanism.

This alternative embodiment of the present invention operates in fundamentally the same manner as the previously described embodiment. When a reverse force is applied to the drive train, normally through a reverse force being applied to the pedals, and this reverse force overcomes the "break free" force, the slave gear overcomes the friction force between the slave gear collar **170** and the outer clutch plate **182** and inner clutch plate **156** which rotate with the flywheel **154**. This allows the flywheel to continue spinning while the drive train is either stopped, pedaled backwards, or pedaled more slowly than the flywheel is spinning. The bearings **172** connecting the slave gear collar **170** to the axle housing **164** are one-way bearings as described above, and when the drive train is actuated in the normal or forward direction, the bearings lock and act as a direct drive connection between the drive train and the flywheel.

When turned in the reverse direction, the bearings **172** allow the slave gear collar **170** to free-wheel, the free wheeling of which is restricted by the frictional engagement of the slave gear collar **170** with the surrounding clutch material **178**, **186**. The compression springs **152** apply the force to the inner clutch plate **156** which presses the inner clutch material **178** against the slave gear collar. The slave gear collar **170** can move longitudinally on the axle housing **164** (the bearing allows small amounts of movement in this direction) and thus transmits a force to the outer clutch material **186**, and finally to the outer clutch plate **182**. As the inner or outer clutch material wears down, the springs **152** extend and push the inner clutch plate **156** outwardly and thus maintain the contact necessary for the frictional engage-

13

ment between the inner clutch plate **156**, the inner clutch material **178**, the slave gear collar **170**, the outer clutch material **186**, and the outer clutch/anchor plate **182**.

FIG. **20** shows the adjusted relationship of the structure of this alternative embodiment when the inner and outer clutch material washers **178**, **186** have worn down. Contrasting FIGS. **19** and **20**, note the gap between the inner clutch plate **156** and the outer end of the hub **150**. The bearings **172** allow the slave gear collar **170** to move longitudinally on the axle housing **164**. Either one of the inner or outer clutch materials **178**, **186** can be replaced with a bearing if it is determined that they are unnecessary.

Another alternative embodiment is shown in FIGS. **21–23**. In this alternative embodiment a Belleville washer **200** is mounted on the end of the axle housing **202** to bias the outer clutch plate **204** inwardly to create the desired friction force between the slave gear collar **206** and the outer and inner clutch plates **204**, **208** through the inner and outer clutch material washers **210**, **212**. In the second alternative embodiment a retainer **214** having an outwardly flanged inner end **215** is threaded on to the end of the axle housing **202** extending from the hub **216**, which has external threads. The outwardly extending flange **215** of the retainer butts up against the hub **216**. The inner clutch plate **208** is then positioned next to the outwardly extending flange **215** and is retained in rotational position therewith by keys in slots or by any other suitable attachment method, such as welding (as shown in FIG. **22**). Alternatively, the outwardly extending flange can act as the inner clutch plate.

An inner clutch material washer **210** is positioned adjacent to and in contact with the inner clutch plate **208**, and the slave gear collar **206** is mounted over the cylindrical body of the retainer **214**. The slave gear collar **206** is similar to the slave gear collars described in the previous two embodiments and includes a bearing **218** positioned between the slave gear collar **206** and the outer circumference of the retainer **214**, the bearing **218** being a one-way bearing allowing the slave gear collar **206** to free-wheel when turned in a reverse direction, and locking to provide a direct drive when turned in the forward direction. Gear teeth **220** are formed on the outer circumference of the slave gear collar **206** for engagement with the chain of the drive train. An outer clutch plate **204** is positioned over the outer circumference of the retainer **214**. As shown in FIG. **23**, the outer clutch plate **204** defines a central bore **222** having at least one key **224** formed for mating insertion into a corresponding slot formed in the retainer **214**. The mating key and slot relationship between the outer clutch plate **204** and the retainer **214** makes the outer clutch plate turn with the flywheel because the retainer turns with the flywheel **226** and the rotational interference between the key and the slot causes the outer clutch plate **204** to turn also, in addition to allowing the outer clutch plate to float or move inwardly and outwardly with respect to the inner clutch plate **208** along the body of the retainer as the friction clutch material **210**, **212** wears down.

The Belleville washer **200** is positioned about the end of the axle housing to engage the outer clutch plate **204** with the bias force. The bias force is created by an outer retainer **228** which defines a cylindrical main body **230** having external threads and an outwardly extending flange **232** at one end. The outer end of the axle housing **202** defines internal threading **234** such that the cylindrical main body **230** of the outer retainer **228** threads into the outer end of the axle housing **202** to the point where the outwardly extending flange **232** abuts the outer end of the axle housing and also engages the inner rim of the Belleville washer **200** to

14

compress the Belleville washer against the outer clutch plate **204**. The compression of the Belleville washer **200** against the outer clutch plate **204** causes the outer clutch plate to be biased inwardly against the outer friction clutch material **212**, which is pushed against the slave gear collar **206**, which in turn is allowed to relatively float on the outer surface of the inner retainer **214** to push against the inner clutch material **210** and in turn frictionally engage the inner clutch plate **208**.

As the slave gear collar **206** is driven in the forward direction by the drive train, the one-way bearings **218** lock and create a direct drive relationship. When a sufficient reverse force is applied to the slave gear collar through the drive train, the one-way bearings release and allow the drive train collar to free-wheel under the influence of the frictional relationship with the inner and outer clutch plates, similar to the interaction as described with respect to the embodiments above.

As the clutch material **210**, **212** wears down and becomes thinner, the Belleville washer **200** extends to continue to create a friction force in the clutch system by pushing the outer clutch plate **204** towards the inner clutch plate **208**, thereby clamping the inner and outer clutch material and the slave gear collar **206** therebetween.

Another alternative embodiment is disclosed in FIG. **24** which shows two Belleville washers **240**, **242** positioned back to back to allow for a longer adjustment stroke due to the wear of the inner and outer clutch material washers **244**, **246**. In this third embodiment the outwardly extending flange **248** of the second retainer **250** is enlarged to engage the outer rim of the second Belleville washer **240**. Belleville washers are very stiff and provide a great deal of force through the length of their extension.

Another alternative embodiment is disclosed in FIGS. **25–26**. This fourth alternative embodiment utilizes a band-brake to create the frictional break-free force. The band-brake **260** includes a retainer **262** fixed to the flywheel **264** through which is positioned a spring loaded adjustment screw **266** which attaches to a housing **268**. The housing includes two guide slots **270** for slidably receiving tabs **272** formed on the flywheel. The housing is also fixed to the opposite ends of a belt **274**. The slidable engagement of the guide slots **270** on the tabs **272** help ensure a properly oriented adjustment of the band-brake by the spring loaded screw. The slots are formed in the housing of the band-brake, the housing being attached to a belt, with the band-brake material **276** attached to the inside surface a reinforcement sheathing **278** of the belt (as best seen in FIG. **26**). The tabs, spring loaded threaded screw, housing and belt are all fixed to rotate with the flywheel. The spring surrounding screw **266** makes the system self-adjusting for wear of the band material by applying a preferably constant tension load on the belt through the housing. The selection of the spring constant properties of the spring determines the amount of tension on the belt, and the amount of adjustment (displacement) the band-brake can accommodate.

As best shown in FIG. **26**, the slave gear collar **280** defines an annular axial extension **282** which fits over a portion of the hub **284** without contacting the hub. This annular extension **282** defines an inner rim **286** and an outer rim **288**, between which is an engagement surface **290**. The band contacts the engagement surface **290** between the inner rim and the outer rim. The slave gear collar **280** includes the same bearing system as previously described for one-way engagement with the outer surface of the axle housing **292**. The proper positioning of the slave gear collar **280** is

15

maintained on the axle housing by a large washer 294 which is tightly pressed against the outer surface of the slave gear collar by a nut 296 to keep the slave gear collar from becoming imbalanced. A second set of one-way bearings could be positioned between the annular extension 282 from the slave gear collar and the outer surface of the hub over which the slave gear collar annular extension is positioned.

As the drive train is actuated in the forward direction by the rider, the one-way bearing 298 between the slave gear collar 280 and the axle housing 292 engages to cause a direct drive relationship between the drive train and the flywheel, as in the previously described embodiments. In the event a sufficient reverse force is applied to the slave gear collar through the drive train, the one-way bearing 298 releases and allows the slave gear collar to free-wheel subject to the frictional engagement of the slave gear collar and the belt 274. The engagement surface 290 is in frictional engagement with the belt to create the "break free" force. The "break free" force is determined by the tightness of the belt around the engagement surface on the annular extension 282 of the slave gear collar. This "break free" force resists the free wheeling of the slave gear collar on the axle housing 292 and provides the beneficial pedal-through feature of traditional direct drive exercise bicycles. It also allows the drive train to free-wheel when a sufficient reverse force is applied to the drive train, likely through the pedals and cranks, to allow the drive train to be driven at a relatively lower RPM than the flywheel, depending on the gear ratio.

As the frictional brake material 276 wears down, the housing 268 is adjusted by tightening the screw 266 to move the housing, and thus tighten the belt 274 around the annular extension 282 of the slave gear collar 280 to maintain the desired frictional engagement, resulting in the desired "break free" force.

Another alternative embodiment is shown in FIGS. 27-29. In this embodiment, the slave gear collar 300 has the same structure as the previous embodiment described, and is held in engagement with the axle housing 302 in the same manner. A compression brake housing 304 is mounted in engagement with the flywheel 306 and includes means 308 for causing engagement of arcuate compression members 310 with the engagement surface 312 on the slave gear (sprocket) collar annular extension 314, between the inner and outer rims 316, 318. The arcuate compression members 310 have a hard backing 320 and a frictional clutch material 322 mated to their inner concave surface for engagement with the slave gear collar annular extension 314. The brake housing 304 includes means 308 for radially adjusting the compression of the compression members against the annular extension 314, such as set screws which are threadably adjustable through the brake housing to engage the hard back surface 320 of the arcuate compression members 310 to press the frictional material 322 of the compression members against the engagement surface 312 of the annular extension. These means can be self-adjusting to accommodate wear of the friction material, such as by being spring-loaded set-screws. As the frictional clutch material wears down, the set screws 324 can be used to maintain the proper compression of the compression members 310 against the engagement surface 312, which creates the desired "break free" force.

This embodiment operates in the same manner to allow a break free clutch mechanism on the flywheel as the previously described embodiments. The brake housing 304 is held in rotational fixed orientation with the flywheel by a pin 326 positioned through a slot 328 in the brake housing. The movement of the pin in the slot allows for uneven wear of the compression members 310.

16

Another alternative embodiment is shown in FIG. 30. Only one side, the inner side 329 as shown, of the sprocket collar 330 is used to create a frictional engagement with an engagement flange 332 attached to the axle housing 334 at the hub 336 of the flywheel 338. The sprocket collar is positioned on a sheath 333 threadably engaging the axle housing 334 at the hub 336, with a one-way bearing 337 (or ratchet and pawl mechanism) positioned between the sprocket collar and the sheath 333 for the same purpose as disclosed above with many of the other embodiments. Clutch material 340 is positioned between the side 329 of the sprocket collar 330 and the engagement flange 332, and can be attached to either one, to create the frictional engagement therebetween. The engagement flange is moveable along the axle housing of the hub to allow the friction force to be kept at a relatively constant level as the clutch material wears out. This self-adjustment, as described above, occurs when the spring 342, or other means, presses the engagement flange outwardly from the hub to clamp the clutch material against the inner side 329 of the sprocket collar 330. The sprocket collar 330 is supported on the inner and outer sides by an inner 344 and outer 346 bearing, respectively. The inside edge 335 of the sheath forms the outer race for the inner bearing 344, while the sprocket collar forms the inner race for both the inner 344 and outer 346 bearings. The outer race 348, or cone, threadably engages the outer end of the sheath 333 to hold the sprocket collar 330 in place and provide a thrust bearing against which the spring 342 pushes.

It is contemplated that these free wheel clutch mechanism structures described herein could be mounted on the drive sprocket of the drive train, in addition to the slave sprocket of the drive train. It is also contemplated that a one-way bearing need not be used in all circumstances, in which case the clutch mechanism would be caused to slip if the break-free force threshold was reached in either the forward or rearward drive-train direction.

Presently preferred embodiments of the present invention and many of its improvements have been described with a degree of particularity. The previous description is of preferred examples for implementing the invention, and the scope of the invention should not necessarily be limited by this description. The scope of the present invention is defined by the scope of the following claims.

We claim:

1. An exercise bicycle comprising:

a frame, including a seat and handlebars;

a high-inertia flywheel having a hub at a center of rotation, the flywheel being rotatably supported on the frame at the hub;

a drive train, including a drive sprocket, a crank arm attached to and extending from the drive sprocket, and a pedal attached to the crank arm, the drive train being rotatably supported by the frame, and a slave sprocket fixed to the flywheel at the hub, with the drive and slave sprockets connected in a direct-drive relationship, the drive train driveable in a forward and rearward directions to cause the flywheel to rotate;

a clutch positioned in engagement with the slave sprocket and the hub creating a frictional engagement between the sprocket and the hub, and creating a break-free force; and

wherein when said drive train is actuated in the forward direction, the slave sprocket and the hub move together, and when the drive train is actuated in the rearward direction and overcomes the break-free force, the clutch slips between the slave sprocket and the hub,

17

allowing the slave sprocket and the flywheel to move independently of one another.

2. An exercise bicycle as defined in claim 1, wherein:

the slave sprocket defines a sprocket collar mounted on the hub and defines an engagement collar;

a one-way bearing mounted between the sprocket collar and the hub to allow the sprocket collar to drive the hub when the sprocket collar is driven in a forward direction, and to allow the sprocket collar to spin independently of the hub when the sprocket collar is driven in the rearward direction;

an engagement flange fixedly mounted on the hub corresponding to the engagement collar;

compression means mounted on said flywheel to bias the flange and the collar towards one another;

a clutch material member positioned between said engagement flange and said collar, and clamped therebetween by the compression means to cause the engagement flange to move in conjunction with the sprocket collar, the engagement creating a break-free force required to cause the sprocket collar to move independently of the engagement flange; and

wherein, when said drive train is actuated in the forward direction, the sprocket collar and the engagement flange move together, and when the drive train is actuated in the rearward direction and overcomes the break-free force, the engagement flange slips with respect to the collar, allowing the sprocket collar and the flywheel to move independently of one another.

3. An exercise bicycle as defined in claim 1, wherein:

the slave sprocket defines a sprocket collar mounted on the hub and defines an inner and outer engagement collars;

a one-way bearing mounted between the sprocket collar and the hub to allow the sprocket collar to drive the hub when the sprocket collar is driven in a forward direction, and to allow the sprocket collar to spin freely on the hub when the sprocket collar is driven in the rearward direction;

an inner engagement flange fixedly mounted on the hub corresponding to the inner engagement collar, and an outer engagement flange fixedly mounted on the hub corresponding to the outer engagement collar;

compression means mounted on said flywheel to bias the inner flange and the inner collar towards one another, and to bias the outer flange and the outer collar towards one another;

a clutch material member positioned between said outer engagement flange and said outer collar, and between said inner engagement flange and said inner collar, and clamped therebetween by the compression means to cause the inner and outer engagement flanges to move in conjunction with the sprocket collar, the engagement creating a break-free force required to cause the sprocket collar to move independently of inner and outer engagement flanges; and

wherein, when said drive train is actuated in the forward direction, the sprocket collar and the inner and outer flanges move together, and when the drive train is actuated in the rearward direction and overcomes the break-free force, the inner and outer engagement flanges slip with respect to the inner and outer collars, allowing the sprocket collar and the flywheel to move independently of one another.

4. An exercise bicycle as defined in claim 2, wherein said compression means is a belleville washer.

5. An exercise bicycle as defined in claim 2, wherein said compression means is a plurality of belleville washers.

18

6. An exercise bicycle as defined in claim 5, wherein said compression means is two belleville washers positioned back-to-back.

7. An exercise bicycle as defined in claim 2, wherein said compression means is an elastomeric material.

8. An exercise bicycle as defined in claim 3, wherein said compression means is a belleville washer.

9. An exercise bicycle as defined in claim 3, wherein said compression means is a plurality of belleville washers.

10. An exercise bicycle as defined in claim 8, wherein said compression means is two belleville washers positioned back-to-back.

11. An exercise bicycle as defined in claim 3, wherein said compression means is an elastomeric material.

12. An exercise bicycle as defined in claim 1, wherein: the slave sprocket defines a sprocket collar mounted on the hub including an engagement collar;

a one-way bearing mounted between the sprocket collar and the hub to allow the sprocket collar to drive the hub when the sprocket collar is driven in a forward direction, and to allow the sprocket collar to spin independently on the hub when the sprocket collar is driven in the rearward direction;

a band brake fixedly mounted on the flywheel, the band brake having a belt attached to a housing, the belt frictionally engaging the engagement collar which causes the flywheel to move in conjunction with the sprocket collar, and creating a break-free force required to cause the belt to slip on the engagement collar allowing the sprocket collar to move independently of the flywheel; and

wherein, when said drive train is actuated in the forward direction, the sprocket collar and the flywheel move together, and when the drive train is actuated in the rearward direction and overcomes the break-free force, the band slips with respect to the engagement collar, allowing the sprocket collar and the flywheel to move independently of one another.

13. An exercise bicycle as defined in claim 1, wherein:

the slave sprocket defines a sprocket collar mounted on the hub including an engagement collar;

a one-way bearing mounted between the sprocket collar and the hub to allow the sprocket collar to drive the axle when the sprocket collar is driven in a forward direction, and to allow the sprocket collar to spin independently on the axle when the sprocket collar is driven in the rearward direction;

a compression brake fixedly mounted on the flywheel, the compression brake having an arcuate compression member frictionally engaging the engagement collar which causes the flywheel to move in conjunction with the sprocket collar, and creating a break-free force required to cause the arcuate compression member to slip on the engagement collar allowing the sprocket collar to move independently of the flywheel; and

wherein, when said drive train is actuated in the forward direction, the sprocket collar and the flywheel move together, and when the drive train is actuated in the rearward direction and overcomes the break-free force, the arcuate compression member slips with respect to the engagement collar, allowing the sprocket collar and the flywheel to move independently of one another.

14. An exercise bicycle as defined in claim 1, wherein said clutch is self-adjusting.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 5,961,424
DATED : October 5, 1999
INVENTOR(S) : Patrick Warner et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page,

Item [56], **References Cited**, U.S. PATENT DOCUMENTS, insert -- 4,673,177, 06/1987, Szymiski, 272/73 --.

Signed and Sealed this

Twenty-eighth Day of December, 2004

A handwritten signature in black ink on a light gray dotted background. The signature reads "Jon W. Dudas" in a cursive, stylized script. The "J" is large and loops around the "on". The "W" is written with two distinct peaks. The "D" is large and loops around the "udas".

JON W. DUDAS

Director of the United States Patent and Trademark Office