



**Related U.S. Application Data**

division of application No. 14/634,007, filed on Feb. 27, 2015, now Pat. No. 9,695,008.

(51) **Int. Cl.**

**B65H 49/20** (2006.01)  
**B65H 75/24** (2006.01)  
**B65H 49/32** (2006.01)  
**B65H 49/30** (2006.01)  
**B65H 75/30** (2006.01)  
**B65H 59/04** (2006.01)

(52) **U.S. Cl.**

CPC ..... **B65H 49/322** (2013.01); **B65H 49/325**  
(2013.01); **B65H 59/04** (2013.01); **B65H**  
**75/14** (2013.01); **B65H 75/22** (2013.01);  
**B65H 75/242** (2013.01); **B65H 75/245**  
(2013.01)

(56)

**References Cited**

**U.S. PATENT DOCUMENTS**

2,400,417 A 5/1946 Hickey  
2,952,420 A 9/1960 Von Hoorn  
2,965,331 A 12/1960 Nagy  
3,693,784 A 9/1972 Holmes  
3,836,093 A 9/1974 Mozina et al.  
4,650,073 A 3/1987 Young  
4,667,896 A 5/1987 Frey et al.  
5,139,210 A 8/1992 Schaffer  
5,464,171 A 11/1995 Ripplinger  
5,810,283 A 9/1998 Shea  
6,145,780 A 11/2000 Fontana

6,234,421 B1 5/2001 Cox et al.  
6,241,181 B1 6/2001 Campbell  
6,328,238 B1 12/2001 Chism  
7,140,598 B2 11/2006 Verakis et al.  
7,204,452 B2 4/2007 Wilkinson et al.  
7,891,601 B2 2/2011 Higashisaka et al.  
7,938,357 B2 5/2011 Johanson et al.  
D641,161 S 7/2011 Houston et al.  
D641,162 S 7/2011 Houston et al.  
D641,163 S 7/2011 Houston et al.  
8,016,222 B2 \* 9/2011 Galgano ..... B62B 1/14  
242/403  
8,230,996 B1 7/2012 Cummings et al.  
8,251,212 B2 8/2012 Dunlap  
8,366,126 B2 2/2013 Galgano et al.  
8,387,909 B2 3/2013 Galgano et al.  
8,424,795 B2 4/2013 Galgano et al.  
D686,907 S 7/2013 Chastain et al.  
9,637,343 B2 5/2017 Allwood  
9,862,566 B2 \* 1/2018 Thakare ..... B65H 75/22  
9,873,588 B2 1/2018 Thakare  
2006/0157366 A1 7/2006 Jamie  
2007/0018031 A1 \* 1/2007 Sycko ..... B65H 49/305  
242/597.4  
2010/0314484 A1 \* 12/2010 Houston ..... A45C 3/00  
242/588.3  
2010/0320309 A1 12/2010 Galgano et al.  
2012/0153069 A1 \* 6/2012 Allwood ..... B65H 49/32  
242/607  
2014/0312159 A1 10/2014 Troitzsch et al.  
2015/0312159 A1 10/2015 Ertugay et al.  
2015/0321876 A1 \* 11/2015 Galindo Gonzalez .....  
B65H 75/241  
242/611

\* cited by examiner




FIG. 1




FIG. 2





FIG. 3






FIG. 4B




FIG. 5A






FIG. 5B




FIG. 6




FIG. 7




FIG. 8

1

## METHOD OF INSTALLING CABLE ON CABLE REEL

### RELATED APPLICATIONS

This application is a continuation of co-pending, commonly owned application Ser. No. 15/433,789, filed Feb. 15, 2017, which is a Divisional of U.S. application Ser. No. 14/634,007, entitled Cable Reel, filed on Feb. 27, 2015, the disclosure of each of which is incorporated herein by reference in its entirety.

### FIELD OF THE INVENTION

The present invention relates to a cable reel and also to a method for installing cable on the cable reel preferably with a cable payoff braking mechanism.

### BACKGROUND OF THE INVENTION

Cable installers are commonly required to carry cable to installation locations. The installers usually use some type of shoulder bag or other types of packing solutions with an opening for paying out the cable. These cables are often wound on a reel to form a cable coil and packaged in a box or bag for payout during installations. The installer may, however, payout too much cable if the installer pulls too hard on the cable.

Therefore, a need exists for a cable reel that allows for easy installation of cable in a bag or the like and that prevents overpayout of the cable.

### SUMMARY OF THE INVENTION

Accordingly, the present invention may provide a cable reel that has first and second opposing flanges. The first flange has a first hub portion and the second flange has a second hub portion. The first and second hub portions are axially aligned and configured to mate with one another to support cable, such as a cable coil. The first hub portion includes an elongated wall that extends from the first flange. The elongated wall is sized to support the cable. The elongated wall defines an inner area that is configured to accept the second hub portion. The elongated wall includes a plurality of flexible segments. The second hub portion includes a truncated wall that is receivable in the inner area of the first hub portion. The truncated wall includes a tapered outer surface for engaging and expanding the plurality of flexible segments.

The present invention may also provide a cable reel that includes at least one support frame that has an outwardly extending braking gear member. The outwardly extending gear member is located off-center on the frame. A first flange has a central opening and a first hub portion that surrounds the central opening. The central opening has an internal braking gear member that engages the outwardly extending gear member of the frame, thereby rotatably coupling the at least one support frame and the first flange. A second flange opposes the first flange and has a second hub portion. The first and second hub portions are configured to mate with one another to support cable. The engagement of the gear members provides a friction for cable payoff.

The present invention may further provide a method of installing the cable, such as a cable coil, on a cable reel that includes the steps of providing a cable reel that includes first and second opposing flanges, the first flange having a first hub portion and the second flange having a second hub

2

portion, the first hub portion being longer than the second hub portion, and the first hub portion having a plurality of flexible segments; placing a cable coil over the first hub portion and on the first flange so that the first hub portion extends through the cable coil; and inserting the second hub portion inside of the first hub portion, thereby expanding the flexible segments so that the flexible segments engage the cable coil.

The present invention may yet further provide a method of installing cable on a cable reel comprising the steps of providing a cable reel that includes first and second opposing flanges where the first flange has a first hub portion and the second flange having a second hub portion and the first hub portion has one or more flexible segments; placing a cable coil over the first hub portion and on the first flange so that the first hub portion substantially extends through an inner diameter of the cable coil; and expanding the one or more flexible segments by inserting the second hub portion inside of the first hub portion so that the one or more flexible segments engage the cable coil.

The present invention may also further provide a method of installing cable on a cable reel, comprising the steps of providing a cable reel that includes first and second frames that rotatably support first and second opposing flanges, respectively, where the first flange has a first hub portion and the second flange has a second hub portion and the first hub portion has an elongated wall that defines a receiving area for a truncated wall of the second hub portion; placing a cable coil over the first hub portion and on the first flange so that the first hub portion substantially extends through an inner diameter of the cable coil; and inserting the truncated wall of the second hub portion inside of the receiving area of the first hub portion, thereby retaining the cable coil between the first and second frames such that the cable coil rotates with respect to the first and second frames, thereby allowing payout of the cable of the cable coil.

Other objects, advantages and salient features of the invention will become apparent from the following detailed description, which, taken in conjunction with the annexed drawings, discloses a preferred embodiment of the present invention.

### BRIEF DESCRIPTION OF THE DRAWINGS

A more complete appreciation of the invention and many of the attendant advantages thereof will be readily obtained as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, wherein:

FIG. 1 is a perspective view of a cable reel in accordance with an exemplary embodiment of the present invention, shown without a supporting bag or box;

FIG. 2 is a perspective view of a support frame of the cable reel illustrated in FIG. 1;

FIG. 3 is an elevational view of a flange of the cable reel illustrated in FIG. 1;

FIG. 4A is a perspective view of a first hub portion of the cable reel illustrated in FIG. 1;

FIG. 4B is a partial perspective view of the first hub portion illustrated in FIG. 4A, showing the bottom hub in cross-section;

FIG. 5A is an elevational view of a second hub of the cable reel illustrated in FIG. 1;

FIG. 5B is a perspective view of the second hub of the cable reel illustrated in FIG. 5A;

FIG. 6 is an enlarged partial perspective view of the frame illustrated in FIG. 2, showing outer gears of the frame;

3

FIG. 7 is an enlarged partial side elevational view of the flange illustrated in FIG. 3, showing the inner gears of the flange; and

FIG. 8 is an enlarged side elevational view of the frame and the flange of the cable reel illustrated in FIG. 1, showing the inner and outer gears engaged.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIGS. 1-3, 4A, 4B, 5A, 5B, and 6-8, the present invention relates to a cable reel 100 that may be carried in a conventional shoulder bag or satchel, a cardboard or plastic box, and the like 101, with an opening 103 for easy payout of cable supported on the cable reel. The cable reel 100 according to an exemplary embodiment of the present invention is designed to provide easy installation of cable C, such as a cable coil, on the reel 100 and also prevents overpayout of the cable. Because the cable reel 100 is designed to be carried by an installer, it is preferable that the components of the cable reel 100 be formed of lighter weight materials, such as plastic. Some exemplary plastic materials include polyethylene, polypropylene, ABS or other polymer products.

As seen in FIG. 1, the cable reel 100 generally includes opposing support frames 102 and 104 that rotatably support first and second flanges 106 and 108 with a hub member 110 therebetween on which the cable is held. A braking mechanism 112 is preferably provided on the reel 100 between the support frames 102 and 104 of the flanges 106 and 108 to limit overpayout of the cable. The cable reel 100 may be inserted into and supported by the payout bag or box wherein the support frames 102 and 104 are attached, preferably removably attached, to the cover and base, respectively, of the bag.

As seen in FIGS. 2 and 6, each support frame 102 and 104 includes an outer frame portion 120 with one or more cross members 122 and a middle flange support 124. The outer frame portion 120 may have a substantially square geometry. The middle flange support 124 includes an annular extension 126 (FIG. 6) that supports a first part of the braking mechanism 112. The first part of the braking mechanism may be an outwardly extending gear member 128 that includes a plurality of annularly arranged teeth 130 extending radially outwardly from the annular extension 126.

The middle flange support 124 and gear member 128 are offset or off-center on the frame such that the distance  $d_1$  (FIG. 2) to one end 132 of the frame is longer than the distance  $d_2$  (FIG. 2) to the opposite end 135 of the frame. This offset provides a gap 134, as seen in FIG. 8, in the braking mechanism 112. Indicia 136, such as a company name, may be provided on the end 132 of the frame to indicate the longer side, that is distance  $d_1$  of the frame to facilitate the orientation of the cable reel 100 in the bag or box.

Each flange 106 and 108 is preferably sized to fit within the outer frame portion 120 of its respective support frame 102 and 104 and is sized to accommodate the cable, such as a cable coil. The cable coil may be, for example, having an outer diameter of 345 mm and an inner diameter of 200 mm and a height of 135 mm. The flanges 106 and 108 are preferably disc-shaped. Each flange has inner and outer surfaces 140 and 142 and a central arbor opening 144. The inner surface 140 of each flange abuts the hub member 110 and the outer surface 142 abuts a respective support frame 102 and 104.

4

The central arbor opening 144 corresponds to the middle flange support 124 of each respective support frame. The central arbor opening 144 supports the second part of the braking mechanism 112 as seen in FIGS. 3 and 7. The second part of the braking mechanism 112 may be an internal gear member 146 that includes a plurality of annular arranged teeth 148 extending radially inwardly.

The hub member 110 is located between the flanges 106 and 108 and supports the cable coil. The hub member 110 includes a first hub portion 150 (FIGS. 4A and 4B) and a second hub portion 152 (FIGS. 5A and 5B) that are axially aligned and configured to mate with one another. The hub portions 150 and 152 may be formed separately from the respective flanges 106 and 108 and attached thereto or the hub portions 150 and 152 may be formed as one-piece with the respective flanges 106 and 108.

As seen in FIGS. 4A and 4B, the first hub portion 150 is preferably the base of the cable reel and provides the main support for the cable. As such, the first hub portion 150 is larger than the second hub portion 152. The first hub portion 150 includes an elongated wall 154 that extends from the inner surface 140 of the first flange 106 and defines an inner area 156 that receives the second hub portion 152. The elongated wall 154 has a tapered outer surface 158 that tapers inwardly from the flange inner surface 140 to the free end 160 of the wall 154. Slots 162 in the elongated wall 154 create flexible segments 164, which engage both the second hub portion 152 and the cable coil to retain the same. A groove 166 (FIG. 4B) may be located at the base of the elongated wall 154 to provide additional flexibility to the segments 164. Any other mechanism may be provided to add flexibility to the segments 164. For example, the segments 164 can be made thinner.

Secondary engagement members 170 may be provided as a back-up to retain the hub portions 150 and 152 together. The secondary engagement members 170 may be, for example, one or more snap arms 172 provided in the inner area 156 that extend from the flange inner surface 140. The one or more snap arms 172 preferably extend beyond the elongated wall 154 of the first hub portion 150, as seen in FIG. 4A, in order to engage the second flange 108. The ends of the snap arms 172 preferably include snap tabs 174 that engage corresponding slots 176 (FIG. 5B) in the second flange 108. Although a snapping engagement is preferred to secure the hub portions 150 and 152 together, any known interlocking mechanism may be used.

As seen in FIGS. 5A and 5B, the second hub portion 152 includes a truncated wall 180 that extends from the inner surface 140 of the second flange 108. The truncated wall 180 has a tapered outer surface 182 that fits inside of the elongated wall 154 of the first hub portion 150 to form a friction fit between the hub portions 150 and 152 and expands the flexible segments 164 of the first hub portion 150.

As seen in FIG. 8, the braking mechanism 112 is provided by meshing the teeth 130 and 148 of the outer and internal gear members 128 and 146. The gap 134 between the teeth 130 and 148 provides clearance for the teeth to slip or jump when the cable is pulled from the reel. The gear members 128 and 146 prevent overpayout of the cable. More specifically, when the cable is pulled from the reel, the flange 106 and 108 rotate, thereby making the gear teeth 148 rotate. The side support 120 is preferably fixed inside of the supporting bag or box and therefore does not rotate. This causes the gear teeth 148 to override meshing gear teeth 130 on the side support 128 which creates friction and provides a braking to the momentum of reel if the cable is pulled too hard. This

5

action also creates a clicking mechanism which in turn prevents overpaying the cable.

The distance of the gap need only be long enough to provide a clearance to have gear teeth **148** to override teeth **130**, thereby allowing the braking mechanism to work. This clearance distance could vary depending upon the gear teeth depth, flange hole inner diameter, side support gear depth, and the outer diameter of the middle flange support **124**. The gap **134** may be, for example, about 1/4 inch.

To install the cable on the cable reel **100**, the cable coil **C** is placed over the first hub portion **150** of the hub member **110** and on the first flange **106** so that the first hub portion **150** extends through the inner diameter of the cable coil. The cable coil **C** may be prepacked in a plastic shrink wrap or with tie wraps or combination of both without any external structure to support that coil. Next the second hub portion **152** is inserted inside of the first hub portion **150** to frictionally engage the same and expand the flexible segments **164**, thereby forcing the flexible segments **164** to engage the inner diameter of the cable coil. The locking tabs **174** are then inserted inside of the slots **176** on the second flange **108** to hold two flanges and hub portions together.

In a preferred embodiment, the first support frame **102** of the reel **100** is secured to the base of the bag or box, such as by straps, such as via strap **105** (FIG. 1), and the second support frame **104** is secured to the cover or flap of the bag. With the cable coil installed on the hub member **110**, the cable coil is inserted into the bag or box between the support frames **102** and **104** in the bag or box. The assembly of the hub portions **150** and **152**, the flanges **106** and **108**, and the cable coil is preferably inserted into the base of the bag on its side such that the middle flange support **124** of the frame secured to the base of the bag fits inside of the central arbor opening **144** of the flange. Similarly, the middle flange support **124** of the frame secured to the cover of the bag fits inside of the opening **144** of the other flange when the bag is closed. Once the frames **102** and **104** are mated with the flanges **106** and **108**, respectively, the operator can then dispense or payout the cable through a cable payout slot or opening in the bag or box. The operator may open the cover of the bag or box to separate the hub portions **150** and **152** by disengaging the snap tabs **174**.

While particular embodiments have been chosen to illustrate the invention, it will be understood by those skilled in the art that various changes and modifications can be made therein without departing from the scope of the invention as defined in the appended claims.

What is claimed is:

1. A method of installing cable on a cable reel, comprising the steps of:

providing a cable reel that includes first and second opposing flanges, the first flange having a first hub portion and the second flange having a second hub portion, the first hub portion having one or more flexible segments;

placing a cable coil over the first hub portion and on the first flange so that the first hub portion substantially extends through an inner diameter of the cable coil; and expanding the one or more flexible segments by inserting the second hub portion inside of the first hub portion so that the one or more flexible segments engage the cable coil.

2. A method according to claim 1, further comprising the step of

prepacking the cable coil prior to the step of placing the cable coil over the first hub portion.

6

3. A method according to claim 2, wherein the cable coil is prepacked by applying a shrink wrap or ties to the cable coil.

4. A method according to claim 1, further comprising the step of securing the first and second hub portions together after the step of inserting the second hub portion inside of the first hub portion.

5. A method according to claim 4, wherein the first and second hub portions are secured together by a snapping engagement.

6. A method according to claim 1, further comprising the steps of:

providing first and second support frames; and rotatably coupling the first and second flanges to the first and second support frames, respectively.

7. A method according to claim 6, wherein the first and second flanges have a substantially disc shape; and

the first and second frames have a substantially square shape.

8. A method according to claim 1, wherein the step of inserting the second hub portion into the first hub portion includes inserting a truncated wall into a receiving area of an elongated wall of the first hub portion.

9. A method of installing a cable reel in a bag, comprising the steps of:

securing a first support frame to a base of a bag;

securing a second support frame to a cover of the bag;

placing a first flange on the first support frame, wherein the first flange includes a first hub portion;

placing a second flange on the second support frame, wherein the second flange includes a second hub portion, wherein either the first hub portion or the second hub portion includes an elongated annular wall having a receiving area and the other of the first hub portion and the second hub portion includes a truncated annular wall receivable in the receiving area; and

placing at least a portion of the truncated annular wall within the receiving area of the elongated annular wall.

10. The method of claim 9, further comprising the step of placing a coil of cable on the elongated annular wall.

11. The method of claim 10, wherein the coil of cable is arranged on a side thereof in the bag.

12. The method of claim 9, further comprising the step of dispensing cable of the coil of cable through a payout opening in the bag.

13. The method of claim 10, further comprising the step of removing the truncated annular wall from the elongated annular wall for replacement of the coil of cable with another coil of cable.

14. The method of claim 10, wherein the coil of cable lacks a support reel prior to the step of placing the coil of cable on the elongated annular wall.

15. The method of claim 10, wherein the step of placing the coil of cable on the elongated annular wall occurs before the step of placing the second flange to hold the coil of cable on the elongated annular wall and before the step of placing the second flange on the second support frame.

16. The method of claim 10, wherein the step of placing at least a portion of the truncated annular wall within the receiving area of the elongated annular wall occurs after placing the coil of cable on the elongated annular wall.

17. The method of claim 9, further comprising the step of strapping the first support frame to the base of the bag and strapping the second support frame to the cover of the bag.

7

8

**18.** The method of claim **9**, wherein each of the first and second flanges has a central arbor opening.

**19.** The method of claim **18**, further comprising the step of fitting a middle support flange of each of the first and second supports frames into the central arbor opening of the first and second flanges, respectively.

\* \* \* \* \*