PTO/SB/16 (2-98)

1-00



Please type a plus sign (+) inside this box  $\longrightarrow$  [+

valid OMB control number.

Approved for use through 01/31/2001. OMB 0651-0037 Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a

<b>PROVISION</b> This is a request fo											
INVENTOR(S)											
Given Name (first and midd	lle [if any])	Family Name	or Surname	(City ar		Residenc State or	ce Foreign Country)				
George		BRAINAR	D	Haddon							
Additional inventor	s are beir	ng named on the _	separately	numbered sh	heets att	ached l	hereto				
		TITLE OF THE IN	VENTION (28	0 characters	max)						
LIGHT SYSTEN CIRCADIAN AN			,		LS FO	OR ST	IMULATING				
Direct all corresponden Customer Numbe OR	r 🦲	CORRESP	ONDENCE A				omer Number abel here				
X Firm or Individual Name	Cliffoi	d Kent Webe	r								
Address	Thoma	as Jefferson L	Iniversity								
Address	1020 \	Valnut St Sui	te 620								
City	Philad	elphia	State	PA		ZIP	19107				
Country	United	States	Telephone	(215) 503-075	7	Fax	(215) 923-3613				
		ENCLOSED APP	LICATION PA	RTS (check	all that	apply)					
X Specification Nur	nber of Pa	ages 3	]	Small Entity S	tatemen	it					
Drawing(s) Numb	ets		Other (specify	Express Mail Letter							
METHOD OF PAYMEN	IT OF FIL	ING FEES FOR T	HIS PROVIS	ONAL APPLI	CATION	FOR F	PATENT (check one)				
A check or money The Commissione fees or credit any	r is hereb	y authorized to ch	arge filing				FILING FEE AMOUNT (\$) \$150.00				
The invention was made United States Governm No. Yes, the name of the	nent.					ontract	with an agency of the				
Respectfully submitted,	A			Date	05,	10 / 0	00				
SIGNATURE	REGISTRATION NO.			2,215							
TYPED or PRINTED NAM TELEPHONE		rd Kent Web		<i>(if appropriate)</i> Docket Number:		В	3RA01-P0002				
SE ONI V EOE						A T1					

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C., 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C., 20231.

		Application Number	Not Known		
TRANSMITTAL		Filing Date	Not Known		
FORM		First Named Inventor	BRAINARD, George		
be used for all correspondence afte	r ınitıal filıng)	Group Art Unit			
		Examiner Name			
Fotal Number of Pages in This Submi	ission 💡	Attorney Docket Numbe	BRA01-P0002		
	ENCLOS	SURES (check all that ap	oly)		
Fee Transmittal Form	ittal Form Assignm		After Allowance Communication to Group		
Fee Attached Draw		g(s)	Appeal Communication to Board of Appeals and Interferences		
Amendment / Response		ng-related Papers	Appeal Communication to Group (Appeal Notice, Brief, Reply Brief)		
After Final Petition and Acc		Routing Slip (PTO/SB/69) companying Petition	Proprietary Information		
Affidavits/declaration(s) To Cor Provisi		vert a onal Application	Status Letter		
Extension of Time Request		of Attorney, Revocation of Correspondence	X Additional Enclosure(s) (please identify below):		
Express Abandonment Request		al Disclaimer	Provisional Application Cover Sheet and Provisional Application,		
Information Disclosure Statement		Entity Statement	including specification		
Certified Copy of Priority		st for Refund			
Document(s) Response to Missing Parts/	Remarks				
Incomplete Application					
Response to Missing Parts under 37 CFR 1.52 or 1.53					
SIGNATU	RE OF APPLI	CANT, ATTORNEY, OR	AGENT		
rm Clifford Kent W	/eber				
gnature	Weber				
ate May 10, 2	000				
	CERTIFIC	ATE OF MAILING			
ereby certify that this correspondence velope addressed to: Assistant Comn	e is being depos	ited with the United States P			
ped or printed name					

Any comments on the amount of time you are required to complete this form should be send to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

.

.

•

\*

3

1. Light system which emits an optimal balance of wavelengths to stimulate the circadian and neurondocrine system and provides light therapy for Light Sensitive Disorder such as Seasonal Affective Disorder (SAD)

2. Transparent or translucent materials which specifically transmit or block the optimum balance of wavelengths for stimulating the circadian and neurondocrine system and provides light therapy for Light Sensitive Disordrs such as Seasonal Affective Disorder (SAD)

## 3. Meter system for quantifying light which stimulates the human circadian and neuroendocrine systems under normal conditions and provides light therapy for individuals with light sensitive disordrs such as seasonal affective disorder (SAD)

This metering device will be specifically configured to accurately quantify electromagnetic radiation that stimulates the circadian and neuroendocrine systems of healthy humans. The meter's wavelength sensitivity will match the wavelength sensitivity of the photoreceptors for circadian and neuroendocrine regulation in humans. This device may also be used to quantify electromagnetic radiation which is optimum for treating Seasonal Affective Disorders (SAD) or other light-responsive disorders.

The science of photobiology involves the study of how the infrared, visible and ultraviolet portions of the electromagnetic spectrum influence biological processes. There are two broad categories of light measurement techniques: radiometric and photometric. Each measurement technique has its merits and drawbacks relative to circadian regulation, neuroendocrine regulation and light therapy. Radiometry is based exclusively on the physical properties of light - its energy and wavelength. A radiometer measures the radiant power of a light source over a defined range of wavelengths. Figure 1 illustrates an example of a radiometer detector response that measures radiant power from the middle ultraviolet spectrum (290 nm) into the near infrared spectrum (770 nm). Radiometers can be configured to measure different bandwidths across the electromagnetic spectrum. The wavelengths within the designated bandwidth can be detected equally as shown in Figure 1, or they can be filtered for differential sensitivity across the various wavelengths.

In contrast to radiometry, photometry is based on the selective responsiveness of the human visual system. A photometer is simply a radiometer that has filters added to the detector which "shape" the detector sensitivity to resemble the luminance (brightness) response of the human visual system. Thus, photometry is a special branch of radiometry. Figure 1 illustrates the well characterized visual responses: photopic or day vision, and scotopic or night vision. Between individual humans, there are substantial differences in visual responses. The curves shown in Figure 1 represent sketches of the average response curves for the "standard observer" as determined by the Commission Internationale de l'Eclairage (CIE 1987). The photopic and scotopic visual functions are defined with reference to the adaptive state of the rod and cone photoreceptors in the human retina. Radiometers can be filtered to detect only those relative proportions of wavelengths that comprise the photopic or scotopic visual response. Such photometers will detect photopic lux or scotopic lux, respectively. Specifically defined, lux measures are measures of illuminance - the amount of light, or luminous flux, falling on a surface. One photopic lux is one lumen per square meter ( $lm/m^2$ ).

Most investigators operate from the assumption that light therapy is mediated via a photoreceptive mechanism in the human eye as opposed to a photoreceptive mechanism in the skin or some other part of the body. There is increasing evidence that the photoreceptive mechanism for the circadian and neuroendocrine system or that mediates light therapy is not identical to the photoreceptive system that mediates the sensory capacity of vision.



**PROUME**, 1-1. Response functions for three light detectors. One line indicates the characteristic response of a radiometer that has a flat sensitivity from 310 nm to 750 nm. The two other curves represent photometric responses for photopic lux and scotopic lux, based on the Commission Internationale de l'Eclairage standard observer (Commission Internationale de l'Eclairage 1987).

.

It is not known which photopigment(s) transduce light stimuli for circadian regulation in mammals. The aim of this ongoing study is to elucidate the ocular photoreceptor system for regulating the human pineal gland by establishing an action spectrum for light-induced melatonin suppression. The 33 females and 31 males who have entered this study have a mean age of 24.5  $\pm$  0.4 yrs. and have normal color vision. Volunteers received full-field monochromatic stimuli while their pupils were dilated with a mydriatic agent. The light exposure system was illuminated by a xenon arc lamp connected to a grating monochromator, and an integrating sphere. Monochromatic light exposures were between 2:00 and 3:30 AM. Blood samples were collected before and after these light exposures and were quantified for melatonin by RIA. Each subject was tested with at least seven different irradiances of one wavelength with a minimum of one week between each nighttime exposure. Presently, over 600 individual nighttime melatonin suppression tests have been completed with eight monochromatic wavelengths ranging from 440 nm to 600 nm. Fluence-response curves were completed with 10 irradiances at 505 and 555 nm for 8 subjects, each. The entire 505 nm curve is "shifted to the left" compared to the 555 nm curve. For example, an equal photon dose of 4.19 x10<sup>13</sup> photon/cm<sup>2</sup>/sec stimulus at 505 nm induces a mean control-adjusted melatonin suppression of 61%. In contrast, the same photon density at 555 nm induced a significantly lower (p<0.01) melatonin suppression of 15%. These data demonstrate that the cone system that mediates photopic vision is not the primary photoreceptor system to transduce light stimuli for melatonin regulation in the human. Support: NIH RO1NS36590 (to GB) and NSF IBN9809916 (to MR).