### **RECEIVED LIBRARY**

JUN 2 1 2010

KIRKLAND & ELLIS LLP CHICAGO OFFICE

# Wireless Encyclopedia

**Eion Reference** 

Published By: Althos Publishing

404 Wake Chapel Road Fuquay-Varina, NC 27526 USA Telephone: 1-800-227-9681 1-919-557-2260 Fax: 1-919-557-2261 email: Success@Althos.com web: www.Althos.com

DEFS-VOIP-2021-CC-0000085

META 1024 META V. VOIP-PAL GOOGLE EXHIBIT 1024

## Althos

All rights reserved. No part of this book may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying recording or by any information storage and retrieval system without written permission from the authors and publisher, except for the inclusion of brief quotations in a review.

Copyright © 2007 By Althos Publishing First Printing

Printed and Bound by Lightning Source Printing, La Vergne, TN USA

Every effort has been made to make this manual as complete and as accurate as possible. However, there may be mistakes both typographical and in content. Therefore, this text should be used only as a general guide and not as the ultimate source of information. Furthermore, this manual contains information on telecommunications accurate only up to the printing date. The purpose of this manual to educate. The authors and Althos Publishing shall have neither liability nor responsibility to any person or entity with respect to any loss or damage caused, or alleged to be caused, directly or indirectly by the information contained in this book.

International Standard Book Number: 1-932813-99-3

DEFS-VOIP-2021-CC-00000086 META 1024 META V. VOIP-PAL

#### **General Packet Radio Service (GPRS)**

#### **Gatekeeper** Cluster

This figure shows how a gatekeeper sets up connections between Internet telephones and telephone gateways. The gatekeeper receives registration messages from an Internet telephone when it is first connected to the Internet. This registration message indicates the current Internet address (IP address) of the Internet telephone. When the Internet telephone desires to make a call, it sends a message to the ITSP that includes the destination telephone number it wants to talk to. The ITSP reviews the destination telephone number with a list of authorized gateways. This list identifies to the ITSP one or more gateways that are located near the destination number and that can deliver the call. The ITSP sends a setup message to the gateway that includes the destination telephone number, the parameters of the call (bandwidth and type of speech compression), along with the current Internet address of the calling Internet telephone. The gatekeeper then sends the address of the destination gateway to the calling Internet telephone. The Internet telephone then can send packets directly to the gateway and the gateway initiates a local call to the destination telephone. If the destination telephone answers, two audio paths between the gateway and the Internet telephone are created. One for each direction and the call operates as a telephone call.

Gatekeeper Cluster-A group of gatekeepers that are linked together (possibly using GUP) to increase the reliability of a system.

Gatekeeper Update Protocol (GUP)-A proprietary protocol developed by Cisco to provide gate. keeper redundancy and load sharing. GUP can provide information about a gatekeeper's memory. CPU usage, number of endpoints that are registered, and available bandwidth. GUP is based on TCP.

Gateway-A gateway is a communications device on assembly that transforms data that is received from one network into a format that can be used by a dif ferent network. A gateway usually has more intelli gence (processing function) than a bridge as it can adjust the protocols and timing between two dissimilar computer systems or data networks. A gatiway can also be a router when its key function is id switch data between network points.

switch data between how a gateway can convert large This figure shows how a gateway can convert large packets from a FDDI into very small packets in an ATM network. Not only does the gateway have to divide the packets, it must also convert the addresse es and control messages into formats that can be understood on both networks.

0000

Gateway Operation

#### Gateway D-Gateway Daemon

Gateway GPRS Support Node (GGSN)-A packet switching system that is used to connect a GSM mobile communication network (GPRS Support Nodes) to other packet networks such as the Internet.

Gateway Location Protocol (GLP)-A protocol that was initially developed by a working group within the IETF to allow the gateway selection process in telephone and multimedia networks. This protocol is now called telephony routing over Internet protocol (TRIP).

Gateway Mobile Switching Center (GMSC)-A witching system that is used in a mobile commuplations network that also connects to other networks such as the public switched telephone network (PSTN).

Gating Pulse-A pulse that operates a logic gate. Gaussian Distribution-A statistical distribution that is used to represent occurences of specific yents that follow a relatively even distribution bround their center reference point. Gaussian disbibution is a bell-shaped curve and it is also called pormal distribution. Also called white noise.

Raussian Frequency Shift Keying (GFSK)-Faussian frequency shift keying is a form of fregency modulation in which the modulating signal at the output frequency between predetermined yalues to represent a digital signal and that information signal (data) is passed through a Gaussian filter prior to modulation to minimize the rapid Fanges to the carrier signal. Typically, one fremency shift is used to represent a digital one formations called a mark) and the other frequency with represents a digital zero (sometimes called a free).

inuasian Minimum Shift Keying (GMSK)-A fram of frequency modulation in which the moduinfu signal shifts the output frequency between restormined values. A form of MSK that uses Pausian low pass filtering of the binary data to dues aideband energy. MWDP-General Audio Video Distribution Profile

Active and a state of the office office of the office of the office office of the office offi

GCAC-Generic Connection Admission Control GCF-Gatekeeper Confirm GCIDs-Global Call Identifiers **GCR-Group Call Register GCRA-Generic Cell Rate Algorithm** GD-Graceful Discard **GDDM-Graphical Data Display Manager GDF-Group** Distribuiton Frame **GDI-Graphics** Device Interface **GDMF-Generic Data Message Format GDOI-Group** Domain of Interpretation GDOP-Geometric Dilution of Precision GDP-PI-GDP Price Index **GDS**-Global Directory Service **GED-Global Engineering Documents** Geek-A geek is a person who is focused on technology, typically computers who does not tend to conform to mainstream habits such as dressing for success and/or regular bathing. General Mobile Radio Service (GMRS)-General

General Mobile Radio Service (GMRS)-General mobile radio service is a licensed FM radio service that operates at on channels in the 462 MHz and 467 MHz UHF band.

General Packet Radio Service (GPRS)-General packet radio service is a packet data communication system that uses the global system for mobile (GSM) radio system packet radio transmission. The GPRS system modifies the GSM channel allocation and time slot control processes to allow for the dynamic assignment of time slots to individual users. GPRS provides a maximum radio channel data transmission rate of 171.2 kbps.

This figure shows some of the key GPRS network elements that include a gateway GPRS support node (GGSN), a serving GPRS support node (SGSN) and a GPRS backbone network (the Internet in this example.) This example shows that the GPRS system adds dynamic time slot control to the standard GSM radio system. To provide packet data service, the GPRS system, the SGSN provides the processes of switching and access control that is similar to a mobile switching center (MSC) and a visitor location register (VLR). However, the SGSN provides for switching and access control (authorization and tracking) based on packets of data rather than continuous connections. The SGSN registers and maintains a list of active packet data radios in its network and coordinates the packet transfer between the mobile radios. The GGSN is a packet switching system that is used to connect a GSM mobile communication network (GPRS Support Nodes) to other packet networks such as the Internet.



Voice Gatekeeper Operation

256

EION Reference - Wireless Encyclopedia

EION Reference - Wireless Encyclopedia

257

Ú

DEFS-VOIP-2021-CC-00000087 META 1024 META V. VOIP-PAL