

(12) **United States Patent**  
**Halac et al.**

(10) **Patent No.:** **US 11,160,926 B1**  
(45) **Date of Patent:** **Nov. 2, 2021**

(54) **PRE-CONNECTED ANALYTE SENSORS**

(71) Applicant: **DexCom, Inc.**, San Diego, CA (US)

(72) Inventors: **Jason Halac**, San Diego, CA (US); **John Charles Barry**, San Diego, CA (US); **Becky L. Clark**, San Diego, CA (US); **Chris W. Dring**, Fremont, CA (US); **John Michael Gray**, San Diego, CA (US); **Kris Elliot Higley**, Ramona, CA (US); **Jeff Jackson**, Poway, CA (US); **David A. Keller**, Encinitas, CA (US); **Ted Tang Lee**, San Diego, CA (US); **Jason Mitchell**, San Diego, CA (US); **Kenneth Pirondini**, San Diego, CA (US); **David Rego**, San Diego, CA (US); **Ryan Everett Schoonmaker**, Oceanside, CA (US); **Peter C. Simpson**, Cardiff, CA (US); **Craig Thomas Gadd**, Lemon Grove, CA (US); **Kyle Thomas Stewart**, San Diego, CA (US); **John Stanley Hayes**, San Diego, CA (US)

(73) Assignee: **DexCom, Inc.**, San Diego, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/369,535**

(22) Filed: **Jul. 7, 2021**

**Related U.S. Application Data**

(63) Continuation of application No. 16/167,976, filed on Oct. 23, 2018.

(Continued)

(51) **Int. Cl.**

**A61M 5/172** (2006.01)

**A61B 5/145** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **A61M 5/1723** (2013.01); **A61B 5/14532** (2013.01); **A61B 5/14546** (2013.01);  
(Continued)

(58) **Field of Classification Search**

CPC ..... **A61B 5/14532**; **A61B 5/14865**; **A61B 5/1473**; **A61B 5/145**; **A61B 5/14503**; **A61B 5/0022**; **A61B 5/0031**; **A61B 5/076**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

52,641 A 2/1866 Gates  
62,334 A 2/1867 Holmes  
(Continued)

**FOREIGN PATENT DOCUMENTS**

CA 2127172 C 7/1998  
EP 0098592 A2 1/1984  
(Continued)

**OTHER PUBLICATIONS**

US 7,530,950 B2, 05/2009, Brister et al. (withdrawn)  
(Continued)

*Primary Examiner* — Manuel A Mendez


(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

(57)

**ABSTRACT**

Pre-connected analyte sensors are provided. A pre-connected analyte sensor includes a sensor carrier attached to an analyte sensor. The sensor carrier includes a substrate configured for mechanical coupling of the sensor to testing, calibration, or wearable equipment. The sensor carrier also includes conductive contacts for electrically coupling sensor electrodes to the testing, calibration, or wearable equipment.

**30 Claims, 42 Drawing Sheets**



Related U.S. Application Data					
(60)	Provisional application No. 62/576,660, filed on Oct. 24, 2017.		4,136,250 A	1/1979	Mueller et al.
			4,151,845 A	5/1979	Clemens
			4,172,770 A	10/1979	Semersky et al.
			4,176,659 A	12/1979	Rolfe
(51)	<b>Int. Cl.</b>		4,197,840 A	4/1980	Beck et al.
			4,197,852 A	4/1980	Schindler et al.
			4,206,755 A	6/1980	Klein
			4,215,703 A	8/1980	Willson
			4,240,438 A	12/1980	Updike et al.
			4,240,889 A	12/1980	Yoda et al.
			4,245,634 A	1/1981	Albisser et al.
			4,253,469 A	3/1981	Aslan
			4,255,500 A	3/1981	Hooke
			4,259,540 A	3/1981	Sabia
			4,265,249 A	5/1981	Schindler et al.
			4,319,578 A	3/1982	Enger
			4,327,725 A	5/1982	Cortese et al.
			4,366,040 A	12/1982	Marsoner et al.
			4,369,785 A	1/1983	Rehkopf et al.
			4,374,013 A	2/1983	Enfors
			(52)	<b>U.S. Cl.</b>	CPC .... <i>A61M 5/14244</i> (2013.01); <i>A61M 5/14276</i> (2013.01); <i>A61M 5/20</i> (2013.01); <i>A61M 11/00</i> (2013.01); <i>A61M 15/008</i> (2014.02); <i>A61M 15/0065</i> (2013.01); <i>A61M 15/0068</i> (2014.02); <i>A61M 15/0083</i> (2014.02); <i>A61M 35/00</i> (2013.01); <i>G16H 20/17</i> (2018.01); <i>G16H 40/63</i> (2018.01); <i>A61B 5/0031</i> (2013.01); <i>A61M 5/003</i> (2013.01); <i>A61M 5/178</i> (2013.01); <i>A61M 5/30</i> (2013.01); <i>A61M 15/00</i> (2013.01); <i>A61M 2005/14296</i> (2013.01); <i>A61M 2205/3569</i> (2013.01); <i>A61M 2205/50</i> (2013.01); <i>A61M 2205/502</i> (2013.01); <i>A61M 2205/52</i> (2013.01); <i>A61M 2205/581</i> (2013.01); <i>A61M 2205/582</i> (2013.01); <i>A61M 2205/587</i> (2013.01); <i>A61M 2205/8206</i> (2013.01); <i>A61M 2230/201</i> (2013.01)
4,403,984 A	9/1983	Ash et al.			
4,415,666 A	11/1983	D'Orazio et al.			
4,431,004 A	2/1984	Bessman et al.			
4,432,366 A	2/1984	Margules			
4,436,094 A	3/1984	Cerami			
4,442,841 A	4/1984	Uehara et al.			
4,454,295 A	6/1984	Wittmann et al.			
4,457,339 A	7/1984	Juan et al.			
4,477,314 A	10/1984	Richter et al.			
4,478,222 A	10/1984	Koning et al.			
4,486,290 A	12/1984	Cahalan et al.			
4,492,575 A	1/1985	Mabille			
4,494,950 A	1/1985	Fischell			
4,506,680 A	3/1985	Stokes			
4,519,973 A	5/1985	Cahalan et al.			
RE31,916 E	6/1985	Oswin et al.			
4,526,569 A	7/1985	Bernardi			
4,534,825 A	8/1985	Koning et al.			
4,535,786 A	8/1985	Kater			
4,538,616 A	9/1985	Rogoff			
4,545,382 A	10/1985	Higgins et al.			
4,554,927 A	11/1985	Fussell			
4,565,665 A	1/1986	Fogt			
4,565,666 A	1/1986	Cahalan et al.			
4,568,444 A	2/1986	Nakamura et al.			
4,571,292 A	2/1986	Liu et al.			
4,573,968 A	3/1986	Parker			
4,577,642 A	3/1986	Stokes			
4,583,976 A	4/1986	Ferguson			
4,592,824 A	6/1986	Smith et al.			
4,600,495 A	7/1986	Fogt			
4,614,514 A	9/1986	Carr et al.			
4,619,793 A	10/1986	Lee			
4,625,730 A	12/1986	Fountain et al.			
4,626,104 A	12/1986	Pointon et al.			
4,632,968 A	12/1986	Yokota et al.			
RE32,361 E	2/1987	Duggan			
4,655,880 A	4/1987	Liu			
4,663,824 A	5/1987	Kenmochi			
4,671,288 A	6/1987	Gough			
4,672,970 A	6/1987	Uchida et al.			
4,680,268 A	7/1987	Clark, Jr.			
4,685,463 A	8/1987	Williams			
4,685,903 A	8/1987	Cable et al.			
4,694,861 A	9/1987	Goodale et al.			
4,702,732 A	10/1987	Powers et al.			
4,703,756 A	11/1987	Gough et al.			
4,705,503 A	11/1987	Dorman et al.			
4,711,245 A	12/1987	Higgins et al.			
4,711,251 A	12/1987	Stokes			
4,721,677 A	1/1988	Clark, Jr.			
4,726,381 A	2/1988	Jones			
4,731,726 A	3/1988	Allen, III			
4,736,748 A	4/1988	Nakamura et al.			
4,747,822 A	5/1988	Peabody			
4,750,496 A	6/1988	Reinhart et al.			
4,753,652 A	6/1988	Langer et al.			
4,755,168 A	7/1988	Romanelli et al.			
(56) <b>References Cited</b>					
U.S. PATENT DOCUMENTS					
65,604 A	6/1867	Reynolds			
1,954,643 A	4/1934	Neuhaus			
2,719,797 A	10/1955	Rosenblatt et al.			
3,210,578 A	10/1965	Sherer			
3,219,533 A	11/1965	Mullins			
3,381,371 A	5/1968	Russell			
3,506,032 A	4/1970	Eveleigh et al.			
3,556,950 A	1/1971	Dahms et al.			
3,610,226 A	10/1971	Albisser			
3,775,182 A	11/1973	Patton et al.			
3,780,727 A	12/1973	King			
3,826,244 A	7/1974	Salcman et al.			
3,837,339 A	9/1974	Aisenberg et al.			
3,838,682 A	10/1974	Clark et al.			
3,874,850 A	4/1975	Sorensen et al.			
3,898,984 A	8/1975	Mandel et al.			
3,910,256 A	10/1975	Clark et al.			
3,929,971 A	12/1975	Roy			
3,933,593 A	1/1976	Sternberg			
3,943,918 A	3/1976	Lewis			
3,957,613 A	5/1976	Macur			
3,964,974 A	6/1976	Banauch et al.			
3,979,274 A	9/1976	Newman			
4,008,717 A	2/1977	Kowarski			
4,016,866 A	4/1977	Lawton			
4,024,312 A	5/1977	Korpman			
4,040,908 A	8/1977	Clark, Jr.			
4,052,754 A	10/1977	Homsy			
4,055,175 A	10/1977	Clemens et al.			
4,073,713 A	2/1978	Newman			
4,076,656 A	2/1978	White et al.			
4,109,505 A	8/1978	Clark et al.			
4,119,406 A	10/1978	Clemens			

(56)

## References Cited

## U.S. PATENT DOCUMENTS

4,757,022 A	7/1988	Shults et al.	4,975,636 A	12/1990	Desautels
4,759,828 A	7/1988	Young et al.	4,976,687 A	12/1990	Martin
4,763,648 A	8/1988	Wyatt	4,979,509 A	12/1990	Hakky
4,763,658 A	8/1988	Jones	4,984,929 A	1/1991	Rock et al.
4,777,953 A	10/1988	Ash et al.	4,986,671 A	1/1991	Sun et al.
4,781,798 A	11/1988	Gough	4,988,341 A	1/1991	Columbus
4,784,157 A	11/1988	Halls et al.	4,989,607 A	2/1991	Keusch et al.
4,786,394 A	11/1988	Enzer et al.	4,992,794 A	2/1991	Brouwers
4,787,398 A	11/1988	Garcia et al.	4,994,026 A	2/1991	Fecondini
4,789,467 A	12/1988	Lindsay et al.	4,994,167 A	2/1991	Shults et al.
4,791,932 A	12/1988	Margules	4,997,627 A	3/1991	Bergkuist et al.
4,803,243 A	2/1989	Fujimoto et al.	5,002,055 A	3/1991	Merki et al.
4,805,624 A	2/1989	Yao et al.	5,002,572 A	3/1991	Picha
4,805,625 A	2/1989	Wyler	5,006,050 A	4/1991	Cooke et al.
4,807,632 A	2/1989	Liess et al.	5,006,111 A	4/1991	Inokuchi et al.
4,808,089 A	2/1989	Buchholtz et al.	5,007,929 A	4/1991	Quaid
4,808,292 A	2/1989	Kessler et al.	5,009,251 A	4/1991	Pike et al.
4,809,704 A	3/1989	Sogawa et al.	5,019,974 A	5/1991	Beckers
4,810,243 A	3/1989	Howson	5,026,348 A	6/1991	Venegas
4,810,470 A	3/1989	Burkhardt et al.	5,030,199 A	7/1991	Barwick et al.
4,815,471 A	3/1989	Stobie	5,030,333 A	7/1991	Clark, Jr.
4,820,281 A	4/1989	Lawler, Jr.	5,034,112 A	7/1991	Murase et al.
4,822,336 A	4/1989	DiTraglia	5,035,711 A	7/1991	Aoki et al.
4,823,808 A	4/1989	Clegg et al.	5,041,092 A	8/1991	Barwick
4,828,544 A	5/1989	Lane et al.	5,045,057 A	9/1991	Van Driessche et al.
4,830,013 A	5/1989	Maxwell	5,046,496 A	9/1991	Betts et al.
4,831,070 A	5/1989	McInally et al.	5,048,525 A	9/1991	Maxwell
4,832,005 A	5/1989	Takamiya et al.	5,050,612 A	9/1991	Matsumura
4,832,034 A	5/1989	Pizziconi et al.	5,055,171 A	10/1991	Peck
4,834,101 A	5/1989	Collison et al.	5,055,198 A	10/1991	Shettigar
4,838,281 A	6/1989	Rogers et al.	5,059,654 A	10/1991	Hou et al.
4,841,974 A	6/1989	Gumbrecht et al.	5,067,491 A	11/1991	Taylor, II et al.
4,849,458 A	7/1989	Reed et al.	5,068,536 A	11/1991	Rosenthal
4,852,573 A	8/1989	Kennedy	5,070,169 A	12/1991	Robertson et al.
4,854,322 A	8/1989	Ash et al.	5,077,476 A	12/1991	Rosenthal
4,858,615 A	8/1989	Meinema	5,088,981 A	2/1992	Howson et al.
4,867,741 A	9/1989	Portnoy	5,089,421 A	2/1992	Dieffenbach
4,871,440 A	10/1989	Nagata et al.	5,096,669 A	3/1992	Lauks et al.
4,874,363 A	10/1989	Abell	5,097,834 A	3/1992	Skrabal
4,883,057 A	11/1989	Broderick	5,098,377 A	3/1992	Borsanyi et al.
4,883,467 A	11/1989	Franetzki et al.	5,101,814 A	4/1992	Palti
4,889,528 A	12/1989	Nadai et al.	5,108,819 A	4/1992	Heller et al.
4,889,744 A	12/1989	Quaid	5,109,850 A	5/1992	Blanco et al.
4,890,620 A	1/1990	Gough	5,112,301 A	5/1992	Fenton, Jr. et al.
4,890,621 A	1/1990	Hakky	5,116,313 A	5/1992	McGregor
4,900,305 A	2/1990	Smith et al.	5,127,405 A	7/1992	Alcala et al.
4,902,294 A	2/1990	Gosserez	5,137,028 A	8/1992	Nishimura
4,907,857 A	3/1990	Giuliani et al.	5,140,985 A	8/1992	Schroeder et al.
4,908,208 A	3/1990	Lee et al.	5,145,565 A	9/1992	Kater et al.
4,909,786 A	3/1990	Gijselhart et al.	5,152,746 A	10/1992	Atkinson et al.
4,919,114 A	4/1990	Miyazaki	5,160,418 A	11/1992	Mullen
4,919,141 A	4/1990	Zier et al.	5,161,532 A	11/1992	Joseph
4,919,649 A	4/1990	Timothy et al.	5,165,406 A	11/1992	Wong
4,921,477 A	5/1990	Davis	5,165,407 A	11/1992	Wilson et al.
4,921,480 A	5/1990	Sealfon	5,174,291 A	12/1992	Schoonen et al.
4,925,444 A	5/1990	Orkin et al.	5,176,632 A	1/1993	Bernardi
4,927,407 A	5/1990	Dorman	5,176,658 A	1/1993	Ranford
4,927,516 A	5/1990	Yamaguchi et al.	5,178,142 A	1/1993	Harjunmaa et al.
4,928,694 A	5/1990	Maxwell	5,182,004 A	1/1993	Kohno
4,934,369 A	6/1990	Maxwell	5,188,591 A	2/1993	Dorsey, III
4,934,375 A	6/1990	Cole et al.	5,190,041 A	3/1993	Palti
4,944,299 A	7/1990	Silvian	5,195,963 A	3/1993	Yafuso et al.
4,946,439 A	8/1990	Eggers	5,196,025 A	3/1993	Ranalletta et al.
4,950,246 A	8/1990	Muller	5,198,771 A	3/1993	Fidler et al.
4,951,657 A	8/1990	Pfister et al.	5,208,147 A	5/1993	Kagenow et al.
4,951,669 A	8/1990	Maxwell et al.	5,208,313 A	5/1993	Krishnan
4,953,552 A	9/1990	DeMarzo	5,220,917 A	6/1993	Cammilli et al.
4,957,483 A	9/1990	Gonser et al.	5,220,920 A	6/1993	Gharib
4,963,595 A	10/1990	Ward et al.	5,224,929 A	7/1993	Remiszewski
4,966,579 A	10/1990	Polaschegg	5,225,063 A	7/1993	Gumbrecht et al.
4,967,940 A	11/1990	Blette et al.	5,232,434 A	8/1993	Inagaki et al.
4,970,145 A	11/1990	Bennetto et al.	5,235,003 A	8/1993	Ward et al.
4,973,320 A	11/1990	Brenner et al.	5,243,982 A	9/1993	Mostl et al.
4,974,592 A	12/1990	Branco	5,243,983 A	9/1993	Tarr et al.
4,974,929 A	12/1990	Curry	5,249,576 A	10/1993	Goldberger
			5,251,126 A	10/1993	Kahn et al.
			5,254,102 A	10/1993	Ogawa
			5,262,305 A	11/1993	Heller et al.
			5,265,594 A	11/1993	Olsson et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,266,179 A	11/1993	Nankai et al.	5,429,602 A	7/1995	Hauser
5,269,891 A	12/1993	Colin	5,429,735 A	7/1995	Johnson et al.
5,271,736 A	12/1993	Picha	5,431,160 A	7/1995	Wilkins
5,271,815 A	12/1993	Wong	5,431,174 A	7/1995	Knute
5,279,294 A	1/1994	Anderson et al.	5,431,921 A	7/1995	Thombre
5,281,319 A	1/1994	Kaneko et al.	5,434,412 A	7/1995	Sodickson et al.
5,282,848 A	2/1994	Schmitt	5,437,635 A	8/1995	Fields et al.
5,284,140 A	2/1994	Allen et al.	5,438,984 A	8/1995	Schoendorfer
5,284,570 A	2/1994	Savage et al.	5,443,508 A	8/1995	Giampapa
5,285,513 A	2/1994	Kaufman et al.	5,445,610 A	8/1995	Evert
5,287,753 A	2/1994	Routh et al.	5,448,992 A	9/1995	Kupersmidt
5,298,022 A	3/1994	Bernardi	5,451,260 A	9/1995	Versteeg et al.
5,299,571 A	4/1994	Mastrototaro	5,453,278 A	9/1995	Chan et al.
5,302,093 A	4/1994	Owens et al.	5,458,631 A	10/1995	Xavier
5,304,468 A	4/1994	Phillips et al.	5,462,051 A	10/1995	Oka et al.
5,307,263 A	4/1994	Brown	5,462,064 A	10/1995	D'Angelo et al.
5,310,469 A	5/1994	Cunningham et al.	5,466,356 A	11/1995	Schneider et al.
5,311,908 A	5/1994	Barone et al.	5,469,846 A	11/1995	Khan
5,312,361 A	5/1994	Zadini et al.	5,474,552 A	12/1995	Palti
5,314,441 A	5/1994	Cusack et al.	5,476,776 A	12/1995	Wilkins
5,314,471 A	5/1994	Brauker et al.	5,482,008 A	1/1996	Stafford et al.
5,316,008 A	5/1994	Suga et al.	5,482,446 A	1/1996	Williamson et al.
5,316,452 A	5/1994	Bogen et al.	5,482,473 A	1/1996	Lord et al.
5,318,511 A	6/1994	Riquier et al.	5,484,404 A	1/1996	Schulman et al.
5,318,583 A	6/1994	Rabenau et al.	5,491,474 A	2/1996	Suni et al.
5,322,063 A	6/1994	Allen et al.	5,494,562 A	2/1996	Maley et al.
5,324,322 A	6/1994	Grill, Jr. et al.	5,496,453 A	3/1996	Uenoyama et al.
5,326,356 A	7/1994	Della Valle et al.	5,497,772 A	3/1996	Schulman
5,326,449 A	7/1994	Cunningham	5,502,396 A	3/1996	Desarzens et al.
5,330,521 A	7/1994	Cohen	5,505,828 A	4/1996	Wong et al.
5,330,634 A	7/1994	Wong et al.	5,507,288 A	4/1996	Bocker et al.
5,331,555 A	7/1994	Hashimoto et al.	5,508,203 A	4/1996	Fuller et al.
5,335,658 A	8/1994	Bedingham	5,509,888 A	4/1996	Miller
5,337,747 A	8/1994	Neffel	5,512,046 A	4/1996	Pusinelli et al.
5,342,409 A	8/1994	Mullett	5,512,055 A	4/1996	Domb et al.
5,342,789 A	8/1994	Chick et al.	5,512,248 A	4/1996	Van
5,343,869 A	9/1994	Pross et al.	5,513,636 A	5/1996	Palti
5,344,454 A	9/1994	Clarke et al.	5,514,253 A	5/1996	Davis et al.
5,345,932 A	9/1994	Yafuso et al.	5,515,851 A	5/1996	Goldstein
5,348,788 A	9/1994	White	5,518,601 A	5/1996	Foos et al.
5,352,348 A	10/1994	Young et al.	5,527,288 A	6/1996	Gross et al.
5,352,351 A	10/1994	White et al.	5,527,334 A	6/1996	Kanner et al.
5,354,272 A	10/1994	Swendson et al.	5,531,679 A	7/1996	Schulman et al.
5,354,449 A	10/1994	Band et al.	5,531,878 A	7/1996	Vadgama et al.
5,356,375 A	10/1994	Higley	5,538,511 A	7/1996	Van Antwerp
5,356,378 A	10/1994	Doan	5,540,828 A	7/1996	Yacynych
5,356,786 A	10/1994	Heller et al.	5,545,220 A	8/1996	Andrews et al.
5,360,405 A	11/1994	Yoon	5,545,223 A	8/1996	Neuenfeldt et al.
5,368,028 A	11/1994	Palti	5,549,547 A	8/1996	Cohen et al.
5,368,224 A	11/1994	Richardson et al.	5,549,548 A	8/1996	Larsson
5,368,562 A	11/1994	Blomquist et al.	5,549,569 A	8/1996	Lynn et al.
5,372,133 A	12/1994	Hogen Esch	5,549,651 A	8/1996	Lynn
5,372,135 A	12/1994	Mendelson et al.	5,551,850 A	9/1996	Williamson et al.
5,372,709 A	12/1994	Hood	5,553,616 A	9/1996	Ham et al.
5,376,070 A	12/1994	Purvis et al.	5,554,339 A	9/1996	Cozzette et al.
5,378,229 A	1/1995	Layer et al.	5,561,615 A	10/1996	Kuo et al.
5,380,268 A	1/1995	Wheeler	5,562,614 A	10/1996	O'Donnell
5,380,491 A	1/1995	Carver, Jr. et al.	5,562,615 A	10/1996	Nassif
5,380,536 A	1/1995	Hubbell et al.	5,564,439 A	10/1996	Picha
5,380,665 A	1/1995	Cusack et al.	5,568,806 A	10/1996	Cheney, II et al.
5,384,028 A	1/1995	Ito	5,569,186 A	10/1996	Lord et al.
5,390,671 A	2/1995	Lord et al.	5,569,188 A	10/1996	Mackool
5,391,250 A	2/1995	Cheney, II et al.	5,569,219 A	10/1996	Hakki et al.
5,397,848 A	3/1995	Yang et al.	5,569,462 A	10/1996	Martinson et al.
5,405,510 A	4/1995	Betts et al.	5,575,293 A	11/1996	Miller et al.
5,411,052 A	5/1995	Murray	5,575,930 A	11/1996	Tietje-Girault et al.
5,411,647 A	5/1995	Johnson et al.	5,577,499 A	11/1996	Teves
5,411,866 A	5/1995	Luong et al.	5,582,184 A	12/1996	Erickson et al.
5,417,206 A	5/1995	Kaneyoshi	5,582,593 A	12/1996	Hultman
5,421,328 A	6/1995	Bedingham	5,584,813 A	12/1996	Livingston et al.
5,421,923 A	6/1995	Clarke et al.	5,584,876 A	12/1996	Bruchman et al.
5,423,738 A	6/1995	Robinson et al.	5,586,553 A	12/1996	Halili et al.
5,423,749 A	6/1995	Merte et al.	5,589,133 A	12/1996	Suzuki
5,428,123 A	6/1995	Ward et al.	5,590,651 A	1/1997	Shaffer et al.
5,429,485 A	7/1995	Dodge	5,593,440 A	1/1997	Brauker et al.
			5,609,572 A	3/1997	Lang
			5,611,900 A	3/1997	Worden et al.
			5,624,409 A	4/1997	Seale
			5,624,537 A	4/1997	Turner et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,626,563 A	5/1997	Dodge et al.	5,840,148 A	11/1998	Campbell et al.
5,628,619 A	5/1997	Wilson	5,848,991 A	12/1998	Gross et al.
5,628,890 A	5/1997	Carter et al.	5,851,197 A	12/1998	Marano et al.
5,637,083 A	6/1997	Bertrand et al.	5,851,229 A	12/1998	Lentz et al.
5,640,470 A	6/1997	Iyer et al.	5,858,365 A	1/1999	Faller
5,643,195 A	7/1997	Drevet et al.	5,858,747 A	1/1999	Schinstine et al.
5,651,767 A	7/1997	Schulman et al.	5,861,019 A	1/1999	Sun et al.
5,653,756 A	8/1997	Clarke et al.	5,863,400 A	1/1999	Drummond et al.
5,653,863 A	8/1997	Genshaw et al.	5,871,514 A	2/1999	Wiklund et al.
5,658,250 A	8/1997	Blomquist et al.	5,873,862 A	2/1999	Lopez
5,660,163 A	8/1997	Schulman	5,879,713 A	3/1999	Roth et al.
5,660,565 A	8/1997	Williams	5,882,494 A	3/1999	Van Antwerp
5,665,061 A	9/1997	Antwiler	5,895,235 A	4/1999	Droz
5,665,065 A	9/1997	Colman et al.	5,897,525 A	4/1999	Dey et al.
5,667,504 A	9/1997	Baumann et al.	5,897,578 A	4/1999	Wiklund et al.
5,673,694 A	10/1997	Rivers	5,899,855 A	5/1999	Brown
5,674,289 A	10/1997	Fournier et al.	5,904,666 A	5/1999	DeDecker et al.
5,676,651 A	10/1997	Larson, Jr. et al.	5,904,708 A	5/1999	Goedeke
5,676,820 A	10/1997	Wang et al.	5,911,219 A	6/1999	Aylsworth et al.
5,681,572 A	10/1997	Seare, Jr.	5,913,998 A	6/1999	Butler et al.
5,682,884 A	11/1997	Hill et al.	5,914,026 A	6/1999	Blubaugh, Jr.
5,683,562 A	11/1997	Schaffar et al.	5,917,346 A	6/1999	Gord
5,686,829 A	11/1997	Girault	5,919,215 A	7/1999	Wiklund et al.
5,688,239 A	11/1997	Walker	5,919,216 A	7/1999	Houben et al.
5,688,244 A	11/1997	Lang	5,921,951 A	7/1999	Morris
5,695,623 A	12/1997	Michel et al.	5,925,021 A	7/1999	Castellano et al.
5,696,314 A	12/1997	McCaffrey et al.	5,928,155 A	7/1999	Eggers et al.
5,697,366 A	12/1997	Kimball et al.	5,928,182 A	7/1999	Kraus et al.
5,697,899 A	12/1997	Hillman et al.	5,928,189 A	7/1999	Phillips et al.
5,704,354 A	1/1998	Preidel et al.	5,928,195 A	7/1999	Malamud et al.
5,706,807 A	1/1998	Picha	5,931,814 A	8/1999	Alex et al.
5,711,861 A	1/1998	Ward et al.	5,932,175 A	8/1999	Knute et al.
5,713,888 A	2/1998	Neuenfeldt et al.	5,933,136 A	8/1999	Brown
5,730,654 A	3/1998	Brown	5,935,785 A	8/1999	Reber et al.
5,733,259 A	3/1998	Valcke et al.	5,938,636 A	8/1999	Kramer et al.
5,733,336 A	3/1998	Neuenfeldt et al.	5,944,661 A	8/1999	Swette et al.
5,743,262 A	4/1998	Lepper, Jr. et al.	5,947,911 A	9/1999	Wong et al.
5,749,832 A	5/1998	Vadgama et al.	5,954,643 A	9/1999	VanAntwerp et al.
5,749,907 A	5/1998	Mann	5,954,954 A	9/1999	Houck et al.
5,755,692 A	5/1998	Manicom	5,957,854 A	9/1999	Besson et al.
5,756,632 A	5/1998	Ward et al.	5,957,903 A	9/1999	Mirzaee et al.
5,758,643 A	6/1998	Wong et al.	5,961,451 A	10/1999	Reber et al.
5,763,760 A	6/1998	Gumbrecht et al.	5,963,132 A	10/1999	Yoakum
5,771,890 A	6/1998	Tamada	5,964,745 A	10/1999	Lyles et al.
5,773,286 A	6/1998	Dionne et al.	5,964,993 A	10/1999	Blubaugh, Jr. et al.
5,776,324 A	7/1998	Usala	5,965,125 A	10/1999	Mineau-Hanschke
5,779,665 A	7/1998	Mastrototaro et al.	5,965,380 A	10/1999	Heller et al.
5,781,455 A	7/1998	Hyodo	5,971,922 A	10/1999	Arita et al.
5,782,880 A	7/1998	Lahtinen et al.	5,972,369 A	10/1999	Roorda et al.
5,782,912 A	7/1998	Brauker et al.	5,976,085 A	11/1999	Kimball et al.
5,787,900 A	8/1998	Butler et al.	5,984,940 A	11/1999	Davis et al.
5,791,344 A	8/1998	Schulman et al.	5,987,352 A	11/1999	Klein et al.
5,791,880 A	8/1998	Wilson	5,995,208 A	11/1999	Sarge et al.
5,795,453 A	8/1998	Gilmartin	5,995,860 A	11/1999	Sun et al.
5,795,774 A	8/1998	Matsumoto et al.	5,997,501 A	12/1999	Gross et al.
5,798,065 A	8/1998	Picha	5,999,848 A	12/1999	Gord et al.
5,800,383 A	9/1998	Chandler et al.	6,001,067 A	12/1999	Shults et al.
5,800,420 A	9/1998	Gross et al.	6,001,471 A	12/1999	Bries et al.
5,800,529 A	9/1998	Brauker et al.	6,002,954 A	12/1999	Van Antwerp et al.
5,806,517 A	9/1998	Gerhardt et al.	6,007,845 A	12/1999	Domb et al.
5,807,274 A	9/1998	Henning et al.	6,011,984 A	1/2000	Van Antwerp et al.
5,807,312 A	9/1998	Dzwonkiewicz	6,014,577 A	1/2000	Henning et al.
5,807,375 A	9/1998	Gross et al.	6,016,448 A	1/2000	Busacker et al.
5,807,406 A	9/1998	Brauker et al.	6,017,435 A	1/2000	Hassard et al.
5,810,770 A	9/1998	Chin et al.	6,023,629 A	2/2000	Tamada
5,811,487 A	9/1998	Schui, Jr. et al.	6,024,720 A	2/2000	Chandler et al.
5,814,599 A	9/1998	Mitragotri et al.	6,027,445 A	2/2000	Von Bahr
5,820,589 A	10/1998	Torgerson et al.	6,027,479 A	2/2000	Alei et al.
5,820,622 A	10/1998	Gross et al.	6,032,059 A	2/2000	Henning et al.
5,822,715 A	10/1998	Worthington et al.	6,032,667 A	3/2000	Heinonen
5,836,887 A	11/1998	Oka et al.	6,036,924 A	3/2000	Simons et al.
5,836,989 A	11/1998	Shelton	6,043,328 A	3/2000	Domschke et al.
5,837,454 A	11/1998	Cozzette et al.	6,045,671 A	4/2000	Wu et al.
5,837,728 A	11/1998	Purcell	6,048,691 A	4/2000	Maracas
5,840,026 A	11/1998	Uber, III et al.	6,049,727 A	4/2000	Crothall
			6,059,946 A	5/2000	Yukawa et al.
			6,063,637 A	5/2000	Arnold et al.
			6,066,088 A	5/2000	Davis
			6,066,448 A	5/2000	Wohlstadter et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,071,391 A	6/2000	Gotoh et al.	6,272,480 B1	8/2001	Tresp et al.
6,077,299 A	6/2000	Adelberg et al.	6,274,285 B1	8/2001	Gries et al.
6,080,583 A	6/2000	Von Bahr	6,275,717 B1	8/2001	Gross et al.
6,081,735 A	6/2000	Diab et al.	6,280,408 B1	8/2001	Sipin
6,081,736 A	6/2000	Colvin et al.	6,281,015 B1	8/2001	Mooney et al.
6,083,523 A	7/2000	Dionne et al.	6,284,478 B1	9/2001	Heller et al.
6,083,710 A	7/2000	Heller et al.	6,293,925 B1	9/2001	Safabash et al.
6,088,608 A	7/2000	Schulman et al.	6,298,254 B2	10/2001	Tamada
6,090,087 A	7/2000	Tsukada et al.	6,299,578 B1	10/2001	Kurnik et al.
6,091,975 A	7/2000	Daddona et al.	6,299,583 B1	10/2001	Eggers et al.
6,093,172 A	7/2000	Funderburk et al.	6,300,002 B1	10/2001	Webb et al.
6,099,511 A	8/2000	Devos et al.	6,302,855 B1	10/2001	Lav et al.
6,103,033 A	8/2000	Say et al.	6,309,351 B1	10/2001	Kurnik et al.
6,103,533 A	8/2000	Hassard et al.	6,309,384 B1	10/2001	Harrington et al.
6,107,083 A	8/2000	Collins et al.	6,309,884 B1	10/2001	Cooper et al.
6,115,634 A	9/2000	Donders et al.	6,312,388 B1	11/2001	Marcovecchio et al.
6,117,290 A	9/2000	Say et al.	6,315,738 B1	11/2001	Nishikawa et al.
6,120,676 A	9/2000	Heller et al.	6,325,978 B1	12/2001	Labuda et al.
6,121,009 A	9/2000	Heller et al.	6,326,160 B1	12/2001	Dunn et al.
6,122,536 A	9/2000	Sun et al.	6,329,161 B1	12/2001	Heller et al.
6,123,827 A	9/2000	Wong et al.	6,329,929 B1	12/2001	Weijand et al.
6,127,154 A	10/2000	Mosbach et al.	6,330,464 B1	12/2001	Colvin, Jr. et al.
6,128,519 A	10/2000	Say	6,343,225 B1	1/2002	Clark, Jr.
6,129,891 A	10/2000	Rolander et al.	6,356,776 B1	3/2002	Berner et al.
6,134,461 A	10/2000	Say et al.	6,358,225 B1	3/2002	Butterfield
6,135,978 A	10/2000	Houben et al.	6,365,670 B1	4/2002	Fry
6,142,939 A	11/2000	Eppstein et al.	6,366,794 B1	4/2002	Moussy et al.
6,144,869 A	11/2000	Berner et al.	6,368,141 B1	4/2002	VanAntwerp et al.
6,159,186 A	12/2000	Wickham et al.	6,368,274 B1	4/2002	Van Antwerp et al.
6,162,201 A	12/2000	Cohen et al.	6,370,941 B2	4/2002	Nakamura et al.
6,162,611 A	12/2000	Heller et al.	6,372,244 B1	4/2002	Antanavich et al.
6,163,720 A	12/2000	Gyory et al.	6,379,301 B1	4/2002	Worthington et al.
6,164,921 A	12/2000	Moubayed et al.	6,379,317 B1	4/2002	Kintzig et al.
6,165,154 A	12/2000	Gray et al.	6,383,478 B1	5/2002	Prokop et al.
6,167,614 B1	1/2001	Tuttle et al.	6,387,709 B1	5/2002	Mason et al.
6,168,568 B1	1/2001	Gavriely	6,391,019 B1	5/2002	Ito
6,169,155 B1	1/2001	Alvarez et al.	6,400,974 B1	6/2002	Lesho
6,171,276 B1	1/2001	Lippe et al.	6,402,703 B1	6/2002	Kensley et al.
6,175,752 B1	1/2001	Say et al.	6,403,944 B1	6/2002	Mackenzie et al.
6,180,416 B1	1/2001	Kurnik et al.	6,406,066 B1	6/2002	Uegane
6,183,437 B1	2/2001	Walker	6,407,195 B2	6/2002	Sherman et al.
6,186,982 B1	2/2001	Gross et al.	6,409,674 B1	6/2002	Brockway et al.
6,187,062 B1	2/2001	Oweis et al.	6,413,393 B1	7/2002	Van Antwerp et al.
6,189,536 B1	2/2001	Martinez et al.	6,416,651 B1	7/2002	Millar
6,191,860 B1	2/2001	Klinger et al.	6,424,847 B1	7/2002	Mastrototaro et al.
6,192,891 B1	2/2001	Gravel et al.	6,430,437 B1	8/2002	Marro
6,201,980 B1	3/2001	Darrow et al.	6,438,397 B1 *	8/2002	Bosquet ..... A61B 5/14532 600/310
6,201,993 B1	3/2001	Kruse et al.	6,447,448 B1	9/2002	Ishikawa et al.
6,206,856 B1	3/2001	Mahurkar	6,447,542 B1	9/2002	Weadock
6,208,894 B1	3/2001	Schulman	6,459,917 B1	10/2002	Gowda et al.
6,212,416 B1	4/2001	Ward et al.	6,461,496 B1	10/2002	Feldman et al.
6,212,424 B1	4/2001	Robinson	6,464,849 B1	10/2002	Say et al.
6,213,739 B1	4/2001	Phallen et al.	6,466,810 B1	10/2002	Ward et al.
6,214,185 B1	4/2001	Offenbacher et al.	6,467,480 B1	10/2002	Meier et al.
6,219,574 B1	4/2001	Cormier et al.	6,471,689 B1	10/2002	Joseph et al.
6,223,080 B1	4/2001	Thompson	6,474,360 B1	11/2002	Ito
6,223,083 B1	4/2001	Rosar	6,475,750 B1	11/2002	Han et al.
6,230,059 B1	5/2001	Duffin	6,477,392 B1	11/2002	Honigs et al.
6,231,879 B1	5/2001	Li et al.	6,477,395 B2	11/2002	Schulman et al.
6,232,783 B1	5/2001	Merrill	6,481,440 B2	11/2002	Gielen et al.
6,233,080 B1	5/2001	Brenner et al.	6,484,045 B1	11/2002	Holker et al.
6,234,964 B1	5/2001	Iliff	6,484,046 B1	11/2002	Say et al.
6,241,863 B1	6/2001	Monbouquette	6,485,449 B2	11/2002	Ito
6,248,067 B1	6/2001	Causey, III et al.	6,488,652 B1	12/2002	Weijand et al.
6,248,077 B1	6/2001	Elson et al.	6,494,830 B1	12/2002	Wessel
6,248,093 B1	6/2001	Moberg	6,494,879 B2	12/2002	Lennox et al.
6,254,586 B1	7/2001	Mann et al.	6,497,729 B1	12/2002	Moussy et al.
6,256,522 B1	7/2001	Schultz	6,498,043 B1	12/2002	Schulman et al.
6,259,937 B1	7/2001	Schulman	6,498,941 B1	12/2002	Jackson
6,263,222 B1	7/2001	Diab et al.	6,501,976 B1	12/2002	Sohrab
6,264,825 B1	7/2001	Blackburn et al.	6,510,239 B1	1/2003	Wieres et al.
6,270,478 B1	8/2001	Mernoee	6,510,329 B2	1/2003	Heckel
6,271,332 B1	8/2001	Lohmann et al.	6,512,939 B1	1/2003	Colvin et al.
6,272,364 B1	8/2001	Kurnik	6,514,718 B2	2/2003	Heller et al.
6,272,382 B1	8/2001	Faltys et al.	6,517,508 B1	2/2003	Utterberg et al.
			6,520,326 B2	2/2003	McIvor et al.
			6,520,477 B2	2/2003	Trimmer
			6,520,937 B2	2/2003	Hart et al.

(56)

**References Cited****U.S. PATENT DOCUMENTS**

6,520,997 B1	2/2003	Pekkarinen et al.	6,683,535 B1	1/2004	Utke
6,526,298 B1	2/2003	Khalil et al.	6,684,904 B2	2/2004	Ito
6,527,729 B1	3/2003	Turcott	6,685,668 B1	2/2004	Cho et al.
6,534,711 B1	3/2003	Pollack	6,687,522 B2	2/2004	Tamada
6,536,433 B1	3/2003	Cewers	6,689,089 B1	2/2004	Tiedtke et al.
6,537,318 B1	3/2003	Ita et al.	6,689,265 B2	2/2004	Heller et al.
6,541,266 B2	4/2003	Modzelewski	6,694,191 B2	2/2004	Starkweather et al.
6,542,765 B1	4/2003	Guy et al.	6,695,860 B1	2/2004	Ward et al.
6,544,212 B2	4/2003	Galley et al.	6,699,188 B2	3/2004	Wessel
6,545,085 B2	4/2003	Kilgour et al.	6,699,218 B2	3/2004	Flaherty et al.
6,546,268 B1	4/2003	Ishikawa et al.	6,699,383 B2	3/2004	Lemire et al.
6,546,269 B1	4/2003	Kurnik	6,702,249 B2	3/2004	Ito
6,549,796 B2	4/2003	Sohrab	6,702,857 B2	3/2004	Brauker et al.
6,551,496 B1	4/2003	Moles et al.	6,702,972 B1	3/2004	Markle
6,553,241 B2	4/2003	Mannheimer et al.	6,711,424 B1	3/2004	Fine et al.
6,553,244 B2	4/2003	Lesho et al.	6,712,796 B2	3/2004	Fentis et al.
6,554,805 B2	4/2003	Hiejima	6,721,587 B2	4/2004	Gough
6,554,822 B1	4/2003	Holschneider et al.	6,723,086 B2	4/2004	Bassuk et al.
6,558,320 B1	5/2003	Causey, III et al.	6,731,976 B2	5/2004	Penn et al.
6,558,321 B1	5/2003	Burd et al.	6,736,783 B2	5/2004	Blake et al.
6,558,347 B1	5/2003	Jhuboo et al.	6,740,072 B2	5/2004	Starkweather et al.
6,558,351 B1	5/2003	Steil et al.	6,740,075 B2	5/2004	Lebel et al.
6,558,955 B1	5/2003	Kristal et al.	6,741,877 B1	5/2004	Shults et al.
6,560,471 B1	5/2003	Heller et al.	6,742,635 B2	6/2004	Hirshberg
6,561,978 B1	5/2003	Conn et al.	6,743,635 B2	6/2004	Neel et al.
6,562,001 B2	5/2003	Lebel et al.	6,749,587 B2	6/2004	Flaherty
6,565,509 B1	5/2003	Say et al.	6,750,055 B1	6/2004	Connelly et al.
6,565,535 B2	5/2003	Zaias et al.	6,770,030 B1	8/2004	Schaupp et al.
6,565,807 B1	5/2003	Patterson et al.	6,770,067 B2	8/2004	Lorenzen et al.
6,569,195 B2	5/2003	Yang et al.	6,773,565 B2	8/2004	Kunimoto et al.
6,569,521 B1	5/2003	Sheridan et al.	6,780,297 B2	8/2004	Matsumoto et al.
6,571,128 B2	5/2003	Lebel et al.	6,793,632 B2	9/2004	Sohrab
6,572,545 B2	6/2003	Knobbe et al.	6,801,041 B2	10/2004	Karinka et al.
6,572,579 B1	6/2003	Raghavan et al.	6,802,957 B2	10/2004	Jung et al.
6,574,490 B2	6/2003	Abbink et al.	6,804,002 B2	10/2004	Fine et al.
6,575,905 B2	6/2003	Knobbe et al.	6,805,693 B2	10/2004	Gray et al.
6,577,899 B2	6/2003	Lebel et al.	6,809,653 B1	10/2004	Mann et al.
6,579,257 B1	6/2003	Elgas et al.	6,810,290 B2	10/2004	Lebel et al.
6,579,498 B1	6/2003	Eglise	6,811,548 B2	11/2004	Jeffrey
6,579,690 B1	6/2003	Bonnecaze et al.	6,813,519 B2	11/2004	Lebel et al.
6,585,644 B2	7/2003	Lebel et al.	6,832,200 B2	12/2004	Greeven et al.
6,585,675 B1	7/2003	O'Mahony et al.	6,850,790 B2	2/2005	Berner et al.
6,585,763 B1	7/2003	Keilman et al.	6,858,020 B2	2/2005	Rusnak
6,587,705 B1	7/2003	Kim et al.	6,862,465 B2	3/2005	Shults et al.
6,589,229 B1	7/2003	Connelly et al.	6,869,413 B2	3/2005	Langley et al.
6,591,125 B1	7/2003	Buse et al.	6,875,195 B2	4/2005	Choi
6,594,514 B2	7/2003	Berner et al.	6,887,228 B2	5/2005	McKay
6,595,756 B2	7/2003	Gray et al.	6,892,085 B2	5/2005	McIvor et al.
6,595,919 B2	7/2003	Berner et al.	6,893,552 B1	5/2005	Wang et al.
6,602,221 B1	8/2003	Saravia et al.	6,895,263 B2	5/2005	Shin et al.
6,605,072 B2	8/2003	Struys et al.	6,895,265 B2	5/2005	Silver
6,607,509 B2	8/2003	Bobroff et al.	6,902,544 B2	6/2005	Ludin et al.
6,607,543 B2	8/2003	Purcell et al.	6,925,393 B1	8/2005	Kalatz et al.
6,609,071 B2	8/2003	Shapiro et al.	6,926,691 B2	8/2005	Miethke
6,612,984 B1	9/2003	Kerr, II	6,931,327 B2	8/2005	Goode, Jr. et al.
6,613,379 B2	9/2003	Ward et al.	6,932,584 B2	8/2005	Gray et al.
6,615,061 B1	9/2003	Khalil et al.	6,936,006 B2	8/2005	Sabra
6,615,078 B1	9/2003	Burson et al.	6,936,029 B2	8/2005	Mann et al.
6,618,603 B2	9/2003	Varalli et al.	6,945,965 B2	9/2005	Whiting
6,618,934 B1	9/2003	Feldman et al.	6,948,492 B2	9/2005	Wermeling et al.
6,620,138 B1	9/2003	Margi et al.	6,952,604 B2	10/2005	Denuzzio et al.
6,633,772 B2	10/2003	Ford et al.	6,954,662 B2	10/2005	Freger et al.
6,635,014 B2	10/2003	Starkweather et al.	6,960,192 B1	11/2005	Flaherty et al.
6,641,533 B2	11/2003	Causey, III et al.	6,965,791 B1	11/2005	Hitchcock et al.
6,642,015 B2	11/2003	Vachon et al.	6,966,325 B2	11/2005	Erickson
6,645,181 B1	11/2003	Lavi et al.	6,975,893 B2	12/2005	Say et al.
6,648,821 B2	11/2003	Lebel et al.	6,979,315 B2	12/2005	Rogers et al.
6,653,091 B1	11/2003	Dunn et al.	6,989,891 B2	1/2006	Braig et al.
6,654,625 B1	11/2003	Say et al.	6,997,921 B2	2/2006	Gray et al.
6,656,157 B1	12/2003	Duchon et al.	6,998,247 B2	2/2006	Monfre et al.
6,663,615 B1	12/2003	Madou et al.	7,003,341 B2	2/2006	Say et al.
6,673,022 B1	1/2004	Bobo et al.	7,008,979 B2	3/2006	Schottman et al.
6,673,596 B1	1/2004	Sayler et al.	7,011,630 B2	3/2006	Desai et al.
6,679,865 B2	1/2004	Shekalim	7,016,713 B2	3/2006	Gardner et al.
6,679,872 B2	1/2004	Turovskiy et al.	7,022,072 B2	4/2006	Fox et al.
			7,022,219 B2	4/2006	Mansouri et al.
			7,025,727 B2	4/2006	Brockway et al.
			7,025,743 B2	4/2006	Mann et al.
			7,027,848 B2	4/2006	Robinson et al.

(56)

**References Cited****U.S. PATENT DOCUMENTS**

7,029,444 B2	4/2006	Shin et al.	7,364,562 B2	4/2008	Braig et al.
7,033,322 B2	4/2006	Silver	7,367,942 B2	5/2008	Grage et al.
7,044,911 B2	5/2006	Drinan et al.	7,396,353 B2	7/2008	Lorenzen et al.
7,048,727 B1	5/2006	Moss	7,399,277 B2	7/2008	Saidara et al.
7,058,437 B2	6/2006	Buse et al.	7,402,153 B2	7/2008	Steil et al.
7,060,059 B2	6/2006	Keith et al.	7,417,164 B2	8/2008	Suri
7,061,593 B2	6/2006	Braig et al.	7,426,408 B2	9/2008	Denuzzio et al.
7,063,086 B2	6/2006	Shahbazpour	7,433,727 B2	10/2008	Ward et al.
7,066,884 B2	6/2006	Custer et al.	7,481,819 B2	1/2009	Koeppel et al.
7,070,577 B1	7/2006	Haller et al.	7,519,408 B2	4/2009	Rasdal et al.
7,074,307 B2	7/2006	Simpson et al.	7,519,478 B2	4/2009	Bartkowiak et al.
7,081,195 B2 *	7/2006	Simpson ..... A61B 5/14532 205/777.5	7,523,004 B2	4/2009	Bartkowiak et al.
7,097,775 B2	8/2006	Greenberg et al.	7,530,964 B2	5/2009	Lavi et al.
7,098,803 B2	8/2006	Mann et al.	7,569,030 B2	8/2009	Lebel et al.
7,100,628 B1	9/2006	Izenson et al.	7,583,990 B2	9/2009	Goode, Jr. et al.
7,108,778 B2	9/2006	Simpson et al.	7,591,801 B2	9/2009	Brauker et al.
7,120,483 B2	10/2006	Russell et al.	7,599,726 B2	10/2009	Goode, Jr. et al.
7,131,967 B2	11/2006	Gray et al.	7,604,593 B2	10/2009	Parris et al.
7,134,999 B2	11/2006	Brauker et al.	7,615,007 B2	11/2009	Shults et al.
7,136,689 B2	11/2006	Shults et al.	7,618,368 B2	11/2009	Brown
7,144,404 B2	12/2006	Whitson et al.	7,618,369 B2	11/2009	Hayter et al.
7,146,202 B2	12/2006	Ward et al.	7,624,028 B1	11/2009	Brown
7,150,741 B2	12/2006	Erickson et al.	7,640,032 B2	12/2009	Jones
7,150,755 B2	12/2006	Levaughn et al.	7,640,048 B2	12/2009	Dobbles et al.
7,162,290 B1	1/2007	Levin	7,647,237 B2	1/2010	Malave et al.
7,166,074 B2	1/2007	Reghabi et al.	7,654,955 B2	2/2010	Polidori et al.
7,168,597 B1	1/2007	Jones et al.	7,657,297 B2	2/2010	Simpson et al.
7,169,289 B2	1/2007	Schuelein et al.	7,670,288 B2	3/2010	Sher
7,183,102 B2	2/2007	Monfre et al.	7,695,434 B2	4/2010	Malecha
7,184,810 B2	2/2007	Caduff et al.	7,727,147 B1	6/2010	Osorio et al.
7,207,968 B1	4/2007	Harcinske	7,731,659 B2	6/2010	Malecha
7,211,074 B2	5/2007	Sansoucy	7,761,126 B2	7/2010	Gardner et al.
7,221,970 B2	5/2007	Parker	7,766,830 B2	8/2010	Fox et al.
7,223,253 B2	5/2007	Hogendijk	7,846,132 B2	12/2010	Gravesen et al.
7,223,276 B2	5/2007	List et al.	7,850,652 B2	12/2010	Liniger et al.
7,225,535 B2	6/2007	Feldman et al.	7,857,760 B2	12/2010	Brister et al.
7,228,162 B2	6/2007	Ward et al.	7,901,394 B2	3/2011	Ireland et al.
7,229,288 B2	6/2007	Stuart et al.	7,905,833 B2	3/2011	Brister et al.
7,238,165 B2	7/2007	Vincent et al.	7,927,274 B2	4/2011	Rasdal et al.
7,247,138 B2	7/2007	Reghabi et al.	7,946,985 B2	5/2011	Mastrototaro et al.
7,254,450 B2	8/2007	Christopherson et al.	7,976,492 B2	7/2011	Brauker et al.
7,255,690 B2	8/2007	Gray et al.	8,000,901 B2	8/2011	Brauker et al.
7,258,681 B2	8/2007	Houde	8,005,524 B2	8/2011	Brauker et al.
7,261,690 B2	8/2007	Teller et al.	8,005,525 B2	8/2011	Goode, Jr. et al.
7,266,400 B2	9/2007	Fine et al.	8,010,174 B2	8/2011	Goode, Jr. et al.
7,267,665 B2	9/2007	Steil et al.	8,025,658 B2	9/2011	Chong et al.
7,276,029 B2	10/2007	Goode, Jr. et al.	8,079,961 B2	12/2011	Saikley et al.
7,278,983 B2	10/2007	Ireland et al.	8,298,172 B2	10/2012	Nielsen et al.
7,279,174 B2	10/2007	Pacetti et al.	8,366,682 B2	2/2013	Wyrick
7,282,029 B1	10/2007	Poulsen et al.	8,366,729 B2	2/2013	Levaughn et al.
7,288,085 B2	10/2007	Olsen	8,409,140 B2	4/2013	Ejlersen et al.
7,291,114 B2	11/2007	Mault	8,409,145 B2	4/2013	Raymond et al.
7,295,867 B2	11/2007	Berner et al.	8,439,838 B2	5/2013	Mogensen et al.
7,297,136 B2	11/2007	Wyrick	8,460,231 B2	6/2013	Brauker et al.
7,299,082 B2	11/2007	Feldman et al.	8,483,792 B2	7/2013	Slomski et al.
7,303,549 B2	12/2007	Flaherty et al.	8,500,654 B2	8/2013	Goldenberg
7,311,690 B2	12/2007	Burnett	8,512,276 B2	8/2013	Talbot et al.
7,313,425 B2	12/2007	Finarov et al.	8,562,567 B2	10/2013	Gundberg
7,314,452 B2	1/2008	Madonia	8,615,281 B2	12/2013	Yodfat et al.
7,315,767 B2	1/2008	Caduff et al.	8,721,585 B2	5/2014	Brauker et al.
7,316,662 B2	1/2008	Delnevo et al.	8,747,363 B2	6/2014	Nielsen et al.
7,317,939 B2	1/2008	Fine et al.	8,808,228 B2	8/2014	Brister et al.
7,318,814 B2	1/2008	Levine et al.	8,870,822 B2	10/2014	Thalmann et al.
7,327,273 B2	2/2008	Hung et al.	8,882,741 B2	11/2014	Brauker et al.
7,329,234 B2	2/2008	Sansoucy	8,920,401 B2	12/2014	Brauker et al.
7,334,594 B2	2/2008	Ludin	8,926,585 B2	1/2015	Brauker et al.
7,335,179 B2	2/2008	Burnett	9,050,413 B2	6/2015	Brauker et al.
7,335,195 B2	2/2008	Mehier	9,155,843 B2	10/2015	Brauker et al.
7,338,464 B2	3/2008	Blischak et al.	9,295,786 B2	3/2016	Gottlieb et al.
7,344,500 B2	3/2008	Talbot et al.	9,380,975 B2	7/2016	Karbowniczek et al.
7,354,420 B2	4/2008	Steil et al.	9,399,094 B2	7/2016	Krag et al.
7,357,793 B2	4/2008	Pacetti	9,451,908 B2	9/2016	Kamath et al.
7,359,723 B2	4/2008	Jones	9,452,258 B2	9/2016	Dobbles et al.
7,361,155 B2	4/2008	Sage, Jr. et al.	9,452,259 B2	9/2016	Dobbles et al.
			9,457,146 B2	10/2016	Dobbles et al.
			9,463,277 B2	10/2016	Dobbles et al.
			9,533,092 B2	1/2017	Gym
			9,572,935 B2	2/2017	Dobbles et al.
			9,572,936 B2	2/2017	Dobbles et al.



(56)

**References Cited****U.S. PATENT DOCUMENTS**

9,586,004	B2	3/2017	Dobbles et al.	2003/0100821	A1	5/2003	Heller et al.
9,597,453	B2	3/2017	Dobbles et al.	2003/0114836	A1	6/2003	Estes et al.
9,675,285	B2	6/2017	Christian	2003/0117296	A1	6/2003	Seely
9,788,771	B2	10/2017	Stafford	2003/0119208	A1	6/2003	Yoon et al.
9,808,574	B2	11/2017	Yodfat et al.	2003/0120152	A1	6/2003	Omiya
9,827,372	B2	11/2017	Dobbles et al.	2003/0125612	A1	7/2003	Fox et al.
9,937,293	B2	4/2018	Brauker et al.	2003/0125613	A1	7/2003	Enegren et al.
10,076,606	B2	9/2018	Ambruzs et al.	2003/0130616	A1	7/2003	Steil et al.
10,278,580	B2	5/2019	Brister et al.	2003/0132227	A1	7/2003	Geisler et al.
10,376,637	B2	8/2019	Gyrn et al.	2003/0134347	A1	7/2003	Heller et al.
10,653,835	B2	5/2020	Dobbles et al.	2003/0143746	A1	7/2003	Sage
11,051,725	B2	7/2021	Pace et al.	2003/0153821	A1	8/2003	Berner et al.
2001/0007950	A1	7/2001	North et al.	2003/0176183	A1	9/2003	Drucker et al.
2001/0016682	A1	8/2001	Berner et al.	2003/0187338	A1	10/2003	Say et al.
2001/0021817	A1	9/2001	Brugger et al.	2003/0187470	A1	10/2003	Chelak et al.
2001/0039053	A1	11/2001	Liseo et al.	2003/0188427	A1	10/2003	Say et al.
2001/0041830	A1	11/2001	Varalli et al.	2003/0199744	A1	10/2003	Buse et al.
2001/0044588	A1	11/2001	Mault	2003/0199745	A1	10/2003	Burson et al.
2001/0051768	A1	12/2001	Schulman et al.	2003/0208113	A1	11/2003	Mault et al.
2002/0009810	A1	1/2002	O'Connor et al.	2003/0211050	A1	11/2003	Majeti et al.
2002/0016535	A1	2/2002	Martin et al.	2003/0211625	A1	11/2003	Cohan et al.
2002/0018843	A1	2/2002	Van Antwerp et al.	2003/0212317	A1	11/2003	Kovatchev et al.
2002/0019022	A1	2/2002	Dunn et al.	2003/0212346	A1	11/2003	Yuzhakov et al.
2002/0019330	A1	2/2002	Murray et al.	2003/0212347	A1	11/2003	Sohrab
2002/0022883	A1	2/2002	Burg	2003/0225324	A1	12/2003	Anderson et al.
2002/0023852	A1	2/2002	McIvor et al.	2003/0225437	A1	12/2003	Ferguson
2002/0026110	A1	2/2002	Parris et al.	2003/0231550	A1	12/2003	MacFarlane
2002/0026111	A1	2/2002	Ackerman	2003/0235817	A1	12/2003	Bartkowiak et al.
2002/0029058	A1	3/2002	Levaughn et al.	2004/0006263	A1	1/2004	Anderson et al.
2002/0042090	A1	4/2002	Heller et al.	2004/0010207	A1	1/2004	Flaherty et al.
2002/0042561	A1	4/2002	Schulman et al.	2004/0011671	A1	1/2004	Shults et al.
2002/0043471	A1	4/2002	Ikeda et al.	2004/0015063	A1	1/2004	Denuzzio et al.
2002/0045808	A1	4/2002	Ford et al.	2004/0015134	A1	1/2004	Lavi et al.
2002/0060692	A1	5/2002	Broemmelsiek	2004/0023253	A1	2/2004	Kunwar et al.
2002/0065453	A1	5/2002	Lesho et al.	2004/0023317	A1	2/2004	Motamedi et al.
2002/0068860	A1	6/2002	Clark	2004/0024327	A1	2/2004	Brodnick
2002/0071776	A1	6/2002	Bandis et al.	2004/0030285	A1	2/2004	Lavi et al.
2002/0084196	A1	7/2002	Liamos et al.	2004/0030294	A1	2/2004	Mahurkar
2002/0099282	A1	7/2002	Knobbe et al.	2004/0039298	A1	2/2004	Abreu
2002/0099997	A1	7/2002	Piret	2004/0039406	A1	2/2004	Jessen
2002/0111547	A1	8/2002	Knobbe et al.	2004/0040840	A1	3/2004	Mao et al.
2002/0119711	A1	8/2002	VanAntwerp et al.	2004/0044272	A1	3/2004	Moerman et al.
2002/0123048	A1	9/2002	Gau	2004/0045879	A1	3/2004	Shults et al.
2002/0133224	A1	9/2002	Bajgar et al.	2004/0052689	A1	3/2004	Yao
2002/0151796	A1	10/2002	Koulik	2004/0054352	A1	3/2004	Adams et al.
2002/0155615	A1	10/2002	Novikov et al.	2004/0068230	A1	4/2004	Estes et al.
2002/0161288	A1	10/2002	Shin et al.	2004/0074785	A1	4/2004	Holker et al.
2002/0182241	A1	12/2002	Borenstein et al.	2004/0078219	A1	4/2004	Kaylor et al.
2002/0188185	A1	12/2002	Sohrab	2004/0106857	A1	6/2004	Gough
2002/0193679	A1	12/2002	Malave et al.	2004/0122297	A1	6/2004	Stahmann et al.
2002/0193885	A1	12/2002	Legeay et al.	2004/0122353	A1	6/2004	Shahmirian et al.
2002/0198513	A1	12/2002	Lebel et al.	2004/0133164	A1	7/2004	Funderburk et al.
2003/0004432	A1	1/2003	Assenheimer	2004/0138543	A1	7/2004	Russell et al.
2003/0006669	A1	1/2003	Pei et al.	2004/0138588	A1	7/2004	Saikley et al.
2003/0021729	A1	1/2003	Moller et al.	2004/0143173	A1	7/2004	Reghabi et al.
2003/0023171	A1	1/2003	Sato et al.	2004/0146909	A1	7/2004	Duong et al.
2003/0023317	A1	1/2003	Brauker et al.	2004/0152187	A1	8/2004	Haight et al.
2003/0028089	A1	2/2003	Galley et al.	2004/0152622	A1	8/2004	Keith et al.
2003/0028126	A1	2/2003	List	2004/0162678	A1	8/2004	Hetzel et al.
2003/0031699	A1	2/2003	Van Antwerp	2004/0167801	A1	8/2004	Say et al.
2003/0032874	A1	2/2003	Rhodes et al.	2004/0173472	A1	9/2004	Jung et al.
2003/0050546	A1	3/2003	Desai et al.	2004/0176672	A1	9/2004	Silver et al.
2003/0054428	A1	3/2003	Monfre et al.	2004/0180391	A1	9/2004	Gratzl et al.
2003/0060692	A1	3/2003	Ruchti et al.	2004/0186362	A1	9/2004	Brauker et al.
2003/0060753	A1	3/2003	Starkweather et al.	2004/0186365	A1	9/2004	Jin et al.
2003/0060765	A1	3/2003	Campbell et al.	2004/0193025	A1	9/2004	Steil et al.
2003/0070548	A1	4/2003	Clausen	2004/0199059	A1	10/2004	Brauker et al.
2003/0072741	A1	4/2003	Berglund et al.	2004/0204687	A1	10/2004	Mogensen et al.
2003/0076082	A1	4/2003	Morgan et al.	2004/0219664	A1	11/2004	Heller et al.
2003/0078481	A1	4/2003	McIvor et al.	2004/0220517	A1	11/2004	Starkweather et al.
2003/0078560	A1	4/2003	Miller et al.	2004/0224001	A1	11/2004	Pacetti et al.
2003/0091433	A1	5/2003	Tam et al.	2004/0248282	A1	12/2004	Sobha et al.
2003/0097082	A1	5/2003	Purdy et al.	2004/0253365	A1	12/2004	Warren et al.
2003/0099682	A1	5/2003	Moussy et al.	2004/0254433	A1	12/2004	Bandis et al.
2003/0100040	A1	5/2003	Bonnecaze et al.	2005/0003399	A1	1/2005	Blackburn et al.
				2005/0010265	A1	1/2005	Baru et al.
				2005/0026689	A1	2/2005	Marks
				2005/0027180	A1	2/2005	Goode, Jr. et al.
				2005/0027181	A1	2/2005	Goode, Jr. et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2005/0027182 A1	2/2005	Siddiqui et al.	2006/0036145 A1	2/2006	Brister et al.
2005/0027462 A1	2/2005	Goode, Jr. et al.	2006/0040402 A1	2/2006	Brauker et al.
2005/0027463 A1	2/2005	Goode, Jr. et al.	2006/0047095 A1	3/2006	Pacetti
2005/0031689 A1	2/2005	Shults et al.	2006/0052745 A1	3/2006	Van Antwerp et al.
2005/0033132 A1	2/2005	Shults et al.	2006/0067908 A1	3/2006	Ding
2005/0038332 A1	2/2005	Saidara et al.	2006/0078908 A1	4/2006	Pitner et al.
2005/0043598 A1	2/2005	Goode, Jr. et al.	2006/0079740 A1	4/2006	Silver et al.
2005/0049472 A1	3/2005	Manda et al.	2006/0079809 A1	4/2006	Goldberger et al.
2005/0051427 A1	3/2005	Brauker et al.	2006/0094946 A1	5/2006	Kellogg et al.
2005/0051440 A1	3/2005	Simpson et al.	2006/0100588 A1	5/2006	Brunnberg et al.
2005/0054909 A1	3/2005	Petisce et al.	2006/0134165 A1	6/2006	Pacetti
2005/0056552 A1	3/2005	Simpson et al.	2006/0171980 A1	8/2006	Helmus et al.
2005/0065464 A1	3/2005	Talbot et al.	2006/0173406 A1	8/2006	Hayes et al.
2005/0077584 A1	4/2005	Uhland et al.	2006/0177379 A1	8/2006	Asgari
2005/0090607 A1	4/2005	Tapsak et al.	2006/0183871 A1	8/2006	Ward et al.
2005/0090850 A1	4/2005	Thoes et al.	2006/0183984 A1	8/2006	Dobbles et al.
2005/0096519 A1	5/2005	Denuzzio et al.	2006/0183985 A1	8/2006	Brister et al.
2005/0101847 A1	5/2005	Routt et al.	2006/0189863 A1	8/2006	Peyser et al.
2005/0107677 A1	5/2005	Ward et al.	2006/0195029 A1	8/2006	Shults et al.
2005/0112169 A1	5/2005	Brauker et al.	2006/0222566 A1	10/2006	Brauker et al.
2005/0113653 A1	5/2005	Fox et al.	2006/0224141 A1	10/2006	Rush et al.
2005/0113744 A1	5/2005	Donoghue et al.	2006/0229512 A1	10/2006	Petisce et al.
2005/0115832 A1	6/2005	Simpson et al.	2006/0235285 A1	10/2006	Brister et al.
2005/0118344 A1	6/2005	Pacetti	2006/0241517 A1	10/2006	Fowler et al.
2005/0119720 A1	6/2005	Gale et al.	2006/0241669 A1	10/2006	Stout et al.
2005/0121322 A1	6/2005	Say et al.	2006/0247671 A1	11/2006	LeVaughn
2005/0124873 A1	6/2005	Shults et al.	2006/0253085 A1	11/2006	Geismar et al.
2005/0131305 A1	6/2005	Danielson et al.	2006/0258929 A1	11/2006	Goode, Jr. et al.
2005/0139489 A1	6/2005	Davies et al.	2006/0258939 A1	11/2006	Pesach et al.
2005/0143635 A1	6/2005	Kamath et al.	2006/0258990 A1	11/2006	Weber
2005/0143675 A1	6/2005	Neel et al.	2006/0263839 A1	11/2006	Ward et al.
2005/0149089 A1	7/2005	Trissei et al.	2006/0269586 A1	11/2006	Pacetti
2005/0154271 A1	7/2005	Rasdal et al.	2006/0275857 A1	12/2006	Kjaer et al.
2005/0176136 A1	8/2005	Burd et al.	2006/0281985 A1	12/2006	Ward et al.
2005/0177036 A1	8/2005	Shults et al.	2006/0287630 A1	12/2006	Hommann
2005/0177398 A1	8/2005	Watanabe et al.	2007/0007133 A1	1/2007	Mang et al.
2005/0181012 A1	8/2005	Saint et al.	2007/0016381 A1	1/2007	Kamath et al.
2005/0182451 A1	8/2005	Griffin et al.	2007/0027381 A1	2/2007	Stafford
2005/0183954 A1	8/2005	Hitchcock et al.	2007/0027385 A1	2/2007	Brister et al.
2005/0187720 A1	8/2005	Goode, Jr. et al.	2007/0032706 A1	2/2007	Kamath et al.
2005/0192557 A1	9/2005	Brauker et al.	2007/0038044 A1	2/2007	Dobbles et al.
2005/0197554 A1	9/2005	Polcha	2007/0049873 A1	3/2007	Hansen et al.
2005/0203360 A1	9/2005	Brauker et al.	2007/0060814 A1	3/2007	Stafford
2005/0211571 A1	9/2005	Schulein et al.	2007/0066873 A1	3/2007	Kamath et al.
2005/0215871 A1	9/2005	Feldman et al.	2007/0066956 A1	3/2007	Finkel
2005/0215872 A1	9/2005	Berner et al.	2007/0073129 A1	3/2007	Shah et al.
2005/0239154 A1	10/2005	Feldman et al.	2007/0078322 A1	4/2007	Stafford
2005/0242479 A1*	11/2005	Petisce .....	2007/0085995 A1	4/2007	Pesach et al.
		A61B 5/14865	2007/0100222 A1	5/2007	Mastrototaro et al.
		264/650	2007/0106135 A1	5/2007	Sloan et al.
2005/0245795 A1	11/2005	Goode, Jr. et al.	2007/0112298 A1	5/2007	Mueller, Jr. et al.
2005/0245799 A1	11/2005	Brauker et al.	2007/0116600 A1	5/2007	Kochar et al.
2005/0245904 A1	11/2005	Estes et al.	2007/0129619 A1	6/2007	Ward et al.
2005/0251083 A1	11/2005	Carr-Brendel et al.	2007/0129621 A1	6/2007	Kellogg et al.
2005/0261563 A1	11/2005	Zhou et al.	2007/0135698 A1	6/2007	Shah et al.
2005/0283114 A1	12/2005	Bresina et al.	2007/0135699 A1	6/2007	Ward et al.
2005/0288596 A1	12/2005	Eigler et al.	2007/0151869 A1	7/2007	Heller et al.
2006/0001550 A1	1/2006	Mann et al.	2007/0167907 A1	7/2007	Deslieries et al.
2006/0007017 A1	1/2006	Mann et al.	2007/0173706 A1	7/2007	Neinast et al.
2006/0015020 A1	1/2006	Neale et al.	2007/0173710 A1	7/2007	Petisce et al.
2006/0015024 A1	1/2006	Brister et al.	2007/0173761 A1	7/2007	Kanderian, Jr. et al.
2006/0016700 A1	1/2006	Brister et al.	2007/0179434 A1	8/2007	Weinert et al.
2006/0019327 A1	1/2006	Brister et al.	2007/0191702 A1	8/2007	Yodfat et al.
2006/0020186 A1	1/2006	Brister et al.	2007/0197889 A1	8/2007	Brister et al.
2006/0020187 A1	1/2006	Brister et al.	2007/0200254 A1	8/2007	Curry
2006/0020188 A1	1/2006	Kamath et al.	2007/0200267 A1	8/2007	Tsai
2006/0020189 A1	1/2006	Brister et al.	2007/0203407 A1	8/2007	Hoss et al.
2006/0020190 A1	1/2006	Kamath et al.	2007/0203410 A1	8/2007	Say et al.
2006/0020191 A1	1/2006	Brister et al.	2007/0203966 A1	8/2007	Brauker et al.
2006/0020192 A1	1/2006	Brister et al.	2007/0206193 A1	9/2007	Pesach
2006/0036139 A1	2/2006	Brister et al.	2007/0208244 A1	9/2007	Brauker et al.
2006/0036140 A1	2/2006	Brister et al.	2007/0208245 A1	9/2007	Brauker et al.
2006/0036141 A1	2/2006	Kamath et al.	2007/0208246 A1	9/2007	Brauker et al.
2006/0036142 A1	2/2006	Brister et al.	2007/0213610 A1	9/2007	Say et al.
2006/0036143 A1	2/2006	Brister et al.	2007/0218097 A1	9/2007	Heller et al.
2006/0036144 A1	2/2006	Brister et al.	2007/0219441 A1	9/2007	Carlin et al.
			2007/0225579 A1	9/2007	Lucassen et al.
			2007/0225675 A1	9/2007	Robinson et al.
			2007/0227907 A1	10/2007	Shah et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2007/0233013	A1	10/2007	Schoenberg	2008/0287764	A1	11/2008	Rasdal et al.
2007/0233167	A1	10/2007	Weiss et al.	2008/0287765	A1	11/2008	Rasdal et al.
2007/0235331	A1	10/2007	Simpson et al.	2008/0287766	A1	11/2008	Rasdal et al.
2007/0240497	A1	10/2007	Robinson et al.	2008/0296155	A1	12/2008	Shults et al.
2007/0244381	A1	10/2007	Robinson et al.	2008/0300572	A1	12/2008	Rankers et al.
2007/0244382	A1	10/2007	Robinson et al.	2008/0305009	A1	12/2008	Gamsey et al.
2007/0249916	A1	10/2007	Pesach et al.	2008/0305506	A1	12/2008	Suri
2007/0249922	A1	10/2007	Peyser et al.	2008/0306368	A1	12/2008	Goode, Jr. et al.
2007/0255126	A1	11/2007	Moberg et al.	2008/0306433	A1	12/2008	Cesaroni
2007/0255302	A1	11/2007	Koeppel et al.	2008/0306434	A1	12/2008	Dobbles et al.
2007/0275193	A1	11/2007	DeSimone et al.	2008/0306435	A1	12/2008	Kamath et al.
2007/0293742	A1	12/2007	Simonsen et al.	2008/0306444	A1	12/2008	Brister et al.
2007/0299409	A1	12/2007	Whitbourne et al.	2009/0005666	A1	1/2009	Shin et al.
2008/0007141	A1	1/2008	Deck	2009/0012379	A1	1/2009	Goode, Jr. et al.
2008/0009805	A1	1/2008	Ethelfeld	2009/0012472	A1	1/2009	Ahm et al.
2008/0021666	A1	1/2008	Goode, Jr. et al.	2009/0018418	A1	1/2009	Markle et al.
2008/0021668	A1	1/2008	Son	2009/0018424	A1	1/2009	Kamath et al.
2008/0027301	A1	1/2008	Ward et al.	2009/0018426	A1	1/2009	Markle et al.
2008/0027474	A1	1/2008	Curry et al.	2009/0036758	A1	2/2009	Brauker et al.
2008/0029390	A1	2/2008	Roche et al.	2009/0043181	A1	2/2009	Brauker et al.
2008/0029391	A1	2/2008	Mao et al.	2009/0043182	A1	2/2009	Brauker et al.
2008/0033254	A1	2/2008	Kamath et al.	2009/0043525	A1	2/2009	Brauker et al.
2008/0034972	A1	2/2008	Gough et al.	2009/0043541	A1	2/2009	Brauker et al.
2008/0045824	A1	2/2008	Tapsak et al.	2009/0043542	A1	2/2009	Brauker et al.
2008/0051714	A1	2/2008	Moberg et al.	2009/0054812	A1	2/2009	Mace
2008/0071157	A1	3/2008	McGarraugh et al.	2009/0061528	A1	3/2009	Suri
2008/0071158	A1	3/2008	McGarraugh et al.	2009/0062635	A1	3/2009	Brauker et al.
2008/0072663	A1	3/2008	Keenan et al.	2009/0062645	A1	3/2009	Fehre et al.
2008/0086040	A1	4/2008	Heller et al.	2009/0076356	A1	3/2009	Simpson et al.
2008/0086041	A1	4/2008	Heller et al.	2009/0076360	A1	3/2009	Brister et al.
2008/0086042	A1	4/2008	Brister et al.	2009/0076361	A1	3/2009	Kamath et al.
2008/0086043	A1	4/2008	Heller et al.	2009/0081803	A1	3/2009	Gamsey et al.
2008/0086044	A1	4/2008	Brister et al.	2009/0088689	A1	4/2009	Carter
2008/0086273	A1	4/2008	Shults et al.	2009/0099434	A1	4/2009	Liu et al.
2008/0091094	A1	4/2008	Heller et al.	2009/0124877	A1	5/2009	Goode, Jr. et al.
2008/0091095	A1	4/2008	Heller et al.	2009/0124878	A1	5/2009	Goode, Jr. et al.
2008/0097246	A1	4/2008	Stafford	2009/0124964	A1	5/2009	Leach et al.
2008/0097289	A1	4/2008	Steil et al.	2009/0124979	A1	5/2009	Raymond et al.
2008/0108942	A1	5/2008	Brister et al.	2009/0131768	A1	5/2009	Simpson et al.
2008/0114227	A1	5/2008	Haar et al.	2009/0131769	A1	5/2009	Leach et al.
2008/0119703	A1	5/2008	Brister et al.	2009/0131776	A1	5/2009	Simpson et al.
2008/0119704	A1	5/2008	Brister et al.	2009/0131777	A1	5/2009	Simpson et al.
2008/0119706	A1	5/2008	Brister et al.	2009/0137886	A1	5/2009	Shariati et al.
2008/0125751	A1	5/2008	Fjield et al.	2009/0137887	A1	5/2009	Shariati et al.
2008/0139903	A1	6/2008	Bruce et al.	2009/0143659	A1	6/2009	Li et al.
2008/0139910	A1	6/2008	Mastrototaro et al.	2009/0156924	A1	6/2009	Shariati et al.
2008/0154101	A1	6/2008	Jain et al.	2009/0177143	A1	7/2009	Markle et al.
2008/0161656	A1	7/2008	Bruce et al.	2009/0178459	A1	7/2009	Li et al.
2008/0167641	A1	7/2008	Hansen et al.	2009/0182217	A1	7/2009	Li et al.
2008/0183061	A1	7/2008	Goode et al.	2009/0192366	A1	7/2009	Mensinger et al.
2008/0183399	A1	7/2008	Goode et al.	2009/0192380	A1	7/2009	Shariati et al.
2008/0187655	A1	8/2008	Markle et al.	2009/0192722	A1	7/2009	Shariati et al.
2008/0188722	A1	8/2008	Markle et al.	2009/0192724	A1	7/2009	Brauker et al.
2008/0188725	A1	8/2008	Markle et al.	2009/0192745	A1	7/2009	Kamath et al.
2008/0188731	A1	8/2008	Brister et al.	2009/0192751	A1	7/2009	Kamath et al.
2008/0188798	A1	8/2008	Weber	2009/0203981	A1	8/2009	Brauker et al.
2008/0189051	A1	8/2008	Goode et al.	2009/0204341	A1	8/2009	Brauker et al.
2008/0193936	A1	8/2008	Squirrell	2009/0216103	A1	8/2009	Brister et al.
2008/0194837	A1	8/2008	Kim et al.	2009/0240120	A1	9/2009	Mensinger et al.
2008/0194935	A1	8/2008	Brister et al.	2009/0240128	A1	9/2009	Mensinger et al.
2008/0194936	A1	8/2008	Goode et al.	2009/0240193	A1	9/2009	Mensinger et al.
2008/0194937	A1	8/2008	Goode et al.	2009/0242399	A1	10/2009	Kamath et al.
2008/0195967	A1	8/2008	Goode et al.	2009/0242425	A1	10/2009	Kamath et al.
2008/0197024	A1	8/2008	Simpson et al.	2009/0264719	A1	10/2009	Markle et al.
2008/0200788	A1	8/2008	Brister et al.	2009/0264856	A1	10/2009	Lebel et al.
2008/0200789	A1	8/2008	Brister et al.	2009/0287074	A1	11/2009	Shults et al.
2008/0200791	A1	8/2008	Simpson et al.	2009/0299155	A1	12/2009	Yang et al.
2008/0208025	A1	8/2008	Shults et al.	2009/0299156	A1	12/2009	Simpson et al.
2008/0210557	A1	9/2008	Heller et al.	2009/0299162	A1	12/2009	Brauker et al.
2008/0214915	A1	9/2008	Brister et al.	2009/0299276	A1	12/2009	Brauker et al.
2008/0249383	A1	10/2008	Sass et al.	2010/0010324	A1	1/2010	Brauker et al.
2008/0249473	A1	10/2008	Rutti et al.	2010/0010331	A1	1/2010	Brauker et al.
2008/0262469	A1	10/2008	Brister et al.	2010/0010332	A1	1/2010	Brauker et al.
2008/0269723	A1	10/2008	Mastrototaro et al.	2010/0010529	A1	1/2010	Shi
2008/0281270	A1	11/2008	Cross et al.	2010/0016687	A1	1/2010	Brauker et al.
				2010/0022855	A1	1/2010	Brauker et al.
				2010/0025174	A1	2/2010	Dayton
				2010/0030053	A1	2/2010	Goode, Jr. et al.
				2010/0030484	A1	2/2010	Brauker et al.

**MASIMO 1067**  
**Masimo v. Apple**  
**IPR2023-00745**

(56)

**References Cited**

## FOREIGN PATENT DOCUMENTS

WO WO-9838906 A1 9/1998  
 WO WO-9948419 A1 9/1999  
 WO WO-9956613 A1 11/1999  
 WO WO-9958051 A1 11/1999  
 WO WO-9958973 A1 11/1999  
 WO WO-9959657 A1 11/1999  
 WO WO-0012720 A2 3/2000  
 WO WO-0013002 A2 3/2000  
 WO WO-0013003 A1 3/2000  
 WO WO-0019887 A1 4/2000  
 WO WO-0032098 A1 6/2000  
 WO WO-0033065 A1 6/2000  
 WO WO-0049941 A1 8/2000  
 WO WO-0059373 A1 10/2000  
 WO WO-0074753 A1 12/2000  
 WO WO-0078210 A1 12/2000  
 WO WO-0112158 A1 2/2001  
 WO WO-0116579 A1 3/2001  
 WO WO-0120019 A2 3/2001  
 WO WO-0120334 A1 3/2001  
 WO WO-0134243 A1 5/2001  
 WO WO-0143660 A2 6/2001  
 WO WO-0152727 A1 7/2001  
 WO WO-0158348 A2 8/2001  
 WO WO-0168901 A2 9/2001  
 WO WO-0169222 A2 9/2001  
 WO WO-0188524 A1 11/2001  
 WO WO-0188534 A2 11/2001  
 WO WO-0205702 A2 1/2002  
 WO WO-0224065 A1 3/2002  
 WO WO-0078210 A9 5/2002  
 WO WO-0208298 A1 10/2002  
 WO WO-0208966 A2 11/2002  
 WO WO-0210026 A1 12/2002  
 WO WO-03000127 A2 1/2003  
 WO WO-03022125 A2 3/2003  
 WO WO-03022327 A2 3/2003  
 WO WO-03063700 A1 8/2003  
 WO WO-03072269 A1 9/2003  
 WO WO-03101862 A1 12/2003  
 WO WO-2004009161 A1 1/2004  
 WO WO-2004110256 A2 12/2004  
 WO WO-2005011489 A1 2/2005  
 WO WO-2005012873 A2 2/2005  
 WO WO-2005026689 A2 3/2005  
 WO WO-2005032400 A2 4/2005  
 WO WO 2005/046780 A1 5/2005  
 WO WO-2005057168 A2 6/2005  
 WO WO-2005057175 A2 6/2005  
 WO WO-2005078424 A1 8/2005  
 WO WO-2005026689 A9 10/2005  
 WO WO-2005093629 A2 10/2005  
 WO WO-2006017358 A1 2/2006  
 WO WO-2006021430 A2 3/2006  
 WO WO 2006/038044 A2 4/2006  
 WO WO-2006050405 A1 5/2006  
 WO WO 2006/067217 A2 6/2006  
 WO WO 2006/075016 A1 7/2006  
 WO WO 2006/077262 A1 7/2006  
 WO WO-2006105146 A2 10/2006  
 WO WO-2006118713 A1 11/2006  
 WO WO-2006131288 A1 12/2006  
 WO WO-2007002209 A2 1/2007  
 WO WO-2007002579 A2 1/2007  
 WO WO 2007/031125 A1 3/2007  
 WO WO-2007065285 A2 6/2007  
 WO WO-2007097754 A1 8/2007  
 WO WO-2007114943 A2 10/2007  
 WO WO-2007127606 A1 11/2007  
 WO WO-2007137286 A2 11/2007  
 WO WO-2007143225 A2 12/2007  
 WO WO-2008001091 A1 1/2008  
 WO WO 2008/065646 A1 6/2008  
 WO WO-2008076868 A2 6/2008  
 WO WO 2008/078319 A1 7/2008

WO WO 2008/083379 A1 7/2008  
 WO WO 2008/115409 A1 9/2008  
 WO WO 2008/124597 A1 10/2008

## OTHER PUBLICATIONS

Aalders, et al., "Development of a Wearable Glucose Sensor; Studies in Healthy Volunteers and in Diabetic Patients," The International Journal Of Artificial Organs, 1991, vol. 14, No. 2, pp. 102-108.  
 Abe, et al., "Characterization of Glucose Microsensors for Intracellular Measurements," Analytical Chemistry, 1992, vol. 64, No. 18, pp. 2160-2163.  
 Abel, et al., "Biosensors For in Vivo Glucose Measurements: Can We Cross the Experimental Stage," Biosensors & Bioelectronics, 2002, vol. 17, pp. 1059-1070.  
 Abel, et al., "Experience With An Implantable Glucose Sensor as a Prerequisite of an Artificial Beta Cell," Biomed. Biochim. Acta, 1984, vol. 43, No. 5, pp. 577-584.  
 Adilman, et al., "Videogames: Knowing The Score, Creative Computing," Dec. 1983, Dialog: File 148; IAC Trade & Industry Database, vol. 9, p. 224(5) (9 pages).  
 Alcock S.J., et al., "Continuous Analyte Monitoring To Aid Clinical Practice," IEEE Engineering in Medicine & Biology, 1994, vol. 13, pp. 319-325.  
 Amer M.M.B., "An Accurate Amperometric Glucose Sensor Based Glucometer with Eliminated Cross-Sensitivity," Journal of Medical Engineering & Technology, vol. 26 (5), Sep./Oct. 2002, pp. 208-213.  
 American Diabetes Association., "Position Statement: Diagnosis and Classification of Diabetes Mellitus," Diabetes Care, vol. 30, Supplement 01, Jan. 2007, pp. S42-S47.  
 American Diabetes Association., "Position Statement: Standards of Medical Care in Diabetes," Diabetes Care, vol. 30, Supplement 01, Jan. 2007, pp. S4-S41.  
 American Diabetes Association., "Summary of Revisions for the 2007 Clinical Practice Recommendations," Diabetes Care, vol. 30, Supplement 01, Jan. 2007, pp. S3.  
 Amin R., et al., "Hypoglycemia Prevalence in Prepubertal Children With Type 1 Diabetes on Standard Insulin Regimen: Use of Continuous Glucose Monitoring System," Diabetes Care, 2003, vol. 26, No. 3, pp. 662-667.  
 Armour J.C., et al., "Application of Chronic Intravascular Blood Glucose Sensor in Dogs," Diabetes, Dec. 1990, vol. 39, pp. 1519-1526.  
 Assolant-Vinet C.H., et al., "New Immobilized Enzyme Membranes for Tailor-Made Biosensors," Analytical Letters, 1986, vol. 19(788), pp. 875-885.  
 Atanasov P., et al., "Biosensor for Continuous Glucose Monitoring," Biotechnology and Bioengineering, John Wiley & sons Inc, 1994, vol. 43, pp. 262-266.  
 Atanasov P., et al., "Implantation of a Refillable Glucose Monitoring-Telemetry Device," Biosensors and Bioelectronics, vol. 12 (7), 1997, pp. 669-680.  
 Aussedat B., et al., "A User-Friendly Method For Calibrating a Subcutaneous Glucose Sensor-Based Hypoglycaemic Alarm," Elsevier Science Limited, Biosensors & Bioelectronic, 1997, vol. 12, No. 11, pp. 1061-1071.  
 Aussedat B., et al., "Interstitial Glucose Concentration and Glycemia: Implications for Continuous Subcutaneous Glucose Monitoring," American Journal of Physiology—Endocrinology and Metabolism, vol. 278 (4), Apr. 1, 2000, pp. E716-E728.  
 Bailey T.S., et al., "Reduction in Hemoglobin A1C with Real-Time Continuous Glucose Monitoring: Results from a 12-Week Observational Study," Diabetes Technology & Therapeutics, vol. 9 (3), 2007, pp. 203-210.  
 Baker D.A., et al., "Dynamic Concentration Challenges for Biosensor Characterization," Biosensors & Bioelectronics, vol. 8, 1993, pp. 433-441.  
 Baker D.A., et al., "Dynamic Delay and Maximal Dynamic Error in Continuous Biosensors," Analytical Chemistry, vol. 68 (8), Apr. 15, 1996, pp. 1292-1297.

(56)

## References Cited

## OTHER PUBLICATIONS

- Bard A.J., et al., "Electrochemical Methods," Fundamentals and Applications, John Wiley & Sons, New York, 1980, pp. 173-175.
- Bardeletti G., et al., "A Reliable L-Lactate Electrode with a New Membrane for Enzyme Immobilization for Amperometric Assay of Lactate," *Analytica Chimica Acta*, vol. 187, 1986, pp. 47-54.
- Beach R.D., et al., "Subminiature Implantable Potentiostat and Modified Commercial Telemetry Device for Remote Glucose Monitoring," *IEEE Transactions on Instrumentation and Measurement*, vol. 48 (6), Dec. 1999, pp. 1239-1245.
- Bellucci F., et al., "Electrochemical Behaviour of Graphite-Epoxy Composite Materials (GECM) in Aqueous Salt Solutions," *Journal of Applied Electrochemistry*, vol. 16 (1), Jan. 1986, pp. 15-22.
- Berger M., et al., "Computer Programs to Assist the Physician in the Analysis of Self-Monitored Blood Glucose Data," *Proceedings of the Annual Symposium on Computer Applications in Medical Care*, 1988, pp. 52-57.
- Bertrand C., et al., "Multipurpose Electrode with Different Enzyme Systems Bound to Collagen Films," *Analytica Chimica Acta*, 1981, vol. 126, pp. 23-34.
- Bessman S.P., et al., "Progress toward a Glucose Sensor for the Artificial Pancreas," *Proceedings of a Workshop on Ion-Selective Microelectrodes*, Jun. 4-5, 1973, Boston University, 1973, pp. 189-197.
- Biermann E., et al., "How Would Patients Behave if they were Continually Informed of their Blood Glucose Levels? A Simulation Study Using a "Virtual" Patient," *Diabetes Technology & Therapeutics*, vol. 10 (3), 2008, pp. 178-187.
- Bindra D.S., et al., "Design and in Vitro Studies of a Needle-Type Glucose Sensor for Subcutaneous Monitoring," *Analytical Chemistry*, vol. 63, Sep. 1, 1991, pp. 1692-1696.
- Bindra D.S., et al., "Pulsed Amperometric Detection of Glucose in Biological Fluids at a Surface-Modified Gold Electrode," *Analytical Chemistry*, vol. 61 (22), Nov. 15, 1989, pp. 2566-2570.
- Bisenberger M., et al., "A Triple-Step Potential Waveform at Enzyme Multisensors with Thick-Film Gold Electrodes for Detection of Glucose and Sucrose," *Sensors and Actuators B*, vol. 28, 1995, pp. 181-189.
- Bland J.M., et al., "A Note on the Use of the Intraclass Correlation Coefficient in the Evaluation of Agreement between Two Methods of Measurement," *Computers in Biology and Medicine*, vol. 20 (5), 1990, pp. 337-340.
- Bland J.M., et al., "Statistical Methods for Assessing Agreement between Two Methods of Clinical Measurement," *The Lancet*, Feb. 8, 1986, pp. 307-310.
- Bobbioni-Harsch E., et al., "Lifespan of Subcutaneous Glucose Sensors and their Performances during Dynamic Glycaemia Changes in Rats," *J. Biomed. Eng.*, vol. 15, 1993, pp. 457-463.
- Bode B.W., "Clinical Utility of the Continuous Glucose Monitoring System," *Diabetes Technology & Therapeutics*, vol. 2, Supplement 1, 2000, pp. S35-S41.
- Bode B.W., et al., "Continuous Glucose Monitoring Used to Adjust Diabetes Therapy Improves Glycosylated Hemoglobin: A Pilot Study," *Diabetes Research and Clinical Practice*, vol. 46, 1999, pp. 183-190.
- Bode B.W., et al., "Using the Continuous Glucose Monitoring System to Improve the Management of Type 1 Diabetes," *Diabetes Technology & Therapeutics*, vol. 2, Supplement 1, 2000, pp. S43-S48.
- Boedeker Plastics Inc., "Polyethylene Specifications," Polyethylene Data Sheet, Retrieved from <http://www.boedeker.com/polye.sub.-p.htm> on Aug. 19, 2009, 4 pages.
- Boland E., et al., "Limitations of Conventional Methods of Self-Monitoring of Blood Glucose," *Diabetes Care*, vol. 24 (11), Nov. 2001, pp. 1858-1862.
- Bolinder J., et al., "Self-Monitoring of Blood Glucose in Type I Diabetic Patients: Comparison with Continuous Microdialysis Measurements of Glucose in Subcutaneous Adipose Tissue during Ordinary Life Conditions," *Diabetes Care*, vol. 20 (1), Jan. 1997, pp. 64-70.
- Bolinder J., et al., "Microdialysis Measurement of the Absolute Glucose Concentration in Subcutaneous Adipose Tissue Allowing Glucose Monitoring in Diabetic Patients," *Rapid Communication, Diabetologia*, vol. 35, 1992, pp. 1177-1180.
- Bott A.W., "A Comparison of Cyclic Voltammetry and Cyclic Staircase Voltammetry," *Current Separations*, vol. 16 (1), 1997, pp. 23-26.
- Bott A.W., "Electrochemical Methods for the Determination of Glucose," *Current Separations*, vol. 17 (1), 1998, pp. 25-31.
- Bowman L., et al., "The Packaging of Implantable Integrated Sensors," *IEEE Transactions in Biomedical Engineering*, vol. BME-33 (2), Feb. 1986, pp. 248-255.
- Brauker J., et al., "Local Inflammatory Response Around Diffusion Chambers Containing Xenografts," *Transplantation*, vol. 61 (12), Jun. 27, 1996, pp. 1671-1677.
- Braunwald E., "Biomarkers in Heart Failure," *Medical Progress, The New England Journal of Medicine*, vol. 358, May 15, 2008, pp. 2148-2159.
- Bremer T., et al., "Is Blood Glucose Predictable from Previous Values? A Solicitation for Data," *Perspectives in Diabetes*, vol. 48, Mar. 1999, pp. 445-451.
- Bremer T.M., et al., "Benchmark Data from the Literature for Evaluation of New Glucose Sensing Technologies," *Diabetes Technology & Therapeutics*, vol. 3 (3), 2001, pp. 409-418.
- Brooks S.L., et al., "Development of an On-line Glucose Sensor for Fermentation Monitoring," *Biosensors*, vol. 3, 1987/1988, pp. 45-56.
- Bruckel J., et al., "In Vivo Measurement of Subcutaneous Glucose Concentrations with an Enzymatic Glucose Sensor and a Wick Method," *Klin Wochenschr*, vol. 67, 1989, pp. 491-495.
- Brunstein E., et al., "Preparation and Validation of Implantable Electrodes for the Measurement of Oxygen and Glucose," *Biomed Biochim. Acta*, vol. 48 (11/12), 1989, pp. 911-917.
- Cai Q., et al., "A Wireless, Remote Query Glucose Biosensor Based on a pH-Sensitive Polymer," *Analytical Chemistry*, vol. 76 (14), Jul. 15, 2004, pp. 4038-4043.
- Cameron T., et al., "Micromodular Implants to Provide Electrical Stimulation of Paralyzed Muscles and Limbs," *IEEE Transactions on Biomedical Engineering*, vol. 44 (9), Sep. 1997, pp. 781-790.
- Campanella L., et al., "Biosensor for Direct Determination of Glucose and Lactate in Undiluted Biological Fluids," *Biosensors & Bioelectronics*, vol. 8, 1993, pp. 307-314.
- Candas B., et al., "An Adaptive Plasma Glucose Controller Based on a Nonlinear Insulin/Glucose Model," *IEEE Transactions on Biomedical Engineering*, vol. 41 (2), Feb. 1994, pp. 116-124.
- Cass A.E.G., et al., "Ferrocene-Mediated Enzyme Electrodes for Amperometric Determination of Glucose," *Analytical Chemistry*, vol. 56 (4), Apr. 1984, pp. 667-671.
- Cassidy J.F., et al., "Novel Electrochemical Device for the Detection of Cholesterol or Glucose," *Analyst*, vol. 118, Apr. 1993, pp. 415-418.
- Chase H.P., et al., "Continuous Subcutaneous Glucose Monitoring in Children with Type 1 Diabetes," *Pediatrics*, vol. 107 (2), Feb. 2001, pp. 222-226.
- Chase J.G., et al., "Targeted Glycemic Reduction in Critical Care Using Closed-Loop Control," *Diabetes Technology & Therapeutics*, vol. 7 (2), 2005, pp. 274-282.
- Chen T., et al., "Defining the Period of Recovery of the Glucose Concentration after its Local Perturbation by the Implantation of a Miniature Sensor," *Clinical Chemistry and Laboratory Medicine*, vol. 40 (8), 2002, pp. 786-789.
- Chia C.W., et al., "Glucose Sensors: Toward Closed Loop Insulin Delivery," *Endocrinology and Metabolism Clinics of North America*, vol. 33, 2004, pp. 175-195.
- Choleau C., et al., "Calibration of a Subcutaneous Amperometric Glucose Sensor Implanted for 7 Days in Diabetic Patients Part 2. Superiority of the One-point Calibration Method," *Biosensors and Bioelectronics*, vol. 17 (8), 2002, pp. 647-654.
- Choleau C., et al., "Calibration of a Subcutaneous Amperometric Glucose Sensor Part 1. Effect of Measurement Uncertainties on the Determination of Sensor Sensitivity and Background Current," *Biosensors and Bioelectronics*, vol. 17, 2002, pp. 641-646.

(56)

## References Cited

## OTHER PUBLICATIONS

- Ciba Specialty Chemicals, "Ciba® IRGACURE® 2959," Coating Effects Segment, Photoinitiator Product Description, Basel Switzerland, Apr. 2, 1998, 3 pages.
- Claremont D.J., et al., "Potentially-Implantable, Ferrocene-Mediated Glucose Sensor," *Journal of Biomedical Engineering*, vol. 8, Jul. 1986, pp. 272-274.
- Claremont D.J., et al., "Subcutaneous Implantation of a Ferrocene-Mediated Glucose Sensor in Pigs," *Diabetologia*, vol. 29, 1986, pp. 817-821.
- Clark L.C., et al., "Configurational Cyclic Voltammetry: Increasing the Specificity and Reliability of Implanted Electrodes," *IEEE/Ninth Annual Conference of the Engineering in Medicine and Biology Society*, 1987, pp. 0782-0783.
- Clark L.C., et al., "Long-Term Stability of Electroenzymatic Glucose Sensors Implanted in Mice," vol. XXXIV, *Transactions—American Society for Artificial Internal Organs*, 1988, vol. 34, pp. 259-265.
- Clark L.C., et al., "One-Minute Electrochemical Enzymic Assay for Cholesterol in Biological Materials," *Clinical Chemistry*, vol. 27 (12), 1981, pp. 1978-1982.
- Clarke W.L., et al., "Evaluating Clinical Accuracy of Systems for Self Monitoring of Blood Glucose," *Technical Articles, Diabetes Care*, vol. 10 (5), Sep.-Oct. 1987, pp. 622-628.
- Colangelo V.J., et al., "Corrosion Rate Measurements in Vivo," *Journal of Biomedical Materials Research*, vol. 1, 1967, pp. 405-414.
- Colowick S.P., et al., "Methods in Enzymology," vol. XLIV, *Immobilized Enzymes*, Edited by Mosbach K, New York Academic Press, 1976, 11 pages.
- Coulet P.R., et al., "Enzymes Immobilized on Collagen Membranes: A Tool for Fundamental Research and Enzyme Engineering," *Journal of Chromatography*, vol. 215, 1981, pp. 65-72.
- Coulet P.R., "Polymeric Membranes and Coupled Enzymes in the Design of Biosensors," *Journal of Membrane Science*, 1992, vol. 68, pp. 217-228.
- Cox D.J., et al., "Accuracy of Perceiving Blood Glucose in IDDM," *Diabetes Care*, vol. 8 (6), Nov.-Dec. 1985, pp. 529-536.
- Csoregi E., et al., "Amperometric Microbiosensors for Detection of Hydrogen Peroxide and Glucose Based on Peroxidase-Modified Carbon Fibers," *Electroanalysis*, vol. 6, 1994, pp. 925-933.
- Csoregi E., et al., "Design, Characterization and One-Point in Vivo Calibration of a Subcutaneously Implanted Glucose Electrode," *American Chemical Society, Analytical Chemistry*, vol. 66 (19), Oct. 1, 1994, pp. 3131-3138.
- Currie J.F., et al., "Novel Non-Intrusive Trans-Dermal Remote Wireless Micro-Fluidic Monitoring System Applied to Continuous Glucose and Lactate Assays for Casualty Care and Combat Readiness Assessment," *RTO HFM Symposium, RTO-MP-HFM-109*, Aug. 16-18, 2004, pp. '24-1'-'24-18'.
- Danielsson B., et al., "Enzyme Thermistors," *Methods in Enzymology*, vol. 137, 1988, pp. 181-197.
- Dassau E., et al., "In Silico Evaluation Platform for Artificial Pancreatic  $\beta$ -Cell Development—A Dynamic Simulator for Closed-Loop Control with Hardware-in-the-loop," *Diabetes Technology & Therapeutics*, vol. 11 (3), 2009, pp. 1-8.
- Davies M.L., et al., "Polymer Membranes in Clinical Sensor Applications," *An overview of membrane function, Biomaterials*, vol. 13 (14), 1992, pp. 971-978.
- Davis G., et al., "Bioelectrochemical Fuel Cell and Sensor Based on a Quinoprotein, Alcohol Dehydrogenase," *Enzyme and Microbial Technology*, vol. 5 (5), Sep. 1983, pp. 383-388.
- De Vos P., et al., "Considerations for Successful Transplantation of Encapsulated Pancreatic Islets," *Diabetologia*, vol. 45, 2002, pp. 159-173.
- Deutsch T., et al., "Time Series Analysis and Control of Blood Glucose Levels in Diabetic Patients," *Computer Methods and Programs in Biomedicine*, Elsevier Scientific Publishers, vol. 41, 1994, pp. 167-182.
- Dixon B.M., et al., "Characterization in Vitro and in Vivo of the Oxygen Dependence of an Enzyme/Polymer Biosensor for Monitoring Brain Glucose," *Journal of Neuroscience Methods*, vol. 119, 2002, pp. 135-142.
- Dupont, "Dimension® AR Clinical Chemistry System," *The Chemistry Analyzer that Makes the most of your Time, Money and Effort*, Dade International, Chemistry Systems, Newark, 1998, 18 pages.
- Durliat H., et al., "Spectrophotometric and Electrochemical Determinations of L(+)-Lactate in Blood by Use of Lactate Dehydrogenase from Yeast," *Clinical Chemistry*, vol. 22 (11), 1976, pp. 1802-1805.
- Edwards Lifesciences, "Accuracy for You and Your Patients," *Marketing materials*, 2002, 4 pages.
- El Degheidy M.M., et al., "Optimization of an Implantable Coated Wire Glucose Sensor," *Journal of Biomedical Engineering*, vol. 8, Apr. 1986, pp. 121-129.
- ELCO Diagnostics Company, "Direct 30/30® Blood Glucose Sensor," *Markwell Medical Catalog*, 1990, 1 page.
- El-Khatib F.H., et al., "Adaptive Closed-Loop Control Provides Blood-Glucose Regulation Using Dual Subcutaneous Insulin and Glucagon Infusion in Diabetic Swine," *Journal of Diabetes Science and Technology, Diabetes Technology Society*, vol. 1 (2), 2007, pp. 181-192.
- El-Sa'ad L., et al., "Moisture Absorption by Epoxy Resins: The Reverse Thermal Effect," *Journal of Materials Science*, vol. 25, 1990, pp. 3577-3582.
- Ernst H., et al., "Reliable Glucose Monitoring Through the Use of Microsystem Technology," *Analytical Bioanalytical Chemistry*, vol. 373, 2002, pp. 758-761.
- European Search Report for Application No. 98908875.2 dated Apr. 29, 2004, 5 pages.
- Extended European Search Report for Application No. 07844038.5 dated Dec. 21, 2012, 9 pages.
- Extended European Search Report for Application No. 10163654.6 dated Aug. 3, 2010, 10 pages.
- Extended European Search Report for Application No. 10163675.1, dated Aug. 3, 2010, 10 pages.
- Fabietti P.G., et al., "Clinical Validation of a New Control-Oriented Model of Insulin and Glucose Dynamics in Subjects with Type 1 Diabetes," *Diabetes Technology & Therapeutics*, vol. 9 (4), 2007, pp. 327-338.
- Fahy B.G., et al., "An Analysis: Hyperglycemic Intensive Care Patients Need Continuous Glucose Monitoring—Easier Said Than Done," *Journal of Diabetes Science and Technology, Diabetes Technology Society*, vol. 2 (2), Mar. 2008, pp. 201-204.
- Fare T.L., et al., "Functional Characterization of a Conducting Polymer-Based Immunoassay System," *Biosensors & Bioelectronics*, vol. 13 (3-4), 1998, pp. 459-470.
- Feldman B., et al., "A Continuous Glucose Sensor Based on Wired Enzyme™ Technology—Results from a 3-Day Trial in Patients with Type 1 Diabetes," *Diabetes Technology & Therapeutics*, vol. 5 (5), 2003, pp. 769-779.
- File History of U.S. Appl. No. 09/447,227, filed Nov. 22, 1999, 1184 pages.
- File History of U.S. Appl. No. 10/789,359, filed Feb. 26, 2004, 361 pages.
- File History of U.S. Appl. No. 10/838,658, filed May 3, 2004, 748 pages.
- File History of U.S. Appl. No. 10/838,909, filed May 3, 2004, 356 pages.
- File History of U.S. Appl. No. 10/838,912, filed May 3, 2004, 1288 pages.
- File History of U.S. Appl. No. 10/885,476, filed Jul. 6, 2004, 226 pages.
- File History of U.S. Appl. No. 10/897,312, filed Jul. 21, 2004, 139 pages.
- File History of U.S. Appl. No. 11/157,365, filed Jun. 21, 2005, 977 pages.
- File History of U.S. Appl. No. 12/133,738, filed Jun. 5, 2008, 557 pages.
- File History of U.S. Appl. No. 12/133,761, filed Jun. 5, 2008, 585 pages.
- File History of U.S. Appl. No. 12/133,786, filed Jun. 5, 2008, 814 pages.

(56)

**References Cited****OTHER PUBLICATIONS**

File History of U.S. Appl. No. 12/133,820, filed Jun. 5, 2008, 1273 pages.

File History of U.S. Appl. No. 12/536,852, filed Aug. 6, 2009, 480 pages.

File History of U.S. Appl. No. 12/579,385, filed Oct. 14, 2009, 558 pages.

File History of U.S. Appl. No. 95/001,818, filed Nov. 11, 2011, 1238 pages.

Fischer U., et al., "Assessment of Subcutaneous Glucose Concentration: Validation of the Wick Technique as a Reference for Implanted Electrochemical Sensors in Normal and Diabetic Dogs," *Diabetologia*, vol. 30, 1987, pp. 940-945.

Fischer U., et al., "Hypoglycaemia-Warning by Means of Subcutaneous Electrochemical Glucose Sensors: An Animal Study," *Horm. Metab. Res.*, vol. 27, 1995, p. 53. (Abstract Only).

Fischer U., et al., "Oxygen Tension at the Subcutaneous Implantation Site of Glucose Sensors," *Biomed. Biochim. Acta*, vol. 48 (11/12), 1989, pp. 965-971.

Freedman D., et al., "Statistics," Second Edition, W.W. Norton & Company, New York & London, 1991, p. 74 (3 pages).

Freiberger P., "Video Game Takes on Diabetes Superhero 'Captain Novolin' Offers Treatment Tips," Fourth Edition, Jun. 26, 1992, Business Section, 2 pages.

Frohnauer M.K., et al., "Graphical Human Insulin Time-Activity Profiles Using Standardized Definitions," *Diabetes Technology & Therapeutics*, vol. 3 (3), 2001, pp. 419-429.

Frost M.C., et al., "Implantable Chemical Sensors for Real-Time Clinical Monitoring: Progress and Challenges," *Current Opinion in Chemical Biology, Analytical Techniques*, vol. 6, 2002, pp. 633-641.

Gabby R.A., et al., "Optical Coherence Tomography-Based Continuous Noninvasive Glucose Monitoring in Patients with Diabetes," *Diabetes Technology & Therapeutics*, vol. 10, Nov. 3, 2008, pp. 188-193.

Ganesan N., et al., "Gold Layer-Based Dual Crosslinking Procedure of Glucose Oxidase with Ferrocene Monocarboxylic Acid Provides a Stable Biosensor," *Analytical Biochemistry, Notes & Tips*, vol. 343, 2005, pp. 188-191.

Ganesh A., et al., "Evaluation of the VIA® Blood Chemistry Monitor for Glucose in Healthy and Diabetic Volunteers," *Journal of Diabetes Science and Technology*, vol. 2 (2), Mar. 2008, pp. 182-193.

Garg S.K., et al., "Correlation of Fingerstick Blood Glucose Measurements With GlucoWatch Biographer Glucose Results in Young Subjects With Type 1 Diabetes," *Emerging Treatments and Technologies, Diabetes Care*, vol. 22 (10), Oct. 1999, pp. 1708-1714.

Garg S.K., et al., "Improved Glucose Excursions Using an Implantable Real-Time Continuous Glucose Sensor in Adults With Type 1 Diabetes," *Emerging Treatments and Technologies, Diabetes Care*, vol. 27 (3), 2004, pp. 734-738.

Garg S.K., "New Insulin Analogues," *Diabetes Technology & Therapeutics*, vol. 7 (5), 2005, pp. 813-817.

Gerritsen M., et al., "Performance of Subcutaneously Implanted Glucose Sensors for Continuous Monitoring," *The Netherlands Journal of Medicine*, vol. 54, 1999, pp. 167-179.

Gerritsen M., et al., "Problems Associated with Subcutaneously Implanted Glucose Sensors," *Diabetes Care*, vol. 23 (2), Feb. 2000, pp. 143-145.

Gilligan B.J., et al., "Evaluation of a Subcutaneous Glucose Sensor Out to 3 Months in a Dog Model" *Diabetes Care*, vol. 17 (8), Aug. 1994, pp. 882-887.

Gilligan B.J., et al., "Feasibility of Continuous Long-Term Glucose Monitoring from a Subcutaneous Glucose Sensor in Humans," *Diabetes Technology & Therapeutics*, vol. 6 (3), 2004, pp. 378-386.

Godsland I.F., et al., "Maximizing the Success Rate of Minimal Model Insulin Sensitivity Measurement in Humans: The Importance of Basal Glucose Levels," *The Biochemical Society and the Medical Research Society, Clinical Science*, vol. 101, 2001, pp. 1-9.

Gouda M.D., et al., "Thermal Inactivation of Glucose Oxidase," *The Journal of Biological Chemistry*, vol. 278 (27), Issue of Jul. 4, 2003, pp. 24324-24333.

Gough D.A., et al., "Frequency Characterization of Blood Glucose Dynamics," *Annals of Biomedical Engineering*, vol. 31, 2003, pp. 91-97.

Gough D.A., et al., "Immobilized Glucose Oxidase in Implantable Glucose Sensor Technology," *Diabetes Technology & Therapeutics*, vol. 2 (3), 2000, pp. 377-380.

Gough D.A., "The implantable Glucose Sensor: An Example of Bioengineering Design," *Introduction to Bioengineering*, 2001, Chapter 3, pp. 57-66.

Gross, et al., "Diabetes Technology & Therapeutics," *Letters to the Editor, Diabetes Technology & Therapeutics*, vol. 3 (1), 2001, pp. 129-131.

Gross T.M., et al., "Efficacy and Reliability of the Continuous Glucose Monitoring System," *Diabetes Technology & Therapeutics*, vol. 2, Supplement 1, 2000, pp. S19-S26.

Gross T.M., et al., "Performance Evaluation Of The Minimed® Continuous Glucose Monitoring System During Patient Home Use," *Diabetes Technology & Therapeutics*, vol. 2(1), 2000, pp. 49-56.

Guerci B., et al., "Clinical Performance of CGMS in Type 1 Diabetic Patients Treated by Continuous Subcutaneous Insulin Infusion Using Insulin Analogs," *Diabetes Care*, vol. 26, 2003, pp. 582-589.

Hagvik J., "Glucose Measurement: Time for a Gold Standard," *Journal of Diabetes Science and Technology*, vol. 1 (2), Mar. 2007, pp. 169-172.

Hall S.B., et al., "Electrochemical Oxidation of Hydrogen Peroxide at Platinum Electrodes. Part I. An Adsorption-controlled Mechanism," *Electrochimica Acta*, vol. 43, Nos. 5/6, 1998, pp. 579-588.

Hall S.B., et al., "Electrochemical Oxidation of Hydrogen Peroxide at Platinum Electrodes. Part II: Effect of potential," *Electrochimica Acta*, vol. 43 (14-15), 1998, pp. 2015-2024.

Hall S.B., et al., "Electrochemical Oxidation of Hydrogen Peroxide at Platinum Electrodes. Part III: Effect of Temperature," *Electrochimica Acta*, vol. 44, 1999, pp. 2455-2462.

Hall S.B., et al., "Electrochemical Oxidation of Hydrogen Peroxide at Platinum Electrodes. Part IV: Phosphate Buffer Dependence," *Electrochimica Acta*, vol. 44, 1999, pp. 4573-4582.

Hall S.B., et al., "Electrochemical Oxidation of Hydrogen Peroxide at Platinum Electrodes. Part V: Inhibition by Chloride," *Electrochimica Acta*, vol. 45, 2000, pp. 3573-3579.

Hamilton, "Complete Guide to Selecting the Right Hamilton Gastight, Microliter, and Specialty Syringe for your Application," *Syringe Selection*, <http://www.hamiltoncompany.com> 2006, 20 pages.

Hashiguchi Y., et al., "Development of a Miniaturized Glucose Monitoring System by Combining a Needle-Type Glucose Sensor with Microdialysis Sampling Method: Long-term subcutaneous tissue glucose monitoring in ambulatory diabetic patients," *Diabetes Care*, vol. 17, No. 5, May 1994, pp. 387-396.

Heinemann L., et al., "Review: Measurement of Insulin Absorption and Insulin Action," *Diabetes Technology & Therapeutics*, vol. 6 (5), 2004, pp. 698-718.

Heinemann L., "Measurement Quality of Blood Glucose Meters: Is There a Need for an Institution with an Unbiased View?," *Journal of Diabetes Science and Technology*, vol. 1 (2), Mar. 2007, pp. 178-180.

Heinemann L., "Review: Variability of Insulin Absorption and Insulin Action," *Diabetes Technology & Therapeutics*, vol. 4 (5), 2002, pp. 673-682.

Heise T., et al., "Hypoglycemia warning signal and glucose sensors: Requirements and concepts," *Diabetes Technology & Therapeutics*, vol. 5, No. 4, 2003, pp. 563-571.

Heller A., "Electrical Connection of Enzyme Redox Centers to Electrodes," *J. Phys. Chem.*, vol. 96, 1992, pp. 3579-3587.

Heller A., "Electrical Wiring of Redox Enzymes," *Ace. Chem. Res.*, vol. 23, 1990, pp. 128-134.

Heller A., "Implanted Electrochemical Glucose Sensors for the Management of Diabetes," *Annu. Rev., Biomed Eng.*, vol. 1, 1999, pp. 153-175.



(56)

## References Cited

## OTHER PUBLICATIONS

- Heller A., "Plugging Metal Connectors into Enzymes," *Nature Biotechnology*, vol. 21, No. 6, Jun. 2003, pp. 631-632.
- Hicks J.M., "In Situ Monitoring," *Clinical Chemistry*, vol. 31 (12), 1985, pp. 1931-1935.
- Hitchman M.L., "Measurement of Dissolved Oxygen," Edited by ELVING P.J. et al., *Chemical Analysis*, New York, John Wiley & Sons, vol. 49, Chapter 3, 1978, pp. 34-49 and 59-123.
- Hoel P.G., "Elementary Statistics," Fourth Edition, John Wiley & Sons, Inc., 1976, pp. 113-114.
- Houghton Mifflin Company, "American Heritage Dictionary," 4th Edition, 2000, pp. 82.
- Houghton Mifflin Company, "Xenogenic, the American Heritage Stedman's Medical Dictionary," 2002, Answers.Com, retrieved from <http://www.answers.com/topic/xenogenic>, on Nov. 7, 2006, 2 Pages.
- Hovorka R., et al., "Closing the Loop: The Adicol Experience," *Diabetes Technology & Therapeutics*, vol. 6 (3), 2004, pp. 307-318.
- Hrapovic S., et al., "Picoamperometric Detection of Glucose at Ultrasmall Platinum-Based Biosensors Preparation and Characterization," *Anal. Chem.*, vol. 75, 2003, pp. 3308-3315.
- Hu Y., et al., "A Needle-Type Enzyme-Based Lactate Sensor for In Vivo Monitoring," *Analytica Chimica Acta*, vol. 281, 1993, pp. 503-511.
- Huang C., et al., "Electrochemical Generation of Oxygen. 1: The Effects of Anions and Cations on Hydrogen Chemisorption and Anodic Oxide Film Formation on Platinum Electrode. 2: The Effects of Anions and Cations on Oxygen Generation on Platinum Electrode," U.S. Department of Commerce/NTIS, 1975, 126 pages.
- Huang Q., et al., "A 0.5mW Passive Telemetry IC for Biomedical Applications," Proceedings of the 23rd European Solid-State Circuits Conference (ESSCIRC '97), Southampton, UK, Sep. 16-18, 1997, pp. 172-175.
- Hunsley B., et al., "Whole Blood Glucose Standard Is Key to Accurate Insulin Dosages," *Journal of Diabetes Science and Technology*, vol. 1 (2), Mar. 2007, pp. 173-177.
- Hunter I., et al., "Minimally Invasive Glucose Sensor and Insulin Delivery System," MIT Home Automation and Healthcare Consortium, Mar. 31, 2000, Progress Report No. 25, 17 pages.
- International Preliminary Report on Patentability for Application No. PCT/US2005/006301, dated Aug. 30, 2006, 4 pages.
- International Preliminary Report on Patentability for Application No. PCT/US2007/080848 dated Apr. 13, 2010, 6 pages.
- International Preliminary Report on Patentability for Application No. PCT/US2008/058158, dated Sep. 29, 2009, 9 pages.
- International Search Report and Written Opinion for Application No. PCT/US2005/006301, dated Jun. 22, 2005, 4 pages.
- International Search Report and Written Opinion for Application No. PCT/US2007/080848 dated Aug. 28, 2008, 6 pages.
- International Search Report and Written Opinion for Application No. PCT/US2008/058158, dated Aug. 8, 2008, 10 pages.
- Ishikawa M., et al., "Initial Evaluation of A 290-Mm Diameter Subcutaneous Glucose Sensor: Glucose Monitoring With A Biocompatible, Flexible-Wire, Enzyme-Based Amperometric Microsensor in Diabetic and Nondiabetic Humans," *Journal of Diabetes and Its Complications*, vol. 12, 1998, pp. 295-301.
- Jablecki M., et al., "Simulations of the Frequency Response of Implantable Glucose Sensors," *Analytical Chemistry*, vol. 72, 2000, 1853-1859.
- Jaffari S.A., et al., "Recent Advances in Amperometric Glucose Biosensors for In Vivo Monitoring," *Physiological Measurement*, 1995, vol. 16, pp. 1-15.
- Jaremkó J., et al., "Advances Toward the Implantable Artificial Pancreas for Treatment of Diabetes," *Diabetes Care*, vol. 21 (3), Mar. 1998, pp. 444-450.
- Jensen M.B., et al., "Fast Wave Forms for Pulsed Electrochemical Detection of Glucose by Incorporation of Reductive Desorption of Oxidation Products," *Analytical Chemistry*, vol. 69 (9), May 1997, pp. 1776-1781.
- Jeong R.A., et al., "In Vivo Calibration of the Subcutaneous Amperometric Glucose Sensors Using a Non-Enzyme Electrode," *Biosensors and Bioelectronics*, Elsevier, vol. 19, 2003, pp. 313-319.
- Jeutter D.C., "A Transcutaneous Implanted Battery Recharging and Biotelemetry Power Switching System," *IEEE Transactions on Biomedical Engineering*, vol. BME-29 (5), May 1982, pp. 314-321.
- Jeutter D.C., et al., "Design of a Radio-Linked Implantable Cochlear Prosthesis Using Surface Acoustic Wave Devices," *IEEE Transactions on Ultrasonics, Ferroelectrics and Frequency Control*, vol. 40 (5), Sep. 1993, pp. 469-477.
- Jobst G., et al., "Thin-Film Microbiosensors for Glucose-Lactate Monitoring," *Anal. Chem.*, Sep. 15, 1996, vol. 68(18), pp. 3173-3179.
- Johnson K.W., et al., "In Vivo Evaluation of an Electroenzymatic Glucose Sensor Implanted in Subcutaneous Tissue," *Biosensors and Bioelectronics*, 1992, vol. 7, pp. 709-714.
- Johnson K.W., "Reproducible Electrodeposition of Biomolecules for the Fabrication of Miniature Electroenzymatic Biosensors," *Sensors and Actuators B*, vol. 5, 1991, pp. 85-89.
- Jones S.M., et al., "Optimal Insulin Pump Dosing and Postprandial Glycemia Following a Pizza Meal Using the Continuous Glucose Monitoring System," *Diabetes Technology & Therapeutics*, vol. 7 (2), Apr. 2005, pp. 233-240.
- Joung G.B., et al., "An Energy Transmission System for an Artificial Heart Using Leakage Inductance Compensation of Transcutaneous Transformer," *IEEE Transactions on Power Electronics*, vol. 13 (6), Nov. 1998, pp. 1013-1022.
- Jovanovic L.M.D., "The Role of Continuous Glucose Monitoring in Gestational Diabetes Mellitus," *Diabetes Technology and Therapeutics*, vol. 2 (1), 2000, pp. S67-S71.
- Kacaniklic V., et al., "Amperometric Biosensors for Detection of L- and D-Amino Acids Based on Coimmobilized Peroxidase and L- and D-Amino Acid Oxidases in Carbon Paste Electrodes," *Electroanalysis*, vol. 6, May-Jun. 1994, pp. 381-390.
- Kamath A., et al., "Calibration of a Continuous Glucose Monitor: Effect of Glucose Rate of Change," Eighth Annual Diabetes Technology Meeting, Nov. 13-15, 2008, pp. A88 (2 pages).
- Kang S.K., et al., "In Vitro and Short-Term in Vivo Characteristics of a Kel-F Thin Film Modified Glucose Sensor," *Analytical Sciences*, vol. 19, Nov. 2003, pp. 1481-1486.
- Kaplan S.M., "Wiley Electrical and Electronics Engineering Dictionary," IEEE Press, John Wiley & Sons, Inc., 2004, pp. 141, 142, 548 & 549.
- Kaufman F.R., et al., "A Pilot Study of the Continuous Glucose Monitoring System," *Diabetes Care*, vol. 24 (12), Dec. 2001, pp. 2030-2034.
- Kaufman F.R., "Role of the Continuous Glucose Monitoring System in Pediatric Patients," *Diabetes Technology and Therapeutics*, vol. 2 (1), 2000, S49-S52.
- Kawagoe J.L., et al., "Enzyme-Modified Organic Conducting Salt Microelectrode," *Analytical Chemistry*, vol. 63, 1991, pp. 2961-2965.
- Keedy F.H., et al., "Determination of Urate in Undiluted Whole Blood by Enzyme Electrode," *Biosensors and Bioelectronics*, vol. 6, 1991, pp. 491-499.
- Kerner, et al., "A Potentially Implantable Enzyme Electrode for Amperometric Measurement of Glucose," *Hormone and Metabolic Research Supplement*, vol. 20, 1988, pp. 8-13.
- Kerner W., et al., "The Function of a Hydrogen Peroxide-Detecting Electroenzymatic Glucose Electrode is Markedly Impaired in Human Sub-Cutaneous Tissue and Plasma," *Biosensors and Bioelectronics*, vol. 8, 1993, pp. 473-482.
- Kerner W., "Implantable Glucose Sensors: Present Status and Future Developments," *Experimental and Clinical Endocrinol Diabetes*, vol. 109 (2), 2001, pp. S341-S346.
- Kiechle F.L., "The Impact of Continuous Glucose Monitoring on Hospital Point-of-Care Testing Programs," *Diabetes Technology and Therapeutics*, vol. 3 (4), 2001, pp. 647-649.
- Kizilel S., et al., "Review: The Bioartificial Pancreas: Progress and Challenges," *Diabetes Technology & Therapeutics*, vol. 7 (6), 2005, pp. 968-985.

(56)

## References Cited

## OTHER PUBLICATIONS

- Klonoff D., et al., "Performance Metrics for Continuous Interstitial Glucose Monitoring; Approved Guideline," Clinical and Laboratory Standards Institute, POCT05-A, vol. 28 (33), 2008, 72 pages.
- Klonoff D.C., "Editorial: Current, Emerging, and Future Trends in Metabolic Monitoring," *Diabetes Technology & Therapeutics*, vol. 4 (5), 2002, pp. 583-588.
- Klueh U., et al., "Use of Vascular Endothelial Cell Growth Factor Gene Transfer to Enhance Implantable Sensor Function in Vivo," *Biosensor Function and VEGF-Gene Transfer*, vol. 67 (4), 2003, pp. 1072-1086.
- Kondo T., et al., "A Miniature Glucose Sensor, Implantable in the Blood Stream," *Diabetes Care*, vol. 5 (3), May-Jun. 1982, 218-221.
- Koschinsky T., et al., "Sensors For Glucose Monitoring: Technical And Clinical Aspects," *Diabetes Metabolism Research and Reviews*, vol. 17, No. 2, Jan. 1, 2001, pp. 113-123.
- Koschinsky T., et al., "New Approach to Technical and Clinical Evaluation of Devices for Self-Monitoring of Blood Glucose," *Diabetes Care*, vol. 11 (8), Sep. 1988, pp. 619-629.
- Koschinsky T., et al., "Review: Glucose Sensors and the Alternate Site Testing-like Phenomenon: Relationship Between Rapid Blood Glucose Changes and Glucose Sensor Signals," *Diabetes Technology & Therapeutics*, vol. 5 (5), 2003, pp. 829-842.
- Kost J., et al., "Glucose-Sensitive Membranes Containing Glucose Oxidase: Activity, Swelling, And Permeability Studies," *Journal of Biomedical Materials Research*, vol. 19, 1985, pp. 1117-1133.
- Koudelka M., et al., "In Vivo Response of Microfabricated Glucose Sensors to Glycemia Changes in Normal Rats," *Biomed. Biochim. Acta*, vol. 48 (11/12), Nov.-Dec. 1989, pp. 953-956.
- Koudelka M., et al., "In-Vivo Behaviour of Hypodermically Implanted Microfabricated Glucose Sensors," *Biosensors and Bioelectronics*, vol. 6, 1991, pp. 31-36.
- Kovatchev B.P., et al., "Evaluating the Accuracy of Continuous Glucose-Monitoring Sensors: Continuous Glucose-Error Grid Analysis Illustrated by TheraSense Freestyle Navigator Data," *Diabetes Care*, vol. 27 (8), Aug. 2004, pp. 1922-1928.
- Kraver., et al., "A Mixed-Signal Sensor Interface Microinstrument," *Sensors and Actuators A, Physical* 2001, vol. 91, pp. 266-277.
- Krouwer J.S., "Setting Performance Goals and Evaluating Total Analytical Error for Diagnostic Assays," *Clinical Chemistry*, vol. 48 (6), 2002, pp. 919-927.
- Kruger D., et al., "Psychological Motivation and Patient Education: A Role for Continuous Glucose Monitoring," *Diabetes Technology and Therapeutics*, vol. 2 (1), 2000, pp. S93-S97.
- Kulys J., et al., "Carbon-Paste Biosensors Array for Long-Term Glucose Measurement," *Biosensors & Bioelectronics*, vol. 9, 1994, pp. 491-500.
- Kunjan K., et al., "Automated Blood Sampling and Glucose Sensing in Critical Care Settings," *Journal of Diabetes Science and Technology*, vol. 2 (2), Mar. 2008, pp. 194-200.
- Kurnik R.T., et al., "Application of the Mixtures of Experts Algorithm for Signal Processing in a Noninvasive Glucose Monitoring System," *Sensors and Actuators B*, vol. 60, 1999, pp. 19-26.
- Kuriz T.W., et al., "Recommendations for Blood Pressure Measurement in Humans and Experimental Animals, Part 2: Blood Pressure Measurement In Experimental Animals: A Statement for Professionals From the Subcommittee of Professional and Public Education of the American Heart Association Council on High Blood Pressure Research," *Hypertension*, Feb. 2005, vol. 45, pp. 299-310.
- Lacourse W.R., et al., "Optimization of Waveforms for Pulsed Amperometric Detection of Carbohydrates Based on Pulsed Voltammetry," *Analytical Chemistry*, vol. 65, 1993, pp. 50-52.
- Ladd M.F.C., et al., "Structure Determination By X-Ray Crystallography," 3rd Edition, Plenum Press, 1994, Ch. 1, pp. xxi-xxiv and 1-58.
- Lee S.W., et al., "Combined Insulin Pump Therapy with Real-Time Continuous Glucose Monitoring Significantly Improves Glycemic Control Compared to Multiple Daily Injection Therapy in Pump Naive Patients with Type 1 Diabetes; Single Center Pilot Study Experience," *Journal of Diabetes Science and Technology*, vol. 1 (3), May 2007, pp. 400-404.
- Lehmann E.D., et al., Retrospective Validation of a Physiological Model of Glucose-Insulin Interaction in Type 1 Diabetes Mellitus. *Medical Engineering & Physics*, vol. 16, May 1994, pp. 193-202.
- Lerner., et al., "An Implantable Electrochemical Glucose Sensor," *Ann. N. Y. Acad. Sci.*, vol. 428, May 1984, pp. 263-278.
- Lewandowski J.J., et al., "Evaluation of a Miniature Blood Glucose Sensor," *Transactions—American Society for Artificial Internal Organs*, vol. 34, 1988, pp. 255-258.
- Leypoldt J.K., et al., "Model of a Two-Substrate Enzyme Electrode for Glucose," *Analytical Chemistry*, vol. 56, 1984, pp. 2896-2904.
- Linke B., et al., "Amperometric Biosensor for In Vivo Glucose Sensing Based on Glucose Oxidase Immobilized In A Redox Hydrogel," *Biosensors and Bioelectronics*, vol. 9, 1994, pp. 151-158.
- Lohn A., et al., "A Knowledge-Based System for Real-Time Validation of Calibrations and Measurements," *Chemometrics and Intelligent Laboratory Systems*, vol. 46, 1999, pp. 57-66.
- Lowe C.R., "Biosensors," *Trends in Biotechnology*, vol. 2 (3), 1984, pp. 59-65.
- Luong J.H.T., et al., "Solubilization of Multiwall Carbon Nanotubes by 3-Aminopropyltriethoxysilane towards the Fabrication of Electrochemical Biosensors with Promoted Electron Transfer," *Electroanalysis*, vol. 16 (1-2), 2004, pp. 132-139.
- Lyandres O., et al. "Progress toward an In Vivo Surface-Enhanced Raman Spectroscopy Glucose Sensor," *Diabetes Technology and Therapeutics*, vol. 10 (4), 2008, pp. 257-265.
- Lynch S.M., et al., "Estimation-Based Model Predictive Control of Blood Glucose in Type 1 Diabetics: A Simulation Study," *Proceedings of the IEEE 27th Annual Northeast Bioengineering Conference*, 2001, pp. 79-80.
- Lynn P.A., "Recursive Digital Filters for Biological Signals," *Med. & Biol. Engineering*, vol. 9, 1971, pp. 37-43.
- Maidan R., et al., "Elimination of Electrooxidizable Interferent-Produced Currents in Amperometric Biosensors," *Analytical Chemistry*, vol. 64, 1992, pp. 2889-2896.
- Makale M.T., et al., "Tissue Window Chamber System for Validation of Implanted Oxygen Sensors," *American Journal of Physiology—Heart and Circulatory Physiology*, vol. 284, Feb. 21, 2003, pp. 1-27.
- Malin S.F., et al., "Noninvasive Prediction of Glucose by Near-Infrared Diffuse Reflectance Spectroscopy," *Clinical Chemistry*, vol. 45 (9), 1999, pp. 1651-1658.
- Mancy K.H., et al., "A Galvanic Cell Oxygen Analyzer," *Journal of Electroanalytical Chemistry*, vol. 4, 1962, pp. 65-92.
- Maran A., et al., "Continuous Subcutaneous Glucose Monitoring in Diabetic Patients," A Multicenter Analysis, *Diabetes Care*, vol. 25 (2), Feb. 2002, pp. 347-352.
- March W.F., "Dealing with the Delay," *Diabetes Technology & Therapeutics*, vol. 4 (1), 2002, pp. 49-50.
- Marena S., et al., "The Artificial Endocrine Pancreas in Clinical Practice and Research," *Panminerva Medica*, vol. 35 (2), 1993, pp. 67-74.
- Martin R.F., "General Deming Regression for Estimating Systematic Bias and its Confidence Interval in Method-Comparison Studies," *Clinical Chemistry*, vol. 46 (1), 2000, pp. 100-104.
- Mascini M., et al., "Glucose Electrochemical Probe with Extended Linearity for Whole Blood," *Journal Pharmaceutical and Biomedical Analysis*, vol. 7 (12), 1989, pp. 1507-1512.
- Mastrototaro J.J., et al., "An Electroenzymatic Glucose Sensor Fabricated on a Flexible Substrate," *Sensors and Actuators B*, vol. 5, 1991, pp. 139-144.
- Mastrototaro J.J., et al., "Reproducibility of the Continuous Glucose Monitoring System Matches Previous Reports and the Intended Use of the Product," *Diabetes Care*, vol. 26 (1), Jan. 2003, pp. 256-257.
- Mastrototaro J.J., "The MiniMed Continuous Glucose Monitoring System," *Diabetes Technology & Therapeutics*, vol. 2, Supplement 1, 2000, pp. S13-S18.
- Matsuki H., "Energy Transfer System Utilizing Amorphous Wires For Implantable Medical Devices," *IEEE Transactions on Magnetics*, vol. 31 (2), 1994, pp. 1276-1282.

(56)

## References Cited

## OTHER PUBLICATIONS

- Matsumoto T., et al., "A Micro-Planar Amperometric Glucose Sensor Unsusceptible to Interference Species," *Sensors and Actuators B*, 49, 1998, pp. 68-72.
- Matthews D.R., et al., "An Amperometric Needle-Type Glucose Sensor Testing in Rats and Man," *Diabetic Medicine*, vol. 5, 1988, pp. 248-252.
- Mazze R.S., et al., "Characterizing Glucose Exposure for Individuals with Normal Glucose Tolerance Using Continuous Glucose Monitoring and Ambulatory Glucose Profile Analysis," *Diabetes Technology & Therapeutics*, vol. 10 (3), 2008, pp. 149-159.
- Mazzola F., et al., "Video Diabetes: A Teaching Tool for Children with Insulin-Dependent Diabetes," *IEEE, Proceedings 7th Annual Symposium on Computer Applications in Medical Care*, Oct. 1983, 1 page Abstract.
- McCartney L.J., et al., "Near-Infrared Fluorescence Lifetime Assay for Serum Glucose Based on Allophycocyanin-Labeled Concanavalin A," *Analytical Biochemistry*, vol. 292, 2001, pp. 216-221.
- McGrath M.J., et al., "The Use of Differential Measurements with a Glucose Biosensor for Interference Compensation During Glucose Determinations by Flow Injection Analysis," *Biosens Bioelectron*, vol. 10, 1995, pp. 937-943.
- McKean B.D., et al., "A Telemetry Instrumentation System for Chronically Implanted Glucose and Oxygen Sensors," *IEEE Transactions on Biomedical Engineering*, vol. 35 (7), Jul. 1988, pp. 526-532.
- Memoli A., et al., "A Comparison between Different Immobilised Glucoseoxidase-Based Electrodes," *Journal of Pharmaceutical and Biomedical Analysis*, vol. 29, 2002, pp. 1045-1052.
- Merriam Webster Online Dictionary, Definition for "Aberrant," retrieved from <https://www.merriam-webster.com/dictionary/aberrant> Aug. 19, 2008, 1 page.
- Merriam-Webster Online Dictionary, Definition of "Acceleration" retrieved from <http://www.merriam-webster.com/dictionary/Acceleration> Jan. 11, 2010, 1 page.
- Merriam-Webster Online Dictionary, Definition of "Nominal" retrieved from <http://www.merriam-webster.com/dictionary/nominal> Apr. 23, 2007, 1 page.
- Merriam-Webster Online Dictionary, Definition of "System". <http://www.merriamwebster.com/dictionary/System> Jan. 11, 2010, 2 pages.
- Metzger M., et al., "Reproducibility of Glucose Measurements using the Glucose Sensor," *Diabetes Care*, vol. 25 (6), Jul. 2002, pp. 1185-1191.
- Meyerhoff C., et al., "On Line Continuous Monitoring of Subcutaneous Tissue Glucose in Men by Combining Portable Glucosensor With Microdialysis," *Diabetologia*, vol. 35 (11), 1992, pp. 1087-1092.
- Miller J.A., et al., "Development of an Autotuned Transcutaneous Energy Transfer System," *ASAIO Journal*, vol. 39, 1993, pp. M706-M710.
- Moatti-Sirat D., et al., "Evaluating In Vitro and In Vivo the Interference of Ascorbate and Acetaminophen on Glucose Detection by a Needle-Type Glucose Sensor," *Biosensors and Bioelectronics*, vol. 7, 1992, pp. 345-352.
- Moatti-Sirat D., et al., "Reduction of Acetaminophen Interference in Glucose Sensors by a Composite Nafion Membrane: Demonstration in Rats and Man," *Diabetologia*, vol. 37 (6), Jun. 1994, pp. 610-616.
- Moatti-Sirat., et al., "Towards Continuous Glucose Monitoring: In Vivo Evaluation of a Miniaturized Glucose Sensor Implanted for Several Days in Rat Subcutaneous Tissue," *Diabetologia*, vol. 35, 1992, pp. 224-230.
- Monsod T.P., et al., "Do Sensor Glucose Levels Accurately Predict Plasma Glucose Concentrations During Hypoglycemia And Hyperinsulinemia?," *Diabetes Care*, vol. 25 (5), 2002, pp. 889-893.
- Morff R.J., et al., "Microfabrication of Reproducible, Economical, Electroenzymatic Glucose Sensors," *Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 12 (2), 1990, pp. 0483-0484.
- Mosbach K., et al., "Determination of Heat Changes in the Proximity of Immobilized Enzymes with an Enzyme Thermistor and its Use for the Assay of Metabolites," *Biochimica Biophysica Acta*, vol. 403, 1975, pp. 256-265.
- Motonaka J., et al., "Determination of Cholesterol and Cholesterol Ester with Novel enzyme Microsensors," *Anal. Chem.*, vol. 65, 1993, pp. 3258-3261.
- Moussy F., et al., "A Miniaturized Nafion-Based Glucose Sensor: In Vitro and In Vivo Evaluation in Dogs," *International Journals of Artificial Organs*, vol. 17 (2), 1994, pp. 88-94.
- Moussy F., et al., "Performance of Subcutaneously Implanted Needle-Type Glucose Sensors Employing a Novel Trilayer Coating," *Analytical Chemistry*, vol. 65, Aug. 1, 1993, pp. 2072-2077.
- Moussy F., "Implantable Glucose Sensor: Progress and Problems," *IEEE*, Nov. 2002, pp. 270-273.
- Murphy S.M., et al., "Polymer Membranes in Clinical Sensor Applications, II. The Design and Fabrication of Permselective Hydrogels for Electrochemical Devices," *Biomaterials*, 1992, vol. 13(14), pp. 979-990.
- Muslu, "Trickling Filter Performance," *Applied Biochemistry and Biotechnology*, vol. 37, 1992, pp. 211-224.
- Neuburger G.G., et al., "Pulsed Amperometric Detection of Carbohydrates at Gold Electrodes with a Two-Step Potential Waveform," *Anal. Chem.*, vol. 59, 1987, pp. 150-154.
- Newsrx, "Glucose Monitoring: FDA OKs New Device to Manage Diabetes," *Medical Letter on the CDC & FDA via NewsRx.com*, Aug. 3, 2003, 1 page.
- Nintendo Healthcare, *Wired*, Dec. 1993, 1 page.
- Novo Nordisk Pharmaceuticals Inc., "Diabetes Educational Video Game Recognized by Software Publishers Association," *Press Release*, Mar. 14, 1994, 4 pages.
- Office Action for European Application No. 05723951.9, dated Feb. 20, 2012, 4 pages.
- Office Action for European Application No. 05723951.9, dated Jan. 28, 2011, 6 pages.
- Office Action for European Application No. 05723951.9, dated Jun. 28, 2012, 9 pages.
- Office Action for European Application No. 05723951.9, dated Nov. 21, 2007, 5 pages.
- Office Action for European Application No. 05723951.9, dated Oct. 10, 2008, 3 pages.
- Office Action for European Application No. 10163654.6, dated Oct. 11, 2012, 6 pages.
- Office Action for European Application No. 10163675.1, dated Mar. 17, 2011, 5 pages.
- Office Action for Japanese Application No. 2007-500777, dated Aug. 17, 2010, 6 pages.
- Office Action for Japanese Application No. 2007-500777, dated Jul. 24, 2012, 27 pages.
- Office Action for Japanese Application No. 2007-500777, dated Jun. 28, 2011, 3 pages.
- Office Action for U.S. Appl. No. 09/636,369, dated Sep. 30, 2002, 4 pages.
- Office Action for U.S. Appl. No. 10/632,537, dated Dec. 21, 2004, 7 pages.
- Office Action for U.S. Appl. No. 10/632,537, dated Oct. 20, 2004, 7 pages.
- Office Action for U.S. Appl. No. 10/633,329, dated Apr. 27, 2010, 5 pages.
- Office Action for U.S. Appl. No. 10/633,329, dated Dec. 18, 2008, 9 pages.
- Office Action for U.S. Appl. No. 10/633,329, dated Feb. 4, 2008, 7 pages.
- Office Action for U.S. Appl. No. 10/633,329, dated Jul. 30, 2007, 9 pages.
- Office Action for U.S. Appl. No. 10/633,329, dated Jun. 11, 2009, 8 pages.
- Office Action for U.S. Appl. No. 10/633,329, dated Jun. 12, 2008, 7 pages.
- Office Action for U.S. Appl. No. 10/633,329, dated Mar. 26, 2007, 05 pages.
- Office Action for U.S. Appl. No. 10/633,329, dated Oct. 5, 2006, 6 pages.

(56)

**References Cited****OTHER PUBLICATIONS**

Office Action for U.S. Appl. No. 10/633,367, dated Jul. 15, 2008, 8 pages.  
 Office Action for U.S. Appl. No. 10/633,367, dated Jun. 11, 2009, 7 pages.  
 Office Action for U.S. Appl. No. 10/633,404, dated Feb. 12, 2007, 14 pages.  
 Office Action for U.S. Appl. No. 10/648,849, dated Jun. 23, 2009, 10 pages.  
 Office Action for U.S. Appl. No. 10/896,772, dated Dec. 14, 2005, 10 pages.  
 Office Action for U.S. Appl. No. 10/896,772, dated Jan. 11, 2005, 16 pages.  
 Office Action for U.S. Appl. No. 10/896,772, dated Jul. 19, 2005, 17 pages.  
 Office Action for U.S. Appl. No. 10/896,772, dated May 22, 2006, 31 pages.  
 Office Action for U.S. Appl. No. 10/991,966, dated Jul. 22, 2008, 12 pages.  
 Office Action for U.S. Appl. No. 10/991,966, dated Nov. 28, 2007, 13 pages.  
 Office Action for U.S. Appl. No. 11/007,635, dated Jan. 27, 2006, 9 pages.  
 Office Action for U.S. Appl. No. 11/007,920, dated Jun. 24, 2008, 10 pages.  
 Office Action for U.S. Appl. No. 11/034,344, dated Jan. 15, 2008, 5 pages.  
 Office Action for U.S. Appl. No. 11/038,340, dated Feb. 2, 2010, 18 pages.  
 Office Action for U.S. Appl. No. 11/038,340, dated Jan. 5, 2009, 13 pages.  
 Office Action for U.S. Appl. No. 11/038,340, dated Jun. 7, 2010, 18 pages.  
 Office Action for U.S. Appl. No. 11/038,340, dated Jun. 17, 2008, 11 pages.  
 Office Action for U.S. Appl. No. 11/038,340, dated May 19, 2009, 14 pages.  
 Office Action for U.S. Appl. No. 11/038,340, dated Nov. 9, 2009, 16 pages.  
 Office Action for U.S. Appl. No. 11/077,714, dated Apr. 10, 2007, 16 pages.  
 Office Action for U.S. Appl. No. 11/077,714, dated Apr. 16, 2009, 12 pages.  
 Office Action for U.S. Appl. No. 11/077,714, dated Dec. 31, 2009, 8 pages.  
 Office Action for U.S. Appl. No. 11/077,714, dated Jan. 10, 2008, 18 pages.  
 Office Action for U.S. Appl. No. 11/077,714, dated Jan. 27, 2010, 9 pages.  
 Office Action for U.S. Appl. No. 11/077,714, dated Jul. 27, 2007, 13 pages.  
 Office Action for U.S. Appl. No. 11/077,714, dated Oct. 11, 2006, 9 pages.  
 Office Action for U.S. Appl. No. 11/077,714, dated Sep. 16, 2008, 16 pages.  
 Office Action for U.S. Appl. No. 11/077,739, dated Dec. 29, 2009, 7 pages.  
 Office Action for U.S. Appl. No. 11/077,739, dated Jul. 21, 2009, 8 pages.  
 Office Action for U.S. Appl. No. 11/077,739, dated Mar. 1, 2010, 9 pages.  
 Office Action for U.S. Appl. No. 11/077,740, dated Apr. 28, 2009, 27 pages.  
 Office Action for U.S. Appl. No. 11/077,740, dated Feb. 7, 2008, 16 pages.  
 Office Action for U.S. Appl. No. 11/077,740, dated Jul. 25, 2008, 24 pages.  
 Office Action for U.S. Appl. No. 11/077,740, dated Jun. 1, 2007, 14 pages.

Office Action for U.S. Appl. No. 11/077,740, dated Nov. 1, 2007, 13 pages.  
 Office Action for U.S. Appl. No. 11/077,759, dated Jul. 10, 2008, 10 pages.  
 Office Action for U.S. Appl. No. 11/077,759, dated Mar. 31, 2008, 16 pages.  
 Office Action for U.S. Appl. No. 11/077,759, dated May 17, 2007, 13 pages.  
 Office Action for U.S. Appl. No. 11/077,759, dated May 26, 2009, 8 pages.  
 Office Action for U.S. Appl. No. 11/077,765, dated Dec. 31, 2007, 10 pages.  
 Office Action for U.S. Appl. No. 11/077,765, dated Feb. 3, 2010, 10 pages.  
 Office Action for U.S. Appl. No. 11/077,765, dated Jan. 23, 2009, 11 pages.  
 Office Action for U.S. Appl. No. 11/077,765, dated May 16, 2008, 9 pages.  
 Office Action for U.S. Appl. No. 11/077,765, dated Sep. 19, 2008, 9 pages.  
 Office Action for U.S. Appl. No. 11/078,072, dated Feb. 18, 2010, 6 pages.  
 Office Action for U.S. Appl. No. 11/078,072, dated Jun. 10, 2010, 8 pages.  
 Office Action for U.S. Appl. No. 11/078,072, dated Sep. 2, 2009, 13 pages.  
 Office Action for U.S. Appl. No. 11/078,232, dated Apr. 27, 2010, 18 pages.  
 Office Action for U.S. Appl. No. 11/078,232, dated Jan. 5, 2010, 15 pages.  
 Office Action for U.S. Appl. No. 11/078,232, dated Jul. 21, 2009, 13 pages.  
 Office Action for U.S. Appl. No. 11/078,232, dated Mar. 5, 2009, 14 pages.  
 Office Action for U.S. Appl. No. 11/078,232, dated May 5, 2008, 21 pages.  
 Office Action for U.S. Appl. No. 11/078,232, dated Nov. 12, 2008, 28 pages.  
 Office Action for U.S. Appl. No. 11/333,837, dated Apr. 12, 2010, 10 pages.  
 Office Action for U.S. Appl. No. 11/333,837, dated Jul. 2, 2010, 7 pages.  
 Office Action for U.S. Appl. No. 11/333,837, dated Jun. 29, 2009, 13 pages.  
 Office Action for U.S. Appl. No. 11/333,837, dated Nov. 28, 2008, 11 pages.  
 Office Action for U.S. Appl. No. 11/334,876, dated Aug. 25, 2009, 18 pages.  
 Office Action for U.S. Appl. No. 11/334,876, dated Aug. 26, 2008, 8 pages.  
 Office Action for U.S. Appl. No. 11/334,876, dated May 2, 2008, 18 pages.  
 Office Action for U.S. Appl. No. 11/334,876, dated Oct. 4, 2006, 9 pages.  
 Office Action for U.S. Appl. No. 11/334,876, dated Sep. 25, 2007, 14 pages.  
 Office Action for U.S. Appl. No. 11/360,252, dated Jan. 29, 2009, 15 pages.  
 Office Action for U.S. Appl. No. 11/360,252, dated Jul. 23, 2009, 10 pages.  
 Office Action for U.S. Appl. No. 11/360,252, dated Jun. 30, 2008, 10 pages.  
 Office Action for U.S. Appl. No. 11/360,819, dated Apr. 7, 2010, 10 pages.  
 Office Action for U.S. Appl. No. 11/360,819, dated Aug. 11, 2008, 10 pages.  
 Office Action for U.S. Appl. No. 11/360,819, dated Dec. 26, 2008, 12 pages.  
 Office Action for U.S. Appl. No. 11/360,819, dated Oct. 29, 2009, 15 pages.  
 Office Action for U.S. Appl. No. 12/055,098, dated Oct. 5, 2010, 12 pages.

(56)

## References Cited

## OTHER PUBLICATIONS

- Office Action for U.S. Appl. No. 12/098,359, dated Jul. 7, 2010, 18 pages.
- Office Action for U.S. Appl. No. 12/102,654, dated Jul. 30, 2009, 9 pages.
- Office Action for U.S. Appl. No. 12/102,654, dated Mar. 10, 2010, 6 pages.
- Office Action for U.S. Appl. No. 12/102,745, dated Dec. 23, 2008, 4 pages.
- Office Action for U.S. Appl. No. 12/113,508, dated Feb. 23, 2010, 9 pages.
- Office Action for U.S. Appl. No. 12/113,724, dated Jun. 24, 2010, 12 pages.
- Office Action for U.S. Appl. No. 12/182,073, dated Jun. 28, 2010, 20 pages.
- Office Action for U.S. Appl. No. 12/182,083, dated Jun. 24, 2010, 8 pages.
- Office Action for U.S. Appl. No. 12/264,160, dated Jun. 3, 2010, 5 pages.
- Office Action for U.S. Appl. No. 12/364,786, dated Jul. 29, 2010, 6 pages.
- Office Action for U.S. Appl. No. 95/001,038, dated Jun. 17, 2008, 32 pages.
- Office Action for U.S. Appl. No. 95/001,038, dated May 28, 2010, 32 pages.
- Office Action for U.S. Appl. No. 95/001,039, dated May 29, 2008, 21 pages.
- Office Action from European Patent Application No. 05723951.9, dated Sep. 7, 2010, 5 pages.
- Ohara T.J., et al., "Glucose Electrodes Based On Cross-Linked [Os(bpy)<sub>2</sub>Cl]<sup>(+2+)</sup> Complexed Poly(1-Vinylimidazole) Films," *Analytical Chemistry*, vol. 65, Dec. 1993, pp. 3512-3517.
- Ohara T.J., et al., "Wired" Enzyme Electrodes for Amperometric Determination of Glucose or Lactate in the Presence of Interfering Substances," *Anal Chem*, vol. 66, 1994, pp. 2451-2457.
- Okuda, et al., "Mutarotase Effect on Micro Determinations of D-Glucose and its Anomers with  $\beta$  D-Glucose Oxidase," *Anal Biochem*, vol. 43 (1), 1971, pp. 312-315.
- Oxford English Dictionary Online, Definition of "Impending," [http://www.askoxford.com/results/?view=devdict&field=12668446\\_Impending&branch](http://www.askoxford.com/results/?view=devdict&field=12668446_Impending&branch) Jan. 11, 2010, 1 page.
- Palmisano F., et al., "Simultaneous Monitoring of Glucose and Lactate by an Interference and Cross-Talk Free Dual Electrode Amperometric Biosensor Based on Electropolymerized Thin Films," *Biosensors & Bioelectronics*, vol. 15, 2000, pp. 531-539.
- Panteleon A.E., et al., "The Role of the Independent Variable to Glucose Sensor Calibration," *Diabetes Technology & Therapeutics*, vol. 5 (3), 2003, pp. 401-410.
- Parker R.S., et al., "A Model-Based Algorithm for Blood Glucose Control In Type I Diabetic Patients," *IEEE Trans Biomed Engg (BME)*, vol. 46(2), 1999, pp. 148-157.
- Patel H., et al., "Amperometric Glucose Sensors Based on Ferrocene Containing Polymeric Electron Transfer Systems—A Preliminary Report," *Biosensors & Bioelectronics*, vol. 18, 2003, pp. 1073-1076.
- Peacock W.F., et al., "Cardiac Troponin and Outcome in Acute Heart Failure," *N. Engl. J. Med.*, vol. 358, 2008, pp. 2117-2126.
- Peguín S., et al., "Pyruvate Oxidase and Oxaloacetate Decarboxylase Enzyme Electrodes—Simultaneous Determination of Transaminases with a Two-electrode-based Analyzer," *Analytica Chimica Acta*, vol. 222, 1989, pp. 83-93.
- Pfeiffer E.F., et al., "On Line Continuous Monitoring of Subcutaneous Tissue Glucose is Feasible by Combining Portable Glucosensor with Microdialysis," *Horm. Metab. Res.*, vol. 25, 1993, pp. 121-124.
- Pfeiffer E.F., "The Glucose Sensor: The Missing Link in Diabetes Therapy," *Horm Metab Res Suppl.*, vol. 24, 1990, pp. 154-164.
- Phillips R.P., "A High Capacity Transcutaneous Energy Transmission System," *ASIAO Journal*, vol. 41, 1995, pp. M259-M262.
- Pichert J.W., et al., "Issues for the Coming Age of Continuous Glucose Monitoring," *Diabetes Educator*, vol. 26 (6), Nov.-Dec. 2000, pp. 969-980.
- Pickup J.C., et al., "Developing Glucose Sensors for In Vivo Use," Elsevier Science Publishers Ltd (Uk), Tibtech, vol. 11, 1993, pp. 285-291.
- Pickup J.C., et al., "Implantable Glucose Sensors: Choosing the Appropriate Sensor Strategy," *Biosensors*, vol. 3, (1987/1988), pp. 335-346.
- Pickup J.C., et al., "In Vivo Molecular Sensing in Diabetes Mellitus: An Implantable Glucose Sensor with Direct Electron Transfer," *Diabetologia*, vol. 32, 1989, pp. 213-217.
- Pickup J.C., et al., "Potentially-Implantable, Amperometric Glucose Sensors with Mediated Electron Transfer: Improving the Operating Stability," *Biosensors*, vol. 4, 1989, pp. 109-119.
- Pickup J.C., et al., "Responses and Calibration of Amperometric Glucose Sensors Implanted in the Subcutaneous Tissue of Man," *ACTA Diabetol*, vol. 30, 1993, pp. 143-148.
- Pinner S.H., et al., "Cross-Linking of Cellulose Acetate by Ionizing Radiation," *Nature*, vol. 184, Oct. 24, 1959, pp. 1303-1304.
- Pishko M.V., et al., "Amperometric Glucose Microelectrodes Prepared Through Immobilization of Glucose Oxidase in Redox Hydrogels," *Analytical Chemistry*, vol. 63 (20), 1991, pp. 2268-2272.
- Pitzer K.R., et al., "Detection of Hypoglycemia with the Glucowatch Biographer," *Diabetes Care*, vol. 24 (5), 2001, pp. 881-885.
- Poirier J.Y., et al., "Clinical and Statistical Evaluation of Self-Monitoring Blood Glucose Meters," *Diabetes Care*, vol. 21 (11), Nov. 1998, pp. 1919-1924.
- Poitout V., et al., "A Glucose Monitoring System for on Line Estimation in Man of Blood Glucose Concentration Using a Miniaturized Glucose Sensor Implanted in the Subcutaneous Tissue and a Wearable Control Unit," *Diabetologia*, vol. 36, 1993, pp. 658-663.
- Poitout V., et al., "Development of a Glucose Sensor for Glucose Monitoring in Man: The Disposable Implant Concept," *Clinical Materials*, vol. 15, 1994, pp. 241-246.
- Poitout V., et al., "In Vitro and In Vivo Evaluation in Dogs of a Miniaturized Glucose Sensor," *ASIAO Transactions*, vol. 37, 1991, pp. M298-M300.
- Postlethwaite T.A., et al., "Interdigitated Array Electrode as an Alternative to the Rotated Ring-Disk Electrode for Determination of the Reaction Products of Dioxygen Reduction," *Analytical Chemistry*, vol. 68 (17), Sep. 1996, pp. 2951-2958.
- Prabhu V.G., et al., "Electrochemical Studies of Hydrogen Peroxide at a Platinum Disc Electrode," *Electrochimica Acta*, vol. 26 (6), 1981, pp. 725-729.
- Quinn C.A.P., et al., "Biocompatible, Glucose-Permeable Hydrogel for In situ Coating of Implantable Biosensors," *Biomaterials*, vol. 18 (24), 1997, pp. 1665-1670.
- Quinn C.P., et al., "Kinetics of Glucose Delivery to Subcutaneous Tissue in Rats Measured with 0.3-mm Amperometric Microsensors," *The American Physiological Society*, vol. 269, 1995, pp. E155-E161.
- Rabah M.A., et al., "Electrochemical Wear of Graphite Anodes During Electrolysis of Brine," *Carbon*, vol. 29 (2), 1991, pp. 165-171.
- Rafael E., "Cell Transplantation and Immunoisolation: Studies on a Macroencapsulation Device," *Departments of Transplantation Surgery and Pathology, Karolinska Institutet, Huddinge Hospital, Stockholm, Sweden*, 1999, pp. 1-83.
- RAYA Systems Pioneers, "Raya Systems Pioneers Healthy Video Games," *Play Right*, Nov. 1993, pp. 14-15.
- Reach G., "A Method for Evaluating in vivo the Functional Characteristics of Glucose Sensors," *Biosensors*, vol. 2, 1986, pp. 211-220.
- Reach G., et al., "Can Continuous Glucose Monitoring Be Used for the Treatment of Diabetes?," *Analytical Chemistry*, vol. 64 (6), Mar. 15, 1992, pp. 381A-386A.
- Reach G., "Which Threshold to Detect Hypoglycemia? Value of Receiver-Operator Curve Analysis to Find a Compromise Between Sensitivity and Specificity," *Diabetes Care*, vol. 24 (5), May 2001, pp. 803-804.

(56)

## References Cited

## OTHER PUBLICATIONS

- Rebrin K., et al., "Automated Feedback Control of Subcutaneous Glucose Concentration in Diabetic Dogs," *Diabetologia*, vol. 32, 1989, pp. 573-576.
- Rebrin K., et al., "Subcutaneous Glucose Monitoring by Means of Electrochemical Sensors: Fiction or Reality?," *Journal of Biomedical Engineering*, vol. 14, Jan. 1992, pp. 33-40.
- Rebrin K., et al., "Subcutaneous Glucose Predicts Plasma Glucose Independent of Insulin: Implications for Continuous Monitoring," *The American Physiological Society*, vol. 277, 1999, pp. E561-E571.
- Renard E., "Implantable Closed-Loop Glucose Sensing and Insulin Delivery: The Future for Insulin Pump Therapy," *Current Opinion in Pharmacology*, vol. 2 (6), 2002, pp. 708-716.
- Reusch, "Organometallic Compounds," *Chemical Reactivity, Virtual Textbook of Organic Chemistry*, Retrieved from <http://www.cem.msu.edu/~reusch/VirtualText/orgmetal.htm> 2004, pp. 1-16.
- Rhodes R.K., et al., "Prediction of Pocket-Portable and Implantable Glucose Enzyme Electrode Performance from Combined Species Permeability and Digital Simulation Analysis," *Analytical Chemistry*, vol. 66 (9), May 1, 1994, pp. 1520-1529.
- Rigla M., et al., "Real-Time Continuous Glucose Monitoring Together with Telemedical Assistance Improves Glycemic Control and Glucose Stability in Pump-Treated Patients," *Diabetes Technology & Therapeutics*, vol. 10 (3), 2008, pp. 194-199.
- Rinken T., et al., "Calibration of Glucose Biosensors By Using Pre-Steady State Kinetic Data," *Biosensors & Bioelectronics*, vol. 13, 1998, pp. 801-807.
- Ristic S., et al., "Review: Effects of Rapid-Acting Insulin Analogs on Overall Glycemic Control in Type 1 and Type 2 Diabetes Mellitus," *Diabetes Technology & Therapeutics*, vol. 5 (1), 2003, pp. 57-66.
- Rivers E.P., et al., "Central Venous Oxygen Saturation Monitoring in the Critically Ill Patient," *Current Opinion in Critical Care*, 2001, vol. 7, pp. 204-211.
- Sakakida M., et al., "Development of Ferrocene-Mediated Needle-Type Glucose Sensor as a Measure of True Subcutaneous Tissue Glucose Concentrations," *Artif. Organs Today*, vol. 2 (2), 1992, pp. 145-158.
- Sakakida M., et al., "Ferrocene-Mediated Needle Type Glucose Sensor Covered with Newly Designed Biocompatible Membrane," *Sensors and Actuators B*, vol. 13-14, 1993, pp. 319-322.
- Salardi S., et al., "The Glucose Area Under the Profiles Obtained with Continuous Glucose Monitoring System Relationships with HbA1C in Pediatric Type 1 Diabetic Patients," *Diabetes Care*, vol. 25 (10), Oct. 2002, pp. 1840-1844.
- Samuels M.P., "The Effects of Flight and Altitude," *Arch Dis Child*, vol. 89, 2004, pp. 448-455.
- San Diego Plastics Inc., "Polyethylene," *Datasheet*, Retrieved from <http://www.sdplastics.com/polyeth.html> on Aug. 19, 2009, 7 pages.
- Sansen W., et al., "A Smart Sensor for the Voltammetric Measurement of Oxygen or Glucose Concentrations," *Sensors and Actuators B1*, 1990, pp. 298-302.
- Sansen W., et al., "Glucose Sensor with Telemetry System," In *Implantable Sensors for Closed Loop Prosthetic Systems* edited by Ko W.H., Chapter 12, 1985, pp. 167-175.
- Schaffar B.P.H., "Thick Film Biosensors for Metabolites in Undiluted Whole Blood and Plasma Samples," *Analytical Bioanalytical Chemistry*, Dec. 2001, vol. 372, pp. 254-260.
- Schmidt F.J., et al., "Calibration of a Wearable Glucose Sensor," *The International Journal of Artificial Organs*, Wichtig Publishing, IT, vol. 15(1), Jan. 1, 1992, pp. 55-61.
- Schmidt F.J., et al., "Glucose Concentration in Subcutaneous Extracellular Space," *Diabetes Care*, vol. 16 (5), May 1993, pp. 695-700.
- Schmidtke D.W., et al., "Accuracy of the One-Point in Vivo Calibration of "Wired" Glucose Oxidase Electrodes Implanted in Jugular Veins of Rats in Periods of Rapid Rise and Decline of the Glucose Concentration," *Analytical Chemistry*, vol. 70 (10), May 15, 1998, pp. 2149-2155.
- Schmidtke D.W., et al., "Measurement and Modeling of the Transient Difference Between Blood and Subcutaneous Glucose Concentrations in the Rat After Injection of Insulin," *Proceedings of the National Academy of Sciences*, vol. 95, Jan. 1998, pp. 294-299.
- Schoemaker M., et al., "The SCGMI System: Subcutaneous Continuous Glucose Monitoring Based on Microdialysis Technique," *Diabetes Technology & Therapeutics*, vol. 5 (4), 2003, pp. 599-608.
- Schoonen A.J.M., et al., "Development of a Potentially Wearable Glucose Sensor for Patients with Diabetes Mellitus: Design and In-vitro Evaluation," *Biosensors & Bioelectronics*, vol. 5, 1990, pp. 37-46.
- Selam J.L., "Management of Diabetes with Glucose Sensors and Implantable Insulin Pumps," *From the Dream of the 60s to the Realities of the 90s*, *ASAIO Journal* 1997, vol. 43, pp. 137-142.
- Service F.J., et al., "Mean Amplitude of Glycemic Excursions, A Measure of Diabetic Instability," *Diabetes*, vol. 19 (9), Sep. 1970, pp. 644-655.
- Service F.J., et al., "Measurements of Glucose Control," *Diabetes Care*, vol. 10 (2), Mar.-Apr. 1987, pp. 225-237.
- Service R.F., "Can Sensors Make a Home in the Body?," *Science, Materials Science: Soft Surface*, vol. 297, Aug. 9, 2002, pp. 962-963.
- Sharkawy A.A., et al., "Engineering the Tissue Which Encapsulates Subcutaneous Implants. I. Diffusion Properties," *Journal of Biomedical Materials Research*, vol. 37, 1996, pp. 401-412.
- Shaw G.W., et al., "In Vitro Testing of a Simply Constructed, Highly Stable Glucose Sensor Suitable for Implantation in Diabetic Patients," *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 401-406.
- Shichiri M., et al., "Glycaemic Control in Pancreatectomized Dogs with a Wearable Artificial Endocrine Pancreas," *Diabetologia*, vol. 24, 1983, pp. 179-184.
- Shichiri M., et al., "Membrane Design for Extending the Long-Life of an Implantable Glucose Sensor," *Diabetes Nutrition & Metabolism*, vol. 2 (4), 1989, pp. 309-313.
- Shichiri M., et al., "Needle Type Glucose Sensor for Wearable Artificial Endocrine Pancreas," In *Implantable Sensors for Closed-Loop Prosthetic Systems* edited by Ko W.H., Chapter 15, 1985, pp. 197-210.
- Shichiri M., et al., "Telemetry Glucose Monitoring Device with Needle-Type Glucose Sensor: A Useful Tool for Blood Glucose Monitoring in Diabetic Individuals," *Diabetes Care*, vol. 9 (3), May-Jun. 1986, pp. 298-301.
- Shichiri M., et al., "Wearable Artificial Endocrine Pancreas with Needle-Type Glucose Sensor," *Preliminary Communication, Lancet*, vol. 2, Nov. 20, 1982, pp. 1129-1131.
- Shults M.C., et al., "A Telemetry-Instrumentation System for Monitoring Multiple Subcutaneously Implanted Glucose Sensors," *IEEE Transactions on Biomedical Engineering*, vol. 41 (10), Oct. 1994, pp. 937-942.
- Sigma-Aldrich Corp. "Nafion® 117 Solution Product Description, Product No. 70160," retrieved from <https://http://www.sigmaaldrich.com/cgi-bin/hsrun/Suite7/Suite/HAHTpage/Suite.HsExternalProd> on Apr. 7, 2005, 1 page.
- Skyler U.S., "The Economic Burden of Diabetes and the Benefits of Improved Glycemic Control: The Potential Role of a Continuous Glucose Monitoring System," *Diabetes Technology & Therapeutics*, vol. 2, Supplement 1, 2000, pp. S7-S12.
- Slater-MacLean L., et al., "Accuracy of Glycemic Measurements in the Critically Ill," *Diabetes Technology and Therapeutics*, vol. 10 (3), 2008, pp. 169-177.
- Smith B., et al., "An Externally Powered, Multichannel, Implantable Stimulator-Telemeter for Control of Paralyzed Muscle," *IEEE Transactions on Biomedical Engineering*, vol. 45 (4), Apr. 1998, pp. 463-475.
- Smith, et al., "A Comparison of Islet Transplantation and Subcutaneous Insulin Injections for the Treatment of Diabetes Mellitus," *Computers in Biology and Medicine*, 1991, vol. 21 (6), pp. 417-427.
- Sokol L., et al., "Immobilized-Enzyme Rate-Determination Method for Glucose Analysis," *Clinical Chemistry*, vol. 26 (1), 1980, pp. 89-92.
- Sokolov S., et al., "Metrological Opportunities of the Dynamic Mode of Operating an Enzyme Amperometric Biosensor," *Medical Engineering & Physics*, vol. 17 (6), 1995, pp. 471-476.

(56)

## References Cited

## OTHER PUBLICATIONS

- Sparacino G., et al., "Continuous Glucose Monitoring Time Series and Hypo-Hyperglycemia Prevention: Requirements, Methods, Open Problems," *Current Diabetes Reviews*, vol. 4 (3), 2008, pp. 181-192.
- Sproule B.A., et al., "Fuzzy Pharmacology: Theory and Applications," *Trends in Pharmacological Sciences*, vol. 23 (9), Sep. 2002, pp. 412-417.
- Sriyudthsak M., et al., "Enzyme-Epoxy Membrane Based Glucose Analyzing System and Medical Applications," *Biosensors & Bioelectronics*, vol. 11 (8), 1996, pp. 735-742.
- Steil G.M., et al., "Determination of Plasma Glucose During Rapid Glucose Excursions with a Subcutaneous Glucose Sensor," *Diabetes Technology & Therapeutics*, vol. 5 (1), 2003, pp. 27-31.
- Stern M., et al., "Electrochemical Polarization: I. A Theoretical Analysis of the Shape of Polarization Curves," *Journal of the Electrochemical Society*, vol. 104 (1), Jan. 1957, pp. 56-63.
- Sternberg F., et al., "Does Fall in Tissue Glucose Precede Fall in Blood Glucose?," *Diabetologia*, vol. 39, 1996, pp. 609-612.
- Sternberg R., et al., "Study and Development of Multilayer Needle-type Enzyme Based Glucose Microsensors," *Biosensors*, vol. 4, 1988, pp. 27-40.
- Street, et al., "Islet Graft Assessment in the Edmonton Protocol: Implications for Predicting Long-Term Clinical Outcome," *Diabetes*, 2004, vol. 53, pp. 3107-3114.
- Street J.O., et al., "A Note on Computing Robust Regression Estimates Via Iteratively Reweighted Least Squares," *The American Statistician*, vol. 42 (2), May 1988, pp. 152-154.
- Sumino T., et al., "Preliminary Study of Continuous Glucose Monitoring with a Microdialysis Technique," *Proceedings of the 20th Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 20 (4), 1998, pp. 1775-1778.
- Supplementary European Search Report for Application No. 05723951.9 dated May 2, 2007, 3 pages.
- Takatsu I., et al., "Solid State Biosensors Using Thin-Film Electrodes," *Sensors and Actuators*, 1987, vol. 11, pp. 309-317.
- Takegami S., et al., "Pervaporation of Ethanol/Water Mixtures Using Novel Hydrophobic Membranes Containing Polydimethylsiloxane," *Journal of Membrane Science*, vol. 75, 1992, pp. 93-105.
- Tamura T., et al., "Preliminary Study of Continuous Glucose Monitoring with a Microdialysis Technique and a Null Method—A Numerical Analysis," *Frontiers of Medical & Biological Engineering*, vol. 10 (2), 2000, pp. 147-156.
- Tanenber R.J., et al., "Continuous Glucose Monitoring System: A New Approach to the Diagnosis of Diabetic Gastroparesis," *Diabetes Technology & Therapeutics*, vol. 2, Supplement 1, 2000, pp. S73-S80.
- Tatsuma T., et al., "Oxidase/Peroxidase Bilayer-Modified Electrodes as Sensors for Lactate, Pyruvate, Cholesterol and Uric Acid," *Analytica Chimica Acta*, vol. 242, 1991, pp. 85-89.
- Thennadil S.N., et al., "Comparison of Glucose Concentration in Interstitial Fluid, and Capillary and Venous Blood During Rapid Changes in Blood Glucose Levels," *Diabetes Technology & Therapeutics*, vol. 3 (3), 2001, pp. 357-365.
- Thijssen, et al., "A Kalman Filter for Calibration, Evaluation of Unknown Samples and Quality Control in Drifting Systems," Part 1, Theory and Simulations, *Analytica chimica Acta*, 1984, vol. 156, pp. 87-101.
- Thijssen, et al., "A Kalman Filter for Calibration, Evaluation of Unknown Samples and Quality Control in Drifting Systems," Part 3, Variance Reduction, *Analytica chimica Acta*, 1985, vol. 173, pp. 265-272.
- Thijssen, et al., "A Kalman Filter for Calibration, Evaluation of Unknown Samples and Quality Control in Drifting Systems," Part 4, Flow Injection Analysis, *Analytica chimica Acta*, 1985, vol. 174, pp. 27-40.
- Thijssen P.C., "A Kalman Filter for Calibration, Evaluation of Unknown Samples and Quality Control in Drifting Systems," Part 2, Optimal Designs, *Analytica chimica Acta*, vol. 162, 1984, pp. 253-262.
- Thome V., et al., "(Abstract) Can the Decrease in Subcutaneous Glucose Concentration Precede the Decrease in Blood Glucose Level? Proposition for a Push-Pull Kinetics Hypothesis," *Horm. metab. Res.*, vol. 27, 1995, p. 53.
- Thome-Duret V., et al., "Continuous Glucose Monitoring in the Free-Moving Rat," *Metabolism*, vol. 47 (7), Jul. 1998, pp. 799-803.
- Thome-Duret V., et al., "Modification of the Sensitivity of Glucose Sensor Implanted into Subcutaneous Tissue," *Diabetes & Metabolism*, vol. 22, 1996, pp. 174-178.
- Thome-Duret V., et al., "Use of a Subcutaneous Glucose Sensor to Detect Decreases in Glucose Concentration Prior to Observation in Blood," *Analytical Chemistry*, vol. 68 (21), Nov. 1, 1996, pp. 3822-3826.
- Thompson M., et al., "In Vivo Probes: Problems and Perspectives," *Clinical Biochemistry*, vol. 19 (5), Oct. 1986, pp. 255-261.
- Tierney M.J., et al., "Effect of Acetaminophen on the Accuracy of Glucose Measurements Obtained with the GlucoWatch Biographer," *Diabetes Technology & Therapeutics*, vol. 2 (2), 2000, pp. 199-207.
- Tierney M.J., et al., "The Gluco Watch® Biographer: A Frequent, Automatic and Noninvasive Glucose Monitor," *Annals of Medicine*, vol. 32, 2000, pp. 632-641.
- Tilbury J.B., et al., "Receiver Operating Characteristic Analysis for Intelligent Medical Systems—A New Approach for Finding Confidence Intervals," *IEEE Transactions on Biomedical Engineering*, vol. 47 (7), Jul. 2000, pp. 952-963.
- Torjman M.C., et al., "Glucose Monitoring in Acute Care: Technologies on the Horizon," *Journal of Diabetes Science and Technology*, vol. 2 (2), Mar. 2008, pp. 178-181.
- Trajanoski Z., et al., "Neural Predictive Controller For Insulin Delivery Using The Subcutaneous Route," *IEEE Transactions on Biomedical Engineering*, vol. 45(9), 1998, pp. 1122-1134.
- Trecroci D., "A Glimpse into the Future—Continuous Monitoring of Glucose with a Microfiber," *Diabetes Interview*, Jul. 2002, pp. 42-43.
- Tse P.S.H., et al., "Time-Dependent Inactivation of Immobilized Glucose Oxidase and Catalase," *Biotechnology & Bioengineering*, vol. 29, 1987, pp. 705-713.
- Turner A.P.F., et al., "Carbon Monoxide: Acceptor Oxidoreductase from *Pseudomonas Thermocarboxydovorans* Strain C2 and its Use in a Carbon Monoxide Sensor," *Analytica Chimica Acta*, vol. 163, 1984, pp. 161-174.
- Turner A.P.F., et al., "Diabetes Mellitus: Biosensors for Research and Management," *Biosensors*, vol. 1, 1985, pp. 85-115.
- Unger J., et al., "Glucose Control in the Hospitalized Patient," *Emergency Medicine*, vol. 36 (9), 2004, pp. 12-18.
- Updike S.J., et al., "A Subcutaneous Glucose Sensor with Improved Longevity, Dynamic Range, and Stability of Calibration," *Diabetes Care*, vol. 23 (2), Feb. 2000, pp. 208-214.
- Updike S.J., et al., "Continuous Glucose Monitor Based on an Immobilized Enzyme Electrode Detector," *Journal of Laboratory and Clinical Medicine*, vol. 93(4), 1979, pp. 518-527.
- Updike S.J., et al., "Enzymatic Glucose Sensor: Improved Long-Term Performance in Vitro and In Vivo," *ASAIO Journal*, vol. 40 (2), Apr.-Jun. 1994, pp. 157-163.
- Updike S.J., et al., "Implanting the Glucose Enzyme Electrode: Problems, Progress, and Alternative Solutions," *Diabetes Care*, vol. 5 (3), May-Jun. 1982, pp. 207-212.
- Updike S.J., et al., "Laboratory Evaluation of New Reusable Blood Glucose Sensor," *Diabetes Care*, vol. 11 (10), Nov.-Dec. 1988, pp. 801-807.
- Updike S.J., et al., "Principles of Long-Term Fully Implanted Sensors with Emphasis on Radiotelemetric Monitoring of Blood Glucose Form Inside a Subcutaneous Foreign Body Capsule (FBC)," Edited by Fraser D M, *Biosensors in the Body: Continuous in vivo Monitoring*, John Wiley & Sons Ltd., New York, 1997, Chapter 4, pp. 117-137.
- Updike S.J., et al., "The Enzyme Electrode," *Nature*, vol. 214, Jun. 3, 1967, pp. 986-988.
- Utah Medical Products Inc., "Deltran—Disposable Blood Pressure Transducers," *Product Specifications*, 2003-2006, 6 pages.
- Vadgama P., "Diffusion Limited Enzyme Electrodes," *NATO ASI Series: Series C, Math and Phys. Sci.*, vol. 226, 1988, pp. 359-377.

(56)

## References Cited

## OTHER PUBLICATIONS

- Vadgama P., "Enzyme Electrodes as Practical Biosensors," *Journal of Medical Engineering & Technology*, vol. 5 (6), Nov. 1981, pp. 293-298.
- Valdes T.I., et al., "In Vitro and In Vivo Degradation of Glucose Oxidase Enzyme used for an Implantable Glucose Biosensor," *Diabetes Technology & Therapeutics*, vol. 2 (3), 2000, pp. 367-376.
- Van Den Berghe, "Tight Blood Glucose Control with Insulin in "Real-Life" Intensive Care," *Mayo Clinic Proceedings*, vol. 79 (8), Aug. 2004, pp. 977-978.
- Velho G., et al., "In Vitro and In Vivo Stability of Electrode Potentials in Needle-Type Glucose Sensors," *Influence of Needle Material*, *Diabetes*, vol. 38, Feb. 1989, pp. 164-171.
- Velho G., et al., "Strategies for Calibrating a Subcutaneous Glucose Sensor," *Biomed Biochim Acta*, vol. 48 (11/12), 1989, pp. 957-964.
- Vesper H.W., et al., "Assessment of Trueness of a Glucose Monitor Using Interstitial Fluid and Whole Blood as Specimen Matrix," *Diabetes Technology & Therapeutics*, vol. 8 (1), 2006, pp. 76-80.
- Von Woedtke T., et al., "In Situ Calibration of Implanted Electrochemical Glucose Sensors," *Biomed. Biochim. Acta* 48 vol. 11/12, 1989, pp. 943-952.
- Wagner, et al., "Continuous Amperometric Monitoring of Glucose in a Brittle Diabetic Chimpanzee with a Miniature Subcutaneous Electrode," *Proc. Natl. Acad. Sci. USA*, vol. 95, May 1998, pp. 6379-6382.
- Wang J., et al., "Highly Selective Membrane-Free Mediator-Free Glucose Biosensor," *Analytical Chemistry*, vol. 66 (21), Nov. 1, 1994, pp. 3600-3603.
- Wang X., et al., "Improved Ruggedness for Membrane-Based Amperometric Sensors using a Pulsed Amperometric Method," *Analytical Chemistry*, vol. 69 (21), Nov. 1, 1997, pp. 4482-4489.
- Ward W.K., et al., "A New Amperometric Glucose Microsensor: In Vitro and Short-Term In Vivo Evaluation," *Biosensors & Bioelectronics*, vol. 17, 2002, pp. 181-189.
- Ward W.K., et al., "Assessment of Chronically Subcutaneous Glucose Sensors in Dogs: The Effect of Surrounding Fluid Masses," *ASAIO Journal*, 1999, vol. 45 (6), pp. 555-561.
- Ward W.K., et al., "Rise in Background Current Over Time in a Subcutaneous Glucose Sensor in the Rabbit," *Relevance to Calibration and Accuracy*, *Biosensors & Bioelectronics*, vol. 15, 2000, pp. 53-61.
- Ward W.K., et al., "Understanding Spontaneous Output Fluctuations of an Amperometric Glucose Sensor: Effect of Inhalation Anesthesia and Use of a Nonenzyme Containing Electrode," *ASAIO Journal*, 2000, pp. 540-546.
- Wentholt I.M.E., et al., "Relationship between Interstitial and Blood Glucose in Type 1 Diabetes Patients: Delay and the Push-pull Phenomenon Revisited," *Diabetes Technology & Therapeutics*, vol. 9 (2), 2007, pp. 169-175.
- Wientjes K.J.C., "Development of a Glucose Sensor for Diabetic Patients," (Ph.D. Thesis), 2000, 212 pages.
- Wikipedia., "Intravenous Therapy," [http://en.wikipedia.org/wiki/Intravenous\\_therapy](http://en.wikipedia.org/wiki/Intravenous_therapy), Aug. 15, 2006, 6 pages.
- Wilkins E., et al., "Glucose Monitoring: State of the Art and Future Possibilities," *Med. Eng. Phys.*, vol. 18 (4), 1996, pp. 273-288.
- Wilkins E., et al., "Integrated Implantable Device for Long-Term Glucose Monitoring," *Biosensors & Bioelectronics*, vol. 10, 1995, pp. 485-494.
- Wilkins E.S., et al., "The Coated Wire Electrode Glucose Sensor," *Horm Metab Res Suppl.*, vol. 20, 1988, pp. 50-55.
- Wilson G.S., et al., "Enzyme-Based Biosensors for In Vivo Measurements," *Chern. Rev.*, vol. 100, 2000, pp. 2693-2704.
- Wilson G.S., et al., "Progress Toward the Development of an Implantable Sensor for Glucose," *Clinical Chemistry*, vol. 38 (9), 1992, pp. 1613-1617.
- Wolpert H., "Establishing a Continuous Glucose Monitoring Program," *Journal of Diabetes Science and Technology*, Mar. 2008, vol. 2 (2), pp. 307-310.
- Wolpert H.A., "Commentary: A Clinician's Perspective on Some of the Challenges in Closed Loop," *Diabetes Technology & Therapeutics*, vol. 5 (5), 2003, pp. 843-846.
- Wood W.D., et al., "Hermetic Sealing with Epoxy," *Pave Technology—Mechanical Engineering*, Mar. 1990, 3 pages.
- Woodward S.C., "How Fibroblasts and Giant Cells Encapsulate Implants: Considerations in Design of Glucose Sensors," *Diabetes Care*, vol. 5 (3) May-Jun. 1982, pp. 278-281.
- Worsley G.J. et al., "Measurement of Glucose in Blood with a Phenylboronic Acid Optical Sensor," *Journal of Diabetes Science and Technology*, vol. 2 (2), Mar. 2008, pp. 213-220.
- Wright M., et al., "Bioelectrochemical Dehalogenations Via Direct Electrochemistry of Poly(ethylene oxide)-Modified Myoglobin," *Electrochemistry Communications*, vol. 1, 1999, pp. 609-613.
- Wu H., et al., "In Situ Electrochemical Oxygen Generation with an Immunoisolation Device," *Annals New York Academy of Sciences*, vol. 875, 1999, pp. 105-125.
- Yamasaki Y., et al., "Direct Measurement of Whole Blood Glucose by a Needle-Type Sensor," *Clinica Chimica Acta*. 93, 1989, pp. 93-98.
- Yamasaki Y., "The Development of a Needle-Type Glucose Sensor for Wearable Artificial Endocrine Pancreas," *Medical Journal of Osaka University*, vol. 35 (1-2), Sep. 1984, pp. 25-34.
- Yang C., et al., "A Comparison of Physical Properties and Fuel Cell Performance of Nafion and Zirconium Phosphate/Nafion Composite Membranes," *Journal of Membrane Science*, vol. 237, 2004, pp. 145-161.
- Yang Q., et al., "Development of Needle-Type Glucose Sensor with High Selectivity," *Science and Actuators B*, vol. 46, 1998, pp. 249-256.
- Yang S., et al., "A Glucose Biosensor Based On an Oxygen Electrode: In-Vitro Performances in a Model Buffer Solution and in Blood Plasma," *Biomedical Instrumentation & Technology*, vol. 30 (1), 1996, pp. 55-61.
- Yang S., et al., "Glucose Biosensors with Enzyme Entrapped in Polymer Coating," *Biomedical Instrument and Technology*, Mar./Apr. 1995, vol. 29 (2), pp. 125-133.
- Ye L., et al., "High Current Density Wired' Quinoprotein Glucose Dehydrogenase Electrode," *Analytical Chemistry*, vol. 65, 1993, pp. 238-241.
- Zamzow K.L., et al., "Development and Evaluation of a Wearable Blood Glucose Monitor," *ASAIO Transactions*, vol. 36 (3), 1990, pp. M588-M591.
- Zavalkoff S.R., et al., "Evaluation Of Conventional Blood Glucose Monitoring as An Indicator of Integrated Glucose Values Using a Continuous Subcutaneous Sensor," *Diabetes Care*, vol. 25(9), 2002, pp. 1603-1606.
- Zethelius B., et al., "Use Of Multiple Biomarkers to Improve the Prediction of Death From Cardiovascular Causes," *N. Engl. J. Med.*, vol. 358, May 2008, pp. 2107-2116.
- Zhang, et al., "Elimination of the Acetaminophen Interference in an Implantable Glucose Sensor," *Analytical Chemistry*, 1994, vol. 66 (7), pp. 1183-1188.
- Zhang Y., et al., "Electrochemical Oxidation Of H<sub>2</sub>O<sub>2</sub> On Pt and Pt + Ir Electrodes in Physiological Buffer and its Applicability to H<sub>2</sub>O<sub>2</sub>-Based Biosensors," *J. Electro Analytical Chemistry*, vol. 345, 1993, pp. 253-271.
- Zhang Y., et al., "In Vitro and In Vivo Evaluation of Oxygen Effects on a Glucose Oxidase Based Implantable Glucose Sensor," *Analytica Chimica Acta*, vol. 281, 1993, pp. 513-520.
- Zhu, et al., "Fabrication and Characterization of Glucose Sensors Based on a Microarray H<sub>2</sub>O<sub>2</sub> Electrode," *Biosensors & Bioelectronics*, 1994, vol. 9, pp. 295-300.
- Zhu, et al., "Planar Amperometric Glucose Sensor Based on Glucose Oxidase Immobilized by Chitosan Film on Prussian blue Layer," *Sensors*, 2002, vol. 2, pp. 127-136.
- Ziaie, et al., "A Single-Channel Implantable Microstimulator for Functional Neuromuscular Stimulation," *IEEE Transactions on Biomedical Engineering*, 1997, vol. 44(10), pp. 909-920.
- Asberg P., et al., "Hydrogels of a Conducting Conjugated Polymer as 3-D Enzyme Electrode," *Biosensors Bioelectronics*, 2003, vol. 19, pp. 199-207.



(56)

## References Cited

## OTHER PUBLICATIONS


- Brauker, et al., "Sustained Expression of High Levels of Human Factor IX from Human Cells Implanted within an Immunoisolation Device into Athymic Rodents," *Human Gene Therapy*, Apr. 10, 1998, vol. 9, pp. 879-888.
- Brauker J H., et al., "Neovascularization of Synthetic Membranes Directed by Membrane Microarchitecture," *Journal of Biomedical Material Research*, 1995, vol. 29, pp. 1517-1524.
- Brauker J., "Unraveling Mysteries at the Biointerface: Molecular Mediator of Inhibition of Blood Vessel Formation in the Foreign Body Capsule Revealed," *SurFACTS in Biomaterials*, vol. 6 (3), 2001, pp. 1,5.
- Brunner G.A., et al., "Validation of Home Blood Glucose Meters with Respect to Clinical and Analytical Approaches," *Diabetes Care*, vol. 21, No. 4, Apr. 1998, pp. 585-590.
- Chen C., et al., "A Noninterference Polypyrrole Glucose Biosensor," *Biosensors and Bioelectronics*, vol. 22, 2006, pp. 639-643.
- Dai W.S., et al., "Hydrogel Membranes with Mesh Size Asymmetry based on the Gradient Crosslinking of Poly(Vinyl Alcohol)," *Journal of Membrane Science*, 1999, vol. 156, pp. 67-79.
- D'Arrigo G., et al., "Porous-Si Based Bio Reactors for Glucose Monitoring and Drugs Production," *Proceedings of SPIE*, 2003, vol. 4982, pp. 178-184.
- Extended European Search Report for Application No. 08756743.4 dated Feb. 26, 2013, 7 pages.
- File History of U.S. Appl. No. 10/632,537, filed Aug. 1, 2003, 211 pages.
- File History of U.S. Appl. No. 10/633,329, filed Aug. 1, 2003, 711 pages.
- File History of U.S. Appl. No. 10/633,367, filed Aug. 1, 2003, 432 pages.
- File History of U.S. Appl. No. 10/896,772, filed Jul. 21, 2004, 210 pages.
- File History of U.S. Appl. No. 10/991,966, filed Nov. 17, 2004, 446 pages.
- File History of U.S. Appl. No. 11/038,340, filed Jan. 18, 2005, 653 pages.
- File History of U.S. Appl. No. 11/077,714, filed Mar. 10, 2005, 320 pages.
- File History of U.S. Appl. No. 11/077,740, filed Mar. 10, 2005, 921 pages.
- File History of U.S. Appl. No. 11/077,759, filed Mar. 10, 2005, 596 pages.
- File History of U.S. Appl. No. 11/077,765, filed Mar. 10, 2005, 932 pages.
- File History of U.S. Appl. No. 11/078,232, filed Mar. 10, 2005, 256 pages.
- File History of U.S. Appl. No. 11/333,837, filed Jan. 17, 2006, 672 pages.
- File History of U.S. Appl. No. 11/360,819, filed Feb. 22, 2006, 778 pages.
- File History of U.S. Appl. No. 11/691,432, filed Mar. 26, 2007, 659 pages.
- File History of U.S. Appl. No. 11/334,876, filed Jan. 18, 2006, 751 pages.
- File History of U.S. Appl. No. 11/360,252, filed Feb. 22, 2006, 594 pages.
- Geller R.I., et al., "Use of an Immunoisolation Device for Cell Transplantation and Tumor Immunotherapy," *Annals of the New York Academy of Science*, 1997, vol. 831, pp. 438-451.
- Gerritsen M., et al., "Influence of Inflammatory Cells and Serum on the Performance of Implantable Glucose Sensors," *Journal of Biomedical Material Research*, 2001, vol. 54, pp. 69-75.
- Gregg B A., et al., "Cross-Linked Redox Gels Containing Glucose Oxidase for Amperometric Biosensor Applications," *Anal Chem*, 1990, vol. 62, pp. 258-263.
- Harrison, et al., "Characterization of Perfluorosulfonic Acid Polymer Coated Enzyme Electrodes and a Miniaturized Integrated Potentiostat for Glucose Analysis in Whole Blood," *Analytical Chemistry*, 1988, vol. 60, pp. 2002-2007.
- International Preliminary Report on Patentability for Application No. PCT/US2008/065978 dated Jun. 19, 2008, 14 pages.
- International Search Report and Written Opinion for Application No. PCT/US2008/065978 dated Oct. 2, 2008, 14 pages.
- Kargol M., et al., "Studies on the Structural Properties of Porous Membranes: Measurement of Linear Dimensions of Solutes," *Biophysical Chemistry*, 2001, vol. 91, pp. 263-271.
- Karube I., et al., "Microbiosensors for Acetylcholine and Glucose," *Biosensors & Bioelectronics*, 1993, vol. 8, pp. 219-228.
- Klueh U., et al., "Inflammation and Glucose Sensors: Use of Dexamethasone to Extend Glucose Sensor Function and Life Span in Vivo," *Journal of Diabetes Science and Technology*, vol. 1 (4), Jul. 2007, pp. 496-504.
- Kunzler J., et al., "Hydrogels based on Hydrophilic Side Chain Siloxanes," *Poly Mat Sci and Eng*, 1993, vol. 69, pp. 226-227.
- Kunzler J F., et al., "Contact Lens Materials," *Chemistry & Industry*, Aug. 21, 1995, pp. 651-655.
- Lee E., et al., "Effects of Pore Size, Void Volume, and Pore Connectivity on Tissue Responses to Porous Silicone Implants," *Society for Biomaterials*, 25th Annual Meeting, 1999, p. 171.
- Löffler P., et al., "Separation and Determination of Traces of Ammonia in Air by Means of Chromatomembrane Cells," *Fresenius Journal of Analytical Chemistry*, 1995, vol. 352, pp. 613-614.
- Lyman D J., "Polyurethanes. I. The Solution Polymerization of Diisocyanates with Ethylene Glycol," *Journal of Polymer Science*, 1960, vol. XLV, pp. 49-59.
- Madaras M B., et al., "Microfabricated Amperometric Creatine and Creatinine Biosensors," *Analytica Chimica Acta*, 1996, vol. 319, pp. 335-345.
- Matsumoto T., et al., "A long-Term Lifetime Amperometric Glucose Sensor with a Perfluorocarbon Polymer Coating," *Biosensors & Bioelectronics*, vol. 16, 2001, pp. 271-276.
- Miller K.M., et al., "Generation of IL-1 like Activity in Response to Biomedical Polymer Implants: a Comparison of in Vitro and in Vivo Models," *Journal of Biomedical Materials Research*, vol. 23(9), 1989, pp. 1007-1026.
- Miller K.M., et al., "Human monocyte/macrophage activation and interleukin 1 generation by biomedical polymers," *Journal of Biomedical Materials Research*, vol. 22 (8), 1988, pp. 713-731.
- Miller K.M., et al., "In Vitro Stimulation of Fibroblast Activity by Factors Generated from Human Monocytes Activated by Biomedical Polymers," *Journal of Biomedical Materials Research*, vol. 23(8), 1989, pp. 911-930.
- Moussy F., et al., "Biomaterials community examines biosensor biocompatibility," *Diabetes Technology & Therapeutics*, vol. 2(3), 2000, pp. 473-477.
- Mowery K.A., et al., "Preparation and Characterization by Hydrophobic Polymeric Films that are Thromboresistant via Nitric Oxide Release," *Biomaterials*, vol. 21, 2000, pp. 9-21.
- Myler S., et al., "Ultra-Thin-Polysiloxane-Film-Composite Membranes for the Optimisation of Amperometric Oxidase Enzyme Electrodes," *Biosensors & Bioelectronics*, vol. 17, 2002, pp. 35-43.
- Nakayama Y., et al., "Surface Fixation of Hydrogels: Heparin and Glucose Oxidase Hydrogelated Surfaces" *ASAIO Journal*, 1992, pp. M421-M424.
- Nam Y.S., et al., "A Novel Fabrication Method of Macroporous Biodegradable Polymer Scaffolds Using Gas Foaming Salt as a Poregen Additive," *J Biomed Mater Res*, 2000, vol. 53, pp. 1-7.
- Office Action for European Application No. 07844038.5 dated Jun. 4, 2020, 14 pages.
- Office Action for U.S. Appl. No. 11/691,424, dated Jun. 11, 2009, 21 pages.
- Office Action for U.S. Appl. No. 11/691,424, dated Sep. 25, 2008, 15 pages.
- Office Action for U.S. Appl. No. 11/691,466, dated Oct. 3, 2008, 15 pages.
- Office Action for U.S. Appl. No. 12/102,729, dated Jul. 7, 2009, 7 pages.
- Office Action for U.S. Appl. No. 12/133,738, dated Sep. 10, 2010, 11 pages.
- Office Action for U.S. Appl. No. 12/133,761, dated Sep. 7, 2010, 11 pages.

(56)

**References Cited****OTHER PUBLICATIONS**

- Panetti T.S., "Differential Effects of Sphingosine 1-Phosphate and Lysophosphatidic Acid on Endothelial Cells," *Biochimica et Biophysica Acta*, vol. 1582, 2002, pp. 190-196.
- Phillips R.E., et al., "Biomedical Applications of Polyurethanes: Implications of Failure Mechanisms," *Journal of Biomedical application*, vol. 3, Oct. 1988, pp. 206-227.
- Pickup J.C., et al., "Progress Towards in Vivo Glucose Sensing with a Ferrocene-Mediated Amperometric Enzyme Electrode," *Horm Metab Res Suppl*, vol. 20, 1988, pp. 34-36.
- Pineda L.M., et al., "Bone Regeneration with Resorbable Polymeric Membranes. III. Effect of Poly(L-lactide) Membrane Pore Size on the Bone Healing Process in Large Defects," *Journal of Biomedical Materials Research*, vol. 31, 1996, pp. 385-394.
- Ratner B.D., "Reducing Capsular Thickness and Enhancing Angiogenesis around Implant Drug Release Systems," *Journal of Controlled Release*, vol. 78, 2002, pp. 211-218.
- Sachlos E., et al., "Making Tissue Engineering Scaffolds Work Review on the Application of Solid Freeform Fabrication Technology to the Production of Tissue Engineering Scaffolds," *European Cells and Materials*, vol. 5, 2003, pp. 29-40.
- Sanders E., et al., "Fibrous Encapsulation of Single Polymer Microfibers Depends on their Vertical Dimension in Subcutaneous Tissue Polymer Microfibers," *Journal of Biomedical Material Research*, vol. 67A, 2003, pp. 1181-1187.
- Schuler, et al., "Modified Gas-Permeable Silicone Rubber Membranes for Covalent Immobilisation of Enzymes and their Use in Biosensor Development," *Analyst*, 1999, vol. 124, pp. 1181-1184.
- Sieminski, et al., "Biomaterial-Microvasculature Interactions," *Biomaterials*, 2000, vol. 21, pp. 2233-2241.
- Sigma-Aldrich Corp., "Cellulose Acetate," Product Description, Product No. 419028, St. Louis, MO, 2005, 1 page.
- Sternberg, et al., "Covalent Enzyme Coupling on Cellulose Acetate Membranes for Glucose Sensor Development," *Anal Chem*, Dec. 1988, vol. 60(24), pp. 2781-2786.
- Stokes, "Polyether Polyurethanes: Biostable or Not," *Journal of Biomaterials Applications*, Oct. 1988, vol. 3, pp. 228-259.
- Suh, et al., "Behavior of Fibroblasts on a Porous Hyaluronic Acid Incorporated Collagen Matrix," *Yonsei Medical Journal*, 2002, vol. 43 (2), pp. 193-202.
- Tang, et al., "Fibrin(ogen) Mediates Acute Inflammatory Responses to Biomaterials," *J.Exp.Med*, 1993, vol. 178, pp. 2147-2156.
- Tang, et al., "Inflammatory Responses to Biomaterials," *Am J Clin Pathol*, 1995, vol. 103, pp. 466-471.
- Tang, et al., "Mast Cells Mediate Acute Inflammatory Responses to Implanted Biomaterials," *Proceedings of the National Academy of Sciences of the USA*, 1998, vol. 95, pp. 8841-8846.
- Tang, et al., "Molecular Determinants of Acute Inflammatory Responses to Biomaterials," *J Clin Invest*, 1996, vol. 97, pp. 1329-1334.
- Tibell, et al., "Survival of Macroencapsulated Allogeneic Parathyroid Tissue One Year after Transplantation in Nonimmunosuppressed Humans," *Cell Transplantation*, 2001, vol. 10, pp. 591-599.
- Turner A.P.F., "Amperometric Biosensor based on Mediator-Modified Electrodes," *Methods in Enzymology*, 1988, vol. 137, pp. 90-103.
- Wade L.G., "Reactions of Aromatic Compounds," *Organic Chemistry*, Chapter 17, 5th edition, 2003, pp. 762-763.
- Office Action from Australian Patent Application No. 2018295116, dated Jul. 5, 2021, 3 pages.
- Communication pursuant to Article 94(3) EPC for European Application No. 18869622.3, dated Aug. 17, 2021, 9 pages.

\* cited by examiner






FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C






FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D






FIG. 5B




FIG. 5C




FIG. 5D







FIG. 5E








FIG. 9






FIG. 12




FIG. 13A




FIG. 13B




FIG. 13C






FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D




FIG. 14E




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 16




FIG. 18




FIG. 17




FIG. 19




FIG. 20




FIG. 21A




FIG. 21B




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26






FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31A




FIG. 31B




FIG. 32




FIG. 33




FIG. 34




FIG. 35A




FIG. 35B




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40






FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47A




FIG. 47B




FIG. 48




FIG. 49




FIG. 50




FIG. 51A




FIG. 51B




FIG. 52A




FIG. 52B




FIG. 53A




FIG. 53B




FIG. 54






FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61

1

**PRE-CONNECTED ANALYTE SENSORS****INCORPORATION BY REFERENCE TO  
RELATED APPLICATIONS**

Any and all priority claims identified in the Application Data Sheet, or any correction thereto, are hereby incorporated by reference under 37 CFR 1.57. This application claims the benefit of U.S. application Ser. No. 15/792,038, filed on Oct. 24, 2017, now U.S. Pat. No. 10,653,835, issued on May 19, 2020. The aforementioned application is incorporated by reference herein in its entirety, and is hereby expressly made a part of this specification.

**TECHNICAL FIELD**

The present disclosure generally relates to sensors and, more particularly, to analyte sensors such as continuous analyte sensors.

**BACKGROUND**

Diabetes mellitus is a disorder in which the pancreas cannot create sufficient insulin (Type I or insulin dependent) and/or in which insulin is not effective (Type 2 or non-insulin dependent). In the diabetic state, the victim suffers from high blood sugar, which can cause an array of physiological derangements associated with the deterioration of small blood vessels, for example, kidney failure, skin ulcers, or bleeding into the vitreous of the eye. A hypoglycemic reaction (low blood sugar) can be induced by an inadvertent overdose of insulin, or after a normal dose of insulin or glucose-lowering agent accompanied by extraordinary exercise or insufficient food intake.

Conventionally, a person with diabetes carries a self-monitoring blood glucose (SMBG) monitor, which typically requires uncomfortable finger pricking methods. Due to the lack of comfort and convenience, a person with diabetes normally only measures his or her glucose levels two to four times per day. Unfortunately, such time intervals are spread so far apart that the person with diabetes likely finds out too late of a hyperglycemic or hypoglycemic condition, sometimes incurring dangerous side effects. Glucose levels may be alternatively monitored continuously by a sensor system including an on-skin sensor assembly. The sensor system may have a wireless transmitter which transmits measurement data to a receiver which can process and display information based on the measurements.

This Background is provided to introduce a brief context for the Summary and Detailed Description that follow. This Background is not intended to be an aid in determining the scope of the claimed subject matter nor be viewed as limiting the claimed subject matter to implementations that solve any or all of the disadvantages or problems presented above.

**SUMMARY**

There are various steps in the manufacturing process of an analyte sensor such as a continuous analyte sensor for which temporary mechanical and electrical connections between the sensor and manufacturing equipment such as testing and/or calibration equipment are used. These connections are facilitated by accurate placement and alignment of the sensor to mechanical and electrical interfaces of the testing and/or calibration equipment. A device such as an “interconnect”, “interposer” or “sensor carrier” can be attached to

2

an elongated body of the sensor, as described hereinafter, to assist with handling, and both temporary and permanent, electrical and mechanical connections. A sensor carrier (also referred to as a “sensor interposer”) may also include features for tracking, data storage, and sealing sensor electrodes, from each other and from the environment. Without limiting the scope of the present embodiments as expressed by the claims that follow, their more prominent features now will be discussed briefly. After considering this discussion, and particularly after reading the section entitled “Detailed Description,” one will understand how the features of the present embodiments provide the advantages described herein.

In accordance with a first aspect, a method of manufacturing a sensor is provided. The method includes providing an analyte sensor having an elongated body, a first electrode, a second electrode coaxially located within the first electrode, and at least two electrical contacts longitudinally aligned and spaced along a longitudinal axis of the sensor. The method includes attaching a sensor carrier to the analyte sensor, the sensor carrier including an intermediate body, a first conductive portion disposed on the intermediate body, the first conductive portion in electrical communication with the first electrode, a second conductive portion disposed on the intermediate body, the second conductive portion in electrical communication with the second electrode. The first and second conductive portions form a connection portion configured to establish electrical connection between the sensor and a separate device.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the first aspect, the method further includes coupling an outer layer to the intermediate body. The outer layer includes an identifier. The outer layer, the sensor, and the intermediate body can form a laminated configuration. The identifier can be a QR code sheet. The identifier can include any of an optical identifier, a radio-frequency identifier, or a memory-encoded identifier. The identifier can identify the analyte sensor, calibration data for the analyte sensor, or a history of the analyte sensor.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the first aspect, the method further includes coating the sensor with a membrane after attaching the sensor to the sensor carrier.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the first aspect, the first conductive portion and the second conductive portion are traces. The traces can extend from a distal position of the sensor carrier and terminate at a proximal end of the sensor carrier. The traces can form exposed contact surfaces in the connection portion. The first and second conductive portions can be embedded into the intermediate body.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the first aspect, the first conductive portion and the second conductive portion are solder welds. The solder welds can attach the sensor to the sensor carrier.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the first aspect, the first conductive portion and the second conductive portion are conductive tapes. The conductive tapes can attach the sensor to the sensor carrier.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the first aspect, the method further includes

tified herein) of the first aspect, the connection portion is configured to mechanically mate with the separate device.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the first aspect, the separate device is an electronics unit configured to measure analyte data.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the first aspect, the separate device is a component of a manufacturing station. The method can further include performing at least one of a potentiostat measurement, a dipping process, a curing process, a calibration process, or a sensitivity measurement while the electrical connection is established between the sensor and the manufacturing station. The method can further include de-establishing electrical connection between the sensor and the calibration station. The method can further include establishing electrical connection between the sensor and at least one testing station via the connection portion of the sensor carrier.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the first aspect, the intermediate body further includes a datum structure that controls a position and spatial orientation of the analyte sensor relative to a substrate of the intermediate body. The datum structure can include a flexible portion of the substrate that is folded over at least a portion of the analyte sensor.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the first aspect, the first conductive portion and/or the second conductive portion comprise at least one of a coil spring, a leaf spring, or a conductive elastomer.

In accordance with a second aspect, an apparatus is provided that includes an analyte sensor having an elongated body, a first electrode in electrical communication with a first conductive contact, a second electrode in electrical communication with a second conductive contact. The sensor carrier can be attached to the analyte sensor. The sensor carrier can include an intermediate body, a first conductive portion disposed on the intermediate body, the first conductive portion in electrical communication with the first conductive contact, and a second conductive portion disposed on the intermediate body, the second conductive portion in electrical communication with the second conductive contact. The first and second conductive portions can form a connection portion configured to establish electrical communication between the first and second conductive contacts and a separate device.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the second aspect, the apparatus further includes an identifier coupled to the intermediate body. The identifier, the sensor, and the intermediate body can form a laminated configuration. The identifier can be a QR code sheet. The identifier can be any of an optical identifier, a radio-frequency identifier, or a memory-encoded identifier. The identifier can be configured to identify any of the analyte sensor, calibration data for the analyte sensor, and a history of the analyte sensor.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the second aspect, the first conductive portion and the second conductive portion are traces. The traces can form exposed contact surfaces in the connection portion. The first and second conductive portions can be at least partially embedded into the intermediate body.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the second aspect, the first conductive portion and the second conductive portion include at least one of a solder weld, a conductive tape, a coil spring, a leaf spring, or a conductive elastomer.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the second aspect, the connection portion is configured to mechanically mate with the separate device.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the second aspect, the separate device is an electronics unit configured to measure analyte data.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the second aspect, the separate device is a component of a manufacturing station. At least one of a potentiostat measurement, a dipping process, a curing process, a calibration process, or a sensitivity measurement can be configured to be performed while the electrical connection is established between the sensor and the manufacturing station. The manufacturing station can comprise a calibration station configured to de-establish electrical connection between the sensor and the calibration station and establish electrical connection between the sensor and at least one testing station via the connection portion of the sensor carrier.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the second aspect, the intermediate body further comprises a datum structure configured to control a position and spatial orientation of the analyte sensor relative to a substrate of the intermediate body.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the second aspect, the first electrode may be positioned coaxially within the second electrode, and the first electrical contact and the second electrical contact may be longitudinally aligned and spaced along a longitudinal axis of the sensor.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the second aspect, the first electrode and the second electrode may be affixed to a flexible planar substrate. In addition, the first electrical contact and the second electrical contact may be affixed to the flexible planar substrate.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the second aspect, the first conductive contact and the second conductive contact are affixed to the intermediate body with conductive adhesive.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the second aspect, the first conductive contact and the second conductive contact are affixed to the intermediate body with anisotropic conductive film.

In accordance with a third aspect, an array of pre-connected analyte sensors is provided. The array includes a substrate, a first plurality of electrical contacts disposed on the substrate, a second plurality of electrical contacts disposed on the substrate, and a plurality of analyte sensors disposed on the substrate. Each of the plurality of analyte sensors includes a first sensor electrical contact coupled to a corresponding one of the first plurality of electrical contacts on the substrate, and a second sensor electrical contact

5

coupled to a corresponding one of the second plurality of electrical contacts on the substrate. The array may comprise one or more strips.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the third aspect, the first plurality of electrical contacts are aligned along the substrate. The first plurality of electrical contacts can be formed from an exposed contact surface.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the third aspect, the second plurality of electrical contacts are aligned along the substrate. The second plurality of electrical contacts can be formed from an exposed contact surface.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the third aspect, the first and second plurality of electrical contacts are configured to connect with a separate device. The separate device can be a component of a manufacturing station.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the third aspect, the substrate includes at least one singulation feature configured to facilitate singulation of the substrate into a plurality of sensor carriers, wherein each of the plurality of sensor carriers is attached to a corresponding one of the analyte sensors.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the third aspect, the strip further includes a plurality of identifiers disposed on the substrate.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the third aspect, the substrate includes an elongated dimension, wherein the plurality of analyte sensors extend beyond an edge of the substrate in a direction orthogonal to the elongated dimension. The strip can further include a feed-guide strip that runs along an opposing edge of the substrate in the elongated dimension. The substrate can further include a flexible substrate configured to be rolled onto a reel. The feed-guide strip can be removable from the substrate.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the third aspect, the substrate comprises a molded thermoplastic having a plurality of datum features that control a position and orientation of the plurality of analyte sensors, and wherein the a first plurality of electrical contacts and the second plurality of electrical contacts each comprise embedded conductive traces in the molded thermoplastic.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the third aspect, the strip further includes a first datum structure coupled to the strip, the first datum structure configured to position the plurality of analyte sensors. The first datum structure includes at least one singulation feature configured to facilitate singulation of the first datum structure into a plurality of second datum structures, wherein each of the plurality of second datum structures is coupled to a corresponding one of a plurality of sensor carriers formed by the substrate.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the third aspect, the strip further includes a carrier having processing circuitry configured to perform at

6

least potentiostat measurements for the plurality of analyte sensors. The strip can further include communications circuitry operable by the processing circuitry to send and receive data associated with each of the analyte sensors together with an identifier for that analyte sensor.

In accordance with a fourth aspect, a method is provided. The method includes providing a pre-connected analyte sensor, the pre-connected analyte sensor comprising an intermediate body, an analyte sensor permanently attached to the intermediate body, and an identifier coupled to the intermediate body. The method includes communicatively coupling the analyte sensor to a processing circuitry of a manufacturing station by coupling the intermediate body to a corresponding feature of the manufacturing station. The method includes operating the processing circuitry of the manufacturing station to communicate with the pre-connected analyte sensor.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the fourth aspect, operating the processing circuitry includes obtaining a signal from the analyte sensor via the connection portion. Operating the processing circuitry can include operating an optical, infrared, or radio-frequency reader of the manufacturing station to obtain the identifier.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the fourth aspect, the method further includes storing, with the processing circuitry of the manufacturing station and in connection with the identifier, sensor data corresponding to the signal. The identifier can identify any of the analyte sensor, calibration data for the analyte sensor, and a history of the analyte sensor.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the fourth aspect, the signal includes a glucose sensitivity signal.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the fourth aspect, the method further includes removing the pre-connected analyte sensor from the manufacturing station and communicatively coupling the analyte sensor to processing circuitry of a wearable device by mechanically coupling an anchoring feature of the intermediate body to a corresponding feature of a wearable device. The method can further include obtaining in vivo measurement data from the analyte sensor with the processing circuitry of the wearable device.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the fourth aspect, the analyte sensor is permanently attached to the intermediate body with conductive adhesive.

In a generally applicable embodiment (i.e. independently combinable with any of the aspects or embodiments identified herein) of the fourth aspect, the analyte sensor is permanently attached to the intermediate body with anisotropic conductive film.

In accordance with a fifth aspect, a wearable device is provided. The wearable device comprises a housing and electronic circuitry configured to process analyte sensor signals. The electronic circuitry is enclosed within the housing. An analyte sensor has a distal portion positioned outside the housing. An intermediate body has an electrical connection to both a proximal portion of the analyte sensor and the electronics, wherein the electrical connection

between the intermediate body and the proximal portion of the analyte sensor is external to the housing.

In generally applicable embodiments (i.e. independently combinable with any of the aspects or embodiments identified herein) of the fifth aspect the intermediate body may be positioned adjacent to an exterior surface of the housing. The device may include electrical contacts coupled to both the electronics and the intermediate body. The intermediate body may be electrically connected to the electrical contacts with conductive epoxy. The intermediate body is electrically connected to the electrical contacts with anisotropic conductive film. The intermediate body may be sealed. The electrical contacts may extend through the housing. The intermediate body may be positioned in a recess on the exterior surface of the housing. The electrical contacts may extend through the housing in the recess to electrically couple the intermediate body to the electronic circuitry enclosed within the housing. The intermediate body may be covered with a polymer in the recess.

In generally applicable embodiments (i.e. independently combinable with any of the aspects or embodiments identified herein) of the fifth aspect the analyte sensor is formed as an elongated body with a distal portion configured for percutaneous implantation in a subject and a proximal portion configured for electrically connecting to the intermediate body. The distal portion of the analyte sensor may extend away from an opening through the housing. The electronic circuitry may comprise a potentiostat and/or a wireless transmitter.

In accordance with a sixth aspect, a method of making a pre-connected analyte sensor is provided. The method comprises mechanically and electrically connecting a proximal portion of an elongated conductor to a conductive portion of an intermediate body, and after the connecting, coating a distal portion of the elongated conductor with a polymer membrane to form an analyte sensor having a working electrode region configured to support electrochemical reactions for analyte detection in the distal portion of the elongated conductor.

In generally applicable embodiments (i.e. independently combinable with any of the aspects or embodiments identified herein) of the sixth aspect, the method additionally comprises testing the analyte sensor, wherein the testing comprises electrically coupling the intermediate body to a testing station. The method may additionally comprise calibrating the analyte sensor, wherein the calibrating comprises electrically coupling the intermediate body to a testing station. The coating may comprise dip coating.

In generally applicable embodiments (i.e. independently combinable with any of the aspects or embodiments identified herein) of the sixth aspect, the intermediate body may be part of an array formed by a plurality of coupled intermediate bodies, wherein the method further comprises mechanically and electrically connecting a proximal portion of each of a plurality of elongated electrodes to a conductive portion of each intermediate body of the array. The coating may be performed in parallel on each distal portion of each of the plurality of elongated electrodes connected to the intermediate bodies of the array. The method may comprise singulating one or more of the intermediate bodies of the array after the coating.

In generally applicable embodiments (i.e. independently combinable with any of the aspects or embodiments identified herein) of the sixth aspect, mechanically and electrically connecting comprises applying conductive paste to the elongated conductor and the conductive portion of the intermediate body. In some embodiments, mechanically and

electrically connecting comprises compressing anisotropic conductive film between the proximal portion of the elongated conductor and the conductive portion of the intermediate body. The connecting may be performed at a location remote from the coating. In some embodiments, the coating, testing, and calibrating are all performed at a location remote from the connecting.

In accordance with a seventh aspect, a method of making an on-skin wearable percutaneous analyte sensor comprises assembling electronic circuitry into an internal volume of a housing, wherein the electronic circuitry is configured for (1) detecting signals generated from an electrochemical reaction under the skin of a subject at a working electrode of an analyte sensor, and (2) wirelessly transmitting data derived from the detected signals outside of the housing for processing and/or display by a separate device. After assembling the electronic circuitry into the internal volume of the housing, attaching a proximal portion of the analyte sensor to an external electrical interface coupled to the electronic circuitry such that the electronic circuitry becomes connected to the analyte sensor to receive signals therefrom without opening the housing.

In generally applicable embodiments (i.e. independently combinable with any of the aspects or embodiments identified herein) of the seventh aspect, the method comprises sealing the interface after attaching the proximal portion of the analyte sensor. The method may comprise testing the electronic circuitry for functionality prior to the attaching. The method may comprise testing the analyte sensor for functionality prior to the attaching. The assembling may be performed at a location remote from the attaching.

In generally applicable embodiments (i.e. independently combinable with any of the aspects or embodiments identified herein) of the seventh aspect, the method may comprise coupling an intermediate body to the proximal portion of the analyte sensor, and the attaching may comprise attaching the intermediate body to the external electrical interface. The method may then comprise performing at least one manufacturing or testing procedure on the working electrode using the intermediate body prior to the attaching. The performing may comprise coating the working electrode of the analyte sensor. The coupling may be performed at a first location, the assembling may be performed at a second location, and the performing may be performed at a third location, wherein the first, second, and third locations are remote from one another. The attaching and/or the coupling may be performed with anisotropic conductive film. The method may further comprise attaching an inserter to the housing for implanting the working electrode into a subject.

It is understood that various configurations of the subject technology will become readily apparent to those skilled in the art from the disclosure, wherein various configurations of the subject technology are shown and described by way of illustration. As will be realized, the subject technology is capable of other and different configurations and its several details are capable of modification in various other respects, all without departing from the scope of the subject technology. Accordingly, the summary, drawings and detailed description are to be regarded as illustrative in nature and not as restrictive.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The present embodiments now will be discussed in detail with an emphasis on highlighting the advantageous features. These embodiments are for illustrative purposes only and are not to scale, instead emphasizing the principles of the



disclosure. These drawings include the following figures, in which like numerals indicate like parts:

FIG. 1 is a schematic view of an analyte sensor system attached to a host and communicating with a plurality of example devices, according to some embodiments.

FIG. 2 is a block diagram that illustrates electronics associated with the sensor system of FIG. 1, according to some embodiments.

FIGS. 3A-3C illustrate a wearable device having an analyte sensor, according to some embodiments.

FIG. 3D illustrates one implementation of an elongated sensor connected to a potentiostat.

FIG. 4A illustrates a schematic of a pre-connected analyte sensor, according to some embodiments.

FIG. 4B illustrates another schematic of a pre-connected analyte sensor, according to some embodiments.

FIG. 4C illustrates a layered view of a pre-connected analyte sensor, according to some embodiments.

FIG. 4D illustrates a schematic view of an array of pre-connected analyte sensors, according to some embodiments.

FIGS. 5A-5E illustrate block diagrams of a system having a manufacturing system and a wearable device for an analyte sensor, according to some embodiments.

FIG. 6 illustrates a cross-sectional schematic view of a wearable device with a pre-connected analyte sensor, according to some embodiments.

FIG. 7 illustrates a cross-sectional schematic view of a wearable device with a pre-connected analyte sensor, according to some embodiments.

FIG. 8 illustrates a cross-sectional schematic view of a wearable device with a pre-connected analyte sensor, according to some embodiments.

FIG. 9 illustrates a perspective view of an on-skin sensor assembly, according to some embodiments.

FIGS. 10 and 11 illustrate perspective views of sensor carriers that have springs, according to some embodiments.

FIG. 12 illustrates a cross-sectional perspective view of a portion of a sensor carrier, according to some embodiments.

FIGS. 13A-13B illustrate perspective views of a wearable sensor assembly, according to some embodiments.

FIG. 13C illustrates an exploded view of components of a wearable sensor assembly, according to some embodiments.

FIGS. 14A-14B illustrate perspective views of another wearable sensor assembly, according to some embodiments.

FIG. 14C illustrates an exploded view of components of another wearable sensor assembly, according to some embodiments, including an external electrical interface embodiment.

FIG. 14D illustrates a top plan view of the external electrical interface of FIG. 14C with a pre-connected sensor assembly installed.

FIG. 14E is a cross section along lines E-E in FIG. 14D.

FIG. 15A illustrates another embodiment of a printed circuit board substrate for a sensor carrier.

FIGS. 15B and 15C illustrate alternative embodiments for coupling a sensor and sensor carrier to an electrical interface of a wearable sensor assembly.

FIG. 16 illustrates a top view of a sensor carrier attached to an analyte sensor with conductive adhesive, according to some embodiments.

FIG. 17 illustrates an end view of a sensor carrier attached to an analyte sensor with conductive adhesive, according to some embodiments.

FIG. 18 illustrates an end view of a sensor carrier attached to an analyte sensor with conductive adhesive in a recess of a sensor carrier substrate, according to some embodiments.

FIG. 19 illustrates an end view of a sensor carrier attached to an analyte sensor with conductive adhesive in a corner of a sensor carrier substrate, according to some embodiments.

FIG. 20 illustrates an end view of a sensor carrier attached to an analyte sensor with conductive adhesive in a rounded recess of a sensor carrier substrate, according to some embodiments.

FIGS. 21A and 21B illustrate a perspective view and an end view respectively of an analyte sensor attached to a sensor carrier in guide structures.

FIG. 22 illustrates a top view of a sensor carrier attached to an analyte sensor with conductive tape, according to some embodiments.

FIG. 23 illustrates a top view of a sensor carrier having a substrate attached to and wrapped around an analyte sensor, according to some embodiments.

FIG. 24 illustrates a top view of a sensor carrier attached to an analyte sensor with welded conductive plastic, according to some embodiments.

FIGS. 25 and 26 illustrate manufacturing equipment for attaching a sensor carrier to an analyte sensor with conductive plastic, according to some embodiments.

FIG. 27 is a perspective-view schematic illustrating a proximal portion of an analyte sensor having flattened electrical connector portions, according to some embodiments.

FIG. 28 illustrates a side view of the analyte sensor of FIG. 24 attached to a sensor carrier, according to some embodiments.

FIG. 29 illustrates a top view of a sensor carrier having a flexible substrate configured to wrap around an analyte sensor, according to some embodiments.

FIG. 30 illustrates a perspective view of a sensor carrier having substrate with a flexible portion configured to wrap around an analyte sensor, according to some embodiments.

FIGS. 31A and 31B illustrate another embodiment of a sensor carrier attached to an analyte sensor.

FIG. 32 illustrates a top view of a sensor carrier having a movable fastener for attaching an analyte sensor, according to some embodiments.

FIG. 33 illustrates a perspective view of the movable fastener of FIG. 29, according to some embodiments.

FIG. 34 illustrates a perspective view of a sensor carrier implemented as a barrel fastener, according to some embodiments.

FIG. 35A illustrates a face-on view of a sensor carrier having a flexible substrate wrapped around an analyte sensor, according to some embodiments.

FIG. 35B illustrates a perspective view of a sensor carrier having a flexible substrate wrapped around multiple analyte sensors, according to some embodiments.

FIG. 36 illustrates an end view of a sensor carrier having a crimp connector, according to some embodiments.

FIG. 37 illustrates an end view of a sensor carrier attached to an analyte sensor by a crimp connector, according to some embodiments.

FIG. 38 illustrates a side view of a sensor carrier having crimp connectors, according to some embodiments.

FIG. 39 illustrates a perspective view of a sensor carrier, according to some embodiments.

FIG. 40 illustrates a perspective view of a sensor carrier formed from a molded interconnect device, according to some embodiments.

11

FIG. 41 illustrates a top view of a sensor carrier formed from a molded interconnect device, according to some embodiments.

FIG. 42 illustrates a side view of a sensor carrier attached to an analyte sensor by a conductive coupler, according to some embodiments.

FIG. 43 illustrates a side view of a sensor carrier having an elongated dimension for attachment to multiple analyte sensors, according to some embodiments.

FIG. 44 illustrates a top view of a sensor carrier having a flexible substrate for wrapping around an analyte sensor, according to some embodiments.

FIG. 45 illustrates a top view of another sensor carrier having a flexible substrate for wrapping around an analyte sensor, according to some embodiments.

FIG. 46 illustrates a top view of another sensor carrier having a flexible substrate for wrapping around an analyte sensor, according to some embodiments.

FIG. 47A illustrates a side view of a sensor carrier having a feed-guide strip on an elongated dimension for attachment to multiple analyte sensors, according to some embodiments.

FIG. 47B illustrates a perspective view of the sensor carrier of FIG. 47A wrapped on a reel, according to some embodiments.

FIG. 48 illustrates a top view of the sensor carrier of FIG. 47A with a sensor carrier singulated from the sensor carrier, according to some embodiments.

FIG. 49 illustrates a perspective view of a sensor carrier having spring-loaded receptacles for attachment of multiple analyte sensors, according to some embodiments.

FIG. 50 illustrates a perspective view of a sensor carrier having magnetic datum features for positioning and orientation of multiple analyte sensors, according to some embodiments.

FIG. 51A illustrates a top view of a sensor carrier having a rigid flex panel for attachment to multiple analyte sensors, according to some embodiments.

FIG. 51B illustrates a top view of a sensor carrier having a rigid flex panel for attachment to multiple analyte sensors having an edge card connector pad for electronic connection, according to some embodiments.

FIG. 52A illustrates a top view of a sensor carrier singulated from the sensor carrier of FIG. 48 and attached to an analyte sensor to form a pre-connected sensor, according to some embodiments.

FIG. 52B illustrates a sensor carrier having a rigid flex panel for attachment to multiple analyte sensors of FIG. 48B without the V-score portion, according to some embodiments.

FIG. 53A illustrates the pre-connected sensor to be installed in a wearable device, according to some embodiments.

FIG. 53B illustrates the pre-connected sensor in a folded position to be installed in a wearable device, according to some embodiments.

FIG. 54 illustrates a sensor carrier implemented as a daughter board for connection to an analyte sensor, according to some embodiments.

FIG. 55 illustrates a sensor carrier implemented with a pinch clip, according to some embodiments.

FIG. 56 illustrates a sensor carrier having clips for connection to an analyte sensor, according to some embodiments.

FIG. 57 is a flow chart of illustrative operations that may be performed for manufacturing and using a pre-connected sensor, according to some embodiments.

12

FIG. 58 illustrates a perspective view of a sensor-holding apparatus having a fluted flexible tube, according to some embodiments.

FIG. 59 illustrates an exploded perspective view of the apparatus of FIG. 58, according to some embodiments.

FIG. 60 illustrates a device that includes a sensor mounted in the apparatus of FIG. 55, according to some embodiments.

FIG. 61 illustrates a diagram of a carrier for pre-connected sensors, according to some embodiments.

Like reference numerals refer to like elements throughout. Elements are not to scale unless otherwise noted.

## DETAILED DESCRIPTION

The following description and examples illustrate some exemplary implementations, embodiments, and arrangements of the disclosed invention in detail. Those of skill in the art will recognize that there are numerous variations and modifications of this invention that are encompassed by its scope. Accordingly, the description of a certain example embodiment should not be deemed to limit the scope of the present invention.

### Definitions

In order to facilitate an understanding of the various embodiments described herein, a number of terms are defined below.

The term “analyte” as used herein is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and furthermore refers without limitation to a substance or chemical constituent in a biological fluid (for example, blood, interstitial fluid, cerebral spinal fluid, lymph fluid or urine) that can be analyzed. Analytes can include naturally occurring substances, artificial substances, metabolites, and/or reaction products. In some embodiments, the analyte for measurement by the sensor heads, devices, and methods is analyte. However, other analytes are contemplated as well, including but not limited to acarboxyprothrombin; acylcarnitine; adenine phosphoribosyl transferase; adenosine deaminase; albumin; alpha-fetoprotein; amino acid profiles (arginine (Krebs cycle), histidine/urocanic acid, homocysteine, phenylalanine/tyrosine, tryptophan); androstenedione; antipyrine; arabinitol enantiomers; arginase; benzoylecgonine (cocaine); biotinidase; biotin; c-reactive protein; carnitine; carnosinase; CD4; ceruloplasmin; chenodeoxycholic acid; chloroquine; cholesterol; cholinesterase; conjugated 1-β hydroxy-cholic acid; cortisol; creatine kinase; creatine kinase MM isoenzyme; cyclosporin A; D-penicillamine; de-ethylchloroquine; dehydroepiandrosterone sulfate; DNA (acetylator polymorphism, alcohol dehydrogenase, alpha 1-antitrypsin, cystic fibrosis, Duchenne/Becker muscular dystrophy, analyte-6-phosphate dehydrogenase, hemoglobin A, hemoglobin S, hemoglobin C, hemoglobin D, hemoglobin E, hemoglobin F, D-Punjab, beta-thalassemia, hepatitis B virus, HCMV, HIV-1, HTLV-1, Leber hereditary optic neuropathy, MCAD, RNA, PKU, *Plasmodium vivax*, sexual differentiation, 21-deoxycortisol); desbutylhalofantrine; dihydropteridine reductase; diphtheria/tetanus antitoxin; erythrocyte arginase; erythrocyte protoporphyrin; esterase D; fatty acids/acylglycines; free β-human chorionic gonadotropin; free erythrocyte porphyrin; free thyroxine (FT4); free tri-iodothyronine (FT3); fumarylacetoacetase; galactose/gal-1-phosphate; galactose-1-phosphate uridylyltransferase; gentamicin; analyte-6-phosphate dehydrogenase; glutathione; glutathione peroxidase; glycocholic acid; glycosyl

13

lated hemoglobin; halofantrine; hemoglobin variants; hexosaminidase A; human erythrocyte carbonic anhydrase I; 17-alpha-hydroxyprogesterone; hypoxanthine phosphoribosyl transferase; immunoreactive trypsin; lactate; lead; lipoproteins ((a), B/A-1, B); lysozyme; mefloquine; netilmicin; phenobarbitone; phenytoin; phytanic/pristanic acid; progesterone; prolactin; prolidase; purine nucleoside phosphorylase; quinine; reverse tri-iodothyronine (rT3); selenium; serum pancreatic lipase; sisomicin; somatomedin C; specific antibodies (adenovirus, anti-nuclear antibody, anti-zeta antibody, arbovirus, Aujeszky's disease virus, dengue virus, *Dracunculus medinensis*, *Echinococcus granulosus*, *Entamoeba histolytica*, enterovirus, *Giardia duodenalis*, *Helicobacter pylori*, hepatitis B virus, herpes virus, HIV-1, IgE (atopic disease), influenza virus, *Leishmania donovani*, *Lep-10 tospira*, measles/mumps/rubella, *Mycobacterium leprae*, *Mycoplasma pneumoniae*, Myoglobin, *Onchocerca volvulus*, parainfluenza virus, *Plasmodium falciparum*, poliovirus, *Pseudomonas aeruginosa*, respiratory syncytial virus, *Rickettsia* (scrub typhus), *Schistosoma mansoni*, *Toxoplasma gondii*, *Treponema pallidum*, *Trypanosoma cruzi/rangeli*, vesicular stomatitis virus, *Wuchereria bancrofti*, yellow fever virus); specific antigens (hepatitis B virus, HIV-1); succinylacetone; sulfadoxine; theophylline; thyrotropin (TSH); thyroxine (T4); thyroxine-binding globulin; trace elements; transferrin; UDP-galactose-4-epimerase; urea; uroporphyrinogen I synthase; vitamin A; white blood cells; and zinc protoporphyrin. Salts, sugar, protein, fat, vitamins, and hormones naturally occurring in blood or interstitial fluids can also constitute analytes in certain embodiments. The analyte can be naturally present in the biological fluid, for example, a metabolic product, a hormone, an antigen, an antibody, and the like. Alternatively, the analyte can be introduced into the body, for example, a contrast agent for imaging, a radioisotope, a chemical agent, a fluorocarbon-based synthetic blood, or a drug or pharmaceutical composition, including but not limited to insulin; ethanol; cannabis (marijuana, tetrahydrocannabinol, hashish); inhalants (nitrous oxide, amyl nitrite, butyl nitrite, chlorohydrocarbons, hydrocarbons); cocaine (crack cocaine); stimulants (amphetamines, methamphetamines, Ritalin, Cylert, Preludin, Didrex, PreState, Voranil, Sandrex, Plegine); depressants (barbiturates, methaqualone, tranquilizers such as Valium, Librium, Miltown, Serax, Equanil, Tranxene); hallucinogens (phen-45 cyclidine, lysergic acid, mescaline, peyote, psilocybin); narcotics (heroin, codeine, morphine, opium, meperidine, Percocet, Percodan, Tussionex, Fentanyl, Darvon, Talwin, Lomotil); designer drugs (analogs of fentanyl, meperidine, amphetamines, methamphetamines, and phencyclidine, for example, Ecstasy); anabolic steroids; and nicotine. The metabolic products of drugs and pharmaceutical compositions are also contemplated analytes. Analytes such as neurochemicals and other chemicals generated within the body can also be analyzed, such as, for example, ascorbic acid, uric acid, dopamine, noradrenaline, 3-methoxy-50 tyramine (3MT), 3,4-Dihydroxyphenylacetic acid (DOPAC), Homovanillic acid (HVA), 5-Hydroxytryptamine (5HT), and 5-Hydroxyindoleacetic acid (FHIAA).

The terms "microprocessor" and "processor" as used herein are broad terms and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and furthermore refer without limitation to a computer system, state machine, and the like that performs arithmetic and logic operations using logic circuitry that responds to and processes the basic instructions that drive a computer.

14


The term "calibration" as used herein is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and furthermore refers without limitation to the process of determining the relationship between the sensor data and the corresponding reference data, which can be used to convert sensor data into meaningful values substantially equivalent to the reference data, with or without utilizing reference data in real time. In some embodiments, namely, in analyte sensors, calibration can be updated or recalibrated (at the factory, in real time and/or retrospectively) over time as changes in the relationship between the sensor data and reference data occur, for example, due to changes in sensitivity, baseline, transport, metabolism, and the like.

The terms "calibrated data" and "calibrated data stream" as used herein are broad terms and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and furthermore refer without limitation to data that has been transformed from its raw state to another state using a function, for example a conversion function, including by use of a sensitivity, to provide a meaningful value to a user.

The term "algorithm" as used herein is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and furthermore refers without limitation to a computational process (for example, programs) involved in transforming information from one state to another, for example, by using computer processing.

The term "sensor" as used herein is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and furthermore refers without limitation to the component or region of a device by which an analyte can be quantified. A "lot" of sensors generally refers to a group of sensors that are manufactured on or around the same day and using the same processes and tools/materials. Additionally, sensors that measure temperature, pressure etc. may be referred to as a "sensor".

The terms "glucose sensor" and "member for determining the amount of glucose in a biological sample" as used herein are broad terms and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and furthermore refer without limitation to any mechanism (e.g., enzymatic or non-enzymatic) by which glucose can be quantified. For example, some embodiments utilize a membrane that contains glucose oxidase that catalyzes the conversion of oxygen and glucose to hydrogen peroxide and gluconate, as illustrated by the following chemical reaction:



Because for each glucose molecule metabolized, there is a proportional change in the co-reactant O<sub>2</sub> and the product H<sub>2</sub>O<sub>2</sub>, one can use an electrode to monitor the current change in either the co-reactant or the product to determine glucose concentration.

The terms "operably connected" and "operably linked" as used herein are broad terms and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and furthermore refer without limitation to one or more components being linked to another component(s) in a manner that allows transmission of sig-

15

nals between the components. For example, one or more electrodes can be used to detect the amount of glucose in a sample and convert that information into a signal, e.g., an electrical or electromagnetic signal; the signal can then be transmitted to an electronic circuit. In this case, the electrode is “operably linked” to the electronic circuitry. These terms are broad enough to include wireless connectivity.

The term “determining” encompasses a wide variety of actions. For example, “determining” may include calculating, computing, processing, deriving, investigating, looking up (e.g., looking up in a table, a database or another data structure), ascertaining and the like. Also, “determining” may include receiving (e.g., receiving information), accessing (e.g., accessing data in a memory) and the like. Also, “determining” may include resolving, selecting, choosing, calculating, deriving, establishing and/or the like. Determining may also include ascertaining that a parameter matches a predetermined criterion, including that a threshold has been met, passed, exceeded, and so on.

The term “substantially” as used herein is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and furthermore refers without limitation to being largely but not necessarily wholly that which is specified.

The term “host” as used herein is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and furthermore refers without limitation to mammals, particularly humans.

The term “continuous analyte (or glucose) sensor” as used herein is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and furthermore refers without limitation to a device that continuously or continually measures a concentration of an analyte, for example, at time intervals ranging from fractions of a second up to, for example, 1, 2, or 5 minutes, or longer. In one exemplary embodiment, the continuous analyte sensor is a glucose sensor such as described in U.S. Pat. No. 6,001,067, which is incorporated herein by reference in its entirety.

The term “sensing membrane” as used herein is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and furthermore refers without limitation to a permeable or semi-permeable membrane that can be comprised of two or more domains and is typically constructed of materials of a few microns thickness or more, which are permeable to oxygen and may or may not be permeable to glucose. In one example, the sensing membrane comprises an immobilized glucose oxidase enzyme, which enables an electrochemical reaction to occur to measure a concentration of glucose.

The term “sensor data,” as used herein is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and furthermore refers without limitation to any data associated with a sensor, such as a continuous analyte sensor. Sensor data includes a raw data stream, or simply data stream, of analog or digital signals directly related to a measured analyte from an analyte sensor (or other signal received from another sensor), as well as calibrated and/or filtered raw data. In one example, the sensor data comprises digital data in “counts” converted by an A/D converter from an analog signal (e.g., voltage or amps) and includes one or more data points

16

representative of a glucose concentration. Thus, the terms “sensor data point” and “data point” refer generally to a digital representation of sensor data at a particular time. The terms broadly encompass a plurality of time spaced data points from a sensor, such as from a substantially continuous glucose sensor, which comprises individual measurements taken at time intervals ranging from fractions of a second up to, e.g., 1, 2, or 5 minutes or longer. In another example, the sensor data includes an integrated digital value representative of one or more data points averaged over a time period. Sensor data may include calibrated data, smoothed data, filtered data, transformed data, and/or any other data associated with a sensor.

The term “sensor electronics,” as used herein, is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to the components (for example, hardware and/or software) of a device configured to process data. As described in further detail hereinafter (see, e.g., FIG. 2) “sensor electronics” may be arranged and configured to measure, convert, store, transmit, communicate, and/or retrieve sensor data associated with an analyte sensor.

The terms “sensitivity” or “sensor sensitivity,” as used herein, are broad terms, and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refer without limitation to an amount of signal produced by a certain concentration of a measured analyte, or a measured species (e.g., H<sub>2</sub>O<sub>2</sub>) associated with the measured analyte (e.g., glucose). For example, in one embodiment, a sensor has a sensitivity from about 1 to about 300 pA/mg of current for every 1 mg/dL of glucose analyte.

The term “sample,” as used herein, is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and it is not to be limited to a special or customized meaning), and refers without limitation to a sample of a host body, for example, body fluids, including, blood, serum, plasma, interstitial fluid, cerebral spinal fluid, lymph fluid, ocular fluid, saliva, oral fluid, urine, excretions, or exudates.

The term “distal to,” as used herein, is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to the spatial relationship between various elements in comparison to a particular point of reference. In general, the term indicates an element is located relatively far from the reference point than another element.

The term “proximal to,” as used herein, is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to the spatial relationship between various elements in comparison to a particular point of reference. In general, the term indicates an element is located relatively near to the reference point than another element.

The terms “electrical connection” and “electrical contact,” as used herein, are broad terms, and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and refer without limitation to any connection between two electrical conductors known to those in the art. In one embodiment, electrodes are in electrical connection with (e.g., electrically connected to) the electronic circuitry of a device. In another embodiment

two materials, such as but not limited to two metals, can be in electrical contact with each other, such that an electrical current can pass from one of the two materials to the other material and/or an electrical potential can be applied.

The term “elongated conductive body,” as used herein, is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an elongated body formed at least in part of a conductive material and includes any number of coatings that may be formed thereon. By way of example, an “elongated conductive body” may mean a bare elongated conductive core (e.g., a metal wire), an elongated conductive core coated with one, two, three, four, five, or more layers of material, each of which may or may not be conductive, or an elongated non-conductive core with conductive coatings, traces, and/or electrodes thereon and coated with one, two, three, four, five, or more layers of material, each of which may or may not be conductive.

The term “ex vivo portion,” as used herein, is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a portion of a device (for example, a sensor) adapted to remain and/or exist outside of a living body of a host.

The term “in vivo portion,” as used herein, is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a portion of a device (for example, a sensor) adapted for insertion into and/or existence within a living body of a host.

The term “potentiostat,” as used herein, is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an electronic instrument that controls the electrical potential between the working and reference electrodes at one or more preset values.

The term “processor module,” as used herein, is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and refers without limitation to a computer system, state machine, processor, components thereof, and the like designed to perform arithmetic or logic operations using logic circuitry that responds to and processes the basic instructions that drive a computer.

The term “sensor session,” as used herein, is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a period of time a sensor is in use, such as but not limited to a period of time starting at the time the sensor is implanted (e.g., by the host) to removal of the sensor (e.g., removal of the sensor from the host’s body and/or removal of (e.g., disconnection from) system electronics).

The terms “substantial” and “substantially,” as used herein, are broad terms, and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and refer without limitation to a sufficient amount that provides a desired function.

“Coaxial two conductor wire based sensor”: A round wire sensor consisting of a conductive center core, an insulating

middle layer and a conductive outer layer with the conductive layers exposed at one end for electrical contact.

“Pre-connected sensor”: A sensor that has a “sensor interconnect/interposer/sensor carrier” attached to it. Therefore this “Pre-connected sensor” consists of two parts that are joined: the sensor itself, and the interconnect/interposer/sensor carrier. The term “pre-connected sensor” unit refers to the unit that is formed by the permanent union of these two distinct parts.

Other definitions will be provided within the description below, and in some cases from the context of the term’s usage.

As employed herein, the following abbreviations apply: Eq and Eqs (equivalents); mEq (milliequivalents); M (molar); mM (millimolar)  $\mu$ M (micromolar); N (Normal); mol (moles); mmol (millimoles);  $\mu$ mol (micromoles); nmol (nanomoles); g (grams); mg (milligrams);  $\mu$ g (micrograms); Kg (kilograms); L (liters); mL (milliliters); dL (deciliters);  $\mu$ L (microliters); cm (centimeters); mm (millimeters);  $\mu$ m (micrometers); nm (nanometers); h and hr (hours); min. (minutes); s and sec. (seconds); ° C. (degrees Centigrade) ° F. (degrees Fahrenheit), Pa (Pascals), kPa (kilopascals), MPa (megapascals), GPa (gigapascals), Psi (pounds per square inch), kPsi (kilopounds per square inch).

#### Overview/General Description of System

In vivo analyte sensing technology may rely on in vivo sensors. In vivo sensors may include an elongated conductive body having one or more electrodes such as a working electrode and a reference electrode.

For example, a platinum metal-clad, tantalum wire is sometimes used as a core bare sensing element with one or more reference or counter electrodes for an analyte sensor. This sensing element is coated in membranes to yield the final sensor.

Described herein are pre-connected sensors that include an analyte sensor attached to a sensor carrier (also referred to herein as a “sensor interposer”). The analyte sensor may include a working electrode and a reference electrode at a distal end of an elongated conductive body. The sensor carrier may include a substrate, one or more electrical contacts coupled to one or more electrical contacts of the sensor, and circuitry such as one or more additional or external electrical contacts for coupling the one or more electrical contacts that are coupled to the sensor contact(s) to external equipment such as a membrane dip coating station, a testing station, a calibration station, or sensor electronics of a wearable device. In some embodiments, the substrate can be referred to as an intermediate body.

The following description and examples described the present embodiments with reference to the drawings. In the drawings, reference numbers label elements of the present embodiments. These reference numbers are reproduced below in connection with the discussion of the corresponding drawing features.

#### Sensor System

FIG. 1 depicts an example system 100, in accordance with some example implementations. The system 100 includes an analyte sensor system 101 including sensor electronics 112 and an analyte sensor 138. The system 100 may include other devices and/or sensors, such as medicament delivery pump 102 and glucose meter 104. The analyte sensor 138 may be physically connected to sensor electronics 112 and may be integral with (e.g., non-releasably attached to) or releasably attachable to the sensor electronics. For example, continuous analyte sensor 138 may be connected to sensor electronics 112 via a sensor carrier that mechanically and electrically interfaces the analyte sensor 138 with the sensor

19

electronics. The sensor electronics **112**, medicament delivery pump **102**, and/or glucose meter **104** may couple with one or more devices, such as display devices **114**, **116**, **118**, and/or **120**.

In some example implementations, the system **100** may include a cloud-based analyte processor **490** configured to analyze analyte data (and/or other patient-related data) provided via network **409** (e.g., via wired, wireless, or a combination thereof) from sensor system **101** and other devices, such as display devices **114**, **116**, **118**, and/or **120** and the like, associated with the host (also referred to as a patient) and generate reports providing high-level information, such as statistics, regarding the measured analyte over a certain time frame. A full discussion of using a cloud-based analyte processing system may be found in U.S. patent application Ser. No. 13/788,375, entitled "Cloud-Based Processing of Analyte Data" and filed on Mar. 7, 2013, published as U.S. Patent Application Publication 2013/0325352, herein incorporated by reference in its entirety. In some implementations, one or more steps of the factory calibration algorithm can be performed in the cloud.

In some example implementations, the sensor electronics **112** may include electronic circuitry associated with measuring and processing data generated by the analyte sensor **138**. This generated analyte sensor data may also include algorithms, which can be used to process and calibrate the analyte sensor data, although these algorithms may be provided in other ways as well. The sensor electronics **112** may include hardware, firmware, software, or a combination thereof, to provide measurement of levels of the analyte via an analyte sensor, such as a glucose sensor. An example implementation of the sensor electronics **112** is described further below with respect to FIG. 2.

In one implementation, the factory calibration algorithms described herein may be performed by the sensor electronics.

The sensor electronics **112** may, as noted, couple (e.g., wirelessly and the like) with one or more devices, such as display devices **114**, **116**, **118**, and/or **120**. The display devices **114**, **116**, **118**, and/or **120** may be configured for presenting information (and/or alarming), such as sensor information transmitted by the sensor electronics **112** for display at the display devices **114**, **116**, **118**, and/or **120**.

In one implementation, the factory calibration algorithms described herein may be performed at least in part by the display devices.

In some example implementations, the relatively small, key fob-like display device **114** may comprise a wrist watch, a belt, a necklace, a pendant, a piece of jewelry, an adhesive patch, a pager, a key fob, a plastic card (e.g., credit card), an identification (ID) card, and/or the like. This small display device **114** may include a relatively small display (e.g., smaller than the large display device **116**) and may be configured to display certain types of displayable sensor information, such as a numerical value, and an arrow, or a color code.

In some example implementations, the relatively large, hand-held display device **116** may comprise a hand-held receiver device, a palm-top computer, and/or the like. This large display device may include a relatively larger display (e.g., larger than the small display device **114**) and may be configured to display information, such as a graphical representation of the sensor data including current and historic sensor data output by sensor system **100**.

In some example implementations, the analyte sensor **138** may comprise a glucose sensor configured to measure glucose in the blood or interstitial fluid using one or more

20

measurement techniques, such as enzymatic, chemical, physical, electrochemical, spectrophotometric, polarimetric, calorimetric, iontophoretic, radiometric, immunochemical, and the like. In implementations in which the analyte sensor **138** includes a glucose sensor, the glucose sensor may comprise any device capable of measuring the concentration of glucose and may use a variety of techniques to measure glucose including invasive, minimally invasive, and non-invasive sensing techniques (e.g., fluorescence monitoring), to provide data, such as a data stream, indicative of the concentration of glucose in a host. The data stream may be sensor data (raw and/or filtered), which may be converted into a calibrated data stream used to provide a value of glucose to a host, such as a user, a patient, or a caretaker (e.g., a parent, a relative, a guardian, a teacher, a doctor, a nurse, or any other individual that has an interest in the wellbeing of the host). Moreover, the analyte sensor **138** may be implanted as at least one of the following types of analyte sensors: an implantable glucose sensor, a transcutaneous glucose sensor, implanted in a host vessel or extracorporeally, a subcutaneous sensor, a refillable subcutaneous sensor, an intravascular sensor.

Although the disclosure herein refers to some implementations that include an analyte sensor **138** comprising a glucose sensor, the analyte sensor **138** may comprise other types of analyte sensors as well. Moreover, although some implementations refer to the glucose sensor as an implantable glucose sensor, other types of devices capable of detecting a concentration of glucose and providing an output signal representative of glucose concentration may be used as well. Furthermore, although the description herein refers to glucose as the analyte being measured, processed, and the like, other analytes may be used as well including, for example, ketone bodies (e.g., acetone, acetoacetic acid and beta hydroxybutyric acid, lactate, etc.), glucagon, acetyl-CoA, triglycerides, fatty acids, intermediaries in the citric acid cycle, choline, insulin, cortisol, testosterone, and the like.

In some manufacturing systems, sensors **138** are manually sorted, placed and held in fixtures. These fixtures are manually moved from station to station during manufacturing for various process steps including interfacing electrical measurement equipment for testing and calibration operations. However, manual handling of sensors can be inefficient, can cause delays due to non-ideal mechanical and electrical connections, and can risk damage to the sensor and/or testing and calibration equipment and can induce sensor variability that can lead to inaccurate verification data being collected in manufacturing. In addition, the process of packaging sensor **138** with the sensor electronics **112** into a wearable device involves further manual manipulation of the sensor that can damage the sensor **138**.

Various systems, devices, and methods described herein help to reduce or eliminate manual interaction with a sensor. For example, a pre-connected sensor may be provided that includes a sensor interconnect or sensor carrier electrically coupled to sensor electrodes and having mechanical and electrical features configured to accurately interface with wearable electronics, automation equipment and/or robustly connect to measurement equipment.

Identification and other data associated with each sensor may be stored on the sensor carrier for logging and tracking of each sensor during manufacturing, testing, calibration, and in vivo operations. Following testing and calibration operations, the sensor carrier may be used to connect the

21

sensor to sensor electronics of a wearable device, such as an on-skin sensor assembly, in an arrangement that is sealed and electrically robust.

FIG. 2 depicts an example of electronics **112** that may be used in sensor electronics **112** or may be implemented in a manufacturing station such as a testing station, a calibration station, a smart carrier, or other equipment used during manufacturing of device **101**, in accordance with some example implementations. The sensor electronics **112** may include electronics components that are configured to process sensor information, such as sensor data, and generate transformed sensor data and displayable sensor information, e.g., via a processor module. For example, the processor module may transform sensor data into one or more of the following: filtered sensor data (e.g., one or more filtered analyte concentration values), raw sensor data, calibrated sensor data (e.g., one or more calibrated analyte concentration values), rate of change information, trend information, rate of acceleration/deceleration information, sensor diagnostic information, location information, alarm/alert information, calibration information such as may be determined by factory calibration algorithms as disclosed herein, smoothing and/or filtering algorithms of sensor data, and/or the like.

In some embodiments, a processor module **214** is configured to achieve a substantial portion, if not all, of the data processing, including data processing pertaining to factory calibration. Processor module **214** may be integral to sensor electronics **112** and/or may be located remotely, such as in one or more of devices **114**, **116**, **118**, and/or **120** and/or cloud **490**. For example, in some embodiments, processor module **214** may be located at least partially within a cloud-based analyte processor **490** or elsewhere in network **409**.

In some example implementations, the processor module **214** may be configured to calibrate the sensor data, and the data storage memory **220** may store the calibrated sensor data points as transformed sensor data. Moreover, the processor module **214** may be configured, in some example implementations, to wirelessly receive calibration information from a display device, such as devices **114**, **116**, **118**, and/or **120**, to enable calibration of the sensor data from sensor **138**. Furthermore, the processor module **214** may be configured to perform additional algorithmic processing on the sensor data (e.g., calibrated and/or filtered data and/or other sensor information), and the data storage memory **220** may be configured to store the transformed sensor data and/or sensor diagnostic information associated with the algorithms. The processor module **214** may further be configured to store and use calibration information determined from a factory calibration, as described below.

In some example implementations, the sensor electronics **112** may comprise an application-specific integrated circuit (ASIC) **205** coupled to a user interface **222**. The ASIC **205** may further include a potentiostat **210**, a telemetry module **232** for transmitting data from the sensor electronics **112** to one or more devices, such as devices **114**, **116**, **118**, and/or **120**, and/or other components for signal processing and data storage (e.g., processor module **214** and data storage memory **220**). Although FIG. 2 depicts ASIC **205**, other types of circuitry may be used as well, including field programmable gate arrays (FPGA), one or more microprocessors configured to provide some (if not all of) the processing performed by the sensor electronics **112**, analog circuitry, digital circuitry, or a combination thereof.

In the example depicted in FIG. 2, through a first input port **211** for sensor data the potentiostat **210** is coupled to an

22

analyte sensor **138**, such as a glucose sensor to generate sensor data from the analyte. The potentiostat **210** may be coupled to a working electrode **211** and reference electrode **212** that form a part of the sensor **138**. The potentiostat may provide a voltage to one of the electrodes **211**, **212** of the analyte sensor **138** to bias the sensor for measurement of a value (e.g., a current) indicative of the analyte concentration in a host (also referred to as the analog portion of the sensor). The potentiostat **210** may have one or more connections to the sensor **138** depending on the number of electrodes incorporated into the analyte sensor **138** (such as a counter electrode as a third electrode).

In some example implementations, the potentiostat **210** may include a resistor that translates a current value from the sensor **138** into a voltage value, while in some example implementations, a current-to-frequency converter (not shown) may also be configured to integrate continuously a measured current value from the sensor **138** using, for example, a charge-counting device. In some example implementations, an analog-to-digital converter (not shown) may digitize the analog signal from the sensor **138** into so-called "counts" to allow processing by the processor module **214**. The resulting counts may be directly related to the current measured by the potentiostat **210**, which may be directly related to an analyte level, such as a glucose level, in the host.

The telemetry module **232** may be operably connected to processor module **214** and may provide the hardware, firmware, and/or software that enable wireless communication between the sensor electronics **112** and one or more other devices, such as display devices, processors, network access devices, and the like. A variety of wireless radio technologies that can be implemented in the telemetry module **232** include Bluetooth, Bluetooth Low-Energy, ANT, ANT+, ZigBee, IEEE 802.11, IEEE 802.16, cellular radio access technologies, radio frequency (RF), infrared (IR), paging network communication, magnetic induction, satellite data communication, spread spectrum communication, frequency hopping communication, near field communications, and/or the like. In some example implementations, the telemetry module **232** comprises a Bluetooth chip, although Bluetooth technology may also be implemented in a combination of the telemetry module **232** and the processor module **214**.

The processor module **214** may control the processing performed by the sensor electronics **112**. For example, the processor module **214** may be configured to process data (e.g., counts), from the sensor, filter the data, calibrate the data, perform fail-safe checking, and/or the like.

Potentiostat **210** may measure the analyte (e.g., glucose and/or the like) at discrete time intervals or continuously, for example, using a current-to-voltage or current-to-frequency converter.

The processor module **214** may further include a data generator (not shown) configured to generate data packages for transmission to devices, such as the display devices **114**, **116**, **118**, and/or **120**. Furthermore, the processor module **214** may generate data packets for transmission to these outside sources via telemetry module **232**. In some example implementations, the data packages may include an identifier code for the sensor and/or sensor electronics **112**, raw data, filtered data, calibrated data, rate of change information, trend information, error detection or correction, and/or the like.

The processor module **214** may also include a program memory **216** and other memory **218**. The processor module **214** may be coupled to a communications interface, such as

23

a communication port **238**, and a source of power, such as a battery **234**. Moreover, the battery **234** may be further coupled to a battery charger and/or regulator **236** to provide power to sensor electronics **112** and/or charge the battery **234**.

The program memory **216** may be implemented as a semi-static memory for storing data, such as an identifier for a coupled sensor **138** (e.g., a sensor identifier (ID)) and for storing code (also referred to as program code) to configure the ASIC **205** to perform one or more of the operations/functions described herein. For example, the program code may configure processor module **214** to process data streams or counts, filter, perform the calibration methods described below, perform fail-safe checking, and the like.

The memory **218** may also be used to store information. For example, the processor module **214** including memory **218** may be used as the system's cache memory, where temporary storage is provided for recent sensor data received from the sensor. In some example implementations, the memory may comprise memory storage components, such as read-only memory (ROM), random-access memory (RAM), dynamic-RAM, static-RAM, non-static RAM, electrically erasable programmable read only memory (EEPROM), rewritable ROMs, flash memory, and the like.

The data storage memory **220** may be coupled to the processor module **214** and may be configured to store a variety of sensor information. In some example implementations, the data storage memory **220** stores one or more days of analyte sensor data. The stored sensor information may include one or more of the following: a time stamp, raw sensor data (one or more raw analyte concentration values), calibrated data, filtered data, transformed sensor data, and/or any other displayable sensor information, calibration information (e.g., reference BG values and/or prior calibration information such as from factory calibration), sensor diagnostic information, and the like.

The user interface **222** may include a variety of interfaces, such as one or more buttons **224**, a liquid crystal display (LCD) **226**, a vibrator **228**, an audio transducer (e.g., speaker) **230**, a backlight (not shown), and/or the like. The components that comprise the user interface **222** may provide controls to interact with the user (e.g., the host).

The battery **234** may be operatively connected to the processor module **214** (and possibly other components of the sensor electronics **112**) and provide the necessary power for the sensor electronics **112**. In other implementations, the receiver can be transcutaneously powered via an inductive coupling, for example.

A battery charger and/or regulator **236** may be configured to receive energy from an internal and/or external charger. In some example implementations, the battery **234** (or batteries) is configured to be charged via an inductive and/or wireless charging pad, although any other charging and/or power mechanism may be used as well.

One or more communication ports **238**, also referred to as external connector(s), may be provided to allow communication with other devices, for example a PC communication (com) port can be provided to enable communication with systems that are separate from, or integral with, the sensor electronics **112**. The communication port, for example, may comprise a serial (e.g., universal serial bus or "USB") communication port, and allow for communicating with another computer system (e.g., PC, personal digital assistant or "PDA," server, or the like). In some example implementations, factory information may be sent to the algorithm from the sensor or from a cloud data source.

24

The one or more communication ports **238** may further include an input port **237** in which calibration data may be received, and an output port **239** which may be employed to transmit calibrated data, or data to be calibrated, to a receiver or mobile device. FIG. 2 illustrates these aspects schematically. It will be understood that the ports may be separated physically, but in alternative implementations a single communication port may provide the functions of both the second input port and the output port.

In some analyte sensor systems, an on-skin portion of the sensor electronics may be simplified to minimize complexity and/or size of on-skin electronics, for example, providing only raw, calibrated, and/or filtered data to a display device configured to run calibration and other algorithms required for displaying the sensor data. However, the sensor electronics **112** (e.g., via processor module **214**) may be implemented to execute prospective algorithms used to generate transformed sensor data and/or displayable sensor information, including, for example, algorithms that: evaluate a clinical acceptability of reference and/or sensor data, evaluate calibration data for best calibration based on inclusion criteria, evaluate a quality of the calibration, compare estimated analyte values with time corresponding measured analyte values, analyze a variation of estimated analyte values, evaluate a stability of the sensor and/or sensor data, detect signal artifacts (noise), replace signal artifacts, determine a rate of change and/or trend of the sensor data, perform dynamic and intelligent analyte value estimation, perform diagnostics on the sensor and/or sensor data, set modes of operation, evaluate the data for aberrancies, and/or the like.

FIGS. 3A, 3B, and 3C illustrate an exemplary implementation of analyte sensor system **101** implemented as a wearable device such as an on-skin sensor assembly **600**. As shown in FIG. 3, on-skin sensor assembly comprises a housing **128**. An adhesive patch **126** can couple the housing **128** to the skin of the host. The adhesive **126** can be a pressure sensitive adhesive (e.g. acrylic, rubber based, or other suitable type) bonded to a carrier substrate (e.g., spun lace polyester, polyurethane film, or other suitable type) for skin attachment. The housing **128** may include a through-hole **180** that cooperates with a sensor inserter device (not shown) that is used for implanting the sensor **138** under the skin of a subject.

The wearable sensor assembly **600** can include sensor electronics **112** operable to measure and/or analyze glucose indicators sensed by glucose sensor **138**. Sensor electronics **112** within sensor assembly **600** can transmit information (e.g., measurements, analyte data, and glucose data) to a remotely located device (e.g., **114**, **116**, **118**, **120** shown in FIG. 1). As shown in FIG. 3C, in this implementation the sensor **138** extends from its distal end up into the through-hole **180** and is routed to an electronics module **135** inside the enclosure **128**. The working electrode **211** and reference electrode **212** are connected to circuitry in the electronics module **135** which includes the potentiostat.

FIG. 3D illustrates one exemplary embodiment of an analyte sensor **138** which includes an elongated body portion. The elongated body portion may be long and thin, yet flexible and strong. For example, in some embodiments, the smallest dimension of the elongated conductive body is less than about 0.1 inches, 0.075 inches, 0.05 inches, 0.025 inches, 0.01 inches, 0.004 inches, or 0.002 inches. While the elongated conductive body is illustrated herein as having a circular cross-section, in other embodiments the cross-section of the elongated conductive body can be ovoid, rect-



25

angular, triangular, or polyhedral, star-shaped, C-shaped, T-shaped, X-shaped, Y-shaped, irregular, or the like.

In the implementation of FIG. 3D, the analyte sensor 138 comprises a wire core 139. At a distal, in vivo portion of the sensor 138, the wire core 139 forms an electrode 211a. At a proximal, ex vivo portion of the sensor 138, the wire core 139 forms a contact 211b. The electrode 211a and the contact 211b are in electrical communication over the length of the wire core 139 as it extends along the elongated body portion of the sensor 138. The wire core can be made from a single material such as platinum or tantalum, or may be formed as multiple layers, such as a conducting or non-conducting material with an outer coating of a different conducting material.

A layer 104 surrounds a least a portion of the wire core 139. The layer 104 may be formed of an insulating material, such as polyimide, polyurethane, parylene, or any other known insulating materials. For example, in one embodiment the layer 104 is disposed on the wire core 139 and configured such that the electrode 211a is exposed via window 106.

In some embodiments, the sensor 138 further comprises a layer 141 surrounding the insulating layer 104 like a sleeve that comprises a conductive material. At a distal, in vivo portion of the sensor 138, the sleeve layer 141 forms an electrode 212a. At a proximal, ex vivo portion of the sensor 138, the sleeve layer 141 forms a contact 212b. The electrode 212a and the contact 212b are in electrical communication over the length of the sleeve layer 141 as it extends along the elongated body portion of the sensor 138. This sleeve layer 141 may be formed of a silver-containing material that is applied onto the insulating layer 104. The silver-containing material may include any of a variety of materials and be in various forms, such as, Ag/AgCl-polymer pastes, paints, polymer-based conducting mixture, and/or inks that are commercially available, for example. This layer 141 can be processed using a pasting/dipping/coating step, for example, using a die-metered dip coating process. In one exemplary embodiment, an Ag/AgCl polymer paste is applied to an elongated body by dip-coating the body (e.g., using a meniscus coating technique) and then drawing the body through a die to meter the coating to a precise thickness. In some embodiments, multiple coating steps are used to build up the coating to a predetermined thickness.

The sensor 138 shown in FIG. 3D also includes a membrane 108 covering at least a portion of the distal in vivo portion of the sensor 138. This membrane is typically formed of multiple layers, which may include one or more of an interference domain, an enzyme domain, a diffusion resistance domain, and a bioprotective domain. This membrane is important to support the electrochemical processes that allow analyte detection and it is generally manufactured with great care by dip-coating, spraying, or other manufacturing steps. It is preferable for the distal in vivo portion of the sensor 138 to be subject to as little handling as possible from the time the membrane 108 is formed to the time the distal in vivo portion of the sensor 138 is implanted into a subject. In some embodiments, electrode 211a forms a working electrode of an electrochemical measuring system, and electrode 212a forms a reference electrode for that system. In use, both electrodes may be implanted into a host for analyte monitoring.

Although the above description is applicable specifically to a coaxial wire type structure, the embodiments herein are also applicable to other physical configurations of electrodes. For example, the two electrodes 211a and 212a could

26

be affixed to a distal in vivo portion of an elongated flexible strip of a planar substrate such as a thin, flat, polymer flex circuit. The two contacts 211b and 212b could be affixed to the proximal ex vivo portion of this flexible planar substrate. Electrodes 211a, 212a could be electrically connected to their respective contacts 211b, 212b a circuit traces on the planar substrate. In this case, the electrodes 211a and 212a and the contacts 211b and 212b may be adjacent to one another on a flat surface rather than being coaxial as shown in FIG. 3D.

Also shown in FIG. 3D is an illustration of the contact 211b and the contact 212b electrically coupled to a simple current-to-voltage converter based potentiostat 210. The potentiostat includes a battery 320 that has an output coupled to an input of an operational amplifier 322. The output of the operational amplifier 322 is coupled to a contact 324 that is electrically coupled to the working electrode contact 211b through a resistor 328. The amplifier 322 will bias the contact 324 to the battery voltage  $V_b$ , and will drive the current  $i_m$  required to maintain that bias. This current will flow from the working electrode 211a through the interstitial fluid surrounding the sensor 138 and to the reference electrode 212a. The reference electrode contact 212b is electrically coupled to another contact 334 which is connected to the other side of the battery 320. For this circuit, the current  $i_m$  is equal to  $(V_b - V_m)/R$ , where  $V_m$  is the voltage measured at the output of the amplifier 322. The magnitude of this current for a given bias on the working electrode 211a is a measure of analyte concentration in the vicinity of the window 106.

The contacts 324 and 334 are typically conductive pads/traces on a circuit board. There is always some level of parasitic leakage current  $i_p$  over the surface of this board during the test. If possible, this leakage current should not form part of the measurement of current due to analyte. To reduce the effect this leakage current has on the measured current, an optional additional pad/trace 336 may be provided between the biased contact 324 and the return contact 334 that is connected directly to the battery output. This optional additional pad/trace may be referred to as a "guard trace." Because they are held at the same potential, there will be essentially no leakage current from the biased contact 324 and the guard trace 336. Furthermore, leakage current from the guard trace 336 to the return contact 334 does not pass through the amplifier output resistor 328, and therefore is not included in the measurement. Additional aspects and implementations of a guard trace may be found in paragraphs [0128] and [0129] of U.S. Patent Publication 2017/0281092, which are incorporated herein by reference.

During manufacturing, various coating, testing, calibration, and assembly operations are performed on the sensor 138. However, it can be difficult to transport individual sensors and electrically interface the sensors with multiple testing and calibration equipment installations. These processes also subject the sensors to damage from handling. To help address these issues, the sensor 138 may be provided as a part of a pre-connected sensor that includes a sensor carrier as described in greater detail below.

FIG. 4A shows a schematic illustration of a pre-connected sensor 400. As shown in FIG. 4A, pre-connected sensor 400 includes sensor carrier 402 permanently attached to sensor 138. In the example of FIG. 4A, sensor carrier 402 includes an intermediate body such as substrate 404, and also includes one or more contacts such as first internal contact 406, and second internal contact 408. First internal contact 406 is electrically coupled to a first contact on a proximal end of sensor 138 and contact internal contact 408 is

27

electrically coupled to a second contact on the proximal end of sensor 138. The distal end of sensor 138 is a free end configured for insertion into the skin of the host. Contacts 406 and 408 may, for example, correspond to contacts 324 and 334 of FIG. 3D in some implementations.

As shown in FIG. 4A, first internal contact 406 may be electrically coupled to a first external contact 410 and second internal contact 408 may be electrically coupled to a second external contact 412. As described in further detail hereinafter, external contacts 410 and 412 may be configured to electrically interface with sensor electronics 112 in wearable device 600. Furthermore, external contacts 410 and 412 may be configured to electrically interface with processing circuitry of manufacturing equipment such one or more testing stations and/or one or more calibration stations. Although various examples are described herein in which two external contacts 410 and 412 on the sensor carrier are coupled to two corresponding contacts on sensor 138, this is merely illustrative. In other implementations, sensor carrier 402 and sensor 138 may each be provided with a single contact or may each be provided with more than two contacts, for example, any N number of external contacts (e.g., more than two external contacts 410 and 412) of the sensor carrier and any M number of contacts (e.g., more than two contacts 406 and 408) of sensor 138 that can be coupled. In some implementations, sensor carrier 402 and sensor 138 may have the same number of contacts (i.e.,  $N=M$ ). In some implementations, sensor carrier 402 and sensor 138 may have a different number of contacts (i.e.,  $N \neq M$ ). For example, in some implementations, sensor carrier 402 may have additional contacts for coupling to or between various components of a manufacturing station.

As described in further detail hereinafter, substrate 404 may be configured to couple with sensor electronics 112 in wearable device 600. In some embodiments, substrate 404 may be sized and shaped to mechanically interface with housing 128 and electrically interface with sensor electronics 112 inside housing 128. Further, substrate 404 may be sized and shaped to mechanically interface with manufacturing equipment, assembly equipment, testing stations and/or one or more calibration stations. As described in further detail hereinafter, sensor carrier 402 may be attached and/or electrically coupled to sensor 138. Sensor 138 may be permanently coupled to a component of sensor carrier 402 (e.g. substrate 404) by using, for example, adhesive (e.g. UV cure, moisture cure, multi part activated, heat cure, hot melt, etc.), including conductive adhesive (e.g. carbon filled, carbon nanotube filled, silver filled, conductive additive, etc.), conductive ink, spring contacts, clips, wrapped flexible circuitry, a conductive polymer (e.g. conductive elastomer, conductive plastic, carbon filled PLA, conductive graphene PLA), conductive foam, conductive fabric, a barrel connector, a molded interconnect device structure, sewing, wire wrapping, wire bonding, wire threading, spot welding, swaging, crimping, stapling, clipping, soldering or brazing, plastic welding, or overmolding. In some embodiments, sensor 138 may be permanently coupled to substrate 404 by rivets, magnets, anisotropic conductive films, metallic foils, or other suitable structures or materials for mechanically and electrically attaching sensor carrier 402 to sensor 138 before or during assembly, manufacturing, testing and/or calibration operations. In some embodiments, sensor carrier 402 may be 3-D printed around sensor 138 to form pre-connected sensor 400. Additionally, sensor carrier 402 may include datum features 430 (sometimes referred to as datum structures) such as a recess, an opening, a surface or a protrusion for aligning, positioning, and orienting sensor

28

138 relative to sensor carrier 402. Sensor carrier 402 may also include, or may itself form, one or more anchoring features for securing and aligning the analyte sensor during manufacturing (e.g., relative to a manufacturing station). Additionally, sensor carrier 402 may include an identifier 450 configured to identify the sensor. In some embodiments, identifier 450 is formed on substrate 404. Identifier 450 will be explained further below.

FIG. 4B illustrates another schematic of a pre-connected analyte sensor 400. The pre-connected analyte sensor 400 shown in FIG. 4B may include similar components of pre-connected analyte sensor 400 shown in FIG. 4A. FIG. 4B is shown without optional cover 460 for clarity. FIG. 4C illustrated an exploded view of pre-connected analyte sensor 400 shown in FIG. 4B.

In the example of FIG. 4B, sensor carrier 402 includes an intermediate body such as a substrate 404, and also includes one or more traces such as first trace 414 and second trace 416. First trace 414 may include a first internal contact 406 and a first external contact 410. Second trace 416 may include a second internal contact 408 and a second external contact 412. In some embodiments, first internal contact 406 is electrically coupled to a first contact on a proximal end of sensor 138 and second internal contact 408 is electrically coupled to a second contact on the proximal end of sensor 138. The distal end of sensor 138 is a free end configured for insertion into the skin of the host. The electrical coupling is described in connection with various embodiments herein, such as clips, conductive adhesive, conductive polymer, conductive ink, metallic foil, conductive foam, conductive fabric, wire wrapping, wire threading or any other suitable methods. In some embodiments, a non-conductive adhesive 426 (e.g. epoxy, cyanoacrylate, acrylic, rubber, urethane, hot melt, etc.) can be used to attach the sensor 138 to substrate 404. Non-conductive adhesive 426 may be configured to affix, seal, insulate, or provide a strain relief to the sensor 138. Sensor 138 may be attached to substrate 404 by other methods, such as those described in FIG. 4A above.

As shown in FIG. 4C, a pressure sensitive adhesive 428 may be configured to isolate an exposed end of traces 414 and 416. For instance, pressure sensitive adhesive 428 may laminate sensor 138 between substrate 404 and cover 460. In such instances, sensor 138, substrate 404, pressure sensitive adhesive 428, and cover 460 may form a laminated configuration. In the laminated configuration, sensor 138 and its connection to one or more contacts (e.g. first internal contact 406 and second internal contact 408) are isolated from one or more exposed contacts (e.g. first external contact 410 and second external contact 412). Furthermore, the laminated configuration may create a moisture sealed region surrounding the sensor 138. The moisture seal may be created as embodied by a combination of a pressure sensitive adhesive 428 and a non-conductive adhesive 426. In other embodiments, the laminated structure can be created by one or a combination of the following materials and methods: A non-conductive adhesive, a pressure sensitive adhesive tape, an elastomer, heat bonding, hot plate welding, laser welding, ultrasonic welding, RF welding, or any suitable type of lamination method. The cover 460 may consist of a polymer sheet, structure, or film that at least partially covers the substrate 404. The cover 460 may optionally contain an identifier 450, which can identify the sensor 138. In some embodiments, identifier 450 may incorporate various identification protocols or techniques such as, but not limited to, NFC, RFID, QR Code, Bar code, Wi-Fi, Trimmed resistor, Capacitive value, Impedance values, ROM, Memory, IC, Flash memory, etc.

29

Guide fixture **420**, which is an optional component, is an exemplary embodiment of an interface with a work station, such as a testing station, a calibration station, an assembly station, a coating station, manufacturing stations, or as part of the wearable assembly. The guide fixture **420** includes datum features (or datum structures) **430**, such as a recess, an opening, a surface or a protrusion for aligning, positioning, and orienting sensor **138** relative to sensor carrier **402**. Datum features **430** may be used in manufacturing and for assembly into a wearable electronic component. In some embodiments, datum features **430** are raised protrusions configured to align with corresponding datum features **432** of substrate **404**. Corresponding datum features **432** of substrate **404** may feature cutouts, slots, holes, or recesses. The corresponding datum features **432** in the sensor carrier may be placement features that can interface with datum features **430** in a work station, such as a testing station, a calibration station, an assembly station, a coating station, or other manufacturing stations. Guide fixture **420** may be configured to ensure proper placement of the sensor carrier **402** to align the exposed external contacts **410** and **412** for connecting to a work station, such as a testing station, a calibration station, an assembly station, a coating station, or other manufacturing stations. In other embodiments, datum features **430** may consist of female features to engage with male corresponding datum features **432**.

FIG. 4D illustrates a schematic view of an array **480** of pre-connected analyte sensors **400** having a plurality of pre-connected sensors **400** with optional identifiers **450**. In FIG. 4D, an array formed as a one-dimensional strip of pre-connected analyte sensors **400** is shown, but a two-dimensional array could also be implanted. In some embodiments, the array **480** of pre-connected analyte sensors may be disposed in a cartridge. Each of the plurality of pre-connected sensors **400** can be singulated. In some embodiments, scoring **4020** may be provided to facilitate singulation into individual pre-connected sensors **400**. In some embodiments, the array **480** can be used in facilitating manufacturing, testing and/or calibrating multiple sensors **138** individually in sequential or random manners. In some embodiments, the array **480** can be used in facilitating manufacturing, testing and/or calibrating multiple sensors **138** concurrently.

FIGS. 5A-5E show block diagrams of various machines and assemblies the pre-connected analyte sensor **400** may be associated with during its pre-implant lifetime. Such machines and assemblies may include manufacturing equipment such as one or more manufacturing stations **5091**, one or more testing stations **5002** and/or one more calibration stations **5004**, and an on-skin wearable assembly **600**. At least some of these are configured to receive sensor carrier **402** and to communicatively couple the machines and assemblies to sensor **138** via sensor carrier **402**.

It is one aspect of some embodiments that the sensor **138** is coupled to the sensor carrier **402** before the membrane **108** described above is applied. With the sensor **138** attached to the sensor carrier, and potentially with multiple carrier mounted sensors attached together as shown in FIG. 4D, subsequent device production steps such as membrane coating, testing, calibration, and assembly into a wearable unit can be performed with easier mounting and dismounting from manufacturing and testing equipment, less sensor handling, less chance of damaging the membrane, producing a significant overall improvement in production efficiency.

Another benefit of the pre-connected sensor construction is that it is easier to separate different kinds of manufacturing and testing among different facilities that are better equipped

30

to handle them. For example, fabricating the electrodes may require various kinds of metal forming/extrusion machines, whereas membrane application, testing, and calibration requires a wet chemistry lab and sensitive electronic test equipment. Accordingly, the sensor electrodes may be formed and mounted on the carrier in one facility in one location, and then shipped to a different remote facility that is equipped for membrane application, testing, and calibration. Remote in this context means not in the same production facility in the same building. It can even be advantageous for different commercial entities to perform the different tasks that specialize in the appropriate manufacturing and testing technologies.

Manufacturing station **5091** may comprise a testing station as described herein, a calibration station as described herein, or another manufacturing station. Manufacturing station **5091** may include processing circuitry **5092** and/or mechanical components **5094** operable to perform testing operations, calibration operations, and/or other manufacturing operations such as sensor straightening operations, membrane application operations, curing operations, calibration-check operations, glucose sensitivity operations (e.g., sensitivity slope, baseline, and/or noise calibration operations), and/or visual inspection operations.

The pre-connected analyte sensor **400** may be connected to one or more testing stations **5002** having processing circuitry **5012** configured to perform testing operations with sensor **138** to verify the operational integrity of sensor **138**. Testing operations may include verifying electrical properties of a sensor **138**, verifying communication between a working electrode and contact **408**, verifying communication between a reference electrode or additional electrodes and contact **406**, and/or other electronic verification operations for sensor **138**. Processing circuitry **5012** may be communicatively coupled with sensor **138** for testing operations by inserting substrate **404** into a receptacle **5006** (e.g., a recess in a housing of testing station **5002**) until contact **410** is coupled to contact **5010** of testing station **5002** and contact **412** is coupled to contact **5008** of testing station **5002**.

System **5000** may include one or more calibration stations **5004** having processing circuitry **5020** configured to perform calibration operations with sensor **138** to obtain calibration data for in vivo operation of sensor **138**. Calibration data obtained by calibration equipment **5004** may be provided to on-skin sensor assembly **600** to be used during operation of sensor **138** in vivo. Processing circuitry **5020** may be communicatively coupled with sensor **138** for calibration operations by inserting substrate **404** into a receptacle **5014** (e.g., a recess in a housing of calibration station **5004**) until contact **410** is coupled to contact **5018** of testing station **5002** and contact **412** is coupled to contact **5016** of testing station **5002**.

In the examples of FIGS. 5A-5E, testing station **5002** and calibration station **5004** include receptacles **5006** and **5014**. However, this is merely illustrative and sensor carrier **402** may be mounted to testing station **5002** and calibration station **5004** and/or manufacturing station **5091** using other mounting features such as grasping, clipping, or clamping figures. For example, manufacturing station **5091** includes grasping structures **5093** and **5095**, at least one of which is movable to grasp sensor carrier **402** (or a carrier having multiple sensor carriers and sensors). Structure **5093** may be a stationary feature having one or more electrical contacts such as contact **5008**. Structure **5095** may be a movable feature that moves (e.g., slides in a direction **5097**) to grasp and secure sensor carrier **402** in an electrically coupled

31

position for manufacturing station **5091**. In other implementations, both features **5093** and **5095** are movable.

Sensor carrier **402** may also include an identifier **450** (see, e.g., FIGS. 4A-4D). Identifier **450** may be formed on or embedded within substrate **404**. Identifier **450** may be implemented as a visual or optical identifier (e.g., a barcode or QR code pre-printed or printed on-the-fly on substrate **404** or etched in to substrate **404**), a radio frequency (RF) identifier, or an electrical identifier (e.g., a laser-trimmed resistor, a capacitive identifier, an inductive identifier, or a micro storage circuit (e.g., an integrated circuit or other circuitry in which the identifier is encoded in memory of the identifier) programmable with an identifier and/or other data before, during, or after testing and calibration). Identifier **450** may be used for tracking each sensor through the manufacturing process for that sensor (e.g., by storing a history of testing and/or calibration data for each sensor). In other words, the identifier **450** identifies any of the analyte sensor, calibration data for the analyte sensor, and a history of the analyte sensor. For example, identifier **450** may be used for binning of testing and calibration performance data. Identifier **450** may be a discrete raw value or may encode information in addition to an identification number. Identifier **450** may be used for digitally storing data in non-volatile memory on substrate **404** or as a reference number for storing data external to sensor carrier **402**.

Testing station **5002** may include a reader **5011** (e.g., an optical sensor, an RF sensor, or an electrical interface such as an integrated circuit interface) that reads identifier **450** to obtain a unique identifier of sensor **138**. Testing data obtained by testing station **5002** may be stored and/or transmitted along with the identifier of sensor **138**.

Calibration station **5004** may include a reader **5011** (e.g., an optical sensor, an RF sensor, or an electrical interface) that reads identifier **450** to obtain a unique identifier of sensor **138**. Calibration data obtained by calibration station **5004** may be stored and/or transmitted along with the identifier of sensor **138**. In some implementations, calibration data obtained by calibration station **5004** may be added to identifier **450** by calibration station **5004** (e.g., by programming the calibration data into the identifier). In some implementations, calibration data obtained by calibration station **5004** may be transmitted to a remote system or device along with identifier **450** by calibration station.

As shown in FIGS. 5A-5E and described in further detail hereinafter, on-skin sensor assembly **600** may include one or more contacts such as contact **5022** configured to couple internal electronic circuitry to contacts **410** and **412** of sensor carrier **402** and thus to sensor **138**. Sensor carrier **402** may be sized and shaped to be secured within a cavity **5024** in or on the housing **128** such that sensor **138** is coupled to electronics in the housing **128** via sensor carrier **402**, and sensor **138** may be positionally secured to extend from the housing **128** for insertion for in vivo operations.

Although one calibration station and one testing station are shown in FIGS. 5A-5E, it should be appreciated that more than one testing station and/or more than one calibration station may be utilized in the manufacturing and testing phase of production. Although calibration station **5004** and testing station **5002** are shown as separate stations in FIGS. 5A-5E, it should be appreciated that, in some implementations calibration stations and testing stations may be combined into one or more calibration/testing stations (e.g., stations in which processing circuitry for performing testing and calibration operations is provided within a common housing and coupled to a single interface **5006**).

32

Wearable assembly **600** may also include a reader (e.g., an optical sensor, an RF sensor, or an electrical interface) positioned near the contacts **5022** that reads identifier **450** to obtain a unique identifier of sensor **138**. Sensor electronics may obtain calibration data for in vivo operation of sensor **138** based on the read identifier **450**. The calibration data may be stored in, and obtained, from identifier **450** itself, or identifier **450** may be used to obtain the calibration data for the installed sensor **138** from a remote system such as a cloud-based system.

FIGS. 6-8 are schematic illustrations of various implementations of securement of a pre-connected sensor **400** within wearable assembly **600**. In the example of FIG. 6, sensor carrier **402** is in direct contact with a base wall **605** and housing **128**, and contact **5022** includes multiple contacts on the housing **128** for contacting both contacts **410** and **412** of sensor carrier **402** (e.g., both located on a top surface of sensor carrier **402**). In the example of FIG. 7, a mechanical receiver **700** is provided on base wall **605** for mechanically securing sensor carrier **402**. In the example of FIG. 8, mechanical receiver **800** is provided on base wall **605** for mechanically securing sensor carrier **402** in cooperation with receiver **702**. In the example of FIG. 8, receiver **702** includes an additional contact **704** for contacting contact **410** of sensor carrier **402** located on a rear surface of the sensor carrier.

FIG. 9 shows a detailed example of a sensor module **300** including a pre-connected sensor **400** and a sealing structure **192**. As shown, sealing structure **192** may be disposed on a substrate **404**, in which sealing structure **192** may be configured to prevent moisture ingress toward contacts **410** and **412**. Furthermore, contacts **410** and **412** may be implemented as leaf spring contact for coupling to sensor electronics. In some embodiments, pre-connected sensor **400** includes at least one contact. In some embodiments, pre-connected sensor **400** includes at least two contacts. In some embodiments, pre-connected sensor **400** includes at least three contacts. In some embodiments, pre-connected sensor **400** includes at least four contacts. An adhesive **126** can couple the housing **128** to the skin **130** of the host. The adhesive **126** can be a pressure sensitive adhesive (e.g. acrylic, rubber based, or other suitable type) bonded to a carrier substrate (e.g., spun lace polyester, polyurethane film, or other suitable type) for skin attachment. As shown in FIG. 9, substrate **404** may include at least one arm **202** or other mechanical features for interfacing with corresponding mating features on base **128** (e.g., mechanical interlocks such as snap fits, clips, and/or interference features) to mechanically secure substrate **404** to housing **128**. Coupling features such as arm **902** and/or other features of substrate **404** may be sized and shaped for releasably mechanically attaching substrate **404** to a connector associated with manufacturing equipment such as one or more of connectors **5006**, **5014**, and/or **5093/5095** of FIGS. 5A-5E for testing and/or calibration operations during manufacturing and prior to attachment to features **900** of housing **128**.

FIG. 10 illustrates a perspective view of the sensor module **400** in an implementation in which contacts **406** and **408** are implemented using coil springs **306**. In the example of FIG. 10, protrusions **308** on substrate **404** can align sensor **138** and secure springs **306** to substrate **404**. (Not all the protrusions **308** are labeled in order to increase the clarity of FIG. 10.) Protrusions **308** can protrude distally.

At least three, at least four, and/or less than ten protrusions **308** can be configured to contact a perimeter of a spring **306**. Protrusions **308** can be separated by gaps. The gaps enable protrusions **308** to flex outward as spring **306** is inserted

33

between protrusions 308. A downward force for coupling electronics unit 500 to base 128 can push spring 306 against sensor 138 to electrically couple spring 306 to the sensor 138. Sensor 138 can run between at least two of protrusions 308. Testing station 5002 and/or calibration station 5004 may also have a mating connector structure that, when substrate 404 is inserted into recess 5006 or 5014, compresses springs 306 to couple springs 306 electrically between sensor 138 and processing circuitry 5012 or 5020.

Sensor 138 may include a distal portion 138a configured for subcutaneous sensing and a proximal portion 138b mechanically coupled to sensor carrier 402 having an electrical interconnect (e.g., springs 306) mechanically coupled to the substrate 404 and electrically coupled to proximal portion 138b. Springs 306 can be conical springs, helical springs, or any other type of spring mentioned herein or suitable for electrical connections.

Substrate 404 may have a base portion 312 that includes at least two proximal protrusions 308 located around a perimeter of spring 306. Proximal protrusions 308 are configured to help orient spring 306. A segment of glucose sensor 138 is located between the proximal protrusions 308 (distally to the spring 306).

Base portion 312 may be configured to be mechanically coupled to the housing 128, to manufacturing equipment 5091, testing equipment 5002, and/or calibration equipment 5004. For example, base portion 312 includes anchoring features such as arms 202. Anchoring features may include arms 202 and/or may include features such as one or more notches, recesses, protrusions, or other features in base 312, arms 202, and/or substrate 404 that mechanically interface with corresponding features of, for example, a receptacle such as one of receptacles 5006 of 5014 of FIGS. 5A-5E or a clamping connector formed by clamping connector features such as features 5093 and 5095 of FIGS. 5A-5E to secure and align sensor 138. In one suitable example, a slidable (or otherwise actuable or rotatable) feature such as feature 5095 of FIGS. 5A-5E may be arranged to slide over, around, or otherwise engage with one or more of arms 202, base 312, and/or sensor carrier 402 altogether to secure sensor carrier 402 to the manufacturing equipment. For example, in other implementations of sensor carrier 402 in which arms 202 are not provided, a receptacle connector such as one of receptacles 5006 of 5014 of FIGS. 5A-5E or a clamping connector formed by clamping connector features such as features 5093 and 5095 of FIGS. 5A-5E may include a clamshell component, a sliding component, or other movable component that bears against or covers sensor carrier 402 to latch sensor carrier 402 to the manufacturing, testing, and/or calibration equipment.

Referring now to FIGS. 11 and 12, another implementation of sensor module 400 is shown that includes a base portion 312d; a glucose sensor 138 having a distal portion 138a configured for subcutaneous sensing and a proximal portion 138b mechanically coupled to base portion 312d; and an electrical interconnect (e.g., leaf springs 306d) mechanically coupled to substrate 404 and electrically coupled to the proximal portion 138b. Leaf springs 306d can be configured to bend in response to pressure from testing station contacts, calibration station contacts, and/or electronics unit 500 coupling with base 128 while pre-connected sensor 400 is disposed between electronics unit 500 coupling with base 128.

As used herein, cantilever springs are a type of leaf spring. As used herein, a leaf spring can be made of a number of strips of curved metal that are held together one above the other. As used herein in many embodiments, leaf springs

34

only include one strip (e.g., one layer) of curved metal (rather than multiple layers of curved metal). For example, leaf spring 306d in FIG. 11 can be made of one layer of metal or multiple layers of metal. In some embodiments, leaf springs include one layer of flat metal secured at one end (such that the leaf spring is a cantilever spring).

As shown in FIGS. 11 and 12, base portion 312d includes a proximal protrusion 320d having a channel 322d in which at least a portion of proximal portion 138b is located. The channel 322d positions a first area of proximal portion 138b such that the area is electrically coupled to leaf spring 306d.

As shown in the cross-sectional, perspective view of FIG. 12, leaf spring 306d arcs away from the first area and protrudes proximally to electrically couple with testing station 5002, calibration station 5004, and/or wearable assembly 600. At least a portion of leaf spring 306d forms a "W" shape. At least a portion of leaf spring 306d forms a "C" shape. Leaf spring 306d bends around the proximal protrusion 320d. Leaf spring 306d protrudes proximally to electrically couple testing station 5002, calibration station 5004, and/or electronics unit 500. Seal 192 is configured to impede fluid ingress to leaf spring 306d.

Leaf spring 306d is oriented such that coupling sensor carrier 402 to testing station 5002, calibration station 5004, and/or electronics unit 500 presses leaf spring 306d against a first electrical contact of the testing station 5002, calibration station 5004, and/or electronics unit 500 and a second electrical contact of the glucose sensor 138 to electrically couple the glucose sensor 138 to the testing station 5002, calibration station 5004, and/or electronics unit 500. The proximal height of seal 192 may be greater than a proximal height of leaf spring 306d such that the testing station 5002, calibration station 5004, and/or electronics unit 500 contacts the seal 192 prior to contacting the leaf spring 306d. Springs 306 and/or leaf springs 306d may cooperate with underlying features on substrate 404 (e.g., features 308) and/or channel 322d, as shown, to form datum features that secure and align sensor 138 with respect to sensor carrier 402 (e.g., for manufacturing, calibration, testing, and/or in vivo operations).

FIGS. 13A and 13B show perspective views of an embodiment of a wearable assembly 600 including a pre-connected sensor 400. Wearable assembly 600 may include sensor electronics and an adhesive patch (not shown). Pre-connected sensor 400 may include a sensor carrier such as sensor carrier 402 described in FIGS. 4A-4D. The sensor carrier 402 may be placed in or on housing 128. Housing 128 may be composed of two housing components, top housing 520 and bottom housing 522. Top housing 520 and bottom housing 522 can be assembled together to form housing 128. Top housing 520 and bottom housing 522 can be sealed to prevent moisture ingress to an internal cavity of housing 128. The sealed housing may include an encapsulating material (e.g. epoxy, silicone, urethane, or other suitable material). In other embodiments, housing 128 is formed as a single component encapsulant (e.g. epoxy) configured to contain sensor carrier 402 and sensor electronics. FIG. 13A illustrates an aperture 524 within top housing 520 configured to allow for an insertion component (e.g. hypodermic needle, C-needle, V-needle, open sided needle, etc.) to pass through the wearable assembly 600 for insertion and/or retraction. Aperture 524 may be aligned with a corresponding aperture in bottom housing 522. In other embodiments, aperture 524 may extend through an off-center location of housing 128. In other embodiments, aperture 524 may extend through an edge of the housing 128, forming a C-shaped channel. In some embodiments the aperture 524

35

includes a sealing material such as a gel, adhesive, elastomer, or other suitable material located within aperture 524.

FIG. 13B shows a perspective view of the bottom of wearable assembly 600. As illustrated, pre-connected sensor 400 may be disposed within the housing 128. Pre-connected sensor 400 may be installed within an aperture 526 of bottom housing 522. As shown in the figure, sensor 138 may extend out from aperture 526. Aperture 526 may be sized and shaped to retain pre-connected sensor 400. Furthermore, aperture 526 may be sized and shaped to retain pre-connected sensor 400 in which sensor 138 extends approximately parallel to the skin surface and forms a 90 degree bend for insertion into the skin. It should be understood that the bottom surface of bottom housing 522 can contain an attachment member (e.g. an adhesive patch) for adhering the wearable assembly to the skin surface of a user.

FIG. 13C shows an exploded view of the wearable assembly 600. Various electronic components such as the potentiostat 210 and other components illustrated in FIG. 2 may be mounted on or to an electronics assembly substrate 530, typically some form of printed circuit board. It is contemplated that sensor carrier 402 has an electrical coupling with electronics assembly substrate 530. Various methods may be used to establish electrical connection (e.g. pins, solder, conductive elastomer, conductive adhesive, etc.) between one or more contacts of pre-connected sensor 400, such as external contacts 410 and 412 and electronics assembly substrate 530. Sensor carrier 402 may be configured to interface with electronics assembly substrate 530 through the bottom housing 522. In other implementations, the sensor carrier 402 may be configured to interface with the electronics assembly substrate 530 through top housing 520. In some other implementations, the sensor carrier 402 is configured to interface with the electronics assembly substrate 530 through the side of wearable assembly 600. Also shown in the figure, an optional sealing member 528 may be configured to insulate at least a portion of sensor carrier 402 from potential moisture ingress. In some instances, the sealing member 528 may be liquid dispensed (e.g., adhesive, gel) or a solid material (e.g., elastomer, polymer). The sealing member 528 may be an assembled component that is welded (e.g., laser or ultrasonic, hot plate), or otherwise permanently attached (e.g., anisotropic adhesive film, pressure sensitive adhesive, cyanoacrylate, epoxy, or other suitable adhesive) to create a sealed region. The sealing member 528 may be used to physically couple and/or provide a sealed region for the sensor carrier 402 to the wearable assembly 600.

FIGS. 14A-14E illustrate another implementation of a wearable assembly 600. The implementation of FIGS. 14A-14E share some similarities to the implementation shown in FIGS. 13A-13C. As illustrated in FIG. 14A, the wearable assembly 600 includes a housing formed as a top housing 520 and a bottom housing 522. The wearable assembly also includes a through hole 524 for use during interstitial insertion of the sensor 138 into a subject. Referring especially to FIGS. 14B, C, and D, the bottom housing 522 includes a recess 726 with a floor 704. The floor 704 may include locating pins 784 and 786 that extend upward from the floor 704 and two apertures 722 and 724. The locating pins may be formed as an integral part of the floor 704, during for example molding of the housing, or they may be separate parts that are coupled to the floor with friction fit, adhesive, or any other means. In some embodiments, there is at least one locating pin. In some embodiments, there are at least two locating pins. In some embodiments, there are at least three locating pins. On the opposite side of the floor

36

704 is a printed circuit board 530 (visible in FIG. 14E) with some or all of the sensor electronic circuitry (e.g. the potentiostat 210 or at least traces that connect to the potentiostat) mounted thereon. The printed circuit board 530 may also have conductive pins 712 and 714 mounted thereon which extend through apertures 722 and 724 in the floor 704, forming an external electrical interface that is accessible without opening the housing. The pre-connected sensor 400 drops into this recess 726. Holes 794 and 796 drop over locating pins 784 and 786 and conductive pins 712 and 714 extend through holes 706 and 708 in the sensor carrier substrate 404. These holes 706 and 708 extend through plated metal (e.g. copper) contacts 406 and 408 on the substrate 404, similar to those shown in a different embodiment in FIGS. 4A to 4C. Generally, the number of holes 706, 708 in the substrate 404 correspond to the number of electrodes present in the sensor 138, which may in turn correspond to the number of pins 712, 714. For example, a three-electrode system with a working, reference, and counter electrode may have three holes in the substrate corresponding to three pins extending up through floor 704. The pins 712 and 714 may be electrically connected to the contacts 408 and 406 in a variety of ways such as solder, swaging, or conductive glue, paste, adhesive, or film. After this connection is made, the electronic circuitry for detecting and/or processing analyte sensor signals that is placed inside the housing becomes connected to the analyte sensor to receive signals therefrom. The connection material bonding the sensor 138 to the sensor carrier 402 is designated 762 and 764 in FIGS. 14D and 14E. These connections may be established by any of the methods described above with reference to FIG. 4A.

Once the substrate 404 is placed over the pins 712, 714, the proximal portion of the sensor 138 can be secured to the floor 704 with a pressure sensitive adhesive 772 to retain the proximal portion of the sensor on or near the housing prior to extending downward at the inserter opening 524. This allows for accurate sensor insertion position and controls the bias force into the insertion needle. A variety of methods and/or structural features may be used to perform this retention function such as a protrusion or shelf in the floor 704, an overmolded part, a snap-fit additional plastic piece installed over the sensor, or any sort of glue or adhesive placed before or after the pre-connected sensor is placed in the recess 726. As is also shown in FIG. 13C, optional sealing members 528a and 528b may be configured to seal and insulate at least a portion of sensor carrier 402 from potential moisture ingress. In some instances, the sealing member 528 may be liquid dispensed (e.g., adhesive, gel) or a solid material (e.g., elastomer, polymer). The sealing member 528 may be an assembled component that is welded (e.g., laser or ultrasonic, hot plate), or otherwise permanently attached (e.g., pressure sensitive adhesive, cyanoacrylate, epoxy, or other suitable adhesive) to create a sealed region. The sealing member 528 may be used to physically couple and/or provide a sealed region for the sensor carrier 402 to the wearable assembly 600. The two sealing members 528a and 528b are partially separated by walls 766 and 768. These walls allow two different sealing methods to be used in the two different portions of the recess 726 that are separated by the walls. For example, 528b may be a solid polymer that is press fit into the recess portion with opening 524 on one side of the walls. The other portion of the recess 726 may then be filled with a liquid UV cured epoxy which hardens to form sealing member 528a. The depth of the two recess portions on either side of the walls may be the same or different.

FIG. 15A shows an alternative embodiment of a sensor carrier 402, also potentially taking the form of a printed circuit board. In this implementation, a guard trace 407 such as described above with reference to item 336 in FIG. 3D is provided on the substrate 404 of the sensor carrier 402. As explained above, this guard trace 407 is positioned between contacts 406 and 408 and is connected to the bias voltage by the sensor electronics. The guard trace 407 can be coupled to the sensor electronics with or more conductive pins 713 (not shown in FIGS. 14A to 14E) that extend through the floor 704 similar to pins 712 and 714. In FIG. 15A, the pins are shown connected to castellated contacts on the side of the substrate 404. An insulating layer 780 such as solder mask may be positioned over the guard trace 407 to eliminate the risk of the analyte sensor electrodes shorting to it.

FIGS. 15B and 15C illustrated other implementations of connecting a sensor carrier 402 having an analyte sensor 138 mounted thereon to electronic circuitry internal to a wearable sensor. In FIG. 15B, the sensor 138 is coupled to the sensor carrier 402 with conductive adhesive 762 and 764 as shown above with reference to FIGS. 14C and 14D. On the other side of the sensor carrier substrate are conductive contact pads 812 and 814. The circuit board 530 also has contact pads 826 and 828 bonded thereto and which are accessible through the floor 704 of the recess 726. An anisotropic film 820 is used to electrically and mechanically bond the sensor carrier contact 812 to circuit board contact 826 and also sensor carrier contact 814 to circuit board contact 828. The anisotropic film 820 is compressed with heat between the contacts, which makes conductive particles in the film 820 bridge the gap vertically between the contact pairs 812/826 and 814/828. The conductive particles in the film 820 are spaced apart horizontally, so no shorting between the contact pairs occurs. This electrical and mechanical bonding technique has found widespread use in display applications for small electronics such as smart phones and lends itself to easy and consistent connections in production environments.

In FIG. 15C, the proximal region of sensor 138 is coupled to the sensor carrier 402 contacts 812 and 814 with anisotropic film 820. A different area of the same anisotropic film 820 may be used to connect the sensor carrier contacts 812 and 814 to circuit board contacts 826 and 828 respectively. In this implementation, the area of the film 820 that connects the sensor 138 to the contacts 812 and 814 may be horizontally adjacent to or otherwise separated from the area of the film 820 that connects the circuit board contacts 826 and 828 to the sensor carrier contacts 812 and 814.

In the examples of FIGS. 10-15, pre-connected sensor 400 can be installed as a standalone interface between sensor 138 and the sensor electronics. However, it should be appreciated that, in some implementations described herein, pre-connected sensor 400 may include a sensor carrier that couples to an additional interface between the sensor 138 and the sensor electronics inside the wearable assembly 600. For example, channel 322d and leaf spring 306d can be formed on separate substrate that, following calibration and testing operations, mechanically attaches to base portion 312d within seal 192 for installation into wearable assembly 600.

It is one benefit of the analyte sensor connection techniques described above that the fabrication of the pre-connected sensor 400 may be separated from the fabrication of the electronics enclosed within the housing. As described above with reference to the pre-connected sensor structure and the subsequent coating, testing and calibrating processes, the housing with the internally contained electronics

can be manufactured in a separate facility from the one that attaches the pre-connected sensor 400 to the sensor electrical interface. This is made possible by providing an analyte sensor electronics interface that is accessible from outside the housing. The housing need not be opened to attach the sensor.

In some advantageous methods, the electrodes for the pre-connected sensor are fabricated and mounted on the substrate in a first location and are shipped to a second location for coating testing and calibrating. The housing with internal electronics is manufactured in a third location. The housing with the electronics is shipped from the third location to the second location, where the completed analyte sensor is attached to the external electrical interface. The three locations can all be remote from each other. This minimizes handling of the sensitive membrane coated sensor, but still allows separate manufacturing of the other components of the complete device.

FIG. 16 shows a top view of an implementation of sensor carrier 402 in which substrate 404 is a substantially planar substrate and sensor 138 is attached to substrate 404 with a conductive adhesive 1500. As shown in FIG. 16, conductive adhesive 1500 may be applied to contacts 1000 and 1002 of sensor 138 to mechanically attach sensor 138 to substrate 404. Once applied the conductive adhesive 1500 on contacts 1000 and 1002, may itself form contacts 408 and 406 for coupling to testing station 5002, calibration station 5004, and/or electronics unit 500. FIG. 17 shows an end view of sensor carrier 402 of FIG. 16 in which conductive adhesive 1500 can be seen covering a portion of sensor 138 at the proximal end. In other embodiments, sensor 138 may be attached to substrate 404 with a conductive adhesive 1500, or via any other suitable methods via the use of, for example, clips, conductive polymer, metallic foil, conductive foam, conductive fabric, wire wrapping, wire threading or via any other suitable methods.

FIGS. 18, 19, and 20 show examples of substrate 404 of FIG. 16, with additional datum features for controlling the position and spatial orientation of sensor 138 on substrate 404. In the example of FIG. 18, substrate 404 includes a v-shaped recess 1700. Sensor 138 is disposed partially within recess 1700 to orient sensor 138 in a direction along the recess, and conductive adhesive 1500 substantially covers sensor 138 and fills in portions of recess 1700 not filled by sensor 138 to secure sensor 138 within the recess. In the example of FIG. 19, substrate 404 includes a first planar portion 1800 and a second planar portion 1802 extending at a non-parallel (e.g., perpendicular) angle with respect to the first planar portion, and sensor 138 is attached at the interface of the first and second planar portions by conductive adhesive 1500. In the example of FIG. 20, substrate 404 includes a rounded recess 1900 in which sensor 138 is attached by conductive adhesive 1500 that substantially covers sensor 138 and fills in portions of recess 1700 not filled by sensor 138 to secure sensor 138 within the recess.

FIGS. 21A and 21B show an example sensor carrier 402 with at least one pair of guide structures 2106 and 2108 formed on the substrate 404, such as on one or both contacts 406 and 408. These guide structures can assist placement of the sensor body 138 on the appropriate location when applying conductive adhesive to bond the two together. This can eliminate the need for external guide fixtures when assembling the sensor to the sensor carrier during manufacturing. The structures 2106, 2108 can be made of solder or other conductive adhesive. Although not shown in FIGS. 21A and 21B, an additional adhesive bonding material can

39

be provided between the guide structures to fix the sensor to the guide structures during manufacturing.

Conductive adhesive **1500** may be, for example, a conductive liquid dispensed glue. The conductive liquid dispensed glue may be a one or two-part adhesive that cures (e.g., at room temperature or an elevated curing temperature). The conductive liquid dispensed glue may be a snap-cure adhesive. A two-part conductive liquid dispensed glue may include a base adhesive (e.g., epoxy, polyurethane, etc.) and a conductive filler (e.g., silver, carbon, nickel, etc.). Conductive adhesive **1500** may include, for example, an adhesive resin with one or more embedded conductive materials such as silver, copper or graphite. Conductive adhesive **1500** may be a heat curable conductive adhesive.

FIG. **22** shows a top view of an implementation of sensor carrier **402** in which substrate **404** is a substantially planar substrate and sensor **138** is attached to substrate **404** with a conductive tape **2000**. As shown in FIG. **22**, conductive tape **2000** may be applied to one or more contacts (e.g. connection areas **1000** and **1002**) of sensor **138** to mechanically attach sensor **138** to substrate **404**. Once applied the conductive tape **2000** on contacts **1000** and **1002**, may itself form contacts **408** and **406** for coupling to testing station **5002**, calibration station **5004**, and/or electronics unit **500**. Tape **200** may be applied over sensor **138** as shown in FIG. **22**, or may be interposed between substrate **404** and sensor **138**. In implementations in which tape **2000** is disposed between substrate **404** and sensor **138**, substrate **404** may be a flexible substrate that can be rolled or folded around sensor **138** as shown in the end view of FIG. **23**. The rolled substrate of FIG. **23** includes extending portions **2100** that can form one or more contacts (e.g. **406** or **408**).

Conductive tape **2000** may be configured for use as a multi-zoned tape with one or more conductive tapes **2000** and non-conductive tape sections. The combination of conductive and non-conductive regions can be used to electrically isolate connection regions. Using a multi-zoned tape may simplify the assembly of multiple connection regions in a single assembly step. The pitch of the conductive regions on the tape may be matched to the targeted connection area of the sensor wire **138**. In other embodiments the pitch of the conductive region of the tape is significantly less than the spacing of the targeted connection area of the sensor wire **138**. A shorter pitch may allow for more variability in tape placement while ensuring isolated connection between the sensor **138** and the substrate **404**. Conductive tape **2000** may be formed from a polymer substrate with a conductive adhesive (e.g. carbon-impregnated adhesive, metal-impregnated adhesive). As another example, conductive tape **2000** may be a metallic substrate with conductive and non-conductive adhesive. Some examples of non-conductive substrates are polyimide, composite, polymers, etc. Some examples of conductive substrates are metals (e.g. Foils, plating, cladding, etc), conductive polymers, and conductive elastomers. Examples of non-conductive adhesive are epoxy, cyanoacrylate, acrylic, rubber, urethane, hot melt, etc. Examples of conductive adhesives are carbon filled adhesive, nano particle filled adhesive, metal filled adhesive (e.g. silver), conductive inks, etc.

FIG. **24** shows a top view of an implementation of sensor carrier **402** in which substrate **404** is a substantially planar substrate and sensor **138** is attached to substrate **404** with a conductive plastic **2200** welded or bonded to a non-conductive (e.g., plastic) substrate **404**. As shown in FIG. **24**, conductive plastic **2200** may be applied to contacts **1000** and **1002** of sensor **138** to mechanically attach sensor **138** to substrate **404**. Once applied the conductive plastic **2200** on

40

contacts **1000** and **1002**, may itself form contacts **408** and **406** for coupling to testing station **5002**, calibration station **5004**, and/or electronics unit **500**.

FIGS. **25** and **26** show an exemplary ultrasonic welding system for welding conductive plastic **2200** to substrate **404**. As shown in FIG. **25**, substrate **404** may be provided with a recess within which a protrusion on a conductive plastic member **2200** can be received. Sensor **138** may be disposed within a recess in the protrusion on conductive plastic member **2200** and conductive plastic member **2200** can be pressed in direction **2302** and vibrated by ultrasonic welding horn **2300** to form a melt region **2400** that, when horn **2300** is removed, solidifies to secure sensor **138** between substrate **404** and conductive plastic **2200** to form a conductive contact to sensor **138**.

In some implementations, in order to provide a sensor **138** with additional surface area for clipping or soldering of contacts to substrate **404**, the proximal end of sensor **138** may be rolled or otherwise flattened as shown in FIG. **27**. As shown in FIG. **27**, contacts **1000F** and **1002F** may be flat contacts that converge into a cylindrical wire sensor **138**. As shown in the side view of sensor carrier **402** in FIG. **28**, flattened contacts **1000F** and **1002F** may be attached to substrate **404** with conductive attachment members **2600** and **2602** such as clips, solder welds, an anisotropic conductive film, a conductive tape, a plastic member with embedded conductors, conductive springs, or elastomeric conductive members (as examples).

In one example, connectors such as contacts **1000F** and **1002F** (and/or other forms of contacts **1000** and **1002** described herein) may be laser soldered to corresponding contacts on substrate **404**. In implementations in which sensor **138** is laser soldered to substrate **404**, a trace surface of substrate **404** may be preheated by laser illumination at a soldering location. The surface heat emission may reflow a pre-deposited solder material on either side of sensor **139**. A guide such as a borosilicate glass “angle” may be placed over the sensor and pre-deposited solder to retain the solder, driving molten solder towards the sensor. A resulting “cradle” bond may then securely anchor the sensor to the trace on substrate **404** which may help increase or maximize a trace-to-solder-sensor contact wire bonding area. Use of a guide such as a borosilicate glass angle may also protect printed circuit board assembly electronics that may be included on and/or in the substrate from solder debris during the hot portion of the soldering process.

In another example, connectors such as contacts **1000F** and **1002F** (and/or other forms of contacts **1000** and **1002** described herein) may be soldered to corresponding contacts on substrate **404** without a laser. In these example, solder wire may be pre-fed onto a tip of a soldering iron to build up a blob of molten solder on the tip. The iron may then be moved down so the blob touches the sensor and conductive trace on the substrate. A coating on the sensor such as the Ag/AgCl coating described herein may be provided with a low thermal mass such that the sensor coating heats up quickly without freezing the solder. Once the coating is heated, the solder wets to the coating. The trace would also have minimal thermal mass so it will heat up quickly without freezing the solder. A solder mask may be provided around the trace that prevents the solder flowing off the edge of the trace.

In some implementations, substrate **404** may be formed, at least in part, by a flexible circuit (e.g., a polyimide substrate having conductive traces or other suitable flex circuit) that folds over and/or around at least a portion of sensor **138** to conductive traces of the flex circuit. FIG. **29**



41

shows a top view of a flex circuit implementation of substrate **404** in which substrate **404** is a flexible circuit having a central, non-conductive, elongated portion **2702** along which sensor **138** is oriented and having upper and lower extensions **2700** and **2704** that extend from central portion in a directed perpendicular to the elongated dimension of central portion **2702**. Extensions **2700** and **2704** respectively include conductive contacts **2706** and **2708** that form contacts **408** and **406**. Conductive contacts **2706** and **2708** may be coupled, via traces and/or conductive vias on or within substrate **404** to external contacts that form contacts **412** and **410**. In some instances, extensions **2700** and **2704** may allow for testing, calibration, sensor electronics or other equipment to connect to sensor carrier/sensor assembly in area that is not occupied by the sensor. This may allow for additional connection types and/or improve electrical coupling of connection.

FIG. **30** shows an implementation of sensor carrier **402** in which substrate **404** includes a wedge-shaped base portion **2800** and a foldable flexible portion **2802**. Conductive contacts **2804** may extend from base portion **2800** to foldable portion **2802** so that, when sensor **138** is placed on base portion **2800** and optionally foldable portion **2802** is be folded over sensor **138** (e.g., in direction **2820**) to wrap over and around sensor **138**, contacts **410** and **412** electrically couple to sensor **138**. Base portion **2800** may be rigid and may taper in a direction away from sensor **138**. Base portion **2800** may include conductive contacts **410** and **412** at a narrow end. Base portion **2800** may, for example, be removably inserted into recesses **5006** and **5014** of testing station **5002** and calibration station **5004** for testing and calibration operations. In the examples of FIGS. **27** and **28**, the flexible substrate may be folded over the sensor and secured (e.g., to the sensor and/or to itself to secure the sensor by a welding soldering, a mechanical crimp, spring contacts, rivets, adhesive such as epoxies, or the like).

FIGS. **31A** and **31B** illustrate another embodiment of a sensor carrier **402**. In this embodiment, the sensor carrier **402** comprises a block **404** made of non-conducting material such as a polymer or ceramic. The block **404** includes a through-hole **1420** extending therethrough along the y-axis through which the proximal ex vivo portion of the analyte sensor **138** extends. Slots or blind holes **1410** and **1412** intersect the through-hole **1420** on an orthogonal z-axis to the through hole y-axis. Conductive contact material **406** and **408** is plated on the top surface and extends into the slots **1410** and **1412**. Additional holes **1430** and **1432** extending along the x-axis intersect both the through-hole **1420** and the slots **1410** and **1412**. Each hole **1430** and **1432** extends across its respective slot and partway into the block on the other side of each slot forming a blind hole or depression **1442**, **1444** on the other side. Plugs **1451** and **1453**, which may be conductive or non-conductive are inserted into the holes **1430** and **1432** and push the contacts **212b** and **211b** of the wire analyte sensor into the depressions **1442**, **1444**, causing the contacts **212b** and **211b** to come into electrical contact with the sensor carrier contacts **406** and **408**.

FIG. **32** shows a top view of a sensor carrier having a substrate **404**, a datum feature **2900**, and a movable connector **2902** for each of contacts **406** and **408**. Sensor **138** may be aligned against datum features **2900** and movable connectors **2902** may be moved to secure each of contacts **1000** and **1002** between the corresponding datum feature and movable connector. Movable connectors **2902** and/or datum features **2900** conductively couple to contacts **1000** and **1002**. Movable connectors **2902** and/or datum features **2900** may be conductively coupled to other contacts (not

42

shown) on substrate **404** that form contacts **410** and **412**. FIG. **33** is a perspective view of one of datum features **2900** and an associate movable contact **2902**, movable in a direction **2904** toward datum feature **2900** to secure sensor **138**. Contacts **1000** and **1002** may be flattened to enhance contact with datum feature **2900** and contact **2902**. Additional conductive material **2906** may be formed on substrate **404** between datum feature **2900** and contact **2902** to enhance electrical contact with sensor **138** if desired. The additional conductive material may be an exposed surface of a portion of an embedded conductive layer (e.g., a copper or other conductive metal layer) within substrate **404** or may be solder or a conductive adhesive (as examples).

FIG. **34** shows a perspective view of a pre-connected sensor formed from a sensor carrier implemented as a barrel connector that substantially surrounds sensor **138**. In the example of FIG. **34**, substrate **404** may be an insulating layer formed around sensor **138** with conductive bands that extend from an internal contact with contacts **1000** and **1002** to an external surface that forms contacts **410** and **412**. As shown in FIG. **34**, annular contacts **410** and **412** may be removably received by a press fit into conductive brackets **3102** and **3104** of a device **3100** (e.g., testing station **5002**, calibration station **5004**, and/or electronics unit **500**). Conductive brackets **3102** and **3104** may establish electrical communication between sensor **138** and device **3100** (e.g., testing station **5002**, calibration station **5004**, and/or electronics unit **500**).

FIG. **35A** shows an implementation of sensor carrier **402** in which a flexible circuit is wrapped over an end of sensor **138** such that a top portion **3200** and a bottom portion **3202** of the flexible substrate are formed on opposing sides of sensor **138**. As shown in FIG. **35B**, top portion **3200** and bottom portion **3202** may be wrapped over the ends of multiple sensors **138** such that a flex circuit strip **3404** forms a common sensor carrier for multiple sensors. Flex circuit strip **3204** may include pairs of internal contacts for coupling to contacts **1000** and **1002** of each sensor **138** and pairs of external contacts, each pair of external contacts coupled to a corresponding pair of internal contacts and forming contacts for coupling to testing station **5002** and/or calibration station **5004**. In this way, multiple sensors can be transported and coupled to testing and calibration equipment as a group. Strip sensor carrier **3204** may include identifiers for each sensor **138** so that testing and/or calibration data for each sensor can be logged and stored. Individual pre-connected sensors may be formed by singulating strip sensor carrier **3204** into individual sensor carriers for each sensor that can be installed in an electronics unit, such as the wearable sensor units of FIGS. **13** and **14**. Strip **3204** may include singulation features **3220** (e.g., markings and/or scoring that facilitate singulation into individual pre-connected sensors).

Although FIGS. **35A** and **35B** show a flexible circuit strip that is wrapped around the ends of sensor **138**, this is merely illustrative. It should be appreciated that a flex strip carrier for more one or more sensors **138** may be attached to the sensor(s) in other ways. For example, the ends or other portions of sensors **138** may extend into a substrate of flexible circuit strip **3204** to couple to internal conductive contacts in the strip or the ends or other portions of sensors **138** may be attached to a surface of flexible circuit strip **3204** (e.g., using an anisotropic conductive film (ACF) or other conductive adhesive, a laser solder or other solder, a clip or other attachment mechanisms and/or datum features that position and align the sensor).

FIG. **36** shows an implementation of sensor carrier **302** in which a crimp connector **3301** extends through a portion of

43

substrate 404. As shown in FIG. 36, crimp connector 3301 may have a base portion 3300 that extends from a first side of substrate 404 (e.g., to form one of contacts 410 and 412). Crimp connector 3301 also includes arms 3302 extend from an opposing second side of substrate 404. As shown in FIG. 37, arms 3302 can be pressed together or crimped to mechanically secure and conductively couple to sensor 138, thereby forming, for example, contact 406. FIG. 38 shows a side view of the sensor carrier of FIGS. 36 and 37 and shows how two crimp connectors may be provided that extend through substrate 404 and form contacts 406 and 408 on a first side and contacts 410 and 412 on a second side. Although contacts 410 and 412 are formed on the second side of substrate 404 in FIG. 38, it should be appreciated that contacts 410 and 412 can be formed on the first side, or on a sidewall or edge of substrate 404 (e.g., by including one or more bends or other conductive couplings within substrate 404).

FIG. 39 shows an implementation of pre-connected sensor in which sensor carrier 402 includes a distally oriented channel 358 that directs sensor 138 distally such that sensor 138 includes a bend that is at least 45 degrees and/or less than 135 degrees. A channel cover 362 secures the glucose sensor 138 in the distally oriented channel 358. In the example of FIG. 39, one or more contacts (e.g. 408 and 406) are implemented using conductive elastomeric members 1400. In other embodiments contacts may be any suitable type (e.g. coil springs 306, leaf spring 306d). Contacts (e.g. conductive elastomeric members 1400) form a conductive coupling between sensor 138 and external equipment (e.g., testing station 5002, calibration station 5004, and/or on-skin sensor assembly 600). Contacts may cooperate with underlying features on substrate 404 (e.g., protrusions 308) and/or channel 322d, as shown, to form datum features that secure and align sensor 138 with respect to sensor carrier 402 (e.g., for manufacturing, calibration, testing, and/or in vivo operations). In some implementations, the sensor 138 maybe bent, glued, or bonded so as to be affixed within sensor carrier 402.

FIG. 40 shows an implementation of sensor carrier 402 in which substrate 404 is a molded interconnect device. In the example of FIG. 40, substrate 404 is formed from molded thermoplastic or thermoset (e.g., acrylonitrile butadiene styrene, a liquid crystal polymer, a polyimide/polyphthalamide plastic, or other thermoplastic or thermoset polymer materials) that includes conductive traces 3702. Conductive traces 3702 may be formed on a surface of substrate 404 and/or may pass into and/or through portions of substrate 404 to form suitable connections. Conductive traces may be formed on the molded substrate using a variety of techniques (e.g. selective plating via laser etching, combining platable and non platable substrate polymers, or other suitable methods). In other embodiments, a conductive material (e.g. conductive polymer, metal stamping, plated polymer, metallic structure) may be overmolded with a non-conductive material.

To create suitable electrical connections as shown in FIG. 40, conductive traces 3702 are electrically coupled between contacts (e.g. contact region 1000 and 1002 on sensor 138) and external contacts (e.g. contacts 410 and 412). Although contacts (e.g. 410 and 412) are formed on the same surface of substrate 404 to which sensor 138 is attached in the example of FIG. 37, this is merely illustrative. It should be appreciated that contacts (e.g. contacts 410 and 412) may be formed on an opposing surface or on an edge or sidewall of substrate 404 and coupled to contacts (e.g. contacts 408 and 406) by conductive materials (e.g. conductive layers, struc-

44

tures, adhesive, clips, solder, or interconnects) within or on substrate 404. For example, contacts (e.g. contacts 410 and 412) may form a designated area to interface electrical coupling on a different surface or region of substrate 404 on which sensor 138 is attached. The designated area may form a channel, groove, recess, slot, or similar alignment feature for orienting the sensor.

Molded thermoplastic substrate 404 may be an injection-molded substrate having features that facilitate various aspects of testing, calibration, and wearable device installation for sensor 138. For example, molded thermoplastic substrate 404 may include datum features or other locating features or positioning features such as a recess 3700 having a shape that is complementary to the shape of the proximal end of sensor 138. For example, recess 3700 may include three or more stepped regions that correspond to the steps between the different layers of the coaxial analyte sensor such as shown in FIG. 3D. In other configurations, molded thermoplastic substrate 404 may include a flat-walled recess as in the example of FIG. 18, a wall that forms a corner as in the example of FIG. 19, or a rounded recess as in the example of FIG. 20. In yet other configurations, molded thermoplastic substrate 404 may include raised features or protrusions on the surface that position and align sensor 138. For example, a raised channel having a shape corresponding to the shape of sensor 138 may be provided on the surface of molded thermoplastic substrate 404. As another example one more posts may extend from the surface of molded thermoplastic substrate 404. For example, one or more lines of protrusions can be formed on the surface of molded thermoplastic substrate 404 against which and/or between which sensor 138 can be positioned and aligned. In this way, various configurations can be provided for a molded thermoplastic substrate 404 including datum features that orient sensor 138 in a preferred direction at a preferred position.

Molded thermoplastic substrate 404 may also include other shaped features such as finger holds 3720 on opposing sides the substrate that facilitate grasping, holding, and transporting of sensor 138. Molded thermoplastic substrate 404 may also include other shaped features such as anchoring features corresponding to the shape of connectors for manufacturing equipment 5091, testing equipment 5004, and calibration equipment 5004 such as grasping connector features 5093/5095 of manufacturing equipment 5091 and/or recess connectors 5006 and 5014 of testing equipment 5002 and calibration equipment 5004. Anchoring features formed on molded thermoplastic substrate 404 and/or by molded thermoplastic substrate 404 itself may include one or more protrusions such as posts, snap-fit features, arms such as arms 202 (see, e.g., FIGS. 11-14), recesses, notches, hooks, and/or tapered portions similar to the tapered portions shown in FIG. 28 (as examples). In some examples, a portion of molded thermoplastic substrate 404 or the entire molded thermoplastic substrate 404 may have a shape that corresponds to the shape of a mounting receptacle on or within one or more of manufacturing equipment 5091, testing equipment 5002, calibration equipment 5004, carriers, and/or a wearable device.

Although substrate 404 is shown in FIG. 40 as being substantially rectilinear, a molded thermoplastic substrate 404 can be provided with features 3720 and/or an overall shape such as a handle shape for inserting, pulling, or otherwise manipulating sensor 138 during manufacturing and assembly operations. For example, molded thermoplastic substrate 404 may include a main portion configured to mechanically and electrically interface with manufacturing equipment 5091, testing equipment 5002, calibration equip-

45

ment **5004**, and/or a wearable device, and a gripping portion that extends from the main portion. The gripping portion may extend from the manufacturing equipment **5091**, testing equipment **5002**, or calibration equipment **5004** during manufacturing operations to facilitate removal of sensor carrier **402** and sensor **138** from the equipment after or between the manufacturing operations. The gripping portion may be integrally formed with the main portion or may be a separate component that extends from the surface of, or from within, molded thermoplastic substrate **404**. The gripping component may be a post, a stock, a shaft, or an arched handle shaped for gripping by a gripping tool or by hand (e.g., by a technician).

As shown in FIG. **40**, sensor **138** may be placed in recess **3700** and secured to substrate **404** using adhesive **3704** (e.g., a conductive adhesive as described herein). Adhesive **3704** may be applied to couple contact **1000** of sensor **138** to a first conductive trace **3702** on substrate **404** to form contact **408** between sensor **138** and sensor carrier **402**. Adhesive **3704** may be also applied to couple contact **1002** of sensor **138** to a second conductive trace **3702** on substrate **404** to form contact **406** between sensor **138** and sensor carrier **402**. In this way, molded thermoplastic substrate **404** can provide a handle and/or a strain relief member for moving and/or otherwise handling sensor **138**.

FIG. **41** shows a top view of sensor carrier **402** of FIG. **40**. As shown in FIGS. **40** and **41**, the first conductive trace **3702** may extend from a contact portion with contact **1000** within recess **3700** to form one or more exposed portions on the surface of substrate **404** that form external contact **412** for coupling to testing station **5002**, calibration station **5004**, and/or electronics unit **500**. The second conductive trace **3702** may extend from a contact portion with contact **1002** within recess **3700** to form one or more exposed portions on the surface of substrate **404** that form external contact **410** for coupling to testing station **5002**, calibration station **5004**, and/or electronics unit **500**.

FIG. **42** shows a specific implementation of sensor carrier **402** as illustrated in FIGS. **40** and **41**. In this implementation of sensor carrier **402**, sensor **138** is attached to substrate **404** with a conductive coupler **3900**, such as, for example, clips, conductive adhesive, conductive polymer, metallic foil, conductive foam, conductive fabric, wire wrapping, wire threading or via any suitable methods. As shown in FIG. **43**, a substrate **4000** may have an elongated dimension along which parallel conductive strips **4001** and **4002** are formed. Multiple sensor **138** may be attached to substrate **4000** and extend beyond an edge of the substrate in a direction perpendicular to the elongated dimension of the substrate. Singulation features such as scoring **4020** may be provided that facilitate singulation of substrate **4000** into individual sensor carrier substrates **404** for each sensor and/or that electrically isolate portions of conductive strips **4001** and **4002** for each sensor. Each sensor may be attached to substrate **4000** using, for example clips **3900** or any other methods including, via the use of conductive adhesive, conductive polymer, metallic foil, conductive foam, conductive fabric, wire wrapping, wire threading or any other suitable methods. An identifier **450** for each sensor may be provided on a corresponding portion of substrate **4000**.

Sensors **138** may each have a pair of sensor electrical contacts (e.g., contacts **1000** and **1002**) coupled to a corresponding pair of electrical contacts formed from strips **4001** and **4002** on the substrate. Openings in substrate **4000** and/or vias that extend through substrate **4000** may provide exposed portions of strips **4001** and **4002** that form a plurality of pairs of electrical contacts for coupling each

46

sensor **138** to testing station **5002**, calibration station **5004**, and/or electronics unit **500** (e.g., an electronics unit of a wearable device). Each of the plurality of pairs of electrical contacts is coupled to an associated pair of portions of strips **4001** and **4002** via the substrate.

FIGS. **44-46** show various contact configurations on sensor carriers that can be singulated from a sensor carrier strip of the type shown in FIG. **43**. In the example of FIG. **44**, a z-shaped contact configuration on substrate **4000** has been singulated to form a pre-connected sensor on a smaller portion of the substrate, referred to as substrate **404**. In this instance, the z-shaped contact configuration may allow for greater distance between connectors (e.g., larger pitch connection) on testing, manufacturing, or calibration equipment, though a z-shaped substrate is not necessary to generate the greater distance and other substrate shapes can be used. In the example of FIG. **45**, a square portion of substrate **4000** has been singulated to form a pre-connected sensor on the substrate **404**. In the example of FIG. **46** a square portion of substrate **4000** has been singulated to form a pre-connected sensor and an opening **4300** (e.g., an air gap) is provided in the singulated substrate **404** to improve electrical isolation between singulated contact strip portions **4001** and **4002**.

As shown in FIG. **47A**, in some implementations, an elongate substrate **4000** that forms a sensor carrier for multiple sensor **138** can be provided with a feed-guide strip **4402** that runs along an elongated edge of the elongate substrate. Feed-guide strip **4402** may include locating features **4404** that can be accessed and manipulated to move and register a strip of pre-connected sensors through one or more manufacturing stations.

In the implementation of FIG. **47A**, sensors **138** can be attached to substrate **4000** in bulk and singulated on substrate **404** after manufacturing or testing operations. As shown in FIG. **47B**, a strip of pre-connected sensors as shown in FIG. **47A** can be provided on a reel **4410** for bulk storage and/or transportation and optionally automatically pulled from the reel using feed-guide strip **4402** to be moved through one or more testing stations and/or one or more calibration stations. FIG. **48** shows a pre-connected sensor having a sensor carrier that has been singulated from substrate **4000** and separated from a singulated portion **4402** of feed-guide strip **4402**. Alternatively, feed-guide strip **4402** can be separated as a strip prior to singulation of individual pre-connected sensors. In other embodiments, the feed guide is integrated into the final product configuration and not removed from the sensor carrier during or after singulation.

FIG. **49** shows an implementation of sensor carrier **402** in which a plurality of sets of contacts **406** and **408** are formed from receptacles **4600** having a slot for receiving a corresponding plurality of sensors **138**. In some implementations, the receptacles **4600** may be an elongated member comprising a resilient or flexible material. The receptacles **4600** may have slots that optionally pierce through an insulation layer or deform a portion of the outer layer so as to make contact with the sensors **138**.

FIG. **50** shows an implementation of a sensor carrier for multiple sensors **138** having recesses **4700** that form datum features to hold each sensor in an accurate alignment and position. Complementary magnetic features may be provided on sensor **138** and substrate **404** to hold each sensor in an accurate alignment and position and thereby facilitate accurate sensor processing.

FIG. **51A** shows an implementation of an elongate substrate **4800** formed using printed circuit board technology from either a rigid, flexible, or a combination rigid/flexible

47

substrate, from which multiple sensor carriers **402** can be singulated. Flexible portion of the substrate may be manufactured from a material such as polyimide, PEEK, polyester or any suitable type. Rigid portion of the substrate may be manufactured from a material such as FR4, FR5, FR6, insulated metal substrate (IMS), PTFE, or any suitable type. As shown in FIG. 51A, each sensor carrier may include a sensor connection portion **4804** and an interface or processing portion **4802**. In some implementations, each sensor carrier may include a sensor connection portion **4804** that extends from a rigid or flexible portion and an interface or processing portion **4802** that extends from a rigid or flexible portion. In these implementations, one or more contacts, such as contacts **406** and **408** can be formed on the sensor connection portion **4804** of each sensor carrier **402**. Sensor connection portions **4804** of substrate **4800** may contain anchoring or datum features of sensor carriers **402**.

FIG. 51B shows another implementation of an elongate substrate **4800** as shown in FIG. 51A with an optional electrical connection interface **4850** for connecting to a work station, such as a testing station, a calibration station, an assembly station, a coating station, or other manufacturing stations. The optional electrical connection interface **4850** may be coupled to one or more sensor carriers **402** through electrical traces configured on one or more layers of the circuit board. As shown in FIG. 51B, a plurality of sensor carriers **402** are assembled in a panel, and each of the sensor carrier **402** may include a sensor connection portion **4804** that extends from a flexible or rigid portion and an interface or processing portion **4802** that extends from a flexible or rigid portion. In these implementations, one or more contacts, such as contacts **406** and **408** can be formed on the sensor connection portion **4804** of each sensor carrier **402**. Sensor connection portions **4804** of substrate **4800** may contain anchoring or datum features of sensor carriers **402**. In some implementations, the elongate substrate **4800** shown in FIG. 51B may be configured to allow the sensor **138** to extend beyond the edge of the substrate. This may be accomplished by removing a portion of the elongated substrate **4860** for further processing. In some embodiments a perforation (e.g. V-score, mouse bites, or other suitable type) is included in elongated substrate **4800** for enabling the removal of the bottom portion of the panel **4860** for dipping or calibration. In this implementation, the elongated substrate **4800** can be configured for dipping or calibration, as described in FIG. 52B.

Now referring to FIG. 52A, an implementation of a sensor carrier **402** is shown with one or more sensor contacts (e.g. contacts **406** and **408**) on sensor connection portion **4804** and one or more one or more interface contacts (e.g. contacts **410** and **412**) on an interface or processing portion **4802**. One or more interface contacts (e.g., **410** and **412**) may be formed on sensor carrier **402** for coupling to testing station **5002**, calibration station **5004**, and/or electronics unit **500**. In this configuration, testing and/or calibration operations can be performed by coupling portion **4802** to the testing and/or calibration equipment.

FIG. 52B shows an example panel implementation of a plurality of sensor carriers **402** with electrical connection interface **4850** for interfacing with electronics of a work station, such as a testing station, a calibration station, an assembly station, a coating station, or other manufacturing stations. The illustration of FIG. 52B shows the elongate substrate **4800** of FIG. 48B after the bottom panel portion **4860** has been removed (from the illustration of FIG. 51B) and with sensor **138** attached via one or more sensor contacts (e.g. contacts **406** and **408**). In some implementations, the

48

sensors can be permanently connected (e.g. conductive adhesive, conductive polymer, conductive ink, solder, welding, brazing, or other suitable methods) to the sensor carriers **402** and both components can be calibrated together or separately. In other implementations, the sensors can be releasably attached (e.g. via clips, metallic foil, conductive foam, conductive fabric, wire wrapping, wire threading or any other suitable methods).

Following testing and/or calibration operations, flexible portion **4802** may be folded around, folded over, wrapped around, wrapped over, or manipulated to envelope portion **4804** for installation into on-skin sensor assembly **600**. In the example of FIG. 53A, portion **4802** may form a stand-alone processing circuit for sensor **138** (e.g., an implementation of sensor electronics **112**). In other implementations, portion **4802** may be coupled directly to signal processing circuit for assembly **600**, to a system in package (SIP) implementation of the sensor electronics or a main printed circuit board for the sensor electronics. In the example of FIG. 53B, the flexible portion **4804** is folded to envelope portion **4802** for installation into on-skin sensor assembly **600** so as to have sensor **138** positionally secured to extend (e.g. through opening **4808**) for insertion for in vivo operations.

FIG. 54 shows an implementation in which sensor carrier **402** is manufactured using printed circuit board technology as a daughter board for a main printed circuit board **5100** for the sensor electronics. As shown in FIG. 54, one or more contacts such as contacts **5104** (e.g., solder contacts) may be formed between sensor carrier **402** and main PCB **5100** to form sensor electronics unit for sensor **138** in on-skin sensor assembly **600**. Conductive traces **5102** may couple contacts **5104** to sensor **138** via a conductive attachment mechanism **5103** (e.g., solder, conductive adhesive, a conductive tape, or other conductive attachment as discussed herein).

FIG. 55 shows an implementation of sensor carrier **402** in which a pinch clip **5200** is provided to close the arms **5204** of a crimp connector **5202** to secure sensor **138** to substrate **404**. Connector **5204** may be formed from a conductive material that forms one of contacts **410** and **412**. As shown in FIG. 55, pinch clip **5200** includes clamping arms **5208** with ramped surfaces that push the arms outward as pinch clip **5200** is moved toward substrate **404** in direction **5206** and snap back to secure pinch clip **5200** to substrate **404**. In other implementations, pinch clip **5200** may be provided without clamping arms **5208** so that pinch clip **5200** is removable after arms **5204** are pinched closed so that pinch clip **5200** does not form a part of the sensor carrier. As shown in FIG. 55, one or more electrode breakouts **5220** may be provided to form, for example, one or more of contacts **410** and **412** on substrate **404**. Although breakout **5220** is formed on a surface of substrate **404** that is opposed to the surface to which sensor **138** is attached in the example of FIG. 55, this is merely illustrative. It should be appreciated that breakouts for contacts such as contacts **410** and **412** may be formed on the opposing surface, on the same surface as sensor **138**, or on an edge or sidewall of substrate **404** and coupled to contacts **408** and **406** by conductive vias or other conductive layers, structures, or interconnects within or on substrate **404**. In some implementations, a pinch clip **5200** may be used to apply bias force against sensor **138** in combination with crimp connector **5202** or directly against substrate without crimp connector **5202**. Pinch clip **5202** may apply force radially, axially, or in a suitable direction to provide a biasing force on sensor **138** and conductive pathway.

FIG. 56 shows an implementation of sensor carrier **402** in which contacts **406** and **408** are formed from foldable

conductive clips **5300**. Sensor **138** may be inserted through openings **5302** in each clip **5300** and mechanically secured to substrate **404** and conductively coupled to clips **5300** by a folding a portion **5304** of each of clips **5300** over onto sensor **138**.

Portions **5304** of clips **5300** may also form contacts **410** and **412** for coupling to external equipment such as a manufacturing station (e.g., a testing station, a calibration station, an assembly station, a coating station, or other manufacturing stations). However, this is merely illustrative. In other implementations, one or more electrode breakouts that are conductively coupled to clips **5300** may be provided to form, for example, one or more of contacts **410** and **412** on substrate **404**. Such breakouts may be formed on a surface of substrate **404** that is opposed to the surface to which sensor **138** is attached, on the same surface as sensor **138**, or on an edge or sidewall of substrate **404** and coupled to clips **5300** by conductive vias or other conductive layers, structures, or interconnects within or on substrate **404**.

Clips **5300** also form datum features for positioning and aligning sensor **138** relative to substrate **404**. Substrate **404** may be sized and shaped (or may include structural features) that form anchoring features for substrate **404** relative to manufacturing stations and/or a housing of a wearable device. In this way, sensor carrier **402** may be used to easily position and align sensor **138** for both manufacturing and assembly operations (e.g., using the datum features to align the sensor relative to substrate **404** and the anchoring features to align the substrate relative to the manufacturing or wearable equipment).

The conductive components of the sensor carrier **402** in the various embodiments described herein are electrically isolated from each other and the environment when installed in on-skin sensor assembly **600**. For example, contacts **406**, **408**, **410**, and **412** may be electrically isolated from each other and the environment, using a non-conductive adhesive such as a one or two-part epoxy, using a polyurethane, using a low pressure overmolding such as a moldable polyamide or a moldable polyolefin, using an injection overmolded thermoplastic or thermoset, using a non-elastomer such as welded clamshell plastic, adhesively bonded clamshell, single or 2-sided cavity potted with sealant, e.g., epoxy, urethane, silicone, etc., or using a factory pre-compressed elastomer such as a constrained two-part cavity that holds an elastomer in a compressed state. The two-part cavity may hold the elastomer in the compressed state by a snap fit, a bonding such as an ultrasonic weld, a laser weld, a solvent bond, or a heat stake, or a mechanical fastener such as a screw, rivet, clip, or other fastener.

Illustrative operations that may be performed for manufacturing and using a pre-connected analyte sensor are shown in FIG. **57**.

At block **5400**, an analyte sensor such as analyte sensor **138** may be provided. As described herein the analyte sensor may have an elongated body (e.g., an elongated conductive body with an elongated conductive core), and a working electrode on the elongated body (e.g., at a distal end of the elongated body). The analyte sensor may also include one or more electrical contacts at a proximal end or elsewhere along the elongated body and coupled, respectively, to the working electrode and/or the reference electrode.

At block **5402**, a sensor carrier such as one of the implementations of sensor carrier **402** described herein may be attached, for example, to the proximal end of the elongated body. Attaching the sensor carrier includes coupling

one or more contacts (e.g., on a substrate) of the sensor carrier to one or more corresponding electrical contacts on the elongated body.

At block **5403**, a work station such as a manufacturing station is provided. As described herein, a manufacturing station can be configured to perform one or more dip coating processes to form the membrane **108** described above on the working electrode.

At block **5404**, the analyte sensor may be coupled to at least one testing station (e.g., testing station **5002**) by coupling the sensor carrier to circuitry of the at least one test station. Coupling the sensor carrier to the circuitry of the at least one test station may include mechanically coupling one or more anchoring features such as a substrate of the sensor carrier to a mating interface of the test station such that one or more external contacts on the substrate are coupled to one or more corresponding contacts at the test station. An identifier for the sensor on the sensor carrier may be read by the testing station. Test data obtained by the test station may be stored and/or transmitted, in association with the identifier, by the test station.

At block **5406**, the analyte sensor may be coupled to at least one calibration station (e.g., calibration station **5004**) by coupling the sensor carrier to circuitry of the at least one calibration station. Coupling the sensor carrier to the circuitry of the at least one calibration station may include mechanically coupling the one or more anchoring features such as the substrate of the sensor carrier to a mating interface of the calibration station such that one or more external contacts on the substrate is coupled to one or more corresponding contacts at the calibration station. An identifier for the sensor on the sensor carrier may be read by the calibration station. Calibration data obtained by the calibration station may be stored and/or transmitted, in association with the identifier, by the calibration station. Calibration data may be stored on the sensor carrier or transmitted for later use by an on-skin sensor assembly **600** during in vivo use of sensor **138**.

Sensor carrier **402** may be coupled to one or more additional manufacturing stations as desired. The additional manufacturing stations may include potentiostat measurement stations, sensor straightening stations, membrane dipping stations, curing stations, analyte sensitivity measurement stations, and/or inspection stations.

At block **5408**, the sensor carrier may be coupled to sensor electronics (e.g., sensor electronics **112** of electronics unit **500**) of a wearable device such as on-skin sensor assembly **600**. Coupling the sensor carrier to the sensor electronics may include coupling the one or more external contacts on the sensor carrier to corresponding contacts of the sensor electronics. In some embodiments, coupling the sensor carrier to the sensor electronics may include securing the sensor carrier between a base such as base **128** and electronics unit **500** as described herein. A reader in the on-skin sensor assembly **600** may obtain an identifier of the sensor from the sensor carrier. Calibration data for the sensor may be obtained based on the identifier.

At block **5410**, in vivo signals from the working electrode (e.g., and a reference electrode) may be obtained and processed with the sensor electronics. The in vivo signals from the working electrode (e.g., and a reference electrode) may be received by the sensor electronics from the sensor through the circuitry of the sensor carrier.

The methods disclosed herein comprise one or more steps or actions for achieving the described methods. The method steps and/or actions may be interchanged with one another without departing from the scope of the claims. In other

51

words, unless a specific order of steps or actions is specified, the order and/or use of specific steps and/or actions may be modified without departing from the scope of the claims. For example, the operations described above in connection with blocks 5404 and 5406 may be reversed and/or may be performed in parallel.

In some scenarios, it may be desirable to couple sensor 138 to one or more contacts on a substrate in a preferred position and orientation. FIG. 58 shows an exemplary apparatus 5531 in which sensor 138 is oriented to substrate 5530 using an elastomeric tube. As shown in FIG. 58, apparatus 5531 may include a substrate 5530 having one or more conductive contacts such as contacts 5532 and 5534 (e.g., exposed copper pads on a printed circuit substrate), and an elastomeric tube 5500. Elastomeric tube 5500 may be formed from a non-conductive elastomer.

As shown, elastomeric tube 5500 may be formed with a “D”, “O”, oval, pyramidal, or hemispherical shaped cross-section having an elongated cutout 5503 in the bottom portion of the elastomeric tube 5500 within which sensor 138 is disposed. In this way, sidewalls of the elongated cutout of elastomeric tube 5500 can align sensor 138 relative to substrate 5530.

Bottom portions 5502 on either side of cutout 5503 may be attached to substrate 5530. The bottom portions 5502 may be attached to substrate using adhesive 5504 such as a pressure-sensitive adhesive. The elongated opening 5501 and cutout 5503 in the elastomeric tube 5500 provides sufficient space that, in order to assemble the apparatus, tube 5500 can be placed over sensor 138 while sensor 138 is in place on substrate 5530.

FIG. 59 shows an exploded perspective view of the apparatus of FIG. 55 in which contacts 5532 and 5534 can be seen on substrate 5530. Sensor 138 may be positioned over one or more contacts such as contacts 5532 and 5534.

Sensor 138 may be loosely held within opening 5501 of tube 5500 during initial placement of the tube over the sensor, and then be fixed to the substrate 5530 by the tube when the tube is compressed (e.g., by an upper housing of a wearable device). In this way, sensor 138 may be communicatively coupled and mechanically fixed to a substrate without soldering or other bonding operations.

During manufacturing operations and/or during in-vivo use of sensor 138, sensor 138 may be held in place on substrate 404 by external compression of tube 5500. FIG. 60 shows an example in which sensor 138 is held in place by compression of tube 5500 by a housing structure. For example, housing 5700 (e.g., a housing of a wearable device or a lid or clip for a manufacturing station) may include a protruding member 5702 that, in an assembled configuration, compresses tube 5500 to secure sensor 138.

As noted above in connection with, for example, FIGS. 35B, 43, 47A, 47B, 50, and 51, during manufacturing operations, multiple sensors 138 may be carried by a common sensor carrier. However, in some scenarios, a common carrier such as an intelligent carrier may be provided for manufacturing operations for multiple pre-connected sensors. FIG. 61 shows an example of a carrier for multiple pre-connected sensors. As shown in FIG. 58, a carrier 5800 may include a housing 5802 with interfaces 5804 for multiple pre-connected sensors. Housing 5802 may be a substantially solid substrate or may be a housing that forms an interior cavity within which other components are mounted and/or connected.

Each interface 5804 may be configured to receive a sensor carrier 402 in any of the implementations described herein. For example, each interface 5804 may include one or more

52

features that interface with one or more corresponding anchoring features of a sensor carrier as described herein in accordance with various implementations. Carrier 5800 may include circuitry 5806 (e.g., one or more processors and/or memory) configured to communicate with sensors 138 and/or external computing equipment. Circuitry 5806 may include communications circuitry such as one or more antennas for transmitting and/or receiving data from external equipment. Housing 5802 may include one or more structures 5810 (e.g., clips, clasps, protrusions, recesses, notches, posts, or the like) for mechanically coupling carrier 5800 to manufacturing equipment. One or more conductive contacts 5808 may be provided on housing 5802 that communicatively couple manufacturing equipment to sensors 138 through the carrier.

As shown, each interface 5804 may be associated with a particular identification number (represented, as an example, in FIG. 58 as  $I_1, I_2, \dots, I_{N-1}$ , and  $I_N$ ). Circuitry 5806 may electronically identify sensors mounted in interfaces 5804 of carrier 5800 with the identification number associated with that interface. However, this is merely illustrative. In other implementations, sensors 138 may be uniquely identified by circuitry 5806 using a reader in each of interfaces 5804 that reads an identifier such as identifier 450 on the sensor carrier. Testing and/or calibration data may be gathered by processing circuitry 5806 and stored and/or transmitted along with an identifier for each sensor.

During manufacturing, one or more pre-connected sensors may be loaded carrier 5800. Carrier 5800 may secure the pre-connected sensors therein and perform potentiostat measurements for each sensor (e.g., using circuitry 5806). Sensors 138 may be secured to interfaces 5804 by individual mounting features or carrier 5800 may be provided with a locking mechanism such as a slidable bar 5812. Slidable bar 5812 may be slidable (e.g., by a handle 5814) between an open position as shown, in which sensor carriers can be inserted into and removed from interfaces 5804, to a closed position in which bar 5812 blocks removal of the sensor carriers from the interfaces.

In some scenarios, an initial measurement test may be performed by carrier 5800 to test the potentiostat connection through the sensor interconnect electrodes and the sensor surfaces. Manufacturing operations that may be performed for sensors 138 coupled to carrier 5800 may include physical manipulation of the sensor such as straightening of the sensors. Carrier 5800 may facilitate more efficient manufacturing by allowing multiple sensors to be straightened in a single operation using automated straightening equipment.

Carrier 5800 may facilitate potentiostat and/or other measurements at various stages of manufacturing for sensors 138. Potentiostat measurements may be performed before, during, and/or after straightening operations and information regarding sensor damage or any other mechanical stress that might be introduced by the straightening may be saved and/or transmitted along with associated sensor ID's.

Manufacturing operations that may be performed for sensors 138 coupled to carrier 5800 may also include a membrane process in which dipping operations are performed to form a membrane such as membrane 508 for each sensor. Straightened sensors 138 mounted in carrier 5800 may be concurrently dipped. Potentiostat measurements may be performed before, during, and/or after membrane operations and information associated with the electrochemistry of the sensors and dipping process may be gathered, processed, stored, and/or transmitted by carrier 5800.

Manufacturing operations that may be performed for sensors 138 coupled to carrier 5800 may also include a

53

curing process. Performing curing for groups of sensors **138** mounted in carrier **5800** may allow the curing process to take less space, which can reduce the footprint of the manufacturing area used by curing equipment. Potentiostat measurements may be performed before, during, and/or after curing operations and information associated with the electrochemistry of the sensors and curing process may be gathered, processed, stored, and/or transmitted by carrier **5800**.

Manufacturing operations that may be performed for sensors **138** coupled to carrier **5800** may also include calibration operations. Because carrier **5800** can perform connection testing early in the manufacturing process, improved analyte/electrochemical calibration can be performed by carrier **5800** itself and/or in cooperation with external manufacturing equipment. Calibration data may be gathered, processed, stored, and/or transmitted by carrier **5800**.

Gathering calibration and/or testing data with carrier **5800** can save time in connecting and disconnecting additional external equipment. Gathering calibration and/or testing data with carrier **5800**, particularly when data is gathered and stored automatically in connection with sensor ID's, can also reduce calibration/testing errors because the data is gathered by the same equipment throughout various processes.

Manufacturing operations that may be performed for sensors **138** coupled to carrier **5800** may also include analyte concentration measurements. For example, carrier **5800** may be moved by manufacturing equipment (e.g., a robotic arm) to expose the sensors **138** mounted in the carrier through various analyte baths (e.g., glucose baths). Carrier **5800** may gather electrical potential measurements during the various bath exposures. Information associated with the electrical potential measurements during the various bath exposures may be gathered, processed, stored, and/or transmitted by carrier **5800**.

Manufacturing operations that may be performed for sensors **138** coupled to carrier **5800** may also include analyte sensitivity measurements. Sensitivity measurements that may be performed by carrier **5800** may include baseline measurements that indicate the signal from each sensor without analyte exposure, slope measurements that indicate the signal change for a given amount of an analyte, and/or noise measurements. These sensitivity measurements may be stored, and/or transmitted by carrier **5800**.

Manufacturing operations that may be performed for sensors **138** coupled to carrier **5800** may also include visual inspection operations (e.g., by a technician). Providing a group of pre-connected sensors, mounted in carrier **5800**, that have already been through all of the testing/calibration/manufacturing operations described above may allow a more efficient and/or more automated visual inspection and rejection (e.g., because the exact physical location of each sensor within carrier **5800** is known). Sensors **138** that have exhibited unusual electrochemistry or mechanical stress during manufacturing operations can be flagged by carrier **5800** (e.g., using a display, a visual indicator, or transmission of flag information to an external device) for retesting or rejection.

The connections between the elements shown in some figures illustrate exemplary communication paths. Additional communication paths, either direct or via an intermediary, may be included to further facilitate the exchange of information between the elements. The communication paths may be bi-directional communication paths allowing the elements to exchange information.

54

Various operations of methods described above may be performed by any suitable means capable of performing the operations, such as various hardware and/or software component(s), circuits, and/or module(s). Generally, any operations illustrated in the figures may be performed by corresponding functional means capable of performing the operations.

The various illustrative logical blocks, modules and circuits described in connection with the present disclosure (such as the blocks of FIG. 2) may be implemented or performed with a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array signal (FPGA) or other programmable logic device (PLD), discrete gate or transistor logic, discrete hardware components or any combination thereof designed to perform the functions described herein. A processor may be a microprocessor, but in the alternative, the processor may be any commercially available processor, controller, microcontroller or state machine. A processor may also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

In one or more aspects, various functions described may be implemented in hardware, software, firmware, or any combination thereof. If implemented in software, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Computer-readable media includes both computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A storage media may be any available media that can be accessed by a computer. By way of example, and not limitation, such computer-readable media can comprise various types of RAM, ROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to carry or store desired program code in the form of instructions or data structures and that can be accessed by a computer. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, WiFi, Bluetooth®, RFID, NFC, and microwave are included in the definition of medium. Disk and disc, as used herein, includes compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray® disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Thus, in some aspects a computer readable medium may comprise non-transitory computer readable medium (e.g., tangible media). In addition, in some aspects a computer readable medium may comprise transitory computer readable medium (e.g., a signal). Combinations of the above should also be included within the scope of computer-readable media.

Certain aspects may comprise a computer program product for performing the operations presented herein. For example, such a computer program product may comprise a computer readable medium having instructions stored (and/or encoded) thereon, the instructions being executable by one or more processors to perform the operations described herein. For certain aspects, the computer program product may include packaging material.

55

Software or instructions may also be transmitted over a transmission medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of transmission medium.

Further, it should be appreciated that modules and/or other appropriate means for performing the methods and techniques described herein can be downloaded and/or otherwise obtained by a user terminal and/or base station as applicable. For example, such a device can be coupled to a server to facilitate the transfer of means for performing the methods described herein. Alternatively, various methods described herein can be provided via storage means (e.g., RAM, ROM, a physical storage medium such as a compact disc (CD) or floppy disk, etc.), such that a user terminal and/or base station can obtain the various methods upon coupling or providing the storage means to the device. Moreover, any other suitable technique for providing the methods and techniques described herein to a device can be utilized.

It is to be understood that the claims are not limited to the precise configuration and components illustrated above. Various modifications, changes and variations may be made in the arrangement, operation and details of the methods and apparatus described above without departing from the scope of the claims.

Unless otherwise defined, all terms (including technical and scientific terms) are to be given their ordinary and customary meaning to a person of ordinary skill in the art, and are not to be limited to a special or customized meaning unless expressly so defined herein. It should be noted that the use of particular terminology when describing certain features or aspects of the disclosure should not be taken to imply that the terminology is being re-defined herein to be restricted to include any specific characteristics of the features or aspects of the disclosure with which that terminology is associated. Terms and phrases used in this application, and variations thereof, especially in the appended claims, unless otherwise expressly stated, should be construed as open ended as opposed to limiting. As examples of the foregoing, the term 'including' should be read to mean 'including, without limitation,' 'including but not limited to,' or the like; the term 'comprising' as used herein is synonymous with 'including,' 'containing,' or 'characterized by,' and is inclusive or open-ended and does not exclude additional, unrecited elements or method steps; the term 'having' should be interpreted as 'having at least;' the term 'includes' should be interpreted as 'includes but is not limited to;' the term 'example' is used to provide exemplary instances of the item in discussion, not an exhaustive or limiting list thereof; adjectives such as 'known', 'normal', 'standard', and terms of similar meaning should not be construed as limiting the item described to a given time period or to an item available as of a given time, but instead should be read to encompass known, normal, or standard technologies that may be available or known now or at any time in the future; and use of terms like 'preferably,' 'preferred,' 'desired,' or 'desirable,' and words of similar meaning should not be understood as implying that certain features are critical, essential, or even important to the structure or function of the invention, but instead as merely intended to highlight alternative or additional features that may or may not be utilized in a particular embodiment of the

56

invention. Likewise, a group of items linked with the conjunction 'and' should not be read as requiring that each and every one of those items be present in the grouping, but rather should be read as 'and/or' unless expressly stated otherwise. Similarly, a group of items linked with the conjunction 'or' should not be read as requiring mutual exclusivity among that group, but rather should be read as 'and/or' unless expressly stated otherwise.

Where a range of values is provided, it is understood that the upper and lower limit and each intervening value between the upper and lower limit of the range is encompassed within the embodiments.

With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations may be expressly set forth herein for sake of clarity. The indefinite article "a" or "an" does not exclude a plurality. A single processor or other unit may fulfill the functions of several items recited in the claims. The mere fact that certain measures are recited in mutually different dependent claims does not indicate that a combination of these measures cannot be used to advantage. Any reference signs in the claims should not be construed as limiting the scope.

It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases "at least one" and "one or more" to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles "a" or "an" limits any particular claim containing such introduced claim recitation to embodiments containing only one such recitation, even when the same claim includes the introductory phrases "one or more" or "at least one" and indefinite articles such as "a" or "an" (e.g., "a" and/or "an" should typically be interpreted to mean "at least one" or "one or more"); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of "two recitations," without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to "at least one of A, B, and C, etc." is used, in general such a construction is intended in the sense one having skill in the art would understand the convention, e.g., as including any combination of the listed items, including single members (e.g., "a system having at least one of A, B, and C" would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to "at least one of A, B, or C, etc." is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., "a system having at least one of A, B, or C" would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that virtually any disjunctive word and/or phrase presenting two or more alternative



terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms. For example, the phrase “A or B” will be understood to include the possibilities of “A” or “B” or “A and B.”

All numbers expressing quantities of ingredients, reaction conditions, and so forth used in the specification are to be understood as being modified in all instances by the term ‘about.’ Accordingly, unless indicated to the contrary, the numerical parameters set forth herein are approximations that may vary depending upon the desired properties sought to be obtained. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of any claims in any application claiming priority to the present application, each numerical parameter should be construed in light of the number of significant digits and ordinary rounding approaches.

All references cited herein are incorporated herein by reference in their entirety. To the extent publications and patents or patent applications incorporated by reference contradict the disclosure contained in the specification, the specification is intended to supersede and/or take precedence over any such contradictory material.

Headings are included herein for reference and to aid in locating various sections. These headings are not intended to limit the scope of the concepts described with respect thereto. Such concepts may have applicability throughout the entire specification.

Furthermore, although the foregoing has been described in some detail by way of illustrations and examples for purposes of clarity and understanding, it is apparent to those skilled in the art that certain changes and modifications may be practiced. Therefore, the description and examples should not be construed as limiting the scope of the invention to the specific embodiments and examples described herein, but rather to also cover all modification and alternatives coming with the true scope and spirit of the invention.

Various system and methods described may be fully implemented and/or controlled in any number of computing devices. Typically, instructions are laid out on computer readable media, generally non-transitory, and these instructions are sufficient to allow a processor in the computing device to implement the method of the invention. The computer readable medium may be a hard drive or solid state storage having instructions that, when run, are loaded into random access memory. Inputs to the application, e.g., from the plurality of users or from any one user, may be by any number of appropriate computer input devices. For example, users may employ a keyboard, mouse, touchscreen, joystick, trackpad, other pointing device, or any other such computer input device to input data relevant to the calculations. Data may also be input by way of an inserted memory chip, hard drive, flash drives, flash memory, optical media, magnetic media, or any other type of file-storing medium. The outputs may be delivered to a user by way of a video graphics card or integrated graphics chipset coupled to a display that maybe seen by a user. Alternatively, a printer may be employed to output hard copies of the results. Given this teaching, any number of other tangible outputs will also be understood to be contemplated by the invention. For example, outputs may be stored on a memory chip, hard drive, flash drives, flash memory, optical media, magnetic media, or any other type of output. It should also be noted that the invention may be implemented on any number of different types of computing devices, e.g., personal computers, laptop computers, notebook computers, net book computers, handheld computers, personal digital assistants,

mobile phones, smart phones, tablet computers, and also on devices specifically designed for these purpose. In one implementation, a user of a smart phone or wi-fi-connected device downloads a copy of the application to their device from a server using a wireless Internet connection. An appropriate authentication procedure and secure transaction process may provide for payment to be made to the seller. The application may download over the mobile connection, or over the WiFi or other wireless network connection. The application may then be run by the user. Such a networked system may provide a suitable computing environment for an implementation in which a plurality of users provide separate inputs to the system and method. In the below system where factory calibration schemes are contemplated, the plural inputs may allow plural users to input relevant data at the same time.

What is claimed is:

1. A wearable device for measuring an analyte concentration in a host, the wearable device comprising:

a housing;

a transcutaneous analyte sensor comprising:

an in vivo portion configured to be inserted in a living body of a host during a sensor session, wherein the in vivo portion comprises an electrode, wherein the electrode is configured to generate a signal indicative of an analyte concentration; and

an ex vivo portion configured to remain outside the living body of the host during the sensor session;

a substrate located in the housing, wherein the substrate comprises:

a first portion; and

a second portion, wherein the second portion is folded over the first portion; and

sensor electronics operably connected to the transcutaneous analyte sensor, wherein the sensor electronics is configured to process the signal generated by the electrode, wherein at least a portion of the sensor electronics is located on the first portion of the substrate.

2. The wearable device of claim 1, wherein the substrate comprises a foldable portion positioned between and connecting the first portion of the substrate to the second portion of the substrate.

3. The wearable device of claim 2, wherein the foldable portion of the substrate has a width that is less than a width of both the first portion of the substrate and the second portion of the substrate.

4. The wearable device of claim 1, wherein the first portion comprises an opening, and wherein the transcutaneous analyte sensor extends into the opening.

5. The wearable device of claim 1, wherein the first portion of the substrate is substantially parallel to the second portion of the substrate when the second portion of the substrate is folded over the first portion of the substrate.

6. The wearable device of claim 1, wherein the first portion of the substrate lies in a common plane with the second portion of the substrate when the substrate is in an unfolded state.

7. The wearable device of claim 1, wherein the substrate comprises a flexible circuit board.

8. The wearable device of claim 1, wherein the sensor electronics comprises a battery, a processor, conductive traces, and wireless communication circuitry.

9. The wearable device of claim 8, wherein a portion of the sensor electronics is located on the second portion of the substrate.

10. The wearable device of claim 9, wherein the portion of the sensor electronics is the conductive traces.

59

11. The wearable device of claim 1, wherein the sensor electronics comprises interface circuitry, and wherein the interface circuitry is configured to connect to calibration equipment during manufacture.

12. The wearable device of claim 11, wherein the interface circuitry is configured to connect to traces on a test panel circuit board during manufacture.

13. The wearable device of claim 12, wherein the substrate is configured to be integrally connected to the test panel circuit board during manufacture.

14. The wearable device of claim 1, wherein the transcutaneous analyte sensor is removably attached to the substrate.

15. The wearable device of claim 1, wherein the sensor electronics is configured to wirelessly transmit sensor data to an external device.

16. The wearable device of claim 1, comprising an electrical contact, wherein the transcutaneous analyte sensor is operably connected to the sensor electronics via the electrical contact.

17. The wearable device of claim 16, wherein the electrical contact is attached to the substrate.

18. The wearable device of claim 17, wherein the electrical contact is located in or on a sensor carrier.

19. A method for manufacturing a wearable device, the method comprising:

providing a substrate in a first state, wherein the substrate comprises a first portion and a second portion, wherein at least a portion of sensor electronics is located on the first portion of the substrate, wherein the sensor electronics are configured to process a signal generated by an electrode during a sensor session, and wherein the signal is indicative of an analyte concentration;

operably connecting a transcutaneous analyte sensor to the sensor electronics, wherein the transcutaneous analyte sensor comprises:

an in vivo portion configured to be inserted in a living body of a host during a sensor session, wherein the in vivo portion comprises the electrode; and  
an ex vivo portion configured to remain outside the living body of the host during the sensor session,

60

wherein the ex vivo portion of the transcutaneous analyte sensor is operably connected to the sensor electronics; and

transforming the substrate from the first state to a second state, wherein the transforming is performed by folding the substrate, wherein in the second state, the second portion is folded over the first portion.

20. The method of claim 19, comprising placing the transformed substrate into a housing.

21. The method of claim 20, comprising placing a portion of the transcutaneous analyte sensor into an opening in the substrate.

22. The method of claim 21, comprising placing a portion of the transcutaneous analyte sensor through an opening in the housing.

23. The method of claim 22, wherein the transforming comprises folding the substrate at a foldable portion having a width that is less than both the first portion and the second portion.

24. The method of claim 19, comprising connecting the sensor electronics to calibration equipment when the substrate is in the first state.

25. The method of claim 24, comprising detaching the substrate from a test panel when the substrate is in the first state.

26. The method of claim 19, comprising singulating the substrate away from an array of other substrates.

27. The method of claim 19, comprising attaching the transcutaneous analyte sensor to the substrate.

28. The method of claim 27, comprising attaching the transcutaneous analyte sensor to the substrate via a sensor module.

29. The method of claim 19, wherein transforming the substrate from the first state to the second state comprises folding the substrate from a common plane into a pair of substantially parallel planes.

30. The method of claim 19, wherein the substrate comprises a flexible circuit board.

\* \* \* \* \*