

PETITIONER LIFECORE'S DEMONSTRATIVES

*LIFECORE FITNESS, LLC D/B/A ASSAULT FITNESS V.
WOODWAY USA, INC.*

IPR2023-00836 (PATENT 9,039,580 B1)

IPR2023-00843 (PATENT 10,561,884 B2)


IPR2023-00849 (PATENT 10,799,745 B2)

ORAL ARGUMENT: JULY 24, 2024

CONTAINS CONFIDENTIAL INFORMATION SUBJECT TO PROTECTIVE ORDER

Woodway Patent Family

PRV	61/161,027 - 17MAR2009	
PCT	PCT/US2010/027543 - 16MAR2010 WO2010/107840 - 23SEPT2010	
CIP	CIP - Abandoned 13/235,065 - 16SEPT2011 US2012/0010053 - 12JAN2012	
	14/243,716 - 2APRIL2014 US8,986,169	14/076,912 - 11NOV2013 US9,114,276
	14/656,942 - 13MAR2015 US9,039,580 - 26MAY2015	14/832,708-21AUG2015 US10,265,566
		15/958,339 - 20APRIL2018 US10,561,884 - 18FEB2020
		15/957,721-19APRIL2018 US10,561,883
	16/792,426 - 17FEB2020 US10,799,745 - 13OCT2020	16/792,444-17FEB2020 US10,850,150
		17/247,101-30NOV2020 US11,465,005-11OCT2022



| The Challenged Claims are Similar in Scope

Patent Owner:

Indeed, a side-by-side comparison of the '580 Patent independent claims challenged in the Petition and exemplary independent claims of the '745 Patent illustrates the relevant similarities in scope:

Challenged '580 Patent Claims (EX1001) (emphasis added)	Exemplary '745 Patent Claims (EX2003) (emphasis added)
<p>1. A manually powered treadmill comprising:</p> <p><u>a frame</u> having a front end and a rear end positioned opposite the front end;</p> <p>a front shaft rotatably coupled to the frame at the front end;</p> <p>a rear shaft rotatably coupled to the frame at the rear end;</p> <p>a first bearing rail having a plurality of bearings, the first bearing rail attached to a left side of the frame;</p>	<p>1. A treadmill, comprising:</p> <p><u>a frame</u>:</p> <p>a front running belt pulley coupled to the frame;</p> <p>a rear running belt pulley coupled to the frame and spaced a distance from the front running belt pulley;</p> <p>a plurality of bearings coupled to the frame;</p> <p><u>a running belt</u> at least partially supported by at least one of the front</p>

IPR Grounds

836 IPR / 580 Patent:
(Chickering & Socwell)

Ground	Basis ²	References	Claims Challenged
1	§ 103	Chickering and Magid	1-5, 10-11, 14, 18, and 25
2	§ 103	Chickering, Magid, and Sclater	6-9 and 12
3	§ 103	Chickering, Magid, and Sclater	1-12, 14, and 18
4	§ 103	Socwell and Magid	1-5, 10-11, 14, 15, 18, and 25
5	§ 103	Socwell, Magid, and Sclater	6-9 and 12
6	§ 103	Socwell, Magid, and Sclater	1-12, 14-15, 18 and 25

843 IPR / 884 Patent:
(Schonenberger & Chickering)

Ground	Basis ²	References	Claims Challenged
1	§ 103	Schonenberger, Socwell, Magid, and Sclater	30-34, 37-43, 45-50, 52-54, 57, 59
2	§ 103	Schonenberger, Socwell, Magid, Sclater, and Skowronski	44, 51
3	§ 103	Schonenberger, Socwell, Magid, and Sclater	30-34, 37-54, 57, 59
4	§ 103	Chickering, Magid, and Sclater	30-34, 37-39, 41, 45-49, 57, 59

849 IPR / 745 Patent:
(Schonenberger & Socwell)

Ground	Basis ²	References	Claims Challenged
1	§ 103	Schonenberger, Socwell, Magid, and Sclater	1, 4, 7-12, 14, 17-18, and 20-27
2	§ 103	Schonenberger, Socwell, Magid, and Sclater	1, 4, 7-12, 14, 17-18, and 20-27
3	§ 103	Socwell, Magid, and Sclater	1, 4, 7-12, 14, 17-18, and 20-25

*Claim Construction

580 Pat. Disputed Limitations: Chickering & Socwell Grounds

1. A manually powered treadmill comprising:
a frame having a front end and a rear end positioned opposite the front end;
a front shaft rotatably coupled to the frame at the front end;
a rear shaft rotatably coupled to the frame at the rear end;
a first bearing rail having a plurality of bearings, the first bearing rail attached to a left side of the frame;
a second bearing rail having a plurality of bearings, the second bearing rail attached to a right side of the frame;
a running belt supported by the first bearing rail and the second bearing rail and disposed about the front shaft and the rear shaft, wherein the running belt follows a curved running surface; and
a safety device coupled to at least one of the front shaft and the rear shaft, wherein the safety device is structured to substantially prevent rotation of at least one of the front shaft and the rear shaft in a first rotational direction while permitting rotation of the at least one of the front shaft and the rear shaft in a second rotational direction opposite the first rotational direction.

25. A method, comprising:
providing a manually powered treadmill, the manually powered treadmill having a frame with a front end and rear end;
providing a first bearing rail and a second bearing rail, the first and second bearing rails each comprising a plurality of bearings and extending longitudinally on the frame, wherein the first and second bearing rails define a curved top profile;
disposing a running belt on the plurality of bearings of the first bearing rail and the second bearing rail such that the running belt follows a top curved running surface corresponding to the curved top profile of the first and second bearing rails;
permitting movement of the running belt in a first direction;
and
substantially preventing movement of the running belt in a second direction opposite the first direction.

Disputed Limitations: Chickering & Socwell Grounds

'884 Patent:

37. A manually powered treadmill, comprising:
a frame;
a first plurality of bearings coupled to the frame;
a second plurality of bearings coupled to the frame and spaced a distance from the first plurality of bearings;
a front shaft assembly coupled to the frame;
a rear shaft assembly coupled to the frame;
a running belt at least partially supported by the first plurality of bearings and the second plurality of bearings, the running belt being at least partially disposed about the front and rear shaft assemblies, and comprising a running surface, at least a portion of which is curved; and
a safety device coupled to the frame and the running belt, the safety device having a first rotatable element and a second rotatable element, wherein at least one of the first and second rotatable elements are adapted for rotation relative to the frame;
wherein one of the first and second rotatable elements of the safety device and the running belt freely rotate relative to the other of the one of the first and second rotatable elements of the safety device in a first direction of rotation relative to the frame, however, in a second direction of rotation, opposite the first direction of rotation, interference between the safety device and at least one of the first rotatable element and the second rotatable element substantially prevents rotation of the running belt and the one of the first and second rotatable elements relative to the other of the one of the first and second rotatable elements.

'745 Patent:


18. A method, comprising:
providing a treadmill having a frame with a front end and a rear end;
providing a plurality of bearings coupled to the frame, wherein the plurality of bearings define at least a portion of a curved top profile;
disposing a running belt on the plurality of bearings such that the curved top profile of the plurality of bearings define at least a portion of a curved running surface of the running belt;
providing a first safety race element coupled to the frame and to the running belt and a second safety race element coupled to the frame, wherein at least one of the first and second safety elements is adapted for rotation relative to the frame, and wherein one of the first and second safety race elements substantially surrounds the other of the one of the first and second safety race elements;
permitting rotation of one of the first and second safety race elements and the running belt in a first direction of rotation; and
substantially preventing rotation of the running belt in a second direction, opposite the first direction, by, at least in part, the one of the first and second safety race elements.

Overview

1. State of the Art
2. Prosecution History
3. Claim Construction
4. Chickering discloses: a) *"curved running surface"* and b) bearing rails that *"define a curved top profile"*
5. Socwell discloses: a) *"plurality of bearings,"* b) *"a running belt" "supported by"* the bearing rails and c) *"disposing"* a running belt *"on"* the bearings
6. Rationale to Combine (R/C) with Magid
7. R/C: Substitute Sclater for Magid
8. R/C: Modify Schonenberger in view of Socwell
9. Skowronski discloses a pulley *"formed from an electrically insulating material"*
10. Secondary Considerations


PO's manual treadmill technology was well-known

Schmidt:




Ex. 1009, Fig. 1

Chickering:




Ex. 1013, Fig. 3

Socwell:



Ex. 1011, Fig. 1

Schonenberger:



Ex. 1010, Fig. 1

Treadmill safety concerns were well known

Chickering:

A person exercising on this type of treadmill is likely to lose his balance because the frictionless surface offers no resistance to the movement of his feet, and he is therefore unable to obtain the leverage necessary for proper balance. Also, the user is likely to run off the lower end of the treadmill because the faster he runs the faster the belt accelerates and moves beneath his feet, carrying him to the rear.

Ex. 1013, 1:30-33

Socwell:

In particular, if the rollers supportably disposed in relation to the endless belt are so easily movable, the user may potentially lose his equilibrium or balance and fall from the exercise treadmill resulting in possible injuries.

Ex. 1011, 1:32-38

ISO 20957:

5.8 Side handrails/front handlebar

Treadmills shall be equipped with side handrails or front handlebar for user support and emergency dismount. Ex. 1020 at 8

treadmill



training equipment with a unidirectional moving surface on which a walking or running activity can take place, where the feet are free to leave the moving surface Ex. 1020 at 4

One-way bearings/clutches were also well known

Emerson:



Ex. 1018, 1, 8



III. Backstopping

In backstop (holdback) applications, the clutches are used to prevent reverse rotation of drive shafts, which could damage machinery and other expensive equipment. With the outer race of the clutch anchored to a stationary member, the inner race can overrun freely in one direction of rotation; reverse rotation is prevented by the automatic engagement of the clutch. Typical backstop applications occur in conveyor systems and gear reducers.

Dr. Blair:


So they may use it to educate themselves on principles of operations on how they work.

Ex. 1038, 89:12-19


“Commercially available and inexpensive sprag-type clutches . . . require less design and qualification work to implement”

Dr. Giachetti, 836 IPR: Ex. 1036, ¶69

Emerson:




NSS Series
Models NSS-8 - NSS-60




The NSS Series clutch is available in 12 sizes and is designed with the same overall dimensions as a light metric series ball bearing. The inner race offers a key seat and the outer race press fits into the housing. The clutch is furnished with protective oil and must be lubricated before operating. These clutches do not have bearings to support radial force, so additional bearing support is required. The NSS Series clutch is excellent for applications where space is restricted, and is suitable for overrunning.

Lubrication

- 1. Oil lubrication is recommended.
- 2. Do not use greases or lubricants with EP additives.



NSS Series
Models NSS-8 - NSS-60



Features

- Sprag type one way clutch
- High torque and longer life than roller ramp clutches
- Full metric design
- Overrunning speed is higher than roller ramp clutches

Industries Served

- Food and beverage
- Gearing
- Printing
- Textile

Field Applications

- Exercise equipment
- Food processing equipment
- Printing presses
- Pulp conveyors

Dimensions

Model Number	Dimensions												Weight	
	A		B		C		D		E		F		G	H
in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm			
NSS-8	0.315	8	0.315	8	0.315	8	0.315	8	0.315	8	0.315	8	0.005	0.13
NSS-10	0.354	9	0.354	9	0.354	9	0.354	9	0.354	9	0.354	9	0.005	0.15
NSS-12	0.393	10	0.393	10	0.393	10	0.393	10	0.393	10	0.393	10	0.005	0.17
NSS-14	0.431	11	0.431	11	0.431	11	0.431	11	0.431	11	0.431	11	0.005	0.19
NSS-16	0.469	12	0.469	12	0.469	12	0.469	12	0.469	12	0.469	12	0.005	0.21
NSS-18	0.508	13	0.508	13	0.508	13	0.508	13	0.508	13	0.508	13	0.005	0.23
NSS-20	0.547	14	0.547	14	0.547	14	0.547	14	0.547	14	0.547	14	0.005	0.25
NSS-22	0.585	15	0.585	15	0.585	15	0.585	15	0.585	15	0.585	15	0.005	0.27
NSS-24	0.623	16	0.623	16	0.623	16	0.623	16	0.623	16	0.623	16	0.005	0.29
NSS-26	0.661	17	0.661	17	0.661	17	0.661	17	0.661	17	0.661	17	0.005	0.31
NSS-28	0.699	18	0.699	18	0.699	18	0.699	18	0.699	18	0.699	18	0.005	0.33
NSS-30	0.737	19	0.737	19	0.737	19	0.737	19	0.737	19	0.737	19	0.005	0.35
NSS-32	0.775	20	0.775	20	0.775	20	0.775	20	0.775	20	0.775	20	0.005	0.37
NSS-34	0.813	21	0.813	21	0.813	21	0.813	21	0.813	21	0.813	21	0.005	0.39
NSS-36	0.851	22	0.851	22	0.851	22	0.851	22	0.851	22	0.851	22	0.005	0.41
NSS-38	0.889	23	0.889	23	0.889	23	0.889	23	0.889	23	0.889	23	0.005	0.43
NSS-40	0.927	24	0.927	24	0.927	24	0.927	24	0.927	24	0.927	24	0.005	0.45
NSS-42	0.965	25	0.965	25	0.965	25	0.965	25	0.965	25	0.965	25	0.005	0.47
NSS-44	1.003	26	1.003	26	1.003	26	1.003	26	1.003	26	1.003	26	0.005	0.49
NSS-46	1.041	27	1.041	27	1.041	27	1.041	27	1.041	27	1.041	27	0.005	0.51
NSS-48	1.079	28	1.079	28	1.079	28	1.079	28	1.079	28	1.079	28	0.005	0.53
NSS-50	1.117	29	1.117	29	1.117	29	1.117	29	1.117	29	1.117	29	0.005	0.55
NSS-52	1.155	30	1.155	30	1.155	30	1.155	30	1.155	30	1.155	30	0.005	0.57
NSS-54	1.193	31	1.193	31	1.193	31	1.193	31	1.193	31	1.193	31	0.005	0.59
NSS-56	1.231	32	1.231	32	1.231	32	1.231	32	1.231	32	1.231	32	0.005	0.61
NSS-58	1.269	33	1.269	33	1.269	33	1.269	33	1.269	33	1.269	33	0.005	0.63
NSS-60	1.307	34	1.307	34	1.307	34	1.307	34	1.307	34	1.307	34	0.005	0.65

Model Number	Torque Capacity		Maximum Overrunning Speed		Drag Torque		Bore Size H7				Keyway		Dimensions	
			Inner Race	Outer Race									A	
	lb - ft	N-m	rpm	rpm	lb - ft	N-m	Inches		mm		Inches	mm	Inches	mm
NSS-8	4.9	6.7	6,000	3,000	0.004	0.005	0.3150	+0.0006 -0.000	8	+0.015 -0.000	0.08 x 0.04	2 x 1.0	0.315	8
NSS-10	8.9	12.0	4,500	2,300	0.005	0.007	0.3937	+0.0006 -0.000	10	+0.015 -0.000	0.12 x 0.06	3 x 1.4	0.354	9

Ex. 1018, 52-53

Ex. 1038, 89:20-90:12

State of the Art: One-Way Bearing Clutch

“A POSA would have considered a sprag-type one-way clutch bearing for an exercise equipment application, such as a treadmill”

Dr. Giachetti, 836 IPR, Ex. 1036, ¶275


Emerson:

Dr. Blair:

Q So based on the description on page 48 that this is serving the fitness industry and exercise equipment field applications, would a person of ordinary skill in the art have considered these one-way bearings for treadmills?

A If they -- if the person of ordinary skill in the art had already identified the need that a one-way bearing fulfills, then they would potentially -- they'd be drawn to -- they would certainly be drawn to this -- or this particular product because it calls it out as an application for it.

Ex. 1038, 89:20-90:12



Ex. 1018, 48

Ex. 1018, 53

A POSA would have used the Emerson catalog to find a solution for “[p]reventing motion in the unintended direction” on “a curved manual treadmill.”

Dr. Blair:

Q What's the reason for including the Morris KK
clutch or something like the Morse KK clutch in a
curved manual treadmill?

A The direction. Preventing motion in the unintended
direction.

Ex. 1038, 105:8-12

Examination focused on the "safety device" limitations

580 Patent: Allowable Subject Matter

The following is an examiner's statement of reasons for allowance:

* * *

1,211,765 (Schmidt). However, the prior art lacks the same in combination with a pair of bearing rails, each bearing rail comprising a plurality of bearings, the bearing rails supporting the running belt, and a safety device associated with one of the shafts to prevent that shaft and the running belt from rotating one direction while allowing free rotation in the opposite direction.

836 IPR, Ex. 1002 at 189

745 Patent: Reasons for Allowance

In particular, the cited references do not disclose a treadmill as claimed, and in particular having the newly added limitations of a safety device having first and second race elements, one of which surrounds the other, the safety device permitting rotation in a first direction and preventing rotation in a second direction.

849 IPR, Ex. 1002 at 233

884 Patent:

38. (Currently Amended) A manually powered treadmill, comprising:

* * *

a safety device coupled to the frame and the running belt, the safety device having a first rotatable element and a second rotatable element, wherein at least one of the first and second rotatable elements are adapted for rotation relative to the frame;

wherein one of the first and second rotatable elements of the safety device and the running belt freely rotate relative to the other of the one of the first and second rotatable elements of the safety device ~~when the first element of the safety device rotates~~ in a first direction of rotation relative to the frame, however, in a second direction of rotation, opposite the first direction of rotation, interference between the safety device and at least one of the first rotatable element and the second rotatable element of the safety device substantially prevents rotation of the running belt and the one of the first and second rotatable elements relative to the other of the one of the first and second rotatable elements of the safety device and the running belt relative to the frame.

843 IPR, Ex. 1002 at 2270-71

Claim Construction

Substantially prevent[]:

Instead, to better align with both, the Court construes the claim term “substantially prevents” as “restricts rotation to allow for only one rotational direction of movement.”⁵

Ex. 1033, 16

Shaft:

For the above reasons, the Court rejects Defendant’s proposed construction for the term “shaft.” Because it agrees with Plaintiff that the term has a widely used and unambiguous meaning, it adopts Plaintiff’s proposal that the term be given its plain and ordinary meaning.

Ex. 1033, 27

Safety Device (580 Patent):

For the above reasons, the Court construes the claim term “safety device” in the ’580 Patent as a means-plus-function claim limitation with the corresponding structure as a one-way bearing assembly, a cam locking system, a taper lock, a user operated pin system, or a band brake system with a lever.

Ex. 1033, 22

Safety Device (884, 745 Patents):

Accordingly, the Court construes the term “safety device” in the ’884 Patent and the ’745 Patent as “a device that includes the elements recited and restricts rotation to allow for only one rotational direction of movement.”

Ex. 1033, 23

PO improperly attempts to read limitations from the specification into the claims

Thorner v. Sony Computer Entm't Am. LLC, 669 F.3d 1362, 1367 (Fed. Cir. 2012)


580 Patent:

The running belt 16 contacts and is supported in part by the bearings 208 of the bearing rails and bearing 208 are configured to rotate, thereby decreasing the friction experienced by the running belt 16 as the belt moves along the top profile 210.

Ex. 1001, 11:58-60

580 Patent re "bearing":

One-Way Bearing Assembly




Ex. 1001, Fig. 36

580 Patent re "disposed on":

The endless belts 226 are shown disposed on opposite sides of the running belt 16, generally interior to the outer, lateral edge of the slats 228.

Ex. 1001, 14:6-9



836 IPR: Ex. 1001, Fig. 6, Reply, 6

Chickering discloses a running belt that follows a "curved running surface"


580 Pat. Claims [1.6], [11.6][b], [25.3]
884 Pat. Claims [30.5], [37.6], [57.3]

Chickering discloses a "curved running surface."

Chickering:

Thus, when the endless belt 28 is placed about the rollers, it follows their contour and provides a forward accelerating area and a rear decelerating area which are inclined from the horizontal with each being lowest at their point of nearest proximity.

Ex. 1013, 3:6-10, Fig. 3



843 IPR: Pet. 84, Ex. 1003, ¶369

Dr. Giachetti:

161. Chickering discloses "a single endless belt 28" that is disposed about the rollers 29, including the front roller 29b and the rear roller 29a, which collectively form a curved running surface:

Ex. 1003, ¶161

Dr. Blair:

Well, the running belt would be bending in a very, very small curve at that point to follow those trajectories, the two planes.

Ex. 1038, 24:23-25

Chickering discloses "first and second bearing rails [that] define a curved top profile"


580 Pat. Claim [25.2][c]

Claim 25 does not require that the bearing rails are formed in a curved shape


580 Patent:

FIGS. 7b-7h illustrate the side profiles of some exemplary non-planar, contoured running surfaces according to the innovations disclosed herein, each including a front portion, a central portion, and a rear portion. Each portion has a particular geometric configuration that is concave, convex, or linear; collectively, the portions define the non-planar running surface.

Dr. Giachetti:



Ex. 1003, ¶162, Fig. 3



According to another exemplary embodiment, a linear portion may replace all or a portion of the curve. Alternatively, multiple linear portions may be included in a profile of a non-planar surface.

Ex. 1001, Figs. 7i-7j, 9:26-32, 10:33-35



836 IPR Ex. 1003, ¶349

As shown, the curved deck treadmill 10 comprises a support frame 12 having a first side 20 and a second opposing side 22 and having a deck 56 supportably disposed therebetween.

Referring now to FIG. 5, the curved deck treadmill 10 may include one or more belt securing assemblies 94 which provide a means for retaining the endless belt 16 in a curvilinear configuration being substantially flush with the upper surface 66 of the deck 56. Preferably, the belt securing

* * *

In one presently preferred embodiment of the present invention, the belt securing assembly 94 comprises a roller 98 having an axle 100 which rotatably engages a mounting bracket 96. The mounting bracket 96 is preferably disposed in relation to the roller 98 such that the roller 98 may engage the belt 16, thereby substantially retaining a side portion of the belt 16 substantially flush with the deck 56. Ex. 1011, 10:5-9, 10:17-23



Socwell discloses "a running belt" "supported by" the bearing rails

580 Patent claims [1.6], [11.6][a]

"The bolt that is used to fasten the cover members 168 'bearing rails' to the treadmill transmits the force from the frame members 168 to the belt, so that the belt is supported and held in place between the deck 56 and the rollers 98."

Dr. Giachetti, 836 IPR Ex. 1036, ¶41

Dr. Giachetti:

351. As illustrated in Figure 5 above, the right cover member 168 ("second bearing rail") includes a vertical side 106 disposed against the right frame side 20

* * *

18:7-10, 10:56-60.) The cover member 168 that supports the belt securing assemblies 94, including the rollers 98, is attached to the frame 12 using bolts 118.

The bolts 118 may also extend through apertures formed through the deck 66 to attach the deck to the frame 12:


Ex. 1003, ¶351

Dr. Giachetti (Dep. Tr.):

A. It's like a sandwich. So the bolt, which is the cover member, and it all holds everything together.

Ex. 2022, 8:23-25

Socwell:




Socwell discloses "disposing" a running belt "on" the bearings


580 Pat. Claim [25.3]
745 Pat. Claim [18.3]

The running belt is disposed on the deck 36 and rollers 98 which collectively provide the "plurality of bearings."

Socwell:



Ex. 1011, Fig. 3



Ex. 1011, Fig. 5


"It would have been obvious to a POSA to combine the manual curved treadmill disclosed in Chickering [Socwell, or Modified-Schonenberger] with the known technique of a one-way clutch to prevent belt motion in a forward direction as disclosed in Magid."

Dr. Giachetti, 836 IPR, Ex. 1003, ¶¶230, 425 | 843 IPR, Ex. 1003, ¶¶187, 432 | 849 IPR, Ex. 1003, ¶¶175, 336


Magid:

A unidirectional control means 6, 6' is installed to permit only unidirectional movement of the left and right foot belts 4, 4'. In this embodiment, the control means 6, 6' includes a


Ex. 1012, 4:46-55



Chickering:



Ex. 1013, Fig. 3




Ex. 1013, Fig. 3

Rationale to combine Sclater and Magid, with Chickering, Socwell, or Modified-Schonenberger


“A POSA would have been motivated to substitute **Sclater**’s one-way sprag-type bearing assembly for Magid’s ratchet-and-pawl one-way mechanism to obtain predictable results, e.g., reduced noise and improved durability.”

Dr. Giachetti, 836 IPR, Ex. 1003, ¶¶271, 465 | 843 IPR, Ex. 1003, ¶¶207, 443 | 849 IPR, Ex. 1003, ¶¶187, 348


Sclater:



Ex. 1017 at 316




Ex. 1017 at 320




Modified Schonenberger has a curved running surface supported by rollers 12 (“bearings”) arranged in a curved profile

Schonenberger:




Ex. 1010, Fig. 10 (cropped)



Ex. 1010, Fig. 12

Socwell:



Ex. 1011, Fig. 3


Modified Schonenberger:



Ex. 1010, Fig. 1


Modified Schonenberger “is actually similar in shape to . . . Socwell”

Socwell:



849 IPR, POR, 26

Modified Schonenberger:



Ex. 1010, Fig. 1 (Modified)
849 IPR Pet. 41.

Dr. Blair:

However, that surface on the left figure at the top of page 77 is actually similar in shape to the Socwell reference.

849 IPR, Ex. 1040, 44:11-13; Ex. 2018, ¶134

A POSA would have been motivated to “combine the flat manual treadmill topology of Schonenberger with the curved manual treadmill topology of Socwell to increase safety and reduce impact loading of the user’s joints”

Dr. Giachetti, 843 IPR, Ex. 1003, ¶168 | 849 IPR, Ex. 1003, ¶148

Socwell:

It is a still further object of the present invention to provide a curved deck treadmill which substantially prevents a user from falling off the back end of the treadmill and whereby serving to keep the user centered on the upper surface of the treadmill without encumbering the natural body motion of the user exercising thereon.

Ex. 1011, 3:40-45


Socwell:

Moreover, it is an object of the present invention to provide a curved deck treadmill which is capable of reducing the physical impact to the joints and muscles (e.g., the knees and back) of a user, thus providing an operative device having rehabilitative functionality.

Ex. 1011, 3:53-57


Modifying Schonenberger to be curved like Socwell is merely use of a known technique

Schonenberger:




Ex. 1010, Fig. 12

Socwell:




Ex. 1011, Fig. 3

Modified Schonenberger:



Ex. 1010, Fig. 1 (Modified)

Combining Schonenberger with Socwell is not just flipping Schonenberger upside-down



Schonenberger, Ex 1010, Fig. 12 (Modified)

Dr. Giachetti:

175. A POSA would have understood that lowering the rollers 12 relative to the front and rear shaft assemblies would result in a curved running surface, as shown below, and such that the movable surface 1 (“running belt”) follows the profile defined by the rollers 12.

176. The movable surface 1 of Schonenberger is comprised of individual slats 4 that are relatively heavy, relatively rigid, interconnected, and movable relative to each other. As such, the movable surface 1 (“*running belt*”) would conform to the profile of the supporting rollers 12. (Schonenberger, Ex. 1010, 4:38-66, Fig. 3.)

Schonenberger and Socwell are properly combinable – Annotated Fig. 12 is just a conceptual aid

Dr. Giachetti:

36. Woodway/Dr. Blair incorrectly allege that my modified Schonenberger is merely flipping the roller arrangement 12 up-side-down. (POR, 26; Dr. Blair Declaration, Ex. 2018, ¶¶136, 143.) However, my position actually was that it would have been obvious to arrange the rollers 12 curvilinearly like the curved deck 56 of Socwell:

843 IPR, Ex. 1036, ¶136

41. Woodway/Dr. Blair allege modified Schonenberger is only illustrated in Figure 12, which they argue does not correspond to Petitioner’s modified Schonenberger Figure 1—i.e., merely to invert Schonenberger’s rollers. (POR, 28.) But this is not accurate. First, as discussed above, the text of the petition and my original declaration explains that Petitioner’s modified Schonenberger is the rollers 12 arranged like the curved deck 56 of Socwell. (Petition, 41-42; Ex. 1003, ¶174). Second, the text of my first declaration makes clear that the above annotated figure is merely a conceptual visual aid to show how Schonenberger’s running belt 1 would sag to conform with the profile defined by the rollers 12. (Ex. 1003, ¶175.)

843 IPR, Ex. 1036, ¶41

Schonenberger does not discourage curved running surfaces

Petitioner Reply:

“A reference teaches away ‘when a person of ordinary skill, upon reading the reference, would *be discouraged from following the path set out in the reference*, or would be led in a direction **divergent** from the path that was taken’ in the claim. A reference that ‘merely expresses a general preference for an alternative invention but does not criticize, discredit, or otherwise discourage investigation into’ the claimed invention does not teach away.” *Meiresonne v. Google, Inc.*, 849 F.3d 1379, 1382 (Fed. Cir. 2017) (Emphasis added).

Gap not required for springy feel

Schonenberger:

The spacing between the upper surface of the support belt 13 and the lower surface 14 of the step slats 4 is so selected in the area, where the V-belt 13 (FIG. 7) or support belt 13 (FIG. 5) is positioned over the rollers 12, that a small distance in the order of, for example, about ½ mm preferably is left when the surface 1 is unloaded.

Ex. 1010: 5:51-58 (cited in 849 POR, 33)

Dr. Giachetti:

52. I did not explicitly discuss a gap between the rollers 12 and belts 5' in my original declaration, but it is my opinion that a user would not perceive the presence or absence of a 0.5 mm gap, especially in my proposed curved arrangement of modified Schonenberger. 843 IPR, Ex. 1036, ¶52

Schonenberger:

These support rollers are formed with lateral flanges; for example, they may be in the form of a V-belt pulleys, and have at least one separate V-belt which is looped about the end support rollers and which is preferably spaced from the inner surface of the upper run of the endless movable surface, when unloaded, by a distance of for example about ½ cm in the area of the support rollers to prevent noise, which is otherwise caused by hits of the

Ex. 1010: 2:25-33

(cited in 843 IPR: Surreply, 13, 849 IPR: Surreply, 14)

FIG. 10 illustrates the belt 5' in engagement with roller 12, that is, the condition when the slat 4 is loaded, for example by the weight of a user symbolically indicated by weight arrow W. When unloaded, rollers 12 and belt 5' are partially spaced.

FIG. 10a shows roller 12 supporting the belt. Lateral toothed or ribbed sections 7', on either side of the roller 12 prevent lateral dislocation of slat 4.

Ex. 1010: 8:58-65;

(cited in 843 IPR: Surreply 13, 849 IPR: 14)


Modified Schonenberger does not destroy intended function – Petitioner accounted for the slat-type belt

Dr. Giachetti:

The slats 4 are also designed for relative movement. (Id., 5:54–56.) For example, the slat-style belt is able to tightly curve at the drums 10, which is a much tighter radius than the curved running surface of my proposed modification. A POSA would have recognized the movable surface 1 of Schonenberger as being suitable for a curved running surface. (Ex.1003, ¶176.) For example, Schmidt, which I described in my background section of my first declaration disclosed a track-style curved belt like the Schonenberger embodiments I relied upon in my analysis. (Ex. 1003, ¶62; Schmidt, Ex. 1009, 1:50-59.)


843 IPR, Ex. 1036, ¶ 47

Schonenberger:



Ex. 1010, Fig. 2 (cropped)

Schmidt:



Ex. 1009, Fig. 2 (cropped)

Skowronski's plastic pulley is an electrically insulating material

Skowronski:

Pulleys **22** and **28** are also preferably of a molded plastic construction. Suitable materials from which pulleys **22** and **28** can be molded include glass-filled polypropylene, polystyrene, polycarbonate, polyurethane and polyester.

Dr. Giachetti

Ex. 1030, 7:49-52

81. I previously opined, "[a] POSA would have understood that plastic is electrically insulating." (Ex. 1003, ¶302; Ex. 2024, 142:5-8, 144:14-22.) This aligns with the specification of the '884 Patent, which discloses plastic as an example electrically insulating material. ('884 Patent, Ex. 1001, 5:61-64.)

Ex. 1036, ¶81

884 Patent:

According to another embodiment, the front and rear running belt pulleys **62**, **66** are formed of a glass-filled nylon, for example, Grivory® GV-5H Black 9915 Nylon Copolymer available from EMS-GRIVORY of Sumter, S.C. 29151, which may save cost and reduce the weight of the pulleys **62**, **66** relative to metal pulleys. To prevent a static charge due to operation of the treadmill **10** from building on a pulley **62**, **66** formed of electrically insulative materials (e.g., plastic, composite, etc.), an antistatic additive, for example Antistat 10124 from Nexus Resin Group of Mystic, Conn. 06355, maybe may be blended with the GV-5H material.

Ex. 1001, 5:56-67

“Where the offered secondary consideration actually results from something other than what is both claimed and *novel* in the claim, there is no nexus.”

Lectrosonics, Inc., v. Zaxcom, Inc., IPR2018-01129, Paper 33, 33 (PTAB Jan. 24, 2020) (precedential)

POR:

The commercial success of Patent Owner’s products was based on the key features of the claimed invention. EX2020, ¶¶34-41. 836 IPR: POR, 59

Weber:

9. Part of Woodway’s innovative technology in the CURVE® Line, and what makes it commercially viable due to safety and hazard considerations associated with falling, is the incorporation of a safety device wherein the curved running surface is substantially prevented from being capable of moving in two directions – the intended direction and the reverse direction. T

Ex. 2020, ¶19

Weber:

34. It is further my opinion that one factor that contributes to the commercial success of Woodway’s CURVE® Line is the use of a safety mechanism to control the unintended rotation of the running belt which results in unintended movement of the running surface (the running surface moving both toward the front of the unit and toward the back of the unit). Indeed, as explained herein, Woodway’s line of curved, manual treadmills would not be commercially successful without such a safety feature.

Ex. 2020, ¶34

PO's sales did not result from unique claim characteristics

PO's Website:

Manual Treadmills

* * *

Curve Series

The Curve Series is a group of non-motorized, curved, treadmills designed to deliver a unique, effective, and efficient workout experience. They rely on the user's effort to move the running surface, providing a more natural running motion that helps improve form and engage more muscle groups. The innovative design of the Curve Series makes it an unmatched tool for High-Intensity Interval Training (HIIT), run/sprint technique, and even short to middle-distance steady-state cardio. Due to the unique curvature, users burn up to 30% more calories than traditional motorized treadmills. Whether you're a seasoned athlete or a fitness beginner, Woodway's Curve treadmills offer an exceptional, user-controlled workout experience that mimics outdoor running.

* * *



Curve

The essential non-motorized curved treadmill.

Explore



Curve LTG

Light on weight, not performance.

Explore



Curve Trainer


Build endurance and increase stamina with a lower incline for longer workouts.

Explore

Ex. 1044, 1-2

PO's 4Front Treadmill:

5.4 Dynamic Mode (Overview)

**WARNING**


Do Not Leave Treadmill Unattended While in Dynamic Mode!
If the treadmill is left unattended while in dynamic mode, there is a possibility of personal injury from people stepping onto device while assuming the running surface is locked.

- Never leave treadmill unattended while in dynamic mode.
- The running surface runs completely free in both directions and is no longer slowed by the motor.
- Always keep children and animals clear of the treadmill while in dynamic mode.

The treadmill makes it possible that the user serves as the running surface belt drive. The user drives the running surface belt manually during training. This is known as "Dynamic Mode"

Ex. 1041, 29


Ex. 1042, 2



Secondary Considerations – No Commercial Success

PO's drop in sales of the Curves can be linked to selling a cheaper alternative (Trueform) side-by-side with the Curve on its website

Industry Criticism:



TreadmillReviews.com

Best Treadmills • Treadmills By Price • Top Brands • Best Exercise Bikes • Best Ellipticals • About •

The Woodway Curve

August 9, 2012 by Treadmill Reviews

* * *

Conclusion

The Woodway Curve is a remarkable treadmill because, if for no other reason, it has no motor and still provides the user with a great workout which is what all treadmills want to do. It's too bad the Curve costs 8,000 dollars because were it affordable, I would have one in my house right now.

Ex. 2050, 1,3


latimes.com

* * *

Dislikes: Twice the price of a great conventional motorized treadmill. The console readouts, which include time, speed, calories, pulse and mileage, are too small.

Ex. 2052, 1


PO's Website:



Ex. 2039 (Annotated) (Printed January 23, 2024)

CONTAINS CONFIDENTIAL INFORMATION SUBJECT TO PROTECTIVE ORDER

| Industry praise was not due to the claimed invention



CONTAINS CONFIDENTIAL INFORMATION SUBJECT TO PROTECTIVE ORDER

“[R]eference to Woodway Customer Service in Ex. 2071 is irrelevant, because statements regarding customer service are not ‘evidence of efforts to replicate a specific product.’”

836 IPR: Reply at 33 quoting *Wyers v. Master Lock Co.*, 616 F.3d 1231, 1246 (Fed. Cir. 2010).

