

(12) **United States Patent**
Haler

(10) **Patent No.:** **US 8,520,069 B2**
(45) **Date of Patent:** **Aug. 27, 2013**

(54) **VEHICLE-MOUNTED VIDEO SYSTEM WITH DISTRIBUTED PROCESSING**

(75) Inventor: **Robert D Haler**, Blue Springs, MO (US)

(73) Assignee: **Digital Ally, Inc.**, Lenexa, KS (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1144 days.

(21) Appl. No.: **12/189,192**

(22) Filed: **Aug. 10, 2008**

(65) **Prior Publication Data**

US 2009/0002491 A1 Jan. 1, 2009

Related U.S. Application Data

(63) Continuation-in-part of application No. 11/531,955, filed on Sep. 14, 2006, now abandoned.

(60) Provisional application No. 60/955,129, filed on Aug. 10, 2007, provisional application No. 60/717,602, filed on Sep. 16, 2005.

(51) **Int. Cl.**
H04N 7/18 (2006.01)

(52) **U.S. Cl.**
USPC **348/148**; 348/739; 340/293; 340/438;
340/936

(58) **Field of Classification Search**
USPC 348/148, 143, 739; 340/293, 438,
340/936

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,409,670 A 10/1983 Herndon et al.
4,863,130 A 9/1989 Marks, Jr.

4,918,473 A	4/1990	Blackshear
5,027,104 A	6/1991	Reid
5,096,287 A	3/1992	Kakinami et al.
5,111,289 A	5/1992	Lucas et al.
5,289,321 A	2/1994	Secor
5,381,155 A	1/1995	Gerber
5,446,659 A	8/1995	Yamawaki
5,453,939 A	9/1995	Hoffman et al.
5,473,729 A	12/1995	Bryant et al.
5,479,149 A	12/1995	Pike
5,497,419 A	3/1996	Hill
5,585,798 A	12/1996	Yoshioka et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE	3248192	3/1984
GB	2273624	6/1994

(Continued)

OTHER PUBLICATIONS

W. Fincham, Data Recorders for Accident Investigation, Monitoring of Driver and Vehicle Performance (Digest No. 1997/122), Publication Date: Apr. 10, 1997, pp. 6/1-6/3.

(Continued)


Primary Examiner — David Lazaro

(74) *Attorney, Agent, or Firm* — Hovey Williams LLP

(57) **ABSTRACT**

A vehicle-mounted system (1010) for recording video and audio. The system (1010) uses distributed processing, including encoding the video and audio at their source(s), and a high-speed, e.g., Ethernet, bus (1148) connecting the various system components and external devices. The system (1010) may include a display monitor (1040) which is integrated into the same housing (1020) as a rear view mirror (170) of the vehicle, with the display monitor (1040) being located behind the mirror (170) and video displayed on the monitor being visible through the mirror (170).

20 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,642,285	A	6/1997	Woo et al.	
5,668,675	A	9/1997	Fredricks	
5,689,442	A	11/1997	Swanson et al.	
5,742,336	A	4/1998	Lee	
5,798,458	A	8/1998	Monroe	
5,815,093	A	9/1998	Kikinis	
5,878,283	A	3/1999	House et al.	
5,890,079	A	3/1999	Levine	
5,926,210	A	7/1999	Hackett et al.	
5,978,017	A	11/1999	Tino	
5,983,161	A	11/1999	Lemelson et al.	
5,996,023	A	11/1999	Winter et al.	
6,008,841	A	12/1999	Charlson	
6,028,528	A	2/2000	Lorenzetti et al.	
6,052,068	A	4/2000	Price et al.	
6,097,429	A	8/2000	Seeley et al.	
6,100,806	A	8/2000	Gaukel	
6,121,881	A	9/2000	Bieback et al.	
6,141,609	A	10/2000	Herdeg et al.	
6,163,338	A	12/2000	Johnson et al.	
6,175,300	B1	1/2001	Kendrick	
6,298,290	B1	10/2001	Abe et al.	
6,310,541	B1	10/2001	Atkins	
6,314,364	B1	11/2001	Nakamura	
6,326,900	B2	12/2001	DeLine et al.	
6,333,694	B2	12/2001	Pierce et al.	
6,333,759	B1	12/2001	Mazzilli	
6,370,475	B1	4/2002	Breed et al.	
RE37,709	E	5/2002	Duke	
6,389,340	B1	5/2002	Rayner	
6,405,112	B1	6/2002	Rayner	
6,449,540	B1	9/2002	Rayner	
6,518,881	B2	2/2003	Monroe	
6,525,672	B2	2/2003	Chainer et al.	
6,546,119	B2	4/2003	Ciolfi et al.	
6,591,242	B1	7/2003	Karp et al.	
6,681,195	B1	1/2004	Poland et al.	
6,697,103	B1	2/2004	Fernandez et al.	
6,718,239	B2	4/2004	Rayner	
6,727,816	B1	4/2004	Helgeson	
6,823,621	B2	11/2004	Gotfried	
6,856,873	B2	2/2005	Breed et al.	
6,970,183	B1	11/2005	Monroe	
7,012,632	B2	3/2006	Freeman et al.	
7,034,683	B2	4/2006	Ghazarian	
7,038,590	B2	5/2006	Hoffman et al.	
D529,528	S	10/2006	Ross, Jr. et al.	
7,119,832	B2	10/2006	Blanco et al.	
7,126,472	B2	10/2006	Kraus et al.	
7,147,155	B2	12/2006	Weekes	
7,180,407	B1	2/2007	Guo et al.	
7,371,021	B2	5/2008	Ross, Jr. et al.	
7,436,955	B2	10/2008	Yan et al.	
7,448,996	B2	11/2008	Khanuja et al.	
7,496,140	B2	2/2009	Winningstad et al.	
7,500,794	B1	3/2009	Clark	
7,536,457	B2	5/2009	Miller	
7,539,533	B2	5/2009	Tran	
7,561,037	B1	7/2009	Monroe	
7,602,301	B1	10/2009	Stirling et al.	
7,659,827	B2	2/2010	Gunderson et al.	
7,680,947	B2	3/2010	Nicholl et al.	
7,804,426	B2	9/2010	Etcheson	
2002/0013517	A1	1/2002	West et al.	
2002/0032510	A1	3/2002	Turnbull et al.	
2002/0044065	A1	4/2002	Quist et al.	
2002/0049881	A1	4/2002	Sugimura	
2002/0131768	A1	9/2002	Gammenthaler	
2002/0135336	A1	9/2002	Zhou et al.	
2003/0040917	A1	2/2003	Fiedler	
2003/0080878	A1*	5/2003	Kirmuss	340/936
2003/0081942	A1*	5/2003	Melnyk et al.	386/125
2003/0173408	A1	9/2003	Mosher, Jr. et al.	
2003/0222982	A1	12/2003	Hamdan et al.	
2004/0043765	A1	3/2004	Tolhurst	

2004/0145457	A1	7/2004	Schofield et al.	
2004/0199785	A1*	10/2004	Pederson	713/200
2005/0030151	A1	2/2005	Singh	
2005/0046583	A1	3/2005	Richards	
2005/0100329	A1*	5/2005	Lao et al.	386/117
2005/0134966	A1	6/2005	Burgner	
2005/0167172	A1	8/2005	Fernandez	
2005/0228234	A1	10/2005	Yang	
2005/0232469	A1	10/2005	Schofield et al.	
2006/0009238	A1	1/2006	Stanco et al.	
2006/0028811	A1	2/2006	Ross et al.	
2006/0164220	A1	7/2006	Harter, Jr. et al.	
2006/0170770	A1	8/2006	MacCarthy	
2006/0176149	A1	8/2006	Douglas	
2006/0256822	A1	11/2006	Kwong et al.	
2006/0270465	A1	11/2006	Lee et al.	
2006/0274828	A1	12/2006	Siemens et al.	
2006/0282021	A1	12/2006	DeVaul et al.	
2006/0287821	A1	12/2006	Lin	
2006/0293571	A1	12/2006	Bao et al.	
2007/0021134	A1	1/2007	Liou	
2007/0064108	A1	3/2007	Haler	
2007/0067079	A1	3/2007	Kosugi	
2007/0102508	A1	5/2007	McIntosh	
2007/0132567	A1*	6/2007	Schofield et al.	340/438
2007/0152811	A1	7/2007	Anderson	
2007/0229350	A1	10/2007	Scalisi et al.	
2007/0257781	A1	11/2007	Denson	
2007/0257782	A1	11/2007	Etcheson	
2007/0257804	A1	11/2007	Gunderson et al.	
2007/0257815	A1	11/2007	Gunderson et al.	
2007/0260361	A1	11/2007	Etcheson	
2007/0268158	A1	11/2007	Gunderson et al.	
2007/0271105	A1	11/2007	Gunderson et al.	
2007/0285222	A1	12/2007	Zadnikar	
2008/0001735	A1	1/2008	Tran	
2008/0043736	A1	2/2008	Stanley	
2008/0049830	A1	2/2008	Richardson	
2008/0129518	A1	6/2008	Carlton-Foss	
2008/0211906	A1	9/2008	Lovric	
2008/0246656	A1	10/2008	Ghazarian	
2008/0266118	A1	10/2008	Pierson et al.	
2009/0002491	A1	1/2009	Haler	
2009/0070820	A1	3/2009	Li	
2009/0122142	A1	5/2009	Shapley	
2009/0243794	A1	10/2009	Morrow	
2009/0252486	A1	10/2009	Ross, Jr. et al.	
2010/0060734	A1	3/2010	Chou	
2010/0188201	A1	7/2010	Cook et al.	
2010/0191411	A1	7/2010	Cook et al.	
2010/0238009	A1	9/2010	Cook et al.	
2010/0250021	A1	9/2010	Cook et al.	

FOREIGN PATENT DOCUMENTS

GB	2320389	6/1998
GB	2343252	5/2000
GB	2351055	12/2000
GB	2417151	2/2006
GB	2425427	10/2006
GB	2455885	7/2009
JP	294188	11/1993
JP	153298	6/1996
JP	198858	9/1997
JP	10076880	3/1998
JP	210395	8/1998
JP	2005119631	5/2005
WO	WO9005076	5/1990
WO	WO9738526	10/1997
WO	WO9831146	7/1998
WO	WO9948308	9/1999
WO	WO0039556	7/2000
WO	WO0051360	8/2000
WO	WO0123214	4/2001
WO	WO0249881	6/2002
WO	WO02095757	11/2002
WO	WO03049446	6/2003
WO	WO2009013526	1/2009

OTHER PUBLICATIONS

S.R. Lewis, Future System Specifications for Traffic Enforcement Equipment, S.R. 1 Source: IEE Colloquium (Digest), N 252, Publication Date: Nov. 18, 1996, pp. 8/1-8/2.

Samuel W. Daskam, Law Enforcement Armed Robbery Alarm System Utilizing Recorded Voice Addresses Via Police Radio Channels, Source: Univ. of Ky, Off of Res and Eng., Serv (UKY BU107), pp. 18-22, 1975.

New Rearview-Mirror-Based Camera Display Takes the Guesswork Out of Backing Up Retrieved from the Internet: <URL: <http://news.thomasnet.com/fullstory/497750>>, Press Release, Oct. 30, 2006.

Lilliput RV 18-50NP 5" Rear View Mirror TFT LCD Screen with Camera, Retrieved from the Internet: <URL: <http://www.case-mod.com/lilliput-rv1850np-rear-view-mirror-tft-lcd-screen-with-camera-p-1271.html>>, Mar. 4, 2005.

Car Rear View Camera—Multimedia Rear View Mirror—4" LCD color monitor, Retrieved from the Internet: <URL: <http://web.archive.org/web/20050209014751/http://laipac.com/multimedia-rear-mirror.htm>>, Feb. 9, 2005.

Frankel, Harry; Riter, Stephen, Bernat, Andrew, Automated Imaging System for Border Control, Source: University of Kentucky, Office of Engineering Services, (Bulletin) UKY BU, pp. 169-173, Aug. 1986.

Supplementary European Search Report dated Sep. 28, 2012 in European Patent Application No. 06803645.8; Applicant: Digital Ally, Inc.

Korean Utility Model Reg. No. 20-0236817, published Oct. 8, 2001. SIIF Award for Multi Black Box, published Dec. 10, 2004.

Automation Systems Article, Know-How Bank Co. Ltd. Takes Leap Forward as a Company Specializing in R&D and Technology Consulting, published Jan. 2005.

Electronic Times Article, published Feb. 24, 2005.

Motor Magazine Article, Recreating the Scene of an Accident, published 2005.


Hankyung Auto News Article, Know-How Bank's Black Box for Cars "Multi-Black Box," Copyright 2005.

<http://www.k-h-b.com/board/board.php?board=products01&comand=body&no=1>, Current State of Technology Held by the Company, Copyright 2005.

http://www.k-h-b.com/sub1_02.html, Copyright 2005.

Near Field Communication; Sony Corporation; pp. 1-7, Date: Unknown.

* cited by examiner

*Fig. 1*




Fig. 2




Fig. 3







Fig. 4






Fig. 8




Fig. 9




Fig. 10





Fig. 11

*Fig. 12*

1

VEHICLE-MOUNTED VIDEO SYSTEM WITH DISTRIBUTED PROCESSING

RELATED APPLICATIONS

The present non-provisional patent application is related to and claims priority benefit of an earlier-filed provisional patent application titled "Vehicle-Mounted Video System With Distributed Processing", Ser. No. 60/955,129, filed Aug. 10, 2007, is a continuation-in-part and claims priority benefit of an earlier-filed non-provisional patent application, titled "Rear View Mirror With Integrated Video System", Ser. No. 11/531,955, filed Sep. 14, 2006, and is related to and claims priority benefit of an earlier-filed provisional patent application titled "Rear View Mirror With Integrated Video System", Ser. No. 60/717,602, filed Sep. 16, 2005. Each of the identified earlier-filed patent applications is hereby incorporated by reference into the present patent application as though fully set forth herein.

FIELD OF THE INVENTION

The present invention relates generally to vehicle-mounted systems for recording video and audio. More particularly, the present invention concerns such a system using distributed processing, including encoding the video and audio at their source(s), and a high-speed, e.g., Ethernet, bus connecting the various system components and external devices.

BACKGROUND OF THE INVENTION

Many law enforcement vehicles include video systems for recording and displaying activity in and around the vehicle. Unfortunately, these systems typically consist of one or two cameras and an independent display monitor that is difficult to view while the vehicle is in operation. Moreover, the current systems are expensive, bulky, and difficult to operate and maintain. It is also difficult to find sufficient space for the camera, recording system, and monitor in the law enforcement vehicles, which are already heavily loaded with extra equipment. It is possible to locate certain components, such as the recording system, which do not need to be frequently accessed, in the trunk of the vehicle, but this then requires long cables extending through the vehicle to connect the recording system with the camera and monitor. Additionally, many current systems are limited to simply recording and displaying visual images of the activity, and do not provide any additional information associated with the activity.

Furthermore, current systems are designed with a single central processor unit (CPU) which controls most or all major functions, including encoding video received from a camera. Unfortunately, centralized processing creates bottlenecks for both speed and processing capabilities (depending on the CPU, encoding video signals may require 75% the CPU's processing capability), requires significant changes in order to add new hardware features, and, generally, results in an inability to make changes to the system without investing significant expense and time. Additionally, communicating unencoded analog signals within the vehicle to the single CPU can result in significant electrical interference and signal degradation.

SUMMARY OF THE INVENTION

The present invention overcomes the above-identified and other problems by providing a vehicle-mounted video and audio recording system using distributed processing, includ-

2

ing encoding the video and audio at their source(s), and a high-speed, e.g., Ethernet, bus connecting the various system components and external devices.

In one embodiment, the video system for a vehicle broadly comprises a video camera mounted on the vehicle and operable to both capture and encode video, a central control unit mounted on the vehicle and operable to receive and decode the encoded video, and a display monitor mounted on the vehicle and operable to display the decoded video.

In various implementations, the video system may further include any one or more of the following features. The video camera may be synchronized with the central control unit so as to provide an accurate time stamp associated with the video. The video camera may be operable to implement a pre-event recording loop. The video camera and central control unit may be connected by a high speed bus. There may be two or more video cameras connected to a hub, wherein the hub is connected to the central control unit, and the central control unit is operable to receive the encoded video from each of the two or more video cameras substantially simultaneously. The system may include a microphone operable to capture and encode audio, wherein the central control unit is operable to receive and decode the encoded audio, a vehicle interface box mounted on the vehicle and operable to interface an external device to the central control unit, wherein the external device may be any one or more of a crash sensor, a radar gun, and a speedometer, and a co-processing module mounted on the vehicle and operable to provide processing for an additional feature of the system, wherein the additional feature may be any one or more of a face recognition feature, a license plate recognition feature, a streaming video feature, and a wireless Internet access feature.

The system may include a rear view mirror housing, a mirror mounted in the rear view mirror housing, and the display monitor mounted in the rear view mirror housing substantially behind the mirror, and the mirror and the display monitor being configured so that the displayed video is viewable through the mirror.

The system may include a location determining device operable to determine a location of the vehicle when the video is captured, and a recording medium operable to record at least a portion of the captured video and the location of the vehicle when the video was captured.

These and other details of the present invention are described in greater below in the section below titled DESCRIPTION OF THE INVENTION.

BRIEF DESCRIPTION OF THE DRAWINGS

Further features of the present invention will become apparent to those skilled in the art to which the present invention relates from reading the following description with reference to the accompanying drawings, in which:

FIG. 1 is a functional block diagram of a video system according to one embodiment of the present invention;

FIG. 2 is a perspective view of a rear view mirror constructed according to one embodiment of the present invention;

FIG. 3 is a perspective view of a rear view mirror constructed according to an embodiment of the present invention and illustrating an active monitor showing the image from a forward facing external camera mounted in close proximity to the rear view mirror;

FIG. 4 is a perspective view of the rear view mirror of FIG. 1;

FIG. 5 is a front elevation view of the rear view mirror of FIG. 1;

3

FIG. 6 is an side elevation view of the rear view mirror of FIG. 1;

FIG. 7 is a plan view of the rear view mirror of FIG. 1;

FIG. 8 is a perspective view of a rear view mirror constructed according to another embodiment of the present invention;

FIG. 9 is a front elevation view of the rear view mirror of FIG. 8;

FIG. 10 is a rear elevation view of the rear view mirror of FIG. 8;

FIG. 11 is a block diagram of a video system according to another embodiment of the present invention; and

FIG. 12 is a block diagram of a camera component of the video system of FIG. 11.

DESCRIPTION OF THE INVENTION

With reference to the figures, a video system is herein described, shown, and otherwise disclosed in accordance with a preferred embodiment of the present invention. More specifically, the present invention provides a vehicle-mounted video system that is capable of recording, storing, and replaying video images, wherein the video system includes at least one internal camera and a display monitor, with both being integrated into the same housing as a rear view mirror of the vehicle, and with the monitor being located substantially behind the mirror such that video images displayed by the monitor are visible through the mirror. The video system may also allow for capturing audio signals and other desirable information, including, for example, location and speed information.

Referring to FIG. 1, an embodiment of the video system 10 is shown broadly comprising various components mounted in or on the rear view mirror housing 20, including an internal camera 30, a video monitor 40, an electronics module 50, a memory 60, an internal microphone 70, a speaker 80, input buttons 90, LED indicators 100, input connectors 110, output connectors 120, and at least one infrared LED 130. The system 10 may also include an external camera 140, a GPS antenna 150, and a speed detector 160.

The internal camera 30 is typically positioned on an upper and central portion of the mirror housing 20 so that it can capture video images of activity within the passenger compartment of the vehicle. Alternatively, the internal camera 30 may be hidden behind the mirror 170. The internal camera 30 may be mounted at an appropriate angle, such as approximately between 10 degrees and 20 degrees to the left, so that the camera 30 is able to properly view the passenger compartment even when the mirror 170 is angled towards the driver during normal use. Camera 30 may also be mounted at approximately 160 degrees or greater when camera 30 is a wide-angle camera. One appropriate camera for use as the internal camera 30 is a 510×492 black and white CMOS sensor with TV resolution, 0.01 Lux sensitivity, and a 140 degree 4-element coated glass lens.

The external camera 140 is mounted outside of the mirror housing 20 in a separate enclosure. The external camera 140 is useful, for example, to record video images when an officer leaves the vehicle, such as during a traffic stop. One appropriate camera for use as the external camera 140 is a color CCD sensor NTSC with 768×484 pixels and 470 lines of resolution, a 10× optical zoom and auto focus capabilities, a wide viewing angle that is from 50.7 to 5.4 degrees, and standard and low light modes.

The monitor 40 is mounted substantially behind the mirror 170 (see FIGS. 2 and 3) and works in conjunction with the mirror 170 so that when the monitor 40 is turned on it is

4

viewable through the mirror 170, and when it is turned off it is not visible. The monitor 40 may be operable to automatically turn off when the vehicle begins to move or when the vehicle's transmission is shifted into reverse or drive, so that the driver has full use of the mirror 170 while the vehicle is in motion. Alternatively, the monitor may be mounted adjacent to or only partially behind the mirror 170. One appropriate monitor for use as the video monitor 40 is a 3.5 inch diagonal, 640×480 TFT LCD monitor.

The electronics module 50 includes a number of electronic components, including components for receiving video signals from the video cameras 30, 140 and for transmitting video signals to the monitor 40. The electronics module 50 also includes components operable to receive and execute instructions stored in internal memory. In one embodiment, for example, these instructions include menu instructions for setting operational modes and resolutions. These instructions may be updated by loading instructions into a memory card and then inserting that card into a port in the system 10.

The input and output connectors 110, 120 are connected to the module 50 for receiving electronic signals thereto and transmitting electronic signals therefrom. The input connectors 110 may include, for example, a connector for power, for the output from the speed detector 160, and for the output from the GPS antenna 150. The input connectors 110 may also include one or more connectors for receiving signals to trigger operation of the system. These triggers may include, for example, turning on the vehicle's siren and/or signal lights. The input connectors 110 may also include a connector for receiving the output of a second external camera, such as a rear-facing camera, and a connector for receiving the output of a second external microphone. The input connectors 110 may also include a port, such as a USB 2.0 port, to allow for directly accessing the memory 60 using a laptop or other computer. The output connectors 120 may include, for example, an audio/visual connector for transmitting audio/visual signals to an external monitor or recording device. Additionally or alternatively, any one or more of these physical connectors 110, 120, may be replaced with wireless communication technology allowing the system 10 to wirelessly receive or transmit any of the aforementioned input or outputs. In one embodiment, the input and output connectors 110, 120 are provided on an interface module or block which is not located on or integrated into the housing 20, but rather is located in a remote location, such as under the vehicle's dash, and operatively coupled with the module 50 by wire or wirelessly.

The module 50 may also include components for receiving audio signals from audio sources, such as the internal microphone 70, and for transmitting audio signals to the speaker 80. The module 50 may also include components for receiving wireless signals from one or more remote microphones, such as a wireless microphone worn by the officer. In this case, the module 50 may include an integrated 900 MHz (or another suitable frequency allowed by law), spread spectrum, dual receiver capable remote microphone system with a nominal range of up to approximately 1000 feet or greater (a range of several miles may be achieved under the proper conditions).

The module 50 may also include an integrated GPS receiver connected to the GPS antenna 150. Utilizing the information provided by these components, the module 50 may mark recorded video with real-time position data. The system may include a "dead reckoning" function which works with GPS to allow for operation in shielded locations, such as underground garages.

The module 50 may also be connected to the speed detector 140, which may be a radar gun or other conventional speed

5

detecting device, and operable to record speed information provided by the speed detector **140** along with the video images.

The memory **60** is in communication with the module **50** for receiving and storing the video, audio, and other data. One appropriate form of electronic memory for use as the memory **60** is a CF card form factor removable memory module, and one appropriate format for storing the data is MPEG 4 format. Other appropriate forms of electronic memory for use as the memory **60** include micro hard drives, laptop-type hard drives, and flash memory cards. As will be understood by those in the field, the amount of data storable in the memory **60** is dependent, at least in part, on the resolution utilized by the electronics module **50**. It is contemplated, however, that the memory **60** may store approximately one hour of data per gigabyte of memory per simultaneous camera for high resolution, approximately two hours of data per gigabyte of memory per simultaneous camera for medium resolution, and approximately four hours of data per gigabyte of memory per simultaneous camera for low resolution.

Referring also to FIGS. 2-7, the input buttons **90** are mounted on the video housing **20** and allow for controlling various components and functions of the system **10**. In one embodiment, these buttons **90** may include and operate as follows. A REC button **180** triggers recording in the mode shown in a menu displayed on the monitor **40**. Pressing the REC button **180** during recording allows for cycling through the various night and day camera settings. Day and night recording modes may be set automatically using information from an on-board real-time clock or from a light sensor or from the camera **30**. A red indicator LED **100** on the front of the unit and a red record LED on the back of the unit are both turned on when the system is recording. A MARK button **190** sets a place for the current GPS position in the video data. A DISP button **200** toggles through settings such as Video Monitor and Control illumination/indicators ON, Video Monitor OFF, Control illumination/indicators ON, and Video Monitor and Control illumination OFF. A Menu button **210** toggles the menu display on the monitor **40** and turns the monitor **40** ON if the display is OFF. A "Play" (large right-facing arrow) button **220** executes commands in Menu Mode and toggles Play/Pause in video playback mode. A "Stop" (square) button **230** acts to cancel the current function in Menu Mode, stops video in Playback Mode, and toggles pre-set Zoom positions in Record Mode. A REV/DOWN button **240** zooms the camera **30** towards Wide in Record Mode, moves down in Menu Mode, and moves in reverse in Playback Mode. A FWD/UP button **250** zooms the camera **40** towards TELE in Record Mode, moves up in Menu Mode, and moves forward in Playback Mode. Other buttons may include an auto zoom feature to assist in reading license plates on other vehicles.

The at least one infrared LED **130** is disposed in the mirror housing **20** and operable to provide infrared illumination inside the vehicle's passenger compartment so that the internal camera **30** can capture video images even when there is little visible light.

Power is supplied to the components of the video system **10** from the vehicle. The power provided is heavily filtered and regulated to avoid interference. The video system **10**, using the particular components described herein, may require **4** amps from a 10 V to 13.8 V DC power supply.

The rear view mirror includes the mirror **170** mounted within the housing **20**. One appropriate mirror **170** is constructed of mirror glass. One appropriate housing for use as the housing **20** is constructed of a polycarbonate plastic that is resistant to high impacts and high temperatures and is

6

approximately between 12 inches and 14 inches long, 3 inches and 4 inches high, and 0.5 inches and 1.5 inches deep. The vehicle's conventional rear view mirror mount may be replaced by a stronger mount better able to support the weight of the mirror **170** and housing **20** and other components of the system **10**. The input buttons **90**, discussed above, may be mounted on a front or side surface of the housing **20**. The mirror housing **20**, and the housings of other components of the system, may include materials operable to shield against electrical or radio interference.

Additionally, the system **10** may be provided with a "stealth" mode in which the cameras **30,140** and the microphone **70** are active and recording, but the lights and indicators, such as the LED **100**, are turned off, thereby making the system **10** appear to be dormant.

Additionally, the system **10** may provide "pre-event" recording in which the system **10** records constantly in a loop of a selected duration of time, such as thirty seconds or sixty seconds, so that when an event triggers recording, the events occurring shortly prior to the initiation of recording are also recorded and stored.

Additionally, various embodiments of the system **10** include any one or more of the following features. The system **10** requires entry of a password or code prior to accessing and changing operational settings. The system **10** requires use of a key to remove any removable memory components. The system **10** incorporates electronic watermarks into the recorded video images to prevent tampering or alteration. The system **10** allows for wirelessly downloading the contents of the memory **60** to a laptop or other computer. The system **10** allows for streaming the live video from the cameras **30,140**, and possibly other inputs and/or outputs, via a high-speed wireless data network. The system **10** is operable to encode multiple video streams from four or more cameras simultaneously. The system **10** includes a remote control device for allowing a user to remotely control the operation of the system **10**. The system **10** includes a temperature sensor and temperature indicator operable to detect and warn the user if the system **10** is at risk of malfunction or damage due to an ambient temperature that is too high or too low for proper operation, such as may easily occur in a vehicle on a very hot or very cold day. The housing **20**, and possibly the housings of other components of the system **10**, is vented to dissipate heat, and may include other passive or active features to moderate temperature, especially in relatively extreme environments.

Referring also to FIGS. 8-10, a second implementation of the system **10** is shown which is somewhat different in appearance than the implementation shown in FIGS. 2-7, particularly with regard to the housing **220** and the layout of certain components thereabout, but which is otherwise substantially similar in functionality.

It will now be apparent that the present invention is both inexpensive to manufacture and easy to use, especially when compared to current vehicle video systems. The video system of the present invention is fully integrated into a small, easily installable and replaceable package that requires minimal space inside the vehicle. Thus, it replaces several single-purpose devices with a multifunction device that requires the same or less space in the vehicle. Moreover, the video system includes novel features and/or capabilities not present in currently available systems. Those skilled in the art will perceive additional significant improvements, changes, and modifications.

Referring also to FIG. 11, another embodiment of the above-described system is shown which uses distributed processing, including encoding the video and audio at their

source(s) rather than at a centralized location, and a high-speed, e.g., Ethernet, bus connecting the system components and various external devices.

In one implementation, the system **1010** broadly comprises the rear view mirror housing **1020**, a central control unit **1012**, the internal camera **1030**, the display monitor **1040**, the input buttons **1090**, one or more of the external cameras **1140**, one or more external microphones **1142**, a vehicle interface box **1144**, one or more co-processing modules **1146**, and the high-speed bus **1148**.

In this implementation, the central control unit **1012** does not itself encode the video and audio generated by the external camera **1140** and microphone **1142**, but rather receives the signals already encoded. As such, the central control unit **1012** includes a decoder for decoding the encoded video and audio to allow for communication via the display monitor **1040** and an associated speaker.

The one or more external cameras **1140** are each operable to both capture video and encode the video before transmitting it to the central control unit **1012** for display and storage. Because encoding can account for 75% of the processing workload in prior art systems, encoding the video at the camera **1140** rather than at the CPU of the central control unit **1012** advantageously allows the central control unit **1012** to support multiple external cameras simultaneously.

Generally, existing IP ("Internet protocol") cameras are unsuitable for use in the present system **1010** because they have a tendency to lose frames, which is not acceptable for law enforcement applications in which the video might be used as evidence, and because they have relatively narrow bandwidths, which is also problematic for law enforcement applications in which activity often takes place under extreme lighting conditions, e.g., bright streetlights and dark shadows. However, referring also to FIG. 12, with significant modification, a camera potentially suitable for use as the external camera **1140** in the system **1010** is the IP Reference Camera available from Nuvation Research Corporation. This particular camera includes its own onboard CPU **1160** for encoding video and audio, can be upgraded to high definition (HD) by changing the CPU, and includes an Ethernet port **1162**. The IP Reference Camera is significantly less likely to lose frames and has a significantly larger bandwidth than other IP cameras. Nevertheless, as mentioned, the IP Reference Camera still requires significant modification for use in the present system **1010**. For example, it is necessary to synchronize the CPU of the central control unit **1012** with the CPUs **1160** of the cameras **1140** in order to obtain an accurate time stamp. Also, the pre-event recording loop, described above, is, in this embodiment, implemented on the camera **1140**.

In one implementation of the present system, a camera used in conjunction with the present system, such as the Nuvation Research Corporation IP Reference Camera described above, includes a storage component such that captured frames are stored in the camera in addition to being sent to central control unit **1012**. These stored frames are also time-stamped during the normal course of operation of the present system. Thus, in the event any frames are lost during transmission from the camera to central control unit **1012**, central control unit **1012** is able to request that the camera transmit the lost frames again. Once the lost frames are received, central control unit **1012** can integrate the lost frames into the data already received so that a complete record is formed. Time synchronization between the camera and central control unit **1012** ensures that central control unit **1012** is able to accurately identify missing frames, query the camera for those frames, and properly integrate the missing frames into the record once they are received.

The one or more external microphones **1142** are also each operable to both capture audio and encode the audio before transmitting it to the central control unit **1012** for play or storage, thereby advantageously allowing the central control unit **1012** to support multiple external microphones simultaneously.

The vehicle interface box **1144** is operable to interface various external devices to the system **1010**. The external devices may include, for example, any one or more of a crash sensor, a radar gun, and a speedometer.

The one or more co-processing modules **1146** are each operable to provide processing for various additional features to the system **1010**. The additional features may include, for example, any one or more of a face recognition feature, a streaming video feature, and a wireless Internet access feature. Further, wireless access may be provided for other networks, such as wireless mesh, that are not associated with the internet in any way.

The high-speed bus **1148** is operable to connect and allow for communication between the various other components of the system **1010**. In one implementation, the bus is an Ethernet bus carrying power and data on the same cable. In one implementation, components, such as the cameras **1140** and microphones **1142** spaced apart from the central processing unit **1012**, are connected to a hub **1064**, and the hub **1064** is connected to the central processing unit **1012** by a single cable. In other implementations of the present system, other methods of communication between the various components of the present system may be used. Such other methods may include, for example, wireless communications, or combinations of wireless and wired communications. Further, although the implementation of the present system shown in the drawings utilize Power Over Ethernet (POE) in order to provide power to components of the present system, it is contemplated that any suitable method of providing such power may be utilized, and that numerous methods of providing power are known to those of skill in the art. It is further contemplated that a backup power source, such as a battery backup, may be used in conjunction with the present system.

It will now be apparent that, along with the earlier-discussed advantages of the first embodiment of the system, the second embodiment provides a number of additional advantages over prior art systems. For example, each external camera and microphone encodes its own video and audio, and therefore, the central control unit can support multiple cameras and microphones simultaneously, the cameras and microphones can be located much further away from the central control housing (which is important in larger vehicles) because encoded digital signals are less susceptible to the electrical interference and signal degradation experienced by unencoded analog signals, and the cameras and microphones can be easily added or replaced without requiring significant changes to the central control unit. Additionally, the high-speed bus carries both data and power to system and external components on the same cable, thereby eliminating the plurality of separate cables for power, video, audio, and communication required by prior art systems. Bus hubs allow for collecting and communicating data streams from multiple cameras, microphones, and other devices over a single cable, thereby eliminating the need to provide a long cable for each device. Bus connectivity and standard communication protocols allow for quickly adding features using plug-in modules. More generally, changes to the system can be accomplished with significantly less expense and time, allowing the system to adapt to user demands and extending the system's useful life.

Although various exemplary data formats and data transfer protocols are identified above, it is contemplated that any suitable format or protocol, whether now existing or hereafter developed, may be used in conjunction with the present invention. The discussion of specific formats or protocols herein is not intended to limit the scope of the present invention. For example, although the MPEG-4 format is mentioned above for encoding and storing audiovisual data obtained by the present system, it is contemplated that other formats such as, for example, H.263 and H.264, may also be used. Likewise, audiovisual data may be stored in high-definition (HD) format. Hardware or software changes or upgrades may be required in order to change formats, however the inventive functionality of the present system, as described herein, is preserved regardless of the specific format used. Because one goal of law enforcement implementations of the present system is to produce an evidentiary record, it is preferred that a lossless format be used in those implementations.

In addition to various suitable formats that may be used in conjunction with the present system, it is contemplated that any suitable data transfer protocol may be used. For example, real-time streaming protocol (RTSP) may be used to transfer data in the present system providing that the system is adapted to recover any lost frames from the camera. User datagram protocol (UDP) provides a better, lossless protocol for use with the present system. Any suitable existing protocol may be used, and new protocols may be developed for use with the present system. Because implementations of the present system include a data storage function in the camera, as described above, for retrieval of frames lost during data transfer, it is contemplated that typical IP cameras having such a storage feature may be used, with the system ensuring that lost frames are faithfully transmitted to central control unit **1012** when requested therefrom.

As noted above, the present system may be used with a variety of software, audiovisual formats, data transfer protocols, and the like. In some instances, changes to formats or protocols, or even making hardware changes such as upgrading the system to a HD-capable camera, may require that the software of the present system be updated. In some implementations of the present system, it is contemplated that the system software will be capable of being upgraded in the field. In such implementations, software upgrades may be provided via a memory card, portable flash memory device, a wireless data link to a portable device, a wireless internet data link, or any other suitable device or method for upgrading the system software in the field. In some implementations wherein wireless communications are used for system upgrades, it is contemplated that the present system may optionally include a wireless communications component adapted to connect to a remote source for obtaining updates automatically. Such communications could, for example, be carried out over the internet via a cellular communications signal that allows the present system to access the internet.

In addition to what has been described above, various peripheral devices may be utilized in conjunction with the present invention. In law enforcement implementations of the present system, for example, or in other implementations where security is important, the present system may be provided with a biometric identification component or other secure identification component. In an implementation of the present system requiring biometric identification, for example, a fingerprint may be required before a user of the present system can log into the system and begin to use the system. Other security peripherals include, for example, a dongle carried by a user of the present system that can be

presented to the system in order to verify the identity of a user. Any suitable security component or method may be included with the present invention.

In addition to maintaining or verifying user security, the present system may also include additional components to establish the security and evidentiary value of the audiovisual data recorded thereby. For example, it is contemplated that the cameras **1140** associated with the present system include a unique identifier, such as a serial number or other identifier that is unalterable, and that audiovisual signals obtained by any given camera are stamped with that camera's identifier. Thus, the identity of the camera that acquired any given data is verified and secured along with the actual data recorded by the system.

It is further contemplated that a CD or DVD burner may be provided as a component of the present system so that a user of the system can make a copy of captured audiovisual data while in the field. Any suitable recording device and medium known in the art may be used in association with the present invention.

Peripheral devices used for interfacing with the present system may also be provided. For example, a keyboard may be provided, the keyboard adapted to plug directly into the present system or to communicate wirelessly with the present system via Bluetooth, infrared, or other suitable method of wireless communication. Further, it is contemplated that a PDA, laptop, smartphone, or other mobile device may be adapted (for example by installing software thereon) for communication with and manipulation of the present system. Such devices may be used to manipulate a display associated with the present system, or to configure or control the present system.

With respect to any of the various peripherals that may be associated with the present system, whether described herein or not, it is contemplated that the peripherals may be plugged into or otherwise associated with electronics module **50** or central control unit **1012**, or that any of cameras **1140** may be adapted to communicate with the peripherals, either through a hard-wired or wireless connection.

Although the invention has been disclosed with reference to various particular embodiments, it is understood that equivalents may be employed and substitutions made herein without departing from the contemplated scope of the invention. For example, specific suitable hardware, processors, software, and the like as described above is exemplary and not intended to limit the present invention. Any suitable hardware may be used to implement the inventive functionality of the present system.

Having thus described the invention, what is claimed as new and desirable to be protected by Letters Patent includes the following:

1. A video system for a law enforcement vehicle, the system comprising:
 - a video camera mounted on the vehicle and operable to capture and encode video for law enforcement applications and to stamp the encoded video with an unalterable unique camera identifier,
 - wherein the video captured and encoded by the video camera is stamped with the camera identifier to verify and secure an identity of the camera on the video;
 - a central control unit mounted on the vehicle and operable to receive and decode the encoded video;
 - a rear view mirror housing;
 - a mirror mounted in the rear view mirror housing;
 - a display monitor operable to display the decoded video, the display monitor being mounted in the rear view mirror housing substantially behind the mirror, and the

11

mirror and the display monitor being configured so that the displayed video is viewable through the mirror;
 a memory for receiving and storing the captured and decoded video from the central control unit;
 a microphone operable to capture and encode audio, wherein the central control unit is operable to receive and decode the encoded audio;
 a vehicle interface box mounted on the vehicle and operable to interface an external device to the central control unit, wherein the external device is a radar gun;
 a co-processing module mounted on the vehicle and operable to provide processing for an additional feature of the system, wherein the additional feature is selected from the group consisting of a face recognition feature and a license plate recognition feature; and
 a recorder operable to make a copy of the captured and decoded video stored in the memory.

2. The video system as set forth in claim 1, wherein the video camera is synchronized with the central control unit so as to provide an accurate time stamp associated with the video.

3. The video system as set forth in claim 1, wherein the video camera is operable to implement a pre-event recording loop.

4. The video system as set forth in claim 1, wherein the video camera and the central control unit are connected by a high speed bus.

5. The video system as set forth in claim 1, wherein there are two or more video cameras connected to a hub, the hub is connected to the central control unit, and the central control unit is operable to receive the encoded video from each of the two or more video cameras simultaneously.

6. The video system as set forth in claim 1, further including a location determining device operable to determine a location of the vehicle when the video is captured, and wherein the memory of the video system is operable to record at least a portion of the captured video and the location of the vehicle when the video was captured.

7. The video system as set forth in claim 1 having at least one software component for implementing the functionality of the system, wherein said at least one software component of said system is upgradable while said system is located in the field as during normal use of the system.

8. The video system as set forth in claim 7, wherein an upgrade of said at least one software component is performed by use of an external device adapted to interface via a wired connection with said video system.

9. The video system as set forth in claim 7, wherein an upgrade of said at least one software component is performed by use of an external device in wireless communication with said video system.

10. The video system as set forth in claim 1, wherein the system is adapted to verify the identity of a user thereof prior to allowing said user to access the functionality of the video system.

11. The video system as set forth in claim 10, wherein the identity of said user is verified by use of biometric data.

12. The video system as set forth in claim 10, wherein the identity of said user is verified by the user of a dongle possessed by said user, the dongle adapted to interface with the video system.

13. The video system as set forth in claim 1, the video system being adapted to communicate wirelessly with an external computing device.

12

14. The video system as set forth in claim 13, wherein the external computing device is selected from the group consisting of a PDA, a smartphone, and a laptop.

15. The video system as set forth in claim 1, wherein at least one of said video camera, central control unit, or display monitor comprises a backup power source for operating said video camera, central control unit, or display monitor in the event a primary power source is lost.

16. The video system as set forth in claim 15, wherein the backup power source is a battery.

17. A video system for a law enforcement vehicle, the system comprising:

- a rear view mirror housing;
- a mirror mounted in the rear view mirror housing;
- a video camera mounted on the vehicle and operable to both capture and encode video for law enforcement applications and to timestamp and store the encoded video;
- a central control unit mounted on the vehicle and operable to receive, decode, and timestamp the encoded video;
- a memory for receiving and storing the captured, decoded, and timestamped video from the central control unit, wherein timestamps from the video camera and the central control unit are synchronized, such that a video frame lost during transmission from the video camera to the central control unit can be retransmitted and integrated with the decoded video received and stored by the central control unit;
- a recorder operable to make a copy of the captured, decoded, and timestamped video stored in the memory, wherein the recorder is selected from the group consisting of a CD burner and a DVD burner; and
- a display monitor operable to display the decoded video, the display monitor being mounted in the rear view mirror housing substantially behind the mirror, and the mirror and the display monitor being configured so that the displayed video is viewable through the mirror;
- a microphone operable to capture and encode audio, wherein the central control unit is operable to receive and decode the encoded audio;
- a vehicle interface box mounted on the vehicle and operable to interface an external device to the central control unit, wherein the external device is a radar gun; and
- a co-processing module mounted on the vehicle and operable to provide processing for an additional feature of the system, wherein the additional feature is selected from the group consisting of a face recognition feature and a license plate recognition feature.

18. The video system as set forth in claim 17, wherein the video camera and the central control unit are connected by a high speed bus.

19. The video system as set forth in claim 17, wherein there are two or more video cameras connected to a hub, the hub is connected to the central control unit, and the central control unit is operable to receive the video from each of the two or more video cameras simultaneously.

20. The video system as set forth in claim 17, further including a location determining device operable to determine a location of the vehicle when the video is captured, wherein the memory of the video system is operable to record at least a portion of the captured video and the location of the vehicle when the video was captured.

* * * * *