

SUPPLEMENTAL FIFRA 2(ee) LABELING

EMPLOY[®]

APPLICATION VIA SPRINKLER CHEMIGATION SYSTEMS

ATTENTION

- It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.
- This labeling must be in the possession of the user at the time of application.
- Read the label affixed to the container of EMPLOY before applying. Carefully follow all precautionary statements and applicable use directions.
- Use of EMPLOY according to this supplemental labeling is subject to all use precautions and limitations imposed by the label affixed to the container of EMPLOY.
- This recommendation is made as permitted by Section 2(ee) of FIFRA.

APPLICATION VIA SPRINKLER CHEMIGATION SYSTEMS

Apply this product only through sprinkler (including center pivot, lateral move, end tow, side (wheel) roll, traveler, big gun, solid set, or hand move) irrigation systems. Do not apply this product through any other type of irrigation system. Crop injury and lack of effectiveness can result from non-uniform distribution of treated water. If you have questions about your system's calibration, you should contact State Extension Service Specialists, equipment manufacturers or other experts. Do not connect an irrigation system (including greenhouse systems) used for pesticide application to a public water system. A person knowledgeable of the chemigation system and responsible for its operation, or under the supervision of the responsible person, shall shut the system down and make necessary adjustments should the need arise.

Sprinkler Chemigation System Requirements: The system must contain a functional check valve, vacuum relief valve and low-pressure drain appropriately located on the irrigation pipeline to prevent water source contamination from back-flow. The pesticide injection pipeline must contain a functional, automatic, quick-closing check valve to prevent the flow of fluid back toward the injection pump. The pesticide injection pipeline must also contain a functional, normally closed, solenoid-operated valve located on the intake side of the injection pump and connected to the system interlock to prevent fluid from being withdrawn from the supply tank when the irrigation system is either automatically or manually shut down. The system must contain functional interlocking controls to automatically shut off the pesticide injection pump when the water pump motor stops. The irrigation line or water pump must include a functional pressure switch that will stop the water pump motor when the water pressure decreases to the point where pesticide distribution is adversely affected. Systems must use a metering pump, such as a positive displacement injection pump (e.g., diaphragm pump), effectively designed and constructed of materials that are compatible with pesticides and capable of being fitted with a system interlock. Do not apply when wind speed favors drift beyond the area intended for treatment. Apply product continuously for the duration of the water application.

EPA Reg. No. 71771-3
EPA Est. No. 069208-MO-001

The contents of this package and/or the use of the contents are covered by U.S. Patents 5,849,868, 5,859,324, 5,776,889, 5,977,060, 6,277,814 as well as pending patent applications.

Plant Health Care, Inc.
285 Kappa Drive, Suite 100
Pittsburgh, PA 15238
1-800-421-9051
www.planthealthcare.com

12.0404 Supplemental EMPLOY 2(ee) – Chemigation